


# Wavelet Toolbox™ Release Notes



# MATLAB®

# How to Contact MathWorks



Latest news: [www.mathworks.com](http://www.mathworks.com)  
Sales and services: [www.mathworks.com/sales\\_and\\_services](http://www.mathworks.com/sales_and_services)  
User community: [www.mathworks.com/matlabcentral](http://www.mathworks.com/matlabcentral)  
Technical support: [www.mathworks.com/support/contact\\_us](http://www.mathworks.com/support/contact_us)



Phone: 508-647-7000



The MathWorks, Inc.  
1 Apple Hill Drive  
Natick, MA 01760-2098

## *Wavelet Toolbox™ Release Notes*

© COPYRIGHT 1997–2019 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

### **Trademarks**

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See [www.mathworks.com/trademarks](http://www.mathworks.com/trademarks) for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

### **Patents**

MathWorks products are protected by one or more U.S. patents. Please see [www.mathworks.com/patents](http://www.mathworks.com/patents) for more information.

## R2019a

---

<b>Wavelet Scattering for Images: Generate compact invariant feature representations automatically for image classification</b> .....	<b>1-2</b>
<b>Image Denoising: Automatically denoise images while preserving sharp features</b> .....	<b>1-2</b>
<b>GPU and C/C++ Code Generation: Automatically generate GPU or C/C++ code for the continuous wavelet transform</b> .....	<b>1-2</b>
<b>Wavelet Scattering Examples: Classify images and time series using wavelet scattering and deep learning</b> .....	<b>1-3</b>
<b>1-D Wavelet Time Scattering: Enable variable downsampling of coefficients</b> .....	<b>1-3</b>
<b>Functionality being removed or changed</b> .....	<b>1-3</b>
waveletScattering property Decimate will be removed .....	<b>1-3</b>

## R2018b

---

<b>Wavelet Scattering: Generate invariant representations of time series data automatically for classification and regression</b> .....	<b>2-2</b>
<b>Signal Multiresolution Analyzer App: Visualize and synthesize wavelet and empirical mode decompositions of signals</b> .....	<b>2-2</b>

<b>Time-Frequency Analysis: Analyze signals using the Wigner-Ville distribution</b> .....	2-2
<b>Scattering Examples: Classify signals using wavelet time scattering and machine learning</b> .....	2-3
<b>Signal Labeling: Define labels and create sets of labeled signals</b> .....	2-3
<b>Functionality being removed or changed</b> .....	2-3

## R2018a

<b>Filter Banks for Continuous Wavelet Transform: Create, visualize, and use filter banks for time-frequency analysis</b> .....	3-2
<b>Filter Banks for Discrete Wavelet Transform: Explore time-frequency characteristics of wavelets and scaling functions</b> .....	3-2
<b>Constant-Q Transform: Perform adaptive time-frequency analysis using nonstationary Gabor frames</b> .....	3-2
<b>Scalogram View: Detect transients and perform time-frequency analysis with the Signal Analyzer App</b> .....	3-3
<b>Empirical Mode Decomposition and Hilbert-Huang Transform: Perform data-adaptive time-frequency analysis of nonlinear and nonstationary processes</b> .....	3-3
<b>Continuous Wavelet Transform: Improved control of time-frequency parameters and timetable support</b> .....	3-3
<b>Machine and Deep Learning Examples: Classify signals using wavelet-based feature extraction and deep learning</b> .....	3-4
<b>Functionality Being Removed or Changed</b> .....	3-4

## R2017b

<b>Wavelet Signal Denoiser App: Visualize and denoise time-series data</b> .....	4-2
<b>Wavelet Denoising: Denoise time-series data with improved automatic selection of input parameters</b> .....	4-2
<b>Continuous Wavelet Transform: Perform time-frequency analysis of complex-valued time-series data</b> .....	4-2
<b>Functionality Being Removed or Changed</b> .....	4-3

## R2017a

<b>Multiscale Local Polynomial Transform: Perform smoothing of nonuniformly sampled signals</b> .....	5-2
<b>3-D Dual-Tree Complex Wavelet Transform: Perform directionally selective wavelet analysis of volumetric data</b> .....	5-2
<b>Length-16 Q-shift filter</b> .....	5-2
<b>Modified treatment of boundary conditions in Wavelet Analyzer</b> .....	5-2

## R2016b

<b>Code Generation: Generate C code for DWT, wavelet packets, and denoising using MATLAB Coder</b> .....	6-2
--	-----

<b>Continuous Wavelet Transform: Analyze signals with improved automatic selection of wavelet and scales</b> .....	<b>6-2</b>
<b>Morse Wavelets: Family of analytic wavelets for continuous wavelet analysis</b> .....	<b>6-3</b>
<b>Wavelet Leaders and Wavelet Transform Modulus Maxima: Characterize fractal data and singularities</b> .....	<b>6-3</b>
<b>Haar Lifting Transforms: Perform multiresolution analysis of images and multichannel signals</b> .....	<b>6-3</b>
<b>Compression data files default to uint64 data</b> .....	<b>6-4</b>
<b>Wavelet Design and Analysis App renamed to Wavelet Analyzer</b> .....	<b>6-4</b>
<b>wavedemo function removed</b> .....	<b>6-4</b>
<b>Functionality being removed or changed</b> .....	<b>6-5</b>

## R2016a

<b>Maximal Overlap Discrete Wavelet Packet Transform: Perform nondecimated wavelet packet analysis on arbitrary-length signals</b> .....	<b>7-2</b>
<b>Wavelet Synchrosqueezing: Sharpen time-frequency estimates and extract signal modes</b> .....	<b>7-2</b>
<b>Wavelet Coherence: Compare time-varying frequency content between signals</b> .....	<b>7-2</b>
<b>Fejer-Korovkin filter with 18 coefficients</b> .....	<b>7-3</b>
<b>Maximum derivative output of gauswavf and cgauwavf</b> .....	<b>7-3</b>
<b>Functionality being removed or changed</b> .....	<b>7-3</b>

**R2015b**

<b>Maximal Overlap Discrete Wavelet Transform: Perform nondecimated analysis on arbitrary-length signals and obtain multiscale variance and correlation estimates . . . . .</b>	<b>8-2</b>
<b>Frequency-Localized Wavelets: Perform more frequency-localized discrete and continuous wavelet analysis . . . . .</b>	<b>8-2</b>
<b>Time-Frequency Analysis: Convert scale to frequency to interpret the continuous wavelet transform as a time-frequency transform . . . . .</b>	<b>8-2</b>
<b>Application examples: Analyze financial data and physiologic signals using wavelets . . . . .</b>	<b>8-3</b>

**R2015a**

<b>Functionality being removed or changed . . . . .</b>	<b>9-2</b>
---	------------

**R2014b**

**Bug Fixes**

**R2014a**

<b>Dual-Tree Wavelet Transforms . . . . .</b>	<b>11-2</b>
---	-------------

**R2013b**

---

<b>Two-Dimensional Continuous Wavelet Transform (2-D CWT)</b> .....	<b>12-2</b>
<b>Dual-Tree Transforms and Double-Density Transforms</b> .....	<b>12-2</b>

**R2013a**

---

**Bug Fixes**

**R2012b**

---

**Bug Fixes**

**R2012a**

---

<b>Matching Pursuit</b> .....	<b>15-2</b>
-------------------------------	-------------

**R2011b**

---

<b>Fourier Transform Based Continuous Wavelet Transform GUI</b> .....	<b>16-2</b>
--	-------------



<b>Inverse Continuous Wavelet Transform Using Linear Scales</b> .....	<b>16-2</b>
<b>MATLAB Code Generation Support for Denoising and Compression GUIs</b> .....	<b>16-2</b>
<b>Signal Reconstruction from Continuous Wavelet Transform Coefficients Demo</b> .....	<b>16-2</b>
<b>Changes in Fourier Transform Based Continuous Wavelet Transform Defaults for Derivative of Gaussian (DOG) and Paul Wavelets</b> .....	<b>16-3</b>

## **R2011a**

<b>Inverse Continuous Wavelet Transform</b> .....	<b>17-2</b>
<b>FFT-based Continuous Wavelet Transform</b> .....	<b>17-2</b>
<b>Pattern-adapted Wavelets for Signal Detection Demo</b> .....	<b>17-2</b>

## **R2010b**

<b>Cone of Influence for Continuous Wavelet Transform</b> .....	<b>18-2</b>
<b>Wavelet Cross Spectrum and Coherence</b> .....	<b>18-2</b>
<b>Wavelet Packet Spectrum</b> .....	<b>18-2</b>
<b>Natural and Frequency Ordering of Wavelet Packet Terminal Nodes</b> .....	<b>18-2</b>
<b>Image and Signal Approximation Quality Metrics</b> .....	<b>18-2</b>

---

## R2010a

<b>3-D Discrete Wavelet Transform</b> .....	<b>19-2</b>
<b>Nondecimated Wavelet Transform</b> .....	<b>19-2</b>
<b>New Denoising Function</b> .....	<b>19-2</b>

---

## R2009b

**Bug Fixes**

---

## R2009a

<b>New Demos</b> .....	<b>21-2</b>
------------------------	-------------

---

## R2008b

<b>True Image Compression Support</b> .....	<b>22-2</b>
<b>New Demo</b> .....	<b>22-2</b>

---

## R2008a

<b>True Color Images Support</b> .....	<b>23-2</b>
--	-------------

<b>New Extension Modes for Continuous Wavelets</b> .....	23-2
<b>New Norms Calculation</b> .....	23-2
<b>Wavelet Families Display</b> .....	23-2
<b>Single Data Type Support</b> .....	23-2
<b>New Demos</b> .....	23-2

## **R2007b**

<b>Importing and Exporting between GUIs and Workspace</b> ....	24-2
<b>Scalograms for Continuous Wavelet Transforms</b> .....	24-2
<b>Constructing Clusters from Hierarchical Cluster Trees</b> .....	24-2

## **R2007a**

<b>1D Multisignal Analysis, Compression, and Denoising Added</b> .....	25-2
<b>1D Multisignal Wavelet and Clustering Added</b> .....	25-2
<b>Wavelet 1D Multisignal Analysis GUI Added</b> .....	25-2

## **R2006b**

<b>Multivariate De-noising Added</b> .....	26-2
--	------

<b>Multiscale Principal Component Analysis Added</b> .....	<b>26-2</b>
<b>New Demos</b> .....	<b>26-2</b>

**R2006a**

---

**No New Features or Changes**

**R14SP3**

---

**No New Features or Changes**

**R14SP2**

---

**No New Features or Changes**

# R2019a

---

**Version: 5.2**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## **Wavelet Scattering for Images: Generate compact invariant feature representations automatically for image classification**

The new `waveletScattering2` function creates a framework for wavelet image scattering. The framework uses complex-valued 2-D Morlet wavelets to automatically generate features from RGB or grayscale images. Wavelet image scattering yields representations insensitive to image translations and rotations without sacrificing class discriminability. As with 1-D wavelet time scattering, you do not need a large dataset to train filters for accurate classification. You can use `waveletScattering2` to create a framework specific to your requirements:

- Specify the number of linearly spaced rotations per wavelet filter and the amount of translation invariance.
- Specify how much the scattering coefficients are oversampled with respect to the critically downsampled values.
- Optimize the scattering transform based on the wavelet bandwidths and the number of wavelets per octave.

You can also examine characteristics of the framework filter banks, including center spatial frequencies and frequency supports.

## **Image Denoising: Automatically denoise images while preserving sharp features**

The `wdenoise2` function provides a simple interface to a variety of denoising methods that can be applied to RGB or grayscale images. You can use `wdenoise2` with preset default values or specify a variety of denoising methods, including empirical Bayesian, false discovery rate, and Donoho-Johnstone methods. You can use cycle spinning for translationally invariant denoising with all the supported denoising methods. You can also denoise an RGB image in its PCA color space.

## **GPU and C/C++ Code Generation: Automatically generate GPU or C/C++ code for the continuous wavelet transform**

You can now generate code for workflows that include continuous wavelet transforms.

- The `cwt` function supports CUDA<sup>®</sup> code generation.
- The `cwtfilterbank` object supports C/C++ code generation.

---

You must have MATLAB® Coder™ to generate C/C++ code. CUDA code generation requires MATLAB Coder and GPU Coder™.

## **Wavelet Scattering Examples: Classify images and time series using wavelet scattering and deep learning**

This release introduces several examples of using wavelet scattering frameworks for image and time series classification. “Texture Classification with Wavelet Image Scattering” and “Digit Classification with Wavelet Scattering” use wavelet image scattering to classify textures and digits, respectively. “Acoustic Scene Recognition Using Late Fusion” and “Spoken Digit Recognition with Wavelet Scattering and Deep Learning” classify audio data using wavelet time scattering and a deep convolutional neural network based on mel-frequency spectrograms.

## **1-D Wavelet Time Scattering: Enable variable downsampling of coefficients**

When you create a framework with `waveletScattering`, you can use the new `OversamplingFactor` property to control the amount of downsampling in the scattering transform. By default, the scattering coefficients are critically downsampled by the maximum amount possible.

## **Functionality being removed or changed**

### **`waveletScattering` property `Decimate` will be removed**

*Still runs*

The `waveletScattering` property `Decimate` will be removed in a future release. Use the new property `OversamplingFactor` instead.

<b>Functionality</b>	<b>What Happens When You Use This Functionality?</b>	<b>Use This Instead</b>	<b>Compatibility Considerations</b>
Decimate	Still runs	Use <code>OversamplingFactor</code> or	<ul style="list-style-type: none"><li>• Replace all instances of <code>'Decimate', true</code> with <code>'OversamplingFactor', 0</code>.</li><li>• Replace all instances of <code>'Decimate', false</code> with <code>'OversamplingFactor', Inf</code>.</li></ul>



# R2018b

---

**Version: 5.1**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## **Wavelet Scattering: Generate invariant representations of time series data automatically for classification and regression**

The new `waveletScattering` function creates a framework for wavelet time scattering. The framework uses wavelets and a lowpass scaling function to automatically generate low-variance representations of real-valued time series data. Wavelet time scattering yields representations insensitive to translations in the input signal without sacrificing class discriminability. `waveletScattering` uses predefined wavelet and lowpass scaling filters for feature extraction. You do not need a large dataset to train filters for accurate classification. You can use `waveletScattering` to create a framework specific for your requirements:

- Specify the duration of translation invariance.
- Set the number of filter banks in the framework, and the number of wavelet filters per octave in each filter bank
- Generate the feature matrix to use in a classifier.

You can also return the filter banks used in the framework, and inspect their characteristics including the wavelet filter center frequencies and frequency standard deviations.

## **Signal Multiresolution Analyzer App: Visualize and synthesize wavelet and empirical mode decompositions of signals**

The **Signal Multiresolution Analyzer** app enables visualization of wavelet and empirical mode decompositions of signals. The relative energy and frequency band of the individual components in the decomposition are provided. You can synthesize signals from components you choose that best capture features of interest. The app enables easy comparison of multiple reconstructions. You can export reconstructions and generate MATLAB scripts to reproduce results in your workspace.

## **Time-Frequency Analysis: Analyze signals using the Wigner-Ville distribution**

This release adds support for the Wigner-Ville distribution, which provides a high-resolution time-frequency representation of a signal. The distribution has applications in signal visualization, detection, and estimation.

- 
- `wvd` computes the Wigner-Ville distribution of a signal.
  - `xwvd` computes the cross Wigner-Ville distribution of two signals.

## **Scattering Examples: Classify signals using wavelet time scattering and machine learning**

This release introduces three examples of feature extraction using wavelet time scattering for machine learning workflows.

- Wavelet Time Scattering for ECG Signal Classification
- Wavelet Time Scattering Classification of Phonocardiogram Data
- Music Genre Classification Using Wavelet Time Scattering

## **Signal Labeling: Define labels and create sets of labeled signals**

This release introduces functionality to define labels for signals and to create sets of labeled signals. You can store signal values and annotations in a form that keeps all data together.

- `signalLabelDefinition` enables users to create signal label definitions. The definitions can be for attributes, regions, or points of interest.
- `labeledSignalSet` enables users to group signals, label definitions, and label values that can be used in learning algorithms.

## **Functionality being removed or changed**

The `BPfrequencies` and `BPperiods` object functions of `cwtfilterbank` have been renamed `centerFrequencies` and `centerPeriods`, respectively. The functionality remains unchanged. `BPfrequencies` and `BPperiods` will be removed in a future release.

## Compatibility Considerations

<b>Functionality</b>	<b>What Happens When You Use This Functionality?</b>	<b>Use This Instead</b>	<b>Compatibility Considerations</b>
BPfrequencies	Still runs	Use centerFrequencies	Replace all instances of BPfrequencies with centerFrequencies.
BPperiods	Still runs	Use centerPeriods	Replace all instances of BPperiods with centerPeriods.

# R2018a

---

**Version: 5.0**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## **Filter Banks for Continuous Wavelet Transform: Create, visualize, and use filter banks for time-frequency analysis**

Use the `cwtfilterbank` function to create a continuous wavelet transform (CWT) filter bank.

- Visualize wavelets in time and frequency.
- Create filter banks with specific frequency or period ranges, and with a specific number of wavelet filters per octave.
- Measure 3-dB bandwidths and q-factor.
- Use the precomputed filter bank with `cwt` to provide a more efficient implementation of the CWT for multiple signals.

## **Filter Banks for Discrete Wavelet Transform: Explore time-frequency characteristics of wavelets and scaling functions**

Use the `dwtfilterbank` function to create a discrete wavelet transform (DWT) filter bank.

- Visualize wavelets and scaling functions in time and frequency.
- Measure the 3-dB bandwidths of the wavelet and scaling functions. You can also measure energy concentration of the wavelet and scaling functions in the theoretical DWT passbands.
- Create a DWT filter bank using your own custom filters. You can determine whether the filter bank is orthogonal or biorthogonal.
- Determine the frame bounds of the filter bank.

## **Constant-Q Transform: Perform adaptive time-frequency analysis using nonstationary Gabor frames**

Use the `cqt` function to take the constant-Q transform of signals. With the `icqt` function, you can invert the transform for perfect reconstruction. The constant-Q transform, which is based on nonstationary Gabor frames, constructs and applies adaptive, compact bandwidth windows directly in the frequency domain.

- Perform minimally redundant and maximally redundant constant-Q transforms.

- 
- Visualize the constant-Q transform of a signal.
  - Obtain the Gabor frames used in the analysis, and the frequency shifts in the discrete Fourier transform bins between the passbands.
  - Use `cqt` with a number of different windows for the nonstationary Gabor frames, including the Hann window and Hamming window.
  - Set the frequency limits over which the constant-Q transform has a logarithmic frequency response. You can also set the number of frequency bins per octave.
  - Use `cqt` on multichannel signals.

## **Scalogram View: Detect transients and perform time-frequency analysis with the Signal Analyzer App**

The **Signal Analyzer** app can now compute scalograms using Morse wavelets. Scalograms enable you to detect transients and perform time-frequency analysis. You must have a Signal Processing Toolbox™ license to use **Signal Analyzer**.

## **Empirical Mode Decomposition and Hilbert-Huang Transform: Perform data-adaptive time-frequency analysis of nonlinear and nonstationary processes**

Use `emd` to decompose a nonlinear or nonstationary process into its intrinsic modes of oscillation. `emd` iterates on an input signal to extract natural AM-FM modes, also known as intrinsic mode functions, contained in the data.

Use `hht` to obtain a time-frequency representation of a signal similar but complementary to the spectrogram or continuous wavelet transform. `hht` uses the data-adaptive intrinsic mode functions obtained from the empirical mode decomposition to obtain instantaneous frequency estimates of a multicomponent nonlinear or nonstationary signal.

## **Continuous Wavelet Transform: Improved control of time-frequency parameters and timetable support**

The `cwt` and `icwt` functions now provide more control over the forward and inverse continuous wavelet transforms.

- The Morse and analytic Morlet scaling functions are now part of the CWT. With the scaling coefficients, you can obtain a more accurate signal reconstruction.

- You can now specify a frequency range and period range to use in the CWT. With the new `cwtfreqbounds` function, you can determine the appropriate frequency limits and customize the behavior of the CWT at low-frequency and high-frequency bounds.
- The `cwt` function now supports a single-variable, uniformly sampled timetable.

## **Machine and Deep Learning Examples: Classify signals using wavelet-based feature extraction and deep learning**

This release introduces two examples for classifying signals using wavelets. *ECG Classification Using Wavelet Features* uses wavelet-based features and a support vector machine to classify human electrocardiogram (ECG) waveforms. The example demonstrates how wavelet features can significantly reduce the size of the data and yet still retain the salient differences between waveforms. *Signal Classification with Wavelet Analysis and Convolutional Neural Networks* uses continuous wavelet analysis and transfer learning to classify ECG waveforms using a deep convolutional neural network (CNN). The example creates time-frequency images of the ECG waveforms using the continuous wavelet transform and leverages a pretrained deep CNN for image classification.

## **Functionality Being Removed or Changed**

The `'NumOctaves'` name-value pair argument in `cwt` will be removed in a future release.



Functionality	Result	Use Instead	Compatibility Considerations
<p>Name-value pair argument 'NumOctaves' for <code>cwt</code>.</p> <p>For example: <code>[ ____ ] = cwt( ____ , 'NumOctaves', 24 )</code></p>	Still runs	<p>In <code>cwt</code>, set either the:</p> <ul style="list-style-type: none"> <li>Name-value pair argument 'FrequencyLimits' to modify the frequency range of the CWT.</li> <li>Name-value pair argument 'PeriodLimits' to modify the period range of the CWT.</li> </ul> <p>See <code>cwtfreqbounds</code> for details.</p>	<p>Replace all instances of the 'NumOctaves' name-value pair argument with either the 'FrequencyLimits' or 'PeriodLimits' name-value pair argument.</p>
Default regression weights for <code>dwtleader</code>	Still runs	<p>In <code>dwtleader</code>, use the name-value pair argument 'RegressionWeight' to set the weight option used in the least-squares regression model. See <code>dwtleader</code> for details.</p>	<p>To duplicate the behavior of <code>dwtleader</code> found in releases prior to R2018a, update all instances of <code>dwtleader</code> to include the name-value pair argument 'RegressionWeight' set to 'scale'.</p>



# R2017b

---

**Version: 4.19**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## **Wavelet Signal Denoiser App: Visualize and denoise time-series data**

The **Wavelet Signal Denoiser** app enables visualization and denoising of 1-D signals in the MATLAB workspace. The app provides an initial denoised version of your data using default parameters. You can duplicate, add, and modify the denoising settings to compare multiple denoised versions of your signal to determine the optimal settings. After you determine the optimal settings for your signal, you can export the denoised data and generate MATLAB scripts to reproduce the results.

## **Wavelet Denoising: Denoise time-series data with improved automatic selection of input parameters**

The `wdenoise` function provides a simple interface to a variety of denoising methods that can be applied to 1-D signals. Input parameters are automatically chosen for quick and easy use. `wdenoise` supports empirical Bayesian methods, false discovery rate, and James-Stein block thresholding. The function also supports the denoising of multichannel time-series data and MATLAB timetables.

## **Continuous Wavelet Transform: Perform time-frequency analysis of complex-valued time-series data**

The `cwt` function now supports complex-valued data for analysis and synthesis. With this enhancement, you can perform time-frequency analysis of rotary components. A visualization affordance has also been added so that you can more easily discern regions where edge effects become significant.

---

## Functionality Being Removed or Changed

Functionality	Result	Use Instead	Compatibility Considerations
swt2	Still runs	Not applicable	<p>To distinguish a single-level decomposition of a truecolor image from a multilevel decomposition of an indexed image, the approximation and detail coefficient arrays of truecolor images are 4-D arrays. See Migrate from R2017b to Previous Release or Migrate from Previous Release to R2017b.</p> <p>swt2 uses double-precision arithmetic internally and returns double-precision coefficient matrices.</p>

Functionality	Result	Use Instead	Compatibility Considerations
i swt2	Still runs	Not applicable	To distinguish a single-level decomposition of a truecolor image from a multilevel decomposition of an indexed image, the approximation and detail coefficient arrays of truecolor images are 4-D arrays. See Migrate from R2017b to Previous Release or Migrate from Previous Release to R2017b.

### Migrate from Previous Releases to R2017b

Depending on the original input data type and level of wavelet decomposition, you might have to take different steps to make swt2 coefficient arrays from previous releases compatible with R2017b coefficient arrays. The steps depend on whether you have a single coefficient array or separate approximation and detail coefficient arrays.

Single Coefficient Array	Multiple Coefficient Arrays
Input: Index image <ul style="list-style-type: none"> <li>• Single-level: No compatibility issues</li> <li>• Multi-level: No compatibility issues</li> </ul>	Input: Index image <ul style="list-style-type: none"> <li>• Single-level: No compatibility issues</li> <li>• Multi-level: No compatibility issues</li> </ul>

Single Coefficient Array	Multiple Coefficient Arrays
<p>Input: Truecolor image</p> <ul style="list-style-type: none"> <li>Single-level: If <code>swc</code> is the output of <code>swt2</code> from a previous release, execute: <code>swc1 = double(swc);</code></li> <li>Multi-level: If <code>swc</code> is the output of <code>swt2</code> from a previous release, execute: <code>swc1 = double(swc);</code></li> </ul>	<p>Input: Truecolor image</p> <ul style="list-style-type: none"> <li>Single-level: If <code>ca</code>, <code>chd</code>, <code>cvd</code>, and <code>cdd</code> are outputs of <code>swt2</code> from a previous release, execute: <code>ca1 = double(ca);</code> <code>chd1 = double(chd);</code> <code>cvd1 = double(cvd);</code> <code>cdd1 = double(cdd);</code> <code>ca2 = reshape(ca1, [m,n,1,3]);</code> <code>chd2 = reshape(chd1, [m,n,1,3]);</code> <code>cvd2 = reshape(cvd1, [m,n,1,3]);</code> <code>cdd2 = reshape(cdd1, [m,n,1,3]);</code></li> <li>Multi-level: If <code>ca</code>, <code>chd</code>, <code>cvd</code>, and <code>cdd</code> are outputs of <code>swt2</code> from a previous release, execute: <code>ca1 = double(ca);</code> <code>chd1 = double(chd);</code> <code>cvd1 = double(cvd);</code> <code>cdd1 = double(cdd);</code></li> </ul>

### Migrate from R2017b to Previous Releases

Depending on the original input data type and level of wavelet decomposition, you might have to take different steps to make R2017b `swt2` coefficient arrays compatible with the coefficient arrays from previous releases. The steps depend on whether you have a single coefficient array or separate approximation and detail coefficient arrays.

Single Coefficient Array	Multiple Coefficient Arrays
<p>Input: Index image</p> <ul style="list-style-type: none"> <li>Single-level: No compatibility issues</li> <li>Multi-level: No compatibility issues</li> </ul>	<p>Input: Index image</p> <ul style="list-style-type: none"> <li>Single-level: No compatibility issues</li> <li>Multi-level: No compatibility issues</li> </ul>

<b>Single Coefficient Array</b>	<b>Multiple Coefficient Arrays</b>
<p>Input: Truecolor image</p> <ul style="list-style-type: none"><li>• Single-level: No compatibility issues</li><li>• Multi-level: No compatibility issues</li></ul>	<p>Input: Truecolor image</p> <ul style="list-style-type: none"><li>• Single-level: If <code>ca</code>, <code>chd</code>, <code>cvd</code>, and <code>cdd</code> are outputs of <code>swt2</code> from R2017b, execute:  <pre>ca1 = single(squeeze(ca)); chd1 = single(squeeze(chd)); cvd1 = single(squeeze(cvd)); cdd1 = single(squeeze(cdd));</pre></li><li>• Multi-level: No compatibility issues</li></ul>



# R2017a

---

**Version: 4.18**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## Multiscale Local Polynomial Transform: Perform smoothing of nonuniformly sampled signals

The `mlpt`, `implpt`, `mlptdenoise`, and `mlptrecon` functions use local polynomial lifting schemes to perform multiresolution analysis, denoising, and reconstruction of nonuniformly sampled single-channel and multichannel signals.

## 3-D Dual-Tree Complex Wavelet Transform: Perform directionally selective wavelet analysis of volumetric data

The `dualtree3` and `idualtree3` functions perform the 3-D complex dual-tree transform. This transform is selective to orientation and provides perfect reconstruction. For an example demonstrating how the dual-tree complex discrete transform provides advantages over the critically sampled discrete wavelet transform for signal, image, and volume processing, see the featured example, [Dual-Tree Wavelet Transforms](#).

## Length-16 Q-shift filter

The `dtfilters` function now includes a Q-shift filter of length 16 that is used in dual-tree transforms. To use this filter, specify `'dtf4'` as the filter name.

## Compatibility Considerations

The previous version of `dtfilters` included filters of lengths 6, 10, 14, and 18. These lengths corresponded to `'dtf1'`, `'dtf2'`, `'dtf3'`, and `'dtf4'`, respectively. To specify the new filter of length 16, use `'dtf4'`. The filter of length 18 now corresponds to `'dtf5'`. If you have any code that specifies `dtfilters` with a `'dtf4'` filter name, change the filter name to `'dtf5'` to continue using a filter of length 18.

## Modified treatment of boundary conditions in Wavelet Analyzer

In previous releases, the **Wavelet Analyzer** app reset the DWT extension mode to the default `'sym'` behavior, overriding any previous setting. Starting with this release, the app uses the current setting. To display or change the current setting, use `dwtmode`.

# R2016b

---

**Version: 4.17**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## **Code Generation: Generate C code for DWT, wavelet packets, and denoising using MATLAB Coder**

You can now generate code for workflows that support:

- 1-D and 2-D critically sampled discrete wavelet transforms (DWT)
- 1-D maximal overlap discrete wavelet transforms (MODWT)
- Wavelet packet transforms (MODWPT)
- 1-D and 2-D wavelet denoising

You must have MATLAB Coder to generate code. The following functions support code generation:

- `dwt`, `idwt`
- `dwt2`, `idwt2`
- `modwt`, `imodwt`, `modwtmra`
- `modwpt`, `imodwpt`, `modwptdetails`
- `appcoef`, `appcoef2`
- `detcoef`, `detcoef2`
- `wavedec`, `wavedec2`
- `waverec`, `waverec2`
- `wden`, `wdencmp`, `ddencmp`
- `qmf`
- `dyadup`
- `wextend`
- `thselect`
- `wthresh`, `wthcoef`, `wthcoef2`

## **Continuous Wavelet Transform: Analyze signals with improved automatic selection of wavelet and scales**

This release provides an updated version of the continuous wavelet transform, `cwt`, and a new inverse transform, `icwt`, for reconstructing the original signal. These functions are easier to use because they have simple interfaces and include default values for the

---

wavelet and scales and frequency and period ranges are easy to specify. When you use the updated `cwt`, which use analytic wavelets and L1 normalization, `icwt` produce a more accurate reconstruction.

## **Compatibility Considerations**

The old version of `cwt` continues to work, however, updating existing code to use the new version of `cwt` is recommended. Both the old and updated versions use the same function name. The inputs to the function determine automatically which version is used.

`icwt` is recommended instead of `icwtft` and `icwtlin`.

## **Morse Wavelets: Family of analytic wavelets for continuous wavelet analysis**

The Morse family of analytic wavelets are ideal for continuous wavelet analysis. These exactly analytic wavelets are characterized by two parameters. You can vary these parameters to change the shape and duration of the wavelet as needed to analyze your signal or image.

## **Wavelet Leaders and Wavelet Transform Modulus Maxima: Characterize fractal data and singularities**

The `wtmm` function returns an estimate of the global Holder exponent, which characterizes multifractal behavior. You can use `wtmm` to characterize cusp-like singularities. The `dwtLeader` function distinguishes monofractal from multifractal behavior. You can use `WTMM` and `wavelet leaders` to analyze turbulence, electrophysical signals, and financial time series. Both functions accept 1-D data.

## **Haar Lifting Transforms: Perform multiresolution analysis of images and multichannel signals**

Four Haar lifting transform functions have been added to the toolbox: `haart` and `ihaart` for 1-D signals, and `haart2` and `ihaart2` for 2-D signals. The Haar wavelet, though not continuous, is the simplest possible wavelet and is a special case of the Daubechies wavelet, `db1`. These new Haar lifting transforms are computationally efficient.

## Compression data files default to uint64 data

By default, `wcompress` now writes `.wtc` files using `uint64` precision data. A new 'legacy' flag has been added to write `.wtc` files using the earlier `uint32` precision data format. You do not need to include the 'legacy' flag for reading a `.wtc` file because `wcompress` automatically detects and correctly reads the data format.

## Compatibility Considerations

To share a data file with someone using a previous release, use the 'legacy' flag to create a `.wtc` file of `uint32` data. For example,  
`wcompress('c',x,'comp_data.wtc','legacy')`.

## Wavelet Design and Analysis App renamed to Wavelet Analyzer

The Wavelet Design and Analysis app has been renamed to Wavelet Analyzer. To open the Wavelet Analyzer from the command line, use `waveletAnalyzer` instead of `wavemenu`.

## Compatibility Considerations

Change all calls to `wavemenu`, which opens the app, to the new `waveletAnalyzer` command. The app functionality remains unchanged.

## wavedemo function removed

The `wavedemo` function has been removed. Use Wavelet Toolbox Examples instead.

## Compatibility Considerations

Change all calls and links to `wavedemo` to point to Wavelet Toolbox Examples.

## Functionality being removed or changed

Functionality	What Happens When You Use This Functionality?	Use This Instead	Compatibility Considerations
Old cwt	Old functionality is detected based on the input syntax and the old cwt still runs.	Updated cwt	Update all instances of cwt to use the updated cwt syntax.
wcompress	An error occurs if you read .wtc files saved using uint32 data.	Add a 'legacy' flag to use uint32 data instead of default uint64 data	Add a 'legacy' flag to instances of wcompress commands that read .wtc files containing uint32 data.
wavemenu	Still opens Wavelet app	waveletAnalyzer	Update instances of wavemenu to use the new waveletAnalyzer function.
wavedemo	An error occurs .	Wavelet Toolbox Examples	Update instances of wavedemo to point to the Examples page.





# R2016a

---

**Version: 4.16**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## **Maximal Overlap Discrete Wavelet Packet Transform: Perform nondecimated wavelet packet analysis on arbitrary-length signals**

This release adds support for the maximal overlap discrete wavelet packet transform (MODWPT) for 1-D signals. You can decompose signals using `modwpt` and invert the transform using `imodwpt`. Also, you can obtain MODWPT details using `modwptdetails`. For an example of using wavelet packets, see [Wavelet Packets: Decomposing the Details](#).

## **Wavelet Synchrosqueezing: Sharpen time-frequency estimates and extract signal modes**

This release adds support for the wavelet synchrosqueezed transform and mode extraction for 1-D signals. Wavelet synchrosqueezing is a time-frequency reassignment technique that enables you to reconstruct the signal from the reassigned transform. This technique enables you to extract and visualize oscillatory modes in the signal. To obtain the synchrosqueezed transform of a signal, use `wsst`. To invert the transform, use `iwsst`. You can determine or extract time-frequency ridges in the synchrosqueezed transform with `wsstridge`. For an example of synchrosqueezing, see [Time-Frequency Reassignment and Mode Extraction with Synchrosqueezing](#).

## **Wavelet Coherence: Compare time-varying frequency content between signals**

This release adds the `wcoherence` function, which computes the magnitude-squared wavelet coherence of two input signals. The `wcoherence` function also computes the wavelet cross spectrum. Wavelet coherence is useful for detecting common time-localized oscillations in nonstationary, bivariate signals. `wcoherence` also provides visualizations that show the magnitude-squared coherence, cross-spectrum phase, and the cone of influence. The phase plot is helpful in determining the lead-lag relationships between the signals. The cone of influence demonstrates where edge effects become significant. For an example of using `wcoherence`, see [Compare Time-Frequency Content in Signals with Wavelet Coherence](#).

## **Compatibility Considerations**

`wcoher` is not recommended. Update code that uses `wcoher` to use `wcoherence` instead.

---

## Fejer-Korovkin filter with 18 coefficients

This release adds support for Fejer-Korovkin (`fejerkorovkin`) scaling and wavelet filters with 18 coefficients. The valid short name is `'fk18'`.

## Maximum derivative output of `gauswavf` and `cgauwavf`

As of R2016a, the highest order derivative supported for the Gaussian (`gauswavf`) and complex Gaussian wavelet (`cgauwavf`) is 8.

## Compatibility Considerations

Specifying a derivative order greater than 8 produces an error. In code that uses `gauswavf` or `cgauwavf`, update these functions to use a derivative value from 1 to 8. The requirement to have Symbolic Math Toolbox™ has been removed.

## Functionality being removed or changed

Functionality	What Happens When You Use This Functionality?	Use This Instead	Compatibility Considerations
<code>wcoher</code>	Still runs	<code>wcoherence</code>	Replace all instances of <code>wcoher</code> with <code>wcoherence</code> .
<code>gauswavf</code> and <code>cgauwavf</code>	Errors when the order of the derivative is greater than 8		Update instances of <code>gauswavf</code> and <code>cgauwavf</code> to use a maximum derivative value of 8.



# R2015b

---

**Version: 4.15**

**New Features**

**Bug Fixes**

## **Maximal Overlap Discrete Wavelet Transform: Perform nondecimated analysis on arbitrary-length signals and obtain multiscale variance and correlation estimates**

This release adds support for the maximal overlap discrete wavelet transform (MODWT) for 1-D signals. You can decompose signals using `modwt` and invert the transform using `imodwt`. Additionally, you can obtain a MODWT-based multiresolution analysis using `modwtmra`. You can also obtain wavelet variance, correlation, and cross-correlation sequence estimates with confidence intervals using `modwtvar`, `modwtcorr`, and `modwtxcorr`.

## **Frequency-Localized Wavelets: Perform more frequency-localized discrete and continuous wavelet analysis**

This release adds new frequency-localized wavelets for continuous and discrete wavelet analysis. The bump wavelet is a frequency-localized wavelet with an adjustable center frequency and bandwidth.

You can use the bump wavelet with `cwtfft`. For discrete decimated and nondecimated wavelet or wavelet packet analysis, use the new Fejer-Korovkin family of frequency-localized orthogonal wavelets. To obtain information on the Fejer-Korovkin wavelets, enter `waveinfo('fk')` at the MATLAB command prompt. To obtain the Fejer-Korovkin filters, use `wfilters` or `fejerkorovkin`. You can specify the Fejer-Korovkin filters in all discrete wavelet and wavelet packet command line and interactive applications using the short name, 'fk' with a valid filter number. For example, `wavedec(data,N,'fk8')` or `modwt(data,'fk8')`.

## **Time-Frequency Analysis: Convert scale to frequency to interpret the continuous wavelet transform as a time-frequency transform**

This release adds scale-to-frequency conversion for `cwtfft` and `cwt`. `cwtfft` returns the scale-to-frequency conversions as a field in the structure array output. `cwt` accepts an optional sampling interval input, which enables you to output scale-to-frequency conversions. This release also adds a featured example, Time-Frequency Analysis with the Continuous Wavelet Transform.

---

## **Application examples: Analyze financial data and physiologic signals using wavelets**

This release introduces new examples for analyzing financial data and physiologic signals using wavelets. The financial example, *Wavelet Analysis of Financial Data*, shows how you can use wavelets to analyze multiscale volatility in financial time series data and explore multiscale correlation in bivariate time series data. The physiologic signal analysis example, *Wavelet Analysis of Physiologic Signals*, showcases QRS detection in the electrocardiogram using wavelets, wavelet coherence, and time-frequency analysis.





# R2015a

---

**Version: 4.14.1**

**Bug Fixes**

**Compatibility Considerations**

## Functionality being removed or changed

<b>Functionality</b>	<b>What Happens When You Use This Functionality?</b>	<b>Use This Instead</b>	<b>Compatibility Considerations</b>
ndwt, indwt, ndwt2, indwt2	Errors	swt, iswt, swt2, iswt2	Replace all instances of ndwt, indwt, ndwt2, and indwt2 with the corresponding function for the stationary wavelet transform.

# R2014b

---

**Version: 4.14**

**Bug Fixes**



# R2014a

---

**Version: 4.13**

**New Features**

**Bug Fixes**

## **Dual-Tree Wavelet Transforms**

This release introduces a new example, Dual-Tree Wavelet Transforms, which demonstrates the advantages of the dual-tree discrete wavelet transform (DWT) over the critically sampled DWT. The example illustrates the approximate shift invariance and directional selectivity of the complex dual-tree wavelet transform. These properties enable the dual-tree wavelet transform to outperform the critically sampled DWT in a number of applications.

# R2013b

---

**Version: 4.12**

**New Features**

**Bug Fixes**

## Two-Dimensional Continuous Wavelet Transform (2-D CWT)

This release introduces the 2-D continuous wavelet transform (CWT) for images. The 2-D CWT provides information about images at specified scales, rotation angles, and positions in the plane. Applications of the 2-D CWT include:

- Fault detection in images
- Object recognition
- Fringe pattern profilometry

For information on how to implement the 2-D CWT at the MATLAB command line, see `cwtft2`.

To use `cwtft2` in the Wavelet Toolbox interactive tool, enter

```
>> wavemenu
```

Then, from the **Two-dimensional** tools section, select **Continuous Wavelet Transform 2-D**. See 2-D Continuous Wavelet Transform App for more information on the 2-D CWT app.

`cwtft2` supports both isotropic and anisotropic 2-D wavelets. Use isotropic wavelets to perform pointwise analysis in images or when oriented features are not relevant. Use anisotropic wavelets when your goal is to detect oriented features.

`cwtft2` implements the 2-D CWT using the 2-D discrete Fourier transform. Use `cwtftinfo2` to obtain the 2-D Fourier transforms of the supported analyzing wavelets.

## Dual-Tree Transforms and Double-Density Transforms

This release introduces two types of 1-D and 2-D oversampled (frame) wavelet perfect reconstruction filter banks. For 1-D wavelet analysis, use `dddtree` to obtain the following wavelet transforms:

- Complex dual-tree
- Double-density
- Complex dual-tree double-density

For 2-D wavelet analysis, use `dddtree2` to obtain the following wavelet transforms:



- 
- Double-density
  - Real oriented dual-tree
  - Complex oriented dual-tree
  - Real oriented double-density dual-tree
  - Complex oriented double-density dual-tree

The dual-tree and double-density transforms mitigate a number of shortcomings of the critically sampled discrete wavelet transform. The double-density and dual-tree transforms achieve directional selectivity and approximate shift invariance with significantly less computational cost than the undecimated discrete wavelet transform.



# R2013a

---

**Version: 4.11**

**Bug Fixes**



# R2012b

---

**Version: 4.10**

**Bug Fixes**



# R2012a

---

**Version: 4.9**

**New Features**

## Matching Pursuit

In R2012a you can decompose a 1-D signal in a dictionary of time/frequency or time/scale atoms with matching pursuit.

Representing a signal in a union of time-frequency/time-scale bases can provide sparser signal representations than attainable with any single basis. Matching pursuit uses iterative greedy algorithms to reduce the computational complexity of searching through a redundant dictionary.

Wavelet Toolbox software supports basic matching pursuit, orthogonal matching pursuit, and weak orthogonal matching pursuit at the command line with `wmpdictionary` and `wmpalg`. You can also perform matching pursuit with the interactive `wavemenu` tool.

You can build dictionaries using several internally supported options or provide your own custom dictionaries. See Matching Pursuit for background information and examples.



# R2011b

---

**Version: 4.8**

**New Features**

**Bug Fixes**

**Compatibility Considerations**

## **Fourier Transform Based Continuous Wavelet Transform GUI**

In R2011b, you can compute the Fourier transform based continuous wavelet transform (CWT) and inverse CWT using the Wavelet Toolbox graphical user interface `wavemenu`. To access these graphical tools, enter `wavemenu` at the command line, and select **Continuous Wavelet 1-D (using FFT)**.

## **Inverse Continuous Wavelet Transform Using Linear Scales**

In R2011b, you can compute the inverse continuous wavelet transform (CWT) for a wider class of analyzing wavelets using `icwtlin`. `icwtlin` returns the inverse for CWT coefficients obtained at linearly spaced scales. `icwtlin` supports the output of `cwtft` and the output of `cwt` for a select number of wavelets. See `icwtlin` for detailed information.

## **MATLAB Code Generation Support for Denoising and Compression GUIs**

In R2011b, you can generate MATLAB code for 1-D and 2-D discrete wavelet transforms (DWT), stationary wavelet transforms (SWT), and wavelet packet transforms. You can denoise or compress a signal or image in the GUI and export the MATLAB code to implement that operation at the command line. This approach allows you to set denoising thresholds or compression ratios aided by visualization tools and save the commands to reproduce those operations at the command line. See *Generating MATLAB Code from Wavelet Toolbox GUI* for examples.

## **Signal Reconstruction from Continuous Wavelet Transform Coefficients Demo**

R2011b includes a new demo illustrating signal reconstruction using the continuous wavelet transform (CWT). The demo emphasizes the use of the CWT to analyze a signal and reconstruct a time- and scale-based approximation with select coefficients using the inverse CWT. See *Signal Reconstruction from Continuous Wavelet Transform Coefficients* for details.

---

## Changes in Fourier Transform Based Continuous Wavelet Transform Defaults for Derivative of Gaussian (DOG) and Paul Wavelets

In R2011b, the default values for the smallest scale, scale increment, and number of scales have changed in `cwtft` for the derivative of Gaussian (DOG) and Paul wavelets. The change in the defaults also affects the Mexican hat wavelet, which is a special case of the DOG wavelet. In R2011b, the default value of the smallest scale for the Paul and DOG wavelets is  $2*dt$ , where  $dt$  is the sampling period. The default scale increment,  $ds$ , is 0.4875. The default number of scales is  $\text{fix}(\log_2(\text{length}(\text{sig}))/ds)+1$  for the Paul wavelet and  $\max([\text{fix}(\log_2(\text{length}(\text{sig}))/ds), 1])$  for the DOG wavelets, where  $\text{sig}$  is the input signal.

### Compatibility Considerations

`cwtft` was introduced in R2011a. In that release, the default smallest scales for the DOG and Paul wavelets are  $dt/8$  and  $dt$  respectively, where  $dt$  is the sampling interval. The default scale increment is 0.5. The default number of scales is  $\text{fix}(1.5*\log_2(\text{length}(\text{sig}))/ds)+1$  for the Paul wavelet. For DOG wavelets, the default number of scales is  $\text{fix}(1.25*\log_2(\text{length}(\text{sig}))/ds)+1$ , where  $\text{sig}$  is the input signal. You can obtain results in R2011b using `cwtft` with the DOG and Paul wavelets identical to results in R2011a with the default values. To do so, specify the smallest scale, scale increment, and number of scales in a structure or cell array. See `cwtft` for details.



# R2011a

---

**Version: 4.7**

**New Features**

**Bug Fixes**

## **Inverse Continuous Wavelet Transform**

In R2011a, you can compute the inverse continuous wavelet transform (CWT) using an FFT-based algorithm. The inverse CWT allows you to synthesize approximations to your 1D signal based on selected scales. The inverse CWT is only supported for coefficients obtained using the FFT-based CWT. See `icwtft` and `cwtft` for details.

## **FFT-based Continuous Wavelet Transform**

In R2011a, you can compute the continuous wavelet transform (CWT) using an FFT-based algorithm with `cwtft`. The CWT computed using an FFT algorithm supports the computation of the inverse CWT. See `cwtft` and `icwtft` for details. Only select wavelets are valid for use with `cwtft`. See `cwtftinfo` for a list of supported wavelets.

## **Pattern-adapted Wavelets for Signal Detection Demo**

In R2011a there is a new demo using pattern adapted wavelets for signal detection. You can view this demo here [Pattern adapted wavelets for signal detection](#). The Wavelet Toolbox software enables you to design admissible wavelets based on the pattern you wish to detect. Designing a valid wavelet based on your desired pattern allows you to exploit the optimality of matched filtering in the framework of the CWT. The demo illustrates this process on simulated data and human EEG recordings.

# R2010b

---

**Version: 4.6**

**New Features**

**Bug Fixes**

## **Cone of Influence for Continuous Wavelet Transform**

In R2010b, you can compute the cone of influence (COI) for the continuous wavelet transform (CWT) of a signal. At each scale, the COI determines the set of CWT coefficients influenced by the value of the signal at a specified position. The COI provides an important visual aid in interpreting the CWT. By overlaying the cone of influence on the CWT image, you can determine which CWT coefficients each value of the signal affects at every scale. See `conofinf` for details.

## **Wavelet Cross Spectrum and Coherence**

In R2010b, you can estimate the wavelet cross spectrum and wavelet coherence of two time series. The wavelet cross spectrum and coherence provide wavelet-based alternatives for the Fourier-based cross spectrum and coherence. These wavelet estimators are suitable for nonstationary signals. Using a complex-valued analyzing wavelet, you can also examine intervals in the time-scale plane where the two time series exhibit common phase behavior. See `wcoher` and the new demo Wavelet Coherence for details.

## **Wavelet Packet Spectrum**

In R2010b, you can compute the wavelet packet spectrum with `wpspectrum`. The wavelet packet spectrum provides a time-frequency analysis of a time series. The wavelet packet spectrum is useful as wavelet-based counterpart of the short-time Fourier transform.

## **Natural and Frequency Ordering of Wavelet Packet Terminal Nodes**

In R2010b, you can order the wavelet packet transform terminal nodes by natural (Payley) or frequency (sequency) order. See `otnodes` for details.

## **Image and Signal Approximation Quality Metrics**

In R2010b, you can measure the quality of your signal or image approximation using a number of widely-used quality metrics. These metrics include: the peak signal-to-noise ratio (PSNR), the mean square error (MSE), the maximum absolute error, and the energy ratio of the approximation to the original. See `measerr` for details.



# R2010a

---

**Version: 4.5**

**New Features**

**Bug Fixes**

## **3-D Discrete Wavelet Transform**

This release adds new functions and a GUI to support the 3-D discrete wavelet transform. This new functionality lets you decompose, analyze, and display a 3-D object using a different wavelet for each dimension. The new functions are: `dwt3`, `idwt3`, `wavedec3`, and `waverec3`. A demo (`wavelet3demo`) is also included.

## **Nondecimated Wavelet Transform**

New nondecimated wavelet transform functions support signals of arbitrary size and different extension modes. Previous functionality had two limitations: signal length had to equal a power of 2 and the only allowable extension mode was periodized. The new functions are: `ndwt`, `indwt`, `ndwt2`, and `indwt2`. A demo (`ndwtdemo`) is also included.

## **New Denoising Function**

The new `cmddenoise` function uses interval-dependent denoising to compute the denoised signal and coefficients. This allows you to apply different denoising thresholds to different portions of the signal, which is typically nonuniform. You can also export thresholds from the GUI and use them in the `cmddenoise` function. The toolbox includes a denoising demo (`cmddenoise`).

# R2009b

---

**Version: 4.4.1**

**Bug Fixes**



# R2009a

---

**Version: 4.4**

**New Features**

**Bug Fixes**

## **New Demos**

The toolbox now includes three new demos:

Adding a New Wavelet

Wavelet Interval-dependant Denoising

Wavelet Scalograms

# R2008b

---

**Version: 4.3**

**New Features**

**Bug Fixes**

## **True Image Compression Support**

The new `wcompress` functions lets you compress 2D image data. You can also interactively compress images using the new Two-Dimensional Images Compression GUI.

## **New Demo**

The toolbox now includes a new codepad demo on image compression.



# R2008a

---

**Version: 4.2**

**New Features**

**Bug Fixes**

## **True Color Images Support**

The toolbox can now process true color images. All major toolbox GUIs and all of the 2D-oriented command line functions have been also updated and support true color images.

## **New Extension Modes for Continuous Wavelets**

The new `cwtext` function lets you calculate 1D continuous wavelet parameters using extension parameters.

## **New Norms Calculation**

The Multisignal 1D GUI and other related GUIs now include 1-norm, 2-norm, and inf-norm calculations.

## **Wavelet Families Display**

A new function, `waveletfamilies`, displays all the available wavelet families and their properties.

## **Single Data Type Support**

The `swt2` and `iswt2` functions now support single data types.

## **New Demos**

The toolbox now includes the following new codepad demos:

- Multiscale Principal Component Analysis
- Multivariate Denoising

# R2007b

---

**Version: 4.1**

**New Features**

**Bug Fixes**

## Importing and Exporting between GUIs and Workspace

You can now import data from the workspace to all toolbox GUIs and export data from all toolbox GUIs to the workspace. Use **Import from Workspace** and **Export to Workspace**, respectively, on the GUI's **File** menu.

## Scalograms for Continuous Wavelet Transforms

The ability to compute scalograms of the wavelet coefficients in continuous wavelet analysis has been added as an option to the `cwt` function. You can also pass the structure produced by `cwt` directly to the new `wscalogram` function. Scalograms show the percentage of energy in each wavelet coefficient.

## Constructing Clusters from Hierarchical Cluster Trees

You can now construct clusters from hierarchical cluster trees in multisignal analysis using the new `mdwtcluster` function.

# R2007a

---

**Version: 4.0**

**New Features**

**Bug Fixes**

## 1D Multisignal Analysis, Compression, and Denoising Added

The following command-line functions for 1D multisignal analysis, compression, and denoising have been added to the toolbox:

<code>mswcmp</code>	Multisignal 1D compression using wavelets.
<code>mswcmpscr</code>	Multisignal 1D wavelet compression scores.
<code>mswcmptp</code>	Multisignal 1D compression thresholds and perf.
<code>mswden</code>	Multisignal 1D denoising using wavelets.
<code>mswthresh</code>	Performs Multisignal 1D thresholding.

## 1D Multisignal Wavelet and Clustering Added

The following command-line functions for 1D multisignal wavelets and clustering have been added to the toolbox:

<code>chgwdccfs</code>	Change Multisignal 1D decomposition coeffs
<code>mdwtdec</code>	Multisignal 1D wavelet decomposition
<code>mdwtrec</code>	Multisignal 1D wavelet reconstruction.
<code>wdecenergy</code>	Multisignal 1D decomposition energy repartition

---

**Note** Clustering analyses require that Statistics Toolbox™ is installed.

---

## Wavelet 1D Multisignal Analysis GUI Added

A graphical user interface for 1-D multisignal analysis has been added. To start this GUI, select **Multisignal Analysis 1D** from the wavemenu dialog.

# R2006b

---

**Version: 3.1**

**New Features**

**Bug Fixes**

## Multivariate De-noising Added

A new command-line function (`wmulden`) and a new GUI (**Multivariate Denoising** from the `wavemenu` initial window) for de-noising a matrix of signals have been added. Both the function and GUI take into account the signals themselves and the correlations between the signals. A two-step process is used. First, a change of basis is performed to deal with noise spatial correlation de-noising in the new basis. Then, a principal component analysis is performed to take advantage of the deterministic relationships between the signals, leading to an additional de-noising effect.

## Multiscale Principal Component Analysis Added

A new command-line function (`wmspca`) and a new GUI (**Multiscale Princ. Comp. Analysis** from the `wavemenu` initial window) for simplifying a matrix of signals have been added. Both the function and GUI take into account the signals themselves and the correlations between the signals. The multiscale principal component analysis mixes wavelet decompositions and principal component analysis.

## New Demos

The following new demos are added:

- Continuous and Discrete Wavelet Analysis
- Detecting Discontinuities and Breakdown Points
- De-Noising Signals and Images
- Data Compression using 2D Wavelet Analysis
- Image Fusion
- Detecting Self-Similarity
- Wavelet Packets: Decomposing the Details



# R2006a

---

**Version: 3.0.4**

**No New Features or Changes**



# R14SP3

---

**Version: 3.0.3**

**No New Features or Changes**



# R14SP2

---

**Version: 3.0.2**

**No New Features or Changes**

