


RF Toolbox™ Release Notes



MATLAB®

How to Contact MathWorks



Latest news: www.mathworks.com
Sales and services: www.mathworks.com/sales_and_services
User community: www.mathworks.com/matlabcentral
Technical support: www.mathworks.com/support/contact_us



Phone: 508-647-7000



The MathWorks, Inc.
1 Apple Hill Drive
Natick, MA 01760-2098

RF Toolbox™ Release Notes

© COPYRIGHT 2004–2019 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See www.mathworks.com/trademarks for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

Patents

MathWorks products are protected by one or more U.S. patents. Please see www.mathworks.com/patents for more information.

R2019b

Inverse Chebyshev Filter: Design inverse Chebyshev filters using command line or RF Budget Analyzer app	1-2
generateSPICE function for rationalfit: Generate SPICE subcircuits for S-parameters rational fitting	1-2
setrfplot function for rfplot: Toggle the scale X-axis of rfplot between scalar and engineering units	1-2

R2019a

Test, visualize, and enforce passivity of rationalfit output	2-2
RF Filter element in RF Budget Analyzer app	2-2
Design narrowband matching networks for RF circuits	2-3

R2018b

S-parameters Plotting in RFBudgetAnalyzer App: Plot S-parameter magnitude, phase, and group delay for the stages of a budget object	3-2
--	------------

RF Filter Element: Design a behavioral model of an RF filter and add it to an RF circuit	3-3
Functionality being removed or changed	3-3
smithchart will be removed	3-3

R2018a

Smith and Polar Plots in RF Budget Analyzer App: Visualize input and output impedances, forward gain budget, and reverse isolation across signal bandwidth	4-2
Improved smithplot Function: Visualize network parameters for rfckt, rfddata, nport, and sparameters objects and support the circle function	4-2

R2017b

smithplot Function: Visualize network parameters, data, and markers on a Smith chart	5-2
Plot button in RF Budget Analyzer App: Visualize budget results across signal bandwidth	5-2

R2017a

Zero IF Support in rfBudgetAnalyzer App: Analyze direct conversion transmitters and receivers	6-2
MATLAB Functionality for RF Budget Analysis: Script and automate RF budget analysis	6-2

Generation of MATLAB script from rfBudgetAnalyzer App: Automate scripting for RF budget analysis	6-2
---	------------

Amplifier and Modulator Objects: Build networks of active and passive components using circuit objects	6-4
---	------------

R2016b

No New Features or Changes

R2016a

RF Budget Analyzer: Analytically compute gain, noise figure, and IP3 for cascaded RF components	8-2
--	------------

R2015b

LC Ladder Objects: Build different ladder configurations of LC elements and include them in arbitrary networks	9-2
---	------------

Group Delay Calculation: Compute the group delay for networks with arbitrary topologies and for any S-parameter data	9-2
---	------------

rationalfit Function Examples: Learn best practices for fitting S-parameter data	9-2
---	------------

R2015a

N-Port S-Parameters Circuit Element: Analyze RF networks containing S-parameter components	10-2
T-Parameters Data Object: Store and convert T-parameters data from other formats	10-2
rfplot Improvements: Plot real, imaginary, magnitude, or angle data	10-2

R2014b

Gain, noise figure, and IP3 cascade analysis for general RF stages	11-2
Network parameter object improvements for conversion of any network data object	11-2

R2014a

General de-embedding function for 2N-port S-parameters	12-2
N-port Touchstone file writing from any network data object or raw data	12-2
rationalfit function at least six times faster	12-2

R2013b

Additional functions for constructing arbitrary RLC networks	13-2
S-parameter extraction for arbitrary RLC networks	13-2

R2013a

Improved rationalfit function	14-2
--	-------------

R2012b

Network parameter interface improvements for faster reading of Touchstone files, plotting, and converting parameters	15-2
Name-value pair syntax for rationalfit function	15-2

R2012a

New Visualization Option for Intermediate-Frequency (IF) Planning Object	16-2
Enhanced S-Parameter Conversion Functions	16-2
New Demos for Signal Integrity Applications	16-2
Enhanced Rational Fitting	16-3

R2011b

New Intermediate Frequency (IF) Planning Object	17-2
New Functions for Calculating Transmission Line RLGC Parameters	17-2
Enhanced Rational Fitting	17-2
Conversion of Error and Warning Message Identifiers	17-2

R2011a

Bug Fixes

R2010b

Enhanced Rational Function Modeling	19-2
Extended Methods and Parameters for RF Object Visualization	19-2

R2010a

Function Added	20-2
Methods Added	20-2
Demo Added	20-2

R2009b

New Function for Testing Passivity of S-Parameters	21-2
Expanded Port-Ordering Schemes for S-Parameter Conversion Functions	21-2
Support for Calculation of Power-Wave Gain for Transfer Functions	21-2

R2009a

New Functions for Converting 4N-Port S-Parameter Matrices	22-2
Enhanced Dielectric Loss Model in Three Transmission Line Objects	22-2
Demos Added	22-2

R2008b

cascadesparams Function now supports N-port S-parameters	23-2
Improvements to the plotyy Method	23-2

R2008a

Calculation and Plotting Metrics Added	24-2
Network Parameter Conversion Functions Enhanced	24-2
gammams and gammaml Functions Added	24-2
z2gamma Function Added	24-2
Demos Added and Updated	24-2
Command-Line Help Updated	24-2

R2007b

snp2smp Function Added	25-2
circle Method Added	25-2
powergain Function Added	25-2
Smith Chart Enhanced	25-2
Demos Added and Updated	25-2

R2007a

Agilent P2D and S2D System-Level Verification Model Support Added	26-2
Mixer Spur Analysis Added	26-2

timeresp Method Added	26-3
Plotting Methods Added	26-3
gamma2z Function Added	26-3
Tab Completion Added	26-3
Data Tips Added	26-3
Demos Added and Updated	26-4

R2006b

S-Parameter Conversion Function Added	27-2
rfmodel Class Added	27-2
rationalfit Function Added	27-2
freqresp and impulse Functions Added	27-2
Support for Exporting Verilog-A Models Added	27-2
Demos Added	27-2

R2006a

S-Parameter Conversion Functions Added	28-2
---	-------------

R14SP3

extract Function Added	29-2
Circuit Object Added	29-2
Transmission Line Object Improved	29-2
Touchstone Data File Support Improved	29-2
Demos Improved	29-2
Command Window Help for Functions That Act on Circuit Objects Added	29-2

R14SP2

Plot Figures Integrated into the RF Tool GUI	30-2
Five Objects Added	30-2
Three Circuit Objects Added	30-2
Methods Added	30-2
Method Enhanced	30-2
Functions Added	30-2
General Enhancements	30-2

R2019b

Version: 3.7

New Features

Inverse Chebyshev Filter: Design inverse Chebyshev filters using command line or RF Budget Analyzer app

Use the `rffilter` object to design an inverse Chebyshev filter using the command line. You can also use the RF Budget Analyzer app to design the inverse Chebyshev filter and export the filter to RF Blockset™ or a measurement testbench.

generateSPICE function for rationalfit: Generate SPICE subcircuits for S-parameters rational fitting

Use the `generateSPICE` function to convert `rationalfit` output of S-parameters into SPICE subcircuits for simulation.

setrfplot function for rfplot: Toggle the scale X-axis of rfplot between scalar and engineering units

Use the `setrfplot` function to toggle the scale of `rfplot` X-axis between scalar units and engineering units (k, M, G, and so on).

R2019a

Version: 3.6

New Features


Test, visualize, and enforce passivity of rationalfit output

The `rationalfit` function converts frequency-domain S-parameters into rational functions that can be used for time-domain simulations. These simulations require the fit output to be passive. So, you can use the `ispassive` function to test the passivity of the `rationalfit` output. Use the `passivity` function to visualize the passivity of the `rationalfit` output. Use the `makepassive` function to enforce the passivity of the `rationalfit` output.

RF Filter element in RF Budget Analyzer app

In previous releases, to include an RF Filter element for budget analysis, you had to model it using the `rffilter` object at the command line and export its S-parameters as an `nport` object. You could then import the `nport` object into the app.

In this release, RF filter is now a budget element and can be directly added to the budget chain. You can also export the filter element into the RF Blockset, RF measurement testbench, a MATLAB[®] script, or the MATLAB workspace.



Design narrowband matching networks for RF circuits

Use the matchingnetwork object to design a set of circuits that match the impedance of a given source to the impedance of a given load at the specified center frequency. You can also export the matching network as circuit elements.

```
m = matchingnetwork % Default matching network
```

```
matchingnetwork with properties:
```

```
SourceImpedance: 50 Ohms
LoadImpedance: 50 Ohms
```

CenterFrequency: 1 GHz
Components: 2
Circuit: [1x2 circuit]

R2018b


Version: 3.5

New Features

Compatibility Considerations

S-parameters Plotting in RFBudgetAnalyzer App: Plot S-parameter magnitude, phase, and group delay for the stages of a budget object

You can now use the **RF Budget Analyzer** app plot button S-Parameters option to plot the magnitude, phase, and group delay of an RF system.



RF Filter Element: Design a behavioral model of an RF filter and add it to an RF circuit

Use the `rffilter` object to build lowpass, highpass, bandpass or bandstop Butterworth and Chebyshev filters. You can also use the `rffilter` object as a circuit element.

Functionality being removed or changed

smithchart will be removed

Still runs

`smithchart` will be removed in a future release. Use `smithplot` instead.

Function Name	What Happens When You Use This Function	Use This Function Instead	Compatibility Considerations
<code>smithchart</code>	Still runs	<code>smithplot</code>	Replace all instances of <code>smithchart</code> function with <code>smithplot</code> function using <code>smithplot</code> .

R2018a

Version: 3.4

New Features

Smith and Polar Plots in RF Budget Analyzer App: Visualize input and output impedances, forward gain budget, and reverse isolation across signal bandwidth

Use the **Smith** and **Polar** buttons in the **RF Budget Analyzer** app to plot output impedances, forward gain budget, RF system S-parameters, and reverse isolation across signal bandwidths.

Improved smithplot Function: Visualize network parameters for rfckt, rfddata, nport, and sparameters objects and support the circle function

Use the smithplot function to visualize network parameters for rfckt, rfddata, rfbudget, and nport objects.

R2017b

Version: 3.3

New Features

smithplot Function: Visualize network parameters, data, and markers on a Smith chart

Use the `smithplot` function to visualize data and network parameters with improved markers.

Plot button in RF Budget Analyzer App: Visualize budget results across signal bandwidth

Use the **Plot** button to visualize cumulative RF budget results versus cascade input frequency from within the **RF Budget Analyzer** app.

R2017a

Version: 3.2

New Features

Zero IF Support in rfBudgetAnalyzer App: Analyze direct conversion transmitters and receivers

You can now use the **RF Budget Analyzer** app to analyze direct conversion and low-IF transmitters and receivers.

MATLAB Functionality for RF Budget Analysis: Script and automate RF budget analysis

Use the `rfbudget` class to compute the cumulative gain, noise figure, and third intercept point (IP3) for an RF circuit created using RF elements. You can also use the `show` function to view the analysis on the **RF Budget Analyzer** app.

Generation of MATLAB script from rfBudgetAnalyzer App: Automate scripting for RF budget analysis

In the **RF Budget Analyzer**, under **Export** tab, click **MATLAB Script** to create a MATLAB script of the RF circuit and RF budget analysis. The figure shows you how to create the script of an RF circuit and its budget analysis.

RF Budget Analyzer - untitled

ANALYSIS deleteantennapfiles

+ New Open Save Delete Amplifier Modulator S-parameters Generic Export

FILE DELETE ADD ELEMENTS

untitled

System Parameters

Input frequency: 2.1 GHz

Available input power: -70 dBm

Signal bandwidth: 10 MHz

Element Parameters

S-parameters

Name: RFFilter

Touchstone file: alpass.s2p


Measurement testbench

RFFilter RFAmplifier Demod FFilter FAmplifier

S_{21} S_{22} S_{11} S_{12} S_{21} S_{22}

Stage	1	2	3	4	5
GainA (dB)	0	0	0	0	0
NF (dB)	0	0	0	0	0
OIP3 (dBm)	Inf	Inf	Inf	Inf	Inf

Cascade	1	1..2	1..3	1..4	1..5
Fout (GHz)	2.1	2.1	0.1	0.1	0.1
Pout (dBm)	-70	-70	-70	-70	-70
GainT (dB)	0	0	0	0	0
NF (dB)	0	0	0	0	0
OIP3 (dBm)	Inf	Inf	Inf	Inf	Inf
SNR (dB)	33.98	33.98	33.98	33.98	33.98



```
1 % Build a cascade (row vector) of RF elements
2 elements(1) = nport('allpass.s2p','RFFilter');
3 elements(2) = amplifier('Name','RFAmplifier');
4 elements(3) = modulator( ...
5     'Name','Demod', ...
6     'LO',2e9, ...
7     'ConverterType','Down');
8 elements(4) = nport('allpass.s2p','IFFilter');
9 elements(5) = amplifier('Name','IFAmplifier');
10
11 % Construct an rfbudget object
12 b = rfbudget( ...
13     'Elements',elements, ...
14     'InputFrequency',2.1e9, ...
15     'AvailableInputPower',-70, ...
16     'SignalBandwidth',10e6);
17
```

Amplifier and Modulator Objects: Build networks of active and passive components using circuit objects

Use the amplifier, modulator, and rfelement to build RF circuits. You can also analyze the RF budget of the circuit by using the rfbudget class.

R2016b

Version: 3.1

No New Features or Changes

R2016a

Version: 3.0

New Features

RF Budget Analyzer: Analytically compute gain, noise figure, and IP3 for cascaded RF components

You can use the RF Budget Analyzer app to compute the per-stage and cumulative gain, noise figure, and third intercept point (IP3) for a system of RF elements. Export the computed values to the MATLAB workspace. Simulate the system using SimRF™. Verify the gain, noise figure, and IP3 using the SimRF testbench simulation. To learn how to use the app, see [Superheterodyne Receiver Using RF Budget Analyzer App](#).

R2015b

Version: 2.17

New Features

LC Ladder Objects: Build different ladder configurations of LC elements and include them in arbitrary networks

You can use the `lcladder` class to create LC filters, calculate the S-parameters of the filters, and add the filters to an RF Toolbox circuit object.

Group Delay Calculation: Compute the group delay for networks with arbitrary topologies and for any S-parameter data

You can use the `groupdelay` function to calculate the group delay of the S-parameters object and these RF network elements: `nport`, `circuit`, and `LC ladder`.

rationalfit Function Examples: Learn best practices for fitting S-parameter data

Use these examples to understand how to improve the quality of `rationalfit` output:

- Using the 'NPoles' Parameter with `rationalfit`
- Using the 'Weight' Parameter with `rationalfit`
- Using the 'DelayFactor' Parameter with `rationalfit`

2015a

Version: 2.16

New Features

N-Port S-Parameters Circuit Element: Analyze RF networks containing S-parameter components

You can use `nport` to create a linear `nport` circuit element from Touchstone files and s-parameter objects. Use the `add` function to add n-port element to circuit element.

T-Parameters Data Object: Store and convert T-parameters data from other formats

You can create `tparameter` objects from touchstone files, network parameters, and `rfdata.network` objects using the `tparameters` data object function.

rfplot Improvements: Plot real, imaginary, magnitude, or angle data

You can now use the `rfplot` function to specify the types of plot such as decibels (default), real, imaginary, absolute, or angle.

R2014b

Version: 2.15

New Features

Bug Fixes

Gain, noise figure, and IP3 cascade analysis for general RF stages

You can now compute the `gain`, `noise figure`, `oip3`, and `iip3` of cascaded networks using the `rfchain` object. Display the stage-by-stage results in a spreadsheet format using the `worksheet` method. Visualize the results using the `plot` method.

Network parameter object improvements for conversion of any network data object

You can now convert `rfckt` or `rfddata.data` or `rfddata.network` objects into any network parameter objects including S-parameters, Y-parameters, ABCD-parameters objects.

R2014a

Version: 2.14

New Features

Bug Fixes

General de-embedding function for 2N-port S-parameters

You can now use the `deembedsparams` function to de-embed 2N-port fixture effects from 2N-port measurements. It supports both three-dimensional S-parameters data and S-parameter objects.

N-port Touchstone file writing from any network data object or raw data

You can use the `rfwrite` function to write Touchstone files from three-dimensional network parameter data or any network parameter object (S-parameters, Y-parameters, Z-parameters, ABCD-parameters, etc.)

rationalfit function at least six times faster

The `rationalfit` function now fits a rational model to S-parameter data at least six times faster than previous releases. This responsiveness improves both RF Toolbox command-line behavior and SimRF simulation of S-parameter blocks.

R2013b

Version: 2.13

New Features

Bug Fixes

Additional functions for constructing arbitrary RLC networks

In R2013b, the following new functions are available:

- resistor, capacitor, inductor, and circuit — Use the basic building functions of an RF circuit to construct RLC networks.
- add — Insert basic RF elements to a circuit.
- clone — Duplicate any existing RF elements or circuits.
- setports — Define node pairs as ports of a circuit.
- setterminals — Map the nodes of a circuit to terminals.

S-parameter extraction for arbitrary RLC networks

The `sparameters` function now includes added functionality that you can use to calculate the S-parameters of RLC networks.

R2013a

Version: 2.12

Bug Fixes

Compatibility Considerations

Improved rationalfit function

This release introduces additional pole-searching optimizations to the `rationalfit` function algorithm. Models that the function returns in this release tend to have fewer poles than those in previous releases.

Compatibility Considerations

To constrain the function results across releases and machine architectures, explicitly specify optional parameters such as error tolerance and number of poles when you call the function. Given a data set and corresponding frequencies, the function attempts to calculate a rational function approximation to within a given specification. However, the exact model that the function returns can differ between releases and machines, as the algorithm improves.

R2012b

Version: 2.11

New Features

Bug Fixes

Network parameter interface improvements for faster reading of Touchstone files, plotting, and converting parameters

New network parameter objects and functions are available, with support for:

- Reading Touchstone files
- Converting network parameters
- Plotting network parameters

Additionally, some functions have been updated to support the new interface. For more information, see RF Network Parameter Objects.

Name-value pair syntax for rationalfit function

The `rationalfit` function now supports using name-value pairs for optional input arguments. Name-value pair arguments can be specified in any order and improve readability of code.

R2012a

Version: 2.10

New Features

Bug Fixes

New Visualization Option for Intermediate-Frequency (IF) Planning Object

The OpenIF object supports a new interactive, graphical interface for assessing spur information in a mixer chain. You access this interface using the new `show` method.

Enhanced S-Parameter Conversion Functions

S-parameter conversion functions have been enhanced to support larger data sets. The following functions now support conversion between parameter sets of $2N$ -port networks.

- `abcd2s`
- `abcd2y`
- `abcd2z`
- `s2abcd`
- `y2abcd`
- `z2abcd`

The `s2smm` function now supports mixed-mode conversions for N -port devices.

The following mixed-mode S-parameter functions now support mixed-mode conversions for $2N$ -port devices:

- `s2scc`
- `s2scd`
- `s2sdc`
- `s2sdd`
- `smm2s`

New Demos for Signal Integrity Applications

Two new signal-integrity demos are available in this version.

- The Bandpass Filter Response demo describes a procedure for designing and analyzing a simple bandpass filter using `rfckt` objects.

-
- The MOS Interconnect and Crosstalk demo reproduces Pillage and Rohrer's classic result from "Waveform Evaluation for Timing Analysis".

Enhanced Rational Fitting

The `rationalfit` function has improved robustness, speed, and accuracy in this version.

R2011b

Version: 2.9

New Features

Bug Fixes

Compatibility Considerations

New Intermediate Frequency (IF) Planning Object

The `OpenIF` object supports a new partial workflow for multiband transmitter or receiver design. Use these objects to analyze intermediate frequencies (IFs) that do not produce interference (spurs) in operating bands.

New Functions for Calculating Transmission Line RLGC Parameters

The `rlgc2s` and `s2rlgc` functions allow you to calculate the per-unit-length RLGC parameters of a transmission line from transmission-line S-parameters.

Enhanced Rational Fitting

The `rationalfit` function has improved robustness, speed, and accuracy in this version.

Compatibility Considerations

Some default values of `rationalfit` have changed. For more information, see the function reference page.

Conversion of Error and Warning Message Identifiers

For R2011b, error and warning messages identifiers have changed in RF Toolbox software.

Compatibility Considerations

If you have scripts or functions that use message identifiers that changed, you must update the code to use the new identifiers. Typically, message identifiers are used to turn off specific warning messages, or in code that uses a `try/catch` statement and performs an action based on a specific error identifier.

For example, the `rf:rfckt:seriesrlc:setpositive:NotAPositive` identifier has changed to `rf:rftbase:rftbase:setpositive:NotAPositive`. If your code checks for `rf:rfckt:seriesrlc:setpositive:NotAPositive`, you must update it to check for `rf:rftbase:rftbase:setpositive:NotAPositive` instead.

To determine the identifier for a warning, run the following command just after you see the warning:

```
[MSG,MSGID] = lastwarn;
```

This command saves the message identifier to the variable `MSGID`.

To determine the identifier for an error, run the following command just after you see the error:

```
exception = MException.last;  
MSGID = exception.identifier;
```

Note Warning messages indicate a potential issue with your code. While you can turn off a warning, a suggested alternative is to change your code so it runs warning-free.

R2011a

Version: 2.8.1

Bug Fixes

R2010b

Version: 2.8

New Features

Compatibility Considerations

Enhanced Rational Function Modeling

An improved algorithm for the `rationalfit` function fits an accurate rational model to passive S-parameter data in less time than in previous versions. In addition, a new parameter specifies the number of iterations `rationalfit` attempts at each value for the number of poles.

Compatibility Considerations

Default behavior for some parameters have changed:

- The number-of-poles argument `npoles` defaults to a minimum value of 0 in version 2.8, instead of 4, as in previous versions.
- `rationalfit` does not display a wait bar by default in this version. A new `showwaitbar` parameter allows you to specify whether `rationalfit` displays a wait bar.

For more information on using this function, see the `rationalfit` reference page.

Extended Methods and Parameters for RF Object Visualization

RF Toolbox version 2.8 extends the Plots and Charts methods to include:

- Support for third-order intercept point and transducer power gain parameters, IIP3 and Gt.
- A new method, `table`, for visualizing network data in the Variable Editor.

R2010a

Version: 2.7

New Features

Function Added

The `makepassive` function creates passive S-Parameters from any S-parameter array. Use this function to enforce strict numerical passivity on an array of S-parameters that represents a passive device.

Methods Added

Two new methods for `rfmodel.rational` objects are available:

- The `ispassive` method tests global passivity of an `rfmodel.rational` object.
- The `stepresp` method calculates the response of an `rfmodel.rational` object to a step signal. You can use this function to perform time-domain reflectometry (TDR) and time-domain transmission (TDT) analysis.

Demo Added

The Modeling a High-Speed Backplane (Part 3: 4-Port S-Parameters to Differential TDR and TDT) demo shows how to perform time-domain reflectometry (TDR) and time-domain transmission (TDT) analysis on network data.

R2009b

Version: 2.6

New Features

Bug Fixes

New Function for Testing Passivity of S-Parameters

The `ispassive` function checks the passivity of N-port S-parameter matrices.

Expanded Port-Ordering Schemes for S-Parameter Conversion Functions

The functions `s2scc`, `s2scd`, `s2sdc`, `s2sdd`, `s2smm`, `s2smm` now support a third commonly-used port-ordering. For more information on using this feature, see the corresponding function reference page.

Support for Calculation of Power-Wave Gain for Transfer Functions

The `s2tf` function can now calculate the power-wave gain of 2-port S-parameters. Calculation in terms of voltage is still the default option.

R2009a

Version: 2.5

New Features

Compatibility Considerations

New Functions for Converting 4N-Port S-Parameter Matrices

There are two new functions for converting between 4N-port single-ended S-parameter matrices and 2N-port mixed-mode S-parameter matrices:

- The `s2smm` function lets you convert 4N-port single-ended S-parameters to 2N-port mixed-mode S-parameters. You can view the 2N-port output data to see interactions, such as crosstalk, that are not apparent in the single-ended data. This lets you easily select the ports of interest for further analysis.
- The `smm2s` function lets you convert 2N-port mixed-mode S-parameters to 4N-port single-ended S-parameters.

Enhanced Dielectric Loss Model in Three Transmission Line Objects

The following objects now provide a more realistic model for dielectric loss:

- `rfckt.coaxial`
- `rfckt.twowire`
- `rfckt.parallelplate`

To specify dielectric loss, you use a new property, `LossTangent`. This property replaces the `SigmaDiel` parameter.

Compatibility Considerations

Your existing objects with a nonzero value for the `SigmaDiel` parameter no longer model dielectric loss. Instead, the objects issue a warning message and use the default value of zero for the `LossTangent` property when you use the `analyze` method.

Demos Added

Two new demos show how to design broadband impedance matching networks for RF components:

- `Designing Broadband Matching Networks (Part 1: Antenna)` shows how to design a matching network for an antenna.

-
- Designing Broadband Matching Networks (Part 2: Amplifier) shows how to design a matching network for an amplifier.

R2008b

Version: 2.4

New Features

cascadesparams Function now supports N-port S-parameters

You can now use the `cascadesparams` function to cascade the S-parameters of an arbitrary number of N-port devices to form a network. The function lets you specify how to connect the ports of each N-port device to the ports of the subsequent N-port device in the cascade. For more information about the function, see the `cascadesparams` reference page.

Improvements to the `plotyy` Method

The `plotyy` method now uses a more intuitive approach when determining how to plot the specified parameters if you do not specify the plot format. For more information about the function, see the `plotyy` reference page.

R2008a

Version: 2.3

New Features

Calculation and Plotting Metrics Added

You can now compute and visualize group delay, voltage gain, and stability factor using the `calculate` and `plot` methods.

Network Parameter Conversion Functions Enhanced

You can now use the `s2sdd`, `s2sdc`, `s2scd`, and `s2scc` functions to perform conversions on network parameters with alternate port arrangements.

`gammams` and `gammaml` Functions Added

Use the new `gammams` and `gammaml` functions to compute source and load reflection coefficients required for simultaneous conjugate match.

`z2gamma` Function Added

Use the new `z2gamma` function to convert impedance values to reflection coefficients.

Demos Added and Updated

A new demo, `Writing a Touchstone File`, shows how to write `rfckt` object data to an industry-standard Touchstone data file.

`Modeling a High-Speed Backplane (Part 2: 4-Port S-Parameters to a Rational Function Model)` now uses the new Communications Toolbox™ `eye` diagram scope, `commscope.eyediagram`, to plot the eye diagram.

Command-Line Help Updated

The `help` function returns additional information for objects and packages. The function now includes descriptions of all properties and links to all relevant methods.

R2007b

Version: 2.2

New Features

snp2smp Function Added

Use the new `snp2smp` function to convert N-port S-parameter data and termination impedances to M-port S-parameters.

circle Method Added

Use the new `circle` method to place circles on a Smith® Chart to depict stability regions and display constant gain, noise figure, reflection, and imittance circles.

powergain Function Added

Use the new `powergain` function to compute various power gains of a 2-port network.

Smith Chart Enhanced

The `smith` method now lets you plot the network parameters of devices with more than two ports on a Smith Chart.

Demos Added and Updated

Modeling a High-Speed Backplane (Part 1: Measured 16-Port S-Parameters to 4-Port S-Parameters) is the new first part of a four-part demo on “Modeling a High-Speed Backplane.” The new demo shows how to extract 4-port S-parameter data from 16-port S-parameter data. The original three parts of the demo are now parts 2, 3, and 4.

The following demos replace the “Designing Impedance Matching Networks” and “Placing Circles on a Smith Chart” demos, respectively, and show how to use the new `circle` method:

- Designing Matching Networks (Part 1: Networks with an LNA and Lumped Elements) uses the available gain design technique to design a low-noise amplifier for a wireless communication system.
- Designing Matching Networks (Part 2: Single Stub Transmission Lines) shows how to design input and output matching networks for an amplifier.

R2007a

Version: 2.1

New Features

Agilent P2D and S2D System-Level Verification Model Support Added

The `rfckt.amplifier` and `rfckt.mixer` objects now let you import system-level verification models of amplifiers and mixers, respectively, using data from Agilent® P2D and S2D files.

Use P2D files to specify the following data for multiple operating conditions, such as temperature and bias values:

- Small-signal network parameters
- Power-dependent network parameters
- Noise data
- Intermodulation tables

Use S2D files to specify the following data for multiple operating conditions:

- Small-signal network parameters
- Gain compression (1 dB)
- Third-order intercept point (IP3)
- Power-dependent S_{21} parameters
- Noise data
- Intermodulation tables

Use the following methods to work with operating condition data after you import a P2D or S2D file into an RF object:

- `setop` — Use this method to set operating condition values or to list all available values.
- `getop` — Use this method to display the selected operating condition values.

Mixer Spur Analysis Added

You can import an intermodulation table into an `rfckt.mixer` object. The object's `plot` method has a new option for plotting mixer spur data.

timeresp Method Added

Use the new `timeresp` method of the `rfmodel.rational` object to compute the time response of an `rfmodel` object to a specified input signal. Use this method rather than computing impulse response with the `impulse` method and then convolving that response with the input signal because the `timeresp` method generally gives a more accurate output signal for a given input signal.

Plotting Methods Added

Four new plotting methods provide additional plotting options:

- Use the `plotyy` method of the `rfckt` class to create a plot that contains RF circuit object data on both the left and right Y-axes.
- Use the `loglog` method of the `rfckt` class to plot RF circuit object data on a log-log scale.
- Use the `semilogx` method of the `rfckt` class to plot RF circuit object data using a logarithmic scale for the X-axis.
- Use the `semilogy` method of the `rfckt` class to plot RF circuit object data using a logarithmic scale for the Y-axis.

gamma2z Function Added

Use the new `gamma2z` function to compute input impedance from a reflection coefficient.

Tab Completion Added

Tab completion is now available in the MATLAB command window for all functions and methods. For more information on tab completion, see the MATLAB documentation.

Data Tips Added

Data tips are now available for any RF plot. For more information on data tips, see [Data Cursor — Displaying Data Values Interactively](#) in the MATLAB documentation.

Demos Added and Updated

Visualizing Mixer Spurs shows how to use the toolbox to perform mixer spur analysis using data from an intermodulation table and then plot the output power spectrum of the desired signal and the undesired spurs.

Modeling a High-Speed Backplane (Part 1: Measured 4-Port S-Parameters to a Rational Function Model) now uses the `timeresp` method to compute the time-domain response of a system characterized by measured data.

Modeling a High-Speed Backplane (Part 2: Rational Function Model to Simulink Model) now includes code that you can use to generate a Simulink model for any `rfmodel.rational` object.

R2006b

Version: 2.0

New Features

S-Parameter Conversion Function Added

Use the `s2tf` function to convert 2-port scattering parameters into a transfer function that represents the normalized voltage gain of a 2-port network.

rfmodel Class Added

Use objects from the `rfmodel` class to represent components and networks with mathematical equations. The `rfmodel.rational` object stores a rational function model of a component or network.

rationalfit Function Added

Use the `rationalfit` function to fit a rational function to passive data that represents an RF component or network and then store the result in an `rfmodel.rational` object. This type of model is useful to signal integrity engineers, whose goal is to reliably connect high-speed semiconductor devices with, for example, multi-Gbit/s serial data streams across backplanes and printed circuit boards.

freqresp and impulse Functions Added

Use the `freqresp` method of the `rfmodel` class to compute the frequency response of an `rfmodel` object.

Use the `impulse` method of the `rfmodel` class to compute the impulse response of an `rfmodel` object.

Support for Exporting Verilog-A Models Added

Use the `writeva` method of the `rfmodel` class to export a description of an RF component or network for use in a time-domain circuit simulator.

Demos Added

“Modeling a High-Speed Backplane (Part 1: Measured 4-Port S-Parameters to a Rational Function Model)” shows how to use the toolbox to model a differential high-speed backplane using rational functions.

“Modeling a High-Speed Backplane (Part 2: Rational Function Model to a Verilog-A Module)” shows how to use toolbox functions to generate a Verilog-A module that models the high-level behavior of a high-speed backplane.

“Modeling a Differential High-Speed Backplane in Simulink” shows how to use Simulink to simulate a differential high-speed backplane.

R2006a

Version: 1.3

New Features

S-Parameter Conversion Functions Added

Use the `s2scc` function to convert 4-port, single-ended S-parameters to 2-port, common mode S-parameters.

Use the `s2scd` function to convert 4-port, single-ended S-parameters to 2-port, cross mode S-parameters.

Use the `s2sdc` function to convert 4-port, single-ended S-parameters to 2-port, cross mode S-parameters.

Use the `s2sdd` function to convert 4-port, single-ended S-parameters to 2-port, differential mode S-parameters.

R14SP3

Version: 1.2

New Features

extract Function Added

Use the `extract` function to extract specified network parameters from a circuit or data object and return the result in an array.

Circuit Object Added

Use `rfckt.rlcgline` to construct an RLCG transmission line object.

Transmission Line Object Improved

The new `Freq` property of the circuit object, `rfckt.txline`, is a vector of positive frequencies at which the parameter values are known.

The `Loss`, `PV`, and `Z0` properties of the circuit object, `rfckt.txline`, can now be vectors of line loss, phase velocity, and characteristic impedance values that correspond to the frequencies specified in the `Freq` property.

The new `IntpType` property of the circuit object, `rfckt.txline`, is the interpolation method used to calculate the parameter values between the known frequencies.

Touchstone Data File Support Improved

You can now read data from Touchstone data files that contain comments and spaces between sections of data.

Demos Improved

The demos have new documentation and can be accessed using an improved interface.

Command Window Help for Functions That Act on Circuit Objects Added

You can access help for functions that act on circuit objects by using the syntax `help functionname` at the MATLAB command prompt.

R14SP2

Version: 1.1

New Features

Plot Figures Integrated into the RF Tool GUI

In earlier versions, a plot figure would appear in a separate window after clicking the **Plot** button. In this version, plot figures are integrated into the GUI itself.

Five Objects Added

These objects can be used to store rfd data such as network parameters, noise figure, power, IP3, and spot noise.

Three Circuit Objects Added

Use `rfckt.delay` to model delay lines, `rfckt.hybridg` to model hybrid G connected networks, and `rfckt.passive` to model RF passive networks.

Methods Added

The new `write` method allows saving of RF network data into files for all `rfckt` objects.

The new methods, `read` and `restore`, read and restore data for `rfckt.datafile`, `rfckt.amplifier`, and `rfckt.mixer`.

Method Enhanced

The `analyze` method now takes three additional optional inputs for the load, source, and reference impedances.

Functions Added

The functions `stabilitymu` and `stabilityk` calculate the stability factors μ and k .

The functions `h2g` and `g2h` convert between hybrid G and hybrid H parameters.

General Enhancements

It is now possible to create the objects `rfckt.amplifier` and `rfckt.mixer` from a MATLAB variable.

The frequency-dependent NF and IP3 data types were added to the AMP format.

