

# MATLAB® Compiler SDK™

## Getting Started Guide



# MATLAB®

R2021b



## How to Contact MathWorks



Latest news: [www.mathworks.com](http://www.mathworks.com)  
Sales and services: [www.mathworks.com/sales\\_and\\_services](http://www.mathworks.com/sales_and_services)  
User community: [www.mathworks.com/matlabcentral](http://www.mathworks.com/matlabcentral)  
Technical support: [www.mathworks.com/support/contact\\_us](http://www.mathworks.com/support/contact_us)



Phone: 508-647-7000



The MathWorks, Inc.  
1 Apple Hill Drive  
Natick, MA 01760-2098

*MATLAB® Compiler SDK™ Getting Started Guide*

© COPYRIGHT 2012–2021 by The MathWorks, Inc.

The software described in this document is furnished under a license agreement. The software may be used or copied only under the terms of the license agreement. No part of this manual may be photocopied or reproduced in any form without prior written consent from The MathWorks, Inc.

FEDERAL ACQUISITION: This provision applies to all acquisitions of the Program and Documentation by, for, or through the federal government of the United States. By accepting delivery of the Program or Documentation, the government hereby agrees that this software or documentation qualifies as commercial computer software or commercial computer software documentation as such terms are used or defined in FAR 12.212, DFARS Part 227.72, and DFARS 252.227-7014. Accordingly, the terms and conditions of this Agreement and only those rights specified in this Agreement, shall pertain to and govern the use, modification, reproduction, release, performance, display, and disclosure of the Program and Documentation by the federal government (or other entity acquiring for or through the federal government) and shall supersede any conflicting contractual terms or conditions. If this License fails to meet the government's needs or is inconsistent in any respect with federal procurement law, the government agrees to return the Program and Documentation, unused, to The MathWorks, Inc.

### Trademarks

MATLAB and Simulink are registered trademarks of The MathWorks, Inc. See [www.mathworks.com/trademarks](http://www.mathworks.com/trademarks) for a list of additional trademarks. Other product or brand names may be trademarks or registered trademarks of their respective holders.

### Patents

MathWorks products are protected by one or more U.S. patents. Please see [www.mathworks.com/patents](http://www.mathworks.com/patents) for more information.

### Revision History

March 2015	Online only	New for Version 6.0 (Release R2015a)
September 2015	Online only	Revised for Version 6.1 (Release 2015b)
October 2015	Online only	Rereleased for Version 6.0.1 (Release 2015aSP1)
March 2016	Online only	Revised for Version 6.2 (Release 2016a)
September 2016	Online only	Revised for Version 6.3 (Release R2016b)
March 2017	Online only	Revised for Version 6.3.1 (Release R2017a)
September 2017	Online only	Revised for Version 6.4 (Release R2017b)
March 2018	Online only	Revised for Version 6.5 (Release R2018a)
September 2018	Online only	Revised for Version 6.6 (Release R2018b)
March 2019	Online only	Revised for Version 6.6.1 (Release R2019a)
September 2019	Online only	Revised for Version 6.7 (Release R2019b)
March 2020	Online only	Revised for Version 6.8 (Release R2020a)
September 2020	Online only	Revised for Version 6.9 (Release R2020b)
March 2021	Online only	Revised for Version 6.10 (Release R2021a)
September 2021	Online only	Revised for Version 6.11 (Release R2021b)

## Overview of MATLAB Compiler SDK

### 1

<b>MATLAB Compiler SDK Product Description</b> .....	<b>1-2</b>
<b>Appropriate Tasks for MATLAB Compiler Products</b> .....	<b>1-3</b>
<b>Deployment Product Terms</b> .....	<b>1-5</b>
<b>Files Generated After Packaging MATLAB Functions</b> .....	<b>1-10</b>
for_redistribution Folder .....	<b>1-10</b>
for_redistribution_files_only Folder .....	<b>1-10</b>
for_testing Folder .....	<b>1-12</b>
<b>Install and Configure MATLAB Runtime</b> .....	<b>1-14</b>
Download MATLAB Runtime Installer .....	<b>1-14</b>
Install MATLAB Runtime Interactively .....	<b>1-14</b>
Install MATLAB Runtime Noninteractively .....	<b>1-16</b>
Install MATLAB Runtime without Administrator Rights .....	<b>1-17</b>
Install Multiple MATLAB Runtime Versions on Single Machine .....	<b>1-17</b>
Install MATLAB and MATLAB Runtime on Same Machine .....	<b>1-18</b>
Uninstall MATLAB Runtime .....	<b>1-18</b>

## Examples

### 2

<b>Create a C Shared Library with MATLAB Code</b> .....	<b>2-2</b>
Create Functions in MATLAB .....	<b>2-2</b>
Create a C Shared Library Using the Library Compiler App .....	<b>2-3</b>
Customize the Application and Its Appearance .....	<b>2-4</b>
Package the Application .....	<b>2-5</b>
<b>Generate a C++ mxArray API Shared Library and Build a C++ Application</b> .....	<b>2-6</b>
Create Functions in MATLAB .....	<b>2-6</b>
Create a C++ Shared Library Using the Library Compiler App .....	<b>2-6</b>
Create a C++ Shared Library Using compiler.build.cppSharedLibrary ...	<b>2-8</b>
Implement the C++ mxArray API Shared Library with a Driver Application .....	<b>2-9</b>
<b>Generate a C++ MATLAB Data API Shared Library and Build a C++ Application</b> .....	<b>2-11</b>
Create Functions in MATLAB .....	<b>2-11</b>
Create a C++ Shared Library Using Library Compiler App .....	<b>2-11</b>

Create a C++ Shared Library Using compiler.build.cppSharedLibrary . . .	2-13
Implement the C++ MATLAB Data API Shared Library with a Driver Application . . . . .	2-14
<b>Generate .NET Assembly and Build .NET Application . . . . .</b>	<b>2-16</b>
Prerequisites . . . . .	2-16
Files . . . . .	2-16
Create Function in MATLAB . . . . .	2-16
Create .NET Assembly Using Library Compiler App . . . . .	2-16
Create .NET Assembly Using compiler.build.dotNETAssembly . . . . .	2-20
Integrate .NET Assembly Into .NET Application . . . . .	2-21
<b>Create a Generic COM Component with MATLAB Code . . . . .</b>	<b>2-24</b>
Prerequisites . . . . .	2-24
Create Function in MATLAB . . . . .	2-24
Create Generic COM Component Using Library Compiler App . . . . .	2-24
Customize the Application and Its Appearance . . . . .	2-25
Package the Application . . . . .	2-26
Create COM Component Using compiler.build.COMComponent . . . . .	2-27
Integrate into COM Application . . . . .	2-29
<b>Generate Java Package and Build Java Application . . . . .</b>	<b>2-30</b>
Prerequisites . . . . .	2-30
Create Function in MATLAB . . . . .	2-30
Create Java Package Using Library Compiler App . . . . .	2-30
Create Java Package Using compiler.build.javaPackage . . . . .	2-34
Compile and Run MATLAB Generated Java Application . . . . .	2-35
<b>Generate a Python Package and Build a Python Application . . . . .</b>	<b>2-37</b>
Prerequisites . . . . .	2-37
Create Function in MATLAB . . . . .	2-37
Create Python Application Using Library Compiler App . . . . .	2-37
Create Python Package Using compiler.build.pythonPackage . . . . .	2-41
Install and Run MATLAB Generated Python Application . . . . .	2-42

## Customizing a Compiler Project

# 3

<b>Customize an Application . . . . .</b>	<b>3-2</b>
Customize the Installer . . . . .	3-2
Manage Required Files in Compiler Project . . . . .	3-4
Sample Driver File Creation . . . . .	3-5
Specify Files to Install with Application . . . . .	3-6
Additional Runtime Settings . . . . .	3-6
API Selection for C++ Shared Library . . . . .	3-7
<b>Manage Support Packages . . . . .</b>	<b>3-9</b>
Using a Compiler App . . . . .	3-9
Using the Command Line . . . . .	3-9

<b>Create Deployable Archive for MATLAB Production Server</b> .....	<b>4-2</b>
Create MATLAB Function .....	<b>4-2</b>
Create Deployable Archive with Production Server Compiler App .....	<b>4-2</b>
Customize Application and Its Appearance .....	<b>4-3</b>
Package Application .....	<b>4-3</b>
<b>Create and Install a Deployable Archive with Excel Integration For MATLAB Production Server</b> .....	<b>4-5</b>
Create Function In MATLAB .....	<b>4-5</b>
Create Deployable Archive with Excel Integration Using Production Server Compiler App .....	<b>4-5</b>
Customize the Application and Its Appearance .....	<b>4-6</b>
Package the Application .....	<b>4-7</b>
Install the Deployable Archive with Excel Integration .....	<b>4-8</b>
<b>Create a C# Client Using MWHttpClient</b> .....	<b>4-9</b>
<b>Create Java Client Using MWHttpClient Class</b> .....	<b>4-12</b>
<b>Create a C++ Client</b> .....	<b>4-15</b>
<b>Create a Python Client</b> .....	<b>4-20</b>



# Overview of MATLAB Compiler SDK

---

- “MATLAB Compiler SDK Product Description” on page 1-2
- “Appropriate Tasks for MATLAB Compiler Products” on page 1-3
- “Deployment Product Terms” on page 1-5
- “Files Generated After Packaging MATLAB Functions” on page 1-10
- “Install and Configure MATLAB Runtime” on page 1-14

## **MATLAB Compiler SDK Product Description**

### **Build software components from MATLAB programs**

MATLAB Compiler SDK extends the functionality of MATLAB Compiler™ to let you build C/C++ shared libraries, Microsoft® .NET assemblies, and Java® classes from MATLAB programs. These components can be integrated with custom applications and then deployed to desktop, web, and enterprise systems.

MATLAB Compiler SDK includes a development version of MATLAB Production Server™ for testing and debugging application code and Excel® add-ins before deploying them to web applications and enterprise systems.

Applications created using software components from MATLAB Compiler SDK can be shared royalty-free with users who do not need MATLAB. These applications use the MATLAB Runtime, a set of shared libraries that enables the execution of compiled MATLAB applications or components. To generate C and C++ source code from MATLAB, use MATLAB Coder™



## Appropriate Tasks for MATLAB Compiler Products

MATLAB Compiler generates standalone applications and Excel add-ins. MATLAB Compiler SDK generates C/C++ shared libraries, deployable archives for use with MATLAB Production Server, Java packages, .NET assemblies, and COM components.

While MATLAB Compiler and MATLAB Compiler SDK let you run your MATLAB application outside the MATLAB environment, it is not appropriate for all external tasks you may want to perform. Some tasks require other products or MATLAB external interfaces. Use the following table to determine if MATLAB Compiler or MATLAB Compiler SDK is appropriate to your needs.

Task	MATLAB Compiler and MATLAB Compiler SDK	MATLAB Coder	Simulink®	HDL Coder™	MATLAB External Interfaces
Package MATLAB applications for deployment to users who do not have MATLAB	■				
Package MATLAB applications for deployment to MATLAB Production Server	■				
Build non-MATLAB applications that include MATLAB functions	■				
Generate readable and portable C/C++ code from MATLAB code		■			
Generate MEX functions from MATLAB code for code verification and acceleration.		■			
Integrate MATLAB code into Simulink			■		

<b>Task</b>	<b>MATLAB Compiler and MATLAB Compiler SDK</b>	<b>MATLAB Coder</b>	<b>Simulink®</b>	<b>HDL Coder™</b>	<b>MATLAB External Interfaces</b>
Generate hardware description language (HDL) from MATLAB code				■	
Integrate custom C code into MATLAB with MEX files					■
Call MATLAB from C and Fortran programs					■
Task	MATLAB Compiler and MATLAB Compiler SDK	MATLAB Coder	Simulink	HDL Coder	MATLAB External Interfaces

---

**Note** Components generated by MATLAB Compiler and MATLAB Compiler SDK cannot be used in the MATLAB environment.

---

## Deployment Product Terms

### A

*Add-in* — A Microsoft Excel add-in is an executable piece of code that can be actively integrated into a Microsoft Excel application. Add-ins are front-ends for COM components, usually written in some form of Microsoft Visual Basic®.

*Application program interface (API)* — A set of classes, methods, and interfaces that is used to develop software applications. Typically an API is used to provide access to specific functionality. See *MWArray*.

*Application* — An end user-system into which a deployed functions or solution is ultimately integrated. Typically, the end goal for the deployment customer is integration of a deployed MATLAB function into a larger enterprise environment application. The deployment products prepare the MATLAB function for integration by wrapping MATLAB code with enterprise-compatible source code, such as C, C++, C# (.NET), F#, and Java code.

*Assembly* — An executable bundle of code, especially in .NET.

### B

*Binary* — See *Executable*.

*Boxed Types* — Data types used to wrap opaque C structures.

*Build* — See *Compile*.

### C

*Class* — A user-defined type used in C++, C#, and Java, among other object-oriented languages, that is a prototype for an object in an object-oriented language. It is analogous to a derived type in a procedural language. A class is a set of objects which share a common structure and behavior. Classes relate in a class hierarchy. One class is a specialization (a subclass) of another (one of its *superclasses*) or comprises other classes. Some classes use other classes in a client-server relationship. Abstract classes have no members, and concrete classes have one or more members. Differs from a MATLAB class

*Compile* — In MATLAB Compiler and MATLAB Compiler SDK, to compile MATLAB code involves generating a binary that wraps around MATLAB code, enabling it to execute in various computing environments. For example, when MATLAB code is compiled into a Java package, a Java wrapper provides Java code that enables the MATLAB code to execute in a Java environment.

*COM component* — In MATLAB Compiler, the executable back-end code behind a Microsoft Excel add-in. In MATLAB Compiler SDK, an executable component, to be integrated with Microsoft COM applications.

*Console application* — Any application that is executed from a system command prompt window.

### D

*Data Marshaling* — Data conversion, usually from one type to another. Unless a MATLAB deployment customer is using type-safe interfaces, data marshaling—as from mathematical data types to MathWorks® data types such as represented by the *MWArray* API—must be performed manually, often at great cost.

*Deploy* — The act of integrating MATLAB code into a larger-scale computing environment, usually to an enterprise application, and often to end users.

*Deployable archive* — The deployable archive is embedded by default in each binary generated by MATLAB Compiler or MATLAB Compiler SDK. It houses the deployable package. All MATLAB-based content in the deployable archive uses the Advanced Encryption Standard (AES) cryptosystem. See “Additional Details”.

*DLL* — Dynamic link library. Microsoft's implementation of the shared library concept for Windows®. Using DLLs is much preferred over the previous technology of static (or non-dynamic) libraries, which had to be manually linked and updated.

## **E**

*Empties* — Arrays of zero (0) dimensions.

*Executable* — An executable bundle of code, made up of binary bits (zeros and ones) and sometimes called a *binary*.

## **F**

*Fields* — For this definition in the context of MATLAB Data Structures, see *Structs*.

*Fields and Properties* — In the context of .NET, *Fields* are specialized classes used to hold data. *Properties* allow users to access class variables as if they were accessing member fields directly, while actually implementing that access through a class method.

## **I**

*Integration* — Combining deployed MATLAB code's functionality with functionality that currently exists in an enterprise application. For example, a customer creates a mathematical model to forecast trends in certain commodities markets. In order to use this model in a larger-scale financial application (one written with the Microsoft .NET Framework, for instance) the deployed financial model must be integrated with existing C# applications, run in the .NET enterprise environment.

*Instance* — For the definition of this term in context of MATLAB Production Server software, see *MATLAB Production Server Server Instance*.

## **J**

*JAR* — Java archive. In computing software, a JAR file (or Java Archive) aggregates many files into one. Software developers use JARs to distribute Java applications or libraries, in the form of classes and associated metadata and resources (text, images, etc.). Computer users can create or extract JAR files using the `jar` command that comes with a Java Development Kit (JDK).

*Java-MATLAB Interface* — Known as the *JMI Interface*, this is the Java interface built into MATLAB software.

*JDK* — The Java Development Kit is a product which provides the environment required for programming in Java.

*JMI Interface* — see *Java-MATLAB Interface*.

*JRE* — Java Run-Time Environment is the part of the Java Development Kit (JDK) required to run Java programs. It comprises the Java Virtual Machine, the Java platform core classes, and supporting files.

It does not include the compiler, debugger, or other tools present in the JDK™. The JRE™ is the smallest set of executables and files that constitute the standard Java platform.

## M

*Magic Square* — A square array of integers arranged so that their sum is the same when added vertically, horizontally, or diagonally.

*MATLAB Runtime* — An execution engine made up of the same shared libraries. MATLAB uses these libraries to enable the execution of MATLAB files on systems without an installed version of MATLAB.

*MATLAB Runtime singleton* — See *Shared MATLAB Runtime instance*.

*MATLAB Runtime workers* — A MATLAB Runtime session. Using MATLAB Production Server software, you have the option of specifying more than one MATLAB Runtime session, using the `--num-workers` options in the server configurations file.

*MATLAB Production Server Client* — In the MATLAB Production Server software, clients are applications written in a language supported by MATLAB Production Server that call deployed functions hosted on a server.

*MATLAB Production Server Configuration* — An instance of the MATLAB Production Server containing at least one server and one client. Each configuration of the software usually contains a unique set of values in the server configuration file, `main_config` (MATLAB Production Server).

*MATLAB Production Server Server Instance* — A logical server configuration created using the `mps-new` command in MATLAB Production Server software.

*MATLAB Production Server Software* — Product for server/client deployment of MATLAB programs within your production systems, enabling you to incorporate numerical analytics in enterprise applications. When you use this software, web, database, and enterprise applications connect to MATLAB programs running on MATLAB Production Server via a lightweight client library, isolating the MATLAB programs from your production system. MATLAB Production Server software consists of one or more servers and clients.

*Marshaling* — See *Data Marshaling*.

*mbuild* — MATLAB Compiler SDK command that compiles and links C and C++ source files into standalone applications or shared libraries. For more information, see the `mbuild` function reference page.

*mcc* — The MATLAB command that invokes the compiler. It is the command-line equivalent of using the compiler apps.

*Method Attribute* — In the context of .NET, a mechanism used to specify declarative information to a .NET class. For example, in the context of client programming with MATLAB Production Server software, you specify method attributes to define MATLAB structures for input and output processing.

*mxArray interface* — The MATLAB data type containing all MATLAB representations of standard mathematical data types.

*MWArray interface* — A proxy to `mxArray`. An application program interface (API) for exchanging data between your application and MATLAB. Using `MWArray`, you marshal data from traditional mathematical types to a form that can be processed and understood by MATLAB data type `mxArray`.

There are different implementations of the `MWArray` proxy for each application programming language.

## **P**

*Package* — The act of bundling the deployed MATLAB code, along with the MATLAB Runtime and other files, into an installer that can be distributed to others. The compiler apps place the installer in the `for_redistribution` subfolder. In addition to the installer, the compiler apps generate a number of loose artifacts that can be used for testing or building a custom installer.

*PID File* — See *Process Identification File (PID File)*.

*Pool* — A pool of threads, in the context of server management using MATLAB Production Server software. Servers created with the software do not allocate a unique thread to each client connection. Rather, when data is available on a connection, the required processing is scheduled on a pool, or group, of available threads. The server configuration file option `--num-threads` sets the size of that pool (the number of available request-processing threads) in the master server process.

*Process Identification File (PID File)* — A file that documents informational and error messages relating to a running server instance of MATLAB Production Server software.

*Program* — A bundle of code that is executed to achieve a purpose. Programs usually are written to automate repetitive operations through computer processing. Enterprise system applications usually consist of hundreds or even thousands of smaller programs.

*Properties* — For this definition in the context of .NET, see *Fields and Properties*.

*Proxy* — A software design pattern typically using a class, which functions as an interface to something else. For example, `MWArray` is a proxy for programmers who need to access the underlying type `mxArray`.

## **S**

*Server Instance* — See MATLAB Production Server Server Instance.

*Shared Library* — Groups of files that reside in one space on disk or memory for fast loading into Windows applications. Dynamic-link libraries (DLLs) are Microsoft's implementation of the shared library concept for Microsoft Windows.

*Shared MATLAB Runtime instance* — When using MATLAB Compiler SDK, you can create a shared MATLAB Runtime instance, also known as a singleton. When you invoke MATLAB Compiler with the `-S` option through the compiler (using either `mcc` or a compiler app), a single MATLAB Runtime instance is created for each COM component or Java package in an application. You reuse this instance by sharing it among all subsequent class instances. Such sharing results in more efficient memory usage and eliminates the MATLAB Runtime startup cost in each subsequent class instantiation. All class instances share a single MATLAB workspace and share global variables in the deployed MATLAB files. MATLAB Compiler SDK creates singletons by default for .NET assemblies. MATLAB Compiler creates singletons by default for the COM components used by the Excel add-ins.

*State* — The present condition of MATLAB, or the MATLAB Runtime. MATLAB functions often carry state in the form of variable values. The MATLAB workspace itself also maintains information about global variables and path settings. When deploying functions that carry state, you must often take additional steps to ensure state retention when deploying applications that use such functions.

*Structs* — MATLAB Structures. Structs are MATLAB arrays with elements that you access using textual field designators. Fields are data containers that store data of a specific MATLAB type.

*System Compiler* — A key part of Interactive Development Environments (IDEs) such as Microsoft Visual Studio®.

## T

*Thread* — A portion of a program that can run independently of and concurrently with other portions of the program. See *pool* for additional information on managing the number of processing threads available to a server instance.

*Type-safe interface* — An API that minimizes explicit type conversions by hiding the `MWArray` type from the calling application.

## W

*Web Application Archive (WAR)* —In computing, a Web Application Archive is a JAR file used to distribute a collection of JavaServer pages, servlets, Java classes, XML files, tag libraries, and static web pages that together constitute a web application.

*Webfigure* — A MathWorks representation of a MATLAB figure, rendered on the web. Using the WebFigures feature, you display MATLAB figures on a website for graphical manipulation by end users. This enables them to use their graphical applications from anywhere on the web, without the need to download MATLAB or other tools that can consume costly resources.

*Windows Communication Foundation (WCF)* — The Windows Communication Foundation™ is an application programming interface in the .NET Framework for building connected, service-oriented, web-centric applications. WCF is designed in accordance with service oriented architecture principles to support distributed computing where services are consumed by client applications.

## Files Generated After Packaging MATLAB Functions

When the packaging process is complete, three folders are generated in the target folder location: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

### for\_redistribution Folder

Distribute the `for_redistribution` folder to users who do not have MATLAB installed on their machines.

The folder contains the file `MyAppInstaller_web.exe` that installs the application and the MATLAB Runtime (if it is included in the application at the time of packaging). It installs all the files that enable use of the packaged application on the target platform with the target language in the target folder.

### for\_redistribution\_files\_only Folder

Distribute the `for_redistribution_files_only` folder to users who do not have MATLAB installed on their machines. This folder contains specific files that enable use of the packaged application on the target platform with the target language.

#### C Shared Library

File	Description
<code>readme.txt</code>	Text file containing packaging information.
<code>filename.lib</code>	Import library for user-written shared library.
<code>filename.h</code>	Header file for user-written shared library.
<code>filename.dll</code>	Code for user-written shared library.

#### C++ Shared Library

File	Description
<code>readme.txt</code>	Text file containing packaging information.
<code>filename.lib</code>	Import library for user-written mxArray API shared library.
<code>filename.hpp</code>	Header file for user-written mxArray API shared library.
<code>filename.dll</code>	Code for user-written mxArray API shared library.
v2: <ul style="list-style-type: none"> <li>• Generic_interface: <ul style="list-style-type: none"> <li>• <code>filename.ctf</code></li> <li>• <code>readme.txt</code></li> </ul> </li> </ul>	<p>The folder <code>v2</code> contains another folder <code>Generic_interface</code>. It contains a <code>ctf</code> file, which is the deployable archive for MATLAB Data API library.</p> <p>It also contains a <code>readme.txt</code> file that has packaging information.</p>



**COM Component**

<b>File</b>	<b>Description</b>
<code>_install.bat</code>	File that registers the generated dll file.
<code>filename_1_0.dll</code>	The generated dll that needs to be registered using <code>mwregsvr.exe</code> or <code>regsvr32.exe</code> .
<code>readme.txt</code>	Text file containing packaging information.

**.NET Assembly**

<b>File</b>	<b>Description</b>
<code>Filename.dll</code>	File that contains the generated component that can be accessed using <code>mwArray</code> API.
<code>Filename_overview.html</code>	HTML overview documentation file for the generated component. It contains requirements for accessing the component and for generating arguments using the <code>mwArray</code> class hierarchy.
<code>FilenameNative.dll</code>	File that contains the generated component that can be accessed using native API.
<code>readme.txt</code>	Text file containing packaging information.

## Java Application

File	Description
doc: <ul style="list-style-type: none"> <li>• html:                             <ul style="list-style-type: none"> <li>• <i>filename</i> <ul style="list-style-type: none"> <li>• Class1.html</li> <li>• Class1Remote.html</li> <li>• <i>Filename</i>MCRFactory.html</li> <li>• packageframe.html</li> <li>• package-summary.html</li> <li>• packagetree.html</li> </ul> </li> <li>• allclasses-frame.html</li> <li>• allclasses-noframe.html</li> <li>• constantvalues.html</li> <li>• deprecated-list.html</li> <li>• help-doc.html</li> <li>• index.html</li> <li>• index-all.html</li> <li>• overview-tree.html</li> <li>• package-list</li> <li>• script.js</li> <li>• stylesheet.css</li> </ul> </li> </ul>	The folder <code>doc</code> contains another folder <code>html</code> which contains HTML documentation for all classes in the packaged Java application.
<i>Filename</i> .jar	Java archive for user-written application.
readme.txt	Text file containing packaging information.

## Python Application

File	Description
<i>Filename</i> : <ul style="list-style-type: none"> <li>• <code>_init_.py</code></li> <li>• <i>Filename</i>.ctf</li> </ul>	The folder <i>Filename</i> contains the following files: <ul style="list-style-type: none"> <li>• File used during initialization of the Python® package.</li> <li>• Deployable archive for the Python package.</li> </ul>
setup.py	File that installs the Python packaged application.
readme.txt	Text file containing packaging information.

## for\_testing Folder

Use the files in this folder to test your application. The folder contains all the intermediate and final artifacts such as binaries, JAR files, header files, and source files for a specific target. The final artifacts created during the packaging process are the same files as described in

“for\_redistribution\_files\_only Folder”. You use these files to test your application. For further information on how to test your packaged applications, see the following topics:

Target	Link
C	“Implement a C Shared Library with a Driver Application”
C++ mxArray API	“Implement the C++ mxArray API Shared Library with a Driver Application” on page 2-9
C++ MATLAB Data API	“Implement the C++ MATLAB Data API Shared Library with a Driver Application” on page 2-14
.NET	“Integrate a .NET Assembly Into a C# Application” “Integrate a .NET Assembly Into a Visual Basic Application”
COM	“Integrate Magic Square into a COM Application”
Java	“Integrate Simple MATLAB Function Into Java Application”
Python	“Integrate a Python Package”

The intermediate artifacts generated are a result of packaging of the MATLAB files. They are not significant to the user.

This folder also contains two text files. `mccExcludedFiles.txt` lists the files excluded from packaged application, and `requiredMCRProducts.txt`, contains product IDs of products required by MATLAB Runtime to run the application.

## See Also

`mcc` | `deploytool`

## More About

- “Create a C Shared Library with MATLAB Code” on page 2-2
- “Generate a C++ mxArray API Shared Library and Build a C++ Application” on page 2-6
- “Generate a C++ MATLAB Data API Shared Library and Build a C++ Application” on page 2-11
- “Generate .NET Assembly and Build .NET Application” on page 2-16
- “Create a Generic COM Component with MATLAB Code” on page 2-24
- “Generate Java Package and Build Java Application” on page 2-30
- “Generate a Python Package and Build a Python Application” on page 2-37

## Install and Configure MATLAB Runtime

**Supported Platforms:** Windows, Linux®, macOS

MATLAB Runtime contains the libraries needed to run MATLAB applications on a target system without a licensed copy of MATLAB.

### Download MATLAB Runtime Installer

Download MATLAB Runtime using one of the following options:

- Download the MATLAB Runtime installer at the latest update level for the selected release from the website at <https://www.mathworks.com/products/compiler/matlab-runtime.html>. This option is best for end users who want to run deployed applications.
- Use the MATLAB function `compiler.runtime.download` to download the MATLAB Runtime installer matching the version and update level of MATLAB from where the command is executed. If the installer has already been downloaded to the machine, it returns the path to the MATLAB Runtime installer. If the machine is offline, it returns a URL to the MATLAB Runtime installer. This option is best for developers who want to create application installers that contain MATLAB Runtime.

### Install MATLAB Runtime Interactively

To install MATLAB Runtime:

- 1 Extract the archive containing the MATLAB Runtime installer.

Platform	Steps
Windows	Unzip the MATLAB Runtime installer.  Right-click the ZIP file <code>MATLAB_Runtime_R2021b_win64.zip</code> and select <b>Extract All</b> .
Linux	Unzip the MATLAB Runtime installer at the terminal using the <code>unzip</code> command.  For example, if you are unzipping the R2021b MATLAB Runtime installer, at the terminal, type:  <code>unzip MATLAB_Runtime_R2021b_glnxa64.zip</code>
macOS	Unzip the MATLAB Runtime installer at the terminal using the <code>unzip</code> command.  For example, if you are unzipping the R2021b MATLAB Runtime installer, at the terminal, type:  <code>unzip MATLAB_Runtime_R2021b_maci64.zip</code>

---

**Note** The release part of the installer file name (`_R2021b_`) changes from one release to the next.

- 2 Start the MATLAB Runtime installer.

Platform	Steps
Windows	Double-click the file <code>setup.exe</code> from the extracted files to start the installer.
Linux	At the terminal, type:  <pre>sudo -H ./install</pre> <p><b>Note</b> The <code>-H</code> option sets the <code>HOME</code> environment variable to the home directory of the root user and should be used for graphical applications such as installers.</p>
macOS	At the terminal, type:  <pre>./install</pre> <p><b>Note</b> You may need to enter an administrator user name and password after you run <code>./install</code>.</p>

**Note** If you are running the MATLAB Runtime installer on a shared folder, be aware that other users of the share may need to alter their system configuration.

- 3 When the MATLAB Runtime installer starts, it displays a dialog box. Read the information and then click **Next** to proceed with the installation.
- 4 In the **Folder Selection** dialog box, specify the folder in which you want to install MATLAB Runtime.

**Note** You can have multiple versions of MATLAB Runtime on your computer, but only one installation for any particular version. If you already have an existing installation, the MATLAB Runtime installer does not display the **Folder Selection** dialog box because it overwrites the existing installation in the same folder.

- 5 Confirm your choices and click **Next**.

The MATLAB Runtime installer starts copying files into the installation folder.

- 6 On Linux and macOS platforms, after copying files to your disk, the MATLAB Runtime installer displays the **Product Configuration Notes** dialog box. This dialog box contains information necessary for setting your path environment variables. Copy the path information from this dialog box, save it to a text file, and then click **Next**. For information on setting environment variables, see “Set MATLAB Runtime Path for Deployment”.
- 7 Click **Finish** to exit the installer.

The default MATLAB Runtime installation directory for **R2021b** is specified in the following table:

Operating System	MATLAB Runtime Installation Directory
Windows	C:\Program Files\MATLAB\MATLAB Runtime\v911
Linux	/usr/local/MATLAB/MATLAB_Runtime/v911
macOS	/Applications/MATLAB/MATLAB_Runtime/v911

## Install MATLAB Runtime Noninteractively

To install MATLAB Runtime without having to interact with the installer dialog boxes, use one of these noninteractive modes:

- Silent — The installer runs as a background task and does not display any dialog boxes.
- Automated — The installer displays the dialog boxes but does not wait for user interaction.

When run in silent or automated mode, the MATLAB Runtime installer uses default values for installation options. You can override these values by using MATLAB Runtime installer command-line options or an installer control file.

---

**Note** When running in silent or automated mode, the installer overwrites the installation location.

---

### Run Installer in Silent Mode

To install MATLAB Runtime in silent mode:

- 1** Extract the contents of the MATLAB Runtime installer archive to a temporary folder.
- 2** In your system command prompt, navigate to the folder where you extracted the installer.
- 3** Run the MATLAB Runtime installer, specifying the `-mode silent` and `-agreeToLicense yes` options on the command line.

---

**Note** On most platforms, the installer is located at the root of the folder into which the archive was extracted. On 64-bit Windows, the installer is located in the archive `bin` folder.

---

Platform	Command
Windows	<code>setup -mode silent -agreeToLicense yes</code>
Linux	<code>./install -mode silent -agreeToLicense yes</code>
macOS	<code>./install -mode silent -agreeToLicense yes</code>

---

**Note** If you do not include the `-agreeToLicense yes` option, the installer does not install MATLAB Runtime.

---

- 4** View a log of the installation.

On Windows systems, the MATLAB Runtime installer creates a log file named `mathworks_username.log`, where `username` is your Windows login name, in the location defined by your `TEMP` environment variable.

- 5** On Linux and macOS systems, the MATLAB Runtime installer displays the log information at the command prompt and also saves it to a file if you use the `-outputFile` option.

## Customize a Noninteractive Installation

When run in one of the noninteractive modes, the installer uses the default values unless you specify otherwise. Like the MATLAB installer, the MATLAB Runtime installer accepts a number of command-line options that modify the default installation properties.

Option	Description
-destinationFolder	Specifies where MATLAB Runtime is installed.
-outputFile	Specifies where the installation log file is written.
-tmpdir	Specifies where temporary files are stored during installation.  <b>Caution</b> The installer deletes everything inside the specified folder.
-automatedModeTimeout	Specifies how long, in milliseconds, that each dialog box is displayed when run in automatic mode.
-inputFile	Specifies an installer control file that contains your command-line options and values. Omit the dashes and put each option and value pair on a separate line.

**Note** The MATLAB installer archive includes an example installer control file called `installer_input.txt`. This file contains all of the options available for a full MATLAB installation. The options listed in this section are valid for the MATLAB Runtime installer.

## Install MATLAB Runtime without Administrator Rights

To install MATLAB Runtime as a user without administrator rights on Windows:

- 1 Use the MATLAB Runtime installer to install it on a Windows machine where you have administrator rights.
- 2 Copy the folder where MATLAB Runtime was installed to the machine without administrator rights. You can compress the folder into a zip file for distribution.
- 3 On the machine without administrator rights, add the `<MATLAB_RUNTIME_INSTALL_DIR>\runtime\arch` directory to the user's PATH environment variable. For more information, see "Set MATLAB Runtime Path for Deployment".

## Install Multiple MATLAB Runtime Versions on Single Machine

MCRInstaller supports the installation of multiple versions of MATLAB Runtime on a target machine. This capability allows applications compiled with different versions of MATLAB Runtime to execute side by side on the same machine.

If you do not want multiple MATLAB Runtime versions on the target machine, you can remove the unwanted ones. On Windows, run **Add or Remove Programs** from the Control Panel to remove a specific version. On Linux, manually delete the unwanted MATLAB Runtime directories. You can remove unwanted versions before or after installation of a more recent version of MATLAB Runtime because versions can be installed or removed in any order.

---

**Note** Installing multiple versions of MATLAB Runtime on the same machine is not supported on macOS.

---

## Install MATLAB and MATLAB Runtime on Same Machine

To test your deployed component on your development machine, you do not need an installation of MATLAB Runtime. The MATLAB installation that you use to compile the component can act as a MATLAB Runtime replacement.

You can, however, install MATLAB Runtime for debugging purposes.

### Modify Path

If you install MATLAB Runtime on a machine that already has MATLAB on it, you must adjust the system library path according to your needs.

To run deployed MATLAB code against MATLAB Runtime rather than MATLAB, ensure that your library path lists the MATLAB Runtime directories before any MATLAB directories.

For information on setting environment variables, see “Set MATLAB Runtime Path for Deployment”.

## Uninstall MATLAB Runtime

The method you use to uninstall MATLAB Runtime from your computer varies depending on your platform.

### Windows

- 1 Start the uninstaller.

From the Windows Start menu, search for the **Add or Remove Programs** control panel, and double-click MATLAB Runtime in the list.

You can also start the MATLAB Runtime uninstaller from the `<MATLAB_RUNTIME_INSTALL_DIR>\uninstall\bin\<arch>` folder, where `<MATLAB_RUNTIME_INSTALL_DIR>` is your MATLAB Runtime installation folder and `<arch>` is an architecture-specific folder, such as `win32` or `win64`.

- 2 Select MATLAB Runtime from the list of products in the Uninstall Products dialog box and click **Next**.
- 3 Click **Finish**.

### Linux

- 1 Close all instances of MATLAB and MATLAB Runtime.
- 2 Enter this command at the Linux terminal:

```
rm -rf <MATLAB_RUNTIME_INSTALL_DIR>
```

---

**Caution** Be careful when using the `rm` command, as deleted files cannot be recovered.

---



**macOS**

- 1 Close all instances of MATLAB and MATLAB Runtime.
- 2 Navigate to your MATLAB Runtime installation folder. For example, the installation folder might be named `MATLAB_Compiler_Runtime.app` in your Applications folder.
- 3 Drag your MATLAB Runtime installation folder to the trash, and then select **Empty Trash** from the Finder menu.

**See Also**

`compiler.runtime.download`

**More About**

- [About MATLAB Runtime](#)
- [“MATLAB Runtime Startup Options”](#)
- [“Set MATLAB Runtime Path for Deployment”](#)



# Examples

---

- “Create a C Shared Library with MATLAB Code” on page 2-2
- “Generate a C++ mxArray API Shared Library and Build a C++ Application” on page 2-6
- “Generate a C++ MATLAB Data API Shared Library and Build a C++ Application” on page 2-11
- “Generate .NET Assembly and Build .NET Application” on page 2-16
- “Create a Generic COM Component with MATLAB Code” on page 2-24
- “Generate Java Package and Build Java Application” on page 2-30
- “Generate a Python Package and Build a Python Application” on page 2-37

## Create a C Shared Library with MATLAB Code

**Supported platform:** Windows, Linux, Mac

This example shows how to create a C shared library using a MATLAB function. You can then pass the generated package to the developer who is responsible for integrating it into an application. The target system does not require a licensed copy of MATLAB.

### Create Functions in MATLAB

In MATLAB, examine the MATLAB code that you want packaged. For this example, open `addmatrix.m`, `multiplymatrix.m`, and `eigmatrix.m` located in `matlabroot\extern\examples\compilersdk\c_cpp\matrix`.

#### `addmatrix.m`

```
function a = addmatrix(a1, a2)
```

```
a = a1 + a2;
```

At the MATLAB command prompt, enter `addmatrix([1 4 7; 2 5 8; 3 6 9], [1 4 7; 2 5 8; 3 6 9])`.

The output is:

```
ans =  
    2     8    14  
    4    10    16  
    6    12    18
```

#### `multiplymatrix.m`

```
function m = multiplymatrix(a1, a2)
```

```
m = a1*a2;
```

At the MATLAB command prompt, enter `multiplymatrix([1 4 7; 2 5 8; 3 6 9], [1 4 7; 2 5 8; 3 6 9])`.

The output is:

```
ans =  
    30    66   102  
    36    81   126  
    42    96   150
```

#### `eigmatrix.m`

```
function e = eigmatrix(a1)
```

```
    try
```

```
        %Tries to calculate the eigenvalues and return them.  
        e = eig(a1);
```

```
    catch
```

```
        %Returns a -1 on error.  
        e = -1;
```

```
end
```


At the MATLAB command prompt, enter `eigmatrix([1 4 7; 2 5 8; 3 6 9])`.

The output is:


```
ans =
    16.1168
    -1.1168
    -0.0000
```

## Create a C Shared Library Using the Library Compiler App

- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Library Compiler**. In the **MATLAB Compiler** project window, click **C Shared Library**.



Alternately, you can open the **Library Compiler** app by entering `libraryCompiler` at the MATLAB prompt.

- 2 In the **Library Compiler** app project window, specify the files of the MATLAB application that you want to deploy.
  - a In the **Exported Functions** section of the toolstrip, click .
  - b In the **Add Files** window, browse to the example folder, and select the function you want to package. Click **Open**.

The function is added to the list of exported function files. Repeat this step to package multiple files in the same application.

Add all three functions to the list of main files.

- 3 In the **Packaging Options** section of the toolstrip, decide whether to include the MATLAB Runtime installer in the generated application by selecting one of the options:
  - **Runtime downloaded from web** — Generate an installer that downloads the MATLAB Runtime and installs it along with the deployed MATLAB application. You can specify the file name of the installer.
  - **Runtime included in package** — Generate an application that includes the MATLAB Runtime installer. You can specify the file name of the installer.

---

**Note** The first time you select this option, you are prompted to download the MATLAB Runtime installer.

---


- 4 In the **Library Name** field, rename the packaged shared library as `libmatrix`. The same name is followed through in the implementation of the shared library.

## Customize the Application and Its Appearance

In the **Library Compiler** app, you can customize the installer, customize your application, and add more information about the application.

- **Library information** — Information about the deployed application. You can also customize the appearance of the application by changing the application icon and splash screen. The generated installer uses this information to populate the installed application metadata. See “Customize the Installer” on page 3-2.
- **Additional installer options** — Default installation path for the generated installer and custom logo selection. See “Change the Installation Path” on page 3-3.
- **Files required for your library to run** — Additional files required by the generated application to run. These files are included in the generated application installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed for your end user** — Files that are installed with your application.

See “Specify Files to Install with Application” on page 3-6.



## Package the Application

When you are finished selecting your packaging options, save your **Library Compiler** project and generate the packaged application.

**1** Click **Package**.

In the Save Project dialog box, specify the location to save the project.

**2** In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the packaging process is complete, examine the generated output in the target folder.

- Three folders are generated: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

For more information about the files generated in these folders, see “Files Generated After Packaging MATLAB Functions” on page 1-10.

- The log file `PackagingLog.html` contains packaging results.

## See Also

`libraryCompiler` | `mcc` | `deploytool`

## Related Examples

- “Create C/C++ Shared Libraries from Command Line”
- “Implement a C Shared Library with a Driver Application”

## Generate a C++ mxArray API Shared Library and Build a C++ Application

**Supported platform:** Windows, Linux, Mac

This example shows how to create a C++ shared library from a MATLAB function. You can integrate the generated library into a C++ application. This example also shows how to call the C++ shared library from a C++ application. The target system does not require a licensed copy of MATLAB.

### Create Functions in MATLAB

In MATLAB, examine the MATLAB code that you want packaged. For this example, open `addmatrix.m` located in `matlabroot\extern\examples\compilersdk\c_cpp\matrix`.

**addmatrix.m**

```
function a = addmatrix(a1, a2)

a = a1 + a2;
```

At the MATLAB command prompt, enter:

```
addmatrix([1 4 7; 2 5 8; 3 6 9], [1 4 7; 2 5 8; 3 6 9])
```

The output is:

```
ans =
     2     8    14
     4    10    16
     6    12    18
```

### Create a C++ Shared Library Using the Library Compiler App


- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Library Compiler**.

Alternatively, you can open the **Library Compiler** app from the MATLAB command prompt by entering:

```
libraryCompiler
```

- 2 In the **Type** section of the toolbar, click **C++ Shared Library**.

In the **Library Compiler** app project window, specify the files of the MATLAB application that you want to deploy.

- a In the **Exported Functions** section of the toolbar, click .
- b In the **Add Files** window, browse to the example folder, and select the function you want to package. Click **Open**.

The function is added to the list of exported function files. Repeat this step to package multiple files in the same application.



For this example, navigate to `matlabroot\extern\examples\compilersdk\c_cpp\matrix` and select `addmatrix.m`.

- 3 In the **Packaging Options** section of the toolstrip, decide whether to include the MATLAB Runtime installer in the generated application by selecting one of the options:

- **Runtime downloaded from web** — Generate an installer that downloads the MATLAB Runtime and installs it along with the deployed MATLAB application. You can specify the file name of the installer.
- **Runtime included in package** — Generate an application that includes the MATLAB Runtime installer. You can specify the file name of the installer.

---

**Note** The first time you select this option, you are prompted to download the MATLAB Runtime installer.

---

### Specify Shared Library Settings

- 1 The **Library Name** field is automatically populated with `addmatrix` as the name of the packaged shared library. Rename it as `libmatrix`. The same name is followed through in the implementation of the shared library.
- 2 Add MATLAB files to generate the sample C++ driver files. Although C++ driver files are not necessary to create shared libraries, they are used to demonstrate how to “Implement the C++ mxArray API Shared Library with a Driver Application” on page 2-9.

In the **Samples** section, select **Create New Sample**, and click `addmatrix.m`. A MATLAB file opens for you to edit. Define the input variables as necessary for your application, save the file, and return to the **Library Compiler** app. For more information and limitations, see “Sample Driver File Creation” on page 3-5.

- 3 Edit the MATLAB file that opens with the following values:

```
% Sample script to demonstrate execution of function a = addmatrix(a1, a2)
a1 = [1 4 7; 2 5 8; 3 6 9]; % Initialize a1 here
a2 = a1; % Initialize a2 here
a = addmatrix(a1, a2);
```

Save the file, and return to the **Library Compiler** app. For more information and limitations, see “Sample Driver File Creation” on page 3-5.

- 4 Select the type of API for the generated C++ shared libraries. In the **API selection** section at the bottom, select **Create interface that uses the mxArray API**. For more information, see “API Selection for C++ Shared Library” on page 3-7.

### Customize the Application and Its Appearance

In the **Library Compiler** app, you can customize the installer, customize your application, and add more information about the application.

- **Library information** — Information about the deployed application. You can also customize the appearance of the application by changing the application icon and splash screen. The generated installer uses this information to populate the installed application metadata. See “Customize the Installer” on page 3-2.
- **Additional installer options** — Default installation path for the generated installer and custom logo selection. See “Change the Installation Path” on page 3-3.

- **Files required for your library to run** — Additional files required by the generated application to run. These files are included in the generated application installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed for your end user** — Files that are installed with your application.

See “Specify Files to Install with Application” on page 3-6.

### Package the Application

When you are finished selecting your packaging options, save your **Library Compiler** project and generate the packaged application.

- 1 Click **Package**.

In the Save Project dialog box, specify the location to save the project.

- 2 In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the packaging process is complete, examine the generated output in the target folder.

- Three folders are generated: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

For more information about the files generated in these folders, see “Files Generated After Packaging MATLAB Functions” on page 1-10.

- The log file `PackagingLog.html` contains packaging results.

## Create a C++ Shared Library Using `compiler.build.cppSharedLibrary`

---

**Note** If you have already created a standalone application using the **Library Compiler** app, you can skip this section. However, if you want to know how to create a C++ shared library from the MATLAB command window using a programmatic approach, follow these instructions.

---

- 1 Save the path to the `addmatrix.m` file located in `matlabroot\extern\examples\compilersdk\c_cpp\matrix`.

```
appFile = fullfile(matlabroot,'extern','examples','compilersdk','c_cpp','matrix','addmatrix.m');
```

- 2 Save the following code in a sample file named `addmatrixSample1.m`:

```
a1 = [1 4 7; 2 5 8; 3 6 9];  
a2 = a1;  
a = addmatrix(a1, a2);
```

- 3 Additional options can be specified in the `compiler.build` command by using one or more of the following name-value arguments.

- `'AdditionalFiles'` — Path to additional files to include in the shared library.
- `'AutoDetectDataFiles'` — Flag to automatically include data files.
- `'DebugBuild'` — Flag to enable debug symbols.
- `'Interface'` — Interface API, specified as `'matlab-data'` (default) or `'mwstring'`. For more information, see “API Selection for C++ Shared Library” on page 3-7.
- `'LibraryName'` — Name of the generated library.

- 'OutputDir' — Path to the output directory that contains generated files.
  - 'SampleGenerationFiles' — MATLAB sample files used to generate sample C++ library files. For more information, see “Sample Driver File Creation” on page 3-5.
  - 'Verbose' — Flag to display progress information indicating compiler output during the build process.
- 4 Build the C++ shared library using the `compiler.build.cppSharedLibrary` function. Use name-value arguments to add a sample file and specify the library name and interface API.

```
buildResults = compiler.build.cppSharedLibrary(appFile,...
'LibraryName','libmatrix',...
'Interface','mvarray',...
'SampleGenerationFiles','addmatrixSample1.m');
```

The `compiler.build.Results` object `buildResults` contains information on the build type, generated files, and build options.

- 5 The function generates the following within a folder named `libmatrixcppSharedLibrary` in your current working directory:
- `samples\addmatrixSample1_mvarray.cpp` — C++ sample driver file.
  - `GettingStarted.html` — HTML file that contains information on integrating your shared library.
  - `libmatrix.cpp` — C++ source code file.
  - `libmatrix.def` — Module-definition file that provides the linker with module information.
  - `libmatrix.dll` — Dynamic-link library file.
  - `libmatrix.exports` — Exports file that contains all nonstatic function names.
  - `libmatrix.h` — C++ header file.
  - `libmatrix.lib` — Import library file.
  - `mccExcludedFiles.log` — Log file that contains a list of any toolbox functions that were not included in the application. For information on non-supported functions, see MATLAB Compiler Limitations.
  - `readme.txt` — Text file that contains packaging information.
  - `requiredMCRProducts.txt` — Text file that contains product IDs of products required by MATLAB Runtime to run the application.
  - `unresolvedSymbols.txt` — Text file that contains information on unresolved symbols.

---

**Note** The generated library does not include MATLAB Runtime or an installer. To create an installer using the `buildResults` object, see `compiler.package.installer`.

---

## Implement the C++ mxArray API Shared Library with a Driver Application

After packaging your C++ shared libraries, you can call them from a C++ application. The C++ application that you create uses the sample C++ driver code generated during packaging. The C++ driver code calls the C++ shared libraries, and it is based on the sample MATLAB file you selected in previous setup steps.

These steps are also explained in the `GettingStarted.html` file in `for_redistribution_files_only` folder. Before starting, make sure that you “Install and Configure MATLAB Runtime”, and that you have a C++ compiler installed.

- 1 Copy and paste the generated C++ driver code file `addmatrixSample1_mwarray.cpp` from the `for_redistribution_files_only\samples` folder into the `for_redistribution_files_only` folder created when you created the shared library.
- 2 Use the system command line to navigate to the `for_redistribution_files_only` folder where you copied the generated sample C++ driver code file.
- 3 Compile and link the application using `mbuild` at the system command prompt.  

```
mbuild addmatrixSample1_mwarray.cpp libmatrix.lib
```
- 4 From the system command prompt, run the application. If you used sample MATLAB code in the packaging steps, this application should return the same output as the MATLAB code.

```
addmatrixSample1_mwarray.exe
```

```
2 8 14  
4 10 16  
6 12 18
```

### See Also

`libraryCompiler` | `mcc` | `deploytool`

### Related Examples

- “Generate a C++ MATLAB Data API Shared Library and Build a C++ Application” on page 2-11

# Generate a C++ MATLAB Data API Shared Library and Build a C++ Application

**Supported platform:** Windows, Linux, Mac

This example shows how to create a C++ shared library from a MATLAB function. You can integrate the generated library into a C++ application. This example also shows how to call the C++ shared library from a C++ application. The target system does not require a licensed copy of MATLAB to run the application.

## Create Functions in MATLAB

In MATLAB, examine the MATLAB code that you want packaged. For this example, open `addmatrix.m` located in `matlabroot\extern\examples\compilersdk\c_cpp\matrix`.

**addmatrix.m**

```
function a = addmatrix(a1, a2)
```

```
a = a1 + a2;
```

At the MATLAB command prompt, enter:

```
addmatrix([1 4 7; 2 5 8; 3 6 9], [1 4 7; 2 5 8; 3 6 9])
```

The output is:

```
ans =
     2     8    14
     4    10    16
     6    12    18
```

## Create a C++ Shared Library Using Library Compiler App


- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Library Compiler**.

Alternatively, you can open the **Library Compiler** app from the MATLAB command prompt by entering:

```
libraryCompiler
```

- 2 In the **Type** section of the toolstrip, click **C++ Shared Library**.

In the **Library Compiler** app project window, specify the files of the MATLAB application that you want to deploy.

- a In the **Exported Functions** section of the toolstrip, click .
- b In the **Add Files** window, browse to the example folder, and select the function you want to package. Click **Open**.

The function is added to the list of exported function files. Repeat this step to package multiple files in the same application.

For this example, navigate to `matlabroot\extern\examples\compilersdk\c_cpp\matrix` and select `addmatrix.m`.

- 3 In the **Packaging Options** section of the toolstrip, decide whether to include the MATLAB Runtime installer in the generated application by selecting one of the options:
  - **Runtime downloaded from web** — Generate an installer that downloads the MATLAB Runtime and installs it along with the deployed MATLAB application. You can specify the file name of the installer.
  - **Runtime included in package** — Generate an application that includes the MATLAB Runtime installer. You can specify the file name of the installer.

---

**Note** The first time you select this option, you are prompted to download the MATLAB Runtime installer.

---

### Specify Shared Library Settings

- 1 The **Library Name** field is automatically populated with `addmatrix` as the name of the packaged shared library. Rename it as `libmatrix`. The same name is followed through in the implementation of the shared library.
- 2 In the **Samples** section, select **Create New Sample**, and click `addmatrix.m`.

In the MATLAB file that opens, edit the code to initialize `a1` to a nonzero value:

```
a1 = [1 4 7; 2 5 8; 3 6 9]; % Initialize a1 here
a2 = a1; % Initialize a2 here
a = addmatrix(a1, a2);
```

Save the file and return to the **Library Compiler** app. For more information and limitations, see “Sample Driver File Creation” on page 3-5.

- 3 Select the type of API for the generated C++ shared libraries. In the **API selection** section at the bottom, select **Create interface that uses the MATLAB Data API**. For more information, see “API Selection for C++ Shared Library” on page 3-7.

### Customize the Application and Its Appearance

In the **Library Compiler** app, you can customize the installer, customize your application, and add more information about the application.

- **Library information** — Information about the deployed application. You can also customize the appearance of the application by changing the application icon and splash screen. The generated installer uses this information to populate the installed application metadata. See “Customize the Installer” on page 3-2.
- **Additional installer options** — Default installation path for the generated installer and custom logo selection. See “Change the Installation Path” on page 3-3.
- **Files required for your library to run** — Additional files required by the generated application to run. These files are included in the generated application installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed for your end user** — Files that are installed with your application.

See “Specify Files to Install with Application” on page 3-6.

## Package the Application

When you are finished selecting your packaging options, save your **Library Compiler** project and generate the packaged application.

**1** Click **Package**.

In the Save Project dialog box, specify the location to save the project.

**2** In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the packaging process is complete, examine the generated output in the target folder.

- Three folders are generated: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

For more information about the files generated in these folders, see “Files Generated After Packaging MATLAB Functions” on page 1-10.

- The log file `PackagingLog.html` contains packaging results.

## Create a C++ Shared Library Using `compiler.build.cppSharedLibrary`

---

**Note** If you have already created a C++ shared library using the **Library Compiler** app, you can skip this section. However, if you want to know how to create a C++ shared library from the MATLAB command window using a programmatic approach, follow these instructions.

---

**1** Save the path to the `addmatrix.m` file located in `matlabroot\extern\examples\compilersdk\c_cpp\matrix`.

```
appFile = fullfile(matlabroot,'extern','examples','compilersdk','c_cpp','matrix','addmatrix.m');
```

**2** Save the following code in a sample file named `addmatrixSample1.m`:

```
a1 = [1 4 7; 2 5 8; 3 6 9];
a2 = a1;
a = addmatrix(a1, a2);
```

**3** Additional options can be specified in the `compiler.build` command by using one or more of the following name-value arguments.

- `'AdditionalFiles'` — Path to additional files to include in the shared library.
- `'AutoDetectDataFiles'` — Flag to automatically include data files.
- `'DebugBuild'` — Flag to enable debug symbols.
- `'Interface'` — Interface API, specified as `'matlab-data'` (default) or `'mwstring'`. For more information, see “API Selection for C++ Shared Library” on page 3-7.
- `'LibraryName'` — Name of the generated library.
- `'OutputDir'` — Path to the output directory that contains generated files.
- `'SampleGenerationFiles'` — MATLAB sample files used to generate sample C++ library files. For more information, see “Sample Driver File Creation” on page 3-5.
- `'Verbose'` — Flag to display progress information indicating compiler output during the build process.

**4** Build the C++ shared library using the `compiler.build.cppSharedLibrary` function. Use name-value arguments to add a sample file and specify the library name.

```
buildResults = compiler.build.cppSharedLibrary(appFile,...  
'LibraryName','libmatrix',...  
'SampleGenerationFiles','addmatrixSample1.m');
```

The `compiler.build.Results` object `buildResults` contains information on the build type, generated files, and build options.

**5** This syntax generates the following files within a folder named `libmatrixcppSharedLibrary` in your current working directory:

- `samples\addmatrixSample1_mda.cpp` — C++ sample driver file.
- `v2\generic_interface\libmatrix.ctf` — Component technology file that contains the deployable archive.
- `v2\generic_interface\readme.txt` — Text file that contains packaging information.
- `GettingStarted.html` — HTML file that contains information on integrating your shared library.
- `mccExcludedFiles.log` — Log file that contains a list of any toolbox functions that were not included in the application. For information on non-supported functions, see MATLAB Compiler Limitations.
- `readme.txt` — Text file that contains packaging and interface information.
- `requiredMCRProducts.txt` — Text file that contains product IDs of products required by MATLAB Runtime to run the application.
- `unresolvedSymbols.txt` — Text file that contains information on unresolved symbols.

---

**Note** The generated library does not include MATLAB Runtime or an installer. To create an installer using the `buildResults` object, see `compiler.package.installer`.

---

## Implement the C++ MATLAB Data API Shared Library with a Driver Application

After packaging your C++ shared libraries, you can call them from a C++ application. The C++ application that you create uses the sample C++ driver code generated during packaging. The C++ driver code calls the C++ shared libraries, and it is based on the sample MATLAB file you selected in previous setup steps.

These steps are also explained in the `GettingStarted.html` file. Before starting, make sure that you “Install and Configure MATLAB Runtime”, and that you have a C++ compiler installed.

- 1** Copy and paste the generated C++ driver code file `addmatrixSample1_mda.cpp` from the `samples` folder into the `v2\generic_interface` folder created when you created the shared library.
- 2** Use the system command line to navigate to the `generic_interface` folder where you copied the sample C++ driver code file.
- 3** Compile and link the application using `mbuild` at the system command prompt.

```
mbuild addmatrixSample1_mda.cpp
```

- 4** Run the application from the system command prompt.

```
addmatrixSample1_mda.exe
```



---

**Note** For information on how to retrieve a struct array, a cell array, or a character vector from an `feval` call, see the files `subtractmatrix.m` and `subtractmatrix_mda.cpp` in `matlabroot\extern\examples\compilersdk\c_cpp\matrix`.

---

## See Also

`libraryCompiler` | `compiler.build.cppSharedLibrary` | `mcc` | `deploytool`

## Related Examples

- “Generate a C++ mxArray API Shared Library and Build a C++ Application” on page 2-6

## Generate .NET Assembly and Build .NET Application

**Supported platform:** Windows

This example shows how to create a .NET assembly from a MATLAB function and integrate the generated assembly into a .NET application.

### Prerequisites

- Verify that you have met all of the MATLAB Compiler SDK .NET target requirements. For details, see “MATLAB Compiler SDK .NET Target Requirements”.
- Verify that you have Microsoft Visual Studio installed.
- End users must have an installation of MATLAB Runtime to run the application. For details, see “Install and Configure MATLAB Runtime”.

For testing purposes, you can use an installation of MATLAB instead of MATLAB Runtime.

### Files

<b>MATLAB Function</b>	<code>matlabroot\toolbox\dotnetbuilder\Examples\VSVersion\NET\MagicSquareExample\MagicSquareComp\makesquare.m</code>
<b>MWArray API Reference</b>	<code>matlabroot\help\dotnetbuilder\MWArrayAPI</code>

### Create Function in MATLAB

In MATLAB, examine the MATLAB code that you want to package. For this example, open `makesquare.m`.

```
function y = makesquare(x)
y = magic(x);
disp(y)
```

At the MATLAB command prompt, enter `makesquare(5)`.

The output is a 5-by-5 matrix.

```
17    24     1     8    15
23     5     7    14    16
 4     6    13    20    22
10    12    19    21     3
11    18    25     2     9
```


### Create .NET Assembly Using Library Compiler App

Package the function into a .NET assembly using the **Library Compiler** app. Alternatively, if you want to create a .NET assembly from the MATLAB command window using a programmatic approach, see “Create .NET Assembly Using `compiler.build.dotNETAssembly`” on page 2-20.

- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Library Compiler**.


Alternatively, you can open the **Library Compiler** app from the MATLAB command prompt.

```
libraryCompiler
```



- 2 In the **Type** section of the toolbar, click **.NET Assembly**.

In the **Library Compiler** app project window, specify the files of the MATLAB application that you want to deploy.

- a In the **Exported Functions** section of the toolbar, click .
- b In the **Add Files** window, browse to the example folder, and select the function you want to package. Click **Open**.

The function is added to the list of exported function files. Repeat this step to package multiple files in the same application.

For this example, select the file `makesquare.m`.

- 3 In the **Packaging Options** section of the toolbar, decide whether to include the MATLAB Runtime installer in the generated application by selecting one of the options:
  - **Runtime downloaded from web** — Generate an installer that downloads the MATLAB Runtime and installs it along with the deployed MATLAB application. You can specify the file name of the installer.
  - **Runtime included in package** — Generate an application that includes the MATLAB Runtime installer. You can specify the file name of the installer.

---

**Note** The first time you select this option, you are prompted to download the MATLAB Runtime installer.

---

### Specify Assembly File Settings

Next, define the name of your assembly and verify the class mapping for the `.m` file that you are building into your application.

- 1 The **Library Name** field is automatically populated with `makesquare` as the name of the assembly. Rename it as `MagicSquareComp`. The same name is followed through in the implementation of the assembly.
- 2 Verify that the function defined in `makesquare.m` is mapped into `MagicSquareClass`. Double-click on the class to change the class name.

### Create Sample Driver File

You can use any MATLAB file in the project to generate sample .NET driver files. Although .NET driver files are not necessary to create an assembly, you can use them to implement the generated assembly into a .NET application in the target language, as shown in “Integrate .NET Assembly Into .NET Application” on page 2-21.

In the **Samples** section, select **Create New Sample**, and click `makesquare.m`. A MATLAB file opens for you to edit.

```
% Sample script to demonstrate execution of function y = makesquare(x)
x = 0; % Initialize x here
y = makesquare(x);
```

Change `x = 0` to `x = 5`, save the file, and return to the **Library Compiler** app.

For more information and limitations, see “Sample Driver File Creation” on page 3-5.

### Customize Application and Its Appearance

In the **Library Compiler** app, you can customize the installer, customize your application, and add more information about the application.

- **Library information** — Information about the deployed application. You can also customize the appearance of the application by changing the application icon and splash screen. The generated installer uses this information to populate the installed application metadata. See “Customize the Installer” on page 3-2.
- **Additional installer options** — Default installation path for the generated installer and custom logo selection. See “Change the Installation Path” on page 3-3.
- **Files required for your library to run** — Additional files required by the generated application to run. These files are included in the generated application installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed for your end user** — Files that are installed with your application.

See “Specify Files to Install with Application” on page 3-6.

- **Additional runtime settings** — Platform-specific options for controlling the generated executable. See “Additional Runtime Settings” on page 3-6.

**Library information**

MagicSquareComp 1.0

Author Name

Email

Company

Summary

Description

Set as default contact

Select custom splash screen

Namespace

Class Name	Method Name
MagicSquareClass	[y] = makesquare (x)

Add Class

**Samples**

Add MATLAB files that demonstrate how to execute the exported functions. These files will be used to generate sample driver files in the target language.

makesquareSampl...

Create New Sample Add Existing Sample

**Additional installer options**

Files required for your library to run

Files installed for your end user

MagicSquareCom... MagicSquareCom... MagicSquareCom...

Additional runtime settings

## Package the Application

When you are finished selecting your packaging options, save your **Library Compiler** project and generate the packaged application.

### 1 Click **Package**.

In the Save Project dialog box, specify the location to save the project.

- 2 In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the packaging process is complete, examine the generated output in the target folder:

- Three folders are generated: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

For more information about the files generated in these folders, see “Files Generated After Packaging MATLAB Functions” on page 1-10.

- The log file `PackagingLog.html` contains packaging results.

## Create .NET Assembly Using `compiler.build.dotNETAssembly`

As an alternative to the **Library Compiler** app, you can create a .NET assembly using a programmatic approach. If you have already created an assembly using the **Library Compiler**, see “Integrate .NET Assembly Into .NET Application” on page 2-21.

- 1 Save the path to the file `makesquare.m` located in `matlabroot\toolbox\dotnetbuilder\Examples\VSVersion\NET\MagicSquareExample\MagicSquareComp`. For example, if you are using Visual Studio version 15, type:

```
appFile = fullfile(matlabroot,'toolbox','dotnetbuilder','Examples', ...
    'VS15','NET','MagicSquareExample','MagicSquareComp','makesquare.m');
```

- 2 Save the following code in a sample file named `makesquareSample1.m`:

```
x = 5;
y = makesquare(x);
```

- 3 Build the .NET assembly using the `compiler.build.dotNETAssembly` function. Use name-value arguments to specify the assembly name, class name, and sample file.

```
buildResults = compiler.build.dotNETAssembly(appFile, ...
    'AssemblyName','MagicSquareComp', ...
    'ClassName','MagicSquareClass', ...
    'SampleGenerationFiles','makesquareSample1.m');
```

The `compiler.build.Results` object `buildResults` contains information on the build type, generated files, and build options.

The function generates the following files within a folder named `MagicSquareCompdotNETAssembly` in your current working directory:

- `samples\makesquareSample1.cs` — .NET sample driver file.
- `GettingStarted.html` — HTML file that contains steps on compiling .NET driver applications from the command line.
- `MagicSquareComp.dll` — Dynamic-link library file that can be accessed using the `mwArray` API.
- `MagicSquareComp.xml` — XML file that contains documentation for the `mwArray` assembly.
- `MagicSquareComp_overview.html` — HTML file that contains requirements for accessing the assembly and for generating arguments using the `mwArray` class hierarchy.
- `MagicSquareCompNative.dll` — Dynamic-link library file that can be accessed using the native API.
- `MagicSquareCompNative.xml` — XML file that contains documentation for the native assembly.

- `MagicSquareCompVersion.cs` — C# file that contains version information.
- `mccExcludedFiles.log` — Log file that contains a list of any toolbox functions that were not included in the application. For information on non-supported functions, see MATLAB Compiler Limitations.
- `readme.txt` — Text file that contains packaging and interface information.
- `requiredMCRProducts.txt` — Text file that contains product IDs of products required by MATLAB Runtime to run the application.
- `unresolvedSymbols.txt` — Text file that contains information on unresolved symbols.

---

**Note** The generated assembly does not include MATLAB Runtime or an installer. To create an installer using the `buildResults` object, see `compiler.package.installer`.

---

You can specify additional options in the `compiler.build` command by using one or more of the following name-value arguments:

- `'AdditionalFiles'` — Path to additional files to include in the assembly.
- `'AssemblyName'` — Name of the generated assembly.
- `'AssemblyVersion'` — Version of the generated assembly.
- `'AutoDetectDataFiles'` — Flag to automatically include data files.
- `'ClassName'` — Name of the .NET class.
- `'DebugBuild'` — Flag to enable debug symbols.
- `'EmbedArchive'` — Flag to embed the assembly archive.
- `'EnableRemoting'` — Flag to control the remoting type.
- `'OutputDir'` — Path to the output directory that contains generated files.
- `'SampleGenerationFiles'` — MATLAB sample files used to generate .NET driver files. For more information, see “Sample Driver File Creation” on page 3-5.
- `'StrongNameKeyFile'` — Path to the encryption key file used to sign the shared assembly.
- `'Verbose'` — Flag to display progress information indicating compiler output during the build process.

## Integrate .NET Assembly Into .NET Application

After creating your .NET assembly, you can integrate it into any .NET application. This example uses the sample .NET application code generated during packaging. You can use this sample .NET application code as a guide to write your own .NET application.

- 1 Open Microsoft Visual Studio and create a C# **Console App (.NET Framework)** called `MainApp`.
- 2 Remove any source code files that were created within your project, if necessary.
- 3 Add the generated sample .NET application code `makesquareSample1.cs` from the `for_redistribution_files_only\samples` folder to the project.

The program listing is shown below.

### **makesquareSample1.cs**

```
using System;
using System.Collections.Generic;
```

```

using System.Text;
using MathWorks.MATLAB.NET.Arrays;
using MathWorks.MATLAB.NET.Utility;
using MagicSquareComp;

/// <summary>
/// Sample driver code that integrates a compiled MATLAB function
/// generated by MATLAB Compiler SDK
///
/// Refer to the MATLAB Compiler SDK documentation for more
/// information.
/// </summary>
class makesquareSample1 {

    static MakeSquareClass makesquareclassInstance;

    static void Setup() {
        makesquareclassInstance = new MakeSquareClass();
    }

    /// <summary>
    /// Example of using the makesquare function.
    /// </summary>
    public static void MakesquareSample() {
        double xInData = 5.0;
        MWNumericArray yOut = null;
        Object[] results = null;
        try {
            MWNumericArray xIn = new MWNumericArray(xInData);
            results = makesquareclassInstance.makesquare(1, xIn);
            if (results[0] is MWNumericArray) {
                yOut = (MWNumericArray) results[0];
            }
            Console.WriteLine(yOut);
        } catch (Exception e) {
            Console.WriteLine(e);
        }
    }

    /// <summary>
    /// The main entry point for the application.
    /// </summary>
    static void Main(string[] args) {
        try {
            Setup();
        } catch (Exception e) {
            Console.WriteLine(e);
            Environment.Exit(1);
        }
        try {
            MakesquareSample();
        } catch (Exception e) {
            Console.WriteLine(e);
            Environment.Exit(1);
        }
    }
}

```

- 4 In Visual Studio, add a reference to your assembly file `MagicSquareComp.dll` located in the folder where you generated or installed the assembly.
- 5 Add a reference to the `MWArray` API.

If MATLAB is installed on your system	<code>matlabroot\toolbox\dotnetbuilder\bin\win64\&lt;framework_version&gt;\MWArray.dll</code>
---------------------------------------	---



If MATLAB Runtime is installed on your system	<MATLAB_RUNTIME_INSTALL_DIR>\toolbox\dotnetbuilder\bin\win64\<framework_version>\MWArray.dll
---	--

- 6 Go to **Build**, then **Configuration Manager**, and change the platform from **Any CPU** to **x64**.
- 7 After you finish adding your code and references, build the application with Visual Studio.

The build process generates an executable named `makesquareSample1.exe`.

- 8 Run the application with Visual Studio, in a command window, or by double-clicking the generated executable.

The application returns the same output as the sample MATLAB code.

```

17    24     1     8    15
23    5     7    14    16
 4     6    13    20    22
10    12    19    21     3
11    18    25     2     9

```

---

**Note** This example shows how to call the .NET assembly from a sample C# application. To call the assembly from a Visual Basic application, use the Microsoft Visual Studio project file `MagicSquareVbApp.vbproj` and Visual Basic file `MagicSquareApp.vb` located in

`matlabroot\toolbox\dotnetbuilder\Examples\VSVersion\NET\MagicSquareExample\MagicSquareVbApp\`

---

## See Also

`libraryCompiler` | `compiler.build.dotNETAssembly` | `mcc` | `deploytool`

## Related Examples

- “Build .NET Core Application That Runs on Linux and macOS”
- “Integrate Simple MATLAB Function Into .NET Application”

## Create a Generic COM Component with MATLAB Code

**Supported platform:** Windows

This example shows how to create a generic COM component using a MATLAB function and integrate it into an application. The target system does not require a licensed copy of MATLAB.

### Prerequisites

- Verify that you have the Windows 10 SDK kit installed. For details, see Windows 10 SDK.
- Verify that you have MinGW-w64 installed. To install it from the MathWorks File Exchange, see MATLAB Support for MinGW-w64 C/C++ Compiler.

To ensure that MATLAB detects the Windows 10 SDK kit and MinGW-w64, use the following command:

```
mbuild -setup -client mbuild_com
```

- Verify that you have Microsoft Visual Studio installed.
- End users must have an installation of MATLAB Runtime to run the application. For details, see “Install and Configure MATLAB Runtime”.

For testing purposes, you can use an installation of MATLAB instead of MATLAB Runtime.

### Create Function in MATLAB

In MATLAB, examine the MATLAB code that you want packaged. For this example, open `makesquare.m` located in `matlabroot\toolbox\dotnetbuilder\Examples\VSVersion\COM\MagicSquareExample\MagicSquareComp`.

```
function y = makesquare(x)
y = magic(x);
```


At the MATLAB command prompt, enter `makesquare(5)`.

```
17    24     1     8    15
23     5     7    14    16
 4     6    13    20    22
10    12    19    21     3
11    18    25     2     9
```


### Create Generic COM Component Using Library Compiler App

Package the function into a COM component using the **Library Compiler** app. Alternatively, if you want to create a COM component from the MATLAB command window using a programmatic approach, see .

- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Library Compiler**. In the **MATLAB Compiler** project window, click **Generic COM Component**.



Alternately, you can open the **Library Compiler** app by entering `libraryCompiler` at the MATLAB prompt.

- 2 In the **Library Compiler** app project window, specify the files of the MATLAB application that you want to deploy.
  - a In the **Exported Functions** section of the toolbar, click .
  - b In the **Add Files** window, browse to the example folder, and select the function you want to package. Click **Open**.

The function is added to the list of exported function files. Repeat this step to package multiple files in the same application.


- 3 In the **Packaging Options** section of the toolbar, decide whether to include the MATLAB Runtime installer in the generated application by selecting one of the options:
  - **Runtime downloaded from web** — Generate an installer that downloads the MATLAB Runtime and installs it along with the deployed MATLAB application. You can specify the file name of the installer.
  - **Runtime included in package** — Generate an application that includes the MATLAB Runtime installer. You can specify the file name of the installer.

---

**Note** The first time you select this option, you are prompted to download the MATLAB Runtime installer.

---

- 4 In the **Library Name** field, replace `makesquare` with `MagicSquareComp`.
- 5 Verify that the function defined in `makesquare.m` is mapped into `Class1`.



## Customize the Application and Its Appearance

In the **Library Compiler** app, you can customize the installer, customize your application, and add more information about the application.

- **Library information** — Information about the deployed application. You can also customize the appearance of the application by changing the application icon and splash screen. The generated

installer uses this information to populate the installed application metadata. See “Customize the Installer” on page 3-2.

- **Additional installer options** — Default installation path for the generated installer and custom logo selection. See “Change the Installation Path” on page 3-3.
- **Files required for your library to run** — Additional files required by the generated application to run. These files are included in the generated application installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed for your end user** — Files that are installed with your application.

See “Specify Files to Install with Application” on page 3-6.

- **Additional runtime settings** — Platform-specific options for controlling the generated executable. See “Additional Runtime Settings” on page 3-6.

The screenshot shows the 'Library information' configuration window. It includes the following sections:

- Library information:** A header section containing a logo icon, the library name 'MagicSquareComp', and the version '1.0'. Below this are input fields for 'Author Name', 'Email', and 'Company', along with a 'Set as default contact' button. A 'Summary' and 'Description' text area are also present.
- Class Name / Method Name:** A table with two columns. The first row shows 'Class1' under 'Class Name' and '[m] = magicsquare (n)' under 'Method Name'. An 'Add Class' button is located below the table.
- Additional installer options:** A blue header bar with a right-pointing arrow.
- Files required for your library to run:** A blue header bar with a right-pointing arrow and a plus sign button.
- Files installed for your end user:** A blue header bar with a right-pointing arrow. Below it, three files are listed: '\_install.bat', 'MagicSquareCo...', and 'readme.txt'. A plus sign button is at the bottom right.
- Additional runtime settings:** A blue header bar with a right-pointing arrow.

## Package the Application

When you are finished selecting your packaging options, save your **Library Compiler** project and generate the packaged application.

**1** Click **Package**.

In the Save Project dialog box, specify the location to save the project.

**2** In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the packaging process is complete, examine the generated output in the target folder.

- Three folders are generated: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

For more information about the files generated in these folders, see “Files Generated After Packaging MATLAB Functions” on page 1-10.

- The log file `PackagingLog.html` contains packaging results.

## Create COM Component Using `compiler.build.COMComponent`

As an alternative to the **Library Compiler** app, you can create a COM component using a programmatic approach using the following steps. If you have already created a component using the **Library Compiler**, see “Integrate into COM Application” on page 2-29.

**1** Save the path to the file `makesquare.m` located in `matlabroot\toolbox\dotnetbuilder\Examples\VSVersion\COM\MagicSquareExample\MagicSquareComp`. For example, if you are using Visual Studio version 15, type:

```
appFile = fullfile(matlabroot,'toolbox','dotnetbuilder','Examples',...
    'VS15','COM','MagicSquareExample','MagicSquareComp','makesquare.m');
```

**2** Build the COM component using the `compiler.build.comComponent` function. Use name-value arguments to specify the component name and class name.

```
buildResults = compiler.build.comComponent(appFile,...
    'ComponentName','MagicSquareComp',...
    'ClassName','Class1');
```

The `compiler.build.Results` object `buildResults` contains information on the build type, generated files, and build options.

The function generates the following files within a folder named `MagicSquareCompcomComponent` in your current working directory:

- `magicsquare.def`
- `magicsquare.rc`
- `magicsquare_1_0.dll`
- `readme.txt`
- `requiredMCRProducts.txt`
- `unresolvedSymbols.txt`
- `Class1_com.cpp` — C++ source code file that defines the class.
- `Class1_com.hpp` — C++ header file that defines the class.
- `dlldata.c` — C source code file that contains entry points and data structures required by the class factory for the DLL.
- `GettingStarted.html` — HTML file that contains steps on installing COM components.
- `includedSupportPackages.txt` — Text file that contains information on included support packages.

- `MagicSquareComp.def` — Module definition file that defines which functions to include in the DLL export table.
- `MagicSquareComp.rc` — Resource script file that describes the resources used by the component.
- `MagicSquareComp_1_0.dll` — Dynamic-link library file.
- `MagicSquareComp_dll.cpp` — C++ source code file that contains helper functions.
- `MagicSquareComp_idl.h` — C++ header file.
- `MagicSquareComp_idl.idl` — Interface definition language file.
- `MagicSquareComp_idl.tlb` — Type library file that contains information about the COM object properties and methods.
- `MagicSquareComp_idl_i.c` — C source code file that contains the IIDs and CLSIDs for the IDL interface.
- `MagicSquareComp_idl_p.c` — C source code file that contains the proxy stub code for the IDL interface.
- `mccExcludedFiles.log` — Log file that contains a list of any toolbox functions that were not included in the application. For information on non-supported functions, see MATLAB Compiler Limitations.
- `mwcomtypes.h` — C++ header file that contains the definitions for the interfaces.
- `mwcomtypes_i.c` — C source code file that contains the IIDs and CLSIDs.
- `mwcomtypes_p.c` — C source code file that contains the proxy stub code.
- `readme.txt` — Text file that contains deployment information.
- `requiredMCRProducts.txt` — Text file that contains product IDs of products required by MATLAB Runtime to run the application.
- `unresolvedSymbols.txt` — Text file that contains information on unresolved symbols.

---

**Note** The generated assembly does not include MATLAB Runtime or an installer. To create an installer using the `buildResults` object, see `compiler.package.installer`.

---

You can specify additional options in the `compiler.build` command by using one or more of the following name-value arguments:

- `'AdditionalFiles'` — Path to additional files to include in the component.
- `'AutoDetectDataFiles'` — Flag to automatically include data files.
- `'ClassName'` — Name of the COM class.
- `'ComponentName'` — Name of the generated component.
- `'ComponentVersion'` — Version of the generated component.
- `'EmbedArchive'` — Flag to embed the assembly archive.
- `'OutputDir'` — Path to the output directory that contains generated files.
- `'Verbose'` — Flag to display progress information indicating compiler output during the build process.

## **Integrate into COM Application**

To integrate your COM component into an application, see “Creating the Microsoft Visual Basic Project”.

### **See Also**

`libraryCompiler` | `mcc` | `deploytool`

### **More About**

- “Call COM Objects in Visual C++ Programs”

## Generate Java Package and Build Java Application

**Supported platforms:** Windows, Linux, Mac

This example shows how to create a Java package from a MATLAB function and generate sample Java code.

### Prerequisites

- Verify that you have a version of Java installed that is compatible with MATLAB Compiler SDK. For information on supported Java versions, see [MATLAB Interfaces to Other Languages](#).

For information on configuring your development environment after installation, see “[Configure Your Java Environment for Generating Packages](#)”.

- End users must have an installation of MATLAB Runtime to run the application. For details, see “[Install and Configure MATLAB Runtime](#)”.

For testing purposes, you can use an installation of MATLAB instead of MATLAB Runtime.

### Create Function in MATLAB

In MATLAB, examine the MATLAB code that you want to package. For this example, open `makesqr.m` located in `matlabroot\toolbox\javabuilder\Examples\MagicSquareExample\MagicDemoComp`.

```
function y = makesqr(x)
y = magic(x);
```

At the MATLAB command prompt, enter `makesqr(5)`.

The output is a 5-by-5 matrix.

```
17    24     1     8    15
23     5     7    14    16
 4     6    13    20    22
10    12    19    21     3
11    18    25     2     9
```

### Create Java Package Using Library Compiler App


Compile the function into a Java package using the **Library Compiler** app. Alternatively, if you want to create a Java package from the MATLAB command window using a programmatic approach, see “[Create Java Package Using compiler.build.javaPackage](#)” on page 2-34.

- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Library Compiler**.

Alternatively, you can open the **Library Compiler** app from the MATLAB command prompt by entering:


```
libraryCompiler
```





- 2 In the **Type** section of the toolstrip, click **Java Package**.

In the **Library Compiler** app project window, specify the files of the MATLAB application that you want to deploy.

- a In the **Exported Functions** section of the toolstrip, click .
- b In the **Add Files** window, browse to the example folder, and select the function you want to package. Click **Open**.

The function is added to the list of exported function files. Repeat this step to package multiple files in the same application.

For this example, select the file `makesqr.m`.

- 3 In the **Packaging Options** section of the toolstrip, decide whether to include the MATLAB Runtime installer in the generated application by selecting one of the options:
  - **Runtime downloaded from web** — Generate an installer that downloads the MATLAB Runtime and installs it along with the deployed MATLAB application. You can specify the file name of the installer.
  - **Runtime included in package** — Generate an application that includes the MATLAB Runtime installer. You can specify the file name of the installer.

---

**Note** The first time you select this option, you are prompted to download the MATLAB Runtime installer.

---

### Specify Package Settings

Next, define the name of your Java package and verify the class mapping for the `.m` file that you are building into your application.

- 1 Choose a name for your package. The **Library Name** field is automatically populated with `makesqr` as the name of the package. The same name is followed through in the package implementation steps below.
- 2 Verify that the function defined in `makesqr.m` is mapped into `Class1`.



### Create Sample Driver File

You can use any MATLAB file in the project to generate sample Java driver files. Although Java driver files are not necessary to create a package, you can use them to implement a Java application, as shown in “Compile and Run MATLAB Generated Java Application” on page 2-35.

In the **Samples** section, select **Create New Sample**, and click `makesqr.m`. A MATLAB file opens for you to edit.

```
% Sample script to demonstrate execution of function y = makesqr(x)
x = 0; % Initialize x here
y = makesqr(x);
```

Change `x = 0` to `x = 5`, save the file, and return to the **Library Compiler** app. The compiler converts this MATLAB code to Java code during packaging.

For more information and limitations, see “Sample Driver File Creation” on page 3-5.

### Customize the Application and Its Appearance

In the **Library Compiler** app, you can customize the installer, customize your application, and add more information about the application.

- **Library information** — Information about the deployed application. You can also customize the appearance of the application by changing the application icon and splash screen. The generated installer uses this information to populate the installed application metadata. See “Customize the Installer” on page 3-2.
- **Additional installer options** — Default installation path for the generated installer and custom logo selection. See “Change the Installation Path” on page 3-3.
- **Files required for your library to run** — Additional files required by the generated application to run. These files are included in the generated application installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed for your end user** — Files that are installed with your application.

See “Specify Files to Install with Application” on page 3-6.

**Library information**

[Set as default contact](#)

Select custom splash screen

Class Name	Method Name	
Class1	[y] = makesqr (x)	<a href="#">+</a>
<a href="#">Add Class</a>		

**▼ Samples**

Add MATLAB files that demonstrate how to execute the exported functions. These files will be used to generate sample driver files in the target language.

[Create New Sample](#)   [Add Existing Sample](#)

**▶ Additional installer options**

**Files required for your library to run**

[+](#)

**Files installed for your end user**

doc

makesqr.jar

[+](#)

## Package the Application

When you are finished selecting your packaging options, save your **Library Compiler** project and generate the packaged application.

### 1 Click **Package**.

In the Save Project dialog box, specify the location to save the project.

- 2 In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the packaging process is complete, examine the generated output in the target folder.

- Three folders are generated: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

For more information about the files generated in these folders, see “Files Generated After Packaging MATLAB Functions” on page 1-10.

- The log file `PackagingLog.html` contains packaging results.

## Create Java Package Using `compiler.build.javaPackage`

As an alternative to the **Library Compiler** app, you can create a Java package using a programmatic approach. If you have already created a package using the **Library Compiler**, see “Compile and Run MATLAB Generated Java Application” on page 2-35.

- 1 Save the path to the `makesqr.m` file located in `matlabroot\toolbox\javabuilder\Examples\MagicSquareExample\MagicDemoComp`.

```
appFile = fullfile(matlabroot,'toolbox','javabuilder','Examples', ...
    'MagicSquareExample','MagicDemoComp','makesqr.m');
```

- 2 Save the following code in a sample file named `makesqrSample1.m`:

```
x = 5;
y = makesqr(x);
```

- 3 Build the Java package using the `compiler.build.javaPackage` function. Use name-value arguments to add a sample file and enable verbose output.

```
buildResults = compiler.build.javaPackage(appFile, ...
    'SampleGenerationFiles','makesqrSample1.m', ...
    'Verbose','on');
```

The `compiler.build.Results` object `buildResults` contains information on the build type, generated files, and build options.

The function generates the following within a folder named `makesqrjavaPackage` in your current working directory:

- `classes` — Folder that contains the Java class files and the deployable archive CTF file.
- `doc` — Folder that contains HTML documentation for all classes in the package.
- `example` — Folder that contains Java source code files.
- `samples` — Folder that contains the Java sample driver file `makesqrSample1.java`.
- `GettingStarted.html` — File that contains information on integrating your package.
- `makesqr.jar` — Java archive file.
- `mccExcludedFiles.log` — Log file that contains a list of any toolbox functions that were not included in the application. For information on non-supported functions, see [Functions Not Supported For Compilation](#).
- `readme.txt` — Text file that contains information on deployment prerequisites and the list of files to package for deployment.
- `requiredMCRProducts.txt` — Text file that contains product IDs of products required by MATLAB Runtime to run the application.

- `unresolvedSymbols.txt` — Text file that contains information on unresolved symbols.

---

**Note** The generated package does not include MATLAB Runtime or an installer. To create an installer using the `buildResults` object, see `compiler.package.installer`.

---

You can specify additional options in the `compiler.build` command by using one or more of the following name-value arguments:

- `'AdditionalFiles'` — Path to additional files and folders to include in the package.
- `'AutoDetectDataFiles'` — Flag to automatically include data files.
- `'ClassName'` — Name of the Java class.
- `'DebugBuild'` — Flag to enable debug symbols.
- `'OutputDir'` — Path to the output directory that contains generated files.
- `'PackageName'` — Name of the generated package.
- `'SampleGenerationFiles'` — MATLAB sample files used to generate sample Java package files. For more information, see “Sample Driver File Creation” on page 3-5.
- `'Verbose'` — Flag to display progress information indicating compiler output during the build process.

## Compile and Run MATLAB Generated Java Application

After creating your Java package, you can call it from a Java application. This example uses the sample Java code generated during packaging. You can use this sample Java application code as a guide to write your own Java application.

- 1 Copy and paste the generated Java file `makesqrSample1.java` from the `samples` folder into the folder that contains the `makesqr.jar` package. If you used the Library Compiler, `makesqr.jar` is located in the `for_testing` folder.
- 2 At the system command prompt, navigate to the folder that contains `makesqrSample1.java` and `makesqr.jar`.
- 3 Compile the application using `javac`. In the classpath argument, you specify the paths to `javabuilder.jar`, which contains the `com.mathworks.toolbox.javabuilder` package, and your generated Java package `makesqr.jar`.

- On Windows, type:

```
javac -classpath "matlabroot\toolbox\javabuilder\jar\javabuilder.jar";.\makesqr.jar makesqrSample1.java
```

- On UNIX®, type:

```
javac -classpath "matlabroot/toolbox/javabuilder/jar/javabuilder.jar":./makesqr.jar makesqrSample1.java
```

Replace `matlabroot` with the path to your MATLAB or MATLAB Runtime installation folder. For example, on Windows, the path may be `C:\Program Files\MATLAB\R2021b`.

---

**Note** If `makesqr.jar` or `makesqrSample1.java` is not in the current directory, specify the full or relative path in the command. If the path contains spaces, surround it with double quotes.

---

- 4 Run the application using `java`.

- On Windows, type:

```
java -classpath .;"matlabroot\toolbox\javabuilder\jar\javabuilder.jar";.\makesqr.jar makesqrSample1
```

- On UNIX, type:

```
javac -classpath .:"matlabroot/toolbox/javabuilder/jar/javabuilder.jar":./makesqr.jar makesqrSample1
```

---

**Note** The dot (.) in the first position of the class path represents the current working directory. If it is not there, you get a message stating that Java cannot load the class.

---

The application returns the same output as the sample MATLAB code.

```
17    24     1     8    15
23     5     7    14    16
 4     6    13    20    22
10    12    19    21     3
11    18    25     2     9
```

### See Also

[libraryCompiler](#) | [compiler.build.javaPackage](#) | [mcc](#) | [deploytool](#)

### Related Examples

- “Integrate Simple MATLAB Function Into Java Application”
- “Display MATLAB Plot in Java Application”

# Generate a Python Package and Build a Python Application

**Supported platforms:** Windows, Linux, Mac

This example shows how to create a Python package from a MATLAB function and integrate the generated package into a Python application.

## Prerequisites

- Verify that you have a version of Python installed that is compatible with MATLAB Compiler SDK. For details, see MATLAB Supported Interfaces to Other Languages.
- End users must have an installation of MATLAB Runtime to run the application. For testing purposes, you can use an installation of MATLAB instead of MATLAB Runtime. For details, see “Install and Configure MATLAB Runtime”.

## Create Function in MATLAB

In MATLAB, examine the MATLAB code that you want packaged. For this example, write a function `makesqr.m`.

```
function makesqr(x)
y = magic(x);
disp(y)
```

At the MATLAB command prompt, enter `makesqr(5)`.

The output is a 5x5 matrix.

```
17    24     1     8    15
23     5     7    14    16
 4     6    13    20    22
10    12    19    21     3
11    18    25     2     9
```


## Create Python Application Using Library Compiler App

Compile the function into a Python package using the **Library Compiler** app. Alternatively, if you want to create a Python package from the MATLAB command window using a programmatic approach, see “Create Python Package Using `compiler.build.pythonPackage`” on page 2-41.

- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Library Compiler**.


Alternatively, you can open the **Library Compiler** app from the MATLAB command prompt.

```
libraryCompiler
```



- 2 In the **Type** section of the toolstrip, click **Python Package**.

In the **Library Compiler** app project window, specify the files of the MATLAB application that you want to deploy.

- a In the **Exported Functions** section of the toolstrip, click .
- b In the **Add Files** window, browse to the example folder, and select the function you want to package. Click **Open**.

The function is added to the list of exported function files. Repeat this step to package multiple files in the same application.

For this example, select the `makesqr.m` file that you wrote earlier.

- 3 In the **Packaging Options** section of the toolstrip, decide whether to include the MATLAB Runtime installer in the generated application by selecting one of the options:
  - **Runtime downloaded from web** — Generate an installer that downloads the MATLAB Runtime and installs it along with the deployed MATLAB application. You can specify the file name of the installer.
  - **Runtime included in package** — Generate an application that includes the MATLAB Runtime installer. You can specify the file name of the installer.

---

**Note** The first time you select this option, you are prompted to download the MATLAB Runtime installer.

---

### Specify Package Settings

Next, define the name of your Python package.

- The **Library Name** field is automatically populated with `makesqr` as the name of the package. Rename it as `MagicSquarePkg`. For more information on naming requirements for the Python package, see “Import Compiled Python Packages”.

### Create Sample Driver File

You can add MATLAB files to the project to generate sample Python driver files. Although Python driver files are not necessary to create a package, you can use them to implement a Python application, as shown in “Install and Run MATLAB Generated Python Application” on page 2-42.



In the **Samples** section, select **Create New Sample**, and click `makesqr.m`. A MATLAB file opens for you to edit.

```
% Sample script to demonstrate execution of function y = makesqr(x)
x = 0; % Initialize x here
y = makesqr(x);
```

Change `x = 0` to `x = 4`, save the file, and return to the **Library Compiler** app.

For more information and limitations, see “Sample Driver File Creation” on page 3-5.

### Customize the Application and Its Appearance

In the **Library Compiler** app, you can customize the installer, customize your application, and add more information about the application.

- **Library information** — Information about the deployed application. You can also customize the appearance of the application by changing the application icon and splash screen. The generated installer uses this information to populate the installed application metadata. See “Customize the Installer” on page 3-2.
- **Additional installer options** — Default installation path for the generated installer and custom logo selection. See “Change the Installation Path” on page 3-3.
- **Files required for your library to run** — Additional files required by the generated application to run. These files are included in the generated application installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed for your end user** — Files that are installed with your application.

See “Specify Files to Install with Application” on page 3-6.

The screenshot shows the 'Library information' section of the Library Compiler. It includes a header 'Library information' and a sub-header 'Library information'. The main area contains several input fields: 'MagicSquarePkg' (with a version of '1.0'), 'Author Name', 'Email', 'Company', 'Summary', and 'Description'. A 'Set as default contact' button is located to the right of the 'Company' field. To the right of the input fields is a preview of a splash screen with a colorful geometric pattern and a 'Select custom splash screen' button. Below the input fields is a 'Namespace' field. The 'Samples' section is expanded, showing instructions to add MATLAB files and a list of sample files including 'makesqrSample1...'. There are 'Create New Sample' and 'Add Existing Sample' buttons. Below the samples section is an 'Additional installer options' section. The 'Files required for your library to run' section is empty with a '+' button. The 'Files installed for your end user' section lists 'MagicSquarePkg' and 'setup.py' with a '+' button.

## Package the Application

When you are finished selecting your packaging options, save your **Library Compiler** project and generate the packaged application.

- 1 Click **Package**.

In the Save Project dialog box, specify the location to save the project.

- 2 In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the packaging process is complete, examine the generated output in the target folder.

- Three folders are generated: `for_redistribution`, `for_redistribution_files_only`, and `for_testing`.

For more information about the files generated in these folders, see “Files Generated After Packaging MATLAB Functions” on page 1-10.

- The log file `PackagingLog.html` contains packaging results.

## Create Python Package Using `compiler.build.pythonPackage`

As an alternative to the **Library Compiler** app, you can create a Python package using a programmatic approach using the following steps.

- 1 Save the following code in a sample file named `makesqrSample1.m`:

```
x = 4;
a = makesqr(x);
```

- 2 Build the Python package using the `compiler.build.pythonPackage` function and the `makesqr.m` file that you wrote earlier. Use name-value arguments to specify the package name and add a sample file.

```
buildResults = compiler.build.pythonPackage('makesqr.m',...
'PackageName','MagicSquarePkg',...
'SampleGenerationFiles','makesqrSample1.m');
```

The `compiler.build.Results` object `buildResults` contains information on the build type, generated files, and build options.

- 3 The function generates the following files within a folder named `MagicSquarePkgpythonPackage` in your current working directory:
  - `samples\makesqrSample1.py` — Python sample driver file.
  - `GettingStarted.html` — HTML file that contains information on integrating your package.
  - `mccExcludedFiles.log` — Log file that contains a list of any toolbox functions that were not included in the application. For information on non-supported functions, see **MATLAB Compiler Limitations**.
  - `readme.txt` — Text file that contains packaging and interface information.
  - `requiredMCRProducts.txt` — Text file that contains product IDs of products required by MATLAB Runtime to run the application.
  - `setup.py` — Python file that installs the package.
  - `unresolvedSymbols.txt` — Text file that contains information on unresolved symbols.

---

**Note** The generated package does not include MATLAB Runtime or an installer. To create an installer using the `buildResults` object, see `compiler.package.installer`.

---

You can specify additional options in the `compiler.build` command by using one or more of the following name-value arguments:

- `'AdditionalFiles'` — Path to additional files to include in the package.
- `'AutoDetectDataFiles'` — Flag to automatically include data files.
- `'OutputDir'` — Path to the output directory that contains generated files.
- `'PackageName'` — Name of the generated package.

- 'SampleGenerationFiles' — MATLAB sample files used to generate sample Python package files. For more information, see “Sample Driver File Creation” on page 3-5.
- 'Verbose' — Flag to display progress information indicating compiler output during the build process.

## Install and Run MATLAB Generated Python Application

After creating your Python package, you can call it from a Python application. This example uses the sample Python code generated during packaging. You can use this sample Python application code as a guide to write your own Python application.

- 1** Copy and paste the generated Python file `makesqrSample1.py` from the `samples` folder into the folder that contains the `setup.py` file.
- 2** At the system command prompt, navigate to the folder that contains `makesqrSample1.py` and `setup.py`.
- 3** Install the application using the `python` command.

```
python setup.py install
```

To install to a location other than the default, consult "Installing Python Modules" in the official Python documentation.

- 4** Run the application. If you used sample MATLAB code in the packaging steps, this application returns the same output as the sample code.

```
python makesqrSample1.py
```

---

**Note** On macOS, you must use the `mwpython` script instead of `python`. For example, `mwpython makesqrSample1.py`.

The `mwpython` script is located in the `matlabroot/bin` folder, where `matlabroot` is the location of your MATLAB installation.

---

### See Also

`mwpython` | `libraryCompiler` | `compiler.build.pythonPackage` | `mcc` | `deploytool`

# Customizing a Compiler Project

---

- “Customize an Application” on page 3-2
- “Manage Support Packages” on page 3-9

## Customize an Application

You can customize an application in several ways: customize the installer, manage files in the project, or add a custom installer path using the **Application Compiler** app or the **Library Compiler** app.

### Customize the Installer

#### Change Application Icon

To change the default icon, click the graphic to the left of the **Library name** or **Application name** field to preview the icon.



Click **Select icon**, and locate the graphic file to use as the application icon. Select the **Use mask** option to fill any blank spaces around the icon with white or the **Use border** option to add a border around the icon.

To return to the main window, click **Save and Use**.

#### Add Library or Application Information

You can provide further information about your application as follows:

- **Library/Application Name:** The name of the installed MATLAB artifacts. For example, if the name is `foo`, the installed executable is `foo.exe`, and the Windows start menu entry is **foo**. The folder created for the application is `InstallRoot/foo`.

The default value is the name of the first function listed in the **Main File(s)** field of the app.

- **Version:** The default value is 1.0.
- **Author name:** Name of the developer.
- **Support email address:** Email address to use for contact information.
- **Company name:** The full installation path for the installed MATLAB artifacts. For example, if the company name is `bar`, the full installation path would be `InstallRoot/bar/ApplicationName`.
- **Summary:** Brief summary describing the application.
- **Description:** Detailed explanation about the application.

All information is optional and, unless otherwise stated, is only displayed on the first page of the installer. On Windows systems, this information is also displayed in the Windows **Add/Remove Programs** control panel.

Library information





### Change the Splash Screen

The installer splash screen displays after the installer has started. It is displayed along with a status bar while the installer initializes.

You can change the default image by clicking the **Select custom splash screen**. When the file explorer opens, locate and select a new image.

You can drag and drop a custom image onto the default splash screen.

### Change the Installation Path

This table lists the default path the installer uses when installing the packaged binaries onto a target system.


Windows	C:\Program Files\ <i>companyName</i> \ <i>appName</i>
Mac OS X	/Applications/ <i>companyName</i> / <i>appName</i>
Linux	/usr/ <i>companyName</i> / <i>appName</i>

You can change the default installation path by editing the **Default installation folder** field under **Additional installer options**.

Additional installer options

Default installation folder:

Installation notes



A text field specifying the path appended to the root folder is your installation folder. You can pick the root folder for the application installation folder. This table lists the optional custom root folders for each platform:

Windows	C:\Users\ <i>userName</i> \AppData
Linux	/usr/local

#### Change the Logo

The logo displays after the installer has started. It is displayed on the right side of the installer.

You change the default image in **Additional Installer Options** by clicking **Select custom logo**. When the file explorer opens, locate and select a new image. You can drag and drop a custom image onto the default logo.

#### Edit the Installation Notes

Installation notes are displayed once the installer has successfully installed the packaged files on the target system. You can provide useful information concerning any additional setup that is required to use the installed binaries and instructions for how to run the application.

### Manage Required Files in Compiler Project

The compiler uses a dependency analysis function to automatically determine what additional MATLAB files are required for the application to package and run. These files are automatically packaged into the generated binary. The compiler does not generate any wrapper code that allows direct access to the functions defined by the required files.

If you are using one of the compiler apps, the required files discovered by the dependency analysis function are listed in the **Files required for your application to run** or **Files required for your library to run** field.

To add files, click the plus button in the field, and select the file from the file explorer. To remove files, select the files, and press the **Delete** key.

---

**Caution** Removing files from the list of required files may cause your application to not package or not to run properly when deployed.

---

#### Using mcc

If you are using `mcc` to package your MATLAB code, the compiler does not display a list of required files before running. Instead, it packages all the required files that are discovered by the dependency analysis function and adds them to the generated binary file.


You can add files to the list by passing one or more `-a` arguments to `mcc`. The `-a` arguments add the specified files to the list of files to be added into the generated binary. For example, `-a hello.m` adds the file `hello.m` to the list of required files and `-a ./foo` adds all the files in `foo` and its subfolders to the list of required files.



## Sample Driver File Creation

The following target types support sample driver file creation in MATLAB Compiler SDK:

- C++ shared library
- Java package
- .NET assembly
- Python package



The sample driver file creation feature in **Library Compiler** uses MATLAB code to generate sample driver files in the target language. The sample driver files are used to implement the generated shared libraries into an application in the target language. In the app, click **Create New Sample** to automatically generate a new MATLAB script, or click **Add Existing Sample** to upload a MATLAB script that you have already written. After you package your functions, a sample driver file in the target language is generated from your MATLAB script and is saved in `for_redistribution_files_only\samples`. Sample driver files are also included in the installer in `for_redistribution`.

To automatically generate a new MATLAB file, click **Create New Sample**. This opens up a MATLAB file for you to edit. The sample file serves as a starting point, and you can edit it as necessary based on the behavior of your exported functions. The sample MATLAB files must follow these guidelines:

- The sample file code must use only exported functions.
- Each exported function must be in a separate sample file.
- Each call to the same exported function must be a separate sample file.
- The output of the exported function must be an n-dimensional numeric, char, logical, struct, or cell array.
- Data must be saved as a local variable and then passed to the exported function in the sample file code.
- Sample file code should not require user interaction.

Additional considerations specific to the target language are as follows:

- C++ `mwArray` API — `varargin` and `varargout` are not supported.
- .NET — Type-safe API is not supported.
- Python — Cell arrays and char arrays must be of size 1xN and struct arrays must be scalar. There are no restrictions on numeric or logical arrays, other than that they must be rectangular, as in MATLAB.

To upload a MATLAB file that you have already written, click **Add Existing Sample**. The MATLAB code should demonstrate how to execute the exported functions. The required MATLAB code can be only a few lines:

```
input1 = [1 4 7; 2 5 8; 3 6 9];
input2 = [1 4 7; 2 5 8; 3 6 9];
addoutput = addmatrix(input1,input2);
```


This code must also follow all the same guidelines outlined for the **Create New Sample** option.

You can also choose not to include a sample driver file at all during the packaging step. If you create your own driver code in the target language, you can later copy and paste it into the appropriate directory once the MATLAB functions are packaged.

### Specify Files to Install with Application

The compiler packages files to install along with the ones it generates. By default, the installer includes a readme file with instructions on installing the MATLAB Runtime and configuring it.

These files are listed in the **Files installed for your end user** section of the app.

To add files to the list, click , and select the file from the file explorer.

JAR files are added to the application class path as if you had called `javaaddpath`.

---

**Caution** Removing the binary targets from the list results in an installer that does not install the intended functionality.

---

When installed on a target computer, the files listed in the **Files installed for your end user** are saved in the application folder.

### Additional Runtime Settings

Type of Packaged Application	Description	Additional Runtime Settings Options
Generic COM Components	<ul style="list-style-type: none"> <li> <b>Register the component for the current user (Recommended for non-admin users)</b> — This option enables registering the component for the current user account. It is provided for users without admin rights.                     </li> </ul>	<div style="background-color: #e0e0e0; padding: 2px;"> <span style="font-size: 0.8em; color: #555;">▼ Additional runtime settings</span> </div> <div style="padding: 10px;"> <input type="checkbox"/> Register the component for the current user (Recommended fo                 </div>

Type of Packaged Application	Description	Additional Runtime Settings Options
.NET Assembly	<ul style="list-style-type: none"> <li>• <b>Create Shared Assembly</b> — Enables sharing MATLAB Runtime installer instances for multiple .NET assemblies.</li> <li>• <b>Enable .NET Remoting</b> — Enables you to remotely access MATLAB functionality, as a part of a distributed system. For more information, see “Create Remotable .NET Assembly”.</li> <li>• <b>Enable Type Safe API</b> — Enables the type safe API for the packaged .NET assembly.</li> </ul>	<p>▼ Additional runtime settings</p> <p>What .NET versions are supported?</p> <p>Assembly Type</p> <p><input type="checkbox"/> Create Shared Assembly</p> <p><input type="checkbox"/> Enable .NET Remoting</p> <p>Type Safe API</p> <p><input type="checkbox"/> Enable type safe API</p>

### API Selection for C++ Shared Library

▼ API selection

C++ Shared Library API

Create all interfaces

Create interface that uses the `mwArray` API

Create interface that uses the MATLAB Data API

- **Create all interfaces** — Create interfaces for shared libraries using both the `mwArray` API and the MATLAB Data API.
- **Create interface that uses the `mwArray` API** — Create an interface for a shared library using the `mwArray` API. The interface uses C-style functions to initialize the MATLAB Runtime, load the compiled MATLAB functions into the MATLAB Runtime, and manage data that is passed between the C++ code and the MATLAB Runtime. The interface supports only C++03 functionality. For an example, see “Generate a C++ `mwArray` API Shared Library and Build a C++ Application” on page 2-6.
- **Create interface that uses the MATLAB Data API** — Create an interface for a shared library using MATLAB Data API. It uses a generic interface that has modern C++ semantics. The interface supports C++11 functionality. For more information, see “Generate a C++ MATLAB Data API Shared Library and Build a C++ Application” on page 2-11.

### See Also

libraryCompiler


### More About

- “Create a C Shared Library with MATLAB Code” on page 2-2
- “Generate a C++ mxArray API Shared Library and Build a C++ Application” on page 2-6
- “Generate a C++ MATLAB Data API Shared Library and Build a C++ Application” on page 2-11
- “Generate .NET Assembly and Build .NET Application” on page 2-16
- “Create a Generic COM Component with MATLAB Code” on page 2-24
- “Generate Java Package and Build Java Application” on page 2-30
- “Generate a Python Package and Build a Python Application” on page 2-37

## Manage Support Packages

### Using a Compiler App

Many MATLAB toolboxes use support packages to interact with hardware or to provide additional processing capabilities. If your MATLAB code uses a toolbox with an installed support package, the app displays a **Suggested Support Packages** section.



The list displays all installed support packages that your MATLAB code requires. The list is determined using these criteria:

- the support package is installed
- your code has a direct dependency on the support package
- your code is dependent on the base product of the support package
- your code is dependent on at least one of the files listed as a dependency in the `mcc.xml` file of the support package, and the base product of the support package is MATLAB

Deselect support packages that are not required by your application.

Some support packages require third-party drivers that the compiler cannot package. In this case, the compiler adds the information to the installation notes. You can edit installation notes in the **Additional Installer Options** section of the app. To remove the installation note text, deselect the support package with the third-party dependency.

---

**Caution** Any text you enter beneath the generated text will be lost if you deselect the support package.

---

### Using the Command Line

Many MATLAB toolboxes use support packages to interact with hardware or to provide additional processing capabilities. If your MATLAB code uses a toolbox with an installed support package, use the `-a` flag with `mcc` command when packaging your MATLAB code to specify supporting files in the

support package folder. For example, if your function uses the OS Generic Video Interface support package, run the following command:

```
mcc -m -v test.m -a C:\MATLAB\SupportPackages\R2016b\toolbox\daq\supportpackages\daqaudio -a 'C:
```

Some support packages require third-party drivers that the compiler cannot package. In this case, you are responsible for downloading and installing the required drivers.

# Using MATLAB Production Server

---

- “Create Deployable Archive for MATLAB Production Server” on page 4-2
- “Create and Install a Deployable Archive with Excel Integration For MATLAB Production Server” on page 4-5
- “Create a C# Client Using MWHttpClient” on page 4-9
- “Create Java Client Using MWHttpClient Class” on page 4-12
- “Create a C++ Client” on page 4-15
- “Create a Python Client” on page 4-20

## Create Deployable Archive for MATLAB Production Server

**Supported platform:** Windows, Linux, Mac

This example shows how to create a deployable archive from a MATLAB function. You can then give the generated archive to a system administrator to deploy it on the MATLAB Production Server environment.

### Create MATLAB Function

In MATLAB, examine the MATLAB program that you want to package.

For this example, write a function `addmatrix.m` as follows.

```
function a = addmatrix(a1, a2)

a = a1 + a2;
```


At the MATLAB command prompt, enter `addmatrix([1 4 7; 2 5 8; 3 6 9], [1 4 7; 2 5 8; 3 6 9])`.

The output is:


```
ans =
     2     8    14
     4    10    16
     6    12    18
```

### Create Deployable Archive with Production Server Compiler App

- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Production Server Compiler**. In the **Production Server Compiler** project window, click **Deployable Archive (.ctf)**.



Alternatively, you can open the **Production Server Compiler** app by entering `productionServerCompiler` at the MATLAB prompt.

- 2 In the **Production Server Compiler** project window, specify the main file of the MATLAB application that you want to deploy.
  - 1 In the **Exported Functions** section, click .
  - 2 In the **Add Files** window, browse to the example folder, and select the function you want to package.



Click **Open**.

Doing so adds the function `addmatrix.m` to the list of main files.


## Customize Application and Its Appearance

You can customize your deployable archive, and add more information about the application as follows:

- **Archive information** — Editable information about the deployed archive.
- **Additional files required for your archive to run** — Additional files required to run the generated archive. These files are included in the generated archive installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files packaged for redistribution** — Files that are installed with your archive. These files include:
  - Generated deployable archive
  - Generated `readme.txt`

See “Specify Files to Install with Application” on page 3-6.


- **Include MATLAB function signature file** — Add or create a function signature file to help clients use your MATLAB functions. See “MATLAB Function Signatures in JSON”.



## Package Application

- 1 To generate the packaged application, click **Package**.

In the Save Project dialog box, specify the location to save the project.



- 2 In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the deployment process is complete, examine the generated output.

- `for_redistribution` — Folder containing the archive `archiveName.ctf`
- `for_testing` — Folder containing the raw generated files to create the installer
- `PackagingLog.html` — Log file generated by MATLAB Compiler SDK

## See Also

`mcc` | `deploytool` | `productionServerCompiler`

## More About

- Production Server Compiler
- “MATLAB Function Signatures in JSON”

# Create and Install a Deployable Archive with Excel Integration For MATLAB Production Server

**Supported platform:** Windows

This example shows how to create a deployable archive with Excel integration from a MATLAB function. You can then give the generated archive to a system administrator to deploy on MATLAB Production Server.

## Create Function In MATLAB

In MATLAB, examine the MATLAB program that you want to package.

For this example, write a function `mymagic.m` as follows.

```
function y = mymagic(x)
```

```
y = magic(x);
```


At the MATLAB command prompt, enter `mymagic(3)`.

The output is:

```
ans =
     8     1     6
     3     5     7
     4     9     2
```

## Create Deployable Archive with Excel Integration Using Production Server Compiler App

- 1 On the **MATLAB Apps** tab, on the far right of the **Apps** section, click the arrow. In **Application Deployment**, click **Production Server Compiler**. In the **Production Server Compiler** project window, click **Deployable Archive with Excel integration**.



Alternatively, you can open the **Production Server Compiler** app by entering `productionServerCompiler` at the MATLAB prompt.

- 2 In the **Production Server Compiler** project window, specify the files of the MATLAB application that you want to deploy.

- 1 In the **Exported Functions** section, click .

- 2 In the **Add Files** window, browse to the example folder, and select the function you want to package.

Click **Open**.

Doing so adds the function `mymagic.m` to the list of main files.

## Customize the Application and Its Appearance

You can customize your deployable archive with Excel integration, and add more information about the application as follows:

- **Archive information** — Editable information about the deployed archive with Excel integration.
- **Client configuration** — Configure the MATLAB Production Server client. Select the **Default Server URL**, decide wait time-out, and maximum size of response for the client, and provide an optional self-signed certificate for `https`.
- **Additional files required for your archive to run** — Additional files required by the generated archive to run. These files are included in the generated archive installer. See “Manage Required Files in Compiler Project” on page 3-4.
- **Files installed with your archive** — Files that are installed with your archive on the client and server. The files installed on the server include:
  - Generated deployable archive (CTF file)
  - Generated `readme.txt`

The files installed on the client include:

- `mymagic.bas`
- `mymagic.dll`
- `mymagic.xla`
- `readme.txt`
- `ServerConfig.dll`

See “Specify Files to Install with Application” on page 3-6.

- **Options** — The option **Register the resulting component for you only on the development machine** exclusively registers the packaged component for one user on the development machine.

**Archive information**

mymagic 1.0

Class Name	Method Name	
Class1	[y] = mymagic (x)	+

**Client configuration**

**Default Server URL**

None

MATLAB Production Server URL: Protocol:  Host:  Port:

Provide your own URL:

**Advanced Options**

Time the client waits before it times out:  Seconds

Maximum size of the response the client accepts:  MB

Provide an optional self-signed certificate for https:  Browse...

**Additional files required for your archive to run (Server only)**

+

**Files installed with your archive**

**Server**

mymagic.ctf
 readme.txt
+

**Client**

mymagic.bas
 mymagic.dll
 mymagic.xla
 readme.txt
 ServerConfig.dll
+


**Options**

Register the resulting component for you only on the development machine

## Package the Application

- 1 To generate the packaged application, click **Package**.

In the Save Project dialog box, specify the location to save the project.



- 2 In the **Package** dialog box, verify that **Open output folder when process completes** is selected.

When the deployment process is complete, examine the generated output.

- `for_redistribution` — Folder containing the installer to distribute the archive on the MATLAB Production Server client and server
- `for_redistribution_files_only` — Folder containing the files required for redistributing the application on the MATLAB Production Server client and server
- `for_testing` — Folder containing the raw generated files to create the installer
- `PackagingLog.html` — Log file generated by MATLAB Compiler SDK

## Install the Deployable Archive with Excel Integration

The archive must be deployed to a MATLAB Production Server instance before the add-in works.

To install the deployable archive on a server instance:

- 1 Locate the archive in the `for_redistribution_files_only\server\` folder.  
The file name is similar to `archiveName.ctf`.
- 2 Copy the archive file to the `auto_deploy` folder of the server instance. The server instance automatically deploys it and makes it available to interested clients.

For more information, see “MATLAB Production Server” documentation.

### See Also

`productionServerCompiler`

## Create a C# Client Using MWHttpClient

This example shows how to write a C# application to call a MATLAB function deployed to MATLAB Production Server. The C# application uses the MATLAB Production Server .NET client library.

A .NET application programmer typically performs this task. The tutorial assumes that you have Microsoft Visual Studio and .NET installed on your computer.

### Create Microsoft Visual Studio Project

- 1 Open Microsoft Visual Studio.
- 2 Click **File > New > Project**.
- 3 In the New Project dialog box, select the template you want to use. For example, if you want to create a C# console application in Visual Studio 2017, select **Visual C# > Windows Desktop** in the left navigation pane, then select the **Console App (.Net Framework)**.
- 4 Type the name of the project in the **Name** field (for example, `Magic`).
- 5 Click **OK**. Your `Magic` source shell is created, typically named `Program.cs`, by default.

### Create Reference to Client Runtime Library

Create a reference in your `Magic` project to the MATLAB Production Server client runtime library. In Microsoft Visual Studio, perform the following steps:

- 1 In the **Solution Explorer** pane within Microsoft Visual Studio (usually on the right side), right-click your `Magic` project, select **Add > Browse**.
- 2 Browse to the MATLAB Production Server .NET client runtime library location.

The library is located in `matlabroot\toolbox\compiler_sdk\mps_client\dotnet`. Select the `MathWorks.MATLAB.ProductionServer.Client.dll` file.

The client library is also available for download at <https://www.mathworks.com/products/matlab-production-server/client-libraries.html>.

- 3 Click **OK**. Your Microsoft Visual Studio project now references the `MathWorks.MATLAB.ProductionServer.Client.dll`.

### Deploy MATLAB Function to Server

Write a MATLAB function `mymagic` that uses the `magic` function to create a magic square, package `mymagic` into a deployable archive called `mymagic_deployed`, then deploy it to a server. The function `mymagic` takes a single `int` input and returns a magic square as a 2-D `double` array. The example assumes that the server instance is running at `http://localhost:9910`.

```
function m = mymagic(in)
    m = magic(in);
```

### Design .NET Interface in C#

Invoke the deployed MATLAB function `mymagic` from a .NET client through a .NET interface. Design a C# interface `Magic` to match the MATLAB function `mymagic`.

- The .NET interface has the same number of inputs and outputs as the MATLAB function.
- Since you are deploying one MATLAB function on the server, you define one corresponding .NET method in your C# code.

- Both the MATLAB function and the .NET interface process the same data types—input type `int` and output type 2-D `double`.
- In your C# client program, use the interface `Magic` to specify the type of the proxy object reference in the `CreateProxy` method. The `CreateProxy` method requires the URL to the deployable archive that contains the `mymagic` function (`http://localhost:9910/mymagic_deployed`) as an input argument.

```
public interface Magic
{
    double[,] mymagic(int in1);
}
```

### Write, Build, and Run .NET Application

- 1 Open the Microsoft Visual Studio project `Magic` that you created earlier.
- 2 In the `Program.cs` tab, paste in the code below.

```
using System;
using System.Net;
using MathWorks.MATLAB.ProductionServer.Client;

namespace Magic
{
    public class MagicClass
    {
        public interface Magic
        {
            double[,] mymagic(int in1);
        }

        public static void Main(string[] args)
        {
            MWClient client = new MWHttpClient();
            try
            {
                Magic me = client.CreateProxy<Magic>
                    (new Uri("http://localhost:9910/mymagic_deployed"));
                double[,] result1 = me.mymagic(4);
                print(result1);
            }
            catch (MATLABException ex)
            {
                Console.WriteLine("{0} MATLAB exception caught.", ex);
                Console.WriteLine(ex.StackTrace);
            }
            catch (WebException ex)
            {
                Console.WriteLine("{0} Web exception caught.", ex);
                Console.WriteLine(ex.StackTrace);
            }
            finally
            {
                client.Dispose();
            }
            Console.ReadLine();
        }

        public static void print(double[,] x)
        {
            int rank = x.Rank;
            int[] dims = new int[rank];

            for (int i = 0; i < rank; i++)
            {
                dims[i] = x.GetLength(i);
            }
        }
    }
}
```



```

        for (int j = 0; j < dims[0]; j++)
        {
            for (int k = 0; k < dims[1]; k++)
            {
                Console.Write(x[j, k]);
                if (k < (dims[1] - 1))
                {
                    Console.Write(",");
                }
            }
            Console.WriteLine();
        }
    }
}

```

The URL value ("http://localhost:9910/mymagic\_deployed") used to create the proxy contains three parts.

- the server address (localhost).
- the port number (9910).
- the archive name (mymagic\_deployed).

**3** Build the application. Click **Build** > **Build Solution**.

**4** Run the application. Click **Debug** > **Start Without Debugging**. The program returns the following console output.

```

16,2,3,13
5,11,10,8
9,7,6,12
4,14,15,1

```

## See Also

### More About

- "Create a .NET MATLAB Production Server Client" (MATLAB Production Server)
- "Configure the Client-Server Connection" (MATLAB Production Server)
- "Synchronous RESTful Requests Using Protocol Buffers in .NET Client" (MATLAB Production Server)

## Create Java Client Using MWHttpClient Class

This example shows how to write a MATLAB Production Server client using the Java client API. In your Java code, you will:

- Define a Java interface that represents the deployed MATLAB function.
- Instantiate a proxy object to communicate with the server.
- Call the deployed function in your Java code.

To create a Java MATLAB Production Server client application:

- 1** Create a new file, for example, `MPSCClientExample.java`.
- 2** Using a text editor, open `MPSCClientExample.java`.
- 3** Add the following import statements to the file:

```
import java.net.URL;
import java.io.IOException;
import com.mathworks.mps.client.MWClient;
import com.mathworks.mps.client.MWHttpClient;
import com.mathworks.mps.client.MATLABException;
```

- 4** Add a Java interface that represents the deployed MATLAB function.

For example, consider the following `addmatrix` function deployed to the server:

```
function a = addmatrix(a1, a2)

a = a1 + a2;
```

The interface for the `addmatrix` function follows.

```
interface MATLABAddMatrix {
    double[][] addmatrix(double[][] a1, double[][] a2)
        throws MATLABException, IOException;
}
```

When creating the interface, note the following:

- You can give the interface any valid Java name.
  - You must give the method defined by this interface the same name as the deployed MATLAB function.
  - The Java method must support the same inputs and outputs supported by the MATLAB function, in both type and number. For more information about data type conversions and how to handle more complex MATLAB function signatures, see “Java Client Programming” (MATLAB Production Server).
  - The Java method must handle MATLAB exceptions and I/O exceptions.
- 5** Add the following class definition:

```
public class MPSCClientExample
{
}
```

This class now has a single `main` method that calls the generated class.

- 6** Add the `main()` method to the application.

```
public static void main(String[] args)
{
}
```

- 7** Add the following code to the top of the `main()` method to initialize the variables used by the application:

```
double[][] a1={{1,2,3},{3,2,1}};
double[][] a2={{4,5,6},{6,5,4}};
```

- 8** Instantiate a client object using the `MWHttpClient` constructor.

```
MWClient client = new MWHttpClient();
```

This class establishes an HTTP connection between the application and the server instance.

- 9** Call the `createProxy` method of the client object to create a dynamic proxy.

You must specify the URL of the deployable archive and the name of your interface class as arguments:

```
MATLABAddMatrix m = client.createProxy(new URL("http://localhost:9910/addmatrix"),
MATLABAddMatrix.class);
```

The URL value ("`http://localhost:9910/addmatrix`") used to create the proxy contains three parts:

- the server address (`localhost`).
- the port number (`9910`).
- the archive name (`addmatrix`).

For more information about the `createProxy` method, see the Javadoc included in the `matlabroot/toolbox/compiler_sdk/mps_client` folder.

- 10** Call the deployed MATLAB function in your Java application by calling the public method of the interface.

```
double[][] result = m.addmatrix(a1,a2);
```

- 11** Call the `close()` method of the client object to free system resources.

```
client.close();
```

- 12** Save the Java file.

The completed Java file should resemble the following:

```
import java.net.URL;
import java.io.IOException;
import com.mathworks.mps.client.MWClient;
import com.mathworks.mps.client.MWHttpClient;
import com.mathworks.mps.client.MATLABException;

interface MATLABAddMatrix
{
    double[][] addmatrix(double[][] a1, double[][] a2)
        throws MATLABException, IOException;
}

public class MPSClientExample {

    public static void main(String[] args){

        double[][] a1={{1,2,3},{3,2,1}};
        double[][] a2={{4,5,6},{6,5,4}};

        MWClient client = new MWHttpClient();

        try{
```

```
MATLABAddMatrix m = client.createProxy(new URL("http://localhost:9910/addmatrix"),
                                         MATLABAddMatrix.class);
double[][] result = m.addmatrix(a1,a2);

// Print the resulting matrix
printResult(result);

}catch(MATLABException ex){

    // This exception represents errors in MATLAB
    System.out.println(ex);
}catch(IOException ex){

    // This exception represents network issues.
    System.out.println(ex);
}finally{
    client.close();
}
}

private static void printResult(double[][] result){
    for(double[] row : result){
        for(double element : row){
            System.out.print(element + " ");
        }
        System.out.println();
    }
}
}
```

- 13** Compile the Java application, using the `javac` command or use the build capability of your Java IDE.

For example, enter the following at the system command prompt:

```
javac -classpath "matlabroot\toolbox\compiler_sdk\mps_client\java\mps_client.jar" MPSClientExample.java
```

- 14** Run the application using the `java` command or your IDE.

For example, enter the following at the system command prompt:

```
java -classpath .;"matlabroot\toolbox\compiler_sdk\mps_client\java\mps_client.jar" MPSClientExample
```

The application returns the following at the console:

```
5.0 7.0 9.0
9.0 7.0 5.0
```

## See Also

### More About

- “Bond Pricing Tool for Java Client” (MATLAB Production Server)
- “Create MATLAB Production Server Java Client Using MWHttpClient Class” (MATLAB Production Server)

## Create a C++ Client

This example shows how to write a MATLAB Production Server client using the C client API. The client application calls the `addmatrix` function you compiled in “Package Deployable Archives with Production Server Compiler App” and deployed in “Share Deployable Archive” (MATLAB Production Server).

Create a C++ MATLAB Production Server client application:

- 1 Create a file called `addmatrix_client.cpp`.
- 2 Using a text editor, open `addmatrix_client.cpp`.
- 3 Add the following include statements to the file:

```
#include <iostream>
#include <mps/client.h>
```

---

**Note** The header files for the MATLAB Production Server C client API are located in the `matlabroot/toolbox/compiler_sdk/mps_client/c/include/mps` folder.

---

- 4 Add the `main()` method to the application.

```
int main ( void )
{
}
```

- 5 Initialize the client runtime.

```
mpsClientRuntime* mpsruntime = mpsInitializeEx(MPS_CLIENT_1_1);
```

- 6 Create the client configuration.

```
mpsClientConfig* config;
mpsStatus status = mpsruntime->createConfig(&config);
```

- 7 Create the client context.

```
mpsClientContext* context;
status = mpsruntime->createContext(&context, config);
```

- 8 Create the MATLAB data to input to the function.

```
double a1[2][3] = {{1,2,3},{3,2,1}};
double a2[2][3] = {{4,5,6},{6,5,4}};

int numIn=2;
mpsArray** inVal = new mpsArray* [numIn];

inVal[0] = mpsCreateDoubleMatrix(2,3,mpsREAL);
inVal[1] = mpsCreateDoubleMatrix(2,3,mpsREAL);

double* data1 = (double *) ( mpsGetData(inVal[0]) );
double* data2 = (double *) ( mpsGetData(inVal[1]) );

for(int i=0; i<2; i++)
{
    for(int j=0; j<3; j++)
    {
        mpsIndex subs[] = { i, j };
        mpsIndex id = mpsCalcSingleSubscript(inVal[0], 2, subs);
        data1[id] = a1[i][j];
        data2[id] = a2[i][j];
    }
}
```

- ```

    }
  }

```
- 9** Create the MATLAB data to hold the output.
- ```

int numOut = 1;
mpsArray **outVal = new mpsArray* [numOut];

```
- 10** Call the deployed MATLAB function.

Specify the following as arguments:

- client context
- URL of the function
- Number of expected outputs
- Pointer to the mpsArray holding the outputs
- Number of inputs
- Pointer to the mpsArray holding the inputs

```

mpsStatus status = mpsruntime->feval(context,
    "http://localhost:9910/addmatrix/addmatrix",
    numOut, outVal, numIn, (const mpsArray**)inVal);

```

For more information about the `feval` function, see the reference material included in the `matlabroot/toolbox/compiler_sdk/mps_client` folder.

- 11** Verify that the function call was successful using an `if` statement.

```

if (status==MPS_OK)
{
}

```

- 12** Inside the `if` statement, add code to process the output.

```

double* out = mpsGetPr(outVal[0]);

for (int i=0; i<2; i++)
{
    for (int j=0; j<3; j++)
    {
        mpsIndex subs[] = {i, j};
        mpsIndex id = mpsCalcSingleSubscript(outVal[0], 2, subs);
        std::cout << out[id] << "\t";
    }
    std::cout << std::endl;
}

```

- 13** Add an `else` clause to the `if` statement to process any errors.

```

else
{
    mpsErrorInfo error;
    mpsruntime->getLastErrorInfo(context, &error);
    std::cout << "Error: " << error.message << std::endl;
    switch(error.type)
    {
        case MPS_HTTP_ERROR_INFO:
            std::cout << "HTTP: " << error.details.http.responseCode << ": "
                << error.details.http.responseMessage << std::endl;
        case MPS_MATLAB_ERROR_INFO:
            std::cout << "MATLAB: " << error.details.matlab.identifier

```

```

        << std::endl;
        std::cout << error.details.matlab.message << std::endl;
    case MPS_GENERIC_ERROR_INFO:
        std::cout << "Generic: " << error.details.general.genericErrorMsg
            << std::endl;
    }

    mpsruntime->destroyLastErrorInfo(&error);
}

```

**14** Free the memory used by the inputs.

```

for (int i=0; i<numIn; i++)
    mpsDestroyArray(inVal[i]);
delete[] inVal;

```

**15** Free the memory used by the outputs.

```

for (int i=0; i<numOut; i++)
    mpsDestroyArray(outVal[i]);
delete[] outVal;

```

**16** Free the memory used by the client runtime.

```

mpsruntime->destroyConfig(config);
mpsruntime->destroyContext(context);
mpsTerminate();

```

**17** Save the file.

The completed program should resemble the following:

```

#include <iostream>
#include <mps/client.h>

int main ( void )
{
    mpsClientRuntime* mpsruntime = mpsInitializeEx(MPS_CLIENT_1_1);

    mpsClientConfig* config;
    mpsStatus status = mpsruntime->createConfig(&config);

    mpsClientContext* context;
    status = mpsruntime->createContext(&context, config);

    double a1[2][3] = {{1,2,3},{3,2,1}};
    double a2[2][3] = {{4,5,6},{6,5,4}};

    int numIn=2;
    mpsArray** inVal = new mpsArray* [numIn];
    inVal[0] = mpsCreateDoubleMatrix(2,3,mpsREAL);
    inVal[1] = mpsCreateDoubleMatrix(2,3,mpsREAL);
    double* data1 = (double *) ( mpsGetData(inVal[0]) );
    double* data2 = (double *) ( mpsGetData(inVal[1]) );
    for(int i=0; i<2; i++)
    {
        for(int j=0; j<3; j++)
        {
            mpsIndex subs[] = { i, j };
            mpsIndex id = mpsCalcSingleSubscript(inVal[0], 2, subs);
            data1[id] = a1[i][j];
            data2[id] = a2[i][j];
        }
    }

    int numOut = 1;
    mpsArray **outVal = new mpsArray* [numOut];

    status = mpsruntime->feval(context,
        "http://localhost:9910/addmatrix/addmatrix",
        numOut, outVal, numIn, (const mpsArray **)inVal);

    if (status==MPS_OK)
    {
        double* out = mpsGetPr(outVal[0]);
    }
}

```

```

for (int i=0; i<2; i++)
{
    for (int j=0; j<3; j++)
    {
        mpsIndex subs[] = {i, j};
        mpsIndex id = mpsCalcSingleSubscript(outVal[0], 2, subs);
        std::cout << out[id] << "\t";
    }
    std::cout << std::endl;
}
}
else
{
    mpsErrorInfo error;
    mpsruntime->getLastErrorInfo(context, &error);
    std::cout << "Error: " << error.message << std::endl;

    switch(error.type)
    {
    case MPS_HTTP_ERROR_INFO:
        std::cout << "HTTP: "
            << error.details.http.responseCode
            << ": " << error.details.http.responseMessage
            << std::endl;
    case MPS_MATLAB_ERROR_INFO:
        std::cout << "MATLAB: " << error.details.matlab.identifier
            << std::endl;
        std::cout << error.details.matlab.message << std::endl;
    case MPS_GENERIC_ERROR_INFO:
        std::cout << "Generic: "
            << error.details.general.genericErrMsg
            << std::endl;
    }
    mpsruntime->destroyLastErrorInfo(&error);
}

for (int i=0; i<numIn; i++)
    mpsDestroyArray(inVal[i]);
delete[] inVal;

for (int i=0; i<numOut; i++)
    mpsDestroyArray(outVal[i]);
delete[] outVal;

mpsruntime->destroyConfig(config);
mpsruntime->destroyContext(context);
mpsTerminate();
}

```

**18** Compile the application.

To compile your client code, the compiler needs access to `client.h`. This header file is stored in `matlabroot/toolbox/compiler_sdk/mps_client/c/include/mps/`.

To link your application, the linker needs access to the following files stored in `matlabroot/toolbox/compiler_sdk/mps_client/c/`:

**Files Required for Linking**

Windows	UNIX/Linux	Mac OS X
<code>\$arch\lib \mpsclient.lib</code>	<code>\$arch/lib/ libprotobuf.so</code>	<code>\$arch/lib/ libprotobuf.dylib</code>
	<code>\$arch/lib/libcurl.so</code>	<code>\$arch/lib/ libcurl.dylib</code>
	<code>\$arch/lib/ libmwmpsclient.so</code>	<code>\$arch/lib/ libmwmpsclient.dylib</code>
	<code>\$arch/lib/ libmwcpp11compat.so</code>	

**19** Run the application.



To run your application, add the following files stored in *matlabroot/toolbox/compiler\_sdk/mps\_client/c/* to the application's path:

#### Files Required for Running

Windows	UNIX/Linux	Mac OS X
\$arch\lib \mpsclient.dll	\$arch/lib/ libprotobuf.so	\$arch/lib/ libprotobuf.dylib
\$arch\lib \libprotobuf.dll	\$arch/lib/libcurl.so	\$arch/lib/ libcurl.dylib
\$arch\lib\libcurl.dll	\$arch/lib/ libmwmpsclient.so	\$arch/lib/ libmwmpsclient.dylib
	\$arch/lib/ libmwcpp11compat.so	

The client invokes `addmatrix` function on the server instance and returns the following matrix at the console:

```
5.0 7.0 9.0
9.0 7.0 5.0
```

## Create a Python Client

This example shows how to write a MATLAB Production Server client using the Python client API. The client application calls the `addmatrix` function you compiled in “Package Deployable Archives with Production Server Compiler App” and deployed in “Share Deployable Archive” (MATLAB Production Server).

Create a Python MATLAB Production Server client application:

- 1 Copy the contents of the `matlabroot\toolbox\compiler_sdk\mps_clients\python` folder to your development environment.
- 2 Open a command line,
- 3 Change directories into the folder where you copied the MATLAB Production Server Python client.
- 4 Run the following command.

```
python setup.py install
```

- 5 Start the Python command line interpreter.
- 6 Enter the following import statements at the Python command prompt.

```
import matlab
from production_server import client
```

- 7 Open the connection to the MATLAB Production Server instance and initialize the client runtime.

```
client_obj = client.MWHttpClient("http://localhost:9910")
```

- 8 Create the MATLAB data to input to the function.

```
a1 = matlab.double([[1,2,3],[3,2,1]])
a2 = matlab.double([[4,5,6],[6,5,4]])
```

- 9 Call the deployed MATLAB function.

You must know the following:

- Name of the deployed archive
- Name of the function

```
client_obj.addmatrix.addmatrix(a1,a2)
```

```
matlab.double([[5.0,7.0,9.0],[9.0,7.0,5.0]])
```

The syntax for invoking a function is `client.archiveName.functionName(arg1, arg2, ..., [nargout=numOutArgs])`.

- 10 Close the client connection.

```
client_obj.close()
```