

nag_random_exp (g05dbc)

1. Purpose

nag_random_exp (g05dbc) returns a pseudo-random real number taken from a (negative) exponential distribution with mean a .

2. Specification

```
#include <nag.h>
#include <nagg05.h>

double nag_random_exp(double a)
```

3. Description

The distribution has PDF (probability density function)

$$\begin{aligned} f(x) &= \frac{1}{a}e^{-x/a} && \text{if } x > 0 \\ f(x) &= 0 && \text{otherwise.} \end{aligned}$$

The function returns the value $-a \ln y$, where y is a pseudo-random number from a uniform distribution over $(0,1)$, generated by nag_random_continuous_uniform (g05cac).

4. Parameters

a

Input: the parameter a of the distribution. If **a** is negative, its absolute value is used.

5. Error Indications and Warnings

None.

6. Further Comments

6.1. References

Kendall M G and Stuart A (1969) *The Advanced Theory of Statistics (Vol 1)* (3rd Edn) Griffin.
 Knuth D E (1981) *The Art of Computer Programming (Vol 2)* (2nd Edn) Addison-Wesley.

7. See Also

nag_random_continuous_uniform (g05cac)

8. Example

The example program prints the first five pseudo-random real numbers from a negative exponential distribution with mean 2.0, generated by nag_random_exp after initialisation by nag_random_init_repeatable (g05cbc).

8.1. Program Text

```
/* nag_random_exp(g05dbc) Example Program
 *
 * Copyright 1990 Numerical Algorithms Group.
 *
 * Mark 1, 1990.
 */

#include <nag.h>
#include <stdio.h>
#include <nag_stdlib.h>
#include <nagg05.h>

main()
{
    Integer seed = 0;
    Integer i;

    Vprintf("g05dbc Example Program Results\n");
    g05cbc(seed);
    for (i=1; i<=5; i++)
        Vprintf("%10.4f\n",g05dbc(2.0));
    exit(EXIT_SUCCESS);
}
```

8.2. Program Data

None.

8.3. Program Results

```
g05dbc Example Program Results
 0.4585
 2.9769
 1.9816
 2.9830
 0.2585
```
