# NAG C Library Function Document

## nag opt sparse mps read (e04mzc)

## 1 Purpose

nag\_opt\_sparse\_mps\_read (e04mzc) reads data for a sparse linear programming or quadratic programming problem from a file which is in standard or compatible MPSX input format.

## 2 Specification

## 3 Description

nag\_opt\_sparse\_mps\_read (e04mzc) reads linear programming (LP) or quadratic programming (QP) problem data from a file which is prepared in standard or compatible MPSX input format and then initializes n (the number of variables), m (the number of general linear constraints), the m by n matrix A, and the vectors l, u and c (stored in row **iobj** of A) for use with nag\_opt\_sparse\_convex\_qp (e04nkc), which is designed to solve problems of the form

$$\underset{x \in R''}{\text{minimize}} \quad c^{\mathsf{T}}x + \frac{1}{2}x^{\mathsf{T}}Hx \quad \text{ subject to } \quad l \leq \left\{ \begin{matrix} x \\ Ax \end{matrix} \right\} \leq u. \tag{1}$$

For LP problems, H = 0. For QP problems, a function must be provided to nag\_opt\_sparse\_convex\_qp (e04nkc) to compute Hx for any given vector x. (This is illustrated in Section 9.) The optional parameter **minimize** may be used to specify whether the objective function is to be minimized or maximized. The document for nag opt sparse convex qp (e04nkc) should be consulted for further details.

Since, in general, the exact size of the problem defined by an MPSX file may not be known in advance, the arrays returned by nag opt sparse mps read (e04mzc) are all allocated internally.

#### **MPSX Input Format**

The MPSX data file may only contain two types of line:

- 1. Indicator lines (specifying the type of data which is to follow).
- 2. Data lines (specifying the actual data).

The input file must not contain any blank lines. Any characters beyond column 80 are ignored. Indicator lines must not contain leading blank characters (in other words they must begin in column 1). The following displays the order in which the indicator lines must appear in the file:

```
NAME user-supplied name
ROWS
data line(s)

COLUMNS
data line(s)

RHS
data line(s)

RANGES (optional)
data line(s)

BOUNDS (optional)
data line(s)

FNDATA
```

The 'user-supplied name' specifies a name for the problem and must occupy columns 15–22. The name can either be blank or up to a maximum of 8 characters.

A data line follows the same fixed format made up of fields defined below. The contents of the fields may have different significance depending upon the section of data in which they appear.

	Field 1	Field 2	Field 3	Field 4	Field 5	Field 6
Columns	2-3	5-12	15-22	25-36	40-47	50-61
Contents	Code	Name	Name	Value	Name	Value

The names and codes consist of 'alphanumeric' characters (i.e., a-z, A-Z, 0-9, +, -, asterisk (\*), blank (), colon (:), dollar sign (\$) or full stop (.) only) and the names must not contain leading blank characters. Values may be entered in several equivalent forms. For example, 1.2345678, 1.2345678e + 0, 123.45678e - 2 and 12345678e - 07 all represent the same number. It is safest to include an explicit decimal point. Note that the lower case 'e' exponential notation is not standard MPSX, and if compatibility with other MPSX readers is required then the upper case notation should be used. The lower case notation is supported by nag\_opt\_sparse\_mps\_read (e04mzc) since this is the natural notation in a C programming language environment.

It is recommended that numeric values be *right-justified* in the 12-character field, with no trailing blanks. This is to ensure compatibility with other MPSX readers, some of which may, in certain situations, interpret trailing blanks as zeros. This can dramatically affect the interpretation of the value and is relevant if the value contains an exponent, or if it contains neither an exponent nor an explicit decimal point.

Comment lines are allowed in the data file. These must have an asterisk (\*) in column 1 and any characters in columns 2–80. In any data line, a dollar sign (\$) as the first character in Field 3 or 5 indicates that the information from that point through column 80 consists of comments.

Columns outside the six fields must be blank, except for columns 72–80, whose contents are ignored by the function. These columns may be used to enter a sequence number. A non-blank character outside the predefined six fields and columns 72–80 is considered to be a major error unless it is part of a comment.

#### **ROWS Data Lines**

These lines specify row (constraint) names and their inequality types (i.e., =,  $\geq$  or  $\leq$ ).

Field 1: defines the constraint type as follows (may be in column 2 or column 3):

- N free row, i.e., no constraint. It may be used to define the objective row.
- G greater than or equal to (i.e.,  $\geq$ ).
- L less than or equal to (i.e.,  $\leq$ ).
- E exactly equal to (i.e., =).

Field 2: defines the row name.

Row type N stands for 'Not binding', also known as 'Free'. It can be used to define the objective row. The objective row is a free row that specifies the vector c in the linear objective term  $c^Tx$ . It is taken to be the first free row, unless some other free row name is specified by the optional parameter **obj\_name** (see Section 10.2). Note that c is assumed to be zero if (for example) the line

```
%N%%DUMMYROW
```

(where % denotes a blank) appears in the ROWS section of the MPSX data file, and the row name DUMMYROW is omitted from the COLUMNS section.

#### **COLUMNS Data Lines**

These lines specify the names to be assigned to the variables (columns) in the general linear constraint matrix A, and define, in terms of column vectors, the actual values of the corresponding matrix elements.

- Field 1: blank (ignored).
- Field 2: gives the name of the column associated with the elements specified in the following fields.
- Field 3: contains the name of a row.
- Field 4: used in conjunction with Field 3; contains the value of the matrix element.
- Field 5: is optional (may be used like Field 3).
- Field 6: is optional (may be used like Field 4).

e04mzc.2 [NP3660/8]

Note that only the non-zero elements of A and c need to be specified in the COLUMNS section, as any zero elements of A are removed and any unspecified elements of c are assumed to be zero. In addition, any non-zero elements in the jth column of A must be grouped together before those in the (j+1)th column, for  $j=1,2,\ldots,\mathbf{n}-1$ . Non-zero elements within a column may however appear in any order.

#### **RHS Data Lines**

This section specifies the right-hand side values of the general linear constraint matrix A (if any). The lines specify the name to be given to the right-hand side (RHS) vector along with the numerical values of the elements of the vector, which may appear in any order. The data lines have exactly the same format as the COLUMNS data lines, except that the column name is replaced by the RHS name. Only the non-zero elements need be specified. Note that this section may be empty, in which case the RHS vector is assumed to be zero.

#### **RANGES Data Lines (optional)**

Ranges are used for constraints of the form  $l \le Ax \le u$ , where both l and u are finite. The effect of specifying a range  $r_j$  for constraint j depends on the type of the constraint (i.e., G, L or E), the sign of  $r_j$ , and the bound associated with the constraint in the RHS section. (Recall that this bound is taken to be zero if the constraint has no entry in the RHS section.) The various possibilities may be summarized as follows.

Row Type	Sign of $r_j$	Bound from RHS	Resultant $l_j$	Resultant $u_j$
G	+ or $-$	$l_{j}$	$l_j$	$l_j +  r_j $
L	+ or -	$u_j$	$u_j -  r_j $	$u_{j}$
E	+	$l_{j}$	$l_j$	$l_j + r_j$
E	_	$u_j$	$u_j -  r_j $	$u_j$

The data lines have exactly the same format as the COLUMNS data lines, except that the column name is replaced by the RANGE name.

### **BOUNDS Data Lines (optional)**

These lines specify limits on the values of the variables (l and u in  $l \le x \le u$ ). If the variable is not specified in the bound set then it is automatically assumed to lie between default lower and upper bounds (usually 0 and  $+\infty$ ). (These default bounds may be reset to the values specified by the optional parameters **col\_lo\_default** and **col\_up\_default**; see Section 10.2.) Like an RHS column which is given a name, the set of variables in one bound set is also given a name.

Field 1: specifies the type of bound or defines the variable type as follows:

LO lower bound. UP upper bound. FX fixed variable. FR free variable  $(-\infty \text{ to } +\infty)$ . MI lower bound is  $-\infty$ . PL upper bound is  $+\infty$ . This is the default variable type.

Field 2: identifies a name for the bound set.

Field 3: identifies the column name of the variable belonging to this set.

Field 4: identifies the value of the bound; this has a numerical value only in association with LO, UP, FX in Field 1, otherwise it is blank.

Field 5: is blank and ignored.

Field 6: is blank and ignored.

Note that if RANGES and BOUNDS sections are both present, the RANGES section must appear first.

#### MPSX and Integer Programming Problems

The MPSX input format allows the specification of *integer programming* (IP) problems in which some or all of the variables are constrained to take integer values within a specified range. nag\_opt\_sparse\_mps\_read (e04mzc) can read MPSX files defining IP problems in either the 'compatible' or 'standard' formats. However, any integer restrictions are ignored: any variable upon which such restrictions are defined by the file is simply treated as a continuous variable with upper and lower bounds as specified. The facility to read such files is offered to allow users to solve IP problems in their 'relaxed' LP or QP form using nag\_opt\_sparse\_convex\_qp (e04nkc). The compatible and standard MPSX forms are described below. Users not interested in this facility may skip the remainder of this section.

In the compatible MPSX format, the type of integer variables are defined in Field 1 of the BOUNDS section, that is:

Field 1: specifies the type of the integer variable as follows:

BV 0–1 integer variable (bound value is 1.0).

UI general integer variable (bound value is in Field 4).

In the standard MPSX format, the integer variables are treated the same as 'ordinary' bounded variables, in the BOUNDS section. Integer markers are, however, introduced in the COLUMNS section to specify the integer variables. The indicator lines for these markers are:

	Field 1	Field 2	Field 3	Field 4	Field 5	Field 6
Columns	2-3	5-12	15–22	25-36	40-47	50-61
Contents		name	'MARKER'		'INTORG'	

to mark the beginning of the integer variables and

	Field 1	Field 2	Field 3	Field 4	Field 5	Field 6
Columns	2-3	5-12	15-22	25-36	40-47	50-61
Contents		name	'MARKER'		'INTEND'	

to mark the end. That is, any variables between these markers are treated as integer variables. The *name* in Field 2 may be any name different from the preceding and following column names, the other entries in the indicator lines must be exactly as described above (including quotation marks). Note that if the INTEND indicator line is not specified then all columns between the INTORG indicator line and the end of the COLUMNS section are assumed to be integer variables. nag\_opt\_sparse\_mps\_read (e04mzc) accepts both standard and/or compatible MPSX format as a means of specifying integer variables.

## 4 References

IBM (1971) MPSX – Mathematical programming system *Program Number 5734 XM4* IBM Trade Corporation, New York

## 5 Arguments

1: **mps file** – const char \*

Input

On entry: the name of the MPSX data file. If **mps\_file** is a null pointer or null string, then the data is assumed to come from stdin.

2: **n** – Integer \*

On exit: the number of columns (variables) specified by the data file.

3: **m** – Integer \* Output

On exit: the number of rows specified by the data file. This is the number of general linear constraints in the problem, including the objective row.

4: **nnz** – Integer \* Output

On exit: the number of non-zeros in the problem (including the objective row).

e04mzc.4 [NP3660/8]

5: iobj - Integer \* Output

On exit: if **iobj** > 0, row **iobj** of A is a free row containing the non-zero coefficients of the vector c (the rows of A are indexed  $1, 2, \dots, m$ ). If iobj = 0, the coefficients of c are assumed to be zero.

a - double \*\* Output 6:

On exit: the nnz non-zero elements of A, ordered by increasing column index.

Sufficient memory is allocated internally by nag opt sparse mps read (e04mzc) and may be freed by the utility function nag opt sparse mps free (e04myc).

ha - Integer \*\* Output 7:

On exit: the **nnz** row indices of the non-zero elements of A.

Sufficient memory is allocated internally by nag opt sparse mps read (e04mzc) and may be freed by the utility function nag opt sparse mps free (e04myc).

ka - Integer \*\* Output

On exit: the n+1 indices indicating the beginning of each column of A in a. More precisely, ka[j-1] contains the index in a of the start of the jth column, for  $j=1,2,\ldots,n-1$ . Note that  $\mathbf{ka}[0] = 0$  and  $\mathbf{ka}[\mathbf{n}] = \mathbf{nnz}$ .

Sufficient memory is allocated internally by nag opt sparse mps read (e04mzc) and may be freed by the utility function nag opt sparse mps free (e04myc).

Output 9: **bl** – double \*\* Output

bu - double \*\* 10:

On exit: bl and bu hold the lower bounds and upper bounds, respectively, for all the variables and constraints, in the following order. The first  $\mathbf{n}$  elements contain the bounds on the variables x and the next **m** elements contain the bounds for the linear objective term  $c^{T}x$  and the general linear constraints Ax (if any). Note that an 'infinite' lower bound is indicated by  $\mathbf{bl}[j-1] = -10^{20}$ , an 'infinite' upper bound by  $\mathbf{bl}[j-1] = 10^{20}$ , and an equality constraint by  $\mathbf{bl}[j-1] = \mathbf{bu}[j-1]$ . (The lower bound for  $c^{T}x$ , stored in  $\mathbf{bl}[\mathbf{n} + \mathbf{iobj} - 1]$ , is set to  $-\mathbf{col\_up\_default}$ , and the upper bound, stored in bl[n + iobj - 1] is set to  $col\_up\_default$ ; the optional parameter  $col\_lo\_default$  has a default value of 10<sup>20</sup>; see Section 10.)

Sufficient memory is allocated internally by nag opt sparse mps read (e04mzc) and may be freed by the utility function nag opt sparse mps free (e04myc).

xs - double \*\* Output 11:

On exit: a set of initial values for the **n** variables and **m** constraints in the problem. More precisely, xs[j] = min(max(0.0, bl[j]), bu[j]), for j = 0, 1, ..., m + n - 1.

Sufficient memory is allocated internally by nag opt sparse mps read (e04mzc) and may be freed by the utility function nag opt sparse mps free (e04myc).

options - Nag E04 Opt \* 12:

Input/Output

On entry/on exit: a pointer to a structure of type Nag E04 Opt whose members are optional parameters for nag opt sparse mps read (e04mzc). These structure members offer the means of adjusting the parameter values used when reading in the MPSX file and on output will supply further details of the results. A description of the members of options is given below in Section 10.2.

If any of these optional parameters are required then the structure options should be declared and initialized by a call to nag opt init (e04xxc) and supplied as an argument to nag opt sparse mps read (e04mzc). However, if the optional parameters are not required the NAG defined null pointer, E04\_DEFAULT, can be used in the function call.

13: **fail** – NagError \*

Input/Output

The NAG error parameter, see the Essential Introduction.

## 5.1 Description of Printed Output

Results are printed out by default. The level of printed output can be controlled by the user with the structure members **list** and **output\_level** (see Section 10.2). If **list** = **NagTrue** then the parameter values to nag\_opt\_sparse\_mps\_read (e04mzc) are listed, whereas the printout of results is governed by **output\_level**. The default, **output\_level** = **Nag\_MPS\_Summary** gives the following information if the MPSX file has been read successfully:

- (a) the number of lines read.
- (b) the number of columns specified by the data. If any of these are specified as integer variables, the number of such variables is also reported. (However, recall that nag\_opt\_sparse\_mps\_read (e04mzc) will nevertheless regard such variables as continuous variables; see Section 3.)
- (c) the number of rows specified by the data. The objective row is counted amongst these.

In addition, the names of the problem, the objective row, the RHS set, the RANGES set, and the BOUNDS set read are listed. Unless specified otherwise by the optional parameters **prob\_name**, **obj\_name**, **rhs\_name**, **range\_name** and/or **bnd\_name** (see Section 10), these names will correspond to the first problem, objective row, etc., encountered in the MPSX file. Where no set was encountered (RANGES and BOUNDS are optional), a 'blank' is output.

Additionally, when **output\_level** = **Nag\_MPS\_List**, each line of the MPSX file is echoed as it is read. This may be useful as a debugging aid.

If **output\_level** = **Nag\_NoOutput** then printout will be suppressed; the user can print the information contained in (b) and (c) when nag opt sparse mps read (e04mzc) returns to the calling program.

## 6 Error Indicators and Warnings

## NE\_2\_REAL\_EE\_OPT\_ARG\_CONS

On entry,  $col_lo_default = \langle value \rangle$  while  $col_lo_default = \langle value \rangle$ . Constraint:  $col_lo_default \leq col_lo_default$ .

### NE ALLOC FAIL

Dynamic memory allocation failed.

#### **NE BAD PARAM**

On entry, parameter prob name had an illegal value.

## NE INT OPT ARG LT

On entry, **nrow approx** =  $\langle value \rangle$ . Constraint: **nrow approx**  $\geq 1$ .

#### NE INVALID REAL RANGE F

Value  $\langle value \rangle$  given to **est\_density** is not valid. Correct range is **est\_density** > 0.0.

#### NE NAMES NOT NAG MEM

**crnames** is not null but does not point to memory allocated by an earlier call to this function. This function does not accept user-allocated memory assigned to **crnames**.

#### NE NOT APPEND FILE

Cannot open file  $\langle string \rangle$  for appending.

e04mzc.6 [NP3660/8]

#### NE NOT CLOSE FILE

Cannot close file  $\langle string \rangle$ .

## NE\_NOT\_READ\_FILE

Cannot open file  $\langle string \rangle$  for reading.

### NE NULL ARGUMENT

Argument **n** is a null pointer. It should contain the address of a variable of type Integer.

### NE OPT NOT INIT

Options structure not initialized.

## 7 Accuracy

Not applicable.

#### **8 Further Comments**

None.

## 9 Example

There is one example program file, the main program of which calls both examples EX1 and EX2. Example 1 (EX1) shows the simple use of nag\_opt\_sparse\_mps\_read (e04mzc) where default values are used for all optional parameters, in conjunction with nag\_opt\_sparse\_convex\_qp (e04nkc). An example showing the use of optional parameters is given in EX2 and is described in Section 11.

#### Example 1 (EX1)

To solve the quadratic programming problem

minimize 
$$c^{T}x + \frac{1}{2}x^{T}Hx$$
 subject to  $\begin{aligned} l &\leq Ax \leq u, \\ -2 &\leq x \leq 2, \end{aligned}$ 

where

$$A = \begin{pmatrix} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 4 \\ 1 & 2 & 3 & 4 & -2 & 1 & 1 & 1 & 1 \\ 1 & -1 & 1 & 1 & -1 & 1 & 1 & 1 & 1 \end{pmatrix}, \quad l = \begin{pmatrix} -2 \\ -2 \\ -2 \end{pmatrix} \quad \text{and} \quad u = \begin{pmatrix} 1.5 \\ 1.5 \\ 4.0 \end{pmatrix}.$$

The optimal solution (to five significant figures) is

$$x^* = (2.0, -0.23333, -0.26667, -0.3, -0.1, 2.0, 2.0, -1.7777, -0.45555)^{\mathrm{T}}.$$

Three bound constraints and two general linear constraints are active at the solution. Note that, although the Hessian is positive semi-definite, the point  $x^*$  is the unique solution.

The function to calculate Hx (required by nag\_opt\_sparse\_convex\_qp (e04nkc)) is qphess for this example.

Note the use of nag\_opt\_sparse\_mps\_free (e04myc) in this example to free the memory returned by nag\_opt\_sparse\_mps\_read (e04mzc), once the problem has been solved.

The MPSX representation of the problem is given in Section 9.2.

## 9.1 Program Text

```
/* nag_opt_sparse_mps_read (e04mzc) Example Program.
* Copyright 1998 Numerical Algorithms Group.
* Mark 5, 1998.
* Mark 7 revised, 2001.
* Mark 8 revised, 2004.
 */
#include <nag.h>
#include <stdio.h>
#include <nag_stdlib.h>
#include <nag_string.h>
#include <nage04.h>
#ifdef
#ifdef \_cplusplus extern "C" {
#endif
 static void qphess(Integer ncolh, double x[], double hx[], Naq_Comm *comm);
#ifdef __cplusplus
#endif
static int ex1(void);
static int ex2(void);
int main(void)
  Integer exit_status_ex1=0;
  Integer exit_status_ex2=0;
  /* Two examples are called: ex1() uses the
   * default settings to read an MPSX file and
   * solve the problem, while ex2() uses the
   * options structure to obtain the column
   * and row names.
   * /
  Vprintf("nag_opt_sparse_mps_read (e04mzc) Example Program Results.\n");
  exit_status_ex1 = ex1();
  exit_status_ex2 = ex2();
  return exit_status_ex1 == 0 && exit_status_ex2 == 0 ? 0 : 1;
}
static int ex1(void)
  Integer exit_status=0, *ha, iobj, *ka, m, n, ncolh, ninf, nnz;
  NagError fail;
  double *a, *bl, *bu, obj, sinf, *xs;
  INIT_FAIL(fail);
  Vprintf("\nExample 1: default options used.\n");
  /* Read the MPSX file */
  /* nag_opt_sparse_mps_read (e04mzc).
   * Read MPSX data for sparse LP or QP problem from a file
  nag_opt_sparse_mps_read((char*)0, &n, &m, &nnz, &iobj, &a, &ha, &ka, &bl, &bu,
                           &xs, E04_DEFAULT, &fail);
```

e04mzc.8 [NP3660/8]

```
if (fail.code != NE_NOERROR)
      \label{lem:printf} \begin{tabular}{ll} Vprintf("Error from nag_opt\_sparse\_mps\_read (e04mzc).\n%s\n", \end{tabular} \label{lem:printf}
              fail.message);
      exit_status = 1;
      goto END;
  /* Solve the problem */
  ncolh = 5:
  /* nag_opt_sparse_convex_qp (e04nkc).
   * Solves sparse linear programming or convex quadratic
   * programming problems
  nag_opt_sparse_convex_qp(n, m, nnz, iobj, ncolh, qphess, a, ha, ka, bl, bu,
                             xs, &ninf, &sinf, &obj, EO4_DEFAULT, NAGCOMM_NULL,
                             &fail);
  if (fail.code != NE_NOERROR)
      Vprintf("Error from nag_opt_sparse_convex_qp (e04nkc).\n%s\n",
               fail.message);
      exit_status = 1;
  /* Free the memory allocated by nag_opt_sparse_mps_read (e04mzc) */
  /* nag_opt_sparse_mps_free (e04myc).
  * Free memory allocated by nag_opt_sparse_mps_read (e04mzc)
  */
 nag_opt_sparse_mps_free(&a, &ha, &ka, &bl, &bu, &xs);
END:
 return exit_status;
static void qphess(Integer ncolh, double x[], double hx[], Nag_Comm *comm)
  /* Function to compute H*x. */
  hx[0] = 2.0*x[0] + x[1] + x[2] + x[3] + x[4];
  hx[1] = x[0] + 2.0*x[1] + x[2] + x[3] + x[4];
  hx[2] = x[0] + x[1] + 2.0*x[2] + x[3] + x[4];
 hx[3] = x[0] + x[1] + x[2] + 2.0*x[3] + x[4];
 hx[4] = x[0] + x[1] + x[2] + x[3] + 2.0*x[4];
} /* qphess */
/* Example 2 */
static int ex2(void)
  Integer exit_status=0, *ha, iobj, *ka, m, n, ncolh, ninf, nnz;
  NagError fail;
  Nag_E04_Opt options;
  double *a, *bl, *bu, obj, sinf, *xs;
  INIT_FAIL(fail);
  Vprintf("\nExample 2: use of options structure.\n");
  /* Initialise the options structure and read MPSX data */
  /* nag_opt_init (e04xxc).
  * Initialization function for option setting
  nag_opt_init(&options);
  Vstrcpy(options.prob_name, "..QP 2..");
Vstrcpy(options.obj_name, "..COST..");
  /* nag_opt_sparse_mps_read (e04mzc), see above. */
  nag_opt_sparse_mps_read((char*)0, &n, &m, &nnz, &iobj, &a, &ha, &ka, &bl, &bu,
                            &xs, &options, &fail);
  if (fail.code != NE_NOERROR)
```

```
fail.message);
      exit_status = 1;
       goto END;
  /* Column and row names are now available via options */
  ncolh = 5;
  /* nag_opt_sparse_convex_qp (e04nkc), see above. */
  nag_opt_sparse_convex_qp(n, m, nnz, iobj, ncolh, qphess, a, ha, ka, bl, bu,
                              xs, &ninf, &sinf, &obj, &options, NAGCOMM_NULL,
                              &fail);
  if (fail.code != NE_NOERROR)
       Vprintf("Error from nag_opt_sparse_convex_qp (e04nkc).\n%s\n",
               fail.message);
       exit_status = 1;
  /* Free memory returned by nag_opt_sparse_mps_read (e04mzc) */
  /* nag_opt_sparse_mps_free (e04myc), see above. */
  nag_opt_sparse_mps_free(&a, &ha, &ka, &bl, &bu, &xs);
  /* Free memory in options (including column & row names) */
  /* nag_opt_free (e04xzc).
   * Memory freeing function for use with option setting
  nag_opt_free(&options, "all", &fail);
  if (fail.code != NE_NOERROR)
      Vprintf("Error from nag opt free (e04xzc).\n%s\n", fail.message);
      exit_status = 1;
       goto END;
    }
 END:
  return exit_status;
9.2 Program Data
* nag_opt_sparse_mps_read (e04mzc) Example Program Data
* Example 1 MPSX data
NAME
               QΡ
ROWS
L R1.....
L R2.....
 L R3.....
N Free Row
COLUMNS
    X1.... R1.... 1.0
X1.... R3.... 1.0
X2.... R1.... 1.0
                                        R2.....
Free Row
                                                             1.0
    X1.... R3....
X2... R1....
X2... R3....
X3... R1....
                                                             -4.0
                                          R2....
                                                              2.0
                                          Free Row R2.....
                             -1.0
                                                             -1.0
                           1.0
                                                              3.0
    X3..... R3.....
                              1.0
                                         Free Row
                                                             -1.0
    X4.... R1....
X4.... R3....
X5.... R1....
                                          R2....
                              1.0
                                                              4.0
                                          Free Row
R2.....
                             -1.0
                                                             -1.0
                              1.0
                                                             -2.0
    X5..... R3.....
                              1.0
                                          Free Row
                                                             -1.0
    X6..... R1.....
                              1.0
                                         R2....
                                                             1.0
    X6... R3... 1.0 Free Row X7... R1... 1.0 R2.... X7... R3... 1.0 Free Row X8... R1... 1.0 R2.... X8... R3... 1.0 Free Row X9... R1... 4.0 R2.... X9... R3... 1.0 Free Row X9... R3... 1.0 Free Row X9... R3... 1.0 Free Row
                                         Free Row
                                                             -1.0
                                                             1.0
                                                             -1.0
                                                             1.0
                                                            -0.1
                                                              1.0
                                          Free Row
                                                            -0.3
```

e04mzc.10 [NP3660/8]

```
RHS
    RHS1
              R1....
                           1.5
              R2....
    RHS1
                            1.5
    RHS1
              R3....
                            4.0
RANGES
    RANGE 1
             R1....
            R2....
    RANGE 1
                            3.5
    RANGE 1
             R3....
                            6.0
BOUNDS
LO BOUND
            х1....
                           -2.0
LO BOUND
            X2....
                           -2.0
LO BOUND
             хз.....
                           -2.0
LO BOUND
              x4....
                           -2.0
LO BOUND
                           -2.0
             X5....
LO BOUND
                           -2.0
             Х6....
LO BOUND
             х7....
                           -2.0
LO BOUND
             х8.....
             X9.....
                           -2.0
LO BOUND
UP BOUND
             X1....
                           2.0
            X2....
UP BOUND
                           2.0
                           2.0
UP BOUND
             хз.....
UP BOUND
              x4....
UP BOUND
                           2.0
             Х5....
UP BOUND
             Х6....
                           2.0
                           2.0
             х7....
UP BOUND
                           2.0
              х8.....
UP BOUND
UP BOUND
             х9....
ENDATA
* Example 2 MPSX data
NAME
             ..QP 2..
ROWS
L ..ROW1..
   ..ROW2..
L ..ROW3..
N FREE ROW
N ..COST..
                        1.0
COLUMNS
                                      ..ROW2..
    ...X1... ..ROW1..
                                                        1.0
                           1.0
    ...X1... ..ROW3..
                                                        -4.0
    ...X2... ..ROW1..
                                       ..ROW2..
                                                        2.0
    ...X2... ROW3..
...X3... ROW1..
...X3... ROW3..
                                      ..COST..
                           -1.0
                                                        -1.0
                         1.0
                                      ..ROW2..
..COST..
                                                        3.0
                                   ROW2...
..COST...
.ROW2...
.COST...
.ROW2...
.ROW2...
.ROW2...
                                                       -1.0
    ...x4... ..ROW1..
                           1.0
                                                        4.0
    ...X4... ..ROW3..
                                                       -1.0
                           -1.0
    ...X5....ROW1...
...X5....ROW3...
...X6....ROW1...
                           1.0
1.0
                                                        -2.0
                                                       -1.0
                           1.0
                                                        1.0
                           1.0
1.0
1.0
    ...x6... ..ROW3..
                                                       -1.0
    ...X7... ..ROW1..
                                                        1.0
                                      ..COST..
             ..ROW3..
    ...X7...
                                                        -1.0
    ...x8...
                                       ..ROW2..
                                                        1.0
    ...X8... ..ROW3..
                           1.0
                                       ..COST..
                                                       -0.1
    ...X9... ..ROW1..
                                       ..ROW2..
                            4.0
                                                        1.0
    ...x9... ..ROW3..
                                       ..COST..
                                                        -0.3
                            1.0
RHS
             ..ROW1..
    RHS1
                           1.5
    RHS1
             ..ROW2..
             ..ROW3..
                            4.0
    RHS1
RANGES
             ..ROW1..
                           3.5
    RANGE 1
    RANGE1 ..ROW2..
                           3.5
    RANGE 1
             ..ROW3..
                            6.0
BOUNDS
LO BOUND
                           -2.0
              ...X1...
LO BOUND
             ...X2...
                           -2.0
             ...X3...
LO BOUND
                           -2.0
LO BOUND
             ...X4...
                           -2.0
LO BOUND
              ...X5...
                           -2.0
```

```
LO BOUND ...X6... -2.0
LO BOUND ...X7... -2.0
LO BOUND ...X8... -2.0
LO BOUND ...X9... -2.0
UP BOUND ...X1... 2.0
UP BOUND ...X1... 2.0
UP BOUND ...X3... 2.0
UP BOUND ...X3... 2.0
UP BOUND ...X4... 2.0
UP BOUND ...X5... 2.0
UP BOUND ...X5... 2.0
UP BOUND ...X6... 2.0
UP BOUND ...X7... 2.0
UP BOUND ...X7... 2.0
UP BOUND ...X8... 2.0
UP BOUND ...X9... 2.0
UP BOUND ...X9... 2.0
UP BOUND ...X9... 2.0
```

## 9.3 Program Results

nag\_opt\_sparse\_mps\_read (e04mzc) Example Program Results.

Example 1: default options used.

```
Parameters to e04mzc
```

prob_name	(first)		
obj_name	(first)	rhs_name	(first)
range_name	(first)	bnd_name	(first)
col_lo_default	0.00e+00	col_up_default	1.00e+20
ncol_approx	500	nrow_approx	500
est_density	5.00e-02		
output_level Nag_MP	S_Summary		

MPS file successfully read.
Number of lines read: 57
Number of columns: 9
Number of rows: 4 (including objective row)

MPS Names Selected: Problem QP

Objective Free Row RHS RHS1
RANGES RANGE1 BOUNDS BOUND

outfile..... stdout

MPS data successfully assigned to problem data.

# Parameters to e04nkc

Problem type sparse QP Linear constraints 4	Number of variables Hessian columns	9
prob_name obj_name range_name crnames not supplied	rhs_namebnd_name	
minimize         Nag_TRUE           ftol         1.00e-06           fcheck         60           scale         Nag_ExtraScale           optim_tol         1.00e-06           crash         Nag_CrashTwice           partial_price         10           max_sb         6	start reset_ftol. factor_freq scale_tol. max_iter. crash_tol. pivot_tol.	Nag_Cold 10000 100 9.00e-01 65 1.00e-01 2.05e-11
inf_bound	<pre>inf_step lu_update_tol machine precision</pre>	1.00e+20 1.00e+01 1.11e-16

e04mzc.12 [NP3660/8]

```
Memory allocation:
                           Nag
                                 lambda.....
state....
                                                             Nag
          Step Ninf Sinf/Objective
  Itn
                                      Norm rg
        0.0e+00 0.000000e+00 0.0e+00
    0
Ttn
        0 -- Factorize detected a singular Hessian.
             Rank = 5, Diag, min diag = 0.0e+00, 3.3e-13.
                        0.000000e+00 6.3e+00
       0.0e+00
                  0
Itn 0 -- Feasible QP solution.
    1 7.5e-01 0
                       -4.375000e+00 3.5e-01
       1.0e+00
                  0
                       -4.400000e+00 0.0e+00
    2
    3
        1.9e-01
                   0
                       -4.700000e+00
                                      1.6e+00
      1.0e+00
                  0
                       -5.100000e+00
                                      2.3e-16
Itn
       5 -- Hessian numerically indefinite.
            Square of diag, min diag = -1.4e-14,
                                                 2.7e-13.
       2.3e-01
                0
0
                       -5.932500e+00
                                      3.7e+00
                       -6.179688e+00
       4.7e-01
    6
                                      1.1e+00
    7
       1.0e+00
                  0
                      -6.267162e+00 8.9e-16
    8
      8.1e-03
                  0 -6.532489e+00 1.4e+00
      6.3e-01
1.0e+00
1.0e+00
                  0 -7.5832300
0 -8.067718e+00
    9
                       -7.583236e+00
                                     1.1e-15
   10
                                      6.7e-16
                  0
                      -8.067778e+00
                                    1.1e-16
   11
Variable State
                    Value
                           Lower Bound Upper Bound Lagr Mult
                                                              Residual
         UL 2.00000e+00
SBS -2.33333e-01
                                                  -8.000e-01
X1..... UL
                           -2.0000e+00
                                       2.0000e+00
                                                              0.000e+00
                                                  0.000e+00
X2....
                           -2.0000e+00
                                        2.0000e+00
                                                              1.767e+00
X3..... SBS -2.66667e-01
                          -2.0000e+00
                                        2.0000e+00
                                                   9.615e-17
                                                              1.733e+00
X4....
         BS -3.00000e-01 -2.0000e+00
                                       2.0000e+00 0.000e+00
                                                              1.700e+00
X5..... SBS -1.00000e-01
                           -2.0000e+00
                                        2.0000e+00
                                                  0.000e+00
                                                              1.900e+00
                                        2.0000e+00 -9.000e-01
Х6....
                          -2.0000e+00
          UL
              2.00000e+00
                                                              0.000e+00
         UL 2.00000e+00
                          -2.0000e+00
                                       2.0000e+00 -9.000e-01
X7....
                                                              0.000e+00
X8..... SBS -1.77778e+00 -2.0000e+00
                                      2.0000e+00 3.899e-17
                                                             2.222e-01
X9..... BS -4.55556e-01
                                      2.0000e+00
                                                  1.504e-17 1.544e+00
                          -2.0000e+00
Constrnt State
                    Value
                          Lower Bound Upper Bound
                                                  Lagr Mult
                                                              Residual
             1.50000e+00 -2.0000e+00
                                       1.5000e+00 -6.667e-02 0.000e+00
R1..... UL
             1.50000e+00
R2....
          UL
                          -2.0000e+00
                                       1.5000e+00 -3.333e-02 0.000e+00
R3....
          ВS
               3.93333e+00
                          -2.0000e+00
                                       4.0000e+00
                                                  0.000e+00
                                                             -6.667e-02
Free Row
         BS -1.07856e+01
                                 None
                                             None
                                                  -1.000e+00
                                                             -1.079e+01
Exit after 11 iterations.
Optimal QP solution found.
Final QP objective value = -8.0677778e+00
Example 2: use of options structure.
Parameters to e04mzc
prob_name...............................QP 2...
rhs_name..... (first)
                      (first)
range_name.....
                                 bnd_name.....
                                                        (first)
col_lo_default.....
                      0.00e+00
                                 col_up_default..... 1.00e+20
ncol_approx.....
                          500
                                 nrow_approx.....
est_density..... 5.00e-02
output_level..... Nag_MPS_Summary
outfile.....
                        stdout
MPS file successfully read.
Number of lines read:
                         57
Number of columns:
                          9
Number of rows:
                          5 (including objective row)
MPS Names Selected:
Problem ..QP 2..
Objective .. COST.. RHS
                          RHS1
```

RANGES RANGE1 BOUNDS BOUND

MPS data successfully assigned to problem data.

# Parameters to e04nkc

```
Problem type..... sparse QP
                                 Number of variables.....
Linear constraints.....
                                 Hessian columns.....
prob_name...............................QP 2...
rhs_name..... RHS1
range_name...... RANGE1 crnames..... supplied
                                 bnd_name.....
minimize..... Nag_TRUE
                                 start.....
                                                        Nag_Cold
ftol..... 1.00e-06
                                 reset_ftol.....
                                                           10000
fcheck.....
                            60
                                 factor_freq.....
                                                            100
scale..... Nag_ExtraScale
                                 scale_tol....
                                                        9.00e-01
                                 max_iter....
optim_tol..... 1.00e-06
                                                             70
                                 crash_tol.....
                                                        1.00e-01
crash..... Nag_CrashTwice
partial_price.....
                                 pivot_tol....
                                                        2.05e-11
max_sb.....
inf_bound..... 1.00e+20
                                                       1.00e+20
                                 inf_step.....
lu_update_tol..... 1.00e+01
                                 machine precision.....
                                                        1.11e-16
print_level..... Nag_Soln_Iter
outfile.....
Memory allocation:
state.....
                           Nag
                                 lambda.....
                                                            Nag
          Step Ninf Sinf/Objective
                                     Norm rq
                        0.000000e+00
                                     0.0e+00
        0.0e+00
                Ω
        0 -- Factorize detected a singular Hessian.
            Rank = 5, Diag, min diag = 0.0e+00, 3.3e-13.
    0 0.0e+00 0
                       0.000000e+00 6.3e+00
Itn 0 -- Feasible QP solution.
       7.5e-01 0 -4.375000e+00
                                     3.5e-01
    1
    2
        1.0e+00
                   0
                       -4.400000e+00
                                     0.0e+00
                      -4.700000e+00
    3
       1.9e-01
                  0
                                     1.6e + 00
                      -5.100000e+00
       1.0e+00
                  0
                                     2.3e-16
It.n
       5 -- Hessian numerically indefinite.
             Square of diag, min diag = -1.4e-14,
                                                2.7e-13.
                       -5.932500e+00
    5
       2.3e-01
                  Ω
                                     3.7e+00
       4.7e-01
                   0
                       -6.179688e+00
                                     1.1e+00
    6
    7
       1.0e+00
                   0
                      -6.267162e+00 8.9e-16
    8
       8.1e-03
                   0
                       -6.532489e+00
                                     1.4e+00
    9
        6.3e-01
                   0
                       -7.583236e+00
                                     1.1e-15
        1.0e+00
                       -8.067718e+00
   10
                   0
                                     6.7e-16
       1.0e+00
                   0
                      -8.067778e+00
                                     1.1e-16
   11
Variable State
                    Value
                           Lower Bound Upper Bound
                                                  Lagr Mult
                                                              Residual
...X1... UL
              2.00000e+00
                           -2.0000e+00
                                       2.0000e+00
                                                 -8.000e-01
                                                             0.000e+00
...X2...
         SBS -2.33333e-01
                           -2.0000e+00
                                       2.0000e+00
                                                   0.000e+00
                                                             1.767e+00
...X3... SBS
             -2.66667e-01
                                       2.0000e+00
                                                   9.615e-17
                           -2.0000e+00
                                                             1.733e+00
...X4...
          BS
             -3.00000e-01
                           -2.0000e+00
                                       2.0000e+00
                                                   0.000e+00
                                                             1.700e+00
...X5...
         SBS
             -1.00000e-01
                           -2.0000e+00
                                       2.0000e+00
                                                   0.000e+00
                                                             1.900e+00
...X6...
         \mathtt{UL}
             2.00000e+00
                           -2.0000e+00
                                       2.0000e+00
                                                 -9.000e-01
                                                             0.000e+00
...x7...
         UL
             2.00000e+00
                           -2.0000e+00
                                       2.0000e+00
                                                 -9.000e-01
                                                             0.000e+00
...X8...
         SBS
                                       2.0000e+00
                                                   3.899e-17
             -1.77778e+00
                           -2.0000e+00
                                                             2.222e-01
...x9...
             -4.55556e-01
                           -2.0000e+00
                                       2.0000e+00
                                                   1.504e-17
                                                             1.544e+00
         BS
                           Lower Bound
                                      Upper Bound
Constrnt State
                    Value
                                                  Lagr Mult
                                                              Residual
             1.50000e+00
                                       1.5000e+00
..ROW1.. UL
                           -2.0000e+00
                                                             0.000e+00
                                                 -6.667e-02
                           -2.0000e+00
                                       1.5000e+00
..ROW2..
          UL
              1.50000e+00
                                                  -3.333e-02
                                                             0.000e+00
.ROW3..
          BS
               3.93333e+00
                           -2.0000e+00
                                       4.0000e+00
                                                  0.000e+00
                                                            -6.667e-02
FREE ROW
          BS
              0.00000e+00
                                 None
                                            None
                                                  0.000e+00
                                                             0.000e+00
..COST..
         BS -1.07856e+01
                                 None
                                            None -1.000e+00 -1.079e+01
```

Exit after 11 iterations.

e04mzc.14 [NP3660/8]

```
Optimal QP solution found.

Final QP objective value = -8.0677778e+00
```

## 10 Optional Parameters

A number of optional input and output parameters to nag\_opt\_sparse\_mps\_read (e04mzc) are available through the structure argument **options**, type **Nag\_E04\_Opt**. A parameter may be selected by assigning an appropriate value to the relevant structure member; those parameters not selected will be assigned default values. If no use is to be made of any of the optional parameters the user should use the NAG defined null pointer, E04\_DEFAULT, in place of **options** when calling nag\_opt\_sparse\_mps\_read (e04mzc); the default settings will then be used for all parameters.

Before assigning values to **options** directly the structure **must** be initialized by a call to the function nag opt\_init (e04xxc). Values may then be assigned to the structure members in the normal C manner.

Option settings may also be read from a text file using the function nag\_opt\_read (e04xyc) in which case initialization of the **options** structure will be performed automatically if not already done. Any subsequent direct assignment to the **options** structure must **not** be preceded by initialization.

## 10.1 Optional Parameter Checklist and Default Values

For easy reference, the following list shows the members of **options** which are valid for nag opt sparse mps read (e04mzc) together with their default values where relevant.

Boolean list Nag_OutputType output_level	Nag_True Nag_MPS_Summary
char outfile[80]	stdout
char prob_name[9]	'\0'
char obj_name[9]	'\0'
char rhs_name[9]	`\0 <b>`</b>
char range_name[9]	`\0 <b>`</b>
char bnd_name[9]	`\0 <b>`</b>
double col_lo_default	0.0
double col_up_default	$10^{20}$
Integer ncol_approx	500
Integer nrow_approx	500
double est_density	0.05
char **crnames	size $\mathbf{n} + \mathbf{m}$

### 10.2 Description of the Optional Arguments

```
list - Nag\_Boolean Default = NagTrue
```

On entry: if **list** = **NagTrue** the parameter settings in the call to nag\_opt\_sparse\_mps\_read (e04mzc) will be printed.

```
output_level - Nag_OutputType Default = Nag_MPS_Summary
```

On entry: the level of printout produced by nag\_opt\_sparse\_mps\_read (e04mzc). The following values are available:

Nag\_NoOutput No output.

Nag\_MPS\_Summary A summary of the dimensions of the problem read and a list of the 'MPSX

names' (problem name, objective row name, etc.).

Nag\_MPS\_List As Nag\_MPS\_Summary but each line of the MPSX file is echoed as it is read.

This can be useful for debugging the file.

Constraint: output level = Nag NoOutput, Nag MPS Summary or Nag MPS List.

outfile - const char[80]

Default = stdout

On entry: the name of the file to which results should be printed. If **outfile** $[0] = \langle 0 \rangle$  then the stdout stream is used.

prob\_name - charDefault:  $prob_name[0] = '0'$ obj\_name - charDefault:  $obj_name[0] = '0'$ rhs\_name - charDefault:  $rhs_name[0] = '0'$ range\_name - charDefault:  $range_name[0] = '0'$ bnd\_name - charDefault:  $prob_name[0] = '0'$ Default:  $prob_name[0] = '0'$ Default:  $prob_name[0] = '0'$ 

On entry: these options contain the names associated with the MPSX form of the problem. These names must be specified as follows:

prob\_name must contain the name of the problem to be read or be blank. The problem name is specified in the NAME indicator line (see Section 3) and if prob\_name is not blank, then nag\_opt\_sparse\_mps\_read (e04mzc) will search the MPSX file for the specified problem. If prob\_name is blank, then the first problem encountered will be read.

**obj\_name** must contain the name of the objective row or be blank (in which case the first objective free row is used).

**rhs\_name** must contain the name of the RHS set to be used or be blank (in which case the first RHS set is used).

**range\_name** must contain the name of the RANGES set to be used or be blank (in which case the first RANGES set, if any, is used).

**bnd\_name** must contain the name of the BOUNDS set to be used or be blank (in which case the first BOUNDS set, if any, is used).

Constraint: the names must be valid MPSX names, i.e., they must consist only of the 'alphanumeric' characters as specified in Section 3 and must not contain leading blank characters

*On exit*: the members contain the appropriate names as read from the MPSX file. Any names specified on input which are not found in the MPSX file are unchanged on exit but will give rise to an error exit from nag\_opt\_sparse\_mps\_read (e04mzc) (see Section 6).

If the MPSX file is successfully read, the **options** structure can be passed on to nag\_opt\_sparse\_convex\_qp (e04nkc), which will solve the problem specified by the file and which can make use of these structure members in its solution output.

 $col\_lo\_default - double$ 

Default = 0.0

On entry: the default lower bound to be used for the variables in the problem when none is specified in the BOUNDS section of the MPSX data file.

**col up default** – double

Default  $= 10^{20}$ 

On entry: the default upper bound to be used for the variables in the problem when none is specified in the BOUNDS section of the MPSX data file.

 $\textit{Constraint}: \ \textbf{col\_up\_default} \geq \textbf{col\_lo\_default}.$ 

e04mzc.16 [NP3660/8]

On entry: an estimate of the number of columns and rows in the problem. nag\_opt\_sparse\_mps\_read (e04mzc) is designed so that the problem size does not have to be known in advance, and allocates memory according to the data contained in the MPSX file. However, for very large problems, an advance estimate of the problem size might allow slightly more efficient memory usage to be achieved. See also the description of optional parameter **est\_density**.

Constraints:

 $\begin{array}{l} \mbox{ncol\_approx} > 0; \\ \mbox{nrow\_approx} > 0. \end{array}$ 

est density – double Default = 0.05

On entry: an estimate of the density of the nonzeros in the sparse matrix A, i.e., an estimate of  $\mathbf{nnz}/(\mathbf{n} \times \mathbf{m})$ . As with the optional parameters  $\mathbf{ncol\_approx}$  and  $\mathbf{nrow\_approx}$ , if this is known to be significantly larger or smaller than the default, then the user should specify an appropriate value to aid nag\_opt\_sparse\_mps\_read (e04mzc) in its memory management.

Constraint:  $est_density > 0.0$ .

**crnames** – char \*\* a Default memory  $\mathbf{n} + \mathbf{m}$  array of char \*

On exit: the MPSX names of all the variables and constraints in the problem in the following order. **crnames**[j-1] contains the name of the jth column, for  $j=1,2,\ldots,\mathbf{n}$ . **crnames** $[\mathbf{n}+i-1]$  contains the name of the ith row, for  $i=1,2,\ldots,\mathbf{m}$ . Each name is eight characters long, and includes any trailing blank characters which appear in the appropriate name field of the MPSX file.

Sufficient memory to hold the names is allocated internally by nag\_opt\_sparse\_mps\_read (e04mzc). The memory freeing function nag\_opt\_free (e04xzc) should be used to free this memory. Users should **not** use the standard C function free() for this purpose.

If, on return from nag\_opt\_sparse\_mps\_read (e04mzc), nag\_opt\_sparse\_convex\_qp (e04nkc) is called with **options** as an argument, and the memory pointed to by **crnames** has not been freed, nag\_opt\_sparse\_convex\_qp (e04nkc) will use the row and column names stored in **crnames** in its solution output.

### 11 Example 2 (EX2)

Example 2 (EX2) solves the same problem as Example 1 (EX1), described in Section 9, but shows the use of the **options** structure. Although the problem is the same, it is defined by a slightly modified MPSX file. The same qphess function is used as in ex1 (see Section 9).

The options structure is initialized by a call to nag\_opt\_init (e04xxc) and two of the optional parameters are set: **prob\_name** is set to "..QP 2.." so that nag\_opt\_sparse\_mps\_read (e04mzc) will attempt to read a problem of this name; and **obj\_name** is set to "..COST..". The MPSX file (see Section 9.2) contains an additional free row, named "FREE ROW". Since this is the first free row in the ROWS section of the MPSX file, by default it would be read as the objective row. However, since **obj\_name** is specified, nag opt sparse mps read (e04mzc) takes the second free row ("..COST..") as the objective row.

nag\_opt\_sparse\_mps\_read (e04mzc) is called to read the MPSX file, and this is followed by a call to nag\_opt\_sparse\_convex\_qp (e04nkc) to solve the problem. As the **options** structure is passed as an argument, the row and column names read from the file are stored in **crnames** and used in the solution output (see Section 9.3).

Finally, nag\_opt\_sparse\_mps\_free (e04myc) is called to free the problem arrays, and nag\_opt\_free (e04xzc) is called to free the memory in **options**.

See Section 9 for the example program.

[NP3660/8] e04mzc.17 (last)