

NAG C Library Function Document

zsyrk (f06zuc)

1 Purpose

zsyrk (f06zuc) performs one of the symmetric rank- k update operations

$$C \leftarrow \alpha AA^T + \beta C \text{ or } C \leftarrow \alpha A^T A + \beta C$$

where A is a complex matrix, C is an n by n complex symmetric matrix, and α and β are complex scalars.

2 Specification

```
#include <nag.h>
#include <nagf06.h>
```

```
void zsyrk (MatrixTriangle uplo, MatrixTranspose trans, Integer n, Integer k,
           Complex alpha, const Complex a[], Integer tda, Complex beta, Complex c[],
           Integer tdc)
```

3 Arguments

- 1: **uplo** – MatrixTriangle *Input*
On entry: specifies whether the upper or lower triangular part of C is stored as follows:
 if **uplo** = **UpperTriangle**, the upper triangular part of C is stored;
 if **uplo** = **LowerTriangle**, the lower triangular part of C is stored.
Constraint: **uplo** = **UpperTriangle** or **LowerTriangle**.
- 2: **trans** – MatrixTranspose *Input*
On entry: specifies the operation to be performed as follows:
 if **trans** = **NoTranspose**, $C \leftarrow \alpha AA^T + \beta C$;
 if **trans** = **Transpose**, $C \leftarrow \alpha A^T A + \beta C$.
Constraint: **trans** = **NoTranspose** or **Transpose**.
- 3: **n** – Integer *Input*
On entry: n , the order of the matrix C ; the number of rows of A if **trans** = **NoTranspose**, or the number of columns of A otherwise.
Constraint: $n \geq 0$.
- 4: **k** – Integer *Input*
On entry: k , the number of columns of A if **trans** = **NoTranspose**, or the number of rows of A otherwise.
Constraint: $k \geq 0$.
- 5: **alpha** – Complex *Input*
On entry: the scalar α .
- 6: **a**[\times **tda**] – const Complex *Input*
On entry: the matrix A ; A is n by k if **trans** = **NoTranspose**, or k by n otherwise.

- 7: **tda** – Integer *Input*
On entry: the second dimension of the array **a** as declared in the function from which zsyrc (f06zuc) is called.
Constraint: **tda** $\geq \max(1, \mathbf{k})$ if **trans** = **NoTranspose**; **tda** $\geq \max(1, \mathbf{n})$ otherwise.
- 8: **beta** – Complex *Input*
On entry: the scalar β .
- 9: **c**[**n** \times **tdc**] – Complex *Input/Output*
On entry: the n by n symmetric matrix C .
uplo = **UpperTriangle**
The upper triangle of C must be stored and the elements of the array below the diagonal are not referenced.
uplo = **LowerTriangle**
The lower triangle of C must be stored and the elements of the array above the diagonal are not referenced.
On exit: the updated matrix C .
- 10: **tdc** – Integer *Input*
On entry: the second dimension of the array **c** as declared in the function from which zsyrc (f06zuc) is called.
Constraint: **tdc** $\geq \max(1, \mathbf{n})$.

4 Error Indicators and Warnings

If a function is called with an invalid argument then an error message is output on stderr, giving the name of the function and the number of the first invalid argument, and execution is terminated.
