

nag_make_indices (m01zac)

1. Purpose

nag_make_indices (m01zac) inverts a permutation, and hence converts a rank vector to an index vector, or vice versa.

2. Specification

```
#include <nag.h>
#include <nag_stddef.h>
#include <nagm01.h>

void nag_make_indices(size_t ranks[], size_t n, NagError *fail)
```

3. Description

There are two common ways of describing a permutation using an Integer vector **ranks**. The first uses ranks: **ranks**[*i*] holds the index value to which the (*i* + 1)th data element should be moved in order to sort the data; in other words its rank in the sorted order. The second uses indices: **ranks**[*i*] holds the current index value of the data element which would occur in (*i* + 1)th position in sorted order. For example, given the values

3.5 5.9 2.9 0.5

to be sorted in ascending order, the ranks would be

2 3 1 0

and the indices would be

3 2 0 1.

The m01d- functions generate ranks, and the m01e- functions require indices to be supplied to specify the re-ordering. However if it is desired simply to refer to the data in sorted order without actually re-ordering them, indices are more convenient than ranks (see the example program). **nag_make_indices** can be used to convert ranks to indices, or indices to ranks, as the two permutations are inverses of one another.

4. Parameters

ranks[n]

Input: **ranks** must contain a permutation of the Integers 0 to **n** – 1.
Output: **ranks** contains the inverse permutation.

n

Input: the length of the array **ranks**.

fail

The NAG error parameter, see the Essential Introduction to the NAG C Library.

5. Error Indications and Warnings

NE_INT_ARG_LT

On entry, **n** must not be less than 0: **n** = ⟨value⟩.

NE_INT_ARG_GT

On entry, **n** must not be greater than ⟨value⟩: **n** = ⟨value⟩.

n is limited to an implementation-dependent size which is printed in the error message.

NE_BAD_RANK

Invalid **ranks** vector.

Elements of **ranks** contain a value outside the range 0 to **n** – 1 or contain a repeated value. **ranks** does not contain a permutation of the Integers 0 to **n** – 1; on exit these elements are usually corrupted.

6. Further Comments

None.

7. See Also

None.

8. Example

The example program reads a matrix of real numbers and prints its rows with the elements of the 1st column in ascending order as ranked by nag_rank_sort (m01dsc). The program first calls nag_rank_sort (m01dsc) to rank the rows, and then calls nag_make_indices to convert the rank vector to an index vector, which is used to refer to the rows in sorted order.

8.1. Program Text

```
/* nag_make_indices(m01zac) Example Program
 *
 * Copyright 1990 Numerical Algorithms Group.
 *
 * Mark 2 revised, 1992.
 */

#include <nag.h>
#include <stdio.h>
#include <nag_stdl�.h>
#include <nag_stddef.h>
#include <nagm01.h>

#ifndef NAG_PROTO
static Integer compare(const Pointer a,const Pointer b)
#else
    static Integer compare(a,b)
    Pointer a, b;
#endif
{
    double x = *((double *)a);
    double y = *((double *)b);
    return (x<y ? -1 : (x==y ? 0 : 1));
}

#define MMAX 20
#define NMAX 20

main()
{
    double vec[MMAX][NMAX];
    size_t i, j, m, n, rank[MMAX];
    static NagError fail;

    fail.print = TRUE;
    /* Skip heading in data file */
    Vscanf("%*[^\n]");
    Vprintf("m01zac Example Program Results\n");
    Vscanf("%d%d", &m, &n);
    if (m>=0 && m<=MMAX && n>=0 && n<=NMAX)
    {
        for (i=0; i<m; ++i)
            for (j=0; j<n; ++j)
                Vscanf("%lf", &vec[i][j]);
        m01dsc((Pointer) vec, m, (ptrdiff_t)(NMAX*sizeof(double)), compare,
                Nag_Ascending, rank, &fail);
        if (fail.code != NE_NOERROR)
            exit(EXIT_FAILURE);
        m01zac(rank, m, &fail);
        if (fail.code != NE_NOERROR)
            exit(EXIT_FAILURE);
        Vprintf("Matrix with rows sorted according to column 1\n");
    }
}
```

```

        for (i=0; i<m; ++i)
        {
            for (j=0; j<n; ++j)
                Vprintf(" %7.1f ", vec[rank[i]][j]);
            Vprintf("\n");
        }
        exit(EXIT_SUCCESS);
    }
else
{
    Vfprintf(stderr, "Data error: program terminated\n");
    exit(EXIT_FAILURE);
}
}

```

8.2. Program Data

```

m01zac Example Program Data
12 3
6.0 5.0 4.0
5.0 2.0 1.0
2.0 4.0 9.0
4.0 9.0 6.0
4.0 9.0 5.0
4.0 1.0 2.0
3.0 4.0 1.0
2.0 4.0 6.0
1.0 6.0 4.0
9.0 3.0 2.0
6.0 2.0 5.0
4.0 9.0 6.0

```

8.3. Program Results

```

m01zac Example Program Results
Matrix with rows sorted according to column 1
    1.0      6.0      4.0
    2.0      4.0      9.0
    2.0      4.0      6.0
    3.0      4.0      1.0
    4.0      9.0      6.0
    4.0      9.0      5.0
    4.0      1.0      2.0
    4.0      9.0      6.0
    5.0      2.0      1.0
    6.0      5.0      4.0
    6.0      2.0      5.0
    9.0      3.0      2.0

```
