

E04NDF – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

To supply optional parameters to E04NCF from an external file.

2 Specification

```
SUBROUTINE E04NDF(IOPTNS, INFORM)
  INTEGER          IOPTNS, INFORM
```

3 Description

E04NDF may be used to supply values for optional parameters to E04NCF. E04NDF reads an external file and each line of the file defines a single optional parameter. It is only necessary to supply values for those parameters whose values are to be different from their default values.

Each optional parameter is defined by a single character string of up to 72 characters, consisting of one or more items. The items associated with a given option must be separated by spaces, or equal signs [=]. Alphabetic characters may be upper or lower case. The string

```
Print level = 1
```

is an example of a string used to set an optional parameter. For each option the string contains one or more of the following items:

- (a) A mandatory keyword.
- (b) A phrase that qualifies the keyword.
- (c) A number that specifies an INTEGER or *real* value. Such numbers may be up to 16 contiguous characters in Fortran 77's I, F, E or D formats, terminated by a space if this is not the last item on the line.

Blank strings and comments are ignored. A comment begins with an asterisk (*) and all subsequent characters in the string are regarded as part of the comment.

The file containing the options must start with **begin** and must finish with **end**. An example of a valid options file is:

```
Begin * Example options file
  Print level = 5
End
```

Normally each line of the file is printed as it is read, on the current advisory message unit (see X04ABF), but printing may be suppressed using the keyword **nolist**. To suppress printing of **begin**, **nolist** must be the first option supplied as in the file:

```
Begin
  Nolist
  Print level = 5
End
```

Printing will automatically be turned on again after a call to E04NCF and may be turned on again at any time by the user by using the keyword **list**.

Optional parameter settings are preserved following a call to E04NCF, and so the keyword **defaults** is provided to allow the user to reset all the optional parameters to their default values prior to a subsequent call to E04NCF.

A complete list of optional parameters, their abbreviations, synonyms and default values is given in Section 11 of the document for E04NCF.

4 References

None.

5 Parameters

1: IOPTNS — INTEGER *Input*

On entry: the unit number of the options file to be read.

Constraint: $0 \leq \text{IOPTNS} \leq 99$.

2: INFORM — INTEGER *Output*

On exit: contains zero if an options file with the correct structure has been read and a value > 0 otherwise, as indicated below.

INFORM = 1

IOPTNS is not in the range $[0, 99]$.

INFORM = 2

begin was found, but end-of-file was found before **end** was found.

INFORM = 3

end-of-file was found before **begin** was found.

6 Error Indicators and Warnings

If a line is not recognized as a valid option, then a warning message is output on the current advisory message unit (see X04ABF).

7 Accuracy

Not applicable.

8 Further Comments

E04NEF may also be used to supply optional parameters to E04NCF.

9 Example

To minimize the quadratic function $c^T x + \frac{1}{2} x^T A x$, where

$$c = (-4.0, -1.0, -1.0, -1.0, -1.0, -1.0, -1.0, -0.1, -0.3)^T,$$

$$A = \begin{pmatrix} 2 & 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 2 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 1 & 2 & 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 2 & 1 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 & 2 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

subject to the bounds

$$\begin{aligned} -2 &\leq x_1 \leq 2 \\ -2 &\leq x_2 \leq 2 \\ -2 &\leq x_3 \leq 2 \\ -2 &\leq x_4 \leq 2 \\ -2 &\leq x_5 \leq 2 \\ -2 &\leq x_6 \leq 2 \\ -2 &\leq x_7 \leq 2 \\ -2 &\leq x_8 \leq 2 \\ -2 &\leq x_9 \leq 2 \end{aligned}$$

and to the general constraints

$$\begin{aligned} -2.0 &\leq x_1 + x_2 + x_3 + x_4 + x_5 + x_6 + x_7 + x_8 + 4x_9 \leq 1.5 \\ -2.0 &\leq x_1 + 2x_2 + 3x_3 + 4x_4 - 2x_5 + x_6 + x_7 + x_8 + x_9 \leq 1.5 \\ -2.0 &\leq x_1 - x_2 + x_3 - x_4 + x_5 + x_6 + x_7 + x_8 + x_9 \leq 4.0 \end{aligned}$$

The initial point, which is feasible, is

$$x_0 = (0, 0, 0, 0, 0, 0, 0, 0, 0)^T,$$

and $F(x_0) = 0$.

The optimal solution (to five figures) is

$$x^* = (2.0, -0.23333, -0.26667, -0.3, -0.1, 2.0, 2.0, -1.7777, -0.45555)^T,$$

and $F(x^*) = -8.0678$. Three bound constraints and two general constraints are active at the solution. Note that, although the Hessian matrix is positive semi-definite, the point x^* is unique.

In this example the options file read by E04NDF is appended to the data file for the program (see Section 9.2). It would usually be more convenient in practice to keep the data file and the options file separate.

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      E04NDF Example Program Text
*      Mark 16 Release. NAG Copyright 1993.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER       (NIN=5,NOUT=6)
      INTEGER          MMAX, NMAX, NCMAX
      PARAMETER       (MMAX=10,NMAX=10,NCMAX=10)
      INTEGER          LDC, LDA
      PARAMETER       (LDC=NCMAX,LDA=MMAX)
      INTEGER          LIWORK, LWORK
      PARAMETER       (LIWORK=100,LWORK=1000)
*      .. Local Scalars ..
      real            OBJ
      INTEGER          I, IFAIL, INFORM, ITER, J, M, N, NCLIN
*      .. Local Arrays ..
      real            A(LDA,NMAX), B(MMAX), BL(NMAX+NCMAX),
+                   BU(NMAX+NCMAX), C(LDC,NMAX), CLAMDA(NMAX+NCMAX),
+                   CVEC(NMAX), WORK(LWORK), X(NMAX)
      INTEGER          ISTATE(NMAX+NCMAX), IWORK(LIWORK), KX(NMAX)
*      .. External Subroutines ..
      EXTERNAL        E04NCF, E04NDF, E04NEF, X04ABF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'E04NDF Example Program Results'
```

```

*      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) M, N, NCLIN
      IF (M.LE.MMAX .AND. N.LE.NMAX .AND. NCLIN.LE.NCMAX) THEN
*
*          Read CVEC, A, C, BL, BU and X from data file
*
      READ (NIN,*) (CVEC(I),I=1,N)
      READ (NIN,*) ((A(I,J),J=1,N),I=1,M)
      READ (NIN,*) ((C(I,J),J=1,N),I=1,NCLIN)
      READ (NIN,*) (BL(I),I=1,N+NCLIN)
      READ (NIN,*)
      READ (NIN,*) (BU(I),I=1,N+NCLIN)
      READ (NIN,*)
      READ (NIN,*) (X(I),I=1,N)
*
*          Set two options using E04NEF
*
      CALL E04NEF(' Infinite Bound Size = 1.0D+25 ')
*
      CALL E04NEF(' Problem Type = QP2 ')
*
*          Set the unit number for advisory messages to NOUT
*
      CALL X04ABF(1,NOUT)
*
*          Read the options file for the remaining options
*
      CALL E04NDF(NIN,INFORM)
*
      IF (INFORM.NE.0) THEN
+         WRITE (NOUT,99999) 'E04NDF terminated with INFORM = ',
+           INFORM
          STOP
      END IF
*
*          Solve the problem
*
      IFAIL = -1
*
      CALL E04NCF(M,N,NCLIN,LDC,LDA,C,BL,BU,CVEC,ISTATE,KX,X,A,B,
+              ITER,OBJ,CLAMDA,IWORK,LIWORK,WORK,LWORK,IFAIL)
*
      END IF
      STOP
*
99999 FORMAT (1X,A,I3)
      END

```

9.2 Program Data

E04NDF Example Program Data

9	9	3	:Values of M, N and NCLIN							
-4.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-0.1	-0.3	:End of CVEC
2.0	1.0	1.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	
1.0	2.0	1.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	
1.0	1.0	2.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	
1.0	1.0	1.0	2.0	1.0	0.0	0.0	0.0	0.0	0.0	

```

1.0  1.0  1.0  1.0  2.0  0.0  0.0  0.0  0.0
0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0
0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0
0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0
0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0      :End of matrix A
1.0  1.0  1.0  1.0  1.0  1.0  1.0  1.0  4.0
1.0  2.0  3.0  4.0 -2.0  1.0  1.0  1.0  1.0
1.0 -1.0  1.0 -1.0  1.0  1.0  1.0  1.0  1.0      :End of matrix C
-2.0 -2.0 -2.0 -2.0 -2.0 -2.0 -2.0 -2.0 -2.0 -2.0 -2.0 -2.0
                                           :End of BL
2.0  2.0  2.0  2.0  2.0  2.0  2.0  2.0  2.0  1.5  1.5  4.0
                                           :End of BU
0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0      :End of X
Begin  Example options file for E04NDF
      Iteration Limit = 30      * (Default = 90)
End

```

9.3 Program Results

E04NDF Example Program Results

Calls to E04NEF

Infinite Bound Size = 1.0E+25
Problem Type = QP2

OPTIONS file

Begin Example options file for E04NDF
 Iteration Limit = 30 * (Default = 90)
End

*** E04NCF
*** Start of NAG Library implementation details ***

Implementation title: Generalised Base Version
Precision: FORTRAN double precision
Product Code: FLBAS19D
Mark: 19A

*** End of NAG Library implementation details ***

Parameters

Problem type.....	QP2	Hessian.....	NO
Linear constraints....	3	Feasibility tolerance..	1.05E-08
Variables.....	9	Crash tolerance.....	1.00E-02
Objective matrix rows..	9	Rank tolerance.....	1.05E-07
Infinite bound size....	1.00E+25	COLD start.....	
Infinite step size....	1.00E+25	EPS (machine precision)	1.11E-16

```

Print level.....          10          Feasibility phase itns.          60
Monitoring file.....       -1          Optimality phase itns.          30

```

```

Workspace provided is      IWORK(    100), WORK(    1000).
To solve problem we need  IWORK(     9), WORK(     270).

```

Rank of the objective function data matrix = 5

Itn	Step	Ninf	Sinf/Objective	Norm Gz
0	0.0E+00	0	0.000000E+00	4.5E+00
1	7.5E-01	0	-4.375000E+00	5.0E-01
2	1.0E+00	0	-4.400000E+00	2.8E-17
3	3.0E-01	0	-4.700000E+00	8.9E-01
4	1.0E+00	0	-5.100000E+00	2.4E-17
5	5.4E-01	0	-6.055714E+00	1.7E+00
6	1.1E-02	0	-6.113326E+00	1.6E+00
7	1.1E-01	0	-6.215049E+00	1.2E+00
8	1.0E+00	0	-6.538008E+00	1.8E-17
9	6.5E-01	0	-7.428704E+00	7.2E-02
10	1.0E+00	0	-7.429717E+00	1.8E-17
11	1.0E+00	0	-8.067718E+00	1.8E-17
12	1.0E+00	0	-8.067778E+00	1.8E-17

Exit from QP problem after 12 iterations.

Varbl	State	Value	Lower Bound	Upper Bound	Lagr Mult	Slack
V 1	UL	2.00000	-2.00000	2.00000	-0.8000	.
V 2	FR	-0.233333	-2.00000	2.00000	.	1.767
V 3	FR	-0.266667	-2.00000	2.00000	.	1.733
V 4	FR	-0.300000	-2.00000	2.00000	.	1.700
V 5	FR	-0.100000	-2.00000	2.00000	.	1.900
V 6	UL	2.00000	-2.00000	2.00000	-0.9000	.
V 7	UL	2.00000	-2.00000	2.00000	-0.9000	.
V 8	FR	-1.77778	-2.00000	2.00000	.	0.2222
V 9	FR	-0.455556	-2.00000	2.00000	.	1.544

L Con	State	Value	Lower Bound	Upper Bound	Lagr Mult	Slack
L 1	UL	1.50000	-2.00000	1.50000	-6.6667E-02	1.1102E-15
L 2	UL	1.50000	-2.00000	1.50000	-3.3333E-02	-4.4409E-16
L 3	FR	3.93333	-2.00000	4.00000	.	6.6667E-02

Exit E04NCF - Optimal QP solution.

Final QP objective value = -8.067778