

G03EFF – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

G03EFF performs K -means cluster analysis.

2 Specification

```

SUBROUTINE G03EFF(WEIGHT, N, M, X, LDX, ISX, NVAR, K, CMEANS, LDC,
1          WT, INC, NIC, CSS, CSW, MAXIT, IWK, WK, IFAIL)
  INTEGER      N, M, LDX, ISX(M), NVAR, K, LDC, INC(N), NIC(K),
1          MAXIT, IWK(N+3*K), IFAIL
  real         X(LDX,M), CMEANS(LDC,NVAR), WT(*), CSS(K),
1          CSW(K), WK(N+2*K)
  CHARACTER*1  WEIGHT

```

3 Description

Given n objects with p variables measured on each object, x_{ij} for $i = 1, 2, \dots, n$; $j = 1, 2, \dots, p$, G03EFF allocates each object to one of K groups or clusters to minimize the within-cluster sum of squares:

$$\sum_{k=1}^K \sum_{i \in S_k} \sum_{j=1}^p (x_{ij} - \bar{x}_{kj})^2,$$

where S_k is the set of objects in the k th cluster and \bar{x}_{kj} is the mean for the variable j over cluster k . This is often known as K -means clustering.

In addition to the data matrix, a K by p matrix giving the initial cluster centres for the K clusters is required. The objects are then initially allocated to the cluster with the nearest cluster mean. Given the initial allocation, the procedure is to iteratively search for the K -partition with locally optimal within-cluster sum of squares by moving points from one cluster to another.

Optionally, weights for each object, w_i , can be used so that the clustering is based on within-cluster weighted sums of squares:

$$\sum_{k=1}^K \sum_{i \in S_k} \sum_{j=1}^p w_i (x_{ij} - \tilde{x}_{kj})^2,$$

where \tilde{x}_{kj} is the weighted mean for variable j over cluster k .

The routine is based on the algorithm of Hartigan and Wong [2].

4 References

- [1] Everitt B S (1974) *Cluster Analysis* Heinemann
- [2] Hartigan J A and Wong M A (1979) Algorithm AS136: A K-means clustering algorithm *Appl. Statist.* **28** 100–108
- [3] Kendall M G and Stuart A (1976) *The Advanced Theory of Statistics (Volume 3)* Griffin (3rd Edition)
- [4] Krzanowski W J (1990) *Principles of Multivariate Analysis* Oxford University Press

5 Parameters

- 1:** WEIGHT — CHARACTER*1 *Input*
On entry: indicates if weights are to be used.
 If WEIGHT = 'U' (Unweighted), then no weights are used.
 If WEIGHT = 'W' (Weighted), then weights are used and must be supplied in WT.
Constraint: WEIGHT = 'U' or 'W'.
- 2:** N — INTEGER *Input*
On entry: the number of objects, n .
Constraint: $N > 1$.
- 3:** M — INTEGER *Input*
On entry: the total number of variables in array X.
Constraint: $M \geq \text{NVAR}$.
- 4:** X(LDX,M) — *real* array *Input*
On entry: X(i, j) must contain the value of the j th variable for the i th object for $i = 1, 2, \dots, n$; $j = 1, 2, \dots, M$.
- 5:** LDX — INTEGER *Input*
On entry: the first dimension of the array X as declared in the (sub)program from which G03EFF is called.
Constraint: $\text{LDX} \geq N$.
- 6:** ISX(M) — INTEGER array *Input*
On entry: ISX(j) indicates whether or not the j th variable is to be included in the analysis. If ISX(j) > 0, then the variable contained in the j th column of X is included, for $j = 1, 2, \dots, M$.
Constraint: ISX(j) > 0 for NVAR values of j .
- 7:** NVAR — INTEGER *Input*
On entry: the number of variables included in the sums of squares calculations, p .
Constraint: $1 \leq \text{NVAR} \leq M$.
- 8:** K — INTEGER *Input*
On entry: the number of clusters, K .
Constraint: $K \geq 2$.
- 9:** CMEANS(LDC,NVAR) — *real* array *Input/Output*
On entry: CMEANS(i, j) must contain the value of the j th variable for the i th initial cluster centre, for $i = 1, 2, \dots, K$; $j = 1, 2, \dots, p$.
On exit: CMEANS(i, j) contains the value of the j th variable for the i th computed cluster centre, for $i = 1, 2, \dots, K$; $j = 1, 2, \dots, p$.
- 10:** LDC — INTEGER *Input*
On entry: the first dimension of the array CMEANS as declared in the (sub)program from which G03EFF is called.
Constraint: $\text{LDC} \geq K$.

- 11:** WT(*) — *real* array *Input*
Note: the dimension of the array WT must be at least N if WEIGHT = 'W', and must be at least 1 otherwise.
On entry: if WEIGHT = 'W' then the first n elements of WT must contain the weights to be used. If $WT(i) = 0.0$, then the i th observation is not included in the analysis. The effective number of observation is the sum of the weights. If WEIGHT = 'U' then WT is not referenced and the effective number of observations is n .
Constraint: if WEIGHT = 'W' then $WT(i) \geq 0.0$, for $i = 1, 2, \dots, n$ and $WT(i) > 0.0$ for at least two values of i .
- 12:** INC(N) — INTEGER array *Output*
On exit: INC(i) contains the cluster to which the i th object has been allocated, for $i = 1, 2, \dots, n$.
- 13:** NIC(K) — INTEGER array *Output*
On exit: NIC(i) contains the number of objects in the i th cluster, for $i = 1, 2, \dots, K$.
- 14:** CSS(K) — *real* array *Output*
On exit: CSS(i) contains the within-cluster (weighted) sum of squares of the i th cluster, for $i = 1, 2, \dots, K$.
- 15:** CSW(K) — *real* array *Output*
On exit: CSW(i) contains the within-cluster sum of weights of the i th cluster, for $i = 1, 2, \dots, K$. If WEIGHT = 'U' the sum of weights is the number of objects in the cluster.
- 16:** MAXIT — INTEGER *Input*
On entry: the maximum number of iterations allowed in the analysis.
Constraint: MAXIT > 0.
Suggested value: MAXIT = 10.
- 17:** IWK(N+3*K) — INTEGER array *Workspace*
- 18:** WK(N+2*K) — *real* array *Workspace*
- 19:** IFAIL — INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. For users not familiar with this parameter (described in Chapter P01) the recommended value is 0.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors detected by the routine:

IFAIL = 1

- On entry, WEIGHT \neq 'W' or 'U',
 - or $N < 2$,
 - or $NVAR < 1$,
 - or $M < NVAR$,
 - or $K < 2$,
 - or $LDX < N$,
 - or $LDC < K$,

or $\text{MAXIT} \leq 0$.

IFAIL = 2

On entry, WEIGHT = 'W' and a value of $\text{WT}(i) < 0.0$ for some i ,
or WEIGHT = 'W' and $\text{WT}(i) = 0.0$ for all or all but one values of i .

IFAIL = 3

On entry, the number of positive values in ISX does not equal NVAR.

IFAIL = 4

On entry, at least one cluster is empty after the initial assignment. Try a different set of initial cluster centres in CMEANS and also consider decreasing the value of K. The empty clusters may be found by examining the values in NIC.

IFAIL = 5

Convergence has not been achieved within the maximum number of iterations given by MAXIT. Try increasing MAXIT and, if possible, use the returned values in CMEANS as the initial cluster centres.

7 Accuracy

The routine produces clusters that are locally optimal; the within-cluster sum of squares may not be decreased by transferring a point from one cluster to another, but different partitions may have the same or smaller within-cluster sum of squares.

8 Further Comments

The time per iteration is approximately proportional to npK .

9 Example

The data consists of observations of five variables on twenty soils (Kendall and Stuart, [2]). The data is read in, the K -means clustering performed and the results printed.

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      G03EFF Example Program Text
*      Mark 16 Release. NAG Copyright 1992.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER       (NIN=5,NOUT=6)
      INTEGER          NMAX, MMAX, KMAX
      PARAMETER       (NMAX=20,MMAX=5,KMAX=3)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, J, K, LDC, LDX, M, MAXIT, N, NVAR
      CHARACTER        WEIGHT
*      .. Local Arrays ..
      real            CMEANS(KMAX,MMAX), CSS(MMAX), CSW(MMAX),
+                   WK(NMAX+2*KMAX), WT(NMAX), X(NMAX,MMAX)
      INTEGER          INC(NMAX), ISX(MMAX), IWK(NMAX+3*KMAX), NIC(MMAX)
*      .. External Subroutines ..
      EXTERNAL         G03EFF
```

```

*      .. Executable Statements ..
*
WRITE (NOUT,*) 'G03EFF Example Program Results'
*      Skip heading in the data file
READ (NIN,*)
READ (NIN,*) WEIGHT, N, M, NVAR, K, MAXIT
IF (N.LE.NMAX .AND. M.LE.MMAX) THEN
  IF (WEIGHT.EQ.'W' .OR. WEIGHT.EQ.'w') THEN
    DO 20 I = 1, N
      READ (NIN,*) (X(I,J),J=1,M), WT(I)
20    CONTINUE
  ELSE
    DO 40 I = 1, N
      READ (NIN,*) (X(I,J),J=1,M)
40    CONTINUE
  END IF
  DO 60 I = 1, K
    READ (NIN,*) (CMEANS(I,J),J=1,NVAR)
60    CONTINUE
  READ (NIN,*) (ISX(J),J=1,M)
  LDX = NMAX
  LDC = KMAX
  IFAIL = 0
*
CALL G03EFF(WEIGHT,N,M,X,LDX,ISX,NVAR,K,CMEANS,LDC,WT,INC,NIC,
+          CSS,CSW,MAXIT,IWK,WK,IFAIL)
*
WRITE (NOUT,*)
WRITE (NOUT,*) ' The cluster each point belongs to'
WRITE (NOUT,99999) (INC(I),I=1,N)
WRITE (NOUT,*)
WRITE (NOUT,*) ' The number of points in each cluster'
WRITE (NOUT,99999) (NIC(I),I=1,K)
WRITE (NOUT,*)
WRITE (NOUT,*)
+ ' The within-cluster sum of weights of each cluster'
WRITE (NOUT,99998) (CSW(I),I=1,K)
WRITE (NOUT,*)
WRITE (NOUT,*)
+ ' The within-cluster sum of squares of each cluster'
WRITE (NOUT,99997) (CSS(I),I=1,K)
WRITE (NOUT,*)
WRITE (NOUT,*) ' The final cluster centres'
WRITE (NOUT,*)
+ '           1           2           3           4           5'
DO 80 I = 1, K
  WRITE (NOUT,99996) I, (CMEANS(I,J),J=1,NVAR)
80  CONTINUE
  END IF
  STOP
*
99999 FORMAT (1X,10I6)
99998 FORMAT (1X,5F9.2)
99997 FORMAT (1X,5F13.4)
99996 FORMAT (1X,I5,5X,5F8.4)
END

```

9.2 Program Data

G03EFF Example Program Data

```
'u' 20 5 5 3 10          : WEIGHT N M NVAR K MAXIT

77.3 13.0  9.7 1.5 6.4
82.5 10.0  7.5 1.5 6.5
66.9 20.6 12.5 2.3 7.0
47.2 33.8 19.0 2.8 5.8
65.3 20.5 14.2 1.9 6.9
83.3 10.0  6.7 2.2 7.0
81.6 12.7  5.7 2.9 6.7
47.8 36.5 15.7 2.3 7.2
48.6 37.1 14.3 2.1 7.2
61.6 25.5 12.9 1.9 7.3
58.6 26.5 14.9 2.4 6.7
69.3 22.3  8.4 4.0 7.0
61.8 30.8  7.4 2.7 6.4
67.7 25.3  7.0 4.8 7.3
57.2 31.2 11.6 2.4 6.5
67.2 22.7 10.1 3.3 6.2
59.2 31.2  9.6 2.4 6.0
80.2 13.2  6.6 2.0 5.8
82.2 11.1  6.7 2.2 7.2
69.7 20.7  9.6 3.1 5.9

82.5 10.0  7.5 1.5 6.5      : CMEANS
47.8 36.5 15.7 2.3 7.2
67.2 22.7 10.1 3.3 6.2

1 1 1 1 1          : ISX
```

9.3 Program Results

G03EFF Example Program Results

The cluster each point belongs to

```
  1   1   3   2   3   1   1   2   2   3
  3   3   3   3   3   3   3   1   1   3
```

The number of points in each cluster

```
  6   3   11
```

The within-cluster sum of weights of each cluster

```
  6.00   3.00   11.00
```

The within-cluster sum of squares of each cluster

```
  46.5717   20.3800   468.8964
```

The final cluster centres

```
          1   2   3   4   5
  1   81.1833 11.6667  7.1500  2.0500  6.6000
  2   47.8667 35.8000 16.3333  2.4000  6.7333
  3   64.0455 25.2091 10.7455  2.8364  6.6545
```