

NAG Fortran Library Routine Document

C06PRF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

C06PRF computes the discrete Fourier transforms of m sequences, each containing n complex data values.

2 Specification

```
SUBROUTINE C06PRF(DIRECT, M, N, X, WORK, IFAIL)
INTEGER          M, N, IFAIL
complex        X(M*N), WORK(M*N+2*N+15)
CHARACTER*1     DIRECT
```

3 Description

Given m sequences of n complex data values z_j^p , for $j = 0, 1, \dots, n-1$ and $p = 1, 2, \dots, m$, this routine simultaneously calculates the (**forward** or **backward**) discrete Fourier transforms of all the sequences defined by

$$z_k^p = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} z_j^p \times \exp\left(\pm i \frac{2\pi jk}{n}\right), \quad k = 0, 1, \dots, n-1; \quad p = 1, 2, \dots, m.$$

(Note the scale factor $\frac{1}{\sqrt{n}}$ in this definition.) The minus sign is taken in the argument of the exponential within the summation when the forward transform is required, and the plus sign is taken when the backward transform is required. A call of the routine with `DIRECT = 'F'` followed by a call with `DIRECT = 'B'` will restore the original data.

The routine uses a variant of the fast Fourier transform (FFT) algorithm (Brigham (1974)) known as the Stockham self-sorting algorithm, which is described in Temperton (1983b). Special code is provided for the factors 2, 3, 4 and 5.

4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice-Hall

Temperton C (1983b) Self-sorting mixed-radix fast Fourier transforms *J. Comput. Phys.* **52** 1–23

5 Parameters

1: DIRECT – CHARACTER*1 *Input*

On entry: if the **Forward** transform as defined in Section 3 is to be computed, then DIRECT must be set equal to 'F'. If the **Backward** transform is to be computed then DIRECT must be set equal to 'B'.

Constraint: DIRECT = 'F' or 'B'.

2: M – INTEGER *Input*

- 3: N – INTEGER *Input*
- 4: X(M*N) – *complex* array *Input/Output*
On entry: the complex data must be stored in X as if in a two-dimensional array of dimension (1 : M, 0 : N – 1); each of the m sequences is stored in a **row** of each array. In other words, if the elements of the p th sequence to be transformed are denoted by z_j^p , for $j = 0, 1, \dots, n - 1$, then $X(j * M + p)$ must contain z_j^p .
On exit: X is overwritten by the complex transforms.
- 5: WORK(M*N+2*N+15) – *complex* array *Workspace*
- 6: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, –1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).
 For environments where it might be inappropriate to halt program execution when an error is detected, the value –1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value –1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or –1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

IFAIL = 2

IFAIL = 3

IFAIL = 4

IFAIL = 5

7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

8 Further Comments

The time taken by the routine is approximately proportional to $nm \times \log n$, but also depends on the factors of n . The routine is fastest if the only prime factors of n are 2, 3 and 5, and is particularly slow if n is a large prime, or has large prime factors.

9 Example

This program reads in sequences of complex data values and prints their discrete Fourier transforms (as computed by C06PRF with DIRECT set to 'F'). Inverse transforms are then calculated using C06PRF with DIRECT set to 'B' and printed out, showing that the original sequences are restored.

9.1 Program Text

```

*      C06PRF Example Program Text.
*      Mark 19 Release. NAG Copyright 1999.
*      .. Parameters ..
INTEGER          NIN, NOUT
PARAMETER       (NIN=5,NOUT=6)
INTEGER         MMAX, NMAX
PARAMETER       (MMAX=5,NMAX=20)
*      .. Local Scalars ..
INTEGER         I, IFAIL, J, M, N
*      .. Local Arrays ..
complex       WORK((MMAX+2)*NMAX+15), X(MMAX*NMAX)
*      .. External Subroutines ..
EXTERNAL        C06PRF
*      .. Intrinsic Functions ..
INTRINSIC       real, imag
*      .. Executable Statements ..
WRITE (NOUT,*) 'C06PRF Example Program Results'
*      Skip heading in data file
READ (NIN,*)
20  CONTINUE
READ (NIN,*,END=120) M, N
IF (M.LE.MMAX .AND. N.LE.NMAX) THEN
  DO 40 J = 1, M
    READ (NIN,*) (X(I*M+J),I=0,N-1)
40  CONTINUE
  WRITE (NOUT,*)
  WRITE (NOUT,*) 'Original data values'
  DO 60 J = 1, M
    WRITE (NOUT,*)
    WRITE (NOUT,99999) 'Real ', (real(X(I*M+J)),I=0,N-1)
    WRITE (NOUT,99999) 'Imag ', (imag(X(I*M+J)),I=0,N-1)
60  CONTINUE
  IFAIL = 0
*
  CALL C06PRF('F',M,N,X,WORK,IFAIL)
*
  WRITE (NOUT,*)
  WRITE (NOUT,*) 'Discrete Fourier transforms'
  DO 80 J = 1, M
    WRITE (NOUT,*)
    WRITE (NOUT,99999) 'Real ', (real(X(I*M+J)),I=0,N-1)
    WRITE (NOUT,99999) 'Imag ', (imag(X(I*M+J)),I=0,N-1)
80  CONTINUE
*
  CALL C06PRF('B',M,N,X,WORK,IFAIL)
*
  WRITE (NOUT,*)
  WRITE (NOUT,*) 'Original data as restored by inverse transform'
  DO 100 J = 1, M
    WRITE (NOUT,*)
    WRITE (NOUT,99999) 'Real ', (real(X(I*M+J)),I=0,N-1)
    WRITE (NOUT,99999) 'Imag ', (imag(X(I*M+J)),I=0,N-1)
100 CONTINUE
  GO TO 20
ELSE
  WRITE (NOUT,*) 'Invalid value of M or N'
END IF
120 CONTINUE
STOP

```

```
*
99999 FORMAT (1X,A,6F10.4)
      END
```

9.2 Program Data

C06PRF Example Program Data

```
3      6
(0.3854,0.5417)
(0.6772,0.2983)
(0.1138,0.1181)
(0.6751,0.7255)
(0.6362,0.8638)
(0.1424,0.8723)
(0.9172,0.9089)
(0.0644,0.3118)
(0.6037,0.3465)
(0.6430,0.6198)
(0.0428,0.2668)
(0.4815,0.1614)
(0.1156,0.6214)
(0.0685,0.8681)
(0.2060,0.7060)
(0.8630,0.8652)
(0.6967,0.9190)
(0.2792,0.3355)
```

9.3 Program Results

C06PRF Example Program Results

Original data values

Real	0.3854	0.6772	0.1138	0.6751	0.6362	0.1424
Imag	0.5417	0.2983	0.1181	0.7255	0.8638	0.8723
Real	0.9172	0.0644	0.6037	0.6430	0.0428	0.4815
Imag	0.9089	0.3118	0.3465	0.6198	0.2668	0.1614
Real	0.1156	0.0685	0.2060	0.8630	0.6967	0.2792
Imag	0.6214	0.8681	0.7060	0.8652	0.9190	0.3355

Discrete Fourier transforms

Real	1.0737	-0.5706	0.1733	-0.1467	0.0518	0.3625
Imag	1.3961	-0.0409	-0.2958	-0.1521	0.4517	-0.0321
Real	1.1237	0.1728	0.4185	0.1530	0.3686	0.0101
Imag	1.0677	0.0386	0.7481	0.1752	0.0565	0.1403
Real	0.9100	-0.3054	0.4079	-0.0785	-0.1193	-0.5314
Imag	1.7617	0.0624	-0.0695	0.0725	0.1285	-0.4335

Original data as restored by inverse transform

Real	0.3854	0.6772	0.1138	0.6751	0.6362	0.1424
Imag	0.5417	0.2983	0.1181	0.7255	0.8638	0.8723
Real	0.9172	0.0644	0.6037	0.6430	0.0428	0.4815
Imag	0.9089	0.3118	0.3465	0.6198	0.2668	0.1614
Real	0.1156	0.0685	0.2060	0.8630	0.6967	0.2792
Imag	0.6214	0.8681	0.7060	0.8652	0.9190	0.3355