NAG Fortran Library Routine Document C06RBF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

C06RBF computes the discrete Fourier cosine transforms of m sequences of real data values.

2 Specification

SUBROUTINE CO6RBF(M, N, X, WORK, IFAIL)

INTEGER M, N, IFAIL

real X(M*(N+3)), WORK(M*N+2*N+15)

3 Description

Given m sequences of n+1 real data values x_j^p , for $j=0,1,\ldots,n$ and $p=1,2,\ldots,m$, this routine simultaneously calculates the Fourier cosine transforms of all the sequences defined by

$$\hat{x}_k^p = \sqrt{\frac{2}{n}} \left(\frac{1}{2} x_0^p + \sum_{j=1}^{n-1} x_j^p \times \cos\left(jk\frac{\pi}{n}\right) + \frac{1}{2} (-1)^k x_n^p \right), \quad k = 0, 1, \dots, n; \quad p = 1, 2, \dots, m.$$

(Note the scale factor $\sqrt{\frac{2}{n}}$ in this definition.)

Since the Fourier cosine transform is its own inverse, two consecutive calls of this routine will restore the original data.

The transform calculated by this routine can be used to solve Poisson's equation when the derivative of the solution is specified at both left and right boundaries (Swarztrauber (1977)).

The routine uses a variant of the fast Fourier transform (FFT) algorithm (Brigham (1974)) known as the Stockham self-sorting algorithm, described in Temperton (1983a), together with pre- and post-processing stages described in Swarztrauber (1982). Special coding is provided for the factors 2, 3, 4 and 5.

4 References

Brigham E O (1974) The Fast Fourier Transform Prentice-Hall

Swarztrauber P N (1977) The methods of cyclic reduction, Fourier analysis and the FACR algorithm for the discrete solution of Poisson's equation on a rectangle SIAM Rev. 19 (3) 490–501

Swarztrauber P N (1982) Vectorizing the FFT's Parallel Computation (ed G Rodrique) 51-83 Academic Press

Temperton C (1983a) Fast mixed-radix real Fourier transforms J. Comput. Phys. 52 340-350

5 Parameters

1: M – INTEGER Input

2: N – INTEGER Input

On entry: one less than the number of real values in each sequence, i.e., the number of values in each sequence is n + 1.

[NP3546/20A] C06RBF.1

Constraint: $N \ge 1$.

3: X(M*(N+3)) - real array

Input/Output

On entry: the data must be stored in X as if in a two-dimensional array of dimension (1:M, 0:N+2); each of the m sequences is stored in a **row** of the array. In other words, if the (n+1) data values of the pth sequence to be transformed are denoted by x_j^p , for $j=0,1,\ldots,n$ and $p=1,2,\ldots,m$, then the first m(n+1) elements of the array X must contain the values

$$x_0^1, x_0^2, \dots, x_0^m, x_1^1, x_1^2, \dots, x_1^m, \dots, x_n^1, x_n^2, \dots, x_n^m$$

The (n+2)th and (n+3)th elements of each row x_{n+2}^p , x_{n+3}^p , for $p=1,2,\ldots,m$, are required as workspace. These 2m elements may contain arbitrary values as they are set to zero by the routine.

On exit: the m Fourier cosine transforms stored as if in a two-dimensional array of dimension (1:M, 0:N+2). Each of the m transforms is stored in a **row** of the array, overwriting the corresponding original data. If the (n+1) components of the pth Fourier cosine transform are denoted by \hat{x}_k^p , for $k=0,1,\ldots,n$ and $p=1,2,\ldots,m$, then the m(n+3) elements of the array X contain the values

$$\hat{x}_0^1, \hat{x}_0^2, \dots, \hat{x}_0^m, \ \hat{x}_1^1, \hat{x}_1^2, \dots, \hat{x}_1^m, \dots, \ \hat{x}_n^1, \hat{x}_n^2, \dots, \hat{x}_n^m, 0, 0, \dots, 0 \ (2m \ \text{times}).$$

4: WORK(M*N+2*N+15) - real array

Workspace

5: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

IFAIL = 2

IFAIL = 3

7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

8 Further Comments

The time taken by the routine is approximately proportional to $nm \times \log n$, but also depends on the factors of n. The routine is fastest if the only prime factors of n are 2, 3 and 5, and is particularly slow if n is a large prime, or has large prime factors.

C06RBF.2 [NP3546/20A]

9 Example

This program reads in sequences of real data values and prints their Fourier cosine transforms (as computed by C06RBF). It then calls the routine again and prints the results which may be compared with the original sequence.

9.1 Program Text

Note: the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
CO6RBF Example Program Text.
*
      Mark 19 Release. NAG Copyright 1999.
      .. Parameters ..
      INTEGER
                       NIN, NOUT
      PARAMETER
                        (NIN=5,NOUT=6)
      INTEGER
                       MMAX, NMAX
      PARAMETER
                        (MMAX=5,NMAX=20)
      .. Local Scalars ..
      INTEGER
                       I, IFAIL, J, M, N
      .. Local Arrays ..
      real
                       WORK (MMAX*NMAX+2*NMAX+15), X((NMAX+3)*MMAX)
      .. External Subroutines ..
      EXTERNAL
                       CO6RBF
      .. Executable Statements ..
      WRITE (NOUT,*) 'CO6RBF Example Program Results'
      Skip heading in data Ûle
      READ (NIN, *)
   20 CONTINUE
      READ (NIN, \star, END=120) M, N
      IF (M.LE.MMAX .AND. N.LE.NMAX) THEN
         DO 40 J = 1, M
            READ (NIN,*) (X(I*M+J),I=0,N)
   40
         CONTINUE
         WRITE (NOUT, *)
         WRITE (NOUT,*) 'Original data values'
         WRITE (NOUT, *)
         DO 60 J = 1, M
            WRITE (NOUT, 99999) (X(I*M+J), I=0, N)
   60
         CONTINUE
         IFAIL = 0
*
          Compute transform
         CALL CO6RBF(M,N,X,WORK,IFAIL)
         WRITE (NOUT, *)
         WRITE (NOUT,*) 'Discrete Fourier cosine transforms'
         WRITE (NOUT, *)
         DO 80 J = 1, M
            WRITE (NOUT, 99999) (X(I*M+J), I=0,N)
   80
         CONTINUE
*
          Compute inverse transform
         CALL CO6RBF(M,N,X,WORK,IFAIL)
         WRITE (NOUT, *)
         WRITE (NOUT,*) 'Original data as restored by inverse transform'
         WRITE (NOUT, *)
         DO 100 J = 1, M
            WRITE (NOUT, 99999) (X(I*M+J), I=0, N)
  100
         CONTINUE
         GO TO 20
      ELSE
         WRITE (NOUT,*) 'Invalid value of M or N'
      END IF
 120 CONTINUE
      STOP
99999 FORMAT (6X,7F10.4)
```

[NP3546/20A] C06RBF.3

END

9.2 Program Data

C06RBF Example Program Data
3 6: Number of sequences, M, (number of values in each sequence)-1, N
0.3854 0.6772 0.1138 0.6751 0.6362 0.1424 0.9562: X, sequence 1
0.5417 0.2983 0.1181 0.7255 0.8638 0.8723 0.4936: X, sequence 2
0.9172 0.0644 0.6037 0.6430 0.0428 0.4815 0.2057: X, sequence 3

9.3 Program Results

CO6RBF Example Program Results

Original data values

| | 0.3854 | 0.6772 | 0.1138 | 0.6751 | 0.6362 | 0.1424 | 0.9562 |
|------------------------------------|---------|----------|------------|-----------|--------|---------|---------|
| | 0.5417 | 0.2983 | 0.1181 | 0.7255 | 0.8638 | 0.8723 | 0.4936 |
| | 0.9172 | 0.0644 | 0.6037 | 0.6430 | 0.0428 | 0.4815 | 0.2057 |
| Discrete Fourier cosine transforms | | | | | | | |
| | 1.6833 | -0.0482 | 0.0176 | 0.1368 | 0.3240 | -0.5830 | -0.0427 |
| | 1.9605 | -0.4884 | -0.0655 | 0.4444 | 0.0964 | 0.0856 | -0.2289 |
| | 1.3838 | 0.1588 | -0.0761 | -0.1184 | 0.3512 | 0.5759 | 0.0110 |
| Original | data as | restored | by inverse | transform | | | |
| | 0.3854 | 0.6772 | 0.1138 | 0.6751 | 0.6362 | 0.1424 | 0.9562 |
| | 0.5417 | 0.2983 | 0.1181 | 0.7255 | 0.8638 | 0.8723 | 0.4936 |
| | 0.9172 | 0.0644 | 0.6037 | 0.6430 | 0.0428 | 0.4815 | 0.2057 |

C06RBF.4 (last) [NP3546/20A]