# NAG Fortran Library Routine Document

# D03MAF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

D03MAF places a triangular mesh over a given two-dimensional region. The region may have any shape, including one with holes.

# 2 Specification

```
SUBROUTINE DO3MAF(H, M, N, NB, NPTS, PLACES, INDEX, IDIM, IN, DIST, LD,1IFAIL)INTEGERM, N, NB, NPTS, INDEX(4,IDIM), IDIM, IN, LD, IFAILrealH, PLACES(2,IDIM), DIST(4,LD)EXTERNALIN
```

# **3** Description

This subroutine begins with a uniform triangular grid as shown in Figure 1 and assumes that the region to be triangulated lies within the rectangle given by the inequalities

$$0 < x < \sqrt{3}(m-1)h, \quad 0 < y < (n-1)h.$$

This rectangle is drawn in bold in Figure 1. The region is specified by the user's function IN which must determine whether any given point (x, y) lies in the region. The uniform grid is processed columnwise, with  $(x_1, y_1)$  preceding  $(x_2, y_2)$  if  $x_1 < x_2$  or  $x_1 = x_2$ ,  $y_1 < y_2$ . Points near the boundary are moved onto it and points well outside the boundary are omitted. The direction of movement is chosen to avoid pathologically thin triangles. The points accepted are numbered in exactly the same order as the corresponding points of the uniform grid were scanned. The output consists of the x, y co-ordinates of all grid points and integers indicating whether they are internal and to which other points they are joined by triangle sides.

The mesh size h must be chosen small enough for the essential features of the region to be apparent from testing all points of the original uniform grid for being inside the region. For instance if any hole is within 2h of another hole or the outer boundary then a triangle may be found with all vertices within  $\frac{1}{2}h$  of a boundary. Such a triangle is taken to be external to the region so the effect will be to join the hole to another hole or to the external region.

Further details of the algorithm are given in the references.




Figure 1

5:

**D03MAF** 

References

Instr. Math. Appl. 9 1-13

**Parameters** 

M - INTEGER

dimensions Harwell Report TP422

4

5

1:

N - INTEGER 3:

H – real

On entry: values m and n such that all points (x, y) inside the region satisfy the inequalities

On entry: the required length, h, for the sides of the triangles of the uniform mesh.

Reid J K (1970) Fortran subroutines for the solutions of Laplace's equation over a general routine in two

Reid J K (1972) On the construction and convergence of a finite-element solution of Laplace's equation J.

Constraint: M, N > 2.

NB - INTEGER 4:

> On entry: the number of times a triangle side is bisected to find a point on the boundary. A value of 10 is adequate for most purposes (see Section 7).

Constraint: NB > 1.

NPTS - INTEGER

- On exit: the number of points in the triangulation.
- 6: PLACES(2,IDIM) - real array

On exit: the x and y co-ordinates respectively of the *i*th point of the triangulation.

7: INDEX(4,IDIM) – INTEGER array

> On exit: INDEX(1, i) contains i if point i is inside the region and -i if it is on the boundary. For each triangle side between points i and j with j > i, INDEX(k, i), k > 1, contains j or -jaccording to whether point j is internal or on the boundary. There can never be more than three such points. If there are less, then some values INDEX(k, i), k > 1, are zero.

**IDIM – INTEGER** 8:

> On entry: the second dimension of the arrays PLACES and INDEX as declared in the (sub)program from which D03MAF is called.

Constraint: IDIM  $\geq$  NPTS.

9: IN - INTEGER FUNCTION, supplied by the user. External Procedure IN must return the value 1 if the given point (X,Y) lies inside the region, and 0 if it lies outside. Its specification is:

Input

Input Input

Input

Output

Output

Output

Input

 INTEGER FUNCTION IN(X, Y)

 real
 X, Y

 1:
 X - real
 Input

 2:
 Y - real
 Input

 On entry: the co-ordinates of the given point.
 Input

IN must be declared as EXTERNAL in the (sub)program from which D03MAF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

#### 10: DIST(4,LD) – *real* array

11: LD – INTEGER

On entry: the second dimension of the array DIST as declared in the (sub)program from which D03MAF is called.

*Constraint*:  $LD \ge 4N$ .

#### 12: IFAIL – INTEGER

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

# 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

IDIM is too small.

IFAIL = 2

A point inside the region violates one of the constraints (see parameters M and N above).

IFAIL = 3

LD is too small.

```
IFAIL = 4
```

 $M \leq 2.$ 

IFAIL = 5

 $N\leq 2.$ 

IFAIL = 6

 $NB \leq 0.$ 

**D03MAF** 

Input/Output

Workspace

Input

# 7 Accuracy

Points are moved onto the boundary by bisecting a triangle side NB times. The accuracy is therefore  $h \times 2^{-NB}$ .

# 8 Further Comments

The time taken by the routine is approximately proportional to  $m \times n$ .

# 9 Example

The following program triangulates the circle with centre (7.0,7.0) and radius 6.0 using a basic grid size h = 4.0.

### 9.1 Program Text

**Note:** the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*
      DO3MAF Example Program Text
      Mark 14 Revised. NAG Copyright 1989.
*
*
      .. Parameters ..
      INTEGER
                       IDIM, LD
      PARAMETER
                       (IDIM=100,LD=20)
      INTEGER
                       NOUT
      PARAMETER
                       (NOUT=6)
      .. Local Scalars ..
*
      real
                       Η
      INTEGER
                       I, IFAIL, J, M, N, NB, NPTS
      .. Local Arrays ..
      real
                       DIST(4,LD), PLACES(2,IDIM)
      INTEGER
                       INDEX(4,IDIM)
      .. External Functions ..
      INTEGER
                       IN1
      EXTERNAL
                       IN1
      .. External Subroutines ..
*
      EXTERNAL
                      DO3MAF
*
      .. Executable Statements ..
      WRITE (NOUT, *) 'DO3MAF Example Program Results'
      WRITE (NOUT, *)
      H = 4.0e0
      M = 3
      N = 5
      NB = 10
      IFAIL = 0
*
      CALL DO3MAF(H,M,N,NB,NPTS,PLACES,INDEX,IDIM,IN1,DIST,LD,IFAIL)
*
      WRITE (NOUT, *) ' I
                             X(I)
                                        Y(I)'
      DO 20 I = 1, NPTS
         WRITE (NOUT, 99999) I, PLACES(1,I), PLACES(2,I)
   20 CONTINUE
      WRITE (NOUT, *)
      WRITE (NOUT,*) 'Index'
      DO 40 I = 1, NPTS
         WRITE (NOUT, 99998) (INDEX(J,I), J=1,4)
   40 CONTINUE
      STOP
99999 FORMAT (1X, I3, 2F10.6)
99998 FORMAT (1X,415)
      END
*
      INTEGER FUNCTION IN1(X,Y)
*
      Circular domain
      .. Scalar Arguments ..
```

```
real X, Y
* .. Executable Statements ..
IF ((X-7.0e0)**2+(Y-7.0e0)**2.LE.36.0e0) THEN
IN1 = 1
ELSE
IN1 = 0
END IF
RETURN
END
```

# 9.2 Program Data

None.

# 9.3 Program Results

DO3MAF Example Program Results

I	X(I)	Y(I)
1	1.013182	6.584961
2	1.412366	9.184570
3	2.268242	3.309570
4	3.464102	8.000000
5	3.584195	11.930664
6	6.928203	1.001953
7	6.928203	6.000000
8	6.928203	10.000000
9	6.928203	12.998047
10	11.686269	3.252930
11	10.392305	8.000000
12	10.392305	11.947266
13	12.978541	6.506836
14	12.562443	9.252930

Index			
-1	-3	4	-2
-2	4	-5	0
-3	-6	7	4
4	7	8	-5
-5	8	-9	0
-6	0	-10	7
7	-10	11	8
8	11	-12	-9
-9	-12	0	0
-10	0	-13	11
11	-13	-14	-12
-12	-14	0	0
-13	0	0	-14
-14	0	0	0