NAG Fortran Library Routine Document

F01LEF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F01LEF computes an LU factorization of a real tridiagonal matrix, using Gaussian elimination with partial pivoting.

2 Specification

```
SUBROUTINE FOILEF(N, A, LAMBDA, B, C, TOL, D, IN, IFAIL)INTEGERN, IN(N), IFAILrealA(N), LAMBDA, B(N), C(N), TOL, D(N)
```

3 Description

The matrix $T - \lambda I$, where T is a real n by n tridiagonal matrix, is factorized as

$$T - \lambda I = PLU,$$

where P is a permutation matrix, L is a unit lower triangular matrix with at most one non-zero subdiagonal element per column, and U is an upper triangular matrix with at most two non-zero superdiagonal elements per column.

The factorization is obtained by Gaussian elimination with partial pivoting and implicit row scaling.

An indication of whether or not the matrix $T - \lambda I$ is nearly singular is returned in the *n*th element of the array IN. If it is important that $T - \lambda I$ is non-singular, as is usually the case when solving a system of tridiagonal equations, then it is strongly recommended that IN(n) is inspected on return from F01LEF. (See the parameter IN and Section 8 for further details.)

The parameter λ is included in the routine so that F01LEF may be used, in conjunction with F04LEF, to obtain eigenvectors of T by inverse iteration.

4 References

Wilkinson J H (1965) The Algebraic Eigenvalue Problem Oxford University Press, Oxford

Wilkinson J H and Reinsch C (1971) Handbook for Automatic Computation II, Linear Algebra Springer-Verlag

5 Parameters

1:	N – INTEGER	Input
	On entry: n , the order of the matrix T .	
	Constraint: $N \ge 1$.	
2:	A(N) – <i>real</i> array	Input/Output
	On entry: the diagonal elements of T.	
	On exit: the diagonal elements of the upper triangular matrix U.	
3:	LAMBDA – <i>real</i>	Input
	On entry: the scalar λ . The routine factorizes $T - \lambda I$.	

4: B(N) - real array

On entry: the super-diagonal elements of T, stored in B(2) to B(n); B(1) is not used. On exit: the elements of the first super-diagonal of U, stored in B(2) to B(n).

5: C(N) - real array

On entry: the sub-diagonal elements of T, stored in C(2) to C(n); C(1) is not used.

On exit: the sub-diagonal elements of L, stored in C(2) to C(n).

6: TOL – *real*

On entry: a relative tolerance used to indicate whether or not the matrix $(T - \lambda I)$ is nearly singular. TOL should normally be chosen as approximately the largest relative error in the elements of T. For example, if the elements of T are correct to about 4 significant figures, then TOL should be set to about 5×10^{-4} . See Section 8 for further details on how TOL is used. If TOL is supplied as less than ϵ , where ϵ is the **machine precision**, then the value ϵ is used in place of TOL.

7: D(N) - real array

On exit: the elements of the second super-diagonal of U, stored in D(3) to D(n); D(1) and D(2) are not used.

8: IN(N) – INTEGER array

On exit: details of the permutation matrix P. If an interchange occurred at the kth step of the elimination, then IN(k) = 1, otherwise IN(k) = 0. If a diagonal element of U is small, indicating that $(T - \lambda I)$ is nearly singular, then the element IN(n) is returned as positive. Otherwise IN(n) is returned as 0. See Section 8 for further details. If the application is such that it is important that $(T - \lambda I)$ is not nearly singular, then it is strongly recommended that IN(n) is inspected on return.

9: IFAIL – INTEGER

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, N < 1.

7 Accuracy

The computed factorization will satisfy the equation

 $PLU = (T - \lambda I) + E,$

Input/Output

Input

Output

Output

Input/Output

Input/Output

where

$$||E||_{1} \le 9 \times \max_{i > i} (|l_{ij}|, |l_{ij}|^{2}) \epsilon ||T - \lambda I||_{1}$$

where ϵ is the *machine precision*.

8 **Further Comments**

The time taken by the routine is approximately proportional to n.

The factorization of a tridiagonal matrix proceeds in (n-1) steps, each step eliminating one sub-diagonal element of the tridiagonal matrix. In order to avoid small pivot elements and to prevent growth in the size of the elements of L, rows k and (k+1) will, if necessary, be interchanged at the kth step prior to the elimination.

The element IN(n) returns the smallest integer, j, for which

$$|u_{jj}| \leq ||(T - \lambda I)_j||_1 \times \text{TOL},$$

where $||(T - \lambda I)_j||_1$ denotes the sum of the absolute values of the *j*th row of the matrix $(T - \lambda I)$. If no such *j* exists, then IN(n) is returned as zero. If such a *j* exists, then $|u_{jj}|$ is small and hence $(T - \lambda I)$ is singular or nearly singular.

This routine may be followed by F04LEF to solve systems of tridiagonal equations. Users wishing to solve single systems of tridiagonal equations may wish to be aware of F04EAF, which solves tridiagonal systems with a single call. F04EAF requires less storage and will generally be faster than the combination of F01LEF and F04LEF, but no test for near singularity is included in F04EAF and so it should only be used when the equations are known to be non-singular.

9 Example

To factorize the tridiagonal matrix T where

$$T = \begin{pmatrix} 3.0 & 2.1 & 0 & 0 & 0 \\ 3.4 & 2.3 & -1.0 & 0 & 0 \\ 0 & 3.6 & -5.0 & 1.9 & 0 \\ 0 & 0 & 7.0 & -0.9 & 8.0 \\ 0 & 0 & 0 & -6.0 & 7.1 \end{pmatrix}$$

and then to solve the equations Tx = y, where

$$y = \begin{pmatrix} 2.7 \\ -0.5 \\ 2.6 \\ 0.6 \\ 2.7 \end{pmatrix}$$

by a call to F04LEF. The example program sets $TOL = 5 \times 10^{-5}$ and, of course, sets LAMBDA=0.

9.1 Program Text

Note: the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
FOILEF Example Program Text
*
*
      Mark 14 Revised. NAG Copyright 1989.
*
      .. Parameters ..
      INTEGER
                       NMAX
      PARAMETER
                        (NMAX=50)
      INTEGER
                        NIN, NOUT
      PARAMETER
                       (NIN=5,NOUT=6)
*
      .. Local Scalars ..
      real
                       LAMBDA, TOL
      INTEGER
                        I, IFAIL, JOB, N
```

F01LEF

```
.. Local Arrays ..
*
      real
                        A(NMAX), B(NMAX), C(NMAX), D(NMAX), Y(NMAX)
      INTEGER
                        IN(NMAX)
      .. External Subroutines ..
EXTERNAL FO1LEF, FO4LEF
*
      .. Executable Statements ..
*
      WRITE (NOUT, *) 'FOILEF Example Program Results'
      Skip heading in data file
      READ (NIN, *)
      READ (NIN, *) N
      WRITE (NOUT, *)
      IF (N.LT.1 .OR. N.GT.NMAX) THEN
          WRITE (NOUT, 99999) 'N is out of range. N = ', N
      ELSE
         READ (NIN, \star) (A(I), I=1, N)
         READ (NIN, \star) (B(I), I=2, N)
         READ (NIN, \star) (C(I), I=2, N)
         TOL = 0.00005e0
         LAMBDA = 0.0e0
         IFAIL = 1
*
          CALL FOILEF(N,A,LAMBDA,B,C,TOL,D,IN,IFAIL)
*
          IF (IFAIL.NE.O) THEN
             WRITE (NOUT, 99999) 'FOILEF fails. IFAIL =', IFAIL
          ELSE
             IF (IN(N).NE.O) THEN
                WRITE (NOUT, *) 'Matrix is singular or nearly singular'
                WRITE (NOUT, 99998) 'Diagonal element', IN(N), 'is small'
             ELSE
                WRITE (NOUT, *) 'Details of factorization'
                WRITE (NOUT, *)
                WRITE (NOUT, *) ' Main diagonal of U'
                WRITE (NOUT, 99997) (A(I), I=1,N)
                WRITE (NOUT, *)
                WRITE (NOUT,*) ' First super-diagonal of U'
                WRITE (NOUT, 99997) (B(I), I=2, N)
                WRITE (NOUT,*)
                WRITE (NOUT,*) ' Second super-diagonal of U'
WRITE (NOUT,99997) (D(I),I=3,N)
                WRITE (NOUT, *)
                WRITE (NOUT, *) ' Multipliers'
                WRITE (NOUT, 99997) (C(I), I=2, N)
                WRITE (NOUT, *)
                WRITE (NOUT, *) ' Vector of interchanges'
                WRITE (NOUT, 99996) (IN(I-1), I=2, N)
*
                READ (NIN, *) (Y(I), I=1, N)
                JOB = 1
                IFAIL = 1
*
                CALL F04LEF(JOB,N,A,B,C,D,IN,Y,TOL,IFAIL)
                WRITE (NOUT, *)
                IF (IFAIL.NE.O) THEN
                   WRITE (NOUT,99999) 'F04LEF fails. IFAIL =', IFAIL
                ELSE
                   WRITE (NOUT, *) ' Solution vector'
                   WRITE (NOUT, 99997) (Y(I), I=1, N)
                END IF
             END IF
         END IF
      END IF
      STOP
99999 FORMAT (1X,A,I5)
99998 FORMAT (1X,A,I4,A)
99997 FORMAT (1X,8F9.4)
99996 FORMAT (1X,519)
      END
```

```
FOILEF Example Program Data

5

3.0 2.3 -5.0 -0.9 7.1

2.1 -1.0 1.9 8.0

3.4 3.6 7.0 -6.0

2.7 -0.5 2.6 0.6 2.7
```

9.3 Program Results

```
FOILEF Example Program Results
```

```
Details of factorization
Main diagonal of U
 3.0000 3.6000 7.0000 -6.0000 1.1508
First super-diagonal of U
  2.1000 -5.0000 -0.9000
                        7.1000
Second super-diagonal of U
  0.0000 1.9000 8.0000
Multipliers
 1.1333 -0.0222 -0.1587 0.0168
Vector of interchanges
                  1 1
      0
         1
Solution vector
 -4.0000 7.0000 3.0000 -4.0000 -3.0000
```

[NP3546/20A]