# NAG Fortran Library Routine Document

# F02FAF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

# 1 Purpose

F02FAF computes all the eigenvalues, and optionally all the eigenvectors, of a real symmetric matrix.

# 2 Specification

SUBROUTINE F02FAF(JOB, UPLO, N, A, LDA, W, WORK, LWORK, IFAIL)

INTEGER N, LDA, LWORK, IFAIL

real A(LDA,\*), W(\*), WORK(LWORK)

CHARACTER\*1 JOB, UPLO

# 3 Description

This routine computes all the eigenvalues, and optionally all the eigenvectors, of a real symmetric matrix A:

$$Az_i = \lambda_i z_i, \quad i = 1, 2, \dots, n.$$

In other words, it computes the spectral factorization of A:

$$A = Z\Lambda Z^T$$
,

where  $\Lambda$  is a diagonal matrix whose diagonal elements are the eigenvalues  $\lambda_i$ , and Z is an orthogonal matrix, whose columns are the eigenvectors  $z_i$ .

#### 4 References

Golub G H and van Loan C F (1996) Matrix Computations (3rd Edition) Johns Hopkins University Press, Baltimore

Parlett B N (1980) The Symmetric Eigenvalue Problem Prentice-Hall

## 5 Parameters

### 1: JOB – CHARACTER\*1

Input

On entry: indicates whether eigenvectors are to be computed as follows:

if JOB = 'N', then only eigenvalues are computed;

if JOB = 'V', then eigenvalues and eigenvectors are computed.

Constraint: JOB = 'N' or 'V'.

### 2: UPLO – CHARACTER\*1

Input

On entry: indicates whether the upper or lower triangular part of A is stored as follows:

if UPLO = 'U', then the upper triangular part of A is stored;

if UPLO = L, then the lower triangular part of A is stored.

Constraint: UPLO = 'U' or 'L'.

[NP3546/20A] F02FAF.1

3: N – INTEGER Input

On entry: n, the order of the matrix A.

Constraint:  $N \ge 0$ .

4: A(LDA,\*) - real array

Input/Output

**Note:** the second dimension of the array A must be at least max(1, N).

On entry: the n by n symmetric matrix A. If UPLO = 'U', the upper triangle of A must be stored and the elements of the array below the diagonal need not be set; if UPLO = 'L', the lower triangle of A must be stored and the elements of the array above the diagonal need not be set.

On exit: If JOB = 'V', A contains the orthogonal matrix Z of eigenvectors, with the ith column holding the eigenvector  $z_i$  associated with the eigenvalue  $\lambda_i$  (stored in W(i)). If JOB = 'N', the original contents of A are overwritten.

5: LDA – INTEGER Input

On entry: the first dimension of the array A as declared in the (sub)program from which F02FAF is called.

*Constraint*: LDA  $\geq \max(1, N)$ .

6: W(\*) - real array Output

**Note:** the dimension of the array W must be at least max(1, N).

On exit: the eigenvalues in ascending order.

7: WORK(LWORK) - *real* array

Workspace

8: LWORK – INTEGER

Input

On entry: the dimension of the array WORK as declared in the (sub)program from which F02FAF is called. On some high-performance computers, increasing the dimension of WORK will enable the routine to run faster; a value of  $64 \times N$  should allow near-optimal performance on almost all machines.

Constraint: LWORK  $\geq \max(1, 3 \times N)$ .

9: IFAIL – INTEGER Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

# 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

F02FAF.2 [NP3546/20A]

```
IFAIL = 1
```

```
On entry, JOB \neq 'N' or 'V',
or UPLO \neq 'U' or 'L',
or N < 0,
or LDA < max(1, N),
or LWORK < max(1, 3 \times N).
```

IFAIL = 2

The QR algorithm failed to compute all the eigenvalues.

### 7 Accuracy

If  $\lambda_i$  is an exact eigenvalue, and  $\tilde{\lambda_i}$  is the corresponding computed value, then

$$|\tilde{\lambda}_i - \lambda_i| \le c(n)\epsilon ||A||_2,$$

where c(n) is a modestly increasing function of n, and  $\epsilon$  is the **machine precision**.

If  $z_i$  is the corresponding exact eigenvector, and  $\tilde{z}_i$  is the corresponding computed eigenvector, then the angle  $\theta(\tilde{z}_i, z_i)$  between them is bounded as follows:

$$\theta(\tilde{z}_i, z_i) \le \frac{c(n)\epsilon ||A||_2}{\min_{i \ne j} |\lambda_i - \lambda_j|}.$$

Thus the accuracy of a computed eigenvector depends on the gap between its eigenvalue and all the other eigenvalues.

#### **8 Further Comments**

The routine calls routines from LAPACK in Chapter F08. It first reduces A to tridiagonal form T, using an orthogonal similarity transformation:  $A = QTQ^T$ . If only eigenvalues are required, the routine uses a root-free variant of the symmetric tridiagonal QR algorithm. If eigenvectors are required, the routine first forms the orthogonal matrix Q that was used in the reduction to tridiagonal form; it then uses the symmetric tridiagonal QR algorithm to reduce T to  $\Lambda$ , using a further orthogonal transformation:  $T = S\Lambda S^T$ ; and at the same time accumulates the matrix Z = QS.

Each eigenvector z is normalized so that  $||z||_2 = 1$  and the element of largest absolute value is positive.

The time taken by the routine is approximately proportional to  $n^3$ .

#### 9 Example

To compute all the eigenvalues and eigenvectors of the matrix A, where

$$A = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.18 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.18 & 0.34 & 1.18 \end{pmatrix}.$$

### 9.1 Program Text

**Note:** the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
* F02FAF Example Program Text

* Mark 16 Release. NAG Copyright 1992.

* .. Parameters ..
INTEGER NIN, NOUT
PARAMETER (NIN=5,NOUT=6)
INTEGER NMAX, LDA, LWORK
```

[NP3546/20A] F02FAF.3

```
PARAMETER
                      (NMAX=8,LDA=NMAX,LWORK=64*NMAX)
      .. Local Scalars ..
                 I, IFAIL, J, N
      TNTEGER
      CHARACTER
                       UPLO
      .. Local Arrays ..
                       A(LDA, NMAX), W(NMAX), WORK(LWORK)
      .. External Subroutines ..
      EXTERNAL
                      FO2FAF, XO4CAF
      .. Executable Statements ..
      WRITE (NOUT,*) 'F02FAF Example Program Results'
      Skip heading in data file
      READ (NIN, *)
      READ (NIN,*) N
      IF (N.LE.NMAX) THEN
         Read A from data file
         READ (NIN, *) UPLO
         IF (UPLO.EQ.'U') THEN
            READ (NIN, *) ((A(I,J), J=I, N), I=1, N)
         ELSE IF (UPLO.EQ.'L') THEN
            READ (NIN, *) ((A(I,J), J=1,I), I=1,N)
         Compute eigenvalues and eigenvectors
         IFAIL = 0
         CALL FO2FAF('Vectors', UPLO, N, A, LDA, W, WORK, LWORK, IFAIL)
         WRITE (NOUT, *)
         WRITE (NOUT, *) 'Eigenvalues'
         WRITE (NOUT, 99999) (W(I), I=1, N)
         WRITE (NOUT, *)
         CALL X04CAF('General',' ',N,N,A,LDA,'Eigenvectors',IFAIL)
      END IF
      STOP
99999 FORMAT (3X, (8F8.4))
      END
9.2 Program Data
FO2FAF Example Program Data
                               :Value of N
  'L'
                              :Value of UPLO
  4.16
       5.03
 -3.12
 0.56 -0.83
                0.76
 -0.10
        1.18
                0.34
                      1.18 :End of matrix A
9.3 Program Results
 FO2FAF Example Program Results
```

```
Eigenvalues
   0.1239 1.0051 1.9963 8.0047
Eigenvectors
            2
                  3
      1
  0.6621 0.7210 0.1588 -0.1288
4 -0.6192 0.4543 0.6266 0.1329
```

[NP3546/20A] F02FAF.4 (last)