# NAG Fortran Library Routine Document G05CGF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

## 1 Purpose

G05CGF restores the values of the seeds used by the generator mechanism (see the G05 Chapter Introduction) after a previous call to G05CFF. G05CGF is for use only with the group of routines G05CAF-G05HDF.

# 2 Specification

```
SUBROUTINE GO5CGF(IA, NI, XA, NX, IFAIL)
INTEGER IA(NI), NI, NX, IFAIL
real XA(NX)
```

# 3 Description

This routine restores the state of the generator used, using information saved by a previous call to G05CFF.

#### 4 References

None.

#### 5 Parameters

#### 1: IA(NI) – INTEGER array

Input

On entry: information about the generator, which must be unchanged from the previous call to G05CFF.

## 2: NI – INTEGER Input

On entry: the dimension of the array IA as declared in the (sub)program from which G05CGF is called.

Constraint:  $NI \geq 9$ .

#### 3: XA(NX) - real array

Input

On entry: information about the generator, which must be unchanged from the previous call of G05CFF.

# 4: NX – INTEGER

Input

On entry: the dimension of the array XA as declared in the (sub)program from which G05CGF is called.

Constraint:  $NX \ge 4$ .

#### 5: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

[NP3546/20A] G05CGF.1

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

# 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

```
\begin{aligned} \text{IFAIL} &= 1 \\ &\quad \text{On entry, NI} < 9, \\ &\quad \text{or} &\quad \text{NX} < 4. \end{aligned} \text{IFAIL} = 2
```

On entry, IA or XA has been corrupted since the previous call to G05CFF.

## 7 Accuracy

Not applicable.

## **8** Further Comments

None.

# 9 Example

The example program prints 10 pseudo-random numbers generated by G05CAF; it saves the generator state after the 2nd, and restores it after the 7th, so that the 8th, 9th and 10th numbers are the same as the 3rd, 4th and 5th.

The generator mechanism used is selected by an initial call to G05ZAF.

#### 9.1 Program Text

**Note:** the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
GO5CGF Example Program Text
Mark 20 Revised. NAG Copyright 2001.
.. Parameters ..
INTEGER
                 NOUT
PARAMETER
                  (NOUT=6)
.. Local Scalars ..
real
                 R
INTEGER
                 I, IFAIL
.. Local Arrays ..
                 X(5), XA(4)
real
INTEGER
                 IA(9)
.. External Functions ..
real
                 G05CAF
EXTERNAL
                 G05CAF
.. External Subroutines ..
                 GO5CBF, GO5CFF, GO5CGF, GO5ZAF
EXTERNAL
.. Executable Statements ..
CALL G05ZAF('O')
WRITE (NOUT, *) 'G05CGF Example Program Results'
WRITE (NOUT, *)
CALL GO5CBF(0)
```

G05CGF.2 [NP3546/20A]

## 9.2 Program Data

None.

## 9.3 Program Results

[NP3546/20A] G05CGF.3 (last)