

NAG Fortran Library Routine Document

G05DZF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

G05DZF returns a pseudo-random logical value `.TRUE.` with probability p and `.FALSE.` with probability $(1 - p)$.

2 Specification

```
LOGICAL FUNCTION G05DZF(P)
  real          P
```

3 Description

The routine returns the logical value of the relation

$$y < p$$

where y is a pseudo-random number from a uniform distribution over $(0,1)$, generated by G05CAF.

4 References

Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison-Wesley

5 Parameters

1: P – <i>real</i>	<i>Input</i>
----------------------	--------------

On entry: the parameter p of the distribution (i.e., the probability of a *true* value).

If $p < 0$, the value 0 is used;
 if $p > 1$, the value 1 is used.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

The example program prints the first five pseudo-random logical values generated by G05CAF after initialisation by G05CBF, when the probability of a `.TRUE.` value is 0.6.

The generator mechanism used is selected by an initial call to G05ZAF.

9.1 Program Text

Note: the listing of the example program presented below uses ***bold italicised*** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```

*      G05DZF Example Program Text
*      Mark 20 Revised. NAG Copyright 2001.
*      .. Parameters ..
  INTEGER          NOUT
  PARAMETER        (NOUT=6)
*      .. Local Scalars ..
  INTEGER          I
  LOGICAL          X
*      .. External Functions ..
  LOGICAL          G05DZF
  EXTERNAL         G05DZF
*      .. External Subroutines ..
  EXTERNAL         GO5CBF, GO5ZAF
*      .. Executable Statements ..
  CALL GO5ZAF('O')
  WRITE (NOUT,*) 'G05DZF Example Program Results'
  WRITE (NOUT,*)
  CALL GO5CBF(0)
  DO 20 I = 1, 5
*
*           X = G05DZF(0.6e0)
*
*           WRITE (NOUT,99999) X
20 CONTINUE
STOP
*
99999 FORMAT (1X,L5)
END

```

9.2 Program Data

None.

9.3 Program Results

G05DZF Example Program Results

```

F
T
T
T
F

```
