

NAG Fortran Library Routine Document

C06PXF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

C06PXF computes the three-dimensional discrete Fourier transform of a trivariate sequence of complex data values (using complex data type).

2 Specification

```
SUBROUTINE C06PXF (DIRECT, N1, N2, N3, X, WORK, IFAIL)
INTEGER          N1, N2, N3, IFAIL
complex*16      X(N1*N2*N3), WORK(*)
CHARACTER*1      DIRECT
```

3 Description

C06PXF computes the three-dimensional discrete Fourier transform of a trivariate sequence of complex data values $z_{j_1 j_2 j_3}$, where $j_1 = 0, 1, \dots, n_1 - 1$, $j_2 = 0, 1, \dots, n_2 - 1$ and $j_3 = 0, 1, \dots, n_3 - 1$.

The discrete Fourier transform is here defined by

$$\hat{z}_{k_1 k_2 k_3} = \frac{1}{\sqrt{n_1 n_2 n_3}} \sum_{j_1=0}^{n_1-1} \sum_{j_2=0}^{n_2-1} \sum_{j_3=0}^{n_3-1} z_{j_1 j_2 j_3} \times \exp\left(\pm 2\pi i \left(\frac{j_1 k_1}{n_1} + \frac{j_2 k_2}{n_2} + \frac{j_3 k_3}{n_3}\right)\right),$$

where $k_1 = 0, 1, \dots, n_1 - 1$, $k_2 = 0, 1, \dots, n_2 - 1$ and $k_3 = 0, 1, \dots, n_3 - 1$.

(Note the scale factor of $\frac{1}{\sqrt{n_1 n_2 n_3}}$ in this definition.) The minus sign is taken in the argument of the exponential within the summation when the forward transform is required, and the plus sign is taken when the backward transform is required. A call of C06PXF with DIRECT = 'F' followed by a call with DIRECT = 'B' will restore the original data.

This routine performs multiple one-dimensional discrete Fourier transforms by the fast Fourier transform (FFT) algorithm (see Brigham (1974)).

4 References

Brigham E O (1974) *The Fast Fourier Transform* Prentice-Hall

Temperton C (1983b) Self-sorting mixed-radix fast Fourier transforms *J. Comput. Phys.* **52** 1–23

5 Parameters

1: DIRECT – CHARACTER*1 *Input*

On entry: if the **Forward** transform as defined in Section 3 is to be computed, then DIRECT must be set equal to 'F'.

If the **Backward** transform is to be computed then DIRECT must be set equal to 'B'.

Constraint: DIRECT = 'F' or 'B'.

2:	N1 – INTEGER	<i>Input</i>
	<i>On entry:</i> the first dimension of the transform, n_1 .	
	<i>Constraint:</i> $N1 \geq 1$.	
3:	N2 – INTEGER	<i>Input</i>
	<i>On entry:</i> the second dimension of the transform, n_2 .	
	<i>Constraint:</i> $N2 \geq 1$.	
4:	N3 – INTEGER	<i>Input</i>
	<i>On entry:</i> the third dimension of the transform, n_3 .	
	<i>Constraint:</i> $N3 \geq 1$.	
5:	X($N1 \times N2 \times N3$) – complex*16 array	<i>Input/Output</i>
	<i>On entry:</i> the complex data values. Data values are stored in X using column-major ordering for storing multi-dimensional arrays; that is, $z_{j_1 j_2 j_3}$ is stored in $X(1 + j_1 + n_1 j_2 + n_1 n_2 j_3)$.	
	<i>On exit:</i> the corresponding elements of the computed transform.	
6:	WORK(*) – complex*16 array	<i>Workspace</i>
	Note: the dimension of the array WORK must be at least $N1 \times N2 \times N3 + N1 + N2 + N3 + 45$.	
	The workspace requirements as documented for C06PXF may be an overestimate in some implementations. For full details of the workspace required by this routine please refer to the Users' Note for your implementation.	
	<i>On exit:</i> the real part of WORK(1) contains the minimum workspace required for the current values of N1, N2 and N3 with this implementation.	
7:	IFAIL – INTEGER	<i>Input/Output</i>
	<i>On entry:</i> IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Chapter P01 for details.	
	<i>On exit:</i> IFAIL = 0 unless the routine detects an error (see Section 6).	
	For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.	

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, $N1 < 1$.

IFAIL = 2

On entry, $N2 < 1$.

IFAIL = 3

On entry, $N3 < 1$.

IFAIL = 4

On entry, DIRECT not equal to one of 'F' or 'B'.

IFAIL = 5

On entry, N1 has more than 30 prime factors.

IFAIL = 6

On entry, N2 has more than 30 prime factors.

IFAIL = 7

On entry, N3 has more than 30 prime factors.

IFAIL = 8

An unexpected error has occurred in an internal call. Check all (sub)program calls and array dimensions. Seek expert help.

7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

8 Further Comments

The time taken is approximately proportional to $n_1 n_2 n_3 \times \log(n_1 n_2 n_3)$, but also depends on the factorization of the individual dimensions n_1 , n_2 and n_3 . C06PXF is somewhat faster than average if their only prime factors are 2, 3 or 5; and fastest of all if they are powers of 2.

9 Example

This example reads in a trivariate sequence of complex data values and prints the three-dimensional Fourier transform. It then performs an inverse transform and prints the sequence so obtained, which may be compared to the original data values.

9.1 Program Text

```

*      C06PXF Example Program Text
*      Mark 19 Release. NAG Copyright 1999.
*      .. Parameters ..
  INTEGER          NIN, NOUT
  PARAMETER        (NIN=5,NOUT=6)
  INTEGER          N1MAX, N2MAX, N3MAX, NMAX, LWORK
  PARAMETER        (N1MAX=16,N2MAX=16,N3MAX=16,
+                  NMAX=N1MAX*N2MAX*N3MAX,LWORK=N1MAX+N2MAX+N3MAX+
+                  NMAX+45)
*      .. Local Scalars ..
  INTEGER          IFAIL, N, N1, N2, N3
*      .. Local Arrays ..
  COMPLEX *16      WORK(LWORK), X(NMAX)
*      .. External Subroutines ..
  EXTERNAL         C06PXF, READX, WRITX
*      .. Executable Statements ..
  WRITE (NOUT,*) 'C06PXF Example Program Results'
*      Skip heading in data file
  READ (NIN,*)
20 CONTINUE
  READ (NIN,*,END=40) N1, N2, N3
  N = N1*N2*N3
  IF (N.GE.1 .AND. N.LE.NMAX) THEN
    CALL READX(NIN,X,N1,N2,N3)
    WRITE (NOUT,*)

```

```

      WRITE (NOUT,*) 'Original data values'
      CALL WRITX(NOUT,X,N1,N2,N3)
      IFAIL = 0
*
*      -- Compute transform
      CALL C06PXF('F',N1,N2,N3,X,WORK,IFAIL)
*
*      WRITE (NOUT,*) 
      WRITE (NOUT,*) 'Components of discrete Fourier transform'
      CALL WRITX(NOUT,X,N1,N2,N3)
*
*      -- Compute inverse transform
      CALL C06PXF('B',N1,N2,N3,X,WORK,IFAIL)
*
*      WRITE (NOUT,*) 
      WRITE (NOUT,*) 
+     'Original sequence as restored by inverse transform'
      CALL WRITX(NOUT,X,N1,N2,N3)
      GO TO 20
      ELSE
         WRITE (NOUT,*) ' ** Invalid value of N1, N2 or N3'
      END IF
40 CONTINUE
      STOP
      END
*
      SUBROUTINE READX(NIN,X,N1,N2,N3)
* Read 3-dimensional complex data
* .. Scalar Arguments ..
      INTEGER          N1, N2, N3, NIN
* .. Array Arguments ..
      COMPLEX *16      X(N1,N2,N3)
* .. Local Scalars ..
      INTEGER          I, J, K
* .. Executable Statements ..
      DO 40 I = 1, N1
         DO 20 J = 1, N2
            READ (NIN,*) (X(I,J,K),K=1,N3)
20      CONTINUE
40 CONTINUE
      RETURN
      END
*
      SUBROUTINE WRITX(NOUT,X,N1,N2,N3)
* Print 3-dimensional complex data
* .. Scalar Arguments ..
      INTEGER          N1, N2, N3, NOUT
* .. Array Arguments ..
      COMPLEX *16      X(N1,N2,N3)
* .. Local Scalars ..
      INTEGER          I, J, K
* .. Intrinsic Functions ..
      INTRINSIC        DBLE, AIMAG
* .. Executable Statements ..
      DO 40 I = 1, N1
         WRITE (NOUT,*)
         WRITE (NOUT,99998) 'z(i,j,k) for i =', I
         DO 20 J = 1, N2
            WRITE (NOUT,*)
            WRITE (NOUT,99999) 'Real ', (DBLE(X(I,J,K)),K=1,N3)
            WRITE (NOUT,99999) 'Imag ', (AIMAG(X(I,J,K)),K=1,N3)
20      CONTINUE
40 CONTINUE
      RETURN
*
99999 FORMAT (1X,A,7F10.3,/(6X,7F10.3))
99998 FORMAT (1X,A,I6)
      END

```

9.2 Program Data

```
C06PXF Example Program Data
2 3 4 : values of N1, N2, N3
( 1.000, 0.000) ( 0.999,-0.040) ( 0.987,-0.159) ( 0.936,-0.352)
( 0.994,-0.111) ( 0.989,-0.151) ( 0.963,-0.268) ( 0.891,-0.454)
( 0.903,-0.430) ( 0.885,-0.466) ( 0.823,-0.568) ( 0.694,-0.720)
( 0.500, 0.500) ( 0.499, 0.040) ( 0.487, 0.159) ( 0.436, 0.352)
( 0.494, 0.111) ( 0.489, 0.151) ( 0.463, 0.268) ( 0.391, 0.454)
( 0.403, 0.430) ( 0.385, 0.466) ( 0.323, 0.568) ( 0.194, 0.720)
```

9.3 Program Results

C06PXF Example Program Results

Original data values

<i>z(i,j,k) for i =</i>	1			
Real	1.000	0.999	0.987	0.936
Imag	0.000	-0.040	-0.159	-0.352
Real	0.994	0.989	0.963	0.891
Imag	-0.111	-0.151	-0.268	-0.454
Real	0.903	0.885	0.823	0.694
Imag	-0.430	-0.466	-0.568	-0.720

<i>z(i,j,k) for i =</i>	2			
Real	0.500	0.499	0.487	0.436
Imag	0.500	0.040	0.159	0.352
Real	0.494	0.489	0.463	0.391
Imag	0.111	0.151	0.268	0.454
Real	0.403	0.385	0.323	0.194
Imag	0.430	0.466	0.568	0.720

Components of discrete Fourier transform

<i>z(i,j,k) for i =</i>	1			
Real	3.292	0.051	0.113	0.051
Imag	0.102	-0.042	0.102	0.246
Real	0.143	0.016	-0.024	-0.050
Imag	-0.086	0.153	0.127	0.086
Real	0.143	-0.050	-0.024	0.016
Imag	0.290	0.118	0.077	0.051

<i>z(i,j,k) for i =</i>	2			
Real	1.225	0.355	0.000	-0.355
Imag	-1.620	0.083	0.162	0.083
Real	0.424	0.020	0.013	-0.007
Imag	0.320	-0.115	-0.091	-0.080
Real	-0.424	0.007	-0.013	-0.020
Imag	0.320	-0.080	-0.091	-0.115

Original sequence as restored by inverse transform

<i>z(i,j,k) for i =</i>	1			
Real	1.000	0.999	0.987	0.936

Imag	-0.000	-0.040	-0.159	-0.352
Real	0.994	0.989	0.963	0.891
Imag	-0.111	-0.151	-0.268	-0.454
Real	0.903	0.885	0.823	0.694
Imag	-0.430	-0.466	-0.568	-0.720
z(i,j,k) for i = 2				
Real	0.500	0.499	0.487	0.436
Imag	0.500	0.040	0.159	0.352
Real	0.494	0.489	0.463	0.391
Imag	0.111	0.151	0.268	0.454
Real	0.403	0.385	0.323	0.194
Imag	0.430	0.466	0.568	0.720
