

NAG Fortran Library Routine Document

D02NMF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

D02NMF is a reverse communication routine for integrating stiff systems of explicit ordinary differential equations.

2 Specification

```

SUBROUTINE D02NMF (NEQ, NEQMAX, T, TOUT, Y, YDOT, RWORK, RTOL, ATOL,
1 ITOL, INFORM, YSAVE, NY2DIM, WKJAC, NWKJAC, JACPVT,
2 NJCPVT, IMON, INLN, IRES, IREVCM, ITASK, ITRACE,
3 IFAIL)

INTEGER NEQ, NEQMAX, ITOL, INFORM(23), NY2DIM, NWKJAC,
1 JACPVT(NJCPVT), NJCPVT, IMON, INLN, IRES, IREVCM,
2 ITASK, ITRACE, IFAIL
   double precision T, TOUT, Y(NEQMAX), YDOT(NEQMAX), RWORK(50+4*NEQMAX),
1 RTOL(*), ATOL(*), YSAVE(NEQMAX,NY2DIM), WKJAC(NWKJAC)

```

3 Description

D02NMF is a general purpose routine for integrating the initial value problem for a stiff system of explicit ordinary differential equations,

$$y' = g(t,y).$$

An outline of a typical calling program is given below:

```

C
C   declarations
C
C   call linear algebra setup routine
C   call integrator setup routine
C   IREVCM=0
1000 CALL D02NMF(NEQ, NEQMAX, T, TOUT, Y, YDOT, RWORK, RTOL,
+ ATOL, ITOL, INFORM, YSAVE, NY2DIM, WKJAC, NWKJAC, JACPVT,
+ NJCPVT, IMON, INLN, IRES, IREVCM, ITASK, ITRACE, IFAIL)
C   IF (IREVCM.GT.0) THEN
C     IF (IREVCM.EQ. 8) THEN
C       supply the Jacobian matrix (i)
C     ELSE IF(IREVCM.EQ.9) THEN
C       perform monitoring tasks requested by the user (ii)
C     ELSE IF(IREVCM.EQ.1.OR.IREVCM.GE.3.AND.IREVCM.LE.5) THEN
C       evaluate the derivative (iii)
C     ELSE IF(IREVCM.EQ.10) THEN
C       indicates an unsuccessful step
C     ENDIF
C   GO TO 1000
C   ENDIF
C
C   post processing (optional linear algebra diagnostic call
C   (sparse case only), optional integrator diagnostic call)
C
C   STOP
C   END

```

There are three major operations that may be required of the (sub)program from which D02NMF is called on an intermeditate return ($IREVCM \neq 0$) from D02NMF; these are denoted (i), (ii) and (iii) above.

The following sections describe in greater detail exactly what is required of each of these operations.

(i) Supply the Jacobian Matrix

You need only provide this facility if the parameter JCEVAL = 'A' (or 'F' if using sparse matrix linear algebra) in a call to the linear algebra setup routine. If the Jacobian matrix is to be evaluated numerically by the integrator, then the remainder of section (i) can be ignored.

We must define the system of nonlinear equations which is solved internally by the integrator. The time derivative, y' , has the form

$$y' = (y - z)/(hd),$$

where h is the current step size and d is a parameter that depends on the integration method in use. The vector y is the current solution and the vector z depends on information from previous time steps. This means that $\frac{d}{dy'}(\) = \frac{1}{(hd)} \frac{d}{dy}(\)$.

The system of nonlinear equations that is solved has the form

$$y' - g(t, y) = 0$$

but is solved in the form

$$r(t, y) = 0,$$

where the function r is defined by

$$r(t, y) = (hd)((y - z)/(hd) - g(t, y)).$$

It is the Jacobian matrix $\frac{\partial r}{\partial y}$ that you must supply as follows:

$$\frac{\partial r_i}{\partial y_j} = 1 - (hd) \frac{\partial g_i}{\partial y_j} \quad \text{if } i = j,$$

$$\frac{\partial r_i}{\partial y_j} = - (hd) \frac{\partial g_i}{\partial y_j} \quad \text{otherwise,}$$

where t , h and d are located in RWORK(19), RWORK(16) and RWORK(20) respectively and the array Y contains the current values of the dependent variables. Only the non-zero elements of the Jacobian need be set, since the locations where it is to be stored are preset to zero.

Hereafter in this document this operation will be referred to as JAC.

(ii) Perform tasks requested by you

This operation is essentially a monitoring function and additionally provides the opportunity of changing the current values of Y, HNEXT (the step size that the integrator proposes to take on the next step), HMIN (the minimum step size to be taken on the next step), and HMAX (the maximum step size to be taken on the next step). The scaled local error at the end of a timestep may be obtained by calling *double precision* function D02ZAF as follows:

```

      IFAIL = 1
      ERRLOC = D02ZAF(NEQ, RWORK(51+NEQMAX), RWORK(51), IFAIL)
C      CHECK IFAIL BEFORE PROCEEDING

```

The following gives details of the location within the array RWORK of variables that may be of interest to you:

Variable	Specification	Location
TCURR	the current value of the independent variable	RWORK(19)
HLAST	last step size successfully used by the integrator	RWORK(15)
HNEXT	step size that the integrator proposes to take on the next step	RWORK(16)
HMIN	minimum step size to be taken on the next step	RWORK(17)
HMAX	maximum step size to be taken on the next step	RWORK(18)
NQU	the order of the integrator used on the last step	RWORK(10)

You are advised to consult the description of MONITR in D02NBF for details on what optional input can be made.

If Y is changed, then IMON must be set to 2 before return to D02NMF. If either of the values of HMIN or HMAX are changed, then IMON must be set ≥ 3 before return to D02NMF. If HNEXT is changed, then IMON must be set to 4 before return to D02NMF.

In addition you can force D02NMF to evaluate the residual vector

$$y' - g(t,y)$$

by setting IMON = 0 and INLN = 3 and then returning to D02NMF; on return to this monitoring operation the residual vector will be stored in RWORK($50 + 2 \times \text{NEQMAX} + i$), for $i = 1, 2, \dots, \text{NEQ}$.

Hereafter in this document this operation will be referred to as MONITR.

(iii) Evaluate the derivative

This operation must evaluate the derivative vector for the explicit ordinary differential equation system defined by

$$y' = g(t,y),$$

where t is located in RWORK(19).

Hereafter in this document this operation will be referred to as FCN.

4 References

See the D02M/N Sub-chapter Introduction.

5 Parameters

Note: this routine uses **reverse communication**. Its use involves an initial entry, intermediate exits and re-entries, and a final exit, as indicated by the **parameter IREVCM**. Between intermediate exits and re-entries, **all parameters other than YDOT, RWORK, WKJAC, IMON, INLN and IRES must remain unchanged**.

- 1: NEQ – INTEGER *Input*
On initial entry: the number of differential equations to be solved.
Constraint: $\text{NEQ} \geq 1$.
- 2: NEQMAX – INTEGER *Input*
On initial entry: an upper bound on the maximum number of differential equations to be solved during the integration.
Constraint: $\text{NEQMAX} \geq \text{NEQ}$.
- 3: T – **double precision** *Input/Output*
On initial entry: the value of the independent variable t . The input value of T is used only on the first call as the initial point of the integration.
On final exit: the value at which the computed solution y is returned (usually at TOUT).
- 4: TOUT – **double precision** *Input*
On initial entry: the next value of t at which a computed solution is desired. For the initial t , the input value of TOUT is used to determine the direction of integration. Integration is permitted in either direction (see also ITASK).
Constraint: $\text{TOUT} \neq \text{T}$.

- 5: Y(NEQMAX) – *double precision* array Input/Output
On initial entry: the values of the dependent variables (solution). On the first call the first NEQ elements of y must contain the vector of initial values.
On final exit: the computed solution vector evaluated at T (usually $t = TOUT$).
- 6: YDOT(NEQMAX) – *double precision* array Input/Output
On intermediate re-entry: must be set to the derivatives as defined under the description of IREVCM.
On final exit: the time derivatives y' of the vector y at the last integration point.
- 7: RWORK(50 + 4 × NEQMAX) – *double precision* array Communication Array
On initial entry: must be the same array as used by one of the method setup routines D02NVF, D02NWF or D02MVF, and by one of the storage setup routines D02NVF, D02NTF or D02NUF. The contents of RWORK must not be changed between any call to a setup routine and the first call to D02NMF.
On intermediate re-entry: elements of RWORK must be set to quantities as defined under the description of IREVCM.
On intermediate exit: contains information for JAC, FCN and MONITR operations as described in Section 3 and the parameter IREVCM.
- 8: RTOL(*) – *double precision* array Input
Note: the dimension of the array RTOL must be at least 1 if ITOL = 1 or ITOL = 2 and at least NEQ otherwise.
On initial entry: the relative local error tolerance.
Constraint: $RTOL(i) \geq 0.0$ for all relevant i (see ITOL).
- 9: ATOL(*) – *double precision* array Input
Note: the dimension of the array ATOL must be at least 1 if ITOL = 1 or ITOL = 3 and at least NEQ otherwise.
On initial entry: the absolute local error tolerance.
Constraint: $ATOL(i) \geq 0.0$ for all relevant i (see ITOL).
- 10: ITOL – INTEGER Input
On initial entry: a value to indicate the form of the local error test. ITOL indicates to D02NMF whether to interpret either or both of RTOL or ATOL as a vector or a scalar. The error test to be satisfied is $\|e_i/w_i\| < 1.0$, where w_i is defined as follows:
- | ITOL | RTOL | ATOL | w_i |
|------|--------|--------|----------------------------------|
| 1 | scalar | scalar | $RTOL(1) \times y_i + ATOL(1)$ |
| 2 | scalar | vector | $RTOL(1) \times y_i + ATOL(i)$ |
| 3 | vector | scalar | $RTOL(i) \times y_i + ATOL(1)$ |
| 4 | vector | vector | $RTOL(i) \times y_i + ATOL(i)$ |
- e_i is an estimate of the local error in y_i , computed internally, and the choice of norm to be used is defined by a previous call to an integrator setup routine.
Constraint: $1 \leq ITOL \leq 4$.

- 11: INFORM(23) – INTEGER array *Communication Array*
- 12: YSAVE(NEQMAX,NY2DIM) – *double precision* array *Communication Array*
- 13: NY2DIM – INTEGER *Input*
- On initial entry:* the second dimension of the array YSAVE as declared in the (sub)program from which D02NMF is called. An appropriate value for NY2DIM is described in the specifications of the integrator setup routines D02NVF and D02NWF. This value must be the same as that supplied to the integrator setup routine.
- 14: WKJAC(NWKJAC) – *double precision* array *Input/Output*
- On intermediate re-entry:* elements of the Jacobian as defined under the description of IREVCM. If a numerical Jacobian was requested then WKJAC is used for workspace.
- On intermediate exit:* the Jacobian is overwritten.
- 15: NWKJAC – INTEGER *Input*
- On initial entry:* the dimension of the array WKJAC as declared in the (sub)program from which D02NMF is called. The actual size depends on the linear algebra method used. An appropriate value for NWKJAC is described in the specifications of the linear algebra setup routines D02NSF, D02NTF and D02NUF for full, banded and sparse matrix linear algebra respectively. This value must be the same as that supplied to the linear algebra setup routine.
- 16: JACPVT(NJCPVT) – INTEGER array *Communication Array*
- 17: NJCPVT – INTEGER *Input*
- On initial entry:* the dimension of the array JACPVT as declared in the (sub)program from which D02NMF is called. The actual size depends on the linear algebra method used. An appropriate value for NJCPVT is described in the specifications of the linear algebra setup routines D02NTF and D02NUF for banded and sparse matrix linear algebra respectively. This value must be the same as that supplied to the linear algebra setup routine. When full matrix linear algebra is chosen, the array JACPVT is not used and hence NJCPVT should be set to 1.
- 18: IMON – INTEGER *Input/Output*
- On intermediate exit:* used to pass information between D02NMF and the MONITR operation (see Section 3). With IREVCM = 9, IMON contains a flag indicating under what circumstances the return from D02NMF occurred.
- IMON = -2
- Exit from D02NMF after IRES = 4 caused an early termination (this facility could be used to locate discontinuities).
- IMON = -1
- The current step failed repeatedly.
- IMON = 0
- Exit from D02NMF after a call to the internal nonlinear equation solver.
- IMON = 1
- The current step was successful.
- On intermediate re-entry:* may be reset to determine subsequent action in D02NMF.
- IMON = -2
- Integration is to be halted. A return will be made from D02NMF to the calling (sub)program with IFAIL = 12.

IMON = -1

Allow D02NMF to continue with its own internal strategy. The integrator will try up to three restarts unless IMON \neq -1.

IMON = 0

Return to the internal nonlinear equation solver, where the action taken is determined by the value of INLN.

IMON = 1

Normal exit to D02NMF to continue integration.

IMON = 2

Restart the integration at the current time point. The integrator will restart from order 1 when this option is used. The solution Y, provided by the MONITR operation (see Section 3), will be used for the initial conditions.

IMON = 3

Try to continue with the same step size and order as was to be used before entering the MONITR operation (see Section 3). HMIN and HMAX may be altered if desired.

IMON = 4

Continue the integration but using a new value of HNEXT and possibly new values of HMIN and HMAX.

19: INLN – INTEGER

Input/Output

On intermediate re-entry: with IMON = 0 and IREVCM = 9, INLN specifies the action to be taken by the internal nonlinear equation solver. By setting INLN = 3 and returning to D02NMF, the residual vector is evaluated and placed in RWORK(50 + 2 × NEQMAX + i), for $i = 1, 2, \dots, \text{NEQ}$ and then the MONITR operation (see Section 3) is invoked again. At present this is the only option available: INLN must not be set to any other value.

On intermediate exit: contains a flag indicating the action to be taken, if any, by the internal nonlinear equation solver.

20: IRES – INTEGER

Input/Output

On intermediate exit: with IREVCM = 1, 2, 3, 4 or 5, IRES contains the value 1.

On intermediate re-entry: should be unchanged unless one of the following actions is required of D02NMF in which case IRES should be set accordingly.

IRES = 2

Indicates to D02NMF that control should be passed back immediately to the calling (sub)program with the error indicator set to IFAIL = 11.

IRES = 3

Indicates to D02NMF that an error condition has occurred in the solution vector, its time derivative or in the value of t . The integrator will use a smaller time step to try to avoid this condition. If this is not possible D02NMF returns to the calling (sub)program with the error indicator set to IFAIL = 7.

IRES = 4

Indicates to D02NMF to stop its current operation and to enter the MONITR operation (see Section 3) immediately.

21: IREVCM – INTEGER

Input/Output

On initial entry: must contain 0.

On intermediate re-entry: should remain unchanged.

On intermediate exit: indicates what action you must take before re-entering. The possible exit values of IREVCM are 1, 3, 4, 5, 8, 9 or 10, which should be interpreted as follows:

IREVCM = 1, 3, 4 and 5

Indicates that an FCN operation (see Section 3) is required: $y' = g(t, y)$ must be supplied, where $Y(i)$ is located in y_i , for $i = 1, 2, \dots, \text{NEQ}$.

For IREVCM = 1 or 3, y'_i should be placed in location $\text{RWORK}(50 + 2 \times \text{NEQMAX} + i)$, for $i = 1, 2, \dots, \text{NEQ}$.

For IREVCM = 4, y'_i should be placed in location $\text{RWORK}(50 + \text{NEQMAX} + i)$, for $i = 1, 2, \dots, \text{NEQ}$.

For IREVCM = 5, y'_i should be placed in location $\text{YDOT}(i)$, for $i = 1, 2, \dots, \text{NEQ}$.

IREVCM = 8

Indicates that a JAC operation (see Section 3) is required: the Jacobian matrix must be supplied.

If full matrix linear algebra is being used, then the (i, j) th element of the Jacobian must be stored in $\text{WKJAC}((j - 1) \times \text{NEQ} + i)$.

If banded matrix linear algebra is being used then the (i, j) th element of the Jacobian must be stored in $\text{WKJAC}((i - 1) \times m_B + k)$, where $m_B = m_L + m_U + 1$ and $k = \min(m_L - i + 1, 0) + j$; here m_L and m_U are the number of subdiagonals and superdiagonals, respectively, in the band.

If sparse matrix linear algebra is being used then D02NRF must be called to determine which column of the Jacobian is required and where it should be stored.

```
CALL D02NRF(J, IPLACE, INFORM)
```

will return in J the number of the column of the Jacobian that is required and will set $\text{IPLACE} = 1$ or 2. If $\text{IPLACE} = 1$, then the (i, j) th element of the Jacobian must be stored in $\text{RWORK}(50 + 2 \times \text{NEQMAX} + i)$; otherwise it must be stored in $\text{RWORK}(50 + \text{NEQMAX} + i)$.

IREVCM = 9

Indicates that a MONITR operation (see Section 3) can be performed.

IREVCM = 10

Indicates that the current step was not successful, due to error test failure or convergence test failure. The only information supplied to you on this return is the current value of the independent variable t , located in $\text{RWORK}(19)$. No values must be changed before re-entering D02NMF; this facility enables you to determine the number of unsuccessful steps.

On final exit: IREVCM = 0 indicated the user-specified task has been completed or an error has been encountered (see the descriptions for ITASK and IFAIL).

Constraint: IREVCM = 0, 1, 3, 4, 5, 8, 9 or 10.

22: ITASK – INTEGER

Input

On initial entry: the task to be performed by the integrator.

ITASK = 1

Normal computation of output values of $y(t)$ at $t = \text{TOUT}$ (by overshooting and interpolating).

ITASK = 2

Take one step only and return.

ITASK = 3

Stop at the first internal integration point at or beyond $t = \text{TOUT}$ and return.

ITASK = 4

Normal computation of output values of $y(t)$ at $t = TOUT$ but without overshooting $t = TCRIT$. TCRIT must be specified as an option in one of the integrator setup routines prior to the first call to the integrator, or specified in the optional input routine prior to a continuation call. TCRIT (e.g., see D02NVF) may be equal to or beyond TOUT, but not before it in the direction of integration.

ITASK = 5

Take one step only and return, without passing TCRIT (e.g., see D02NVF). TCRIT must be specified under ITASK = 4.

Constraint: $1 \leq ITASK \leq 5$.

23: ITRACE – INTEGER *Input*

On initial entry: the level of output that is printed by the integrator. ITRACE may take the value $-1, 0, 1, 2$ or 3 .

ITRACE < -1

-1 is assumed and similarly if ITRACE > 3 , then 3 is assumed.

ITRACE = -1

No output is generated.

ITRACE = 0

Only warning messages are printed on the current error message unit (see X04AAF).

ITRACE > 0

Warning messages are printed as above, and on the current advisory message unit (see X04ABF) output is generated which details Jacobian entries, the nonlinear iteration and the time integration. The advisory messages are given in greater detail the larger the value of ITRACE.

24: IFAIL – INTEGER *Input/Output*

On initial entry: IFAIL must be set to $0, -1$ or 1 . If you are unfamiliar with this parameter you should refer to Chapter P01 for details.

On final exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, because for this routine the values of the output parameters may be useful even if IFAIL $\neq 0$ on exit, the recommended value is -1 . **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, the integrator detected an illegal input, or that a linear algebra and/or integrator setup routine has not been called prior to the call to the integrator. If ITRACE ≥ 0 , the form of the error will be detailed on the current error message unit (see X04AAF).

IFAIL = 2

The maximum number of steps specified has been taken (see the description of optional inputs in the integrator setup routines and the optional input continuation routine, D02NZF).

IFAIL = 3

With the given values of RTOL and ATOL no further progress can be made across the integration range from the current point T. The components $Y(1), Y(2), \dots, Y(\text{NEQ})$ contain the computed values of the solution at the current point T.

IFAIL = 4

There were repeated error test failures on an attempted step, before completing the requested task, but the integration was successful as far as T. The problem may have a singularity, or the local error requirements may be inappropriate.

IFAIL = 5

There were repeated convergence test failures on an attempted step, before completing the requested task, but the integration was successful as far as T. This may be caused by an inaccurate Jacobian matrix or one which is incorrectly computed.

IFAIL = 6

Some error weight w_i became zero during the integration (see the description of ITOL). Pure relative error control ($\text{ATOL}(i) = 0.0$) was requested on a variable (the i th) which has now vanished. The integration was successful as far as T.

IFAIL = 7

The FCN operation (see Section 3) set the error flag IRES = 3 continually despite repeated attempts by the integrator to avoid this.

IFAIL = 8

Not used for this integrator.

IFAIL = 9

A singular Jacobian $\frac{\partial r}{\partial y}$ has been encountered. This error exit is unlikely to be taken when solving explicit ordinary differential equations. You should check the problem formulation and Jacobian calculation.

IFAIL = 10

An error occurred during Jacobian formulation or back-substitution (a more detailed error description may be directed to the current error message unit, see X04AAF).

IFAIL = 11

The FCN operation (see Section 3) signalled the integrator to halt the integration and return by setting IRES = 2. Integration was successful as far as T.

IFAIL = 12

The MONITR operation (see Section 3) set IMON = -2 and so forced a return but the integration was successful as far as T.

IFAIL = 13

The requested task has been completed, but it is estimated that a small change in RTOL and ATOL is unlikely to produce any change in the computed solution. (Only applies when you are not operating in one step mode, that is when ITASK \neq 2 or 5.)

IFAIL = 14

The values of RTOL and ATOL are so small that the routine is unable to start the integration.

7 Accuracy

The accuracy of the numerical solution may be controlled by a careful choice of the parameters RTOL and ATOL, and to a much lesser extent by the choice of norm. You are advised to use scalar error control unless the components of the solution are expected to be poorly scaled. For the type of decaying solution typical of many stiff problems, relative error control with a small absolute error threshold will be most appropriate (that is, you are advised to choose ITOL = 1 with ATOL(1) small but positive).

8 Further Comments

The cost of computing a solution depends critically on the size of the differential system and to a lesser extent on the degree of stiffness of the problem; also on the type of linear algebra being used. For further details see Section 8 of the documents for D02NBF (full matrix), D02NCF (banded matrix) or D02NDF (sparse matrix).

In general, you are advised to choose the backward differentiation formula option (setup routine D02NVF) but if efficiency is of great importance and especially if it is suspected that $\frac{\partial g}{\partial y}$ has complex eigenvalues near the imaginary axis for some part of the integration, you should try the BLEND option (setup routine D02NWF).

9 Example

We solve the well-known stiff Robertson problem

$$\begin{aligned} a' &= -0.04a + 1.0D4bc \\ b' &= 0.04a - 1.0D4bc - 3.0D7b^2 \\ c' &= 3.0D7b^2 \end{aligned}$$

over the range $[0, 10]$ with initial conditions $a = 1.0$ and $b = c = 0.0$ and with scalar error control (ITOL = 1). We integrate until we pass TOUT = 10.0 providing C^1 interpolation at intervals of 2.0 through a MONITR operation. The integration method used is the BDF method (setup routine D02NVF) with a modified Newton method. We specify that the Jacobian is a full matrix (setup routine D02NSF) and is to be calculated numerically.

9.1 Program Text

```
*      D02NMF Example Program Text
*      Mark 14 Revised. NAG Copyright 1989.
*      .. Parameters ..
      INTEGER          NOUT
      PARAMETER       (NOUT=6)
      INTEGER          NEQ, NEQMAX, NRW, NINF, NWKJAC, NJCPVT, MAXORD,
+                    NY2DIM, MAXSTP, MXHNIL
      PARAMETER       (NEQ=3, NEQMAX=NEQ, NRW=50+4*NEQMAX, NINF=23,
+                    NWKJAC=NEQMAX*(NEQMAX+1), NJCPVT=1, MAXORD=5,
+                    NY2DIM=MAXORD+1, MAXSTP=200, MXHNIL=5)
      INTEGER          LACORB, LSAVRB
      PARAMETER       (LACORB=50+NEQMAX, LSAVRB=LACORB+NEQMAX)
      DOUBLE PRECISION HO, HMAX, HMIN, TCRIT
      PARAMETER       (HO=0.0D0, HMAX=10.0D0, HMIN=1.0D-10, TCRIT=0.0D0)
      LOGICAL          PETZLD
      PARAMETER       (PETZLD=.FALSE.)
*      .. Local Scalars ..
      DOUBLE PRECISION H, HLAST, HNEXT, HU, T, TC, TCUR, TOLSF, TOUT,
+                    XOUT
      INTEGER          I, IFAIL, IFLAG, IMON, IMXER, INLN, IOUT, IRES,
+                    IREVCN, ITASK, ITOL, ITRACE, LACOR1, LACOR2,
+                    LACOR3, LSAVR1, LSAVR2, LSAVR3, NITER, NJE, NQ,
```

```

+           NQU, NRE, NST
* .. Local Arrays ..
DOUBLE PRECISION ATOL(NEQMAX), CONST(6), RTOL(NEQMAX), RWORK(NRW),
+           WKJAC(NWKJAC), Y(NEQMAX), YDOT(NEQMAX),
+           YSAVE(NEQMAX,NY2DIM)
INTEGER        INFORM(NINF), JACPVT(NJCPVT)
LOGICAL        ALGEQU(NEQMAX)
* .. External Subroutines ..
EXTERNAL       DO2NMF, DO2NSF, DO2NVF, DO2NYF, DO2XKF, X04ABF
* .. Intrinsic Functions ..
INTRINSIC      DBLE, INT
* .. Executable Statements ..
WRITE (NOUT,*) 'D02NMF Example Program Results'
WRITE (NOUT,*)
CALL X04ABF(1,NOUT)

*
* Integrate to TOUT by overshooting TOUT (ITASK=1) using B.D.F.
* formulae with a Newton method. Default values for the array CONST
* are used. Employ scalar tolerances and the Jacobian is evaluated
* internally. On the reverse communication call equivalent to the
* MONITR call in forward communication routines carry out
* interpolation using DO2XKF.
*
T = 0.0D0
TOUT = 10.0D0
ITASK = 1
IOUT = 1
XOUT = 2.0D0
Y(1) = 1.0D0
Y(2) = 0.0D0
Y(3) = 0.0D0
ITOL = 1
RTOL(1) = 1.0D-4
ATOL(1) = 1.0D-7
DO 20 I = 1, 6
    CONST(I) = 0.0D0
20 CONTINUE
IFAIL = 0

*
CALL DO2NVF(NEQMAX,NY2DIM,MAXORD,'Newton',PETZLD,CONST,TCRIT,HMIN,
+           HMAX,HO,MAXSTP,MXHNIL,'Average-L2',RWORK,IFAIL)
CALL DO2NSF(NEQ,NEQMAX,'Numerical',NWKJAC,RWORK,IFAIL)

*
LACOR1 = LACORB + 1
LACOR2 = LACORB + 2
LACOR3 = LACORB + 3
LSAVR1 = LSAVRB + 1
LSAVR2 = LSAVRB + 2
LSAVR3 = LSAVRB + 3
WRITE (NOUT,*) '      X           Y(1)           Y(2)           Y(3)'
WRITE (NOUT,99999) T, (Y(I),I=1,NEQ)

*
* Soft fail and error messages only
IREVCM = 0
ITRACE = 0
40 IFAIL = 1

*
CALL DO2NMF(NEQ,NEQMAX,T,TOUT,Y,YDOT,RWORK,RTOL,ATOL,ITOL,INFORM,
+           YSAVE,NY2DIM,WKJAC,NWKJAC,JACPVT,NJCPVT,IMON,INLN,
+           IRES,IREVCM,ITASK,ITRACE,IFAIL)

*
IF (IREVCM.NE.0) THEN
    IF (IREVCM.EQ.1 .OR. IREVCM.EQ.3) THEN
*       Equivalent to FCN evaluation in forward communication
*       routines
        RWORK(LSAVR1) = -0.04D0*Y(1) + 1.0D4*Y(2)*Y(3)
        RWORK(LSAVR2) = 0.04D0*Y(1) - 1.0D4*Y(2)*Y(3) - 3.0D7*Y(2)
+           *Y(2)
        RWORK(LSAVR3) = 3.0D7*Y(2)*Y(2)
    ELSE IF (IREVCM.EQ.4) THEN
*       Equivalent to FCN evaluation in forward communication

```

```

*      routines
      RWORK(LACOR1) = -0.04D0*Y(1) + 1.0D4*Y(2)*Y(3)
      RWORK(LACOR2) = 0.04D0*Y(1) - 1.0D4*Y(2)*Y(3) - 3.0D7*Y(2)
+      *Y(2)
      RWORK(LACOR3) = 3.0D7*Y(2)*Y(2)
ELSE IF (IREVCM.EQ.5) THEN
*      Equivalent to FCN evaluation in forward communication
*      routines
      YDOT(1) = -0.04D0*Y(1) + 1.0D4*Y(2)*Y(3)
      YDOT(2) = 0.04D0*Y(1) - 1.0D4*Y(2)*Y(3) - 3.0D7*Y(2)*Y(2)
      YDOT(3) = 3.0D7*Y(2)*Y(2)
ELSE IF (IREVCM.EQ.9) THEN
*      Equivalent to MONITR call in forward communication routines
      IF (IMON.EQ.1) THEN
          TC = RWORK(19)
          HLAST = RWORK(15)
          HNEXT = RWORK(16)
          NQU = INT(RWORK(10))
60      CONTINUE
          IF (TC-HLAST.LT.XOUT .AND. XOUT.LE.TC) THEN
              IFLAG = 1
*
+          CALL D02XKF(XOUT,RWORK(LSAVR1),NEQ,YSAVE,NEQMAX,
+          NY2DIM,RWORK(LACOR1),NEQ,TC,NQU,HLAST,
+          HNEXT,IFLAG)
*
          IF (IFLAG.NE.0) THEN
              IMON = -2
          ELSE
              WRITE (NOUT,99999) XOUT, (RWORK(LSAVRB+I),I=1,NEQ)
              IOUT = IOUT + 1
              XOUT = DBLE(IOUT)*2.0D0
              IF (IOUT.LT.6) GO TO 60
          END IF
      END IF
      END IF
      ELSE IF (IREVCM.EQ.2 .OR. IREVCM.EQ.6 .OR. IREVCM.EQ.7 .OR.
+      IREVCM.EQ.8) THEN
          WRITE (NOUT,*)
          WRITE (NOUT,99995) 'Illegal value of IREVCM = ', IREVCM
          STOP
      END IF
      GO TO 40
  ELSE
      IF (IFAIL.EQ.0) THEN
*
+          CALL D02NYF(NEQ,NEQMAX,HU,H,TCUR,TOLSF,RWORK,NST,NRE,NJE,
+          NQU,NQ,NITER,IMXER,ALGEQU,INFORM,IFAIL)
*
          WRITE (NOUT,*)
          WRITE (NOUT,99997) ' HUSED = ', HU, ' HNEXT = ', H,
+          ' TCUR = ', TCUR
          WRITE (NOUT,99996) ' NST = ', NST, ' NRE = ', NRE,
+          ' NJE = ', NJE
          WRITE (NOUT,99996) ' NQU = ', NQU, ' NQ = ', NQ,
+          ' NITER = ', NITER
          WRITE (NOUT,99995) ' Max err comp = ', IMXER
          WRITE (NOUT,*)
      ELSE
          WRITE (NOUT,*)
          WRITE (NOUT,99998) 'Exit D02NMF with IFAIL = ', IFAIL,
+          ' and T = ', T
      END IF
      END IF
      STOP
*
99999 FORMAT (1X,F8.3,3(F13.5,2X))
99998 FORMAT (1X,A,I2,A,E12.5)
99997 FORMAT (1X,A,E12.5,A,E12.5,A,E12.5)
99996 FORMAT (1X,A,I6,A,I6,A,I6)
99995 FORMAT (1X,A,I4)

```

END

9.2 Program Data

None.

9.3 Program Results

D02NMF Example Program Results

X	Y(1)	Y(2)	Y(3)
0.000	1.00000	0.00000	0.00000
2.000	0.94161	0.00003	0.05836
4.000	0.90551	0.00002	0.09446
6.000	0.87926	0.00002	0.12072
8.000	0.85854	0.00002	0.14144
10.000	0.84135	0.00002	0.15863

HUSED = 0.90178E+00 HNEXT = 0.90178E+00 TCUR = 0.10766E+02
NST = 55 NRE = 128 NJE = 16
NQU = 4 NQ = 4 NITER = 78
Max err comp = 3
