

NAG Fortran Library Routine Document

D02TGF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

D02TGF solves a system of linear ordinary differential equations by least-squares fitting of a series of Chebyshev polynomials using collocation.

2 Specification

```

SUBROUTINE D02TGF(N, M, L, XO, X1, K1, KP, C, IC, COEFF, BDYC, W, LW,
1              IW, LIW, IFAIL)
  INTEGER      N, M(N), L(N), K1, KP, IC, LW, IW(LIW), LIW, IFAIL
  real       XO, X1, C(IC,N), W(LW)
  EXTERNAL    COEFF, BDYC

```

3 Description

The routine calculates an approximate solution of a linear or linearised system of ordinary differential equations as a Chebyshev-series. Suppose there are n differential equations for n variables y_1, y_2, \dots, y_n , over the range (x_0, x_1) . Let the i th equation be

$$\sum_{j=1}^{m_i+1} \sum_{k=1}^n f_{kj}^i(x) y_k^{(j-1)}(x) = r^i(x)$$

where $y_k^{(j)}(x) = \frac{d^j y_k(x)}{dx^j}$. The routine COEFF provided by the user evaluates the coefficients $f_{kj}^i(x)$ and the right-hand side $r^i(x)$ for each i , $1 \leq i \leq n$, at any point x . The boundary conditions may be applied either at the end-points or at intermediate points; they are written in the same form as the differential equations, and specified by the routine BDYC. For example the j th boundary condition out of those associated with the i th differential equation takes the form

$$\sum_{j=1}^{l_i+1} \sum_{k=1}^n f_{kj}^{ij}(x^{ij}) y_k^{(j-1)}(x^{ij}) = r^{ij}(x^{ij}),$$

where x^{ij} lies between x_0 and x_1 . It is assumed in this routine that certain of the boundary conditions are associated with each differential equation. This is for the user's convenience; the grouping does not affect the results.

The degree of the polynomial solution must be the same for all variables. The user specifies the degree required, $k_1 - 1$, and the number of collocation points, k_p , in the range. The routine sets up a system of linear equations for the Chebyshev coefficients, with n equations for each collocation point and one for each boundary condition. The collocation points are chosen at the extrema of a shifted Chebyshev polynomial of degree $k_p - 1$. The boundary conditions are satisfied exactly, and the remaining equations are solved by a least-squares method. The result produced is a set of Chebyshev coefficients for the n functions y_1, y_2, \dots, y_n , with the range normalised to $[-1, 1]$.

E02AKF can be used to evaluate the components of the solution at any point on the range $[x_0, x_1]$ (see Section 9 for an example). E02AHF and E02AJF may be used to obtain Chebyshev-series representations of derivatives and integrals (respectively) of the components of the solution.

4 References

Picken S M (1970) Algorithms for the solution of differential equations in Chebyshev-series by the selected points method *Report Math. 94* National Physical Laboratory

5 Parameters

- 1: N – INTEGER *Input*
On entry: the number of differential equations in the system, n .
Constraint: $N \geq 1$.
- 2: M(N) – INTEGER array *Input*
On entry: $M(i)$ must be set to the highest order derivative occurring in the i th equation, for $i = 1, 2, \dots, N$.
Constraint: $M(i) \geq 1$, for $i = 1, 2, \dots, n$.
- 3: L(N) – INTEGER array *Input*
On entry: $L(i)$ must be set to the number of boundary conditions associated with the i th equation, for $i = 1, 2, \dots, n$.
Constraint: $L(i) \geq 0$, for $i = 1, 2, \dots, n$.
- 4: X0 – *real* *Input*
On entry: the left-hand boundary, x_0 .
- 5: X1 – *real* *Input*
On entry: the right-hand boundary, x_1 .
Constraint: $X1 > X0$.
- 6: K1 – INTEGER *Input*
On entry: the number of coefficients, k_1 , to be returned in the Chebyshev-series representation of the solution (hence, the degree of the polynomial approximation is $K1 - 1$).
Constraint: $K1 \geq 1 + \max_{1 \leq i \leq N} M(i)$.
- 7: KP – INTEGER *Input*
On entry: the number of collocation points to be used, k_p .
Constraint: $N \times KP \geq N \times K1 + \sum_{i=1}^N L(i)$.
- 8: C(IC,N) – *real* array *Output*
On exit: the k th column of C contains the computed Chebyshev coefficients of the k th component of the solution, y_k ; that is, the computed solution is:
- $$y_k = \sum_{i=1}^{k_1} C(i, k) T_{i-1}(x), \quad 1 \leq k \leq n,$$
- where $T_i(x)$ is the Chebyshev polynomial of the first kind and Σ' denotes that the first coefficient, $C(1, k)$, is halved.
- 9: IC – INTEGER *Input*
On entry: the first dimension of the array C as declared in the (sub)program from which D02TGF is called.

Constraint: $IC \geq K1$.

- 10: COEFF – SUBROUTINE, supplied by the user. *External Procedure*

COEFF defines the system of differential equations (see Section 3). It must evaluate the coefficient functions $f_{kj}^i(x)$ and the right-hand side function $r^i(x)$ of the i th equation at a given point. Only non-zero entries of the array A and RHS need be specifically assigned, since all elements are set to zero by D02TGF before calling COEFF.

Its specification is:

| | | |
|---|-------------------------------|---------------------|
| <pre> SUBROUTINE COEFF(X, I, A, IA, IA1, RHS) INTEGER I, IA, IA1 real X, A(IA,IA1), RHS </pre> | | |
| <p>Important: the dimension declaration for A must contain the variable IA, not an integer constant.</p> | | |
| 1: | X – real | <i>Input</i> |
| <i>On entry:</i> the point x at which the functions must be evaluated. | | |
| 2: | I – INTEGER | <i>Input</i> |
| <i>On entry:</i> the equation for which the coefficients and right-hand side are to be evaluated. | | |
| 3: | A(IA,IA1) – real array | <i>Input/Output</i> |
| <i>On entry:</i> all elements of A are set to zero. | | |
| <i>On exit:</i> A(k, j) must contain the value $f_{kj}^i(x)$, for $1 \leq k \leq n$, $1 \leq j \leq m_i + 1$. | | |
| 4: | IA – INTEGER | <i>Input</i> |
| 5: | IA1 – INTEGER | <i>Input</i> |
| <i>On entry:</i> the first and second dimensions of A, respectively. | | |
| 6: | RHS – real | <i>Input/Output</i> |
| <i>On entry:</i> RHS is set to zero. | | |
| <i>On exit:</i> it must contain the value $r^i(x)$. | | |

COEFF must be declared as EXTERNAL in the (sub)program from which D02TGF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

- 11: BDYC – SUBROUTINE, supplied by the user. *External Procedure*

BDYC defines the boundary conditions (see Section 3). It must evaluate the coefficient functions f_{kj}^{ij} and right-hand side function r^{ij} in the j th boundary condition associated with the i th equation, at the point x^{ij} at which the boundary condition is applied. Only non-zero entries of the array A and RHS need be specifically assigned, since all elements are set to zero by D02TGF before calling BDYC.

Its specification is:

| | | |
|--|-----------------|---------------|
| <pre> SUBROUTINE BDYC(X, I, J, A, IA, IA1, RHS) INTEGER I, J, IA, IA1 real X, A(IA,IA1), RHS </pre> | | |
| <p>Important: the dimension declaration for A must contain the variable IA, not an integer constant.</p> | | |
| 1: | X – real | <i>Output</i> |
| <i>On exit:</i> the value x^{ij} at which the boundary condition is applied. | | |

| | | |
|----|---|---------------------|
| 2: | I – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the differential equation with which the condition is associated. | |
| 3: | J – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the boundary condition for which the coefficients and right-hand side are to be evaluated. | |
| 4: | A(IA,IA1) – <i>real</i> array | <i>Input/Output</i> |
| | <i>On entry:</i> all elements of A are set to zero. | |
| | <i>On exit:</i> the value $f_{kj}^{ij}(x^{ij})$ for $1 \leq k \leq n$, $1 \leq j \leq m_i + 1$. | |
| 5: | IA – INTEGER | <i>Input</i> |
| 6: | IA1 – INTEGER | <i>Input</i> |
| | <i>On entry:</i> the first and second dimensions of A, respectively. | |
| 7: | RHS – <i>real</i> | <i>Input/Output</i> |
| | <i>On entry:</i> RHS is set to zero. | |
| | <i>On exit:</i> the value $r^{ij}(x^{ij})$. | |

BDYC must be declared as EXTERNAL in the (sub)program from which D02TGF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

- 12: W(LW) – *real* array *Workspace*
 13: LW – INTEGER *Input*
- On entry:* the dimension of the array W as declared in the (sub)program from which D02TGF is called.
- Constraint:* $LW \geq 2 \times (N \times KP + NL) \times (N \times K1 + 1) + 7 \times N \times K1$, where $NL = \sum_{i=1}^n L(i)$.
- 14: IW(LIW) – INTEGER array *Workspace*
 15: LIW – INTEGER *Input*
- On entry:* the dimension of the array IW as declared in the (sub)program from which D02TGF is called.
- Constraint:* $LIW \geq N \times K1 + 1$.
- 16: IFAIL – INTEGER *Input/Output*
- On entry:* IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.
- On exit:* IFAIL = 0 unless the routine detects an error (see Section 6).
- For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, $N < 1$,
 or $M(i) < 1$ for some i ,
 or $L(i) < 0$ for some i ,
 or $X0 \geq X1$,
 or $K1 < 1 + M(i)$ for some i ,
 or $N \times KP < N \times K1 + \sum_{i=1}^n L(i)$,
 or $IC < K1$.

IFAIL = 2

On entry, LW is too small (see Section 5),
 or $LIW < N \times K1$.

IFAIL = 3

Either the boundary conditions are not linearly independent, or the rank of the matrix of equations for the coefficients is less than the number of unknowns. Increasing KP may overcome this latter problem.

IFAIL = 4

The least-squares routine F04AMF has failed to correct the first approximate solution (see F04AMF). Increasing KP may remove this difficulty.

7 Accuracy

Estimates of the accuracy of the solution may be obtained by using the checks described in Section 8. The Chebyshev coefficients are calculated by a stable numerical method.

8 Further Comments

The time taken by the routine depends on the complexity of the system of differential equations, the degree of the polynomial solution and the number of matching points.

If the number of matching points k_p is equal to the number of coefficients k_1 minus the average number of boundary conditions $\frac{1}{n} \sum_{i=1}^n l_i$, then the least-squares solution reduces to simple solution of linear equations and true collocation results. The accuracy of the solution may be checked by repeating the calculation with different values of k_1 . If the Chebyshev coefficients decrease rapidly, the size of the last two or three gives an indication of the error. If they do not decrease rapidly, it may be desirable to use a different method. Note that the Chebyshev coefficients are calculated for the range normalised to $[-1, 1]$.

Generally the number of boundary conditions required is equal to the sum of the orders of the n differential equations. However, in some cases fewer boundary conditions are needed, because the assumption of a polynomial solution is equivalent to one or more boundary conditions (since it excludes singular solutions).

A system of **nonlinear** differential equations must be linearised before using the routine. The calculation is repeated iteratively. On each iteration the linearised equation is used. In the example in Section 9, the y variables are to be determined at the current iteration whilst the z variables correspond to the solution determined at the previous iteration, (or the initial approximation on the first iteration). For a starting approximation, we may take, say, a linear function, and set up the appropriate Chebyshev coefficients before starting the iteration. For example, if $y_1 = ax + b$ in the range (x_0, x_1) , we set B, the array of coefficients,

$$B(1, 1) = a \times (x_0 + x_1) + 2 \times b,$$

$$B(1, 2) = a \times (x_1 - x_0)/2,$$

and the remainder of the entries to zero.

In some cases a better initial approximation may be needed and can be obtained by using E02ADF or E02AFF to obtain a Chebyshev-series for an approximate solution. The coefficients of the current iterate must be communicated to COEFF and BDYC, e.g., in COMMON. (See Section 9.) The convergence of the (Newton) iteration cannot be guaranteed in general, though it is usually satisfactory from a good starting approximation.

9 Example

To solve the nonlinear system

$$2y_1' + (y_2^2 - 1)y_1 + y_2 = 0,$$

$$2y_2'' - y_1' = 0,$$

in the range $(-1, 1)$, with $y_1 = 0$, $y_2 = 3$, $y_2' = 0$ at $x = -1$.

Suppose an approximate solution is z_1 , z_2 such that $y_1 \sim z_1$, $y_2 \sim z_2$: then the first equation gives, on linearising,

$$2y_1' + (z_2^2 - 1)y_1 + (2z_1z_2 + 1)y_2 = 2z_1z_2^2.$$

The starting approximation is taken to be $z_1 = 0$, $z_2 = 3$. In the program below, the array B is used to hold the coefficients of the previous iterate (or of the starting approximation). We iterate until the Chebyshev coefficients converge to 5 figures. E02AKF is used to calculate the solution from its Chebyshev coefficients.

9.1 Program Text

Note: the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      D02TGF Example Program Text
*      Mark 20 Revised. NAG Copyright 2001.
*      .. Parameters ..
INTEGER          N, MIMAX, K1, IC, KP, LSUM, LW, LIW
PARAMETER       (N=2, MIMAX=8, K1=MIMAX+1, IC=K1, KP=15, LSUM=3,
+              LW=2*(N*KP+LSUM)*(N*K1+1)+7*N*K1, LIW=N*K1)
INTEGER          NOUT
PARAMETER       (NOUT=6)
*      .. Scalars in Common ..
real           XO, X1
*      .. Arrays in Common ..
real          B(K1,N)
*      .. Local Scalars ..
real          EMAX, X
INTEGER          I, IA1, IFAIL, ITER, J, K
*      .. Local Arrays ..
real          C(IC,N), W(LW), Y(N)
INTEGER          IW(LIW), L(N), M(N)
*      .. External Subroutines ..
EXTERNAL        BDYC, COEFF, D02TGF, E02AKF
*      .. Intrinsic Functions ..
INTRINSIC       ABS, real, MAX
*      .. Common blocks ..
COMMON         /ABC/B, XO, X1
*      .. Executable Statements ..
WRITE (NOUT,*) 'D02TGF Example Program Results'
XO = -1.0e0
X1 = 1.0e0
M(1) = 1
M(2) = 2
L(1) = 1
L(2) = 2
DO 40 J = 1, N
  DO 20 I = 1, K1
    B(I,J) = 0.0e0
```

```

20    CONTINUE
40    CONTINUE
      B(1,2) = 6.0e0
      ITER = 0
60    ITER = ITER + 1
      WRITE (NOUT,*)
      WRITE (NOUT,99999) ' Iteration', ITER,
+    ' Chebyshev coefficients are'
      IFAIL = 1
*
      CALL D02TGF(N,M,L,X0,X1,K1,KP,C,IC,COEFF,BDYC,W,LW,IW,LIW,IFAIL)
*
      IF (IFAIL.EQ.0) THEN
        DO 80 J = 1, N
          WRITE (NOUT,99998) (C(I,J),I=1,K1)
80      CONTINUE
          EMAX = 0.0e0
          DO 120 J = 1, N
            DO 100 I = 1, K1
              EMAX = MAX(EMAX,ABS(C(I,J)-B(I,J)))
              B(I,J) = C(I,J)
100     CONTINUE
120    CONTINUE
          IF (EMAX.LT.1.0e-5) THEN
            K = 9
            IA1 = 1
            WRITE (NOUT,*)
            WRITE (NOUT,99999) 'Solution evaluated at', K,
+          ' equally spaced points'
            WRITE (NOUT,*)
            WRITE (NOUT,99997) '      X ', (J,J=1,N)
            DO 160 I = 1, K
              X = (X0*real(K-I)+X1*real(I-1))/real(K-1)
              DO 140 J = 1, N
                IFAIL = 0
*
                CALL E02AKF(K1,X0,X1,C(1,J),IA1,K1,X,Y(J),IFAIL)
*
140         CONTINUE
            WRITE (NOUT,99996) X, (Y(J),J=1,N)
160        CONTINUE
          ELSE
            GO TO 60
          END IF
        ELSE
          WRITE (NOUT,*)
          WRITE (NOUT,99999) 'D02TGF fails with IFAIL =', IFAIL
        END IF
      STOP
*
99999  FORMAT (1X,A,I3,A)
99998  FORMAT (1X,9F8.4)
99997  FORMAT (1X,A,2('      Y(',I1,')'))
99996  FORMAT (1X,3F10.4)
      END
*
      SUBROUTINE COEFF(X,I,A,IA,IA1,RHS)
*    .. Parameters ..
      INTEGER          N, MIMAX, K1
      PARAMETER        (N=2,MIMAX=8,K1=MIMAX+1)
*    .. Scalar Arguments ..
      real             RHS, X
      INTEGER          I, IA, IA1
*    .. Array Arguments ..
      real             A(IA,IA1)
*    .. Scalars in Common ..
      real             X0, X1
*    .. Arrays in Common ..
      real             B(K1,N)
*    .. Local Scalars ..
      real             Z1, Z2

```

```

      INTEGER          IFAIL
*    .. External Subroutines ..
EXTERNAL            EO2AKF
*    .. Common blocks ..
COMMON              /ABC/B, X0, X1
*    .. Executable Statements ..
IF (I.LE.1) THEN
  IFAIL = 0
*
  CALL EO2AKF(K1,X0,X1,B(1,1),1,K1,X,Z1,IFAIL)
  CALL EO2AKF(K1,X0,X1,B(1,2),1,K1,X,Z2,IFAIL)
*
  A(1,1) = Z2*Z2 - 1.0e0
  A(1,2) = 2.0e0
  A(2,1) = 2.0e0*Z1*Z2 + 1.0e0
  RHS = 2.0e0*Z1*Z2*Z2
ELSE
  A(1,2) = -1.0e0
  A(2,3) = 2.0e0
END IF
RETURN
END
*
SUBROUTINE BDYC(X,I,J,A,IA,IA1,RHS)
*    .. Scalar Arguments ..
  real              RHS, X
INTEGER            I, IA, IA1, J
*    .. Array Arguments ..
  real              A(IA,IA1)
*    .. Executable Statements ..
X = -1.0e0
A(I,J) = 1.0e0
IF (I.EQ.2 .AND. J.EQ.1) RHS = 3.0e0
RETURN
END

```

9.2 Program Data

None.

9.3 Program Results

D02TGF Example Program Results

```

Iteration 1 Chebyshev coefficients are
-0.5659 -0.1162 0.0906 -0.0468 0.0196 -0.0069 0.0021 -0.0006 0.0001
 5.7083 -0.1642 -0.0087 0.0059 -0.0025 0.0009 -0.0003 0.0001 -0.0000

```

```

Iteration 2 Chebyshev coefficients are
-0.6338 -0.1599 0.0831 -0.0445 0.0193 -0.0071 0.0023 -0.0006 0.0001
 5.6881 -0.1792 -0.0144 0.0053 -0.0023 0.0008 -0.0003 0.0001 -0.0000

```

```

Iteration 3 Chebyshev coefficients are
-0.6344 -0.1604 0.0828 -0.0446 0.0193 -0.0071 0.0023 -0.0006 0.0001
 5.6880 -0.1793 -0.0145 0.0053 -0.0023 0.0008 -0.0003 0.0001 -0.0000

```

```

Iteration 4 Chebyshev coefficients are
-0.6344 -0.1604 0.0828 -0.0446 0.0193 -0.0071 0.0023 -0.0006 0.0001
 5.6880 -0.1793 -0.0145 0.0053 -0.0023 0.0008 -0.0003 0.0001 -0.0000

```

Solution evaluated at 9 equally spaced points

| X | Y(1) | Y(2) |
|---------|---------|--------|
| -1.0000 | -0.0000 | 3.0000 |
| -0.7500 | -0.2372 | 2.9827 |
| -0.5000 | -0.3266 | 2.9466 |
| -0.2500 | -0.3640 | 2.9032 |
| 0.0000 | -0.3828 | 2.8564 |
| 0.2500 | -0.3951 | 2.8077 |
| 0.5000 | -0.4055 | 2.7577 |

| | | |
|--------|---------|--------|
| 0.7500 | -0.4154 | 2.7064 |
| 1.0000 | -0.4255 | 2.6538 |
