NAG Fortran Library Routine Document F04ABF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

F04ABF calculates the accurate solution of a set of real symmetric positive-definite linear equations with multiple right-hand sides, using a Cholesky factorization and iterative refinement.

2 Specification

```
SUBROUTINE FO4ABF(A, IA, B, IB, N, M, C, IC, WKSPCE, BB, IBB, IFAIL)

INTEGER

IA, IB, N, M, IC, IBB, IFAIL

real

A(IA,*), B(IB,*), C(IC,*), WKSPCE(*), BB(IBB,*)
```

3 Description

Given a set of real linear equations AX = B, where A is symmetric positive-definite, this routine first computes a Cholesky factorization of A as $A = LL^T$, where L is lower triangular. An approximation to X is found by forward and backward substitution. The residual matrix R = B - AX is then calculated using **additional precision**, and a correction D to X is found by solving $LL^TD = R$. X is replaced by X + D, and this iterative refinement of the solution is repeated until full machine accuracy has been obtained.

4 References

Wilkinson J H and Reinsch C (1971) Handbook for Automatic Computation II, Linear Algebra Springer-Verlag

5 Parameters

1: A(IA,*) - real array

Input/Output

Note: the second dimension of the array A must be at least max(1, N).

On entry: the upper triangle of the n by n positive-definite symmetric matrix A. The elements of the array below the diagonal need not be set.

On exit: the elements of the array below the diagonal are overwritten; the upper triangle of A is unchanged.

2: IA – INTEGER Input

On entry: the first dimension of the array A as declared in the (sub)program from which F04ABF is called.

Constraint: IA $\geq \max(1, N)$.

3: B(IB,*) - real array

Input

Note: the second dimension of the array B must be at least max(1, M).

On entry: the n by m right-hand side matrix B.

4: IB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F04ABF is called.

[NP3546/20A] F04ABF.1

Constraint: $IB \ge max(1, N)$.

5: N – INTEGER

Input

On entry: n, the order of the matrix A.

Constraint: N > 0.

6: M - INTEGER

Input

On entry: m, the number of right-hand sides.

Constraint: $M \ge 0$.

7: C(IC,*) - real array

Output

Note: the second dimension of the array C must be at least max(1, M).

On exit: the n by m solution matrix X.

8: IC – INTEGER

Input

On entry: the first dimension of the array C as declared in the (sub)program from which F04ABF is called.

Constraint: $IC \ge max(1, N)$.

9: WKSPCE(*) - *real* array

Workspace

Note: the dimension of the array WKSPCE must be at least max(1, N).

10: BB(IBB,*) - real array

Output

Note: the second dimension of the array BB must be at least max(1, M).

On exit: the final n by m residual matrix R = B - AX.

11: IBB – INTEGER

Input

On entry: the first dimension of the array BB as declared in the (sub)program from which F04ABF is called.

Constraint: IBB $\geq \max(1, N)$.

12: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

The matrix A is not positive-definite possibly due to rounding errors.

F04ABF.2 [NP3546/20A]

IFAIL = 2

Iterative refinement fails to improve the solution, i.e., the matrix A is too ill-conditioned.

```
\begin{split} IFAIL &= 3 \\ On \ entry, \ N &< 0, \\ or \qquad M &< 0, \\ or \qquad IA &< max(1,N), \\ or \qquad IB &< max(1,N), \\ or \qquad IC &< max(1,N), \\ or \qquad IBB &< max(1,N). \end{split}
```

7 Accuracy

The computed solutions should be correct to full machine accuracy. For a detailed error analysis see page 39 of Wilkinson and Reinsch (1971).

8 Further Comments

The time taken by the routine is approximately proportional to n^3 .

If there is only one right-hand side, it is simpler to use F04ASF.

9 Example

To solve the set of linear equations AX = B where

$$A = \begin{pmatrix} 5 & 7 & 6 & 5 \\ 7 & 10 & 8 & 7 \\ 6 & 8 & 10 & 9 \\ 5 & 7 & 9 & 10 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 23 \\ 32 \\ 33 \\ 31 \end{pmatrix}.$$

9.1 Program Text

Note: the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
FO4ABF Example Program Text
*
      Mark 15 Revised. NAG Copyright 1991.
      .. Parameters ..
                        NMAX, IA, IB, IC, IBB
      INTEGER
                        (NMAX=8, IA=NMAX, IB=NMAX, IC=NMAX, IBB=NMAX)
      PARAMETER
                       NIN, NOUT
      INTEGER
      PARAMETER
                        (NIN=5, NOUT=6)
      .. Local Scalars ..
                        I, IFAIL, J, M, N
      INTEGER
      .. Local Arrays ..
      real
                        A(IA,NMAX), B(IB,1), BB(IBB,1), C(IC,1),
                        WKSPCE (NMAX)
      .. External Subroutines ..
                       FO4ABF
      .. Executable Statements ..
      WRITE (NOUT,*) 'F04ABF Example Program Results'
      Skip heading in data Ûle
      READ (NIN, *)
      READ (NIN,*) N
      WRITE (NOUT, *)
      IF (N.GE.O .AND. N.LE.NMAX) THEN
         READ (NIN, *) ((A(I,J), J=1,N), I=1,N), (B(I,1), I=1,N)
         IFAIL = 0
         CALL FO4ABF(A, IA, B, IB, N, M, C, IC, WKSPCE, BB, IBB, IFAIL)
```

[NP3546/20A] F04ABF.3

```
*
    WRITE (NOUT,*) ' Solution'
    WRITE (NOUT,99998) (C(I,1),I=1,N)
ELSE
    WRITE (NOUT,99999) 'N is out of range: N = ', N
END IF
STOP
*
99999 FORMAT (1X,A,I5)
99998 FORMAT (1X,F9.4)
END
```

9.2 Program Data

```
FO4ABF Example Program Data
           6
   7
       10
           8
      8 10
   6
                9
   5
       7
           9
                10
  23
           33
       32
                31
```

9.3 Program Results

```
FO4ABF Example Program Results Solution
```

1.0000 1.0000 1.0000

1.0000

F04ABF.4 (last) [NP3546/20A]