

NAG Fortran Library Routine Document

F04CHF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F04CHF computes the solution to a complex system of linear equations $AX = B$, where A is an n by n Hermitian matrix and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

2 Specification

```

SUBROUTINE F04CHF (UPLO, N, NRHS, A, LDA, IPIV, B, LDB, RCOND, ERBND,
1                IFAIL)
INTEGER          N, NRHS, LDA, IPIV(*), LDB, IFAIL
double precision RCOND, ERBND
complex*16      A(LDA,*), B(LDB,*)
CHARACTER*1     UPLO

```

3 Description

The diagonal pivoting method is used to factor A as $A = UDU^H$, if $UPLO = 'U'$, or $A = LDL^H$, if $UPLO = 'L'$, where U (or L) is a product of permutation and unit upper (lower) triangular matrices, and D is Hermitian and block diagonal with 1 by 1 and 2 by 2 diagonal blocks. The factored form of A is then used to solve the system of equations $AX = B$.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia URL: <http://www.netlib.org/lapack/lug>

Higham N J (2002) *Accuracy and Stability of Numerical Algorithms* (2nd Edition) SIAM, Philadelphia

5 Parameters

- 1: UPLO – CHARACTER*1 *Input*
On entry: if UPLO = 'U', the upper triangle of the matrix A is stored, if UPLO = 'L', the lower triangle of the matrix A is stored.
Constraint: UPLO = 'U' or 'L'.
- 2: N – INTEGER *Input*
On entry: the number of linear equations n , i.e., the order of the matrix A .
Constraint: $N \geq 0$.
- 3: NRHS – INTEGER *Input*
On entry: the number of right-hand sides r , i.e., the number of columns of the matrix B .
Constraint: NRHS ≥ 0 .

- 4: A(LDA,*) – **complex*16** array Input/Output
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the n by n Hermitian matrix A .
 If UPLO = 'U', the leading N by N upper triangular part of the array A contains the upper triangular part of the matrix A , and the strictly lower triangular part of A is not referenced; if UPLO = 'L', the leading N by N lower triangular part of the array A contains the lower triangular part of the matrix A , and the strictly upper triangular part of A is not referenced.
On exit: if IFAIL ≥ 0 , the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization $A = UDU^H$ or $A = LDL^H$ as computed by F07MRF (ZHETRF).
- 5: LDA – INTEGER Input
On entry: the first dimension of the array A as declared in the (sub)program from which F04CHF is called.
Constraint: $LDA \geq \max(1, N)$.
- 6: IPIV(*) – INTEGER array Output
Note: the dimension of the array IPIV must be at least $\max(1, N)$.
On exit: if IFAIL ≥ 0 , details of the interchanges and the block structure of D , as determined by F07MRF (ZHETRF).
 If $IPIV(k) > 0$, then rows and columns k and $IPIV(k)$ were interchanged, and d_{kk} is a 1 by 1 diagonal block;
 if UPLO = 'U' and $IPIV(k) = IPIV(k-1) < 0$, then rows and columns $k-1$ and $-IPIV(k)$ were interchanged and $d_{k-1:k, k-1:k}$ is a 2 by 2 diagonal block;
 if UPLO = 'L' and $IPIV(k) = IPIV(k+1) < 0$, then rows and columns $k+1$ and $-IPIV(k)$ were interchanged and $d_{k:k+1, k:k+1}$ is a 2 by 2 diagonal block.
- 7: B(LDB,*) – **complex*16** array Input/Output
Note: the second dimension of the array B must be at least $\max(1, NRHS)$. To solve the equations $Ax = b$, where b is a single right-hand side, B may be supplied as a one-dimensional array with length $LDB = \max(1, N)$.
On entry: the n by r matrix of right-hand sides B .
On exit: if IFAIL = 0 or $N + 1$, the n by r solution matrix X .
- 8: LDB – INTEGER Input
On entry: the first dimension of the array B as declared in the (sub)program from which F04CHF is called.
Constraint: $LDB \geq \max(1, N)$.
- 9: RCOND – **double precision** Output
On exit: if IFAIL ≥ 0 , an estimate of the reciprocal of the condition number of the matrix A , computed as $RCOND = 1 / (\|A\|_1 \|A^{-1}\|_1)$.
- 10: ERRBND – **double precision** Output
On exit: if IFAIL = 0 or $N + 1$, an estimate of the forward error bound for a computed solution \hat{x} , such that $\|\hat{x} - x\|_1 / \|x\|_1 \leq ERRBND$, where \hat{x} is a column of the computed solution returned in the array B and x is the corresponding column of the exact solution X . If RCOND is less than **machine precision**, then ERRBND is returned as unity.

11: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL < 0 and IFAIL \neq -999

If IFAIL = - i , the i th argument had an illegal value.

IFAIL = -999

Allocation of memory failed. The **double precision** allocatable memory required is N , and the **complex*16** allocatable memory required is $\max(2 \times N, \text{LWORK})$, where LWORK is the optimum workspace required by F07MNF (ZHESV). If this failure occurs it may be possible to solve the equations by calling the packed storage version of F04CHF, F04CJF, or by calling F07MNF (ZHESV) directly with less than the optimum workspace (see Chapter F07).

IFAIL > 0 and IFAIL \leq N

If IFAIL = i , d_{ii} is exactly zero. The factorization has been completed, but the block diagonal matrix D is exactly singular, so the solution could not be computed.

IFAIL = N + 1

RCOND is less than **machine precision**, so that the matrix A is numerically singular. A solution to the equations $AX = B$ has nevertheless been computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A + E)\hat{x} = b,$$

where

$$\|E\|_1 = O(\epsilon)\|A\|_1$$

and ϵ is the **machine precision**. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \leq \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$, the condition number of A with respect to the solution of the linear equations. F04CHF uses the approximation $\|E\|_1 = \epsilon \|A\|_1$ to estimate ERRBND. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Further Comments

The total number of floating-point operations required to solve the equations $AX = B$ is proportional to $(\frac{1}{3}n^3 + 2n^2r)$. The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

Routine F04DHF is for complex symmetric matrices, and the real analogue of F04CHF is F04BHF.

9 Example

To solve the equations

$$AX = B,$$

where A is the Hermitian indefinite matrix

$$A = \begin{pmatrix} -1.84 & 0.11 - 0.11i & -1.78 - 1.18i & 3.91 - 1.50i \\ 0.11 + 0.11i & -4.63 & -1.84 + 0.03i & 2.21 + 0.21i \\ -1.78 + 1.18i & -1.84 - 0.03i & -8.87 & 1.58 - 0.90i \\ 3.91 + 1.50i & 2.21 - 0.21i & 1.58 + 0.90i & -1.36 \end{pmatrix}$$

and

$$B = \begin{pmatrix} 2.98 - 10.18i & 28.68 - 39.89i \\ -9.58 + 3.88i & -24.79 - 8.40i \\ -0.77 - 16.05i & 4.23 - 70.02i \\ 7.79 + 5.48i & -35.39 + 18.01i \end{pmatrix}.$$

An estimate of the condition number of A and an approximate error bound for the computed solutions are also printed.

9.1 Program Text

Note: the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      F04CHF Example Program Text
*      Mark 21 Release. NAG Copyright 2004.
*      .. Parameters ..
INTEGER          NIN, NOUT
PARAMETER       (NIN=5,NOUT=6)
INTEGER          NMAX, NRHSMX
PARAMETER       (NMAX=8,NRHSMX=2)
INTEGER          LDA, LDB
PARAMETER       (LDA=NMAX,LDB=NMAX)
*      .. Local Scalars ..
DOUBLE PRECISION ERRBND, RCOND
INTEGER          I, IERR, IFAIL, J, N, NRHS
*      .. Local Arrays ..
COMPLEX *16      A(LDA,NMAX), B(LDB,NRHSMX)
INTEGER          IPIV(NMAX)
CHARACTER        CLABS(1), RLABS(1)
*      .. External Subroutines ..
EXTERNAL         F04CHF, X04DBF
*      .. Executable Statements ..
WRITE (NOUT,*) 'F04CHF Example Program Results'
WRITE (NOUT,*)
*      Skip heading in data file
READ (NIN,*)
READ (NIN,*) N, NRHS
IF (N.LE.NMAX .AND. NRHS.LE.NRHSMX) THEN
*
*          Read the upper triangular part of A from data file
*
```

```

      READ (NIN,*) ((A(I,J),J=I,N),I=1,N)
*
*   Read B from data file
*
      READ (NIN,*) ((B(I,J),J=1,NRHS),I=1,N)
*
*   Solve the equations AX = B for X
*
      IFAIL = -1
      CALL F04CHF('Upper',N,NRHS,A,LDA,IPIV,B,LDB,RCOND,ERRBND,IFAIL)
*
      IF (IFAIL.EQ.0) THEN
*
*       Print solution, estimate of condition number and approximate
*       error bound
*
          IERR = 0
          CALL X04DBF('General',' ',N,NRHS,B,LDB,'Bracketed',' ',
+                   'Solution','Integer',RLABS,'Integer',CLABS,80,0,
+                   IERR)
*
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'Estimate of condition number'
          WRITE (NOUT,99999) 1.0D0/RCOND
          WRITE (NOUT,*)
          WRITE (NOUT,*)
+         'Estimate of error bound for computed solutions'
          WRITE (NOUT,99999) ERBND
          ELSE IF (IFAIL.EQ.N+1) THEN
*
*       Matrix A is numerically singular. Print estimate of
*       reciprocal of condition number and solution
*
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'Estimate of reciprocal of condition number'
          WRITE (NOUT,99999) RCOND
*
          WRITE (NOUT,*)
          IERR = 0
          CALL X04DBF('General',' ',N,NRHS,B,LDB,'Bracketed',' ',
+                   'Solution','Integer',RLABS,'Integer',CLABS,80,0,
+                   IERR)
*
          ELSE IF (IFAIL.GT.0 .AND. IFAIL.LE.N) THEN
*
*       The upper triangular matrix U is exactly singular. Print
*       details of factorization
*
          WRITE (NOUT,*)
          IERR = 0
          CALL X04DBF('Upper','Non-unit diagonal',N,N,A,LDA,
+                   'Bracketed',' ','Details of factorization',
+                   'Integer',RLABS,'Integer',CLABS,80,0,IERR)
*
*       Print pivot indices
*
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'Pivot indices'
          WRITE (NOUT,99998) (IPIV(I),I=1,N)
          END IF
          ELSE
            WRITE (NOUT,*) 'NMAX and/or NRHSMX too small'
          END IF
          STOP
*
99999 FORMAT (8X,1P,E9.1)
99998 FORMAT ((1X,7I11))
      END

```

9.2 Program Data

F04CHF Example Program Data

```

      4              2                      :N and NRHS
( -1.84,  0.00) (  0.11, -0.11) ( -1.78, -1.18) (  3.91, -1.50)
              ( -4.63 , 0.00) ( -1.84,  0.03) (  2.21,  0.21)
              ( -8.87,  0.00) (  1.58, -0.90)
                              ( -1.36 , 0.00) :End matrix A

(  2.98,-10.18) ( 28.68,-39.89)
( -9.58,  3.88) (-24.79, -8.40)
( -0.77,-16.05) (  4.23,-70.02)
(  7.79,  5.48) (-35.39, 18.01)                      :End matrix B

```

9.3 Program Results

F04CHF Example Program Results

Solution

```

              1              2
1 (  2.0000,  1.0000) ( -8.0000,  6.0000)
2 (  3.0000, -2.0000) (  7.0000, -2.0000)
3 ( -1.0000,  2.0000) ( -1.0000,  5.0000)
4 (  1.0000, -1.0000) (  3.0000, -4.0000)

```

Estimate of condition number
6.7E+00

Estimate of error bound for computed solutions
7.4E-16
