

NAG Fortran Library Routine Document

F06TMF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06TMF performs the transformation

$$A \leftarrow PAP^H$$

where A is an n by n complex Hermitian matrix, and P is a complex unitary matrix defined as a sequence of plane rotations, P_k , applied in planes k_1 to k_2 .

The 2 by 2 plane rotation part of P_k is assumed to have the form

$$\begin{pmatrix} c_k & \bar{s}_k \\ -s_k & c_k \end{pmatrix}$$

with c_k real.

2 Specification

```
SUBROUTINE F06TMF (UPLO, PIVOT, DIRECT, N, K1, K2, C, S, A, LDA)
INTEGER          N, K1, K2, LDA
double precision C(*)
complex*16     S(*), A(LDA,*)
CHARACTER*1     UPLO, PIVOT, DIRECT
```

3 Description

None.

4 References

None.

5 Parameters

- 1: UPLO – CHARACTER*1 *Input*
On entry: specifies whether the upper or lower triangular part of A is stored as follows:
 if UPLO = 'U', the upper triangular part of A is stored;
 if UPLO = 'L', the lower triangular part of A is stored.
Constraint: UPLO = 'U' or 'L'.
- 2: PIVOT – CHARACTER*1 *Input*
On entry: specifies the plane rotated by P_k :
 if PIVOT = 'V' (variable pivot), P_k rotates the $(k, k + 1)$ plane;
 if PIVOT = 'T' (top pivot), P_k rotates the $(k_1, k + 1)$ plane;
 if PIVOT = 'B' (bottom pivot), P_k rotates the (k, k_2) plane.
Constraint: PIVOT = 'V', 'T' or 'B'.

- 3: DIRECT – CHARACTER*1 *Input*
On entry: specifies the sequence direction:
 if DIRECT = 'F' (forward sequence), $P = P_{k_2-1} \cdots P_{k_1+1} P_{k_1}$;
 if DIRECT = 'B' (backward sequence), $P = P_{k_1} P_{k_1+1} \cdots P_{k_2-1}$.
Constraint: DIRECT = 'F' or 'B'.
- 4: N – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 5: K1 – INTEGER *Input*
 6: K2 – INTEGER *Input*
On entry: the values k_1 and k_2 .
- 7: C(*) – **double precision** array *Input*
On entry: $C(k)$ must hold c_k , the cosine of the rotation P_k , for $k = k_1, \dots, k_2 - 1$.
- 8: S(*) – **complex*16** array *Input*
On entry: $S(k)$ must hold s_k , the sine of the rotation P_k , for $k = k_1, \dots, k_2 - 1$.
- 9: A(LDA,*) – **complex*16** array *Input/Output*
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the n by n Hermitian matrix A . If UPLO = 'U', the upper triangle of A must be stored and the elements of the array below the diagonal are not referenced; if UPLO = 'L', the lower triangle of A must be stored and the elements of the array above the diagonal are not referenced.
On exit: the transformed matrix A . The imaginary parts of the diagonal elements are set to zero.
- 10: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F06TMF is called.
Constraint: $LDA \geq \max(1, N)$.

6 Error Indicators and Warnings

None.
