

NAG Fortran Library Routine Document

F06TSF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F06TSF transforms an n by n complex upper spiked matrix H to upper triangular form R by applying a complex unitary matrix P from the left or the right. H is assumed to have real diagonal elements except where the spike joins the diagonal; R has real diagonal elements. P is formed as a sequence of plane rotations in planes k_1 to k_2 .

If `SIDE = 'L'`, H is assumed to have a row spike, with non-zero elements $h_{k_2,k}$ for $k = k_1, k_1 + 1, \dots, k_2 - 1$. The rotations are applied from the left:

$$PH = R, \quad \text{where} \quad P = DP_{k_2-1} \cdots P_{k_1+1} P_{k_1},$$

P_k is a rotation in the (k, k_2) plane, and $D = \text{diag}(1, \dots, 1, d_{k_2}, 1, \dots, 1)$ with $|d_{k_2}| = 1$.

If `SIDE = 'R'`, H is assumed to have a column spike, with non-zero elements h_{k+1,k_1} for $k = k_1, k_1 + 1, \dots, k_2 - 1$. The rotations are applied from the right:

$$HP^H = R, \quad \text{where} \quad P = DP_{k_1} P_{k_1+1} \cdots P_{k_2-1},$$

P_k is a rotation in the $(k_1, k + 1)$ plane, and $D = \text{diag}(1, \dots, 1, d_{k_1}, 1, \dots, 1)$ with $|d_{k_1}| = 1$.

The 2 by 2 plane rotation part of P_k has the form

$$\begin{pmatrix} c_k & \bar{s}_k \\ -s_k & c_k \end{pmatrix}$$

with c_k real.

2 Specification

```

SUBROUTINE F06TSF (SIDE, N, K1, K2, C, S, A, LDA)
  INTEGER          N, K1, K2, LDA
  double precision C(*)
  complex*16     S(*), A(LDA,*)
  CHARACTER*1     SIDE

```

3 Description

None.

4 References

None.

5 Parameters

1: `SIDE` – CHARACTER*1

Input

On entry: specifies whether H is operated on from the left or the right, as follows:

- if `SIDE = 'L'`, H is pre-multiplied from the left;
- if `SIDE = 'R'`, H is post-multiplied from the right.

Constraint: `SIDE = 'L' or 'R'`.

- 2: N – INTEGER *Input*
On entry: n , the order of the matrix H .
Constraint: $N \geq 0$.
- 3: K1 – INTEGER *Input*
4: K2 – INTEGER *Input*
On entry: the values k_1 and k_2 .
- 5: C(*) – **double precision** array *Output*
On exit: $C(k)$ holds c_k , the cosine of the rotation P_k , for $k = k_1, \dots, k_2 - 1$.
- 6: S(*) – **complex*16** array *Input/Output*
On entry: the non-zero elements of the spike of H : $S(k)$ must hold $h_{k_2,k}$ if $SIDE = 'L'$, and h_{k+1,k_1} if $SIDE = 'R'$, for $k = k_1, k_1 + 1, \dots, k_2 - 1$.
On exit: $S(k)$ holds s_k , the sine of the rotation P_k , for $k = k_1, \dots, k_2 - 1$; $S(k_2)$ holds d_{k_2} , the k_2 th diagonal element of D , if $SIDE = 'L'$, or d_{k_1} , the k_1 th diagonal element of D , if $SIDE = 'R'$.
- 7: A(LDA,*) – **complex*16** array *Input/Output*
Note: the second dimension of the array A must be at least $\max(1, N)$.
On entry: the upper triangular part of the n by n upper spiked matrix H . The imaginary parts of the diagonal elements must be zero, except for the (k_2, k_2) element if $SIDE = 'L'$, or the (k_1, k_1) element if $SIDE = 'R'$.
On exit: the upper triangular matrix R . The imaginary parts of the diagonal elements are set to zero.
- 8: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F06TSF is called.
Constraint: $LDA \geq \max(1, N)$.

6 Error Indicators and Warnings

None.
