

NAG Fortran Library Routine Document

F07BNF (ZGBSV)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F07BNF (ZGBSV) computes the solution to a complex system of linear equations

$$AX = B,$$

where A is an n by n band matrix, with k_l sub-diagonals and k_u super-diagonals, and X and B are n by r matrices.

2 Specification

```
SUBROUTINE F07BNF (N, KL, KU, NRHS, AB, LDAB, IPIV, B, LDB, INFO)
INTEGER          N, KL, KU, NRHS, LDAB, IPIV(*), LDB, INFO
complex*16     AB(LDAB,*), B(LDB,*)
```

The routine may be called by its LAPACK name *zgbsv*.

3 Description

The LU decomposition with partial pivoting and row interchanges is used to factor A as $A = PLU$, where P is a permutation matrix, L is a product of permutation and unit lower triangular matrices with k_l sub-diagonals, and U is upper triangular with $(k_l + k_u)$ super-diagonals. The factored form of A is then used to solve the system of equations $AX = B$.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia URL: <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- | | | |
|----|--|--------------|
| 1: | N – INTEGER | <i>Input</i> |
| | <i>On entry:</i> n , the number of linear equations, i.e., the order of the matrix A . | |
| | <i>Constraint:</i> $N \geq 0$. | |
| 2: | KL – INTEGER | <i>Input</i> |
| | <i>On entry:</i> k_l , the number of sub-diagonals within the band of the matrix A . | |
| | <i>Constraint:</i> $KL \geq 0$. | |
| 3: | KU – INTEGER | <i>Input</i> |
| | <i>On entry:</i> k_u , the number of super-diagonals within the band of the matrix A . | |
| | <i>Constraint:</i> $KU \geq 0$. | |

- 4: NRHS – INTEGER *Input*
On entry: r , the number of right-hand sides, i.e., the number of columns of the matrix B .
Constraint: $\text{NRHS} \geq 0$.
- 5: AB(LDAB,*) – **complex*16** array *Input/Output*
Note: the second dimension of the array AB must be at least $\max(1, N)$.
On entry: the n by n coefficient matrix A in band storage, in rows $\text{KL} + 1$ to $2 \times \text{KL} + \text{KU} + 1$; rows 1 to KL of the array need not be set. The j th column of A is stored in the j th column of the array AB as follows:

$$\text{AB}(k_l + k_u + 1 + i - j, j) = a_{ij} \quad \text{for } \max(1, j - k_u) \leq i \leq \min(n, j + k_l).$$
See Section 8 for further details.
On exit: if $\text{INFO} \geq 0$, details of the factorization $A = \text{PLU}$; U is stored as an upper triangular band matrix with $\text{KL} + \text{KU}$ super-diagonals in rows 1 to $\text{KL} + \text{KU} + 1$, and the multipliers used during the factorization are stored in rows $\text{KL} + \text{KU} + 2$ to $2 \times \text{KL} + \text{KU} + 1$.
- 6: LDAB – INTEGER *Input*
On entry: the first dimension of the array AB as declared in the (sub)program from which F07BNF (ZGBSV) is called.
Constraint: $\text{LDAB} \geq 2 \times \text{KL} + \text{KU} + 1$.
- 7: IPIV(*) – INTEGER array *Output*
Note: the dimension of the array IPIV must be at least $\max(1, N)$.
On exit: if $\text{INFO} \geq 0$, the pivot indices that define the permutation matrix P ; at the i th step row i of the matrix was interchanged with row $\text{IPIV}(i)$. $\text{IPIV}(i) = i$ indicates a row interchange was not required.
- 8: B(LDB,*) – **complex*16** array *Input/Output*
Note: the second dimension of the array B must be at least $\max(1, \text{NRHS})$.
On entry: the n by r right-hand side matrix B .
On exit: if $\text{INFO} = 0$, the n by r solution matrix X .
- 9: LDB – INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F07BNF (ZGBSV) is called.
Constraint: $\text{LDB} \geq \max(1, N)$.
- 10: INFO – INTEGER *Output*
On exit: $\text{INFO} = 0$ unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

$\text{INFO} < 0$

If $\text{INFO} = -i$, the i th argument had an illegal value. An explanatory message is output, and execution of the program is terminated.

$$b = \begin{pmatrix} -1.06 + 21.50i \\ -22.72 - 53.90i \\ 28.24 - 38.60i \\ -34.56 + 16.73i \end{pmatrix}.$$

Details of the *LU* factorization of *A* are also output.

9.1 Program Text

Note: the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```

*      F07BNF Example Program Text
*      Mark 21 Release. NAG Copyright 2004.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER       (NIN=5,NOUT=6)
      INTEGER          NMAX, KLMAX, KUMAX
      PARAMETER       (NMAX=8,KLMAX=4,KUMAX=4)
      INTEGER          LDAB
      PARAMETER       (LDAB=2*KLMAX+KUMAX+1)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, INFO, J, K, KL, KU, N
*      .. Local Arrays ..
      COMPLEX *16      AB(LDAB,NMAX), B(NMAX)
      INTEGER          IPIV(NMAX)
      CHARACTER        CLABS(1), RLABS(1)
*      .. External Subroutines ..
      EXTERNAL         X04DFF, ZGBSV
*      .. Intrinsic Functions ..
      INTRINSIC        MAX, MIN
*      .. Executable Statements ..
      WRITE (NOUT,*) 'F07BNF Example Program Results'
      WRITE (NOUT,*)
*      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N, KL, KU
      IF (N.LE.NMAX .AND. KL.LE.KLMAX .AND. KU.LE.KUMAX) THEN
*
*          Read the band matrix A and the right hand side b from data file
*
          K = KL + KU + 1
          READ (NIN,*) ((AB(K+I-J,J),J=MAX(I-KL,1),MIN(I+KU,N)),I=1,N)
          READ (NIN,*) (B(I),I=1,N)
*
*          Solve the equations Ax = b for x
*
          CALL ZGBSV(N,KL,KU,1,AB,LDAB,IPIV,B,N,INFO)
*
          IF (INFO.EQ.0) THEN
*
*              Print solution
*
              WRITE (NOUT,*) 'Solution'
              WRITE (NOUT,99999) (B(I),I=1,N)
*
*              Print details of the factorization
*
              WRITE (NOUT,*)
              IFAIL = 0
              CALL X04DFF(N,N,KL,KL+KU,AB,LDAB,'Bracketed','F7.4',
+                  'Details of factorization','None',RLABS,'None',
+                  CLABS,80,0,IFAIL)
*
*              Print pivot indices'
*
              WRITE (NOUT,*)

```

```

        WRITE (NOUT,*) 'Pivot indices'
        WRITE (NOUT,99998) (IPIV(I),I=1,N)

        ELSE
            WRITE (NOUT,99997) 'The (', INFO, ', ', INFO, ')',
+            ' element of the factor U is zero'
        END IF
    ELSE
        WRITE (NOUT,*)
+        'One or more of NMAX, KLMAX or KUMAX is too small'
    END IF
    STOP
*
99999 FORMAT ((3X,4(' (',F7.4,',',F7.4,')',:)))
99998 FORMAT (1X,I5,3I18)
99997 FORMAT (1X,A,I3,A,I3,A,A)
    END

```

9.2 Program Data

F07BNF Example Program Data

```

  4  1  2                                     :Values of N, KL and KU
(-1.65,  2.26) (-2.05, -0.85) ( 0.97, -2.84)
( 0.00,  6.30) (-1.48, -1.75) (-3.99,  4.01) ( 0.59, -0.48)
              (-0.77,  2.83) (-1.06,  1.94) ( 3.33, -1.04)
              ( 4.48, -1.09) (-0.46, -1.72) :End of matrix A
(-1.06, 21.50) (-22.72,-53.90) ( 28.24,-38.60) (-34.56, 16.73) :End of vector B

```

9.3 Program Results

F07BNF Example Program Results

Solution

```
(-3.0000, 2.0000) ( 1.0000,-7.0000) (-5.0000, 4.0000) ( 6.0000,-8.0000)
```

Details of factorization

```
( 0.0000, 6.3000) (-1.4800,-1.7500) (-3.9900, 4.0100) ( 0.5900,-0.4800)
( 0.3587, 0.2619) (-0.7700, 2.8300) (-1.0600, 1.9400) ( 3.3300,-1.0400)
              ( 0.2314, 0.6358) ( 4.9303,-3.0086) (-1.7692,-1.8587)
              ( 0.7604, 0.2429) ( 0.4338, 0.1233)

```

Pivot indices

```

  2                3                3                4

```
