

NAG Fortran Library Routine Document

F07HTF (ZPBEQU)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F07HTF (ZPBEQU) computes a diagonal scaling matrix S intended to equilibrate a complex n by n Hermitian positive-definite band matrix A , with bandwidth $(2k_d + 1)$, and reduce its condition number.

2 Specification

```
SUBROUTINE F07HTF (UPLO, N, KD, AB, LDAB, S, SCOND, AMAX, INFO)
INTEGER N, KD, LDAB, INFO
double precision S(*), SCOND, AMAX
complex*16 AB(LDAB,*)
CHARACTER*1 UPLO
```

The routine may be called by its LAPACK name *zpbequ*.

3 Description

F07HTF (ZPBEQU) computes a diagonal scaling matrix S chosen so that

$$s_j = 1/\sqrt{a_{jj}}.$$

This means that the matrix B given by

$$B = SAS,$$

has diagonal elements equal to unity. This in turn means that the condition number of B , $\kappa_2(B)$, is within a factor n of the matrix of smallest possible condition number over all possible choices of diagonal scalings (see Corollary 7.6 of Higham (2002)).

4 References

Higham N J (2002) *Accuracy and Stability of Numerical Algorithms* (2nd Edition) SIAM, Philadelphia

5 Parameters

1: UPLO – CHARACTER*1 *Input*

On entry: indicates whether the upper or lower triangular part of A is stored in the array AB, as follows:

UPLO = 'U'

The upper triangle of A is stored.

UPLO = 'L'

The lower triangle of A is stored.

Constraint: UPLO = 'U' or 'L'.

2: N – INTEGER *Input*

On entry: n , the order of the matrix A .

Constraint: $N \geq 0$.

3:	KD – INTEGER	<i>Input</i>
<i>On entry:</i> k_d , the number of superdiagonals of the matrix A if $\text{UPLO} = \text{'U'}$, or the number of subdiagonals if $\text{UPLO} = \text{'L'}$.		
<i>Constraint:</i> $\text{KD} \geq 0$.		
4:	AB(LDAB,*) – complex*16 array	<i>Input</i>
Note: the second dimension of the array AB must be at least $\max(1, N)$.		
<i>On entry:</i> the upper or lower triangle of the Hermitian positive-definite band matrix A whose scaling factors are to be computed, stored in the first $(k_d + 1)$ rows of the array AB. The j th column of A is stored in the j th column of the array AB as follows:		
if $\text{UPLO} = \text{'U'}$, $\text{AB}(k_d + 1 + i - j, j) = a_{ij}$ for $\max(1, j - k_d) \leq i \leq j$; if $\text{UPLO} = \text{'L'}$, $\text{AB}(1 + i - j, j) = a_{ij}$ for $j \leq i \leq \min(n, j + k_d)$.		
Only the elements of the array AB corresponding to the diagonal elements of A are referenced. (Row $(k_d + 1)$ of AB when $\text{UPLO} = \text{'U'}$, row 1 of AB when $\text{UPLO} = \text{'L'}$.)		
5:	LDAB – INTEGER	<i>Input</i>
<i>On entry:</i> the first dimension of the array AB as declared in the (sub)program from which F07HTF (ZPBEQU) is called.		
<i>Constraint:</i> $\text{LDAB} \geq \text{KD} + 1$.		
6:	S(*) – double precision array	<i>Output</i>
Note: the dimension of the array S must be at least $\max(1, N)$.		
<i>On exit:</i> if $\text{INFO} = 0$ on exit, S contains the diagonal elements of the scaling matrix S .		
7:	SCOND – double precision	<i>Output</i>
<i>On exit:</i> if $\text{INFO} = 0$ on exit, SCOND contains the ratio of the smallest value of $S(i)$ to the largest value of $S(i)$. If $\text{SCOND} \geq 0.1$ and AMAX is neither too large nor too small, it is not worth scaling by S .		
8:	AMAX – double precision	<i>Output</i>
<i>On exit:</i> $\max a_{ij} $. If AMAX is very close to overflow or underflow, the matrix A should be scaled.		
9:	INFO – INTEGER	<i>Output</i>
<i>On exit:</i> $\text{INFO} = 0$ unless the routine detects an error (see Section 6).		

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

$\text{INFO} < 0$

If $\text{INFO} = -i$, the i th argument had an illegal value. An explanatory message is output, and execution of the program is terminated.

$\text{INFO} > 0$

If $\text{INFO} = i$, the i th diagonal element of A is not positive (and hence A cannot be positive-definite).

7 Accuracy

The computed scale factors will be close to the exact scale factors.

8 Further Comments

The real analogue of this routine is F07HFF (DPBEQU).

9 Example

To equilibrate the Hermitian positive-definite matrix A given by

$$A = \begin{pmatrix} 9.39 & 1.08 - 1.73i & 0 & 0 \\ 1.08 + 1.73i & 1.69 & (-0.04 + 0.29i) \times 10^{10} & 0 \\ 0 & (-0.04 - 0.29i) \times 10^{10} & 2.65 \times 10^{20} & (-0.33 + 2.24i) \times 10^{10} \\ 0 & 0 & (-0.33 - 2.24i) \times 10^{10} & 2.17 \end{pmatrix}.$$

Details of the scaling factors and the scaled matrix are output.

9.1 Program Text

```

*      F07HTF Example Program Text
*      Mark 21 Release. NAG Copyright 2004.
*      .. Parameters ..
INTEGER           NIN, NOUT
PARAMETER        (NIN=5,NOUT=6)
INTEGER           KDMAX, NMAX
PARAMETER        (KDMAX=4,NMAX=8)
INTEGER           LDAB
PARAMETER        (LDAB=KDMAX+1)
CHARACTER         UPLO
PARAMETER        (UPLO='U')
*      .. Local Scalars ..
DOUBLE PRECISION AMAX, BIG, SCOND, SJ, SMALL
INTEGER           I, IFAIL, INFO, J, JJ, KD, N
*      .. Local Arrays ..
COMPLEX *16       AB(LDAB,NMAX)
DOUBLE PRECISION S(NMAX)
CHARACTER         CLABS(1), RLABS(1)
*      .. External Functions ..
DOUBLE PRECISION X02AJF, X02AMF
INTEGER           X02BHF
EXTERNAL          X02AJF, X02AMF, X02BHF
*      .. External Subroutines ..
EXTERNAL          X04dff, ZPBEQU
*      .. Intrinsic Functions ..
INTRINSIC         MAX, MIN
*      .. Executable Statements ..
WRITE (NOUT,*) 'F07HTF Example Program Results'
WRITE (NOUT,*) 
*      Skip heading in data file
READ (NIN,*) 
READ (NIN,*) N, KD
IF (N.LE.NMAX .AND. KD.LE.KDMAX) THEN
*
*      Read the upper or lower triangular part of the band matrix A
*      from data file
*
IF (UPLO.EQ.'U') THEN
    DO 20 I = 1, N
        READ (NIN,*) (AB(KD+1+I-J,J),J=I,MIN(N,I+KD))
20   CONTINUE
ELSE IF (UPLO.EQ.'L') THEN
    DO 40 I = 1, N
        READ (NIN,*) (AB(1+I-J,J),J=MAX(1,I-KD),I)
40   CONTINUE
END IF
*
*      Print the matrix A
*
IFAIL = 0
IF (UPLO.EQ.'U') THEN

```

```

      CALL X04DFF(N,N,0,KD,AB,LDAB,'Bracketed','1P,E10.2',
      +           'Matrix A','Integer',RLABS,'Integer',CLABS,80,0,
      +           IFAIL)
      ELSE IF (UPLO.EQ.'L') THEN
          CALL X04DFF(N,N,KD,0,AB,LDAB,'Bracketed','1P,E10.2',
      +           'Matrix A','Integer',RLABS,'Integer',CLABS,80,0,
      +           IFAIL)
      END IF
      WRITE (NOUT,*)

*
* Compute diagonal scaling factors
*
      CALL ZPBEQU(UPLO,N,KD,AB,LDAB,S,SCOND,AMAX,INFO)
*
      IF (INFO.GT.0) THEN
          WRITE (NOUT,99999) 'Diagonal element', INFO,
      +           ' of A is non positive'
      ELSE
*
* Print SCOND, AMAX and the scale factors
*
          WRITE (NOUT,99998) 'SCOND = ', SCOND, ', AMAX = ', AMAX
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'Diagonal scaling factors'
          WRITE (NOUT,99997) (S(I),I=1,N)
          WRITE (NOUT,*)

*
* Compute values close to underflow and overflow
*
      SMALL = X02AMF()/(X02AJF()*X02BHF())
      BIG = 1.0D0/SMALL
      IF ((SCOND.LT.0.1D0) .OR. (AMAX.LT.SMALL) .OR. (AMAX.GT.BIG)
      +     ) THEN
*
* Scale A
*
      IF (UPLO.EQ.'U') THEN
          DO 80 J = 1, N
              SJ = S(J)
              JJ = KD + 1 - J
              DO 60 I = MAX(1,J-KD), J
                  AB(I+JJ,J) = S(I)*AB(I+JJ,J)*SJ
              CONTINUE
          CONTINUE
      ELSE IF (UPLO.EQ.'L') THEN
          DO 120 J = 1, N
              SJ = S(J)
              JJ = 1 - J
              DO 100 I = J, MIN(N,J+KD)
                  AB(I+JJ,J) = S(I)*AB(I+JJ,J)*SJ
              CONTINUE
          CONTINUE
      END IF
*
* Print the scaled matrix
*
      IFAIL = 0
      IF (UPLO.EQ.'U') THEN
          CALL X04DFF(N,N,0,KD,AB,LDAB,'Bracketed','F7.4',
      +           'Scaled matrix','Integer',RLABS,'Integer',
      +           CLABS,80,0,IFAIL)
      ELSE IF (UPLO.EQ.'L') THEN
          CALL X04DFF(N,N,KD,0,AB,LDAB,'Bracketed','F7.4',
      +           'Scaled matrix','Integer',RLABS,'Integer',
      +           CLABS,80,0,IFAIL)
      END IF
      END IF
      END IF
      ELSE
          WRITE (NOUT,*) 'NMAX and/or KDMAX too small'
      END IF

```

```

STOP
*
99999 FORMAT (1X,A,I4,A)
99998 FORMAT (1X,2(A,1P,E7.1))
99997 FORMAT ((1X,1P,7E11.1))
END

```

9.2 Program Data

```

F07HTF Example Program Data
 4   1                               :Values of N and KD
(  9.39, 0.00) ( 1.08,-1.73)
      ( 1.69, 0.00) ( -0.04E+10, 0.29E+10)
      ( 2.65E+20, 0.00      ) ( -0.33E+10, 2.24E+10)
      ( 2.17,      0.00      )
:End of matrix A

```

9.3 Program Results

F07HTF Example Program Results

Matrix A

	1	2	3
1	(9.39E+00, 0.00E+00)	(1.08E+00, -1.73E+00)	
2		(1.69E+00, 0.00E+00)	(-4.00E+08, 2.90E+09)
3			(2.65E+20, 0.00E+00)
4			
	4		
1			
2			
3	(-3.30E+09, 2.24E+10)		
4	(2.17E+00, 0.00E+00)		

SCOND = 8.0E-11, AMAX = 2.6E+20

Diagonal scaling factors

3.3E-01	7.7E-01	6.1E-11	6.8E-01
---------	---------	---------	---------

Scaled matrix

	1	2	3	4
1	(1.0000, 0.0000)	(0.2711,-0.4343)		
2		(1.0000, 0.0000)	(-0.0189, 0.1370)	
3			(1.0000, 0.0000)	(-0.1376, 0.9341)
4				(1.0000, 0.0000)
