NAG Fortran Library Routine Document F07MBF (DSYSVX)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

F07MBF (DSYSVX) uses the diagonal pivoting factorization to compute the solution to a real system of linear equations

$$AX = B$$
.

where A is an n by n symmetric matrix and X and B are n by r matrices. Error bounds on the solution and a condition estimate are also provided.

2 Specification

```
SUBROUTINE FO7MBF (FACT, UPLO, N, NRHS, A, LDA, AF, LDAF, IPIV, B, LDB, X, LDX, RCOND, FERR, BERR, WORK, LWORK, IWORK, INFO)

INTEGER N, NRHS, LDA, LDAF, IPIV(*), LDB, LDX, LWORK, IWORK(*), INFO

double precision A(LDA,*), AF(LDAF,*), B(LDB,*), X(LDX,*), RCOND, FERR(*), BERR(*), WORK(*)

CHARACTER*1 FACT, UPLO
```

The routine may be called by its LAPACK name dsysvx.

3 Description

The following steps are performed:

- 1. If FACT = 'N', the diagonal pivoting method is used to factor A. The form of the factorization is $A = UDU^T$, if UPLO = 'U' or $A = LDL^T$, if UPLO = 'L', where U (or L) is a product of permutation and unit upper (lower) triangular matrices, and D is symmetric and block diagonal with 1 by 1 and 2 by 2 diagonal blocks.
- 2. If some $d_{ii} = 0$, so that D is exactly singular, then the routine returns with INFO = i. Otherwise, the factored form of A is used to estimate the condition number of the matrix A. If the reciprocal of the condition number is less than **machine precision**, INFO = N + 1 is returned as a warning, but the routine still goes on to solve for X and compute error bounds as described below.
- 3. The system of equations is solved for X using the factored form of A.
- 4. Iterative refinement is applied to improve the computed solution matrix and to calculate error bounds and backward error estimates for it.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia URL: http://www.netlib.org/lapack/lug

Golub G H and Van Loan C F (1996) Matrix Computations (3rd Edition) Johns Hopkins University Press, Baltimore

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

[NP3657/21] F07MBF (DSYSVX).1

5 Parameters

1: FACT – CHARACTER*1

Input

On entry: specifies whether or not the factored form of A has been supplied on entry:

if FACT = 'F' on entry, AF and IPIV contain the factored form of A. AF and IPIV will not be modified;

if FACT = 'N', The matrix A will be copied to AF and factored.

Constraint: FACT = 'F' or 'N'.

2: UPLO - CHARACTER*1

Input

On entry: if UPLO = 'U', the upper triangle of A is stored.

If UPLO = 'L', the lower triangle of A is stored.

Constraint: UPLO = 'U' or 'L'.

3: N – INTEGER

Input

On entry: n, the number of linear equations, i.e., the order of the matrix A.

Constraint: N > 0.

4: NRHS – INTEGER

Input

On entry: r, the number of right-hand sides, i.e., the number of columns of the matrix B.

Constraint: NRHS ≥ 0 .

5: A(LDA,*) – *double precision* array

Input

Note: the second dimension of the array A must be at least max(1, N).

On entry: the symmetric matrix A.

If UPLO = 'U', the leading n by n upper triangular part of A contains the upper triangular part of the matrix A, and the strictly lower triangular part of A is not referenced.

If UPLO = 'L', the leading n by n lower triangular part of A contains the lower triangular part of the matrix A, and the strictly upper triangular part of A is not referenced.

6: LDA – INTEGER

Input

On entry: the first dimension of the array A as declared in the (sub)program from which F07MBF (DSYSVX) is called.

Constraint: LDA $\geq \max(1, N)$.

7: AF(LDAF,*) - double precision array

Input/Output

Note: the second dimension of the array AF must be at least max(1, N).

On entry: if FACT = 'F', AF contains the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization $A = UDU^T$ or $A = LDL^T$ as computed by F07MDF (DSYTRF).

On exit: if FACT = 'N', AF returns the block diagonal matrix D and the multipliers used to obtain the factor U or L from the factorization $A = UDU^T$ or $A = LDL^T$.

8: LDAF – INTEGER

Input

On entry: the first dimension of the array AF as declared in the (sub)program from which F07MBF (DSYSVX) is called.

Constraint: LDAF $\geq \max(1, N)$.

F07MBF (DSYSVX).2

9: IPIV(*) - INTEGER array

Input/Output

Note: the dimension of the array IPIV must be at least max(1, N).

On entry: if FACT = 'F', IPIV contains details of the interchanges and the block structure of D, as determined by F07MDF (DSYTRF). If IPIV(k) > 0, then rows and columns k and IPIV(k) were interchanged and D(k,k) is a 1 by 1 diagonal block. If UPLO = 'U' and IPIV(k) = IPIV(k-1) < 0, then rows and columns k-1 and -IPIV(k) were interchanged and D(k-1:k,k-1:k) is a 2 by 2 diagonal block. If UPLO = 'L' and IPIV(k) = IPIV(k+1) < 0, then rows and columns k+1 and -IPIV(k) were interchanged and D(k:k+1,k:k+1) is a 2 by 2 diagonal block.

On exit: if FACT = 'N', IPIV contains details of the interchanges and the block structure of D, as determined by F07MDF (DSYTRF).

10: B(LDB,*) – *double precision* array

Input

Note: the second dimension of the array B must be at least max(1, NRHS).

On entry: the n by r right-hand side matrix B.

11: LDB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F07MBF (DSYSVX) is called.

Constraint: LDB $\geq \max(1, N)$.

12: X(LDX,*) – double precision array

Output

Note: the second dimension of the array X must be at least max(1, NRHS).

On exit: if INFO = 0 or INFO = N + 1, the n by r solution matrix X.

13: LDX – INTEGER

Input

On entry: the first dimension of the array X as declared in the (sub)program from which F07MBF (DSYSVX) is called.

Constraint: LDX $\geq \max(1, N)$.

14: RCOND – double precision

Output

On exit: the estimate of the reciprocal condition number of the matrix A. If RCOND is less than the **machine precision** (in particular, if RCOND = 0), the matrix is singular to working precision. This condition is indicated by a return code of INFO > 0.

15: FERR(*) – *double precision* array

Output

Note: the dimension of the array FERR must be at least max(1, NRHS).

On exit: if INFO = 0 or INFO = N + 1, an estimate of the forward error bound for each computed solution vector, such that $\|\hat{x}_j - x_j\|_{\infty} / \|x_j\|_{\infty} \le \text{FERR}(j)$ where \hat{x}_j is the *j*th column of the computed solution returned in the array X and x_j is the corresponding column of the exact solution X. The estimate is as reliable as the estimate for RCOND, and is almost always a slight overestimate of the true error.

16: BERR(*) – *double precision* array

Output

Note: the dimension of the array BERR must be at least max(1, NRHS).

On exit: if INFO = 0 or INFO = N + 1, an estimate of the componentwise relative backward error of each computed solution vector \hat{x}_j (i.e., the smallest relative change in any element of A or B that makes \hat{x}_j an exact solution).

[NP3657/21] F07MBF (DSYSVX).3

17: WORK(*) – *double precision* array

Workspace

Note: the dimension of the array WORK must be at least max(1,LWORK).

On exit: if INFO = 0, WORK(1) returns the optimal LWORK.

18: LWORK – INTEGER

Input

On entry: the dimension of the array WORK as declared in the (sub)program from which F07MBF (DSYSVX) is called.

LWORK $\geq \max(1, 3 \times N)$, and for best performance, when FACT = 'N', LWORK $\geq \max(1, 3 \times N, N \times nb)$, where nb is the optimal blocksize for F07MDF (DSYTRF).

If LWORK = -1, a workspace query is assumed; the routine only calculates the optimal size of the WORK array, returns this value as the first entry of the WORK array, and no error message related to LWORK is issued.

19: IWORK(*) – INTEGER array

Workspace

Note: the dimension of the array IWORK must be at least max(1, N).

20: INFO - INTEGER

Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO = -i, the *i*th argument had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

If INFO = i and $i \le N$, d_{ii} is exactly zero. The factorization has been completed but the factor D is exactly singular, so the solution and error bounds could not be computed. RCOND = 0 is returned.

If $\mathrm{INFO} = i$ and $i = \mathrm{N} + 1$, D is nonsingular, but RCOND is less than *machine precision*, meaning that the matrix is singular to working precision. Nevertheless, the solution and error bounds are computed because there are a number of situations where the computed solution can be more accurate than the value of RCOND would suggest.

7 Accuracy

For each right-hand side vector b, the computed solution \hat{x} is the exact solution of a perturbed system of equations $(A+E)\hat{x}=b$, where

$$||E||_1 O(\epsilon) ||A||_1$$

where ϵ is the *machine precision*. See Chapter 11 of Higham (2002) for further details.

If \hat{x} is the true solution, then the computed solution x satisfies a forward error bound of the form

$$\frac{\|x - \hat{x}\|_{\infty}}{\|\hat{x}\|_{\infty}} \leq w_c \operatorname{cond}(A, \hat{x}, b)$$

where $\operatorname{cond}(A, \hat{x}, b) = \||A^{-1}|(|A||\hat{x}| + |b|)\|_{\infty}/\|\hat{x}\|_{\infty} \leq \operatorname{cond}(A) = \||A^{-1}||A|\|_{\infty} \leq \kappa_{\infty}(A)$. If \hat{x} is the jth column of X, then w_c is returned in $\operatorname{BERR}(j)$ and a bound on $\|x - \hat{x}\|_{\infty}/\|\hat{x}\|_{\infty}$ is returned in $\operatorname{FERR}(j)$. See Section 4.4 of Anderson *et al.* (1999) for further details.

F07MBF (DSYSVX).4

8 Further Comments

The factorization of A requires approximately $\frac{1}{2}n^3$ floating point operations.

For each right-hand side, computation of the backward error involves a minimum of $4n^2$ floating point operations. Each step of iterative refinement involves an additional $6n^2$ operations. At most 5 steps of iterative refinement are performed, but usually only 1 or 2 steps are required. Estimating the forward error involves solving a number of systems of equations of the form Ax = b; the number is usually 4 or 5 and never more than 11. Each solution involves approximately $2n^2$ operations.

The complex analogues of this routine are F07MPF (ZHESVX) for Hermitian matrices, and F07NPF (ZSYSVX) for symmetric matrices.

9 Example

To solve the equations

$$AX = B$$
,

where A is the symmetric matrix

$$A = \begin{pmatrix} -1.81 & 2.06 & 0.63 & -1.15 \\ 2.06 & 1.15 & 1.87 & 4.20 \\ 0.63 & 1.87 & -0.21 & 3.87 \\ -1.15 & 4.20 & 3.87 & 2.07 \end{pmatrix}$$

and

$$B = \begin{pmatrix} 0.96 & 3.93 \\ 6.07 & 19.25 \\ 8.38 & 9.90 \\ 9.50 & 27.85 \end{pmatrix}.$$

Error estimates for the solutions, and an estimate of the reciprocal of the condition number of the matrix A are also output.

9.1 Program Text

Note: the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
FO7MBF Example Program Text
Mark 21 Release. NAG Copyright 2004.
.. Parameters ..
INTEGER
                 NIN, NOUT
PARAMETER
                 (NIN=5,NOUT=6)
                NB, NMAX, NRHSMX
INTEGER
PARAMETER
                (NB=64,NMAX=8,NRHSMX=2)
                LDA, LDAF, LDB, LDX, LWORK
TNTEGER
PARAMETER
                 (LDA=NMAX,LDAF=NMAX,LDB=NMAX,LDX=NMAX,
                 LWORK=NB*NMAX)
.. Local Scalars ..
DOUBLE PRECISION RCOND
                I, IFAIL, INFO, J, N, NRHS
INTEGER
.. Local Arrays ..
DOUBLE PRECISION A(LDA,NMAX), AF(LDAF,NMAX), B(LDB,NRHSMX),
                 BERR(NRHSMX), FERR(NRHSMX), WORK(LWORK),
                 X(LDX,NRHSMX)
INTEGER
                 IPIV(NMAX), IWORK(NMAX)
.. External Subroutines ..
EXTERNAL
                DSYSVX, X04CAF
.. Executable Statements ..
WRITE (NOUT,*) 'FO7MBF Example Program Results'
WRITE (NOUT, *)
Skip heading in data file
READ (NIN, *)
```

[NP3657/21] F07MBF (DSYSVX).5

```
READ (NIN,*) N, NRHS
      IF (N.LE.NMAX .AND. NRHS.LE.NRHSMX) THEN
         Read the upper triangular part of A from data file
         READ (NIN,*) ((A(I,J),J=I,N),I=1,N)
         Read B from data file
         READ (NIN, *) ((B(I,J), J=1, NRHS), I=1, N)
         Solve the equations AX = B for X
         CALL DSYSVX('Not factored', 'Upper', N, NRHS, A, LDA, AF, LDAF, IPIV, B,
                     LDB, X, LDX, RCOND, FERR, BERR, WORK, LWORK, IWORK, INFO)
         IF ((INFO.EQ.O) .OR. (INFO.EQ.N+1)) THEN
            Print solution, error bounds and condition number
            IFAIL = 0
            CALL XO4CAF('General',' ',N,NRHS,X,LDX,'Solution(s)',IFAIL)
            WRITE (NOUT, *)
            WRITE (NOUT,*) 'Backward errors (machine-dependent)'
            WRITE (NOUT, 99999) (BERR(J), J=1, NRHS)
            WRITE (NOUT, *)
            WRITE (NOUT, *)
              'Estimated forward error bounds (machine-dependent)'
            WRITE (NOUT, 99999) (FERR(J), J=1, NRHS)
            WRITE (NOUT, *)
            WRITE (NOUT,*) 'Estimate of reciprocal condition number'
            WRITE (NOUT, 99999) RCOND
            WRITE (NOUT, *)
            IF (INFO.EQ.N+1) THEN
               WRITE (NOUT, *)
               WRITE (NOUT,*)
                 'The matrix A is singular to working precision'
     +
            END IF
            WRITE (NOUT, 99998) 'The diagonal block ', INFO,
              ' of D is zero'
         END IF
      ELSE
         WRITE (NOUT,*) 'NMAX and/or NRHSMX too small'
      END IF
      STOP
99999 FORMAT ((3X,1P,7E11.1))
99998 FORMAT (1X,A,I3,A)
      END
```

9.2 Program Data

```
FO7MBF Example Program Data
                           :Values of N and NRHS
 Δ
        2
-1.81
        2.06
               0.63 -1.15
               1.87 4.20
        1.15
              -0.21
                      3.87
                      2.07 :End of matrix A
 0.96
       3.93
 6.07 19.25
       9.90
 8.38
 9.50 27.85
                           :End of matrix B
```

F07MBF (DSYSVX).6 [NP3657/21]

9.3 Program Results

```
FO7MBF Example Program Results
```

```
Solution(s)

1 2
1 -5.0000 2.0000
2 -2.0000 3.0000
3 1.0000 4.0000
4 4.0000 1.0000

Backward errors (machine-dependent)
6.7E-17 5.2E-17

Estimated forward error bounds (machine-dependent)
2.4E-14 3.2E-14

Estimate of reciprocal condition number
1.3E-02
```