

# NAG Fortran Library Routine Document

## S10ACF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

S10ACF returns the value of the hyperbolic cosine,  $\cosh x$ , via the routine name.

### 2 Specification

```

real FUNCTION S10ACF(X, IFAIL)
INTEGER                IFAIL
real                  X

```

### 3 Description

The routine calculates an approximate value for the hyperbolic cosine,  $\cosh x$ .

For  $|x| \leq E_1$ ,  $\cosh x = \frac{1}{2}(e^x + e^{-x})$ .

For  $|x| > E_1$ , the routine fails owing to danger of setting overflow in calculating  $e^x$ . The result returned for such calls is  $\cosh E_1$ , i.e., it returns the result for the nearest valid argument. The value of machine-dependent constant  $E_1$  may be given in the Users' Note for your implementation.

### 4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

### 5 Parameters

1:  $X$  – *real* *Input*  
*On entry:* the argument  $x$  of the function.

2: IFAIL – INTEGER *Input/Output*  
*On entry:* IFAIL must be set to 0,  $-1$  or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.  
*On exit:* IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value  $-1$  or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. **When the value  $-1$  or 1 is used it is essential to test the value of IFAIL on exit.**

### 6 Error Indicators and Warnings

If on entry IFAIL = 0 or  $-1$ , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

The routine has been called with an argument too large in absolute magnitude. There is a danger of overflow. The result returned is the value of  $\cosh x$  at the nearest valid argument.

## 7 Accuracy

If  $\delta$  and  $\epsilon$  are the relative errors in the argument and result, respectively, then in principle

$$\epsilon \simeq x \tanh x \times \delta.$$

That is, the relative error in the argument,  $x$ , is amplified by a factor, at least  $x \tanh x$ . The equality should hold if  $\delta$  is greater than the *machine precision* ( $\delta$  is due to data errors etc.) but if  $\delta$  is simply a result of round-off in the machine representation of  $x$  then it is possible that an extra figure may be lost in internal calculation round-off.

The behaviour of the error amplification factor is shown by the following graph:




Figure 1

It should be noted that near  $x = 0$  where this amplification factor tends to zero the accuracy will be limited eventually by the *machine precision*. Also for  $|x| \geq 2$

$$\epsilon \sim x\delta = \Delta$$

where  $\Delta$  is the absolute error in the argument  $x$ .

## 8 Further Comments

None.

## 9 Example

The example program reads values of the argument  $x$  from a file, evaluates the function at each value of  $x$  and prints the results.

## 9.1 Program Text

**Note:** the listing of the example program presented below uses *bold italicised* terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      S10ACF Example Program Text
*      Mark 14 Revised.  NAG Copyright 1989.
*      .. Parameters ..
INTEGER          NIN, NOUT
PARAMETER       (NIN=5,NOUT=6)
*      .. Local Scalars ..
real           X, Y
INTEGER         IFAIL
*      .. External Functions ..
real          S10ACF
EXTERNAL        S10ACF
*      .. Executable Statements ..
WRITE (NOUT,*) 'S10ACF Example Program Results'
*      Skip heading in data file
READ (NIN,*)
WRITE (NOUT,*)
WRITE (NOUT,*) '      X              Y              IFAIL'
WRITE (NOUT,*)
20 READ (NIN,*,END=40) X
   IFAIL = 1
*
   Y = S10ACF(X,IFAIL)
*
   WRITE (NOUT,99999) X, Y, IFAIL
   GO TO 20
40 STOP
*
99999 FORMAT (1X,1P,2e12.3,I7)
END
```

## 9.2 Program Data

```
S10ACF Example Program Data
-10.0
-0.5
0.0
0.5
25.0
```

## 9.3 Program Results

```
S10ACF Example Program Results
```

| X          | Y         | IFAIL |
|------------|-----------|-------|
| -1.000E+01 | 1.101E+04 | 0     |
| -5.000E-01 | 1.128E+00 | 0     |
| 0.000E+00  | 1.000E+00 | 0     |
| 5.000E-01  | 1.128E+00 | 0     |
| 2.500E+01  | 3.600E+10 | 0     |

---