

# NAG Toolbox for MATLAB

## c06fa

### 1 Purpose

c06fa calculates the discrete Fourier transform of a sequence of  $n$  real data values (using a work array for extra speed).

### 2 Syntax

```
[x, ifail] = c06fa(x, 'n', n)
```

### 3 Description

Given a sequence of  $n$  real data values  $x_j$ , for  $j = 0, 1, \dots, n-1$ , c06fa calculates their discrete Fourier transform defined by

$$\hat{z}_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} x_j \times \exp\left(-i \frac{2\pi jk}{n}\right), \quad k = 0, 1, \dots, n-1.$$

(Note the scale factor of  $\frac{1}{\sqrt{n}}$  in this definition.) The transformed values  $\hat{z}_k$  are complex, but they form a Hermitian sequence (i.e.,  $\hat{z}_{n-k}$  is the complex conjugate of  $\hat{z}_k$ ), so they are completely determined by  $n$  real numbers (see also the C06 Chapter Introduction).

To compute the inverse discrete Fourier transform defined by

$$\hat{w}_k = \frac{1}{\sqrt{n}} \sum_{j=0}^{n-1} x_j \times \exp\left(+i \frac{2\pi jk}{n}\right),$$

this function should be followed by a call of c06gb to form the complex conjugates of the  $\hat{z}_k$ .

c06fa uses the fast Fourier transform (FFT) algorithm (see Brigham 1974). There are some restrictions on the value of  $n$  (see Section 5).

### 4 References

Brigham E O 1974 *The Fast Fourier Transform* Prentice–Hall

### 5 Parameters

#### 5.1 Compulsory Input Parameters

- 1: **x(n)** – double array  
 $x(j+1)$  must contain  $x_j$ , for  $j = 0, 1, \dots, n-1$ .

#### 5.2 Optional Input Parameters

- 1: **n** – int32 scalar

*Default:* The dimension of the array **x**.

$n$ , the number of data values. The largest prime factor of **n** must not exceed 19, and the total number of prime factors of **n**, counting repetitions, must not exceed 20.

*Constraint:*  $n > 1$ .

### 5.3 Input Parameters Omitted from the MATLAB Interface

work

### 5.4 Output Parameters

1: **x(n) – double array**

The discrete Fourier transform stored in Hermitian form. If the components of the transform  $\hat{z}_k$  are written as  $a_k + ib_k$ , and if **x** is declared with bounds  $(0 : n - 1)$  in the (sub)program from which c06fa is called, then for  $0 \leq k \leq n/2$ ,  $a_k$  is contained in **x(k)**, and for  $1 \leq k \leq (n - 1)/2$ ,  $b_k$  is contained in **x(n - k)**. (See also Section [missing entity c06background12](#) in the C06 Chapter Introduction and Section 9.)

2: **ifail – int32 scalar**

0 unless the function detects an error (see Section 6).

## 6 Error Indicators and Warnings

Errors or warnings detected by the function:

**ifail** = 1

At least one of the prime factors of **n** is greater than 19.

**ifail** = 2

**n** has more than 20 prime factors.

**ifail** = 3

On entry,  $n \leq 1$ .

**ifail** = 4

An unexpected error has occurred in an internal call. Check all (sub)program calls and array dimensions. Seek expert help.

## 7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

## 8 Further Comments

The time taken is approximately proportional to  $n \times \log n$ , but also depends on the factorization of  $n$ . c06fa is faster if the only prime factors of  $n$  are 2, 3 or 5; and fastest of all if  $n$  is a power of 2.

## 9 Example

```
x = [0.34907;
      0.54890000000000000001;
      0.74776;
      0.94459;
      1.1385;
      1.3285;
      1.5137];
[xOut, ifail] = c06fa(x)
```

```
xOut =  
    2.4836  
   -0.2660  
   -0.2577  
   -0.2564  
    0.0581  
    0.2030  
    0.5309  
ifail =  
        0
```

---