

Specifications for the NI SCXI™-1191

4 GHz Quad 4x1 50 Ω Multiplexer

This document lists specifications for the NI SCXI-1191 multiplexer module. All specifications are subject to change without notice. Visit ni.com/manuals for the most current specifications.

Configuration Quad 4x1 multiplexers

RF Performance Characteristics

Characteristic impedance (Z_0)..... 50 Ω nominal

Insertion loss

≤2.5 GHz..... <0.6 dB

≤4 GHz..... <0.9 dB

VSWR

≤2.5 GHz..... <1.3

≤4 GHz..... <1.5

Channel-to-channel isolation

≤2.5 GHz..... >60 dB

≤4 GHz..... >55 dB

Input Characteristics

All input characteristics are DC, AC_{rms} , or a combination unless otherwise specified.

Maximum switching voltage..... 30 V
(channel-to-channel and channel-to-ground)

Maximum switching current 0.33 A
(per channel)

National Instruments™, NI™, ni.com™, and SCXI™ are trademarks of National Instruments Corporation. Product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your CD, or ni.com/patents.

April 2003
323481A-01

Maximum carry current0.33 A
(per channel)

Maximum switching power10 W
(per channel)



Note National Instruments recommends against switching active RF signals. As a relay actuates, the channel is momentarily unterminated. Some RF sources can be damaged by reflections if their outputs are not properly terminated. Consult your RF source documentation for more information.

Maximum RF carry power10 W
(per channel)

DC path resistance

Initial.....<0.2 Ω

End of life>1 Ω

Path resistance is a combination of relay contact resistance and trace resistance. Contact resistance typically remains low for the life of a relay. At the end of relay life, the contact resistance rises rapidly above 1.0 Ω .

Dynamic Characteristics

Relay operate time (at 20 °C)15 ms

Release time (at 20 °C)15 ms

Expected relay life

Mechanical5,000,000 cycles

Electrical.....100,000 cycles
(maximum load)

Physical Characteristics

Relay typeElectromechanical, non-latching

I/O connectors.....20 SMA jacks

Contact material.....Gold

Dimensions (W × H × D)..... 3.0 cm × 17.3 cm × 19.6 cm
 (1.2 in. × 6.7 in. × 7.6 in.)

Weight..... 825 g
 (1 lb, 13 oz)

Environment

Operating temperature..... 0 °C to 50 °C

Storage temperature –20 °C to 70 °C

Relative humidity 5% to 85% noncondensing

Pollution Degree 2




Figure 1. NI SCXI-1191 Power-On State

Compliance and Certifications

Safety

This product is designed to meet the requirements of the following standards of safety for electrical equipment for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 3111-1, UL 61010B-1
- CAN/CSA C22.2 No. 1010.1



Note For UL and other safety certifications refer to the product label or visit ni.com.

Electromagnetic Compatibility

EmissionsEN 55011 Class A at 10 m
FCC Part 15A above 1 GHz

ImmunityEN 61326:1997 + A2:2001,
Table 1

EMC/EMICE, C-Tick, and FCC Part 15
(Class A) Compliant



Note For EMC compliance, you *must* operate this device with shielded cabling.

CE Compliance

This product meets the essential requirements of applicable European Directives, as amended for CE Marking, as follows:

Low-Voltage Directive (safety).....73/23/EEC

Electromagnetic Compatibility
Directive (EMC)89/336/EEC



Note Refer to the Declaration of Conformity (DoC) for this product for any additional regulatory compliance information. To obtain the DoC for this product, click **Declarations of Conformity Information** at ni.com/hardref.nsf/.



323481A-01

Apr03