

NI PXI/PCI-5401 Specifications

PXI/PCI Arbitrary Function Generator

This document lists the specifications for the NI PXI/PCI-5401. These specifications are typical at 25 °C unless otherwise stated. The operating temperature range is 0–50 °C.

Analog Output

Number of channels	1
Resolution	12 bits
Maximum update rate	40 MHz
DDS accumulator	32 bits
Frequency range	
Sine	16 MHz, max
SYNC (TTL).....	16 MHz, max
Square	1 MHz, max
Ramp	1 MHz, max
Triangle	1 MHz, max
Frequency resolution.....	9.31 mHz

Voltage Output

Ranges	±5 V into a 50 Ω load; ±10 V into a high-impedance load
Accuracy	±0.1 dB
Output attenuation.....	0–73 dB
Resolution	0.001 dB steps

Pre-attenuation offset	
Range	± 2.5 V into $50\ \Omega^1$
Accuracy	± 5 mV
Output coupling	DC
Output impedance	$50\ \Omega$ or $75\ \Omega$, software selectable
Load impedance	$50\ \Omega$ or greater
Output enable	Software switchable
Protection	Short-circuit protected
Typical rise/fall time	8 ns (10–90% 0–5 V square wave into $50\ \Omega$ load, filters off)

Sine Spectral Purity

Harmonic products and spurs	
Up to 1 MHz	-60 dBc
Up to 16 MHz	-35 dBc
Phase noise	-105 dBc/Hz at 10 kHz from carrier

Filter Characteristics

Digital

Type	Half-band interpolating
Selection	Software switchable (enable or disable)
Taps	67
Filter coefficients	Fixed 20-bit
Data interpolating frequency	80 MS/s
Pipeline signal delay	26 sampling periods

Analog

Type	7th-order L-C lowpass filter
Passband ripple	± 2 dB

¹ With less than 10 dB of attenuation, signal maximum plus offset (before attenuation) must not exceed ± 5 V (into $50\ \Omega$).

Waveform Specifications

Memory	16,384 16-bit samples
Segment length.....	16,384 samples, exact
Segment linking (instruction FIFO).....	512 links

Timing I/O

Update clock	Internal, 40 MHz only
Frequency locking	
External reference sources	
NI PCI-5401	Front panel PLL IN SMB connector, internal, or RTSI clock line
NI PXI-5401	Front panel PLL Ref SMB connector, internal, or PXI_CLK10
Reference clock frequencies	1 MHz, 5–20 MHz in 1 MHz steps
Frequency locking range.....	± 100 ppm

Triggers

Digital Trigger

Compatibility	TTL
Response	Rising edge
Pulse width (T_{d1}).....	20 ns, minimum
Trigger to waveform output delay (T_{d2}).....	28 sample clocks plus 150 ns, max

RTSI

Trigger lines	
NI PCI-5401	7
NI PXI-5401	7
Clock lines	
NI PCI-5401	1
NI PXI-5401	Not applicable

Bus Interface

TypeSlave

Operational Modes

TypeSingle, continuous, stepped

SYNC Out

LevelTTL

Duty cycle20–80%, software controllable

External Clock Reference Input

Frequency1 MHz or 5–20 MHz in
1 MHz steps

Amplitude $1 V_{pk-pk} \leq \text{level} \leq 5 V_{pk-pk}$

Internal Clock

Frequency40 MHz

Initial accuracy ± 5 ppm

Temperature stability (0 to 50 °C) ± 25 ppm

Aging (1 year) ± 5 ppm

Mechanical

Connectors

ARB (output)

PCISMB

PXIBNC

SYNC (output)

PCISMB

PXIBNC

PLL reference (input)SMB

External trigger in

PCI50-pin digital

PXISMB

Size.....	1 slot
Power requirements.....	5 V, 3.5 A, max; 12 V, 125 mA

Safety

This product meets the requirements of the following standards for safety for electrical equipment for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1
- CAN/CSA C22.2 No. 61010-1



Note For UL and other safety certifications, refer to the product label, or visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Electromagnetic Compatibility

Emissions	EN 55011 Class A at 10 m FCC Part 15A above 1 GHz
Immunity	EN 61326:1997 + A2:2001, Table 1
EMC/EMI.....	CE, C-Tick, and FCC Part 15 (Class A) Compliant



Note For EMC compliance, you *must* operate this device with shielded cabling.

CE Compliance

This product meets the essential requirements of applicable European Directives, as amended for CE marking, as follows:

Low-Voltage Directive (safety)	73/23/EEC
Electromagnetic Compatibility Directive (EMC)	89/336/EEC



Note Refer to the Declaration of Conformity (DoC) for this product for any additional regulatory compliance information. To obtain the DoC for this product, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

National Instruments™, NI™, ni.com™, and RTSI™ are trademarks of National Instruments Corporation. Product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your CD, or ni.com/patents.
© 2002–2004 National Instruments Corp. All rights reserved.



371321A-01

Jul04