

Oracle® Data Provider for .NET

Developer's Guide



19c for Microsoft Windows

E96613-01

May 2019

The Oracle logo, consisting of a solid red square with the word "ORACLE" in white, uppercase, sans-serif font centered within it.

ORACLE®

Oracle Data Provider for .NET Developer's Guide, 19c for Microsoft Windows

E96613-01

Copyright © 2002, 2019, Oracle and/or its affiliates. All rights reserved.

Primary Author: Maitreyee Chaliha

Contributing Authors: Janis Greenberg, Alex Keh, Kiminari Akiyama, Sumit Jeloka, Sinclair Hsu, Shailendra Jain, Riaz Ahmed, Ashish Shah, Lakshminarayanan Suriamoorthy, Steven Caminez, Naveen Doraiswamy, Neeraj Gupta, Chithra Ramamurthy, Martha Woo, Arun Singh, Sujith Somanathan, Nishant Singh

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Audience	lxxxix
Documentation Accessibility	lxxxix
Related Documents	lxxxix
Passwords in Code Examples	lxxxix
Conventions	lxxxix

Changes in This Release for Oracle Data Provider for .NET

Changes in Oracle Data Provider for .NET Release 19c (19.3)	lxxxix
Changes in Oracle Data Provider for .NET in ODAC Release 18c (18.3)	lxxxix
Changes in Oracle Data Provider for .NET Release 18c (18.3)	lxxxix
Changes in Oracle Data Provider for .NET in ODAC 12.2c Release 1	lxxxix
Changes in Oracle Data Provider for .NET Release 12.2.0.1	lxxxix
Changes in Oracle Data Provider for .NET in ODAC 12c Release 4	xc
Changes in Oracle Data Provider for .NET in ODAC 12c Release 3	xcii
Changes in Oracle Data Provider for .NET Release 12.1.0.2	xciii
Changes in Oracle Data Provider for .NET in ODAC 12c Release 2	xciv
Changes in Oracle Data Provider for .NET in ODAC 12c Release 1	xcv
Changes in Oracle Data Provider for .NET Release 12.1	xcv

1 Introducing Oracle Data Provider for .NET

.NET Data Access in Oracle: Products and Documentation	1-1
Oracle Data Provider for .NET (ODP.NET)	1-1
Oracle Developer Tools for Visual Studio	1-2
Oracle Database Extensions for .NET	1-2
Oracle Providers for ASP.NET	1-3
Oracle Services for Microsoft Transaction Server	1-3
Oracle TimesTen In-Memory Database	1-3
Overview of Oracle Data Provider for .NET (ODP.NET)	1-4
Oracle Data Provider for .NET Assemblies	1-5
Oracle Data Provider for .NET, Unmanaged Driver Assemblies	1-5

Oracle Data Provider for .NET, Managed Driver and ODP.NET Core Assemblies	1-5
Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces	1-6
Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client	1-6
Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations	1-15
Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces	1-19
Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Structures	1-19
Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Exceptions	1-19
Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes	1-20
Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces	1-21
Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Enumerations	1-21
Differences between the ODP.NET Drivers	1-22
Using ODP.NET Client Provider in a Simple Application	1-26

2 Installing and Configuring Oracle Data Provider for .NET

System Requirements	2-1
Entity Framework Requirements	2-3
Entity Framework Database First and Model First Requirements	2-3
Entity Framework Code First Requirements	2-3
Entity Framework 6 Requirements	2-3
Oracle Data Provider for .NET Versioning Scheme	2-3
Installing Oracle Data Provider for .NET, Unmanaged Driver	2-5
File Locations After Installation	2-6
Search Order for Unmanaged DLLs	2-7
ODP.NET and Dependent Unmanaged DLL Mismatch	2-8
Installing Oracle Data Provider for .NET, Managed Driver	2-8
Platform-Dependent Assemblies and Their Search Order	2-9
File Locations After Installation	2-10
Installing Oracle Data Provider for .NET Core	2-11
Entity Framework Code First Assemblies and File Location	2-11
Configuring Oracle Data Provider for .NET	2-12
Oracle Client Configuration File Automated Setup During Installation	2-13
Oracle Client Configuration File Settings	2-14
Configuring .NET Framework to Use ODP.NET	2-15
Oracle Data Provider for .NET, Unmanaged Driver Configuration	2-17
Supported Configuration Settings	2-18

Windows Registry	2-26
Configuration File Support	2-27
SQL Translation Framework Configuration	2-28
Specifying UDT Mappings with Unified Configuration for Unmanaged ODP.NET	2-31
Oracle Data Provider for .NET, Managed Driver Configuration	2-32
version Section	2-33
dataSources Section	2-34
settings section	2-37
LDAPsettings section	2-42
Lightweight Directory Access Protocol	2-42
implicitRefCursor section	2-43
distributedTransaction section	2-44
connectionPools section	2-44
edmMappings section	2-44
onsConfig section	2-45
ONS TCPS and Wallets	2-46
Client Side ONS Daemon Configuration	2-46
Relative Windows Path and Windows Environment Variable Configuration Settings	2-48
Oracle Data Provider for .NET Core Configuration	2-49
Distributed Transactions	2-52
Microsoft Distributed Transaction Coordinator Integration	2-52
ODP.NET, Managed Driver Setup	2-53
ODP.NET, Unmanaged Driver Setup	2-54
Configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver	2-54
Configuring for Entity Framework Code First	2-55
Entity Framework 6 Code-Based Registration	2-56
Migrating from ODP.NET, Unmanaged Driver to ODP.NET, Managed Driver	2-57
Configuring a Port to Listen for Database Notifications	2-58
General .NET Programming Recommendations and Tips for ODP.NET	2-59

3 Features of Oracle Data Provider for .NET

Base Classes and Provider Factory Classes	3-1
Code Access Security	3-2
Configuring OraclePermission	3-3
Configuring OraclePermission for Web Applications with High or Medium Trust Levels	3-4
Configuring OraclePermission for Windows Applications Running in a Partial Trust Environment	3-4
Connecting to Oracle Database	3-5

Connecting to Oracle Database Cloud Service	3-5
Connection String Attributes	3-6
Connection String Builder	3-8
Specifying the Data Source Attribute	3-8
Using the TNS Alias	3-9
Using the Connect Descriptor	3-9
Easy Connect and Easy Connect Plus Naming Methods	3-9
Using LDAP	3-10
Data Source Enumerator	3-11
Using Transport Layer Security and Secure Sockets Layer	3-11
Secure Sockets Layer and Transport Layer Security Differences	3-11
ODP.NET Secure Sockets Layer Configuration	3-12
Troubleshooting TLS/SSL Setup	3-14
HTTPS Proxy for Cloud Connections	3-16
Using Secure External Password Store	3-17
Configuring Secure External Password Store (SEPS)	3-17
Using Kerberos	3-18
File Based Credential Cache and MSLSA	3-19
ODP.NET, Managed Driver Dependency on MIT Kerberos	3-19
Configuring Kerberos Authentication with ODP.NET	3-19
Using Windows Native Authentication (NTS)	3-23
Configuring Windows Native Authentication (NTS) for the ODP.NET Client	3-23
Network Data Encryption and Integrity	3-24
Using Data Encryption	3-24
Using Data Integrity	3-25
Schema Discovery	3-25
User Customization of Metadata	3-26
Connection Pooling	3-27
Using Connection Pooling	3-28
Connection Pool Management	3-29
Connection Performance Counters	3-29
Registering Performance Counters	3-30
Enabling Performance Counters	3-30
Setting Performance Counters in .NET Configuration Files	3-31
Setting Performance Counters in Windows Registry	3-32
Publishing Performance Counters	3-33
Database Resident Connection Pooling	3-34
Oracle Multitenant and Pluggable Databases	3-37
Edition-Based Redefinition	3-38
Operating System Authentication	3-40
Privileged Connections	3-42

Connection Pooling with OracleCredential	3-42
Password Expiration	3-44
Proxy Authentication	3-45
Dynamic Distributed Transaction Enlistment	3-46
Client Identifier and End-to-End Tracing	3-47
Transparent Application Failover (TAF) Callback Support	3-47
TAF Notification	3-48
When Failover Occurs	3-48
Registering an Event Handler for Failover	3-49
Real Application Clusters and Global Data Services	3-50
Fast Application Notification	3-51
Runtime Connection Load Balancing	3-52
Fast Connection Failover (FCF)	3-53
Using FCF Planned Outage to Minimize Service Disruption	3-54
Pool Behavior in an Oracle RAC Database	3-56
Using Transaction Guard to Prevent Logical Corruption	3-57
ODP.NET and Transaction Guard	3-57
Application Continuity	3-61
ODP.NET and Application Continuity	3-61
Database Sharding	3-62
ODP.NET Sharding	3-62
OracleCommand Object	3-64
Transactions	3-64
System.Transactions and Promotable Transactions	3-65
Implicit Transaction Enlistment Using TransactionScope	3-66
Explicit Transaction Enlistment Using CommittableTransaction	3-67
Local Transaction Support for Older Databases	3-68
Parameter Binding	3-69
Command Timeouts	3-70
OracleDbType Enumeration Type	3-70
Inference of DbType, OracleDbType, and .NET Types	3-72
PL/SQL Associative Array Binding	3-75
Array Binding	3-79
Batch Processing	3-82
Statement Caching	3-83
Statement Caching Connection String Attributes	3-83
Enabling Statement Caching through the Registry	3-83
Statement Caching Methods and Properties	3-84
Connections and Statement Caching	3-84
Pooling and Statement Caching	3-84
Self-Tuning	3-84

Self-Tuning Statement Caching	3-85
Enabling or Disabling Self-Tuning for Applications	3-86
Tracing Optimization Changes	3-87
ODP.NET Types Overview	3-87
Obtaining Data from an OracleDataReader Object	3-88
Typed OracleDataReader Accessors	3-89
.NET Type Accessors	3-89
ODP.NET Type Accessors	3-91
Obtaining LONG and LONG RAW Data	3-93
Setting InitialLONGFetchSize to Zero or a Value Greater than Zero	3-93
Setting InitialLONGFetchSize to -1	3-94
Obtaining LOB Data	3-94
Setting InitialLOBFetchSize to Zero	3-95
Setting InitialLOBFetchSize to a Value Greater than Zero	3-95
Setting InitialLOBFetchSize to -1	3-95
Performance Considerations Related to the InitialLOBFetchSize Property	3-97
Controlling the Number of Rows Fetched in One Database Round-Trip	3-98
Use of FetchSize	3-98
Fine-Tuning FetchSize	3-98
Using the RowSize Property	3-99
PL/SQL REF CURSOR and OracleRefCursor	3-100
Obtaining an OracleRefCursor Object	3-100
Obtaining a REF CURSOR Data Type	3-100
Populating an OracleDataReader from a REF CURSOR	3-100
Populating the DataSet from a REF CURSOR	3-101
Populating an OracleRefCursor from a REF CURSOR	3-101
Updating a DataSet Obtained from a REF CURSOR	3-101
Behavior of ExecuteScalar Method for REF CURSOR	3-102
Passing a REF CURSOR to a Stored Procedure	3-102
Implicit REF CURSOR Binding	3-103
Specifying REF CURSOR Bind and Metadata Information in the .NET Configuration File	3-104
Sample Configuration File and Application	3-108
Usage Considerations	3-111
CommandText Property Considerations	3-111
Bind Considerations	3-111
Overloaded Stored Procedures	3-111
Type Initialization Exceptions	3-112
Using Stored Functions with Function Import	3-112
LOB Support	3-112
Large Character and Large Binary Data Types	3-112

Oracle Data Provider for .NET LOB Objects	3-113
Updating LOBs Using a DataSet	3-114
Updating LOBs Using OracleCommand and OracleParameter	3-114
Updating LOBs Using ODP.NET LOB Objects	3-114
Temporary LOBs	3-115
ODP.NET XML Support	3-115
Supported XML Features	3-116
XQuery Support	3-117
OracleXmlType and Connection Dependency	3-117
Updating XMLType Data in the Database	3-118
Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder	3-118
Updating with OracleCommand and OracleParameter	3-118
Updating XML Data in OracleXmlType	3-119
Characters with Special Meaning in XML	3-120
Retrieving Query Result Set as XML	3-120
Handling Date and Time Format	3-120
Characters with Special Meaning in Column Data	3-120
Characters in Table or View Name	3-122
Case-Sensitivity in Column Name to XML Element Name Mapping	3-122
Column Name to XML Element Name Mapping	3-122
Object-Relational Data	3-124
NULL Values	3-124
Data Manipulation Using XML	3-124
Handling Date and Time Format	3-124
Saving Changes Using XML	3-125
Characters with Special Meaning in Column Data	3-125
Characters with Special Meaning in Table or View Name	3-126
Case-Sensitivity in XML Element Name to Column Name Mapping	3-126
XML Element Name to Column Name Mapping	3-126
Saving Changes to a Table Using an XML Document	3-127
Object-Relational Data	3-128
Multiple Tables	3-128
Commit Transactions	3-129
Oracle User-Defined Types (UDTs) and .NET Custom Types	3-129
Oracle User-Defined Types (UDTs)	3-129
Custom Types	3-130
Required Custom Type Implementations	3-130
Optional Custom Type Implementations	3-132
Specifying Custom Type Mappings	3-133
Using a Custom Type Factory to Specify Custom Type Mappings	3-133
Using XML in Configuration Files to Specify Custom Type Mappings	3-134

Using Custom Type Mappings	3-135
Converting Between Custom Types and Oracle UDTs	3-135
Oracle UDT Attribute Mappings	3-136
Oracle UDT Retrieval from OracleDataReader	3-138
Oracle UDT Metadata Retrieval from OracleDataReader	3-139
Oracle UDT Parameter Binding with OracleParameter	3-140
Guidelines for Binding UDT Input and Output Parameters	3-140
UDT Input Parameter Binding with OracleParameters	3-141
UDT Output Parameter Binding with OracleParameters	3-142
Populating the DataSet with Oracle UDTs	3-143
UDT Method Invocation	3-144
Configuration Settings for Oracle UDTs	3-145
StatementCacheWithUdts	3-145
UdtCacheSize	3-145
Bulk Copy	3-145
Data Types Supported by Bulk Copy	3-146
Restrictions on Oracle Bulk Copy of a Single Partition	3-147
Integrity Constraints Affecting Oracle Bulk Copy	3-147
Database Insert Triggers	3-147
Field Defaults	3-148
Oracle Database Advanced Queuing Support	3-148
Using ODP.NET for Advanced Queuing	3-150
Enqueuing and Dequeuing Example	3-151
Continuous Query Notification Support	3-153
Continuous Query Notification Classes	3-155
Supported Operations	3-156
Requirements of Notification Registration	3-157
Using Continuous Query Notification	3-157
Application Steps	3-157
Flow of Notification Process	3-158
Best Practice Guidelines and Performance Considerations	3-160
OracleDataAdapter Safe Type Mapping	3-160
Comparison Between Oracle Data Types and .NET Types	3-161
SafeMapping Property	3-162
Using Safe Type Mapping	3-163
OracleDataAdapter Requery Property	3-164
Guaranteeing Uniqueness in Updating DataSet to Database	3-165
What Constitutes Uniqueness in DataRow Objects?	3-166
Configuring PrimaryKey and Constraints Properties	3-166
Updating Without PrimaryKey and Constraints Configuration	3-167
Globalization Support	3-167

Globalization Settings	3-168
Client Globalization Settings	3-168
Session Globalization Settings	3-168
Thread-Based Globalization Settings	3-169
Globalization-Sensitive Operations	3-170
Operations Dependent on Client Computer's Globalization Settings	3-170
Operations Dependent on Thread Globalization Settings	3-170
Operations Sensitive to Session Globalization Parameters	3-171
ODP.NET Drivers Differences	3-171
Debug Tracing	3-172
Database Application Migration: SQL Translation Framework	3-173
The SQL Translation Profile	3-173

4 ADO.NET Entity Framework and LINQ to Entities

Overview of Entity Framework	4-1
Language Integrated Query and Entity SQL	4-2
Mapping Oracle Data Types to EDM Types	4-3
EDM Type Facets	4-6
Oracle Number Default Data Type Mapping and Customization	4-14
Entity Framework 5 and Earlier Mapping and Customization	4-14
Entity Framework 6 Mapping and Customization	4-16
New Default Mappings	4-17
Data Type Mapping and Customization Process	4-18
StoreGeneratedPattern Enumeration	4-18
Identity Attribute	4-19
Virtual Column	4-19
Resolving Compilation Errors When Using Custom Mapping	4-19
Mapping Boolean and Guid Parameters in Custom INSERT, UPDATE, and DELETE Stored Procedures	4-19
Migrating Existing Entity Framework 5 Applications to Entity Framework 6	4-20
Code First	4-21
Mapping of .NET Types to Oracle Types	4-21
Code First Migrations	4-25
Code First Migrations With No Supporting Code Migration File	4-26
Code First Database Initialization	4-26
Oracle Database Object Creation	4-26
Using the Default Connection Factory	4-29
Unsupported Entity Framework Features	4-29

5 Oracle Data Provider for .NET Stored Procedures

Introducing .NET Stored Procedure Execution Using ODP.NET	5-1
Limitations and Restrictions on ODP.NET Within .NET Stored Procedure	5-2
Implicit Database Connection	5-3
Transaction Support	5-3
Unsupported SQL Commands	5-6
Oracle User-Defined Type (UDT) Support	5-6
Porting Client Application to .NET Stored Procedure	5-6

6 Oracle Data Provider for .NET Classes

OracleClientFactory Class	6-2
OracleClientFactory Members	6-3
OracleClientFactory Field	6-5
Instance	6-5
OracleClientFactory Constructor	6-6
OracleClientFactory Public Properties	6-6
CanCreateDataSourceEnumerator	6-7
OracleClientFactory Public Methods	6-7
CreateCommand	6-8
CreateCommandBuilder	6-8
CreateConnection	6-9
CreateConnectionStringBuilder	6-9
CreateDataAdapter	6-10
CreateDataSourceEnumerator	6-10
CreateParameter	6-11
CreatePermission	6-11
OracleCommand Class	6-12
OracleCommand Members	6-14
OracleCommand Constructors	6-17
OracleCommand()	6-18
OracleCommand(string)	6-18
OracleCommand(string, OracleConnection)	6-19
OracleCommand Static Methods	6-19
OracleCommand Properties	6-20
AddRowid	6-21
AddToStatementCache	6-22
ArrayBindCount	6-24
ArrayBindRowsAffected	6-25
BindByName	6-25
CommandText	6-26

CommandTimeout	6-27
CommandType	6-28
Connection	6-29
DesignTimeVisible	6-29
FetchSize	6-30
ImplicitRefCursors	6-31
InitialLOBFetchSize	6-32
InitialLONGFetchSize	6-32
Notification	6-34
NotificationAutoEnlist	6-35
Parameters	6-35
RowSize	6-36
Transaction	6-37
UpdatedRowSource	6-38
UseEdmMapping	6-38
XmlCommandType	6-39
XmlQueryProperties	6-40
XmlSaveProperties	6-41
OracleCommand Public Methods	6-41
Cancel	6-42
Clone	6-46
CreateParameter	6-47
Dispose	6-47
ExecuteNonQuery	6-48
ExecuteReader	6-50
ExecuteReader()	6-50
ExecuteReader(CommandBehavior)	6-52
ExecuteScalar	6-53
ExecuteStream	6-54
ExecuteToStream	6-55
ExecuteXmlReader	6-56
Prepare	6-57
OracleCommandBuilder Class	6-57
OracleCommandBuilder Members	6-59
OracleCommandBuilder Constructors	6-62
OracleCommandBuilder()	6-62
OracleCommandBuilder(OracleDataAdapter)	6-63
OracleCommandBuilder Static Methods	6-63
DeriveParameters	6-64
OracleCommandBuilder Properties	6-67
CaseSensitive	6-67

CatalogLocation	6-68
CatalogSeparator	6-68
ConflictOption	6-69
DataAdapter	6-69
QuotePrefix	6-70
QuoteSuffix	6-70
SchemaSeparator	6-71
OracleCommandBuilder Public Methods	6-72
GetDeleteCommand	6-73
GetDeleteCommand()	6-74
GetDeleteCommand(bool)	6-74
GetInsertCommand	6-75
GetInsertCommand()	6-76
GetInsertCommand(bool)	6-76
GetUpdateCommand	6-77
GetUpdateCommand()	6-78
GetUpdateCommand(bool)	6-78
QuoteIdentifier	6-79
RefreshSchema	6-80
UnquoteIdentifier	6-81
OracleCommandBuilder Events	6-82
OracleConfiguration Class	6-82
OracleConfiguration Members	6-85
OracleConfiguration Connection Properties	6-88
DatabaseEditionName	6-89
DisableOOB	6-90
DrcpConnectionClass	6-90
HostnameDefaultServiceIsHost	6-91
NamesDirectoryPath	6-91
OracleDataSources	6-92
TcpConnectTimeout	6-92
TnsAdmin	6-93
OracleConfiguration Secure Connection Properties	6-93
HttpsProxy	6-94
HttpsProxyPort	6-95
SqlNetAuthenticationServices	6-96
SqlNetEncryptionClient	6-96
SqlNetEncryptionTypesClient	6-97
SqlNetCryptoChecksumClient	6-98
SqlNetCryptoChecksumTypesClient	6-98
SqlNetWalletOverride	6-99

SSLServerDNMatch	6-100
SSLVersion	6-100
UseHttpsProxy	6-101
WalletLocation	6-101
OracleConfiguration Command Properties	6-102
BindByName	6-102
CommandTimeout	6-103
OracleConfiguration Directories Properties	6-103
DefaultAdminContext	6-104
DirectoryServers	6-105
DirectoryType	6-105
LdapAdmin	6-106
NamesLdapAuthenticateBind	6-107
NamesLdapConnTimeout	6-107
OracleConfiguration High Availability Properties	6-108
DbNotificationAddress	6-109
DbNotificationPort	6-109
HAEvents	6-110
OnsConfigFile	6-110
OnsMode	6-111
OnsProtocol	6-112
OnsWalletLocation	6-112
OracleOnsServers	6-113
ServiceRelocationConnectionTimeout	6-113
OracleConfiguration Performance Properties	6-114
FetchSize	6-115
LoadBalancing	6-115
MaxStatementCacheSize	6-116
PerformanceCounters	6-116
ReceiveBufferSize	6-117
SelfTuning	6-117
SendBufferSize	6-118
StatementCacheSize	6-118
TcpNoDelay	6-119
OracleConfiguration Debug Tracing Properties	6-119
TraceFileLocation	6-120
TraceLevel	6-120
TraceOption	6-121
OracleConnection Class	6-121
OracleConnection Members	6-123
OracleConnection Constructors	6-127

OracleConnection()	6-128
OracleConnection(string)	6-129
OracleConnection(string, OracleCredential)	6-129
OracleConnection Static Properties	6-130
IsAvailable	6-131
OracleConnection Static Methods	6-132
ClearPool	6-132
ClearAllPools	6-134
OracleConnection Properties	6-135
ActionName	6-137
ClientId	6-137
ClientInfo	6-138
ConnectionString	6-139
ConnectionTimeout	6-146
ConnectionType	6-146
Credential	6-147
Database	6-148
DatabaseDomainName	6-148
DatabaseEditionName	6-149
DatabaseName	6-149
DataSource	6-150
DRCPConnectionClass	6-150
DRCPPurity	6-151
HostName	6-152
InstanceName	6-153
ModuleName	6-153
PDBName	6-154
ServerVersion	6-155
ServiceName	6-156
State	6-157
StatementCacheSize	6-157
SwitchedConnection	6-158
OracleConnection Public Methods	6-159
BeginTransaction	6-160
BeginTransaction()	6-161
BeginTransaction(IsolationLevel)	6-161
ChangeDatabase	6-163
Clone	6-164
Close	6-165
CreateCommand	6-165
EnlistDistributedTransaction	6-167

EnlistTransaction	6-169
FlushCache	6-170
GetSchema	6-170
GetSchema()	6-171
GetSchema (string collectionName)	6-172
GetSchema (string collectionName, string[] restrictions)	6-174
GetSessionInfo	6-177
GetSessionInfo()	6-177
GetSessionInfo(OracleGlobalization)	6-178
Open	6-179
OpenWithNewPassword	6-179
OpenWithNewPassword(String)	6-180
OpenWithNewPassword(SecureString)	6-181
PurgeStatementCache	6-182
SetSessionInfo	6-183
SetShardingKey(OracleShardingKey, OracleShardingKey)	6-184
OracleConnection Events	6-185
ConnectionOpen	6-186
Failover	6-187
HAEvent	6-188
InfoMessage	6-189
StateChange	6-190
OracleConnectionOpenEventArgs Class	6-191
OracleConnectionOpenEventArgs Members	6-192
OracleConnectionOpenEventArgs Properties	6-192
Connection	6-193
OracleConnectionOpenEventHandler Delegate	6-193
OracleConnectionStringBuilder Class	6-194
OracleConnectionStringBuilder Members	6-197
OracleConnectionStringBuilder Constructors	6-200
OracleConnectionStringBuilder()	6-201
OracleConnectionStringBuilder(string)	6-201
OracleConnectionStringBuilder Public Properties	6-202
ConnectionLifeTime	6-204
ConnectionTimeout	6-205
ContextConnection	6-205
DataSource	6-206
DBAPrivilege	6-206
DecrPoolSize	6-207
Enlist	6-208
HAEvents	6-208

IncrPoolSize	6-209
IsFixedSize	6-210
Item	6-210
Keys	6-211
LoadBalancing	6-211
MaxPoolSize	6-212
MetadataPooling	6-213
MinPoolSize	6-213
Password	6-214
PersistSecurityInfo	6-214
Pooling	6-215
PromotableTransaction	6-215
ProxyPassword	6-216
ProxyUserId	6-216
SelfTuning	6-217
StatementCachePurge	6-217
StatementCacheSize	6-218
UserID	6-219
ValidateConnection	6-219
Values	6-220
OracleConnectionStringBuilder Public Methods	6-220
Clear	6-221
ContainsKey	6-222
Remove	6-222
TryGetValue	6-223
OracleCredential Class	6-224
OracleCredential Members	6-226
OracleCredential Constructors	6-227
OracleCredential(string, SecureString)	6-227
OracleCredential(string, SecureString, OracleDBAPrivilege)	6-228
OracleCredential(string, SecureString, string, SecureString)	6-229
OracleCredential Properties	6-229
DBAPrivilege	6-230
Password	6-231
ProxyPassword	6-231
ProxyUserId	6-232
UserId	6-232
OracleDataAdapter Class	6-233
OracleDataAdapter Members	6-235
OracleDataAdapter Constructors	6-237
OracleDataAdapter()	6-238

OracleDataAdapter(OracleCommand)	6-238
OracleDataAdapter(string, OracleConnection)	6-239
OracleDataAdapter(string, string)	6-240
OracleDataAdapter Static Methods	6-241
OracleDataAdapter Properties	6-241
DeleteCommand	6-242
IdentityInsert	6-243
IdentityUpdate	6-244
InsertCommand	6-245
Requery	6-245
ReturnProviderSpecificTypes	6-246
SafeMapping	6-247
SelectCommand	6-247
UpdateBatchSize	6-248
UpdateCommand	6-249
OracleDataAdapter Public Methods	6-250
Fill	6-251
Fill(DataTable, OracleRefCursor)	6-251
Fill(DataSet, OracleRefCursor)	6-252
Fill(DataSet, string, OracleRefCursor)	6-253
Fill(DataSet, int, int, string, OracleRefCursor)	6-254
OracleDataAdapter Events	6-255
RowUpdated	6-256
RowUpdating	6-258
OracleDatabase Class	6-259
OracleDatabase Members	6-261
OracleDatabase Constructors	6-262
OracleDatabase Constructor(string)	6-262
OracleDatabase Constructor(string, OracleCredential)	6-263
OracleDatabase Properties	6-264
ServerVersion	6-264
OracleDatabase Public Methods	6-265
Dispose	6-265
ExecuteNonQuery	6-266
Shutdown	6-266
Shutdown()	6-267
Shutdown(OracleDBShutdownMode, bool)	6-268
Startup	6-270
Startup()	6-271
Startup(OracleDBStartupMode, string, bool)	6-271
OracleDataReader Class	6-272

OracleDataReader Members	6-275
OracleDataReader Static Methods	6-279
OracleDataReader Properties	6-279
Depth	6-280
FetchSize	6-281
FieldCount	6-282
HasRows	6-283
HiddenFieldCount	6-284
IsClosed	6-285
Item	6-285
Item [index]	6-286
Item [string]	6-286
InitialLOBFetchSize	6-287
InitialLONGFetchSize	6-288
RecordsAffected	6-289
RowSize	6-290
UseEdmMapping	6-290
VisibleFieldCount	6-291
OracleDataReader Public Methods	6-292
Close	6-295
Dispose	6-296
GetBoolean	6-296
GetByte	6-297
GetBytes	6-298
GetChar	6-299
GetChars	6-300
GetData	6-301
GetDataTypeName	6-301
GetDateTime	6-302
GetDateTimeOffset	6-303
GetDecimal	6-304
GetDouble	6-305
GetEnumerator	6-305
GetFieldType	6-306
GetFloat	6-307
GetGuid	6-308
GetInt16	6-309
GetInt32	6-310
GetInt64	6-311
GetName	6-312
GetOracleBFile	6-312

GetOracleBinary	6-313
GetOracleBlob	6-314
GetOracleBlobForUpdate	6-315
GetOracleBlobForUpdate(int)	6-315
GetOracleBlobForUpdate(int, int)	6-317
GetOracleClob	6-319
GetOracleClobForUpdate	6-320
GetOracleClobForUpdate(int)	6-320
GetOracleClobForUpdate(int, int)	6-322
GetOracleDate	6-324
GetOracleDecimal	6-325
GetOracleIntervalDS	6-326
GetOracleIntervalYM	6-327
GetOracleRef	6-327
GetOracleString	6-328
GetOracleTimeStamp	6-329
GetOracleTimeStampLTZ	6-330
GetOracleTimeStampTZ	6-330
GetOracleXmlType	6-331
GetOracleValue	6-332
GetOracleValues	6-333
GetOrdinal	6-334
GetProviderSpecificFieldType	6-334
GetProviderSpecificValue	6-335
GetProviderSpecificValues	6-336
GetSchemaTable	6-337
GetString	6-341
GetTimeSpan	6-342
GetValue	6-343
GetValues	6-344
GetXmlReader	6-345
IsDBNull	6-345
NextResult	6-346
Read	6-347
OracleDataSourceCollection Class	6-348
OracleDataSourceCollection Members	6-350
OracleDataSourceCollection Methods	6-350
Add	6-351
Remove	6-352
OracleDataSourceCollection Properties	6-352
Count	6-353

This	6-353
OracleDataSourceEnumerator Class	6-354
OracleDataSourceEnumerator Members	6-355
OracleDataSourceEnumerator Constructor	6-356
OracleDataSourceEnumerator Public Methods	6-357
GetDataSources	6-357
OracleError Class	6-358
OracleError Members	6-360
OracleError Static Methods	6-361
OracleError Properties	6-361
ArrayBindIndex	6-362
DataSource	6-362
Message	6-363
Number	6-363
Procedure	6-364
Source	6-364
OracleError Methods	6-365
ToString	6-365
OracleErrorCollection Class	6-366
OracleErrorCollection Members	6-367
OracleErrorCollection Static Methods	6-368
OracleErrorCollection Properties	6-369
OracleErrorCollection Public Methods	6-369
OracleException Class	6-370
OracleException Members	6-372
OracleException Static Methods	6-373
OracleException Properties	6-374
DataSource	6-375
Errors	6-375
IsRecoverable	6-376
Message	6-376
Number	6-377
OracleLogicalTransaction	6-377
Procedure	6-378
Source	6-379
OracleException Methods	6-379
GetObjectData	6-380
ToString	6-380
OracleInfoMessageEventArgs Class	6-381
OracleInfoMessageEventArgs Members	6-383
OracleInfoMessageEventArgs Static Methods	6-384

OracleInfoMessageEventArgs Properties	6-385
Errors	6-385
Message	6-385
Source	6-386
OracleInfoMessageEventArgs Public Methods	6-386
ToString	6-387
OracleInfoMessageEventHandler Delegate	6-387
OracleLogicalTransaction Class	6-388
OracleLogicalTransaction Members	6-389
OracleLogicalTransaction Public Read-Only Properties	6-390
Committed	6-391
ConnectionString	6-392
LogicalTransactionId	6-393
UserCallCompleted	6-393
OracleLogicalTransaction Methods	6-394
Dispose	6-394
GetOutcome	6-395
OracleOnsServerCollection Class	6-396
OracleOnsServerCollection Members	6-398
OracleOnsServerCollection Methods	6-398
Add	6-399
Remove	6-400
OracleOnsServerCollection Properties	6-400
Count	6-401
This	6-401
OracleParameter Class	6-402
OracleParameter Members	6-404
OracleParameter Constructors	6-406
OracleParameter()	6-407
OracleParameter(string, OracleDbType)	6-408
OracleParameter(string, object)	6-409
OracleParameter(string, OracleDbType, ParameterDirection)	6-410
OracleParameter(string, OracleDbType, object, ParameterDirection)	6-411
OracleParameter(string, OracleDbType, int)	6-412
OracleParameter(string, OracleDbType, int, string)	6-413
OracleParameter(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)	6-415
OracleParameter(string, OracleDbType, int, object, ParameterDirection)	6-416
OracleParameter Static Methods	6-418
OracleParameter Properties	6-418
ArrayBindSize	6-419

ArrayBindStatus	6-421
CollectionType	6-422
DbType	6-422
Direction	6-423
IsNullable	6-424
Offset	6-424
OracleDbType	6-425
OracleDbTypeEx	6-426
ParameterName	6-427
Precision	6-427
Scale	6-428
Size	6-429
SourceColumn	6-430
SourceColumnNullMapping	6-431
SourceVersion	6-431
Status	6-432
UdtTypeName	6-433
Value	6-434
OracleParameter Public Methods	6-436
Clone	6-436
Dispose	6-437
ResetDbType	6-438
ResetOracleDbType	6-438
ToString	6-439
OracleParameterCollection Class	6-440
OracleParameterCollection Members	6-441
OracleParameterCollection Static Methods	6-443
OracleParameterCollection Properties	6-444
Count	6-444
Item	6-445
Item[int]	6-445
Item[string]	6-446
IsFixedSize	6-447
IsReadOnly	6-447
IsSynchronized	6-448
SyncRoot	6-448
OracleParameterCollection Public Methods	6-449
Add	6-450
Add(object)	6-451
Add(OracleParameter)	6-451
Add(string, object)	6-452

Add(string, OracleDbType)	6-453
Add(string, OracleDbType, ParameterDirection)	6-453
Add(string, OracleDbType, object, ParameterDirection)	6-454
Add(string, OracleDbType, int, object, ParameterDirection)	6-455
Add(string, OracleDbType, int)	6-456
Add (string, OracleDbType, int, string)	6-457
Add(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)	6-458
AddRange	6-459
Clear	6-460
Contains	6-461
Contains(object)	6-461
Contains(string)	6-463
CopyTo	6-464
GetEnumerator	6-464
IndexOf	6-465
IndexOf(object)	6-465
IndexOf(String)	6-466
Insert	6-467
Remove	6-467
RemoveAt	6-469
RemoveAt(int)	6-469
RemoveAt(String)	6-470
OraclePermission Class	6-470
OraclePermission Members	6-471
OraclePermission Constructor	6-473
OraclePermission Static Methods	6-474
OraclePermission Public Properties	6-474
OraclePermission Public Methods	6-475
Add	6-475
Copy	6-477
IsSubsetOf	6-477
OraclePermissionAttribute Class	6-478
OraclePermissionAttribute Members	6-479
OraclePermissionAttribute Constructor	6-481
OraclePermissionAttribute Static Methods	6-481
OraclePermissionAttribute Public Properties	6-482
OraclePermissionAttribute Public Methods	6-482
CreatePermission	6-483
OracleRowUpdatedEventArgs Class	6-483
OracleRowUpdatedEventArgs Members	6-484

OracleRowUpdatedEventArgs Constructor	6-486
OracleRowUpdatedEventArgs Static Methods	6-487
OracleRowUpdatedEventArgs Properties	6-487
Command	6-488
OracleRowUpdatedEventArgs Public Methods	6-488
OracleRowUpdatedEventHandler Delegate	6-489
OracleRowUpdatingEventArgs Class	6-489
OracleRowUpdatingEventArgs Members	6-491
OracleRowUpdatingEventArgs Constructor	6-492
OracleRowUpdatingEventArgs Static Methods	6-493
OracleRowUpdatingEventArgs Properties	6-493
Command	6-494
OracleRowUpdatingEventArgs Public Methods	6-494
OracleRowUpdatingEventHandler Delegate	6-495
OracleShardingKey Class	6-496
OracleShardingKey Members	6-497
OracleShardingKey Constructors	6-498
OracleShardingKey()	6-498
OracleShardingKey(OracleDbType, object)	6-499
OracleShardingKey Instance Methods	6-499
SetShardingKey(OracleDbType, object)	6-500
Dispose	6-500
OracleTransaction Class	6-501
OracleTransaction Members	6-503
OracleTransaction Static Methods	6-505
OracleTransaction Properties	6-505
IsolationLevel	6-506
Connection	6-506
OracleTransaction Public Methods	6-507
Commit	6-507
Dispose	6-509
Rollback	6-510
Rollback()	6-510
Rollback(string)	6-512
Save	6-513
OracleConnectionType Enumeration	6-515
OracleCollectionType Enumeration	6-516
OracleDBAPrivilege Enumeration	6-516
OracleDBShutdownMode Enumeration	6-517
OracleDBStartupMode Enumeration	6-518
OracleDbType Enumeration	6-519

OracleDRCPPurity Enumeration	6-521
OracleIdentityType Enumeration	6-522
OracleParameterStatus Enumeration	6-522

7 Oracle Data Provider for .NET XML-Related Classes

OracleXmlCommandType Enumeration	7-1
OracleXmlQueryProperties Class	7-2
OracleXmlQueryProperties Members	7-5
OracleXmlQueryProperties Constructor	7-6
OracleXmlQueryProperties Properties	7-7
MaxRows	7-7
RootTag	7-8
RowTag	7-9
Xslt	7-9
XsltParams	7-10
OracleXmlQueryProperties Public Methods	7-11
Clone	7-11
OracleXmlSaveProperties Class	7-11
OracleXmlSaveProperties Members	7-14
OracleXmlSaveProperties Constructor	7-16
OracleXmlSaveProperties Properties	7-16
KeyColumnsList	7-17
RowTag	7-17
Table	7-18
UpdateColumnsList	7-18
Xslt	7-19
XsltParams	7-20
OracleXmlSaveProperties Public Methods	7-20
Clone	7-21
OracleXmlStream Class	7-21
OracleXmlStream Members	7-22
OracleXmlStream Constructor	7-24
OracleXmlStream Static Methods	7-25
OracleXmlStream Instance Properties	7-25
CanRead	7-26
CanSeek	7-26
CanWrite	7-27
Connection	7-27
Length	7-28
Position	7-28

Value	7-29
OracleXmlStream Instance Methods	7-30
Clone	7-31
Close	7-31
Dispose	7-32
Flush	7-32
Read	7-33
Read(byte[], int, int)	7-33
Read(char[], int, int)	7-34
Seek	7-35
SetLength	7-36
Write	7-36
WriteLine	7-37
OracleXmlType Class	7-37
OracleXmlType Members	7-38
OracleXmlType Constructors	7-40
OracleXmlType(OracleClob)	7-41
OracleXmlType(OracleConnection, string)	7-42
OracleXmlType(OracleConnection, XmlReader)	7-42
OracleXmlType(OracleConnection, XmlDocument)	7-43
OracleXmlType Static Methods	7-44
OracleXmlType Static Fields	7-44
Null	7-45
OracleXmlType Instance Properties	7-45
Connection	7-46
IsEmpty	7-47
IsFragment	7-47
IsNull	7-48
IsSchemaBased	7-48
RootElement	7-49
Schema	7-50
SchemaUrl	7-50
Value	7-51
OracleXmlType Instance Methods	7-51
Clone	7-52
Dispose	7-53
Extract	7-53
Extract(string, string)	7-54
Extract(string, XmlNamespaceManager)	7-55
GetStream	7-56
GetXmlDocument	7-56

GetXmlReader	7-57
IsExists	7-58
IsExists(string, string)	7-58
IsExists(string, XmlNameSpaceManager)	7-59
Transform	7-60
Transform(OracleXmlType, string)	7-61
Transform(string, string)	7-61
Update	7-62
Update(string, string, string)	7-63
Update(string, XmlNameSpaceManager, string)	7-64
Update(string, string, OracleXmlType)	7-65
Update(string, XmlNameSpaceManager, OracleXmlType)	7-66
Validate	7-67

8 Oracle Data Provider for .NET HA Event Classes

OracleHAEventArgs Class	8-1
OracleHAEventArgs Members	8-2
OracleHAEventArgs Properties	8-3
DatabaseDomainName	8-3
DatabaseName	8-4
DrainTimeout	8-4
HostName	8-5
InstanceName	8-6
Reason	8-6
ServiceName	8-7
Source	8-7
Status	8-7
Time	8-8
OracleHAEventHandler Delegate	8-8
OracleHAEventSource Enumeration	8-9
OracleHAEventStatus Enumeration	8-10

9 Continuous Query Notification Classes

OracleDependency Class	9-1
OracleDependency Members	9-2
OracleDependency Constructors	9-4
OracleDependency ()	9-5
OracleDependency(OracleCommand)	9-5
OracleDependency(OracleCommand, bool, int, bool)	9-7

OracleDependency Static Fields	9-8
Address	9-9
Port	9-9
OracleDependency Static Methods	9-10
GetOracleDependency	9-11
OracleDependency Properties	9-12
DataSource	9-12
HasChanges	9-13
Id	9-13
IsEnabled	9-14
QueryBasedNotification	9-15
RegisteredQueryIDs	9-16
RegisteredResources	9-16
RowidInfo	9-17
UserName	9-18
OracleDependency Methods	9-18
AddCommandDependency	9-19
RemoveRegistration	9-20
OracleDependency Events	9-21
OnChange	9-21
OracleNotificationRequest Class	9-22
OracleNotificationRequest Members	9-23
OracleNotificationRequest Static Methods	9-24
OracleNotificationRequest Properties	9-24
IsNotifiedOnce	9-25
IsPersistent	9-26
Timeout	9-27
GroupingNotificationEnabled	9-27
GroupingType	9-28
GroupingInterval	9-29
OracleNotificationRequest Methods	9-29
OracleNotificationEventArgs Class	9-30
OracleNotificationEventArgs Members	9-31
OracleNotificationEventArgs Static Fields	9-32
OracleNotificationEventArgs Static Methods	9-32
OracleNotificationEventArgs Properties	9-33
Details	9-33
Info	9-34
ResourceNames	9-35
Source	9-36
Type	9-37

OracleNotificationEventArgs Methods	9-38
OnChangeEventHandler Delegate	9-38
OracleRowidInfo Enumeration	9-39
OracleNotificationType Enumeration	9-40
OracleNotificationSource Enumeration	9-41
OracleNotificationInfo Enumeration	9-42

10 Oracle Data Provider for .NET Globalization Classes

OracleGlobalization Class	10-1
OracleGlobalization Members	10-2
OracleGlobalization Static Methods	10-4
GetClientInfo	10-5
GetClientInfo()	10-5
GetClientInfo(OracleGlobalization)	10-6
GetThreadInfo	10-7
GetThreadInfo()	10-7
GetThreadInfo(OracleGlobalization)	10-8
SetThreadInfo	10-9
OracleGlobalization Properties	10-10
Calendar	10-11
ClientCharacterSet	10-12
Comparison	10-13
Currency	10-13
DateFormat	10-14
DateLanguage	10-15
DualCurrency	10-15
ISOCurrency	10-16
Language	10-16
LengthSemantics	10-17
NCharConversionException	10-18
NumericCharacters	10-18
Sort	10-19
Territory	10-20
TimeStampFormat	10-20
TimeStampTZFormat	10-21
TimeZone	10-21
OracleGlobalization Public Methods	10-22
Clone	10-23
Dispose	10-23

11 Oracle Data Provider for .NET Failover Classes

OracleFailoverEventArgs Class	11-1
OracleFailoverEventArgs Members	11-3
OracleFailoverEventArgs Static Methods	11-4
OracleFailoverEventArgs Properties	11-5
FailoverType	11-5
FailoverEvent	11-5
OracleFailoverEventArgs Public Methods	11-6
OracleFailoverEventHandler Delegate	11-6
FailoverEvent Enumeration	11-8
FailoverReturnCode Enumeration	11-9
FailoverType Enumeration	11-10

12 Oracle Database Advanced Queuing Classes

OracleAQAgent Class	12-1
OracleAQAgent Members	12-2
OracleAQAgent Constructors	12-3
OracleAQAgent (string)	12-3
OracleAQAgent (string, string)	12-4
OracleAQAgent Properties	12-5
Address	12-5
Name	12-6
OracleAQDequeueOptions Class	12-6
OracleAQDequeueOptions Members	12-7
OracleAQDequeueOptions Constructor	12-8
OracleAQDequeueOptions Properties	12-9
ConsumerName	12-9
Correlation	12-10
DeliveryMode	12-11
DequeueMode	12-11
MessageId	12-12
NavigationMode	12-13
ProviderSpecificType	12-13
Visibility	12-14
Wait	12-15
OracleAQDequeueOptions Public Methods	12-15
Clone	12-16
OracleAQEnqueueOptions Class	12-16
OracleAQEnqueueOptions Members	12-17
OracleAQEnqueueOptions Constructor	12-18

OracleAQEnqueueOptions Properties	12-19
DeliveryMode	12-19
Visibility	12-20
OracleAQEnqueueOptions Public Methods	12-20
Clone	12-21
OracleAQMessage Class	12-21
OracleAQMessage Members	12-23
OracleAQMessage Constructors	12-24
OracleAQMessage()	12-24
OracleAQMessage(Object)	12-25
OracleAQMessage Properties	12-25
Correlation	12-26
Delay	12-27
DeliveryMode	12-28
DequeueAttempts	12-28
EnqueueTime	12-29
ExceptionQueue	12-29
Expiration	12-30
MessageId	12-31
OriginalMessageId	12-31
Payload	12-32
Priority	12-32
Recipients	12-33
SenderId	12-34
State	12-34
TransactionGroup	12-35
OracleAQMessageAvailableEventArgs Class	12-35
OracleAQMessageAvailableEventArgs Members	12-36
OracleAQMessageAvailableEventArgs Constructor	12-37
OracleAQMessageAvailableEventArgs Properties	12-38
AvailableMessages	12-39
ConsumerName	12-39
Correlation	12-40
Delay	12-40
DeliveryMode	12-41
EnqueueTime	12-41
ExceptionQueue	12-42
Expiration	12-42
MessageId	12-43
NotificationType	12-43
OriginalMessageId	12-44

Priority	12-44
QueueName	12-45
SenderId	12-45
State	12-46
OracleAQMessageAvailableEventHandler Delegate	12-46
OracleAQQueue Class	12-47
OracleAQQueue Members	12-48
OracleAQQueue Constructors	12-50
OracleAQQueue(string)	12-50
OracleAQQueue(string, OracleConnection)	12-51
OracleAQQueue(string, OracleConnection, OracleAQMessageType)	12-52
OracleAQQueue(string, OracleConnection, OracleAQMessageType, string)	12-53
OracleAQQueue Static Methods	12-54
Listen	12-54
Listen(OracleConnection, OracleAQAgent[])	12-55
Listen(OracleConnection, OracleAQAgent[], int)	12-56
OracleAQQueue Properties	12-57
Connection	12-58
DequeueOptions	12-58
EnqueueOptions	12-59
MessageType	12-60
Name	12-61
Notification	12-61
NotificationConsumers	12-62
UdtTypeName	12-63
OracleAQQueue Public Methods	12-63
Dequeue	12-64
Dequeue()	12-65
Dequeue(OracleAQDequeueOptions)	12-65
DequeueArray	12-66
DequeueArray(int)	12-67
DequeueArray(int, OracleAQDequeueOptions)	12-68
Dispose	12-69
Enqueue	12-69
Enqueue(OracleAQMessage)	12-70
Enqueue(OracleAQMessage, OracleAQEnqueueOptions)	12-71
EnqueueArray	12-72
EnqueueArray(OracleAQMessage[])	12-72
EnqueueArray(OracleAQMessage[], OracleAQEnqueueOptions)	12-73
Listen	12-74
Listen(string[])	12-75

Listen (string[], int)	12-79
OracleAQQueue Events	12-80
MessageAvailable Event	12-80
OracleAQDequeueMode Enumeration	12-84
OracleAQMessageDeliveryMode Enumeration	12-85
OracleAQMessageState Enumeration	12-87
OracleAQMessageType Enumeration	12-87
OracleAQNavigationMode Enumeration	12-88
OracleAQNotificationGroupingType Enumeration	12-90
OracleAQNotificationType Enumeration	12-90
OracleAQVisibilityMode Enumeration	12-91

13 Oracle Data Provider for .NET Types Classes

OracleBFile Class	13-1
OracleBFile Members	13-3
OracleBFile Constructors	13-6
OracleBFile(OracleConnection)	13-7
OracleBFile(OracleConnection, string, string)	13-7
OracleBFile Static Fields	13-8
MaxSize	13-9
Null	13-9
OracleBFile Static Methods	13-10
OracleBFile Instance Properties	13-10
CanRead	13-11
CanSeek	13-11
CanWrite	13-12
Connection	13-12
DirectoryName	13-13
FileExists	13-14
FileName	13-14
IsEmpty	13-15
IsNull	13-16
IsOpen	13-16
Length	13-16
Position	13-17
Value	13-18
OracleBFile Instance Methods	13-18
Clone	13-20
Close	13-21
CloseFile	13-22

Compare	13-22
CopyTo	13-25
CopyTo(OracleBlob)	13-25
CopyTo(OracleBlob, Int64)	13-26
CopyTo(Int64, OracleBlob, Int64, Int64)	13-27
CopyTo(OracleClob)	13-28
CopyTo(OracleClob, Int64)	13-29
CopyTo(Int64, OracleClob, Int64, Int64)	13-30
Dispose	13-31
Flush	13-32
FlushAsync	13-32
IsEqual	13-33
OpenFile	13-33
Read	13-34
Search	13-36
Seek	13-38
SetLength	13-40
Write	13-40
OracleBlob Class	13-40
OracleBlob Members	13-43
OracleBlob Constructors	13-46
OracleBlob(OracleConnection)	13-46
OracleBlob(OracleConnection, bool)	13-47
OracleBlob Static Fields	13-47
MaxSize	13-48
Null	13-48
OracleBlob Static Methods	13-49
OracleBlob Instance Properties	13-49
CanRead	13-50
CanSeek	13-51
CanWrite	13-51
Connection	13-52
IsEmpty	13-52
IsInChunkWriteMode	13-53
IsNull	13-53
IsTemporary	13-54
Length	13-54
OptimumChunkSize	13-55
Position	13-55
Value	13-56
OracleBlob Instance Methods	13-57

Append	13-58
Append(OracleBlob)	13-59
Append(byte[], int, int)	13-59
BeginChunkWrite	13-61
Clone	13-61
Close	13-63
Compare	13-63
CopyTo	13-64
CopyTo(OracleBlob)	13-65
CopyTo(OracleBlob, Int64)	13-66
CopyTo(Int64, OracleBlob, Int64, Int64)	13-67
Dispose	13-69
EndChunkWrite	13-69
Erase	13-70
Erase()	13-70
Erase(Int64, Int64)	13-71
Flush	13-72
IsEqual	13-72
Read	13-73
Search	13-75
Seek	13-76
SetLength	13-77
Write	13-78
OracleClob Class	13-80
OracleClob Members	13-82
OracleClob Constructors	13-85
OracleClob(OracleConnection)	13-85
OracleClob(OracleConnection, bool, bool)	13-86
OracleClob Static Fields	13-87
MaxSize	13-87
Null	13-88
OracleClob Static Methods	13-88
OracleClob Instance Properties	13-89
CanRead	13-89
CanSeek	13-90
CanWrite	13-90
Connection	13-91
IsEmpty	13-91
IsInChunkWriteMode	13-92
IsNClob	13-92
IsNull	13-93

IsTemporary	13-93
Length	13-94
OptimumChunkSize	13-94
Position	13-95
Value	13-96
OracleClob Instance Methods	13-96
Append	13-98
Append(OracleClob)	13-98
Append(byte [], int, int)	13-99
Append(char [], int, int)	13-100
BeginChunkWrite	13-101
Clone	13-102
Close	13-103
Compare	13-104
CopyTo	13-105
CopyTo(OracleClob)	13-105
CopyTo(OracleClob, Int64)	13-106
CopyTo(Int64, OracleClob, Int64, Int64)	13-107
Dispose	13-109
EndChunkWrite	13-109
Erase	13-110
Erase()	13-110
Erase(Int64, Int64)	13-111
Flush	13-112
GetHashCode	13-112
IsEqual	13-112
Read	13-113
Read(byte [], int, int)	13-114
Read(char [], int, int)	13-115
Search	13-117
Search(byte[], Int64, Int64)	13-117
Search(char[], Int64, Int64)	13-118
Seek	13-120
SetLength	13-121
Write	13-122
Write(byte[], int, int)	13-122
Write(char[], int, int)	13-123
OracleRefCursor Class	13-125
OracleRefCursor Members	13-127
OracleRefCursor Static Methods	13-129
OracleRefCursor Static Fields	13-129

Null	13-130
OracleRefCursor Properties	13-130
Connection	13-130
FetchSize	13-131
IsNull	13-132
RowSize	13-133
OracleRefCursor Instance Methods	13-134
Dispose	13-134
GetDataReader	13-135

14 Oracle Data Provider for .NET Types Structures

OracleBinary Structure	14-1
OracleBinary Members	14-3
OracleBinary Constructor	14-5
OracleBinary Static Fields	14-6
Null	14-6
OracleBinary Static Methods	14-7
Concat	14-7
Equals	14-8
GetXsdType	14-9
GreaterThan	14-9
GreaterThanOrEqual	14-11
LessThan	14-12
LessThanOrEqual	14-12
NotEquals	14-13
OracleBinary Static Operators	14-14
operator +	14-14
operator ==	14-15
operator >	14-16
operator >=	14-17
operator !=	14-18
operator <	14-18
operator <=	14-19
OracleBinary Static Type Conversion Operators	14-20
explicit operator byte[]	14-20
implicit operator OracleBinary	14-21
OracleBinary Properties	14-21
IsNull	14-22
Item	14-22
Length	14-23

Value	14-24
OracleBinary Instance Methods	14-24
CompareTo	14-25
Equals	14-26
GetHashCode	14-27
ToString	14-28
OracleBoolean Structure	14-28
OracleBoolean Members	14-30
OracleBoolean Constructors	14-33
OracleBoolean(bool)	14-34
OracleBoolean(int)	14-34
OracleBoolean Static Fields	14-35
False	14-35
Null	14-36
One	14-36
True	14-36
Zero	14-37
OracleBoolean Static Methods	14-37
And	14-38
Equals	14-39
GreaterThan	14-40
GreaterThanOrEquals	14-40
LessThan	14-41
LessThanOrEquals	14-42
NotEquals	14-42
OnesComplement	14-43
Or	14-44
Parse	14-45
Xor	14-45
OracleBoolean Static Operators	14-46
operator >	14-47
operator >=	14-48
operator <	14-48
operator <=	14-49
operator ==	14-50
operator !=	14-51
operator !	14-51
operator ~	14-52
operator false	14-53
operator true	14-53
operator &	14-54

operator	14-55
operator ^	14-55
OracleBoolean Static Type Conversions	14-56
implicit operator OracleBoolean	14-57
explicit operator bool	14-57
explicit operator OracleBoolean	14-58
explicit operator OracleBoolean(byte)	14-59
explicit operator OracleBoolean(Decimal)	14-59
explicit operator OracleBoolean(Double)	14-60
explicit operator OracleBoolean(Int16)	14-60
explicit operator OracleBoolean(int)	14-61
explicit operator OracleBoolean(Int64)	14-61
explicit operator OracleBoolean(Single)	14-62
explicit operator OracleBoolean(String)	14-63
OracleBoolean Properties	14-63
ByteValue	14-64
IsFalse	14-64
IsNull	14-65
IsTrue	14-65
Value	14-66
OracleBoolean Instance Methods	14-66
CompareTo	14-67
Equals	14-68
GetHashCode	14-68
ToString	14-69
OracleDate Structure	14-70
OracleDate Members	14-71
OracleDate Constructors	14-74
OracleDate(DateTime)	14-75
OracleDate(string)	14-75
OracleDate(int, int, int)	14-77
OracleDate(int, int, int, int, int, int)	14-78
OracleDate(byte [])	14-78
OracleDate Static Fields	14-79
MaxValue	14-80
MinValue	14-80
Null	14-80
OracleDate Static Methods	14-81
Equals	14-81
GreaterThan	14-82
GreaterThanOrEqual	14-83

LessThan	14-84
LessThanOrEqual	14-85
NotEquals	14-85
GetSysDate	14-86
Parse	14-87
OracleDate Static Operators	14-88
operator ==	14-89
operator >	14-89
operator >=	14-90
operator !=	14-91
operator <	14-92
operator <=	14-92
OracleDate Static Type Conversions	14-93
explicit operator DateTime	14-94
explicit operator OracleDate	14-94
explicit operator OracleDate(DateTime)	14-95
explicit operator OracleDate(OracleTimeStamp)	14-95
explicit operator OracleDate(string)	14-96
OracleDate Properties	14-97
BinData	14-98
Day	14-99
IsNull	14-99
Hour	14-99
Minute	14-100
Month	14-100
Second	14-101
Value	14-101
Year	14-102
OracleDate Methods	14-102
CompareTo	14-103
Equals	14-104
GetHashCode	14-105
GetDaysBetween	14-105
ToOracleTimeStamp	14-106
ToString	14-107
OracleDecimal Structure	14-108
OracleDecimal Members	14-110
OracleDecimal Constructors	14-115
OracleDecimal(byte [])	14-116
OracleDecimal(decimal)	14-117
OracleDecimal(double)	14-117

OracleDecimal(int)	14-118
OracleDecimal(float)	14-119
OracleDecimal(long)	14-119
OracleDecimal(string)	14-120
OracleDecimal(string, string)	14-120
OracleDecimal Static Fields	14-122
MaxPrecision	14-123
MaxScale	14-123
MaxValue	14-123
MinScale	14-124
MinValue	14-124
NegativeOne	14-124
Null	14-125
One	14-125
Pi	14-126
Zero	14-126
OracleDecimal Static (Comparison) Methods	14-126
Equals	14-127
GreaterThan	14-128
GreaterThanOrEqual	14-129
LessThan	14-130
LessThanOrEqual	14-130
NotEquals	14-131
OracleDecimal Static (Manipulation) Methods	14-132
Abs	14-133
Add	14-134
AdjustScale	14-134
Ceiling	14-136
ConvertToPrecScale	14-136
Divide	14-138
Floor	14-138
Max	14-139
Min	14-139
Mod	14-140
Multiply	14-141
Negate	14-141
Parse	14-142
Round	14-143
SetPrecision	14-144
Shift	14-145
Sign	14-145

Sqrt	14-146
Subtract	14-147
Truncate	14-148
OracleDecimal Static (Logarithmic) Methods	14-148
Exp	14-149
Log	14-149
Log(OracleDecimal)	14-150
Log(OracleDecimal, int)	14-151
Log(OracleDecimal, OracleDecimal)	14-152
Pow	14-152
Pow(OracleDecimal, int)	14-153
Pow(OracleDecimal, OracleDecimal)	14-154
OracleDecimal Static (Trigonometric) Methods	14-154
Acos	14-155
Asin	14-156
Atan	14-156
Atan2	14-157
Cos	14-158
Sin	14-158
Tan	14-159
Cosh	14-160
Sinh	14-160
Tanh	14-161
OracleDecimal Static (Comparison) Operators	14-162
operator +	14-162
operator /	14-163
operator ==	14-164
operator >	14-164
operator >=	14-165
operator !=	14-166
operator <	14-167
operator <=	14-168
operator *	14-168
operator -	14-169
operator -	14-170
operator%	14-170
OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)	14-171
implicit operator OracleDecimal	14-172
implicit operator OracleDecimal(decimal)	14-172
implicit operator OracleDecimal(int)	14-173
implicit operator OracleDecimal(long)	14-173

explicit operator OracleDecimal	14-174
explicit operator OracleDecimal(double)	14-174
explicit operator OracleDecimal(string)	14-175
OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)	14-176
explicit operator byte	14-177
explicit operator decimal	14-177
explicit operator double	14-178
explicit operator short	14-178
explicit operator int	14-179
explicit operator long	14-180
explicit operator float	14-180
OracleDecimal Properties	14-181
BinData	14-182
Format	14-182
IsInt	14-183
IsNull	14-184
IsPositive	14-184
IsZero	14-185
Value	14-185
OracleDecimal Instance Methods	14-186
CompareTo	14-187
Equals	14-188
GetHashCode	14-188
ToByte	14-189
ToDouble	14-189
ToInt16	14-190
ToInt32	14-191
ToInt64	14-191
ToSingle	14-192
ToString	14-192
OracleIntervalDS Structure	14-193
OracleIntervalDS Members	14-195
OracleIntervalDS Constructors	14-198
OracleIntervalDS(TimeSpan)	14-199
OracleIntervalDS(string)	14-200
OracleIntervalDS(double)	14-201
OracleIntervalDS(int, int, int, int, double)	14-201
OracleIntervalDS(int, int, int, int, int)	14-202
OracleIntervalDS(byte[])	14-203
OracleIntervalDS Static Fields	14-204
MaxValue	14-204

MinValue	14-205
Null	14-205
Zero	14-206
OracleIntervalDS Static Methods	14-206
Equals	14-207
GreaterThan	14-208
GreaterThanOrEqual	14-209
LessThan	14-209
LessThanOrEqual	14-210
NotEquals	14-211
Parse	14-212
SetPrecision	14-213
OracleIntervalDS Static Operators	14-214
operator +	14-214
operator ==	14-215
operator >	14-216
operator >=	14-217
operator !=	14-217
operator <	14-218
operator <=	14-219
operator -	14-220
operator -	14-220
operator *	14-221
operator /	14-222
OracleIntervalDS Type Conversions	14-222
explicit operator TimeSpan	14-223
explicit operator OracleIntervalDS	14-224
implicit operator OracleIntervalDS	14-225
OracleIntervalDS Properties	14-225
BinData	14-226
Days	14-227
Hours	14-227
IsNull	14-228
Milliseconds	14-228
Minutes	14-229
Nanoseconds	14-229
Seconds	14-230
TotalDays	14-230
Value	14-231
OracleIntervalDS Methods	14-231
CompareTo	14-232

Equals	14-233
GetHashCode	14-234
ToString	14-234
OracleIntervalYM Structure	14-235
OracleIntervalYM Members	14-236
OracleIntervalYM Constructors	14-240
OracleIntervalYM(long)	14-240
OracleIntervalYM(string)	14-241
OracleIntervalYM(double)	14-242
OracleIntervalYM(int, int)	14-242
OracleIntervalYM(byte[])	14-243
OracleIntervalYM Static Fields	14-244
MaxValue	14-244
MinValue	14-245
Null	14-245
Zero	14-246
OracleIntervalYM Static Methods	14-246
Equals	14-247
GreaterThan	14-248
GreaterThanOrEqual	14-248
LessThan	14-249
LessThanOrEqual	14-250
NotEquals	14-251
Parse	14-251
SetPrecision	14-252
OracleIntervalYM Static Operators	14-253
operator +	14-254
operator ==	14-255
operator >	14-255
operator >=	14-256
operator !=	14-257
operator <	14-258
operator <=	14-259
operator -	14-259
operator -	14-260
operator *	14-261
operator /	14-261
OracleIntervalYM Type Conversions	14-262
explicit operator long	14-263
explicit operator OracleIntervalYM	14-263
implicit operator OracleIntervalYM	14-264

OracleIntervalYM Properties	14-265
BinData	14-265
IsNull	14-266
Months	14-266
TotalYears	14-267
Value	14-267
Years	14-268
OracleIntervalYM Methods	14-268
CompareTo	14-269
Equals	14-270
GetHashCode	14-271
ToString	14-271
OracleString Structure	14-272
OracleString Members	14-273
OracleString Constructors	14-276
OracleString(string)	14-277
OracleString(string, bool)	14-278
OracleString(byte [], bool)	14-278
OracleString(byte [], bool, bool)	14-279
OracleString(byte [], int, int, bool)	14-279
OracleString(byte [], int, int, bool, bool)	14-280
OracleString Static Fields	14-281
Null	14-282
OracleString Static Methods	14-282
Concat	14-283
Equals	14-283
GreaterThan	14-284
GreaterThanOrEqual	14-285
LessThan	14-286
LessThanOrEqual	14-287
NotEquals	14-287
OracleString Static Operators	14-288
operator +	14-289
operator ==	14-289
operator >	14-290
operator >=	14-291
operator !=	14-292
operator <	14-292
operator <=	14-293
OracleString Type Conversions	14-294
explicit operator string	14-294

implicit operator OracleString	14-295
OracleString Properties	14-296
IsCaseIgnored	14-296
IsNull	14-297
Item	14-298
Length	14-298
Value	14-299
OracleString Methods	14-299
Clone	14-300
CompareTo	14-301
Equals	14-302
GetHashCode	14-303
GetNonUnicodeBytes	14-303
GetUnicodeBytes	14-304
ToString	14-304
OracleTimeStamp Structure	14-305
OracleTimeStamp Members	14-306
OracleTimeStamp Constructors	14-310
OracleTimeStamp(DateTime)	14-311
OracleTimeStamp(string)	14-312
OracleTimeStamp(int, int, int)	14-313
OracleTimeStamp(int, int, int, int, int, int)	14-314
OracleTimeStamp(int, int, int, int, int, int, double)	14-315
OracleTimeStamp(int, int, int, int, int, int, int)	14-316
OracleTimeStamp(byte [])	14-317
OracleTimeStamp Static Fields	14-318
MaxValue	14-318
MinValue	14-318
Null	14-319
OracleTimeStamp Static Methods	14-319
Equals	14-320
GreaterThan	14-321
GreaterThanOrEqual	14-322
LessThan	14-322
LessThanOrEqual	14-323
NotEquals	14-324
GetSysDate	14-325
Parse	14-325
SetPrecision	14-327
OracleTimeStamp Static Operators	14-328
operator +	14-328

operator + (OracleTimeStamp, OracleIntervalDS)	14-329
operator + (OracleTimeStamp, OracleIntervalYM)	14-330
operator + (OracleTimeStamp, TimeSpan)	14-330
operator ==	14-331
operator >	14-332
operator >=	14-333
operator !=	14-334
operator <	14-334
operator <=	14-335
operator -	14-336
operator - (OracleTimeStamp, OracleIntervalDS)	14-336
operator - (OracleTimeStamp, OracleIntervalYM)	14-337
operator - (OracleTimeStamp, TimeSpan)	14-338
OracleTimeStamp Static Type Conversions	14-338
explicit operator OracleTimeStamp	14-339
explicit operator OracleTimeStamp(OracleTimeStampLTZ)	14-340
explicit operator OracleTimeStamp(OracleTimeStampTZ)	14-340
explicit operator OracleTimeStamp(string)	14-341
implicit operator OracleTimeStamp	14-342
implicit operator OracleTimeStamp(OracleDate)	14-343
implicit operator OracleTimeStamp(DateTime)	14-343
explicit operator DateTime	14-344
OracleTimeStamp Properties	14-345
BinData	14-345
Day	14-346
IsNull	14-346
Hour	14-347
Millisecond	14-347
Minute	14-348
Month	14-348
Nanosecond	14-349
Second	14-349
Value	14-350
Year	14-350
OracleTimeStamp Methods	14-351
AddDays	14-352
AddHours	14-353
AddMilliseconds	14-353
AddMinutes	14-354
AddMonths	14-355
AddNanoseconds	14-355

AddSeconds	14-356
AddYears	14-357
CompareTo	14-357
Equals	14-358
GetHashCode	14-359
GetDaysBetween	14-360
GetYearsBetween	14-360
ToOracleDate	14-361
ToOracleTimeStampLTZ	14-362
ToOracleTimeStampTZ	14-362
ToString	14-363
OracleTimeStampLTZ Structure	14-364
OracleTimeStampLTZ Members	14-366
OracleTimeStampLTZ Constructors	14-370
OracleTimeStampLTZ(DateTime)	14-371
OracleTimeStampLTZ(string)	14-372
OracleTimeStampLTZ(int, int, int)	14-373
OracleTimeStampLTZ(int, int, int, int, int, int)	14-374
OracleTimeStampLTZ(int, int, int, int, int, int, double)	14-375
OracleTimeStampLTZ(int, int, int, int, int, int, int)	14-376
OracleTimeStampLTZ(byte [])	14-377
OracleTimeStampLTZ Static Fields	14-378
MaxValue	14-378
MinValue	14-379
Null	14-379
OracleTimeStampLTZ Static Methods	14-379
Equals	14-380
GetLocalTimeZoneName	14-381
GetLocalTimeZoneOffset	14-381
GetSysDate	14-382
GreaterThan	14-382
GreaterThanOrEqual	14-383
LessThan	14-384
LessThanOrEqual	14-385
NotEquals	14-386
Parse	14-386
SetPrecision	14-388
OracleTimeStampLTZ Static Operators	14-389
operator +	14-389
operator + (OracleTimeStampLTZ, OracleIntervalDS)	14-390
operator + (OracleTimeStampLTZ, OracleIntervalYM)	14-391

operator + (OracleTimeStampLTZ, TimeSpan)	14-391
operator ==	14-392
operator >	14-393
operator >=	14-394
operator !=	14-395
operator <	14-395
operator <=	14-396
operator -	14-397
operator - (OracleTimeStampLTZ, OracleIntervalDS)	14-398
operator - (OracleTimeStampLTZ, OracleIntervalYM)	14-398
operator - (OracleTimeStampLTZ, TimeSpan)	14-399
OracleTimeStampLTZ Static Type Conversions	14-400
explicit operator OracleTimeStampLTZ	14-400
explicit operator OracleTimeStampLTZ(OracleTimeStamp)	14-401
explicit operator OracleTimeStampLTZ(OracleTimeStampTZ)	14-402
explicit operator OracleTimeStampLTZ(string)	14-402
implicit operator OracleTimeStampLTZ	14-404
implicit operator OracleTimeStampLTZ(OracleDate)	14-404
implicit operator OracleTimeStampLTZ(DateTime)	14-405
explicit operator DateTime	14-406
OracleTimeStampLTZ Properties	14-406
BinData	14-407
Day	14-408
IsNull	14-408
Hour	14-409
Millisecond	14-409
Minute	14-410
Month	14-410
Nanosecond	14-411
Second	14-411
Value	14-412
Year	14-412
OracleTimeStampLTZ Methods	14-413
AddDays	14-414
AddHours	14-415
AddMilliseconds	14-415
AddMinutes	14-416
AddMonths	14-417
AddNanoseconds	14-417
AddSeconds	14-418
AddYears	14-419

CompareTo	14-419
Equals	14-420
GetHashCode	14-421
GetDaysBetween	14-422
GetYearsBetween	14-422
ToOracleDate	14-423
ToOracleTimeStamp	14-424
ToOracleTimeStampTZ	14-424
ToString	14-425
ToUniversalTime	14-426
OracleTimeStampTZ Structure	14-427
OracleTimeStampTZ Members	14-429
OracleTimeStampTZ Constructors	14-433
OracleTimeStampTZ(DateTime)	14-434
OracleTimeStampTZ(DateTime, string)	14-435
OracleTimeStampTZ(string)	14-436
OracleTimeStampTZ(int, int, int)	14-437
OracleTimeStampTZ(int, int, int, string)	14-438
OracleTimeStampTZ(int, int, int, int, int, int)	14-439
OracleTimeStampTZ(int, int, int, int, int, int, string)	14-440
OracleTimeStampTZ(int, int, int, int, int, int, double)	14-441
OracleTimeStampTZ(int, int, int, int, int, int, double, string)	14-442
OracleTimeStampTZ(int, int, int, int, int, int, int)	14-444
OracleTimeStampTZ(int, int, int, int, int, int, int, string)	14-445
OracleTimeStampTZ(byte [])	14-446
OracleTimeStampTZ Static Fields	14-447
MaxValue	14-447
MinValue	14-448
Null	14-448
OracleTimeStampTZ Static Methods	14-449
Equals	14-449
GetSysDate	14-450
GreaterThan	14-451
GreaterThanOrEqual	14-451
LessThan	14-452
LessThanOrEqual	14-453
NotEquals	14-454
Parse	14-455
SetPrecision	14-456
OracleTimeStampTZ Static Operators	14-457
operator +	14-458

operator +(OracleTimeStampTZ, OracleIntervalDS)	14-458
operator +(OracleTimeStampTZ, OracleIntervalYM)	14-459
operator +(OracleTimeStampTZ, TimeSpan)	14-460
operator ==	14-460
operator >	14-461
operator >=	14-462
operator !=	14-463
operator <	14-464
operator <=	14-464
operator -	14-465
operator - (OracleTimeStampTZ, OracleIntervalDS)	14-466
operator - (OracleTimeStampTZ, OracleIntervalYM)	14-466
operator - (OracleTimeStampTZ value1, TimeSpan value2)	14-467
OracleTimeStampTZ Static Type Conversions	14-468
explicit operator OracleTimeStampTZ	14-468
explicit operator OracleTimeStampTZ(OracleTimeStamp)	14-469
explicit operator OracleTimeStampTZ(OracleTimeStampLTZ)	14-470
explicit operator OracleTimeStampTZ(string)	14-471
implicit operator OracleTimeStampTZ	14-472
implicit operator OracleTimeStampTZ(OracleDate)	14-472
implicit operator OracleTimeStampTZ(DateTime)	14-473
explicit operator DateTime	14-474
OracleTimeStampTZ Properties	14-475
BinData	14-476
Day	14-476
IsNull	14-477
Hour	14-477
Millisecond	14-478
Minute	14-478
Month	14-479
Nanosecond	14-479
Second	14-480
TimeZone	14-480
Value	14-481
Year	14-481
OracleTimeStampTZ Methods	14-482
AddDays	14-483
AddHours	14-484
AddMilliseconds	14-484
AddMinutes	14-485
AddMonths	14-486

AddNanoseconds	14-486
AddSeconds	14-487
AddYears	14-488
CompareTo	14-488
Equals	14-489
GetDaysBetween	14-490
GetHashCode	14-491
GetTimeZoneOffset	14-491
GetYearsBetween	14-492
ToLocalTime	14-492
ToOracleDate	14-493
ToOracleTimeStampLTZ	14-494
ToOracleTimeStamp	14-494
ToString	14-495
ToUniversalTime	14-496
INullable Interface	14-497
INullable Interface Members	14-498
INullable Interface Properties	14-498
IsNull	14-498

15 Oracle Data Provider for .NET Types Exceptions

OracleTypeException Class	15-1
OracleTypeException Members	15-2
OracleTypeException Constructors	15-3
OracleTypeException(string)	15-4
OracleTypeException(SerializationInfo, StreamingContext)	15-4
OracleTypeException Static Methods	15-5
OracleTypeException Properties	15-5
Message	15-6
Number	15-6
Source	15-7
OracleTypeException Methods	15-7
ToString	15-8
OracleNullValueException Class	15-8
OracleNullValueException Members	15-9
OracleNullValueException Constructors	15-11
OracleNullValueException()	15-11
OracleNullValueException(string)	15-12
OracleNullValueException Static Methods	15-12
OracleNullValueException Properties	15-13

OracleNullValueException Methods	15-13
OracleTruncateException Class	15-14
OracleTruncateException Members	15-15
OracleTruncateException Constructors	15-16
OracleTruncateException()	15-17
OracleTruncateException(string)	15-17
OracleTruncateException Static Methods	15-18
OracleTruncateException Properties	15-18
OracleTruncateException Methods	15-19

16 Oracle Data Provider for .NET UDT-Related Classes

OracleCustomTypeMappingAttribute Class	16-1
OracleCustomTypeMappingAttribute Members	16-3
OracleCustomTypeMappingAttribute Constructors	16-4
OracleCustomTypeMappingAttribute(string)	16-4
OracleCustomTypeMappingAttribute Static Methods	16-5
OracleCustomTypeMappingAttribute Properties	16-5
UdtTypeName	16-6
OracleCustomTypeMappingAttribute Methods	16-6
OracleObjectMappingAttribute Class	16-7
OracleObjectMappingAttribute Members	16-8
OracleObjectMappingAttribute Constructors	16-10
OracleObjectMappingAttribute(string)	16-10
OracleObjectMappingAttribute(int)	16-11
OracleObjectMappingAttribute Static Methods	16-11
OracleObjectMappingAttribute Properties	16-12
AttributeIndex	16-12
AttributeName	16-13
OracleObjectMappingAttribute Methods	16-13
OracleArrayMappingAttribute Class	16-14
OracleArrayMappingAttribute Members	16-15
OracleArrayMappingAttribute Constructors	16-16
OracleArrayMappingAttribute()	16-17
OracleArrayMappingAttribute Static Methods	16-17
OracleArrayMappingAttribute Properties	16-18
OracleArrayMappingAttribute Methods	16-18
IOracleCustomType Interface	16-19
IOracleCustomType Members	16-19
IOracleCustomType Interface Methods	16-20
FromCustomObject	16-20

ToCustomObject	16-21
IOracleCustomTypeFactory Interface	16-22
IOracleCustomTypeFactory Members	16-23
IOracleCustomTypeFactory Interface Methods	16-23
CreateObject	16-24
IOracleArrayTypeFactory Interface	16-24
IOracleArrayTypeFactory Members	16-25
IOracleArrayTypeFactory Interface Methods	16-26
CreateArray	16-26
CreateStatusArray	16-27
OracleUdt Class	16-28
OracleUdt Members	16-28
OracleUDT Static Methods	16-29
GetValue	16-29
GetValue(OracleConnection, IntPtr, string)	16-30
GetValue(OracleConnection, IntPtr, int)	16-31
GetValue(OracleConnection, IntPtr, string, out object)	16-32
GetValue(OracleConnection, IntPtr, int, out object)	16-34
IsDBNull	16-35
IsDBNull(OracleConnection, IntPtr, string)	16-36
IsDBNull(OracleConnection, IntPtr, int)	16-37
SetValue	16-38
SetValue(OracleConnection, IntPtr, string, object)	16-38
SetValue(OracleConnection, IntPtr, int, object)	16-40
SetValue(OracleConnection, IntPtr, string, object, object)	16-41
SetValue(OracleConnection, IntPtr, int, object, object)	16-42
OracleRef Class	16-43
OracleRef Members	16-44
OracleRef Constructors	16-46
OracleRef(OracleConnection, string)	16-46
OracleRef(OracleConnection, string, string)	16-47
OracleRef Static Fields	16-48
Null	16-48
OracleRef Static Methods	16-49
OracleRef Instance Properties	16-49
Connection	16-50
HasChanges	16-50
IsLocked	16-51
IsNull	16-52
ObjectTableName	16-52
Value	16-53

Oracle Ref Instance Methods	16-54
Clone	16-54
Delete	16-55
Dispose	16-56
Flush	16-56
GetCustomObject	16-57
GetCustomObject(OracleUdtFetchOption)	16-57
GetCustomObject(OracleUdtFetchOption, int)	16-59
GetCustomObjectForUpdate	16-60
GetCustomObjectForUpdate(bool)	16-61
GetCustomObjectForUpdate(bool, int)	16-62
IsEqual	16-63
Lock	16-64
Update	16-65
OracleUdtFetchOption Enumeration	16-66
OracleUdtStatus Enumeration	16-67

17 Oracle Data Provider for .NET Bulk Copy Classes

OracleBulkCopy Class	17-1
OracleBulkCopy Members	17-2
OracleBulkCopy Constructors	17-4
OracleBulkCopy(OracleConnection)	17-4
OracleBulkCopy(string)	17-5
OracleBulkCopy(OracleConnection, OracleBulkCopyOptions)	17-6
OracleBulkCopy(string, OracleBulkCopyOptions)	17-7
OracleBulkCopy Properties	17-8
BatchSize	17-8
BulkCopyOptions	17-10
BulkCopyTimeout	17-10
ColumnMappings	17-11
Connection	17-12
DestinationPartitionName	17-12
DestinationTableName	17-13
NotifyAfter	17-14
OracleBulkCopy Public Methods	17-14
Close	17-15
Dispose	17-15
WriteToServer	17-16
WriteToServer(DataRow[])	17-17
WriteToServer(DataTable)	17-17

WriteToServer(IDataReader)	17-18
WriteToServer(DataTable, DataRowState)	17-19
WriteToServer(OracleRefCursor)	17-20
OracleBulkCopy Events	17-21
OracleRowsCopied	17-21
OracleBulkCopyColumnMapping Class	17-22
OracleBulkCopyColumnMapping Members	17-23
OracleBulkCopyColumnMapping Constructors	17-24
OracleBulkCopyColumnMapping()	17-25
OracleBulkCopyColumnMapping(int, int)	17-25
OracleBulkCopyColumnMapping(int, string)	17-26
OracleBulkCopyColumnMapping(string, int)	17-26
OracleBulkCopyColumnMapping(string, string)	17-27
OracleBulkCopyColumnMapping Methods	17-27
CompareTo	17-28
OracleBulkCopyColumnMapping Properties	17-28
DestinationColumn	17-29
DestinationOrdinal	17-30
SourceColumn	17-30
SourceOrdinal	17-31
OracleBulkCopyColumnMappingCollection Class	17-31
OracleBulkCopyColumnMappingCollection Members	17-33
OracleBulkCopyColumnMappingCollection Properties	17-34
Item[index]	17-34
OracleBulkCopyColumnMappingCollection Public Methods	17-35
Add	17-36
Add(OracleBulkCopyColumnMapping)	17-36
Add(int, int)	17-37
Add(int, string)	17-38
Add(string, int)	17-39
Add(string, string)	17-40
Clear	17-41
Contains	17-42
CopyTo	17-42
IndexOf	17-43
Insert	17-44
Remove	17-44
RemoveAt	17-45
OracleBulkCopyOptions Enumeration	17-46
OracleRowsCopiedEventHandler Delegate	17-47
OracleRowsCopiedEventArgs Class	17-48

OracleRowsCopiedEventArgs Members	17-49
OracleRowsCopiedEventArgs Constructors	17-49
OracleRowsCopiedEventArgs(long)	17-50
OracleRowsCopiedEventArgs Properties	17-50
Abort	17-51
RowsCopied	17-52

A Oracle Schema Collections

Common Schema Collections	A-1
MetaDataCollections	A-1
DataSourceInformation	A-2
DataTypes	A-3
Restrictions	A-5
ReservedWords	A-5
ODP.NET-Specific Schema Collection	A-6
Tables	A-6
Columns	A-7
Views	A-7
XMLSchema	A-8
Users	A-8
Synonyms	A-9
Sequences	A-9
Functions	A-10
Procedures	A-10
ProcedureParameters	A-11
Arguments	A-12
Packages	A-13
PackageBodies	A-14
JavaClasses	A-15
Indexes	A-15
IndexColumns	A-18
PrimaryKeys	A-19
ForeignKeys	A-20
ForeignKeyColumns	A-21
UniqueKeys	A-21

B Mapping LINQ Canonical Functions and Oracle Functions

Glossary

Index

List of Examples

2-1	Setting the profile which could be used for all connections	2-31
2-2	Setting the Profile for a Specific Data Source	2-31
2-3	Setting the Profile for a Specific User Id	2-31
2-4	Setting the Profile for a Specific Data Source and User Id'	2-31
2-5	Configuring Multiple Default Profile Entries	2-31
2-6	Code Sample	2-49
3-1	Using Database Resident Connection Pooling: Sample Code	3-35
3-2	Using Pluggable Database: Sample Code	3-38
3-3	Using Edition-Based Redefinition: Sample Code	3-39
3-4	Using Transaction Guard: Sample Code	3-59
3-5	Using the add Element with bindinfo	3-108
3-6	Using the add Element with metadata	3-108
4-1	First Sample ODP.NET, Unmanaged Driver Application Configuration File to Custom Map the Number (p,0) Data Type	4-15
4-2	Second Sample ODP.NET, Unmanaged Driver Application Configuration File to Custom Map the Number (p,0) Data Type	4-16
4-3	Sample ODP.NET, Managed Driver Application Configuration File to Custom Map the Number Data Type	4-16

List of Tables

1-1	Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client	1-6
1-2	Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations	1-16
1-3	Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Structures	1-19
1-4	Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Exceptions	1-20
1-5	Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes	1-20
1-6	Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces	1-21
1-7	Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Enumerations	1-22
1-8	Application Programming Interfaces not supported in ODP.NET, Managed Driver and ODP.NET Core	1-22
2-1	ODP.NET, Managed Driver Files with Descriptions	2-9
2-2	ODP.NET, Core Files with Descriptions	2-11
2-3	Configuration Attributes	2-18
2-4	Encryption Algorithms for ODP.NET, Managed Driver	2-42
2-5	Microsoft Active Directory: Encryption Types and Authentication Credentials For Connecting and Binding	2-43
2-6	Oracle Internet Directory: Encryption Types and Authentication Credentials For Connecting and Binding	2-43
2-7	Required ONS Configuration Parameters	2-47
2-8	Optional ONS Configuration Parameters	2-47
2-9	Supported ODP.NET Type and .NET Framework Version for Distributed Transaction	2-53
2-10	Configuration Differences between ODP.NET, Unmanaged Driver and ODP.NET, Managed Driver	2-54
3-1	ODP.NET Classes that Inherit from ADO.NET 2.0 Base Classes	3-2
3-2	Supported Connection String Attributes	3-6
3-3	Performance Counters for Connection Pooling	3-31
3-4	Field Names of Performance Counters and Maximum Number of Characters	3-33
3-5	Configurations for ODP.NET Driver Types	3-51
3-6	Implication of Committed and UserCallCompleted Values	3-59
3-7	OracleDbType Enumeration Values	3-71
3-8	Inference of System.Data.DbType from OracleDbType	3-72
3-9	Inference of OracleDbType from DbType	3-73
3-10	Inference of DbType and OracleDbType from Value (.NET Datatypes)	3-74
3-11	Inference of DbType and OracleDbType from Value (ODP.NET Types)	3-75
3-12	OracleParameterStatus Members	3-82
3-13	Value Property Type of ODP.NET Type	3-87

3-14	.NET Type Accessors	3-89
3-15	ODP.NET Type Accessors	3-92
3-16	Supported OracleDataReader CLOB Methods for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1	3-96
3-17	Supported OracleDataReader BLOB Methods for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1	3-97
3-18	Allowed Parameters in Attributes List	3-106
3-19	ODP.NET LOB Objects	3-113
3-20	Characters with Special Meaning in XML	3-120
3-21	Attribute Mappings Between UDTs and Custom Object Types	3-137
3-22	Type and Value Returned from OracleDataReader Object	3-138
3-23	Values Returned from OracleDataReader Methods	3-140
3-24	Valid Ways to Bind Input Parameters for Oracle UDTs	3-141
3-25	Valid Ways to Bind Output Parameters for Oracle UDTs	3-143
3-26	Types that Populate the DataSet with ADO.NET 2.0	3-144
3-27	Mapping AQ Features with their ODP.NET Implementation	3-150
3-28	Oracle NUMBER to .NET Decimal Comparisons	3-161
3-29	Oracle Date to .NET DateTime Comparisons	3-162
3-30	Oracle TimeStamp to .NET DateTime Comparisons	3-162
3-31	Oracle INTERVAL DAY TO SECOND to .NET TimeSpan Comparisons	3-162
4-1	Mapping of Oracle Data Types and EDM Types	4-3
4-2	EDM Type Facets for Bfile	4-7
4-3	EDM Type Facets for Blob	4-7
4-4	EDM Type Facets for Char	4-7
4-5	EDM Type Facets for Clob	4-7
4-6	EDM Type Facets for Date	4-8
4-7	EDM Type Facets for Float	4-8
4-8	EDM Type Facets for Interval Day To Second	4-8
4-9	EDM Type Facets for Interval Year To Month	4-9
4-10	EDM Type Facets for Long	4-9
4-11	EDM Type Facets for Long Raw	4-10
4-12	EDM Type Facets for NChar	4-10
4-13	EDM Type Facets for NClob	4-10
4-14	EDM Type Facets for Number	4-11
4-15	EDM Type Facets for NVarchar2	4-11
4-16	EDM Type Facets for Raw	4-12
4-17	EDM Type Facets for ROWID	4-12

4-18	EDM Type Facets for Timestamp	4-12
4-19	EDM Type Facets for Timestamp with Local Time Zone	4-13
4-20	EDM Type Facets for Timestamp with Time Zone	4-13
4-21	EDM Type Facets for UROWID	4-13
4-22	EDM Type Facets for Varchar2	4-13
4-23	EDM Type Facets for XMLType	4-14
4-24	Mapping of .NET Data Types to Oracle Data Types	4-21
4-25	Mapping of Data Annotations and the Code First Fluent APIs	4-24
5-1	API Support Comparison Between Client Application and .NET Stored Procedure	5-7
6-1	OracleClientFactory Field	6-4
6-2	OracleClientFactory Constructor	6-4
6-3	OracleClientFactory Public Properties	6-4
6-4	OracleClientFactory Public Method	6-4
6-5	OracleClientFactory Field	6-5
6-6	OracleClientFactory Public Properties	6-6
6-7	OracleClientFactory Public Method	6-7
6-8	OracleCommand Constructors	6-14
6-9	OracleCommand Static Method	6-14
6-10	OracleCommand Properties	6-15
6-11	OracleCommand Public Methods	6-16
6-12	OracleCommand Static Method	6-19
6-13	OracleCommand Properties	6-20
6-14	OracleCommand Public Methods	6-41
6-15	OracleCommandBuilder Constructors	6-60
6-16	OracleCommandBuilder Static Methods	6-60
6-17	OracleCommandBuilder Properties	6-60
6-18	OracleCommandBuilder Public Methods	6-61
6-19	OracleCommandBuilder Events	6-61
6-20	OracleCommandBuilder Static Methods	6-63
6-21	OracleCommandBuilder Properties	6-67
6-22	OracleCommandBuilder Public Methods	6-72
6-23	OracleCommandBuilder Event	6-82
6-24	OracleConfiguration Connection Properties	6-85
6-25	OracleConfiguration Secure Connection Properties	6-86
6-26	OracleConfiguration Command Properties	6-86
6-27	OracleConfiguration Directories Properties	6-86
6-28	OracleConfiguration High Availability Properties	6-87

6-29	OracleConfiguration Performance Properties	6-88
6-30	OracleConfiguration Debug Tracing Properties	6-88
6-31	OracleConfiguration Connection Properties	6-88
6-32	OracleConfiguration Secure Connection Properties	6-93
6-33	OracleConfiguration Command Properties	6-102
6-34	OracleConfiguration Directories Properties	6-104
6-35	OracleConfiguration High Availability Properties	6-108
6-36	OracleConfiguration Performance Properties	6-114
6-37	OracleConfiguration Debug Tracing Properties	6-119
6-38	OracleConnection Constructors	6-123
6-39	OracleConnection Static Property	6-123
6-40	OracleConnection Static Methods	6-124
6-41	OracleConnection Properties	6-124
6-42	OracleConnection Public Methods	6-125
6-43	OracleConnection Events	6-127
6-44	OracleConnection Static Property	6-130
6-45	OracleConnection Static Methods	6-132
6-46	OracleConnection Properties	6-135
6-47	Supported Connection String Attributes	6-140
6-48	OracleConnection Public Methods	6-159
6-49	OracleConnection Events	6-185
6-50	OracleConnectionOpenEventArgs Properties	6-192
6-51	OracleConnectionOpenEventArgs Properties	6-192
6-52	OracleConnectionStringBuilder Constructors	6-198
6-53	OracleConnectionStringBuilder Public Properties	6-198
6-54	OracleConnectionStringBuilder Public Methods	6-200
6-55	OracleConnectionStringBuilder Public Properties	6-202
6-56	OracleConnectionStringBuilder Public Methods	6-220
6-57	OracleCredential Constructors	6-226
6-58	OracleCredential Properties	6-226
6-59	OracleCredential Public Methods	6-227
6-60	OracleCredential Properties	6-230
6-61	OracleDataAdapter Constructors	6-235
6-62	OracleDataAdapter Static Method	6-235
6-63	OracleDataAdapter Properties	6-235
6-64	OracleDataAdapter Public Methods	6-237
6-65	OracleDataAdapter Events	6-237

6-66	OracleDataAdapter Static Method	6-241
6-67	OracleDataAdapter Properties	6-241
6-68	OracleDataAdapter Public Methods	6-250
6-69	OracleDataAdapter Events	6-255
6-70	OracleDatabase Constructors	6-261
6-71	OracleDatabase Properties	6-261
6-72	OracleDatabase Public Methods	6-261
6-73	OracleDatabase Properties	6-264
6-74	OracleDatabase Public Methods	6-265
6-75	OracleDataReader Static Method	6-275
6-76	OracleDataReader Properties	6-276
6-77	OracleDataReader Public Methods	6-276
6-78	OracleDataReader Static Method	6-279
6-79	OracleDataReader Properties	6-279
6-80	OracleDataReader Public Methods	6-293
6-81	OracleDataReader SchemaTable	6-337
6-82	OracleDataSourceCollection Methods	6-350
6-83	OracleDataSourceCollection Properties	6-350
6-84	OracleDataSourceCollection Methods	6-351
6-85	OracleDataSourceCollection Properties	6-352
6-86	OracleDataSourceEnumerator Method	6-355
6-87	OracleDataSourceEnumerator Method	6-356
6-88	OracleDataSourceEnumerator Method	6-357
6-89	OracleError Static Method	6-360
6-90	OracleError Properties	6-360
6-91	OracleError Methods	6-360
6-92	OracleError Static Method	6-361
6-93	OracleError Properties	6-361
6-94	OracleError Methods	6-365
6-95	OracleErrorCollection Static Methods	6-368
6-96	OracleErrorCollection Properties	6-368
6-97	OracleErrorCollection Public Methods	6-368
6-98	OracleErrorCollection Static Method	6-369
6-99	OracleErrorCollection Properties	6-369
6-100	OracleErrorCollection Public Methods	6-370
6-101	OracleException Static Method	6-372
6-102	OracleException Properties	6-372

6-103	OracleException Methods	6-373
6-104	OracleException Static Method	6-373
6-105	OracleException Properties	6-374
6-106	OracleException Methods	6-379
6-107	OracleInfoMessageEventArgs Static Method	6-383
6-108	OracleInfoMessageEventArgs Properties	6-384
6-109	OracleInfoMessageEventArgs Public Methods	6-384
6-110	OracleInfoMessageEventArgs Static Method	6-384
6-111	OracleInfoMessageEventArgs Properties	6-385
6-112	OracleInfoMessageEventArgs Public Methods	6-386
6-113	OracleLogicalTransaction Public Read-Only Properties	6-389
6-114	OracleLogicalTransaction Methods	6-390
6-115	OracleLogicalTransaction Public Read-Only Properties	6-390
6-116	Outcome of OracleLogicalTransaction Committed and UserCallCompleted Properties	6-391
6-117	OracleLogicalTransaction Methods	6-394
6-118	OracleOnsServerCollection Methods	6-398
6-119	OracleOnsServerCollection Properties	6-398
6-120	OracleOnsServerCollection Methods	6-399
6-121	OracleOnsServerCollection Properties	6-400
6-122	OracleParameter Constructors	6-404
6-123	OracleParameter Static Methods	6-404
6-124	OracleParameter Properties	6-404
6-125	OracleParameter Public Methods	6-405
6-126	OracleParameter Static Method	6-418
6-127	OracleParameter Properties	6-418
6-128	OracleParameter Public Methods	6-436
6-129	OracleParameterCollection Static Methods	6-442
6-130	OracleParameterCollection Properties	6-442
6-131	OracleParameterCollection Public Methods	6-442
6-132	OracleParameterCollection Static Method	6-443
6-133	OracleParameterCollection Properties	6-444
6-134	OracleParameterCollection Public Methods	6-449
6-135	OraclePermission Constructor	6-471
6-136	OraclePermission Static Methods	6-472
6-137	OraclePermission Public Properties	6-472
6-138	OraclePermission Public Methods	6-472
6-139	OraclePermission Static Methods	6-474

6-140	OraclePermission Public Properties	6-474
6-141	OraclePermission Public Methods	6-475
6-142	OraclePermission Constructor	6-479
6-143	OraclePermissionAttribute Static Methods	6-479
6-144	OraclePermissionAttribute Public Properties	6-480
6-145	OraclePermissionAttribute Public Methods	6-480
6-146	OraclePermissionAttribute Static Methods	6-481
6-147	OraclePermissionAttribute Public Properties	6-482
6-148	OraclePermissionAttribute Public Methods	6-482
6-149	OracleRowUpdatedEventArgs Constructors	6-485
6-150	OracleRowUpdatedEventArgs Static Method	6-485
6-151	OracleRowUpdatedEventArgs Properties	6-485
6-152	OracleRowUpdatedEventArgs Public Methods	6-485
6-153	OracleRowUpdatedEventArgs Static Method	6-487
6-154	OracleRowUpdatedEventArgs Properties	6-487
6-155	OracleRowUpdatedEventArgs Public Methods	6-488
6-156	OracleRowUpdatingEventArgs Constructors	6-491
6-157	OracleRowUpdatingEventArgs Static Methods	6-491
6-158	OracleRowUpdatingEventArgs Properties	6-491
6-159	OracleRowUpdatingEventArgs Public Methods	6-492
6-160	OracleRowUpdatingEventArgs Static Method	6-493
6-161	OracleRowUpdatingEventArgs Properties	6-493
6-162	OracleRowUpdatingEventArgs Public Methods	6-494
6-163	OracleShardingKey Constructors	6-497
6-164	OracleShardingKey Instance Methods	6-497
6-165	OracleShardingKey Instance Methods	6-499
6-166	OracleTransaction Static Method	6-504
6-167	OracleTransaction Properties	6-504
6-168	OracleTransaction Public Methods	6-504
6-169	OracleTransaction Static Method	6-505
6-170	OracleTransaction Properties	6-505
6-171	OracleTransaction Public Methods	6-507
6-172	OracleConnectionType Enumeration Values	6-515
6-173	OracleCollectionType Enumeration Values	6-516
6-174	OracleDBAPrivilege Enumeration Values	6-517
6-175	OracleDBShutdownMode Enumeration Values	6-517
6-176	OracleDBStartupMode Enumeration Values	6-518

6-177	OracleDbType Enumeration Values	6-519
6-178	OracleDRCPPurity Enumeration Values	6-521
6-179	OracleIdentityType Members	6-522
6-180	OracleParameterStatus Members	6-523
7-1	OracleXmlCommandType Members	7-1
7-2	OracleXmlQueryProperties Constructors	7-5
7-3	OracleXmlQueryProperties Properties	7-6
7-4	OracleXmlQueryProperties Public Methods	7-6
7-5	OracleXmlQueryProperties Properties	7-7
7-6	OracleXmlQueryProperties Public Methods	7-11
7-7	OracleXmlSaveProperties Constructor	7-15
7-8	OracleXmlSaveProperties Properties	7-15
7-9	OracleXmlSaveProperties Public Methods	7-15
7-10	OracleXmlSaveProperties Properties	7-16
7-11	OracleXmlSaveProperties Public Methods	7-20
7-12	OracleXmlStream Constructors	7-22
7-13	OracleXmlStream Static Methods	7-22
7-14	OracleXmlStream Instance Properties	7-23
7-15	OracleXmlStream Instance Methods	7-23
7-16	OracleXmlStream Static Methods	7-25
7-17	OracleXmlStream Instance Properties	7-25
7-18	OracleXmlStream Instance Methods	7-30
7-19	OracleXmlType Constructors	7-38
7-20	OracleXmlType Static Methods	7-38
7-21	OracleXmlType Static Field	7-39
7-22	OracleXmlType Instance Properties	7-39
7-23	OracleXmlType Instance Methods	7-39
7-24	OracleXmlType Static Methods	7-44
7-25	OracleXmlType Static Field	7-44
7-26	OracleXmlType Instance Properties	7-45
7-27	OracleXmlType Instance Methods	7-52
8-1	OracleHAEventArgs Properties	8-2
8-2	OracleHAEventArgs Properties	8-3
8-3	OracleHAEventSource Enumeration Member Values	8-9
8-4	OracleHAEventStatus Enumeration Values	8-10
9-1	OracleDependency Constructors	9-2
9-2	OracleDependency Static Fields	9-3

9-3	OracleDependency Static Methods	9-3
9-4	OracleDependency Properties	9-3
9-5	OracleDependency Methods	9-4
9-6	OracleDependency Events	9-4
9-7	OracleDependency Static Fields	9-8
9-8	OracleDependency Static Methods	9-10
9-9	OracleDependency Properties	9-12
9-10	OracleDependency Methods	9-19
9-11	OracleDependency Event	9-21
9-12	OracleNotificationRequest Static Method	9-23
9-13	OracleNotificationRequest Properties	9-23
9-14	OracleNotificationRequest Methods	9-24
9-15	OracleNotificationRequest Static Method	9-24
9-16	OracleNotificationRequest Properties	9-25
9-17	OracleNotificationRequest Methods	9-29
9-18	OracleNotificationEventArgs Static Field	9-31
9-19	OracleNotificationEventArgs Static Method	9-31
9-20	OracleNotificationEventArgs Properties	9-31
9-21	OracleNotificationEventArgs Methods	9-32
9-22	OracleNotificationEventArgs Static Field	9-32
9-23	OracleNotificationEventArgs Static Method	9-33
9-24	OracleNotificationEventArgs Properties	9-33
9-25	DataTable Object Column Data	9-34
9-26	OracleNotificationEventArgs Methods	9-38
9-27	OracleRowidInfo Members	9-39
9-28	OracleNotificationType Members	9-40
9-29	OracleNotificationSource Members	9-41
9-30	OracleNotificationInfo Members	9-42
10-1	OracleGlobalization Static Methods	10-3
10-2	OracleGlobalization Properties	10-3
10-3	OracleGlobalization Public Methods	10-4
10-4	OracleGlobalization Static Methods	10-4
10-5	OracleGlobalization Properties	10-11
10-6	OracleGlobalization Public Methods	10-22
11-1	OracleFailoverEventArgs Static Methods	11-3
11-2	OracleFailoverEventArgs Properties	11-3
11-3	OracleFailoverEventArgs Public Methods	11-4

11-4	OracleFailoverEventArgs Static Methods	11-4
11-5	OracleFailoverEventArgs Properties	11-5
11-6	OracleFailoverEventArgs Public Methods	11-6
11-7	FailoverEvent Enumeration Values	11-8
11-8	FailoverReturnCode Enumeration Values	11-9
11-9	FailoverType Enumeration Values	11-10
12-1	OracleAQAgent Constructors	12-2
12-2	OracleAQAgent Properties	12-2
12-3	OracleAQAgent Properties	12-5
12-4	OracleAQDequeueOptions Constructor	12-7
12-5	OracleAQDequeueOptions Properties	12-7
12-6	OracleAQDequeueOptions Public Methods	12-8
12-7	OracleAQDequeueOptions Properties	12-9
12-8	OracleAQDequeueOptions Public Methods	12-16
12-9	OracleAQEnqueueOptions Constructor	12-17
12-10	OracleAQEnqueueOptions Properties	12-18
12-11	OracleAQEnqueueOptions Public Methods	12-18
12-12	OracleAQEnqueueOptions Properties	12-19
12-13	OracleAQEnqueueOptions Public Methods	12-21
12-14	OracleAQMessage Constructors	12-23
12-15	OracleAQMessage Properties	12-23
12-16	OracleAQMessage Properties	12-25
12-17	OracleAQMessageAvailableEventArgs Constructor	12-36
12-18	OracleAQMessageAvailableEventArgs Properties	12-37
12-19	OracleAQMessageAvailableEventArgs Properties	12-38
12-20	OracleAQQueue Constructors	12-48
12-21	OracleAQQueue Static Methods	12-48
12-22	OracleAQQueue Properties	12-48
12-23	OracleAQQueue Public Methods	12-49
12-24	OracleAQQueue Events	12-49
12-25	OracleAQQueue Static Methods	12-54
12-26	OracleAQQueue Properties	12-57
12-27	Message Types and Payloads	12-60
12-28	Payload Types for Dequeued Messages	12-60
12-29	OracleAQQueue Public Methods	12-64
12-30	OracleAQQueue Events	12-80
12-31	OracleAQDequeueMode Members	12-84

12-32	OracleAQMessageDeliveryMode Members	12-86
12-33	OracleAQMessageState Members	12-87
12-34	OracleAQMessageType Members	12-88
12-35	OracleAQNavigationMode Members	12-88
12-36	OracleAQNotificationGroupingType Members	12-90
12-37	OracleAQNotificationType Members	12-90
12-38	OracleAQVisibilityMode Members	12-91
13-1	OracleBFile Constructors	13-4
13-2	OracleBFile Static Fields	13-4
13-3	OracleBFile Static Methods	13-4
13-4	OracleBFile Instance Properties	13-4
13-5	OracleBFile Instance Methods	13-5
13-6	OracleBFile Static Fields	13-8
13-7	OracleBFile Static Methods	13-10
13-8	OracleBFile Instance Properties	13-10
13-9	OracleBFile Instance Methods	13-19
13-10	OracleBlob Constructors	13-43
13-11	OracleBlob Static Fields	13-43
13-12	OracleBlob Static Methods	13-43
13-13	OracleBlob Instance Properties	13-44
13-14	OracleBlob Instance Methods	13-44
13-15	OracleBlob Static Fields	13-48
13-16	OracleBlob Static Methods	13-49
13-17	OracleBlob Instance Properties	13-49
13-18	OracleBlob Instance Methods	13-57
13-19	OracleClob Constructors	13-82
13-20	OracleClob Static Fields	13-82
13-21	OracleClob Static Methods	13-83
13-22	OracleClob Instance Properties	13-83
13-23	OracleClob Instance Methods	13-84
13-24	OracleClob Static Fields	13-87
13-25	OracleClob Static Methods	13-88
13-26	OracleClob Instance Properties	13-89
13-27	OracleClob Instance Methods	13-97
13-28	OracleRefCursor Static Methods	13-127
13-29	OracleRefCursor Static Field	13-128
13-30	OracleRefCursor Properties	13-128

13-31	OracleRefCursor Instance Methods	13-128
13-32	OracleRefCursor Static Methods	13-129
13-33	OracleRefCursor Static Field	13-129
13-34	OracleRefCursor Properties	13-130
13-35	OracleRefCursor Instance Methods	13-134
14-1	OracleBinary Constructors	14-3
14-2	OracleBinary Static Fields	14-3
14-3	OracleBinary Static Methods	14-4
14-4	OracleBinary Static Operators	14-4
14-5	OracleBinary Static Type Conversion Operators	14-5
14-6	OracleBinary Properties	14-5
14-7	OracleBinary Instance Methods	14-5
14-8	OracleBinary Static Fields	14-6
14-9	OracleBinary Static Methods	14-7
14-10	OracleBinary Static Operators	14-14
14-11	OracleBinary Static Type Conversion Operators	14-20
14-12	OracleBinary Properties	14-22
14-13	OracleBinary Instance Methods	14-25
14-14	OracleBoolean Constructors	14-30
14-15	OracleBoolean Static Fields	14-30
14-16	OracleBoolean Static Methods	14-31
14-17	OracleBoolean Static Operators	14-31
14-18	OracleBoolean Static Type Conversions	14-32
14-19	OracleBoolean Properties	14-32
14-20	OracleBoolean Instance Methods	14-33
14-21	OracleBoolean Static Fields	14-35
14-22	OracleBoolean Static Methods	14-37
14-23	OracleBoolean Static Operators	14-46
14-24	OracleBoolean Static Type Conversions	14-56
14-25	OracleBoolean Properties	14-63
14-26	OracleBoolean Instance Methods	14-66
14-27	OracleDate Constructors	14-71
14-28	OracleDate Static Fields	14-72
14-29	OracleDate Static Methods	14-72
14-30	OracleDate Static Operators	14-72
14-31	OracleDate Static Type Conversions	14-73
14-32	OracleDate Properties	14-73

14-33	OracleDate Methods	14-74
14-34	OracleDate Static Fields	14-79
14-35	OracleDate Static Methods	14-81
14-36	OracleDate Static Operators	14-88
14-37	OracleDate Static Type Conversions	14-93
14-38	OracleDate Properties	14-97
14-39	OracleDate Methods	14-103
14-40	OracleDecimal Constructors	14-110
14-41	OracleDecimal Static Fields	14-110
14-42	OracleDecimal Static (Comparison) Methods	14-110
14-43	OracleDecimal Static (Manipulation) Methods	14-111
14-44	OracleDecimal Static (Logarithmic) Methods	14-112
14-45	OracleDecimal Static (Trigonometric) Methods	14-112
14-46	OracleDecimal Static (Comparison) Operators	14-113
14-47	OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)	14-114
14-48	OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)	14-114
14-49	OracleDecimal Properties	14-114
14-50	OracleDecimal Instance Methods	14-115
14-51	OracleDecimal Static Fields	14-122
14-52	OracleDecimal Static (Comparison) Methods	14-127
14-53	OracleDecimal Static (Manipulation) Methods	14-132
14-54	OracleDecimal Static (Logarithmic) Methods	14-148
14-55	OracleDecimal Static (Trigonometric) Methods	14-154
14-56	OracleDecimal Static (Comparison) Operators	14-162
14-57	OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)	14-171
14-58	OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)	14-176
14-59	OracleDecimal Properties	14-181
14-60	OracleDecimal Instance Methods	14-186
14-61	OracleIntervalDS Constructors	14-195
14-62	OracleIntervalDS Static Fields	14-195
14-63	OracleIntervalDS Static Methods	14-196
14-64	OracleIntervalDS Static Operators	14-196
14-65	OracleIntervalDS Type Conversions	14-197
14-66	OracleIntervalDS Properties	14-197
14-67	OracleIntervalDS Methods	14-198
14-68	OracleIntervalDS Static Fields	14-204
14-69	OracleIntervalDS Static Methods	14-206

14-70	OracleIntervalDS Static Operators	14-214
14-71	OracleIntervalDS Type Conversions	14-223
14-72	OracleIntervalDS Properties	14-226
14-73	OracleIntervalDS Methods	14-231
14-74	OracleIntervalYM Constructors	14-236
14-75	OracleIntervalYM Static Fields	14-237
14-76	OracleIntervalYM Static Methods	14-237
14-77	OracleIntervalYM Static Operators	14-237
14-78	OracleIntervalYM Type Conversions	14-238
14-79	OracleIntervalYM Properties	14-239
14-80	OracleIntervalYM Methods	14-239
14-81	OracleIntervalYM Static Fields	14-244
14-82	OracleIntervalYM Static Methods	14-246
14-83	OracleIntervalYM Static Operators	14-253
14-84	OracleIntervalYM Type Conversions	14-262
14-85	OracleIntervalYM Properties	14-265
14-86	OracleIntervalYM Methods	14-269
14-87	OracleString Constructors	14-273
14-88	OracleString Static Fields	14-274
14-89	OracleString Static Methods	14-274
14-90	OracleString Static Operators	14-274
14-91	OracleString Type Conversions	14-275
14-92	OracleString Properties	14-275
14-93	OracleString Methods	14-275
14-94	OracleString Static Fields	14-281
14-95	OracleString Static Methods	14-282
14-96	OracleString Static Operators	14-288
14-97	OracleString Type Conversions	14-294
14-98	OracleString Properties	14-296
14-99	OracleString Methods	14-299
14-100	OracleTimeStamp Constructors	14-306
14-101	OracleTimeStamp Static Fields	14-307
14-102	OracleTimeStamp Static Methods	14-307
14-103	OracleTimeStamp Static Operators	14-308
14-104	OracleTimeStamp Static Type Conversions	14-308
14-105	OracleTimeStamp Properties	14-308
14-106	OracleTimeStamp Methods	14-309

14-107	OracleTimeStamp Static Fields	14-318
14-108	OracleTimeStamp Static Methods	14-319
14-109	OracleTimeStamp Static Operators	14-328
14-110	OracleTimeStamp Static Type Conversions	14-339
14-111	OracleTimeStamp Properties	14-345
14-112	OracleTimeStamp Methods	14-351
14-113	OracleTimeStampLTZConstructors	14-366
14-114	OracleTimeStampLTZ Static Fields	14-366
14-115	OracleTimeStampLTZ Static Methods	14-367
14-116	OracleTimeStampLTZ Static Operators	14-367
14-117	OracleTimeStampLTZ Static Type Conversions	14-368
14-118	OracleTimeStampLTZ Properties	14-368
14-119	OracleTimeStampLTZ Methods	14-369
14-120	OracleTimeStampLTZ Static Fields	14-378
14-121	OracleTimeStampLTZ Static Methods	14-380
14-122	OracleTimeStampLTZ Static Operators	14-389
14-123	OracleTimeStampLTZ Static Type Conversions	14-400
14-124	OracleTimeStampLTZ Properties	14-406
14-125	OracleTimeStampLTZ Methods	14-413
14-126	OracleTimeStampTZ Constructors	14-429
14-127	OracleTimeStampTZ Static Fields	14-429
14-128	OracleTimeStampTZ Static Methods	14-429
14-129	OracleTimeStampTZ Static Operators	14-430
14-130	OracleTimeStampTZ Static Type Conversions	14-431
14-131	OracleTimeStampTZ Properties	14-431
14-132	OracleTimeStampTZ Methods	14-432
14-133	OracleTimeStampTZ Static Fields	14-447
14-134	OracleTimeStampTZ Static Methods	14-449
14-135	OracleTimeStampTZ Static Operators	14-457
14-136	OracleTimeStampTZ Static Type Conversions	14-468
14-137	OracleTimeStampTZ Properties	14-475
14-138	OracleTimeStampTZ Methods	14-482
14-139	INullable Interface Properties	14-498
14-140	INullable Interface Properties	14-498
15-1	OracleTypeException Constructor	15-2
15-2	OracleTypeException Static Methods	15-2
15-3	OracleTypeException Properties	15-2

15-4	OracleTypeException Methods	15-3
15-5	OracleTypeException Static Methods	15-5
15-6	OracleTypeException Properties	15-5
15-7	OracleTypeException Methods	15-7
15-8	OracleNullValueException Constructors	15-10
15-9	OracleNullValueException Static Methods	15-10
15-10	OracleNullValueException Properties	15-10
15-11	OracleNullValueException Methods	15-10
15-12	OracleNullValueException Static Methods	15-12
15-13	OracleNullValueException Properties	15-13
15-14	OracleNullValueException Methods	15-13
15-15	OracleTruncateException Constructors	15-15
15-16	OracleTruncateException Static Methods	15-15
15-17	OracleTruncateException Properties	15-15
15-18	OracleTruncateException Methods	15-16
15-19	OracleTruncateException Static Methods	15-18
15-20	OracleTruncateException Properties	15-18
15-21	OracleTruncateException Methods	15-19
16-1	OracleCustomTypeMappingAttribute Constructors	16-3
16-2	OracleCustomTypeMappingAttribute Static Methods	16-3
16-3	OracleCustomTypeMappingAttribute Properties	16-3
16-4	OracleCustomTypeMappingAttribute Methods	16-3
16-5	OracleCustomTypeMappingAttribute Static Methods	16-5
16-6	OracleCustomTypeMappingAttribute Properties	16-6
16-7	OracleCustomTypeMappingAttribute Methods	16-7
16-8	OracleObjectMappingAttribute Constructors	16-8
16-9	OracleObjectMappingAttribute Static Methods	16-8
16-10	OracleObjectMappingAttribute Properties	16-9
16-11	OracleObjectMappingAttribute Methods	16-9
16-12	OracleObjectMappingAttribute Static Method	16-11
16-13	OracleObjectMappingAttribute Properties	16-12
16-14	OracleObjectMappingAttribute Methods	16-13
16-15	OracleArrayMappingAttribute Constructors	16-15
16-16	OracleArrayMappingAttribute Static Methods	16-15
16-17	OracleArrayMappingAttribute Properties	16-16
16-18	OracleArrayMappingAttribute Methods	16-16
16-19	OracleArrayMappingAttribute Static Methods	16-17

16-20	OracleArrayMappingAttribute Properties	16-18
16-21	OracleArrayMappingAttribute Methods	16-18
16-22	IOracleCustomType Interface Methods	16-20
16-23	IOracleCustomType Interface Methods	16-20
16-24	IOracleCustomTypeFactory Interface Methods	16-23
16-25	IOracleCustomTypeFactory Interface Methods	16-23
16-26	IOracleArrayTypeFactory Interface Methods	16-25
16-27	IOracleArrayTypeFactory Interface Methods	16-26
16-28	OracleUdt Static Methods	16-28
16-29	OracleUdt Static Methods	16-29
16-30	OracleRef Constructors	16-44
16-31	OracleRef Static Fields	16-44
16-32	OracleRef Static Methods	16-45
16-33	OracleRef Instance Properties	16-45
16-34	OracleRef Instance Methods	16-45
16-35	OracleRef Static Fields	16-48
16-36	OracleRef Static Methods	16-49
16-37	OracleRef Instance Properties	16-49
16-38	OracleRef Instance Methods	16-54
16-39	OracleUdtFetchOption Enumeration Values	16-66
16-40	OracleUdtStatus Enumeration Values	16-67
17-1	OracleBulkCopy Constructors	17-2
17-2	OracleBulkCopy Properties	17-3
17-3	OracleBulkCopy Public Methods	17-3
17-4	OracleBulkCopy Events	17-3
17-5	OracleBulkCopy Properties	17-8
17-6	OracleBulkCopy Public Methods	17-14
17-7	OracleBulkCopy Events	17-21
17-8	OracleBulkCopyColumnMapping Constructors	17-23
17-9	OracleBulkCopyColumnMapping Method	17-23
17-10	OracleBulkCopyColumnMapping Properties	17-24
17-11	OracleBulkCopyColumnMapping Method	17-27
17-12	OracleBulkCopyColumnMapping Properties	17-29
17-13	OracleBulkCopyColumnMappingCollection Properties	17-33
17-14	OracleBulkCopyColumnMappingCollection Public Methods	17-33
17-15	OracleBulkCopyColumnMappingCollection Properties	17-34
17-16	OracleBulkCopyColumnMappingCollection Public Methods	17-35

17-17	OracleBulkCopyOptions Enumeration Members	17-46
17-18	OracleRowsCopiedEventArgs Constructors	17-49
17-19	OracleRowsCopiedEventArgs Properties	17-49
17-20	OracleRowsCopiedEventArgs Properties	17-51
A-1	MetaDataCollections	A-2
A-2	DataSource Information	A-2
A-3	Data Types	A-3
A-4	Restrictions	A-5
A-5	ReservedWords	A-6
A-6	Tables	A-6
A-7	Columns	A-7
A-8	Views	A-7
A-9	XMLSchema	A-8
A-10	Users	A-9
A-11	Synonyms	A-9
A-12	Sequences	A-9
A-13	Functions	A-10
A-14	Procedures	A-11
A-15	ProcedureParameters	A-11
A-16	Arguments	A-13
A-17	Packages	A-13
A-18	PackageBodies	A-14
A-19	JavaClasses	A-15
A-20	Indexes	A-15
A-21	IndexColumns	A-18
A-22	PrimaryKeys	A-19
A-23	ForeignKeys	A-20
A-24	ForeignKeyColumns	A-21
A-25	UniqueKeys	A-21
B-1	Mapping of Aggregate Canonical Functions and Oracle Functions	B-1
B-2	Mapping of Math Canonical Functions and Oracle Functions	B-1
B-3	Mapping of String Canonical Functions and Oracle Functions	B-2
B-4	Mapping of Date And Time Canonical Functions and Oracle Functions	B-2
B-5	Mapping of Bitwise Canonical Functions and Oracle Functions	B-4
B-6	Mapping of Other Canonical Functions and Oracle Functions	B-4

Preface

This document is your primary source of introductory, installation, postinstallation configuration, and usage information for Oracle Data Provider for .NET.

Oracle Data Provider for .NET is an implementation of the Microsoft ADO.NET interface.

This Preface contains these topics:

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Passwords in Code Examples](#)
- [Conventions](#)

Audience

Oracle Data Provider for .NET Developer's Guide is intended for programmers who are developing applications to access an Oracle database using Oracle Data Provider for .NET. This documentation is also valuable to systems analysts, project managers, and others interested in the development of database applications.

To use this document, you must be familiar with Microsoft .NET Framework classes and ADO.NET and have a working knowledge of application programming using Microsoft C#, Visual Basic .NET, or another .NET language.

Although the examples in the documentation and the samples in the sample directory are written in C#, developers can use these examples as models for writing code in other .NET languages.

Users should also be familiar with the use of Structured Query Language (SQL) to access information in relational database systems.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information, see these Oracle resources:

- *Oracle Database Installation Guide for Microsoft Windows*
- *Oracle Database Release Notes for Microsoft Windows*
- *Oracle Database Platform Guide for Microsoft Windows*
- *Oracle Database Administrator's Guide*
- *Oracle Database Development Guide*
- *Oracle Database SecureFiles and Large Objects Developer's Guide*
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database New Features Guide*
- *Oracle Database Concepts*
- *Oracle Database Reference*
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows*
- *Oracle Database Object-Relational Developer's Guide*
- *Oracle Database SQL Language Reference*
- *Oracle Database Net Services Administrator's Guide*
- *Oracle Database Net Services Reference*
- *Oracle Call Interface Programmer's Guide*
- *Oracle Services for Microsoft Transaction Server Developer's Guide for Microsoft Windows*
- *Oracle Database Globalization Support Guide*
- *Oracle XML DB Developer's Guide*
- *Oracle XML Developer's Kit Programmer's Guide*
- *Oracle Database Security Guide*
- *Oracle Spatial Developer's Guide*
- *Oracle Data Guard Concepts and Administration*

Many of the examples in this book use the sample schemas, which are installed by default when you select the Basic Installation option with an Oracle Database installation. Refer to *Oracle Database Sample Schemas* for information on how these schemas were created and how you can use them yourself.

To download free release notes, installation documentation, white papers, or other collateral, please visit the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://www.oracle.com/technetwork/index.html>

If you already have a username and password for OTN, then you can go directly to the documentation section of the OTN Web site at

<http://docs.oracle.com/database/122/index.htm>

For additional information, see:

<https://msdn.microsoft.com/en-us/default.aspx>

and

<http://msdn.microsoft.com/library>

Passwords in Code Examples

For simplicity in demonstrating this product, code examples do not perform the password management techniques that a deployed system normally uses. In a production environment, follow the Oracle Database password management guidelines, and disable any sample accounts. See *Oracle Database Security Guide* for password management guidelines and other security recommendations.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Changes in This Release for Oracle Data Provider for .NET

This preface contains:

- [Changes in Oracle Data Provider for .NET Release 19c \(19.3\)](#)
- [Changes in Oracle Data Provider for .NET in ODAC Release 18c \(18.3\)](#)
- [Changes in Oracle Data Provider for .NET Release 18c \(18.3\)](#)
- [Changes in Oracle Data Provider for .NET in ODAC 12.2c Release 1](#)
- [Changes in Oracle Data Provider for .NET Release 12.2.0.1](#)
- [Changes in Oracle Data Provider for .NET in ODAC 12c Release 4](#)
- [Changes in Oracle Data Provider for .NET in ODAC 12c Release 3](#)
- [Changes in Oracle Data Provider for .NET Release 12.1.0.2](#)
- [Changes in Oracle Data Provider for .NET in ODAC 12c Release 2](#)
- [Changes in Oracle Data Provider for .NET in ODAC 12c Release 1](#)
- [Changes in Oracle Data Provider for .NET Release 12.1](#)

Changes in Oracle Data Provider for .NET Release 19c (19.3)

The following are the changes in Oracle Data Provider for .NET for Release 19c (19.3).

New Features

The following features are new in this release:

- ODP.NET Core -- Lightweight Directory Access Protocol (LDAP)

ODP.NET Core can use connect identifiers mapped to connect descriptors in an LDAP-compliant directory server, such as Oracle Internet Directory and Microsoft Active Directory. The provider supports the same LDAP features and settings as managed ODP.NET.

ODP.NET Core LDAP support is available on Windows operating systems only. It requires the `System.DirectoryServices` namespace.

 **See Also:**

[OracleConfiguration Directories Properties](#)

- ODP.NET Core -- Performance Counters

ODP.NET Core can publish key runtime connection counters to Windows Performance Monitor or a file. The provider supports the same counters, setup process, and settings as managed and unmanaged ODP.NET.

ODP.NET Core performance counters are available on Windows operating systems only. They require `System.Diagnostics` namespace in using performance counters programmatically.

 **See Also:**

[Connection Performance Counters](#)

- Easy Connect Plus

Oracle Easy Connect Plus provides a simple way to configure TCP/IP connections to the Oracle Database without having to use parameter files, such as `tnsnames.ora`, nor environment variables. Easy Connect Plus includes support for:

- TCP/IP with SSL/TLS
- Any SQL*Net description level parameter can be used
- Multiple hosts and ports
- A straightforward name-value pair format

Easy Connect Plus supports more configurations and a wider breadth of ODP.NET applications than traditional Easy Connect, including clustered or cloud databases.

 **See Also:**

[Easy Connect and Easy Connect Plus Naming Methods](#)

- HTTPS Proxy for Cloud Connections

ODP.NET supports HTTPS proxy configuration. The feature enables tunneling secure connections over forward HTTP proxy using the HTTP CONNECT method.

HTTPS proxy improves public cloud database service access as it eliminates requiring the client side firewall to open an outbound port.

- More Secure Oracle Notification Service Connections

ODP.NET now enables Oracle Notification Service (ONS) communications to occur over TCP/IP with SSL/TLS (TCPS), which is more secure than just TCP/IP. As TCPS requires using a wallet for storing keys and certificates, ODP.NET can use one wallet for both ONS and ODP.NET connections or have separate wallets for each.

TCPS provides more secure ONS communication, gives administrators flexibility in how to configure their wallets, and enables cloud database connections.

Changes in Oracle Data Provider for .NET in ODAC Release 18c (18.3)

The following are the changes in Oracle Data Provider for .NET for ODAC Release 18c (18.3).

New Features

The following features are new in this release:

- .NET Core 2.1 Certification
ODP.NET Core is certified for .NET Core 2.1 and higher.
See Also [Installing Oracle Data Provider for .NET Core](#)

Changes in Oracle Data Provider for .NET Release 18c (18.3)

The following are the changes in Oracle Data Provider for .NET for Release 18c (18.3).

New Features

The following features are new in this release:

- .NET Framework 4.7.x Certification
ODP.NET, Managed and Unmanaged Drivers are certified for all versions of .NET Framework 4.7.x, including 4.7.1 and 4.7.2.
- Secure Passwords with `OracleCredential`
ODP.NET `OracleCredential` class allows application developers to store user names and passwords outside of the connection string without exposure in a memory dump.
`OracleCredential` can be used with or without connection pooling.
This feature is available in the terminal releases of ODP.NET 11.2, 12.1, and 12.2 and with the first release of ODP.NET 18c.
See Also [Connection Pooling with OracleCredential](#)

Desupported Features

Some features previously described in this document are desupported in Oracle Database 18c (18.3). See *Oracle Database Upgrade Guide* for a complete list of desupported features.

The following feature is no longer supported by Oracle:

- Oracle.ManagedDataAccessDTC.dll

Changes in Oracle Data Provider for .NET in ODAC 12.2c Release 1

The following are the changes in Oracle Data Provider for .NET for ODAC 12.2c Release 1.

New Features

The following features are new in this release:

- .NET Framework 4.7 Certification
ODP.NET, Managed and Unmanaged Drivers are certified for .NET Framework 4.7.
- Entity Framework 6.2 Certification
ODP.NET, Managed and Unmanaged Drivers are certified for Entity Framework 6.2.
- Database Resident Connection Pooling
Database Resident Connection Pooling (DRCP) optimizes resource usage by pooling connections at the database server level. With DRCP, server connections can be shared across application that are executed on different client machines, especially in the case when connections are not always in use. DRCP can be used in conjunction with either managed or unmanaged ODP.NET client side pooling to improve scalability and lower resource usage at the database server level.
See also [Database Resident Connection Pooling](#) for more information.
- Multitenant and Pluggable Databases Connection Pooling
Oracle Multitenant is a database architecture that enables customers to easily consolidate multiple pluggable databases without changing their application. This architecture delivers all the benefits of managing many databases as one, yet retains the isolation and resource prioritization of separate databases.
Managed and unmanaged ODP.NET now support hosting connections to multiple pluggable databases from the same connection pool. This feature enhances application performance and scalability, plus makes using multiple pluggable databases from the same application easier.
See also [Oracle Multitenant and Pluggable Databases](#) for more information.
- Edition-Based Redefinition Connection Pooling
Edition-based redefinition enables applications to upgrade the database component while it is in use, thereby minimizing or eliminating down time. Managed and unmanaged ODP.NET now support using the same connection pool to connect to multiple Editions. This feature enhances performance and scalability while using different Editions from the same application, and also makes using multiple Editions from the same application easier.
See also [Edition-Based Redefinition](#) for more information.
- Connection Configuration Upon Open

Managed and unmanaged ODP.NET introduce the `ConnectionOpen` event handler, which allows developers to provide setup logic and change settings before ODP.NET connections are dispensed from the `Open()` method invocation. This feature is similar in concept to a logon trigger, but is most optimal for client side initialization settings. It works with both pooled and non-pooled connections. The event handler provides a centralized, standardized location for connection initialization.

See also [ConnectionOpen](#) for more information.

Deprecated Features

The following feature is deprecated in ODAC 12.2c Release 1:

- `Oracle.ManagedDataAccessDTC.dll`

Oracle provided a native managed distributed transaction support for ODP.NET, Managed Driver using `Oracle.ManagedDataAccessDTC.dll`. In .NET Framework 4.5.2, Microsoft introduced its own native managed distributed transaction implementation, which managed ODP.NET could use. The new .NET Framework made the `Oracle.ManagedDataAccessDTC.dll` unnecessary. Moreover, Microsoft has desupported all .NET Framework 4 versions earlier than 4.5.2. In accordance with Microsoft policy, Oracle is deprecating the `Oracle.ManagedDataAccessDTC.dll` file.

The deprecation extends to the `UseManagedDTC` .NET configuration file parameter, and `Oracle.ManagedDataAccessDTC.dll`.

See Also:

- [Microsoft Distributed Transaction Coordinator Integration](#)
- *Oracle Database Upgrade Guide* for a complete list of deprecated features.

Changes in Oracle Data Provider for .NET Release 12.2.0.1

The following are the changes in Oracle Data Provider for .NET for Release 12.2.0.1.

New Features

The following features are new in this release:

- .NET Framework 4.6.2 Certification

ODP.NET, Managed and Unmanaged Drivers are certified for .NET Framework 4.6.2.

See also [System Requirements](#) for more information.

- .NET Cloud Development and Deployment

ODP.NET, Managed and Unmanaged Drivers can be deployed easily to Oracle Cloud, private clouds, and third-party cloud environments through Web Deploy. All ODP.NET specific settings no longer require any operating system level

configuration. These settings can be made in the .NET configuration files. Managed and Unmanaged ODP.NET Drivers now share a unified configuration file format.

- Application Continuity

Application Continuity recovers incomplete requests from an ODP.NET, Unmanaged Driver perspective and masks many system failures, communication failures, hardware failures, and storage outages from the user.

See also "[Application Continuity](#)" for more information.

- Sharding and ODP.NET Routing

Starting from Release 12.2.0.1, ODP.NET, Unmanaged Driver and Oracle Database support sharding. Oracle Sharding provides the ability to horizontally partition the data across multiple independent Oracle databases (shards). Based on a key specified in the connect string, ODP.NET can route the database requests to a particular shard.

Oracle Sharding is a shared-nothing architecture that allows near-linear scaling of the database across low-cost commodity database servers located in one or more local or global data centers. Other key benefits include global data distribution (store particular data close to consumers) and fault containment (failure of one shard does not affect the availability of other shards). Global Data Services manages the location of data among the shards and allows ODP.NET client requests to be routed to the appropriate shard in this distributed database system.

See also "[Database Sharding](#)" for more information.

- Longer Schema Identifiers

Oracle Data Provider for .NET now supports schema object identifier names, such as tables, columns, views, stored procedures, and functions, up to 128 characters in length. This feature is available in both ODP.NET, Managed and Unmanaged Drivers.

- ODP.NET, Managed Driver – Data Integrity

ODP.NET, Managed Driver supports cryptographic hash functions to better ensure data integrity between the database server and the client. The algorithms supported include MD5, SHA-1, and SHA-2 (SHA-256, SHA-384, and SHA-512).

See also "[settings section](#)" and "[Network Data Encryption and Integrity](#)" for more information.

- ODP.NET, Managed Driver -- Transport Layer Security (TLS)

ODP.NET, Managed Driver has added support for TLS 1.1 and 1.2 in addition to existing support for TLS 1.0 and SSL 3.0.

- ODP.NET, Managed Driver -- Distinguished Name for SSL/TLS

ODP.NET, Managed Driver connections using SSL/TLS can ensure that the distinguished name (DN) is correct for the database server that it is trying to connect to.

- ODP.NET, Managed Driver - Boolean Data Type

ODP.NET, Managed Driver now supports the `OracleBoolean` data type when using the database's PL/SQL `Boolean` data type. The managed driver must be connected to Oracle Database 12c Release 2 (12.2) or higher. Booleans store `TRUE` or `FALSE` values.

The ODP.NET `OracleBoolean` data type eases parameter binding and data type mapping setup with Boolean values.

See also "[OracleBoolean Structure](#)" for more information.

Desupported Features

Some features previously described in this document are desupported in Oracle Database 12c Release 2 (12.2). See *Oracle Database Upgrade Guide* for a complete list of desupported features in this release.

The following features are no longer supported by Oracle:

- `OracleLogicalTransactionStatus` class
- `OracleConnection.GetLogicalTransactionStatus` method
- `OracleConnection.LogicalTransactionId` property
- `OracleConnection.OracleLogicalTransaction` property
- `OracleLogicalTransaction.DataSource` property
- `OracleLogicalTransaction.GetOutcome()` method
- `OracleLogicalTransaction.GetOutcome(string, string, string)` method
- `OracleLogicalTransaction.UserId` property

Changes in Oracle Data Provider for .NET in ODAC 12c Release 4

The following are the changes in Oracle Data Provider for .NET for ODAC 12c Release 4.

New Features

The following features are new in this release:

- .NET Framework 4.6 and 4.6.1 Certification
ODP.NET, Managed and Unmanaged Drivers are certified for .NET Framework 4.6 and 4.6.1.
See also "[System Requirements](#)" for more information.
- ODP.NET, Managed Driver - Windows Installer
ODP.NET, Managed Driver is now available as part of an ODAC Microsoft Windows Installer package.
- ODP.NET, Managed Driver - Network Data Encryption
ODP.NET, Managed Driver supports database security network data encryption using Advanced Encryption Standard (AES), RC4, or Triple-DES to enable more secure database communication over intranet and cloud access.
See also "[settings section](#)" and "[Network Data Encryption and Integrity](#)" for more information.
- ODP.NET, Managed Driver - Secure External Password Store

ODP.NET, Managed Driver supports connection establishment by retrieving password credentials from a client-side Oracle wallet.

See also "[Using Secure External Password Store](#)" for more information.

- ODP.NET, Managed Driver - Microsoft Local Security Authority (MSLSA)

ODP.NET, Managed Driver now supports the Kerberos credential cache type, MSLSA. MSLSA is used to access the Microsoft Kerberos Logon Session credentials cache.

See also "[Using Kerberos](#)" for more information.

- ODP.NET, Managed Driver - SSL/TLS Connections Use a Single Port

An ODP.NET, Managed Driver SSL/TLS connection will now continue on the original connection to the database listener instead of the previous SSL/TLS client redirection to a database server created new listening endpoint on a dynamic (ephemeral) port. Hence, firewalls will only need to allow access to the TNS listener's port. For example, 1521.

See also "[Using Transport Layer Security and Secure Sockets Layer](#)" for more information.

- Service Relocation Connection Timeout

Whenever a database service becomes unavailable, an application can encounter numerous connectivity errors. To avoid connection attempts to an unavailable service, ODP.NET, Managed and Unmanaged Drivers block any connection attempts until the service is up or until the configured time limit expires from the time when the service DOWN event was received. This feature is useful for planned outages and service relocations. It works with Oracle RAC and Oracle Data Guard.

See also "[ServiceRelocationConnectionTimeout](#)" for more information.

- ODP.NET, Unmanaged Driver - Transaction Guard

Transaction Guard allows ODP.NET applications to use at-most-once execution in case of planned and unplanned outages and repeated submissions. This feature's architecture has been modified to simplify the application code needed for transaction recovery. Developers will find it easier to utilize Transaction Guard in their applications.

See also "[Using Transaction Guard to Prevent Logical Corruption](#)" for more information.

- ODP.NET, Managed Driver - Transaction Guard

ODP.NET, Managed Driver now supports Transaction Guard. Its API and architecture are the same as ODP.NET, Unmanaged Driver's in ODAC 12c Release 4 to provide improved developer productivity.

See also "[Using Transaction Guard to Prevent Logical Corruption](#)" for more information.

- ODP.NET, Unmanaged Driver - Managed Code for Distributed Transactions

In .NET Framework 4.5.2 or higher, ODP.NET, Unmanaged Driver includes managed code for distributed transaction enlistment and commitment services using Microsoft Distributed Transaction Coordinator. Previously, applications had to use Oracle Services for Microsoft Transaction Server for these services. This new feature simplifies setup and deployment of ODP.NET, Unmanaged Driver applications that use distributed transactions.

See also "[Distributed Transactions](#)" for more information.

- ODP.NET, Unmanaged Driver - SQL Translation Framework

Introduced in Oracle Database 12c, SQL Translation Framework helps migrate .NET client applications that use SQL statements with vendor-proprietary syntax to semantically-equivalent Oracle syntax.

The framework automatically translates non-Oracle SQL to Oracle SQL, thereby enabling existing client-side application code to run largely unchanged against an Oracle Database. This reduces the cost of migration to Oracle Database significantly.

See also "[Database Application Migration: SQL Translation Framework](#)" and "[SQL Translation Framework Configuration](#)" for more information.

- Tracing Enhancements

ODP.NET improves and unifies tracing features between managed and unmanaged ODP.NET. Key features include traces now output to a Windows temporary files directory and both providers use the same tracing parameters.

See also "[Debug Tracing](#)" for more information.

Changes in Oracle Data Provider for .NET in ODAC 12c Release 3

The following are the changes in Oracle Data Provider for .NET for ODAC 12c Release 3.

New Features

The following features are new in this release:

- Entity Framework Code First and Code First Migrations

In Entity Framework 6 and higher, managed and unmanaged ODP.NET support Code First and Code First Migrations.

See also "[ADO.NET Entity Framework and LINQ to Entities](#)" for more information.

- Entity Framework 6

ODP.NET, Managed and Unmanaged Drivers are certified and supported natively for Entity Framework version 6.

See also "[Entity Framework Requirements](#)" for more information.

- NuGet

ODP.NET, Managed Driver is available in a NuGet package. This feature simplifies distributing customized ODP.NET, Managed Driver to developers.

The Entity Framework assembly for Code First and Entity Framework 6 is available as a separate NuGet package.

NuGet is the package manager for Microsoft .NET. NuGet can install software by copying library files to a .NET solution and automatically updating the project accordingly by adding references and updating config files.

See also "[Installing Oracle Data Provider for .NET, Managed Driver](#)" for more information.

- ODP.NET, Managed Driver - XML DB APIs
ODP.NET, Managed Driver now supports all ODP.NET XML classes supported by ODP.NET, Unmanaged Driver.
- Distributed Transactions without `Oracle.ManagedDataAccessDTC.dll`
The `Oracle.ManagedDataAccessDTC.dll` assembly is no longer required for distributed transaction applications running in .NET Framework 4.5.2 or higher and ODP.NET, Managed Driver. Upon ODP.NET installation, `Oracle.ManagedDataAccessDTC.dll` is no longer placed into the Global Assembly Cache (GAC). For applications that use .NET Framework 4.5.1 or earlier, `Oracle.ManagedDataAccessDTC.dll` needs to either be placed in the application directory or in the GAC.
- ODP.NET, Managed Driver - Kerberos
Kerberos is a network authentication service for security in distributed environments. ODP.NET, Managed Driver can now use Kerberos for single sign-on and centralized user authentication.
See also "[Using Kerberos](#)" for more information.
- ODP.NET, Managed Driver - Implicit Ref Cursor
ODP.NET, Managed Driver introduces support for the new Oracle Database 12c Implicit Ref Cursor. Configuration occurs using the `<implicitrefcursor>` .NET configuration section. When using database implicit ref cursors, the `bindInfo` element should be specified with a mode of "Implicit":

```
<bindinfo mode="Implicit" />
```


See also "[implicitRefCursor section](#)" for more information.
- Configuration Files: Unified Managed and Unmanaged ODP.NET Format
ODP.NET, Unmanaged Driver now has the option of using the same configuration file format as ODP.NET, Managed Driver. The format simplifies configuration by using a single unified scheme. To utilize this format, the existing unmanaged ODP.NET configuration section should be renamed from `<oracle.dataaccess.client>` to `<oracle.unmanageddataaccess.client>`. The existing unmanaged ODP.NET elements and values are supported within the new section using the same format as with ODP.NET, Managed Driver.
The traditional ODP.NET, Unmanaged Driver configuration file format will continue to be supported.
See Also "[Configuration File Support](#)" for more information.

Changes in Oracle Data Provider for .NET Release 12.1.0.2

The following are the changes in Oracle Data Provider for .NET for Release 12.1.0.2.

New Features

The following features are new in this release:

- .NET Framework 4.5.2 Certification
ODP.NET, Managed and Unmanaged Drivers are certified for .NET Framework 4.5.2.

See also "[System Requirements](#)" for more information.

- Character Data Types Extended to 32 KB
ODP.NET, Managed Driver supports the VARCHAR2, NVARCHAR2, and RAW data types up to 32 KB in size. No code changes are required to use the larger data types.
By being able to store more data, developers can use these data types more frequently, providing programming flexibility. In addition, SQL Server to Oracle Database application migration is easier with these new data type sizes.
- Return Number of Rows Affected from Each Input in Array Binding Operations
When using array binding to execute multiple DML statements, ODP.NET, Managed Driver provides an array that lists the number of rows affected for each input value from the bound array, rather than just the total number of rows affected. This information provides more detailed feedback for the application developer. To retrieve the row count, ODP.NET can call the `OracleCommand.ArrayBindRowsAffected` property.
With more detailed feedback on the array bound DML execution, the developer can better evaluate the query's efficiency and whether the data changes were correctly applied.
See Also "[ArrayBindRowsAffected](#)" for more information.

Changes in Oracle Data Provider for .NET in ODAC 12c Release 2

The following are the changes in Oracle Data Provider for .NET for ODAC 12c Release 2.

New Features

The following features are new in this release:

- .NET Framework 4.5.1 Certification
Oracle Data Provider for .NET is now certified for .NET Framework 4.5.1.
See also "[System Requirements](#)" for more information.
- .NET Framework 4.6 Certification
Oracle Data Provider for .NET is now certified for .NET Framework 4.6.
See also "[System Requirements](#)" for more information.
- Improvements to ODP.NET, Managed Driver Versioning
This feature allows unique identification of ODP.NET, Managed Driver assemblies which have the same assembly version number.
See also "[Oracle Data Provider for .NET Versioning Scheme](#)" for more information.

Changes in Oracle Data Provider for .NET in ODAC 12c Release 1

The following are the changes in Oracle Data Provider for .NET for ODAC 12c Release 1.

New Features

The following feature is new in this release:

- LDAP Connections to Active Directory and Oracle Internet Directory
ODP.NET, Managed Driver supports TNS alias resolution through a LDAP server/service, specifically Microsoft Active Directory and Oracle Internet Directory.
This feature allows ODP.NET, Managed Driver to connect to a database using a directory server/service.
See also "[Lightweight Directory Access Protocol](#)".

Changes in Oracle Data Provider for .NET Release 12.1

The following are the changes in Oracle Data Provider for .NET for Release 12.1.

New Features

The following features are new in this release:

- ODP.NET, Managed Driver
ODP.NET now includes a fully managed provider version, which is 100% native .NET code. ODP.NET, Managed Driver includes nearly all the features of ODP.NET, Unmanaged Driver and uses the same application programming interface. This makes migrating existing ODP.NET applications to ODP.NET, Managed Driver easier.
With ODP.NET, Managed Driver, it is easier and faster to deploy ODP.NET. There are fewer assemblies, as few as one to deploy, which also makes patching straightforward, and the install size is smaller at less than 10 MB. Only one ODP.NET, Managed Driver assembly is necessary whether you are using 32-bit or 64-bit .NET Framework. Side-by-side deployment with other ODP.NET versions is simple since there are no unmanaged assemblies to account for. As a fully managed provider, ODP.NET can better integrate with Code Access Security and ClickOnce deployment.
See also "[Installing Oracle Data Provider for .NET, Managed Driver](#)".
- Support for Pluggable Database
Pluggable Databases (PDBs) enable an Oracle database to contain a portable collection of schemas, schema objects, and nonschema objects that appears to ODP.NET as a separate database. ODP.NET can seamlessly use PDBs.
PDBs allow fast database provisioning, fast database redeployment by unplugging and plugging in existing databases, and quick patching or upgrading many databases at the cost of doing it once or by unplugging a PDB and plugging it into

a different container database. A machine can run more database instances in the form of PDBs than as individual, monolithic databases. It is also easier to separate application administrator duties from the Oracle system administrator duties.

 **See Also:**

- ["Oracle Multitenant and Pluggable Databases"](#)

- **Support for Auto Increment Identity Column**

Oracle Database 12c Release 1 (12.1) introduces an auto increment identity column. ODP.NET, Unmanaged Driver 12.1 and higher releases support interacting with this column data. Identity columns are generally used to uniquely identify rows in a table when there is no other natural primary key constraint.

An identity column simplifies .NET development for applications with no natural primary key and eases application migration from databases that have an identity column.

 **See Also:**

- ["IdentityInsert"](#)
- ["IdentityUpdate"](#)
- ["OracleIdentityType Enumeration"](#)

- **Support for Character Data Types Extended to 32 KB**

Starting with Oracle Database 12c Release 1 (12.1), ODP.NET, Unmanaged Driver now supports the `VARCHAR2`, `NVARCHAR2`, and `RAW` data types up to 32 KB in size. No code changes are required to use the larger data types.

By being able to store more data, developers can use these data types more frequently, providing programming flexibility. In addition, SQL Server to Oracle Database application migration is easier with these new data type sizes.

- **Boolean Data Type**

Oracle Database 12c Release 1 (12.1) introduces a new PL/SQL Boolean data type, which ODP.NET, Unmanaged Driver can store as an `OracleBoolean` data type. Booleans store `TRUE` or `FALSE` values.

The ODP.NET `OracleBoolean` data type eases parameter binding and data type mapping setup with Boolean values.

 **See Also:**

- ["OracleBoolean Structure"](#)

- **Enhanced Implicit REF Cursor Binding**

In Oracle Database 12c Release 1 (12.1), ODP.NET 12c can retrieve the results of a SELECT statement run in PL/SQL without an explicit target nor REF CURSOR data type. ODP.NET retrieves result sets from stored procedures implicitly without declaring a return type. It is no longer necessary to declare REF CURSOR metadata in a .NET configuration file, except when using Entity Framework, REF Cursors that can be updated, or constraint metadata is required to be passed to the client side.

This capability simplifies using implicit Oracle result sets. In addition, it eases migration to the Oracle database from other vendor databases that use a similar feature.

 **See Also:**

- ["ImplicitRefCursors"](#)
- ["Implicit REF CURSOR Binding"](#)

- **Return Number of Rows Affected from Each Input in Array Binding Operations**

When using array binding to execute multiple DML statements, Oracle Data Provider for .NET, Unmanaged Driver, now provides an array that lists the number of rows affected for each input value from the bound array, rather than just the total number of rows affected. This information provides more detailed feedback for the application developer. To retrieve the row count, ODP.NET can call the `OracleCommand.ArrayBindRowsAffected` property.

With more detailed feedback on the array bound DML execution, the developer can better evaluate the query's efficiency and whether the data changes were correctly applied.

 **See Also:**

- ["ArrayBindRowsAffected"](#)

- **Support for APPLY Keyword**

Language Integrated Query (LINQ) is a .NET querying language. At runtime, LINQ is translated into native database SQL before it can query the database. In some circumstances, LINQ uses the non-standard APPLY keyword in its SQL translation for retrieving lateral views. Oracle Database and ODP.NET support the APPLY keyword in Oracle Database 12c Release 1 (12.1) to more fully support LINQ.

This feature allows the occasional LINQ query that uses SQL APPLY to work seamlessly with ODP.NET and Oracle Database for lateral views.

 **See Also:**

- [ADO.NET Entity Framework and LINQ to Entities](#)

- **Transaction Guard Support**

Transaction Guard in Oracle Database 12c Release 1 (12.1) preserves transaction commit outcomes for ODP.NET, Unmanaged Driver, 12c applications during planned and unplanned outages, preventing applications from repeatedly submitting the same transaction. Applications use a new logical transaction identifier to determine the last open transaction's outcome in a database session following an outage. With the known outcome, the application can confidently determine whether to resubmit the transaction or not. Without Transaction Guard, applications that retry operations following outages by committing duplicate transactions can cause logical corruptions.

Transaction Guard preserves the commit outcome for every transaction and makes it available to ODP.NET applications. It allows ODP.NET developers to maintain at-most-once transaction execution.

 **See Also:**

- ["Using Transaction Guard to Prevent Logical Corruption"](#)

- Recoverable Error Detection and Recovery

After an Oracle Database 12c Release 1 (12.1) failure, ODP.NET, Unmanaged Driver, 12c can determine if a failed transaction is recoverable or not. ODP.NET returns the `OracleException.IsRecoverable` property indicating whether the transaction is recoverable. If true, the application can retry the transaction.

This feature makes determining whether failed transactions are recoverable easier, allowing applications to proceed quickly to the next step in the recovery process.

 **See Also:**

- ["Using Transaction Guard to Prevent Logical Corruption"](#)

- Support for Faster and Planned Database Outage

In Oracle Database 12c Release 1 (12.1), a database being brought offline automatically alerts ODP.NET applications of the impending downtime. ODP.NET will then stop allocating new connections and close connections returned to the pool from that particular instance.

This feature enables databases to be brought offline more quickly and minimizes potential end user disruptions by disallowing new ODP.NET connections to databases being brought offline.

 **See Also:**

- ["Using FCF Planned Outage to Minimize Service Disruption"](#)

- Support for Oracle Notification Service

Oracle Notification Service (ONS) is a publish and subscribe service for communicating Fast Application Notification (FAN) events. ODP.NET receives fast connection failover and load balancing messages from the database server through ONS. Previously, ODP.NET used Oracle Advanced Queuing (AQ) as its FAN publish and subscribe service.

Because ONS is a memory-based service, it delivers messages faster than AQ. Using ONS, Oracle consolidates the publish and subscribe service that all Oracle data access drivers use.

 **See Also:**

- ["Fast Application Notification"](#)

- **Support for Global Data Services**

Global Data Services (GDS) is a capability of Oracle Database 12c that extends the concept of services, which previously only was available in Oracle RAC, to a globally distributed configuration that can include a combination of Oracle RAC, Oracle Data Guard, and Oracle GoldenGate. This allows services to be deployed anywhere within this globally distributed configuration, supporting load balancing, high availability, database affinity, and so on with ODP.NET.

ODP.NET applications can now more efficiently use database resources on a global basis to improve performance and availability. Applications that utilize the Oracle RAC concept of services can now extend the same benefits of automatic workload management to their Oracle Data Guard and Oracle GoldenGate configurations. Similarly, Oracle Data Guard and Oracle GoldenGate customers can now fully utilize the benefits of services and automatic workload management for their replicated configurations.

 **See Also:**

- ["Runtime Connection Load Balancing"](#)
- ["Fast Connection Failover \(FCF\)"](#)

- **Transaction and Connection Association**

Connections associate with `System.Transactions` transactions when they enlist either implicitly through `enlist=true` connection string attribute, or explicitly through `OracleConnection.EnlistTransaction()` method. A connection in ODP.NET now, by default, detaches from a transaction only when the connection object is closed or when the transaction object is disposed.

In earlier ODP.NET releases, the connection would get detached from a transaction under the conditions mentioned earlier and when the transaction was complete (committed, aborted, or timed out). When the transaction timeout elapses before the transaction completes, the connection unbinds itself from the transaction and all subsequent operations on this connection execute in `AutoCommit` mode. Any operations prior to the timeout roll back, but operations performed after the timeout commit. The new transaction unbinding default behavior also alerts users with an exception if transactions time out and

subsequent operations execute on this connection before the transaction is disposed. This new behavior provides a consistent transactional experience for the end user, even when a timeout occurs.

See also "[LegacyTransactionBindingBehavior](#)" for more information.

- Greater Granular Connection Pool Monitoring

Performance counters can now monitor at the application domain, pool, or database instance level.

It is now easier to distinguish which application domains, pools, and instances are healthy and which ones are having problems.

 **See Also:**

["Connection Performance Counters"](#)

1

Introducing Oracle Data Provider for .NET

This chapter introduces Oracle Data Provider for .NET (ODP.NET), an implementation of a .NET data provider for Oracle Database.

This chapter contains these topics:

- [.NET Data Access in Oracle: Products and Documentation](#)
- [Overview of Oracle Data Provider for .NET \(ODP.NET\)](#)
- [Oracle Data Provider for .NET Assemblies](#)
- [Differences between the ODP.NET Drivers](#)
- [Using ODP.NET Client Provider in a Simple Application](#)

.NET Data Access in Oracle: Products and Documentation

This section discusses Oracle Data Provider for .NET and Oracle Database components that use Oracle Data Provider for .NET for data access. It briefly describes what each component does and where to find additional documentation.

These Oracle products provide .NET integration on the Windows operating system:

Oracle Data Provider for .NET (ODP.NET)

Oracle Data Provider for .NET provides fast data access from .NET clients to Oracle databases. ODP.NET enables .NET applications to take advantage of Oracle advanced features, such as Oracle Real Application Clusters (Oracle RAC) and XML DB. It is accessible through any .NET language, including C#, Visual Basic .NET, and C++ .NET.

ODP.NET consists of three drivers: ODP.NET, Managed Driver, ODP.NET, Unmanaged and ODP.NET Core. ODP.NET, Managed Driver is a fully managed ADO.NET provider, consisting of fewer DLLs and smaller install size than ODP.NET, Unmanaged Driver. The managed driver has the same exact application programming interfaces (APIs) as ODP.NET, Unmanaged Driver. However, the managed driver's APIs are a subset of the Unmanaged Driver's APIs.

ODP.NET Core is a multi-platform provider for Microsoft .NET Core. In functionality, it is very similar to ODP.NET, Managed Driver. However, ODP.NET Core has a subset of managed ODP.NET's APIs.

This guide describes Oracle Data Provider for .NET features, their use, installation, requirements, and classes. The guide distinguishes which classes and APIs are supported for the managed driver, unmanaged driver, .NET stored procedures, and .NET clients.

Additionally, Oracle Data Provider for .NET Dynamic Help, which is context-sensitive online help, contains the same reference sections available in *Oracle Data Provider for .NET Developer's Guide for Microsoft Windows*, this guide.

Oracle Data Provider for .NET Dynamic Help is integrated with Visual Studio Dynamic Help. With Dynamic Help, you can access Oracle Data Provider for .NET documentation within Visual Studio by placing the cursor on an Oracle Data Provider for .NET keyword and pressing the F1 function key.

Oracle Developer Tools for Visual Studio

Oracle Developer Tools is an add-in to Visual Studio that provides graphical user interface (GUI) access to Oracle functionality. It provides improved developer productivity and ease of use. Oracle Developer Tools provide the ability to build .NET stored procedures using Visual Basic .NET, C#, and other .NET languages.

Oracle Developer Tools for Visual Studio Help describes Oracle Developer Tools. This help is in the form of dynamic help, which installs as part of the product.

Additionally, the Oracle Developer Tools for Visual Studio Help includes the following documentation:

- *Oracle Database PL/SQL Language Reference*
- *Oracle Database SQL Language Reference*
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows*
- *Oracle Database Error Messages Reference*
- Access to Oracle Data Provider for .NET Dynamic Help
- Access to Oracle Providers for ASP.NET Dynamic Help

Oracle Database Extensions for .NET

Oracle Database Extensions for .NET provides the following:

- Hosting of Microsoft Common Language Runtime (CLR) in an external process on the server side, to execute .NET stored procedures.
- ODP.NET data access on the server side, from within the .NET stored procedure.

Oracle Data Provider for .NET Developer's Guide for Microsoft Windows describes all ODP.NET classes. Classes that are not supported by Oracle Database Extensions for .NET are described as *Not Supported in a .NET Stored Procedure*.



See Also:

- Oracle Developer Tools for Visual Studio Help
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows* for more information about Oracle Database Extensions for .NET features, their use, installation, and requirements.
- "[Oracle Data Provider for .NET Assemblies](#)" for class listings
- [Oracle Data Provider for .NET Stored Procedures](#)

Oracle Providers for ASP.NET

Oracle Providers for ASP.NET offer ASP.NET developers an easy to use method to store state common to web applications within an Oracle database. These providers are modeled on existing Microsoft ASP.NET providers, sharing similar schema and programming interfaces to provide .NET developers a familiar interface. Oracle supports the following providers:

- Cache Dependency Provider
- Membership Provider
- Profile Provider
- Role Provider
- Session State Provider
- Site Map Provider
- Web Events Provider
- Web Parts Personalization Provider

Oracle Providers for ASP.NET classes, their use, installation, and requirements are described in *Oracle Providers for ASP.NET Developer's Guide for Microsoft Windows*, which is also provided as dynamic help.

Oracle Services for Microsoft Transaction Server

Oracle Services for Microsoft Transaction Server (OraMTS) permit Oracle databases to be used as resource managers in Microsoft application coordinated transactions. OraMTS acts as a proxy for the Oracle database to the Microsoft Distributed Transaction Coordinator (MSDTC). As a result, OraMTS provides client-side connection pooling and allows client components that leverage Oracle to participate in promotable and distributed transactions. In addition, OraMTS can operate with Oracle databases running on any operating system, given that the services themselves are run on Windows.

See Also:

Oracle Services for Microsoft Transaction Server Developer's Guide for Microsoft Windows for description about OraMTS, which allows Oracle databases to be used as resource managers in distributed transactions.

Oracle TimesTen In-Memory Database

ODP.NET support for Oracle TimesTen In-Memory Database (TimesTen) provides fast and efficient ADO.NET data access for applications that require the highest performance.

You can use ODP.NET with any of the following TimesTen installations:

- TimesTen Data Manager only (for direct connections)

- TimesTen Client only (for client/server connections, assuming a TimesTen Data Manager instance and TimesTen Server instance are accessible elsewhere)
- TimesTen Data Manager with TimesTen Server

For more information on ODP.NET features specific to a TimesTen environment, refer to the *Oracle Data Provider for .NET Oracle TimesTen In-Memory Database Support User's Guide*.



Note:

TimesTen does not support ODP.NET, Managed Driver and ODP.NET Core.

Overview of Oracle Data Provider for .NET (ODP.NET)

Oracle Data Provider for .NET (ODP.NET) is an implementation of a .NET data provider for Oracle Database, using and inheriting from classes and interfaces available in the [Microsoft .NET Framework Class Library](#).

Following the .NET Framework, ODP.NET uses the ADO.NET model, which allows native providers to expose provider-specific features and data types. This is similar to Oracle Provider for OLE DB, where ADO (ActiveX Data Objects) provides an automation layer that exposes an easy programming model. ADO.NET provides a similar programming model, but without the automation layer, for better performance.

Oracle Data Provider for .NET uses Oracle native APIs to offer fast and reliable access to Oracle data and features from any .NET application. ODP.NET consists of three drivers: ODP.NET, Managed Driver, ODP.NET, Unmanaged Driver, and ODP.NET Core. ODP.NET, Managed Driver is a fully managed ADO.NET provider, consisting of fewer DLLs and smaller install size than ODP.NET, Unmanaged Driver. The managed driver has the same exact application programming interfaces (APIs) as ODP.NET, Unmanaged Driver. However, the managed driver's APIs are a subset of the Unmanaged Driver's APIs.

ODP.NET Core employs the same namespaces and application programming interfaces (APIs) as ODP.NET, Managed Driver. This parallel eases migration and developer learning curve from managed ODP.NET to ODP.NET Core. It does not support all managed ODP.NET functionality. ODP.NET Core supports a subset of managed ODP.NET APIs. These differences are listed later on in this documentation.

The ODP.NET classes described in this guide are contained in the `Oracle.DataAccess.dll` and `Oracle.ManagedDataAccess.dll` assembly.

- Client Applications: All ODP.NET classes are available for use in client applications.

As ODP.NET, Managed Driver does not support all classes and members in the ODP.NET, Unmanaged Driver, the unsupported managed driver classes and members will be labeled *Not Supported in ODP.NET, Managed Driver*.

ODP.NET Core does not support all classes and members in the ODP.NET, Managed Driver. The unsupported managed driver classes and members will be labeled *Not Supported in ODP.NET Core*.

- .NET Stored Procedures: Most ODP.NET classes can be used from within .NET stored procedures and functions. Those classes which cannot, are labeled *Not*

Supported in a .NET Stored Procedure. Additionally, some classes contain members which may not be supported, and this is so indicated in the member tables that follow the class descriptions, and listed in Chapter 4 of this guide.

See Also:

- [Table 5-1](#)
- ["Oracle Data Provider for .NET Assemblies"](#) for class lists
- [Oracle Data Provider for .NET Stored Procedures](#)
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows* for more information about .NET stored procedures and functions

Oracle Data Provider for .NET Assemblies

This section contains the following topics:

- [Oracle Data Provider for .NET, Unmanaged Driver Assemblies](#)
- [Oracle Data Provider for .NET, Managed Driver and ODP.NET Core Assemblies](#)
- [Oracle.DataAccess.Client](#) and [Oracle.ManagedDataAccess.Client](#) Namespaces
- [Oracle.DataAccess.Types](#) and [Oracle.ManagedDataAccess.Types](#) Namespaces

Oracle Data Provider for .NET, Unmanaged Driver Assemblies

The `Oracle.DataAccess.dll` [assembly](#) provides two namespaces:

- The `Oracle.DataAccess.Client` namespace contains ODP.NET classes and enumerations for the client-side provider.
- The `Oracle.DataAccess.Types` namespace contains the Oracle Data Provider for .NET data types (ODP.NET Types).

To use Code First or Entity Framework 6 or higher with ODP.NET, Unmanaged Driver, add `Oracle.DataAccess.EntityFramework.dll` as a project assembly reference. It contains the namespace `Oracle.DataAccess.EntityFramework`.

Oracle Data Provider for .NET, Managed Driver and ODP.NET Core Assemblies

The `Oracle.ManagedDataAccess.dll` [assembly](#) provides two namespaces:

- The `Oracle.ManagedDataAccess.Client` namespace contains ODP.NET classes and enumerations for the client-side provider.
- The `Oracle.ManagedDataAccess.Types` namespace contains the Oracle Data Provider for .NET data types (ODP.NET Types).

ODP.NET, Managed Driver contains additional assemblies. These assemblies are optional to install if not using the specific functionality.

Applications do not need to explicitly add these assemblies to their project. ODP.NET, Managed Driver will access these assemblies by default if installed.

The one exception is `Oracle.ManagedDataAccess.EntityFramework.dll`. That DLL must be explicitly added to a project for its functionality to be used.

- `Oracle.ManagedDataAccess.EntityFramework.dll` - Only required when using Code First or Entity Framework 6 or higher. It contains the `Oracle.ManagedDataAccess.EntityFramework` namespace.
- `Oracle.ManagedDataAccessIOP.dll` - Only required when using Kerberos. The assembly has 32-bit and x64 versions depending on the .NET Framework's bitness in which it runs. The assembly makes calls to unmanaged assemblies. Applications do not need to explicitly add this assembly to their project as ODP.NET is already configured to access this assembly by default.

Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces

The `Oracle.DataAccess.Client` and `Oracle.ManagedDataAccess.Client` namespaces contains implementations of core ADO.NET classes and enumerations for ODP.NET, as well as ODP.NET specific classes.

The following tables list ODP.NET classes, enumerations, and types that are supported by the `Oracle.DataAccess.Client` and `Oracle.ManagedDataAccess.Client` namespaces. The tables indicate which of them are not supported by ODP.NET, Managed Driver, ODP.NET Core and/or by .NET stored procedures. All are supported by ODP.NET, Unmanaged Driver.

Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

[Table 1-1](#) lists the `Oracle.DataAccess.Client` and `Oracle.ManagedDataAccess.Client` classes and delegates.

Table 1-1 Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OnChangeEventHandler Delegate	-	-	No	The <code>OnChangeEventHandler</code> event delegate represents the signature of the method that handles the notification.
OracleAQAgent Class	No	No	-	The <code>OracleAQAgent</code> class represents agents that may be senders or recipients of a message.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleAQDequeueOptions Class	No	No	-	An OracleAQDequeueOptions object represents the options available when dequeuing a message from an OracleAQQueue object.
OracleAQEnqueueOptions Class	No	No	-	The OracleAQEnqueueOptions class represents the options available when enqueueing a message to an OracleAQQueue.
OracleAQMessage Class	No	No	-	An OracleAQMessage object represents a message to be enqueued and dequeued.
OracleAQMessageAvailableEventArgs Class	No	No	-	The OracleAQMessageAvailableEventArgs class provides event data for the OracleAQQueue.MessageAvailable event.
OracleAQMessageAvailableEventHandler Delegate	No	No	-	The OracleAQMessageAvailableEventHandler delegate represents the signature of the method that handles the OracleAQQueue.MessageAvailable event.
OracleAQQueue Class	No	No	-	An OracleAQQueue object represents a queue.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleBulkCopy Class	No	No	-	An <code>OracleBulkCopy</code> object efficiently bulk loads or copies data into an Oracle table from another data source.
OracleBulkCopyColumnMapping Class	No	No	-	The <code>OracleBulkCopyColumnMapping</code> class defines the mapping between a column in the data source and a column in the destination database table.
OracleBulkCopyColumnMappingCollection Class	No	No	-	The <code>OracleBulkCopyColumnMappingCollection</code> class represents a collection of <code>OracleBulkCopyColumnMapping</code> objects that are used to map columns in the data source to columns in a destination table.
OracleClientFactory Class	-	No	-	An <code>OracleClientFactory</code> object allows applications to instantiate ODP.NET classes in a generic way.
OracleCommand Class	-	-	-	An <code>OracleCommand</code> object represents a SQL command, a stored procedure or function, or a table name.
OracleCommandBuilder Class	-	-	-	An <code>OracleCommandBuilder</code> object provides automatic SQL generation for the <code>OracleDataAdapter</code> when the database is updated.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleConfiguration Class	-	-	-	An OracleConfiguration is a static class for setting ODP.NET Core configuration data using a single programming interface.
OracleConnection Class	-	-	-	An OracleConnection object represents a connection to Oracle Database.
OracleConnectionOpenEventArgs Class	-	-	-	An OracleConnectionOpenEventArgs object provides connection information for the OracleConnection.Open() method.
OracleConnectionOpenEventHandler Delegate	-	-	-	The OracleConnectionOpenEventHandler delegate represents the signature of the method that handles OracleConnection.ConnectionOpen event.
OracleConnectionStringBuilder Class	-	-	-	An OracleConnectionStringBuilder object allows applications to create or modify connection strings.
OracleCredential Class	-	-	-	OracleCredential class provides a secure way to provide password while opening connection with Oracle Database using the ODP.NET driver

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleDataAdapter Class	-	-	-	An <code>OracleDataAdapter</code> object represents a data provider object that communicates with the <code>DataSet</code> .
OracleDatabase Class	No	No	-	An <code>OracleDatabase</code> object represents an Oracle Database instance.
OracleDataReader Class	-	-	-	An <code>OracleDataReader</code> object represents a forward-only, read-only, in-memory result set.
OracleDataSourceCollection Class	-	-	-	An <code>OracleDataSourceCollection</code> object supports adding and deleting network service name (i.e. TNS) entries in the <code>OracleDataSourceCollection</code> .
OracleDataSourceEnumerator Class	-	-	-	An <code>OracleDataSourceEnumerator</code> object allows applications to generically obtain a collection of data sources to connect to.
OracleDependency Class	-	-	No	An <code>OracleDependency</code> class represents a dependency between an application and an Oracle database.
OracleError Class	-	-	-	The <code>OracleError</code> object represents an error reported by an Oracle database.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleErrorCollection Class	-	-	-	An OracleErrorCollection object represents a collection of OracleErrors.
OracleException Class	-	-	-	The OracleException object represents an exception that is thrown when Oracle Data Provider for .NET encounters an error.
OracleFailoverEventArgs Class	No	No	No	The OracleFailoverEventArgs class provides event data for the OracleConnection.Failover event.
OracleFailoverEventHandler Delegate	No	No	No	The OracleFailoverEventHandler represents the signature of the method that handles the OracleConnection.Failover event.
OracleGlobalization Class	-	-	-	The OracleGlobalization class is used to obtain and set the Oracle globalization settings of the session, thread, and local computer (read-only).
OracleHAEventArgs Class	-	-	-	The OracleHAEventArgs class provides event data for the OracleConnection.HAEvent event.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleHAEventHandler Delegate	-	-	-	The OracleHAEventHandler delegate represents the signature of the method that handles the OracleConnection.HAEvent event.
OracleInfoMessageEventArgs Class	-	-	-	The OracleInfoMessageEventArgs object provides event data for the OracleConnection.InfoMessage event.
OracleInfoMessageEventHandler Delegate	-	-	-	The OracleInfoMessageEventHandler delegate represents the signature of the method that handles the OracleConnection.InfoMessage event.
OracleLogicalTransaction Class	-	-	-	The OracleLogicalTransaction class provides detailed information about the logical transaction status.
OracleNotificationEventArgs Class	-	-	-	The OracleNotificationEventArgs class provides event data for a notification.
OracleNotificationRequest Class	-	-	No	An OracleNotificationRequest class represents a notification request to be subscribed in the database.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleOnsServerCollection Class	-	-	-	The <code>OracleOnsServerCollection</code> class supports adding to and deleting from a collection of logical servers with their corresponding list of nodes where the Oracle Notification Service (ONS) daemons are talking to their remote clients.
OracleParameter Class	-	-	-	An <code>OracleParameter</code> object represents a parameter for an <code>OracleCommand</code> .
OracleParameterCollection Class	-	-	-	An <code>OracleParameterCollection</code> object represents a collection of <code>OracleParameters</code> .
OraclePermission Class	-	No	-	An <code>OraclePermission</code> object enables ODP.NET to enforce imperative security and helps ensure that a user has a security level adequate for accessing data.
OraclePermissionAttribute Class	-	No	-	An <code>OraclePermissionAttribute</code> object enables ODP.NET to enforce declarative security and helps ensure that a user has a security level adequate for accessing data.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleRowsCopiedEventHandler Delegate	No	No	-	The <code>OracleRowsCopiedEventHandler</code> delegate represents the method that handles the <code>OracleRowsCopied</code> event of an <code>OracleBulkCopy</code> object.
OracleRowsCopiedEventArgs Class	No	No	-	The <code>OracleRowsCopiedEventArgs</code> class represents the set of arguments passed as part of event data for the <code>OracleRowsCopied</code> event.
OracleRowUpdatedEventArgs Class	-	-	-	The <code>OracleRowUpdatedEventArgs</code> object provides event data for the <code>OracleDataAdapter.RowUpdated</code> event.
OracleRowUpdatedEventHandler Delegate	-	-	-	The <code>OracleRowUpdatedEventHandler</code> delegate represents the signature of the method that handles the <code>OracleDataAdapter.RowUpdated</code> event.
OracleRowUpdatingEventArgs Class	-	-	-	The <code>OracleRowUpdatingEventArgs</code> object provides event data for the <code>OracleDataAdapter.RowUpdating</code> event.

Table 1-1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

Class or Delegate	Supported in the ODP.NET, Managed Driver	Supported in the ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleRowUpdatingEventHandler Delegate	-	-	-	The <code>OracleRowUpdatingEventHandler</code> delegate represents the signature of the method that handles the <code>OracleDataAdapter.RowUpdating</code> event.
OracleShardingKey Class	No	No	-	An <code>OracleShardingKey</code> object can represent either a sharding key or a super sharding key.
OracleTransaction Class	-	-	No	An <code>OracleTransaction</code> object represents a local transaction.
OracleXmlQueryProperties Class	-	-	-	An <code>OracleXmlQueryProperties</code> object represents the XML properties used by the <code>OracleCommand</code> class when the <code>XmlCommandType</code> property is <code>Query</code> .
OracleXmlSaveProperties Class	-	-	-	An <code>OracleXmlSaveProperties</code> object represents the XML properties used by the <code>OracleCommand</code> class when the <code>XmlCommandType</code> property is <code>Insert</code> , <code>Update</code> , or <code>Delete</code> .

Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

Table 1-2 lists the client enumerations.

Table 1-2 Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

Enumeration	Supported in the ODP.NET, Managed Driver and ODP.NET Core	Supported in .NET Stored Procedures	Description
FailoverEvent Enumeration	No	No	FailoverEvent enumerated values are used to specify the state of the failover.
FailoverReturnCode Enumeration	No	No	FailoverReturnCode enumerated values are passed back by the application to the ODP.NET provider to request a retry in case of a failover error, or to continue in case of a successful failover.
FailoverType Enumeration	No	No	FailoverType enumerated values are used to indicate the type of failover event that was raised.
OracleAQDequeueMode Enumeration	No	-	The OracleAQDequeueMode enumeration type specifies the dequeue mode.
OracleAQMessageDeliveryMode Enumeration	No	-	The OracleAQMessageDeliveryMode enumeration type specifies the delivery mode of the message.
OracleAQMessageState Enumeration	No	-	The OracleAQMessageState enumeration type identifies the state of the message at the time of dequeue.
OracleAQMessageType Enumeration	No	-	The OracleAQMessageType enumeration type specifies the message payload type.
OracleAQNavigationMode Enumeration	No	-	The OracleAQNavigationMode enumeration type specifies the navigation mode.
OracleAQNotificationGroupingType Enumeration	No	-	The OracleAQNotificationGroupingType enumeration type specifies the notification grouping type.
OracleAQNotificationType Enumeration	No	-	The OracleAQNotificationType enumeration type specifies the notification type of the received notification.

Table 1-2 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

Enumeration	Supported in the ODP.NET, Managed Driver and ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleAQVisibilityMode Enumeration	No	-	The <code>OracleAQVisibilityMode</code> enumeration type specifies whether the enqueue or dequeue operation is part of the current transaction.
OracleBulkCopyOptions Enumeration	No	-	The <code>OracleBulkCopyOptions</code> enumeration specifies the values that can be combined with an instance of the <code>OracleBulkCopy</code> class and used as options to determine its behavior and the behavior of the <code>WriteToServer</code> methods for that instance.
OracleCollectionType Enumeration	-	No	<code>OracleCollectionType</code> enumerated values specify whether or not the <code>OracleParameter</code> object represents a collection, and if so, specifies the collection type.
OracleConnectionType Enumeration	No	-	<code>OracleConnectionType</code> enumerated values specify whether a particular connection object is associated with an Oracle database connection, a TimesTen database connection, or no physical connection at all.
OracleDBShutdownMode Enumeration	No	-	<code>OracleDBShutdownMode</code> enumerated values specify the database shutdown options.
OracleDBStartupMode Enumeration	No	-	<code>OracleDBStartupMode</code> enumerated values specify the database startup options.
OracleDbType Enumeration	-	-	<code>OracleDbType</code> enumerated values are used to explicitly specify the <code>OracleDbType</code> of an <code>OracleParameter</code> .
OracleDRCPpurity Enumeration	-	-	<code>OracleDRCPpurity</code> enumerated values specify the session purity.
OracleHAEventSource Enumeration	-	-	The <code>OracleHAEventSource</code> enumeration indicates the source of the HA event.

Table 1-2 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

Enumeration	Supported in the ODP.NET, Managed Driver and ODP.NET Core	Supported in .NET Stored Procedures	Description
OracleHAEventStatus Enumeration	-	-	The <code>OracleHAEventStatus</code> enumeration indicates the status of the HA event source.
OracleIdentityType Enumeration	-	-	The <code>OracleIdentityType</code> enumeration specifies how Oracle identity column values are generated.
OracleNotificationInfo Enumeration	-	No	<code>OracleNotificationInfo</code> enumerated values specify the database event that causes the notification.
OracleNotificationSource Enumeration	-	No	<code>OracleNotificationSource</code> enumerated values specify the different sources that cause notification.
OracleNotificationType Enumeration	-	No	<code>OracleNotificationType</code> enumerated values specify the different types that cause the notification.
OracleParameterStatus Enumeration	-	-	The <code>OracleParameterStatus</code> enumeration type indicates whether a NULL value is fetched from a column, or truncation has occurred during the fetch, or a NULL value is to be inserted into a database column.
OracleRowidInfo Enumeration	-	-	The <code>OracleRowidInfo</code> enumeration values specify whether ROWID information is included as part of the <code>ChangeNotificationEventArgs</code> or not.
OracleXmlCommandType Enumeration	-	-	The <code>OracleXmlCommandType</code> enumeration specifies the values that are allowed for the <code>OracleXmlCommandType</code> property of the <code>OracleCommand</code> class.

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces

The `Oracle.DataAccess.Types` and `Oracle.ManagedDataAccess.Types` namespaces provides classes, structures, and exceptions for Oracle native types that can be used with Oracle Data Provider for .NET.

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Structures

[Table 1-3](#) lists the type structures.

Table 1-3 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Structures

Structure	Description
OracleBinary Structure	The <code>OracleBinary</code> structure represents a variable-length stream of binary data.
OracleBoolean Structure	The <code>OracleBoolean</code> structure represents a logical value that is either <code>TRUE</code> or <code>FALSE</code> .
OracleDate Structure	The <code>OracleDate</code> structure represents the Oracle <code>DATE</code> data type.
OracleDecimal Structure	The <code>OracleDecimal</code> structure represents an Oracle <code>NUMBER</code> in the database or any Oracle numeric value.
OracleIntervalDS Structure	The <code>OracleIntervalDS</code> structure represents the Oracle <code>INTERVAL DAY TO SECOND</code> data type.
OracleIntervalYM Structure	The <code>OracleIntervalYM</code> structure represents the Oracle <code>INTERVAL YEAR TO MONTH</code> data type.
OracleString Structure	The <code>OracleString</code> structure represents a variable-length stream of characters.
OracleTimeStamp Structure	The <code>OracleTimeStamp</code> structure represents the Oracle <code>TimeStamp</code> data type.
OracleTimeStampLTZ Structure	The <code>OracleTimeStampLTZ</code> structure represents the Oracle <code>TIMESTAMP WITH LOCAL TIME ZONE</code> data type.
OracleTimeStampTZ Structure	The <code>OracleTimeStampTZ</code> structure represents the Oracle <code>TIMESTAMP WITH TIME ZONE</code> data type.

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Exceptions

Type Exceptions are thrown only by ODP.NET type structures. [Table 1-4](#) lists the type exceptions.

Table 1-4 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Exceptions

Exception	Description
OracleTypeException Class	The <code>OracleTypeException</code> object is the base exception class for handling exceptions that occur in the ODP.NET Types classes.
OracleNullValueException Class	The <code>OracleNullValueException</code> represents an exception that is thrown when trying to access an ODP.NET Types structure that is null.
OracleTruncateException Class	The <code>OracleTruncateException</code> class represents an exception that is thrown when truncation in an ODP.NET Types class occurs.

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes

Table 1-5 lists the type classes.

Table 1-5 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes

Class	Supported in the ODP.NET, Managed Driver and ODP.NET Core	Description
OracleArrayMappingAttribute Class	No	The <code>OracleArrayMappingAttribute</code> class is required to mark a custom class field or property with information that ODP.NET uses when a custom type represents an Oracle Collection type.
OracleBFile Class	-	An <code>OracleBFile</code> is an object that has a reference to BFILE data. It provides methods for performing operations on BFILE objects.
OracleBlob Class	-	An <code>OracleBlob</code> object is an object that has a reference to BLOB data. It provides methods for performing operations on BLOB objects.
OracleClob Class	-	An <code>OracleClob</code> is an object that has a reference to CLOB data. It provides methods for performing operations on CLOB objects.
OracleCustomTypeMappingAttribute Class	No	The <code>OracleCustomTypeMappingAttribute</code> class is used to mark a custom type factory class or struct with information that is used by ODP.NET when a custom type is used to represent an Oracle UDT.
OracleObjectMappingAttribute Class	No	The <code>OracleObjectMappingAttribute</code> class marks custom class fields or properties with information that ODP.NET uses when a custom type represents an Oracle Object type.

Table 1-5 (Cont.) Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes

Class	Supported in the ODP.NET, Managed Driver and ODP.NET Core	Description
OracleRef Class	No	An <code>OracleRef</code> instance represents an Oracle REF, which references a persistent, standalone, referenceable object that resides in the database. The <code>OracleRef</code> object provides methods to insert, update, and delete the Oracle REF.
OracleRefCursor Class	-	An <code>OracleRefCursor</code> object represents an Oracle REF CURSOR.
OracleUdt Class	No	The <code>OracleUdt</code> class defines static methods that are used when converting between Custom Types and Oracle UDTs and vice-versa.
OracleXmlStream Class	-	An <code>OracleXmlStream</code> object represents a sequential read-only stream of XML data stored in an <code>OracleXmlType</code> object.
OracleXmlType Class	-	An <code>OracleXmlType</code> object represents an Oracle <code>XmlType</code> instance.

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces

[Table 1-6](#) lists the type interfaces.

Table 1-6 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces

Interface	Supported in the ODP.NET, Managed Driver and ODP.NET Core	Description
IOracleArrayTypeFactory Interface	No	The <code>IOracleArrayTypeFactory</code> interface is used by ODP.NET to create arrays that represent Oracle Collections.
IOracleCustomType Interface	No	<code>IOracleCustomType</code> is an interface for converting between a Custom Type and an Oracle Object or Collection Type.
IOracleCustomTypeFactory Interface	No	The <code>IOracleCustomTypeFactory</code> interface is used by ODP.NET to create custom objects that represent Oracle Objects or Collections.
INullable Interface	-	The <code>INullable</code> interface is used to determine whether or not an ODP.NET type has a NULL value.

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Enumerations

[Table 1-7](#) lists the type enumerations.

Table 1-7 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Enumerations

Enumeration	Supported in the ODP.NET, Managed Driver and ODP.NET Core	Description
OracleUdtFetchOption Enumeration	No	OracleUdtFetchOption enumeration values specify how to retrieve a copy of the referenceable object.
OracleUdtStatus Enumeration	No	OracleUdtStatus enumeration values specify the status of an object attribute or collection element. An object attribute or a collection element can be a valid value or a null value.

Differences between the ODP.NET Drivers

ODP.NET, Managed Driver, ODP.NET, Unmanaged Driver, and ODP.NET Core have a number of configuration setting differences.

Table 1-8 Application Programming Interfaces not supported in ODP.NET, Managed Driver and ODP.NET Core

Namespace	Class/Enumeration/Interface	Unsupported Method/Property/Event
Oracle.ManagedDataAccess.Client	FailoverEvent enumeration	All
Oracle.ManagedDataAccess.Client	FailoverReturnCode enumeration	All
Oracle.ManagedDataAccess.Client	FailoverType enumeration	All
Oracle.ManagedDataAccess.Client	OracleAQAgent class	All
Oracle.ManagedDataAccess.Client	OracleAQDequeueMode enumeration	All
Oracle.ManagedDataAccess.Client	OracleAQDequeueOptions class	All
Oracle.ManagedDataAccess.Client	OracleAQEnqueueOptions class	All
Oracle.ManagedDataAccess.Client	OracleAQMessage class	All
Oracle.ManagedDataAccess.Client	OracleAQMessageAvailableEventArgs class	All
Oracle.ManagedDataAccess.Client	OracleAQMessageAvailableEventHandler class	All
Oracle.ManagedDataAccess.Client	OracleAQMessageDeliveryMode enumeration	All

Table 1-8 (Cont.) Application Programming Interfaces not supported in ODP.NET, Managed Driver and ODP.NET Core

Namespace	Class/Enumeration/Interface	Unsupported Method/Property/Event
Oracle.ManagedDataAccess.Client	OracleAQMessageState enumeration	All
Oracle.ManagedDataAccess.Client	OracleAQMessageType enumeration	All
Oracle.ManagedDataAccess.Client	OracleAQNavigationMode enumeration	All
Oracle.ManagedDataAccess.Client	OracleAQNotificationGroupingType enumeration	All
Oracle.ManagedDataAccess.Client	OracleAQNotificationType enumeration	All
Oracle.ManagedDataAccess.Client	OracleAQQueue class	All
Oracle.ManagedDataAccess.Client	OracleAQVisibilityMode enumeration	All
Oracle.ManagedDataAccess.Client	OracleBulkCopy class	All
Oracle.ManagedDataAccess.Client	OracleBulkCopyColumnMapping class	All
Oracle.ManagedDataAccess.Client	OracleBulkCopyColumnMappingCollection class	All
Oracle.ManagedDataAccess.Client	OracleBulkCopyOptions class	All
Oracle.ManagedDataAccess.Client	OracleClientFactory class	<i>Not supported in ODP.NET Core only</i>
Oracle.ManagedDataAccess.Client	OracleCommand class	ArrayBindRowsAffected property
Oracle.ManagedDataAccess.Client	OracleCommand class	ImplicitRefCursors property
Oracle.ManagedDataAccess.Client	OracleConnection class	FlushCache() method
Oracle.ManagedDataAccess.Client	OracleConnection class	Failover event
Oracle.ManagedDataAccess.Client	OracleConnection class	ConnectionType property
Oracle.ManagedDataAccess.Client	OracleConnection class	SetShardingKey method
Oracle.ManagedDataAccess.Client	OracleConnection class	EnlistDistributedTransaction(ITransaction) method <i>Not supported in ODP.NET Core only</i>

Table 1-8 (Cont.) Application Programming Interfaces not supported in ODP.NET, Managed Driver and ODP.NET Core

Namespace	Class/Enumeration/Interface	Unsupported Method/Property/Event
Oracle.ManagedDataAccess.Client	OracleConnectionType enumeration	All
Oracle.ManagedDataAccess.Client	OracleDBShutdownMode enumeration	All
Oracle.ManagedDataAccess.Client	OracleDBStartupMode enumeration	All
Oracle.ManagedDataAccess.Client	OracleDataReader class	GetOracleRef() method
Oracle.ManagedDataAccess.Client	OracleDataReader class	GetOracleBlobForUpdate() method If the method is called, then a NotSupportedException is thrown.
Oracle.ManagedDataAccess.Client	OracleDataReader class	GetOracleClobForUpdate() method If the method is called, then a NotSupportedException is thrown.
Oracle.ManagedDataAccess.Client	OracleDataReader class	IsAutoIncrement and IdentityType properties of the GetSchemaTable
Oracle.ManagedDataAccess.Client	OracleDataAdapter class	IdentityInsert property
Oracle.ManagedDataAccess.Client	OracleDataAdapter class	IdentityUpdate property
Oracle.ManagedDataAccess.Client	OracleDataAdapter class	SafeMapping property
Oracle.ManagedDataAccess.Client	OracleDatabase class	All
Oracle.ManagedDataAccess.Client	OracleDbType enumeration	Array
Oracle.ManagedDataAccess.Client	OracleDbType enumeration	Object
Oracle.ManagedDataAccess.Client	OracleDbType enumeration	Ref
Oracle.ManagedDataAccess.Client	OracleException class	IsRecoverable property
Oracle.ManagedDataAccess.Client	OracleFailoverEventArgs class	All

Table 1-8 (Cont.) Application Programming Interfaces not supported in ODP.NET, Managed Driver and ODP.NET Core

Namespace	Class/Enumeration/Interface	Unsupported Method/Property/Event
Oracle.ManagedDataAccess.Client	OracleFailoverEventHandler class	All
Oracle.ManagedDataAccess.Client	OracleGlobalization class	ClientCharacterSet property
Oracle.ManagedDataAccess.Client	OracleGlobalization class	GetClientInfo() method
Oracle.ManagedDataAccess.Client	OracleGlobalization class	GetThreadInfo() method
Oracle.ManagedDataAccess.Client	OracleGlobalization class	SetThreadInfo() method
Oracle.ManagedDataAccess.Client	OracleIdentityType enumeration	All
Oracle.ManagedDataAccess.Client	OracleNotificationRequest class	GroupingInterval property
Oracle.ManagedDataAccess.Client	OracleNotificationRequest class	GroupingNotificationEnabled property
Oracle.ManagedDataAccess.Client	OracleNotificationRequest class	GroupingType property
Oracle.ManagedDataAccess.Client	OraclePermission class	<i>Not supported in ODP.NET Core only</i>
Oracle.ManagedDataAccess.Client	OraclePermissionAttribute class	<i>Not supported in ODP.NET Core only</i>
Oracle.ManagedDataAccess.Client	OracleRowsCopiedEventArgs class	All
Oracle.ManagedDataAccess.Client	OracleRowsCopiedEventHandler class	All
Oracle.ManagedDataAccess.Types	IOracleArrayTypeFactory interface	All
Oracle.ManagedDataAccess.Types	IOracleCustomType interface	All
Oracle.ManagedDataAccess.Types	IOracleCustomTypeFactory interface	All
Oracle.ManagedDataAccess.Types	OracleArrayMappingAttribute class	All
Oracle.ManagedDataAccess.Types	OracleCustomTypeMappingAttribute class	All
Oracle.ManagedDataAccess.Types	OracleObjectMappingAttribute class	All

Table 1-8 (Cont.) Application Programming Interfaces not supported in ODP.NET, Managed Driver and ODP.NET Core

Namespace	Class/Enumeration/Interface	Unsupported Method/Property/Event
Oracle.ManagedDataAccess.Types	OracleRef class	All
Oracle.ManagedDataAccess.Types	OracleShardingKey class	All
Oracle.ManagedDataAccess.Types	OracleTimestampTZ structure	OracleTimeStampTZ(DateTime dt, string timeZone) constructor. This constructor is supported but the timeZone must be an hour offset.
Oracle.ManagedDataAccess.Types	OracleUdt class	All
Oracle.ManagedDataAccess.Types	OracleUdtFetchOption enumeration	All
Oracle.ManagedDataAccess.Types	OracleUdtStatus enumeration	All

ODP.NET Core supports the `OracleConfiguration`, `OracleDataSourceCollection`, and `OracleOnsServerCollection` classes, which are not present in managed nor unmanaged ODP.NET.

See Also:

[Oracle Data Provider for .NET, Managed Driver Configuration and Configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver](#) for more information about ODP.NET, Managed Driver .NET configuration settings.

[Distributed Transactions](#) for information about distributed transaction setup difference.

[Oracle Data Provider for .NET Core Configuration](#) for more information about configuring ODP.NET Core.

Using ODP.NET Client Provider in a Simple Application

The following is a simple C# application that connects to Oracle Database and displays its version number before disconnecting using ODP.NET, Unmanaged Driver:

```
// C#

using System;
using Oracle.DataAccess.Client;

class Sample
```

```
{
    static void Main()
    {
        // Connect to Oracle
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Display Version Number
        Console.WriteLine("Connected to Oracle " + con.ServerVersion);

        // Close and Dispose OracleConnection
        con.Close();
        con.Dispose();
    }
}
```

If you are using ODP.NET, Managed Driver or ODP.NET Core, then replace the contents of `Program.cs` with the following C# code. The namespace of ODP.NET, Managed Driver (`Oracle.ManagedDataAccess.*`) is different from the namespace of ODP.NET, Unmanaged Driver (`Oracle.DataAccess.*`)

```
// C#
using System;
using Oracle.ManagedDataAccess.Client;
using Oracle.ManagedDataAccess.Types;

namespace Connect
{
    class Program
    {
        static void Main(string[] args)
        {
            try
            {
                // Please replace the connection string attribute settings
                string constr = "user id=scott;password=tiger;data source=oracle";

                OracleConnection con = new OracleConnection(constr);
                con.Open();
                Console.WriteLine("Connected to Oracle Database {0}", con.ServerVersion);
                con.Dispose();

                Console.WriteLine("Press RETURN to exit.");
                Console.ReadLine();
            }
            catch (Exception ex)
            {
                Console.WriteLine("Error : {0}", ex);
            }
        }
    }
}
```

 **Note:**

Additional samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODACsamples` directory from Oracle Universal Installer ODAC installations. Microsoft Installer (MSI) ODAC installations include managed ODP.NET samples in the Oracle Developer Tools for Visual Studio subdirectory usually located in the `C:\Program Files (x86)` directory.

2

Installing and Configuring Oracle Data Provider for .NET

This section describes installation and configuration requirements for Oracle Data Provider for .NET.

This section contains these topics:

- [System Requirements](#)
- [Entity Framework Requirements](#)
- [Oracle Data Provider for .NET Versioning Scheme](#)
- [Installing Oracle Data Provider for .NET, Unmanaged Driver](#)
- [Installing Oracle Data Provider for .NET, Managed Driver](#)
- [Entity Framework Code First Assemblies and File Location](#)
- [Configuring Oracle Data Provider for .NET](#)
- [Oracle Data Provider for .NET, Unmanaged Driver Configuration](#)
- [Oracle Data Provider for .NET, Managed Driver Configuration](#)
- [Distributed Transactions](#)
- [Configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver](#)
- [Configuring for Entity Framework Code First](#)
- [Migrating from ODP.NET, Unmanaged Driver to ODP.NET, Managed Driver](#)
- [Configuring a Port to Listen for Database Notifications](#)
- [General .NET Programming Recommendations and Tips for ODP.NET](#)

System Requirements

Oracle Data Provider for .NET, Unmanaged Driver requires the following:

- Windows operating system
 - 64-bit: Windows 8.1 (Pro and Enterprise Editions), Windows Server 2012 R2 x64 (Standard, Datacenter, Essentials, and Foundation Editions), Windows 10 x64 (Pro, Enterprise, and Education Editions), Windows Server 2016 x64 (Standard, Datacenter, and Essentials Editions), or Windows Server 2019 (Standard, Datacenter, and Essentials Editions).

Oracle supports 32-bit ODP.NET and 64-bit ODP.NET for Windows x64 on these operating systems.

 **Note:**

ODP.NET does not support Itanium systems.

- Microsoft .NET Framework
 - ODP.NET for .NET Framework 2.0 is only supported with Microsoft .NET Framework 3.5 SP 1 and later.
 - ODP.NET for .NET Framework 4 is only supported with Microsoft .NET Framework 4.5.2, 4.6.x, and 4.7.x.
- Access to Oracle Database 11g Release 2 or later
- Oracle Client release 19c

This is automatically installed as part of the ODP.NET installation.

Promotable and distributed transactions may require Oracle Services for Microsoft Transaction Server in whole or in part. Refer to the [Distributed Transactions](#) section for more information.

Oracle Data Provider for .NET, Managed Driver requires the following:

- Same Windows operating system support as ODP.NET, Unmanaged Driver.
ODP.NET, Managed Driver is built with AnyCPU. It runs on either 32-bit or 64-bit (x64) Windows and on either 32-bit or 64-bit (x64) .NET Framework.
- Microsoft .NET Framework 4.5.2, 4.6.x, or 4.7.x.
- Access to Oracle Database 11g Release 2 or later

ODP.NET Core requires the following:

- Operating systems:
 - Same Windows operating system support as managed and unmanaged ODP.NET
 - Oracle Linux 7
 - Red Hat Enterprise Linux 7
- Microsoft .NET Framework
 - Microsoft .NET Core 2.1 or later
 - Microsoft .NET Framework 4.6.1 and later

 **Note:**

.NET Core 3.x is not currently supported.

- Access to Oracle Database 11g Release 2 or later

ODP.NET Core is compatible with ASP.NET Core 2.x and ASP.NET.

ODP.NET Core is built with AnyCPU. It supports 64-bit .NET and 32-bit .NET.

 **See Also:**

- Document 726240.1 on My Oracle Support (formerly *OracleMetaLink*) for details on supported configuration for different ODP.NET versions. You can access My Oracle Support from:
<https://support.oracle.com>
- <https://msdn.microsoft.com/en-us/default.aspx>

Entity Framework Requirements

This section contains the following topics:

- [Entity Framework Database First and Model First Requirements](#)
- [Entity Framework Code First Requirements](#)
- [Entity Framework 6 Requirements](#)

Entity Framework Database First and Model First Requirements

Oracle's support for Entity Framework Database First and Model First has the following version requirement:

- Microsoft Entity Framework 4 or higher, up to and including the 6.x versions.

If using Visual Studio tools, then use Visual Studio 2010 or higher and install Oracle Developer Tools for Visual Studio.

Entity Framework Code First Requirements

Oracle's support for Entity Framework Code First has the following version requirements:

- Microsoft Entity Framework 6 or higher
- Microsoft .NET Framework 4.5 or higher

Projects must set the target framework to .NET Framework 4.5 or higher. This can be done by modifying the project's properties in Visual Studio 2012 or higher.

Entity Framework 6 Requirements

Oracle's support for Entity Framework 6 has the following version requirement:

- Microsoft .NET Framework 4.5 or higher

Oracle Data Provider for .NET Versioning Scheme

Starting with 11.2.0.1.2, Oracle Data Provider for .NET, Unmanaged Driver ships with two sets of binaries: one set for .NET Framework 2.0 and another for .NET Framework 4. ODP.NET. Managed Driver ships with one set of binaries for .NET Framework 4. ODP.NET Core has one set of binaries for .NET Core.

For example, ODP.NET 11.2.0.1.2 binaries would be the following:

- ODP.NET for .NET Framework 4
 - Oracle.DataAccess.dll
 - * Built with .NET Framework 4
 - * Assembly version number: 4.x.x.x
 - OraOps11w.dll
 - * Used by ODP.NET for .NET Framework 2.0 and 4
- ODP.NET for .NET Framework 2.0
 - Oracle.DataAccess.dll
 - * Built with .NET Framework 2.0
 - * Assembly version number: 2.x.x.x
 - OraOps11w.dll
 - * Used by ODP.NET for .NET Framework 2.0 and 4

The convention for ODP.NET assembly/DLL versioning is

n1.o1o2.o3o4.o5

where:

- *n1* is the most significant .NET Framework version number.
- *o1o2* are the first two digits of the ODP.NET product version number.
- *o3o4* are the third and fourth digits of the ODP.NET product version number.
- *o5* is the fifth and last digit of the ODP.NET product version number.

For example, if the ODP.NET product version number is 11.2.0.2.0, the corresponding ODP.NET assembly versions are:

- .NET Framework 4 version: 4.112.2.0
- .NET Framework 2.0 version: 2.112.2.0

Note that the Oracle installer and documentation still refer to the ODP.NET product version number and not the assembly/DLL version number.

As with the .NET Framework system libraries, the first digit of the assembly version number indicates the version of the .NET Framework to use with an ODP.NET assembly.

Publisher Policy DLL is provided as before so that applications built with older versions of ODP.NET are redirected to the newer ODP.NET assembly, even though the versioning scheme has changed.

ODP.NET, Managed Driver follows a similar version model for its binaries.

ODP.NET for .NET Framework 4:

- Oracle.ManagedDataAccess.dll
 - Built with .NET Framework 4
 - Assembly version number: 4.x.x.x
- Oracle.ManagedDataAccessDTC.dll

- Used by ODP.NET for .NET Framework 4 for distributed transactions only.

ODP.NET, Managed Driver Versioning

Starting with ODAC 12c Release 2, the ODP.NET, Managed Driver uses assembly manifest attribute `AssemblyInformationalVersionAttribute` to uniquely identify assemblies with the same `AssemblyVersionAttribute` attribute value. This value can be accessed via .NET code, PowerShell, and other Windows applications to identify ODP.NET, Managed Driver versions uniquely.

`AssemblyInformationalVersionAttribute` is set to the same version as the actual .NET assembly version, except the fourth digit, which will no longer be 0. Instead, the version will be unique for each ODP.NET, Managed Driver release by incrementing the fourth digit for every subsequent release.

This value is accessible using .NET Framework `System.Diagnostics.FileVersionInfo.ProductVersion` property. The returned value can be used as a Version object or as a comparison String using comparison operators or methods. Essentially, among a collection of ODP.NET, Managed Driver assemblies that have the same assembly version, the newest ODP.NET, Managed Driver assembly will have the largest fourth digit `ProductVersion` value than an older assembly.

PowerShell Example: In this example, administrators uniquely distinguish the assemblies between ODP.NET, Managed Driver versions from an old version of ODP.NET, Managed Driver in `c:\old` and a more recent one in `c:\new`.

Script:

```
$VC1 = New-Object System.Version((Get-Command C:\old
\Oracle.ManagedDataAccess.dll).FileVersionInfo.ProductVersion)
$VC2 = New-Object System.Version((Get-Command C:\new
\Oracle.ManagedDataAccess.dll).FileVersionInfo.ProductVersion)
"Compare V1 to V2: " + $VC1.CompareTo($VC2)
"Compare V1 to V1: " + $VC1.CompareTo($VC1)
"Compare V2 to V1: " + $VC2.CompareTo($VC1)
```

Output:

```
Compare V1 to V2: -1
Compare V1 to V1: 0
Compare V2 to V1: 1
```

Note:

`ProductVersion` property comparisons will provide correct information on which version is more recent than the other *only* for ODP.NET, Managed Driver released from ODAC 12c Release 2 and later.

Installing Oracle Data Provider for .NET, Unmanaged Driver

Oracle Data Provider for .NET is part of Oracle Data Access Components (ODAC), which can be downloaded from OTN. Oracle Data Provider for .NET, Unmanaged Driver can be installed through XCopy or Oracle Universal Installer.

- XCopy
Administrators use XCopy to deploy Oracle Data Provider for .NET to large numbers of computers for production deployments. The XCopy has a smaller installation size and fine-grain control during installation and configuration than Oracle Universal Installer.
- Oracle Universal Installer (OUI)
Developers and administrators use Oracle Universal Installer for automated ODP.NET installations. It includes documentation and code samples that are not part of the XCopy.

 **Note:**

This section describes installation using the Oracle Universal Installer. For installation and configuration using the XCopy install, refer to the README.TXT file that is part of the XCopy installation.

Additionally, Oracle Data Provider for .NET Dynamic Help is registered with Visual Studio, providing context-sensitive online help that is seamlessly integrated with Visual Studio Dynamic Help. With Dynamic Help, the user can access ODP.NET documentation within the Visual Studio IDE by placing the cursor on an ODP.NET keyword and pressing the F1 function key.

Oracle Data Provider for .NET creates an entry in the `machine.config` file of the computer on which it is installed, for applications using the `OracleClientFactory` class. This enables the `DbProviderFactories` class to recognize ODP.NET.

ODP.NET, Unmanaged Driver Entity Framework 6 and Code First functionality are available through a NuGet package. OUI and Xcopy installations include this package as well, but require post-install configuration steps. The NuGet package for ODP.NET, Unmanaged Driver Entity Framework automates these post-install steps, except for the application-specific connection string settings.

 **See Also:**

[Configuring for Entity Framework Code First](#)

File Locations After Installation

The `Oracle.DataAccess.dll` assembly is installed to the following locations

.NET Framework 2.0:

`ORACLE_BASE\ORACLE_HOME\odp.net\bin\2.x` directory

.NET Framework 4:

`ORACLE_BASE\ORACLE_HOME\odp.net\bin\4` directory

 **Note:**

If the machine has the corresponding .NET Framework installed, then the `Oracle.DataAccess.dll` assembly is added to the Global Assembly Cache (GAC) if machine-wide configuration is set. This is to ensure that existing applications can start using the newly installed ODP.NET version immediately. If this is not desired, then be sure to remove the policy DLLs from the GAC or choose non-machine-wide configuration.

Documentation and the `readme.txt` file can be accessed through `ORACLE_BASE\ORACLE_HOME\ODACDoc\DocumentationLibrary\doc\index.htm` in ODAC installations done using Oracle Universal Installer. When Oracle Developer Tools for Visual Studio is installed, Oracle documentation is installed in Visual Studio itself.

Samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODACsamples` directory for ODAC installations done using Oracle Universal Installer.

Search Order for Unmanaged DLLs

ODP.NET consists of managed and unmanaged binaries. Through the use of the `DllPath` configuration parameter, each application can specify the `ORACLE_BASE\ORACLE_HOME\bin` location that the dependent unmanaged Oracle Client binaries are loaded from. However, the `ORACLE_BASE\ORACLE_HOME` must have the same ODP.NET version installed as the version that the application uses. Otherwise, a version mismatch exception is thrown.

The `Oracle.DataAccess.dll` searches for dependent unmanaged DLLs (such as Oracle Client) based on the following order:

1. Directory of the application or executable.
2. `DllPath` setting specified by application config or `web.config`.
3. `DllPath` setting specified by `machine.config`.
4. `DllPath` setting specified by the Windows Registry.
`HKEY_LOCAL_MACHINE\Software\Oracle\ODP.NET\version\DllPath`
5. Directories specified by the Windows `PATH` environment variable.

Upon installation of ODP.NET, Oracle Universal Installer sets the `DllPath` Windows Registry value to the `ORACLE_BASE\ORACLE_HOME\bin` directory where the corresponding dependent DLLs are installed. Developers must provide this configuration information on an application-by-application basis.

When a new ODP.NET version is installed, default values are set in the Windows Registry for the new version. Because the policy DLLs redirect all ODP.NET references to this new ODP.NET version, applications use the default values. Developers can provide a config or `web.config` file specific to the application to prevent this redirection. The configuration file settings always apply to the application, regardless of whether or not patches or new versions are installed later.



Note:

Both `Oracle.DataAccess.dll` for .NET Framework 2.0 and `Oracle.DataAccess.dll` for .NET Framework 4 use the same unmanaged DLL, `OraOps12.dll`.

ODP.NET and Dependent Unmanaged DLL Mismatch

To enforce the usage of `Oracle.DataAccess.dll` assembly with the correct version of its unmanaged DLLs, an exception is raised if `Oracle.DataAccess.dll` notices it has loaded a mismatched version of a dependent unmanaged DLL.

Installing Oracle Data Provider for .NET, Managed Driver

Getting started with ODP.NET, Managed Driver

You can get started with ODP.NET Managed Driver by either using the Windows Installer, Oracle Universal Installer (OUI), XCopy, or NuGet.

If you are using OUI: Follow the Oracle Universal Installer (OUI) steps to install ODP.NET, Managed Driver

If you are using XCopy: Download ODP.NET, Managed Driver .zip file to a directory for staging the install. The .zip file contains a README file with XCopy installation instructions.

Run the `configure.bat` script in one of the following directories:

- For 32-bit .NET Framework: `OH\odp.net\managed\x86`
- For 64-bit .NET Framework: `OH\odp.net\managed\x64`

Each directory contains an `unconfigure.bat` if ODP.NET, Managed Driver needs to be unconfigured and removed from the machine.

If you are using NuGet: Download the ODP.NET NuGet package(s) and use NuGet Package Manager to install.

The following NuGet packages are available:

- ODP.NET, Managed Driver
- Entity Framework assembly for Code First and Entity Framework 6 or higher use with ODP.NET, Managed Driver

If you are using Windows Installer: Follow the Microsoft Windows Installer (MSI) steps to install ODP.NET, Managed Driver.

ODP.NET, Managed Driver Files

ODP.NET, Managed Driver consists of the following files:

Table 2-1 ODP.NET, Managed Driver Files with Descriptions

File	Description
Oracle.ManagedDataAccess.dll	Platform-independent (AnyCPU), fully-managed ADO.NET provider
\Resources\<<lang> \Oracle.ManagedDataAccess.resources. dll	Platform-independent (AnyCPU), fully-managed ADO.NET provider resource DLLs.
OraProvCfg.exe	Platform-independent (AnyCPU) utility to configure/unconfigure ODP.NET, Managed and Unmanaged Drivers.
configure.bat	Batch file to place ODP.NET, Managed Driver into the GAC and add configuration entries into the machine.config.
unconfigure.bat	Batch file to remove ODP.NET, Managed Driver from the GAC and remove configuration entries from machine.config.
tnsnames.ora	A sample configuration file that defines data source aliases.
sqlnet.ora	A sample configuration file that configures network related settings.
ConfigSchema.xsd	An XML schema file that defines the configuration section for ODP.NET, Managed Driver.
Oracle.ManagedDataAccess.EntityFramework. work.dll	Platform-independent (AnyCPU), fully-managed assembly for Code First and Entity Framework 6 higher
\x64\Oracle.ManagedDataAccessIOP.dll	Platform-dependent (64-bit .NET Framework), Managed Assembly for Kerberos support
\x86\Oracle.ManagedDataAccessIOP.dll	Platform-dependent (32-bit .NET Framework), Managed Assembly for Kerberos support

 **See Also:**

Oracle Database Installation Guide for Microsoft Windows for installation instructions

Platform-Dependent Assemblies and Their Search Order

ODP.NET, Managed Driver has one set of platform-dependent DLL: Oracle.ManagedDataAccessIOP.dll, which has a 32-bit .NET version and a 64-bit .NET version. While they consist of 100% managed code, they call APIs outside of .NET, which is why they are platform dependent.

Oracle.ManagedDataAccessIOP.dll supports Kerberos. These assemblies are only needed in your application if you are using Kerberos security.

These assemblies are not intended to be directly referenced by an application. Rather, they will be referenced implicitly. ODP.NET, Managed Driver will reference the assemblies by using the following search order:

1. Global Assembly Cache
2. The web application's bin directory or Windows application's EXE directory
3. The x86 or x64 subdirectory based on whether the application runs in 32-bit or 64-bit .NET Framework. If the application is built using AnyCPU, then ODP.NET will use the correct DLL bitness as long as the assembly is available. Oracle recommends using this method of finding dependent assemblies if your application is AnyCPU.

For example, use the following steps for your application to use the 64-bit version of `Oracle.ManagedDataAccessIOP.dll`:

1. Right click **Visual Studio project**, select **Add**, and then select **New Folder**.
2. Name the folder x64.
3. Right-click the newly created **x64** folder, select **Add**, and then select **Existing Item**.
4. Browse to the folder where the DLL is located, which usually is `ORACLE_HOME\odp.net\managed\x64`, and then select **Oracle.ManagedDataAccessIOP.dll**.
5. Click **Add**.
6. Click the newly added **Oracle.ManagedDataAccessIOP.dll** in the x64 folder.
7. In the properties window, set Copy To Output Director to **Copy Always**.

For x86 targeted applications, name the folder x86 and add the assembly from the x86 directory.

To make your application platform independent even if it depends on `Oracle.ManagedDataAccessIOP.dll` create both x64 and x86 folders with the necessary assemblies added to them.

File Locations After Installation

In an Oracle Universal Installer based install, the `Oracle.ManagedDataAccess.dll` assembly is installed to the following location:

.NET Framework 4:

`ORACLE_BASE\ORACLE_HOME\odp.net\managed\common` directory

Documentation and the `readme.txt` file can be accessed through `ORACLE_BASE\ORACLE_HOME\ODACDoc\DocumentationLibrary\doc\index.htm` in ODAC installations done using Oracle Universal Installer. When Oracle Developer Tools for Visual Studio is installed, Oracle documentation is installed in Visual Studio itself.

Samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODACsamples` directory for ODAC installations done using Oracle Universal Installer or the Oracle Developer Tools for Visual Studio subdirectory usually located in the `C:\Program Files (x86)` directory for ODAC MSI installs.

Installing Oracle Data Provider for .NET Core

Getting started with ODP.NET Core

You can get started with ODP.NET Core on Windows by using the Windows Installer, Oracle Universal Installer (OUI), or NuGet. Only NuGet can be used to install ODP.NET Core on Linux.

If you are using Windows Installer: Follow the Oracle Developer Tools for Visual Studio Microsoft Windows Installer (MSI) steps. MSI will copy the ODP.NET Core NuGet package to the machine.

If you are using OUI: Follow the ODAC OUI steps to install ODP.NET Core. OUI will copy the ODP.NET Core NuGet package to the machine.

If you are using NuGet: Download the ODP.NET Core NuGet package and use NuGet Package Manager to install.

ODP.NET Core Files

ODP.NET Core consists of the following files:

Table 2-2 ODP.NET, Core Files with Descriptions

File	Description
<code>Oracle.ManagedDataAccess.dll</code>	Platform-independent (AnyCPU), operating system independent, fully-managed ADO.NET provider

File Locations After Installation

In an Oracle Universal Installer based install, the ODP.NET Core package is installed to the following directory:

`ORACLE_BASE\ORACLE_HOME\odp.net\Core2`

Documentation and the `readme.txt` file can be accessed through `ORACLE_BASE\ORACLE_HOME\ODACDoc\DocumentationLibrary\doc\index.htm` in ODAC installations done using Oracle Universal Installer. When Oracle Developer Tools for Visual Studio is installed, Oracle documentation is installed in Visual Studio itself.

Samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODACsamples` directory for ODAC installations done using Oracle Universal Installer or the Oracle Developer Tools for Visual Studio subdirectory usually located in the `C:\Program Files (x86)` directory for ODAC MSI installs.

Entity Framework Code First Assemblies and File Location

ODP.NET now ships with a separate assembly to support Code First and Entity Framework 6. This functionality resides in a dedicated assembly, while the ADO.NET and earlier Entity Framework version functionality resides in the main ODP.NET assembly. This model physically separates Entity Framework 6 functionality from ADO.NET functionality.

This ODP.NET assembly is:

- `Oracle.DataAccess.EntityFramework.dll` for ODP.NET, Unmanaged Driver.
- `Oracle.ManagedDataAccess.EntityFramework.dll` for ODP.NET, Managed Driver.

Whether it is installed using the Oracle Universal Installer or the XCopy package, the Oracle Entity Framework assemblies may be found in the following location after install (where `%ORACLE_HOME%` represents the operating system path to the installation directory):

For Unmanaged Driver:

```
%ORACLE_HOME%\odp.net\bin\4\EF6\Oracle.DataAccess.EntityFramework.dll
```

For Managed Driver:

```
%ORACLE_HOME%\odp.net\managed\common  
\EF6\Oracle.ManagedDataAccess.EntityFramework.dll
```

Both assemblies are compiled as Any CPU and therefore there is no need for separate 32-bit and 64-bit versions of the assemblies. Each assembly is designed to be `bin` deployable meaning that the assembly should be copied into the application's `bin` directory. As such the assemblies are not registered in the Global Assembly Cache (GAC) during installation.

 **Note:**

If desired the Oracle Entity Framework 6 assemblies may be registered in the GAC manually but Oracle recommends not doing so.

Configuring Oracle Data Provider for .NET

The settings for specific versions of ODP.NET, can be configured in several ways for specific effects on precedence:

- The Windows registry entries are machine-wide settings for a particular version of ODP.NET.
Windows registry based configuration is not supported for ODP.NET, Managed Driver.
- The `machine.config` settings are .NET framework-wide settings that override the Windows registry values.
- The application or web config file settings are application-specific settings that override the `machine.config` settings and the Windows registry settings.

 **Note:**

There is one exception to `app/web/config` settings overriding `machine.config`. For `oracle.manageddataaccess.client` and `oracle.unmanageddataaccess.client` sections, a `machine.config` with a specific ODP.NET version subsection, that is, `<version number="4.121.2.0">`, will override an `app/web.config` subsection that references all versions generically, that is, `<version number="*">`. To override the `machine.config` subsection, create a subsection for that version in the `app/web/config` file, that is, `<version number="4.121.2.0">`.

- Any attribute settings that are equivalent to the connection string override everything.

The application or web config file can be useful and sometimes essential in scenarios where more than one application on a computer use the same version of ODP.NET, but each application needs a different ODP.NET configuration. The Windows registry value settings for a given version of ODP.NET affect all the applications that use that version of ODP.NET. However, having ODP.NET configuration values in the application or web config file assure that these settings are applied only for that application, thus providing more granularities.

For example, if the application or `web.config` file has a `StatementCacheSize` configuration setting of 100, this application-specific setting forces the version of ODP.NET that is loaded by that application to use 100 for the `StatementCacheSize` and overrides any setting in the `machine.config` and in the registry. Note that for any setting that does not exist in a config file (`machine.config` or application/web config), the value in the registry for a loaded version of ODP.NET is used, as in previous releases.

Note that ODP.NET reads the `machine.config` files from the version of the .NET Framework on which ODP.NET runs, not from the version of ODP.NET.

ODP.NET only reads the Windows Registry and the XML configuration file when it is loaded into memory, thus any configuration changes made after that are not read or used until the application is re-started.

All boolean attributes in ODP.NET .NET configuration settings accept `true`, `false`, `1`, and `0` as valid values. `1` is equivalent to `true` and `0` is equivalent to `false`.

 **Note:**

ODP.NET Core does not support the Windows registry nor .NET configuration files. ODP.NET Core configuration can be set using .NET Configuration API, `sqlnet.ora` file, and `tnsnames.ora` file.

Oracle Client Configuration File Automated Setup During Installation

When installing Oracle Data Access Components (ODAC) in a new Oracle Home, Oracle Universal Installer (OUI) automatically copies the Oracle local naming (`tnsnames.ora`), profile (`sqlnet.ora`), and directory (`ldap.ora`) parameter files and

settings from an existing Oracle home into the newly installed ODAC home, as long as they share the same bitness. That is, they are both 32-bit installations or they are both 64-bit installations.

Alternatively, existing *.ora files can be copied over from another existing Oracle home, besides the last active one, to the new ODAC Oracle home. OUI provides location information for these files from up to three other existing Oracle homes if they exist. The *.ora files can be customized if the new Oracle home uses a different configuration from the previous Oracle home from which the files were copied over.

If you install into an existing ODAC or RDBMS Oracle home, then no new *.ora files is copied or created.

If you install onto a computer without any previous Oracle homes present, then OUI prompts the user for the database connection alias information. OUI then automatically creates the tnsnames.ora file. If no alias information is provided, then no tnsnames.ora file is created. Even if the user does not have all the database connection information readily available, Oracle recommends inserting placeholder values during the install process, then modifying the tnsnames.ora file later with actual values to replace the placeholders.

Oracle Client Configuration File Settings

ODP.NET tnsnames.ora, sqlnet.ora, and ldap.ora parameter values can be set in a .NET configuration file or within the *.ora file itself. The *.ora file location can be a location different from the standard *ORACLE_HOME/network/admin* directory. The *.ora settings order of precedence is similar to ODP.NET's settings order of precedence. The main difference is that the *.ora files themselves are included in the search order. The tnsnames.ora and sqlnet.ora precedence order is as follows:

1. app.config Or web.config
2. machine.config
3. File location specified by TNS_ADMIN setting
4. The current .EXE or web application root directory
5. %ORACLE_HOME%\network\admin if using ODP.NET, Unmanaged Driver

The ldap.ora precedence order is as follows:

1. app.config Or web.config
2. machine.config
3. File location specified by TNS_ADMIN setting in .NET config file
4. File location specified by LDAP_ADMIN setting in .NET config file
5. The current .EXE or web application root directory
6. %ORACLE_HOME%\network\admin if using ODP.NET, Unmanaged Driver
7. %ORACLE_HOME%\ldap\admin if using ODP.NET, Unmanaged Driver

Oracle recommends using an app.config or web.config file to store all these Oracle Client configuration parameter settings.

Once the first tnsnames.ora, sqlnet.ora, and ldap.ora are found and read, no additional *.ora file lower in the precedence order is read. That means all Oracle Client configuration settings must be made in the app.config, web.config,

machine.config, or the first set of *.ora files found. Additional parameter values set in *.ora files lower in the precedence order will not be read.

Configuring .NET Framework to Use ODP.NET

Automatic ODP.NET machine-wide configuration upon installation is no longer available as of ODAC 18c. This change improves compatibility when applications on the same machine use different ODP.NET versions and/or depend on application-specific configuration settings instead of machine-wide assembly registration and configuration.

Nonetheless, administrators can still manually place managed and unmanaged ODP.NET in the Global Assembly Cache (GAC), as well as add configurations for section handler, DbProviderFactories, TNS_ADMIN, LDAP_ADMIN, and assembly redirection (in place of policy DLLs), into machine.config, if desired.

Most ODP.NET settings in machine.config can be overridden by local settings in app.config or web.config. However, conflicts between the machine.config and, app.config or web.config can prevent applications from running properly. Care should be taken when configuring ODP.NET at both the machine.config level and application level using app.config or web.config.

To avoid such issues, Oracle recommends ODP.NET application configuration settings reside in the app.config or web.config. The following sections explore how to set up these ODP.NET configuration sections and provide sample configuration sections and files.

Configuration Section Handler

In order for the application to read the ODP.NET configuration section, a section handler must be configured. The following entry should be added to the .NET configuration file to enable applications to add an oracle.manageddataaccess.client section for ODP.NET, Managed Driver-specific configuration:

```
<configuration>
  <configSections>
    <section name="oracle.manageddataaccess.client"
      type="OracleInternal.Common.ODPMSectionHandler, Oracle.ManagedDataAccess,
      Version=4.122.19.1, Culture=neutral, PublicKeyToken=89b483f429c47342" />
    </configSections>
  </configuration>
```

 **Note:**

In all the examples in this section, the version of the ODP.NET assembly is understood to be 4.122.19.1. This version number should be modified appropriately if you are using another version.

The unmanaged ODP.NET equivalent section handler is as follows:

```
<configuration>
  <configSections>
    <section name="oracle.unmanageddataaccess.client"
      type="OracleInternal.Common.CustomSectionHandler, Oracle.DataAccess,
      Version=4.122.19.1, Culture=neutral, PublicKeyToken=89b483f429c47342" />
  </configuration>
```

```

    </configSections>
  </configuration>

```

One of the configuration entries that either has to match between `machine.config` and, `app.config` or `web.config`, or only exist in the `app.config` or `web.config` to avoid any conflict is the configuration for the section handler. For example, if your application is a web application and the above entry was added to a `web.config` and the same configuration section handler for `oracle.manageddataaccess.client` also exists in `machine.config` but the `Version` attribute values are different, an error message of "There is a duplicate `oracle.manageddataaccess.client` section defined." may be observed at runtime. To avoid this issue, the configuration section handler entry in the `machine.config` for `oracle.manageddataaccess.client` has to be removed from the `machine.config` or the ODP.NET config section handler entry in `machine.config` and `web.config` has to match exactly. If there are other applications on the machine that depend on this entry in the `machine.config`, then this section handler entry will need to be moved to all local applications' .NET configuration files.

DbProviderFactories

The following entry should be added in the `app.config` or `web.config` for applications that use `DbProviderFactories` and `DbProviderFactory` classes. Also, any `DbProviderFactories` entry for `Oracle.ManagedDataAccess.Client` in the `machine.config` will be ignored due to the `<remove>` entry:

```

<configuration>
  <system.data>
    <DbProviderFactories>
      <remove invariant="Oracle.ManagedDataAccess.Client" />
      <add name="ODP.NET, Managed Driver"
invariant="Oracle.ManagedDataAccess.Client" description="Oracle Data Provider
for .NET, Managed Driver" type="Oracle.ManagedDataAccess.Client.OracleClientFactory,
Oracle.ManagedDataAccess, Version=4.122.19.1, Culture=neutral,
PublicKeyToken=89b483f429c47342" />
    </DbProviderFactories>
  </system.data>
</configuration>

```

The equivalent for unmanaged ODP.NET is as follows:

```

<configuration>
  <system.data>
    <DbProviderFactories>
      <remove invariant="Oracle.DataAccess.Client" />
      <add name="Oracle Data Provider for .NET" invariant="Oracle.DataAccess.Client"
description="Oracle Data Provider for .NET"
type="Oracle.DataAccess.Client.OracleClientFactory, Oracle.DataAccess,
Version=4.122.19.1, Culture=neutral, PublicKeyToken=89b483f429c47342" />
    </DbProviderFactories>
  </system.data>
</configuration>

```

Dependent Assembly

For users accustomed to the policy DLLs that were registered automatically upon installation, the same can be accomplished through configuration. The following is an example configuration that redirects the application that depends on 4.122 version of ODP.NET and higher to be redirected to use ODP.NET 4.122.19.1. Note that in this example, an entry is added to ignore policy ODP.NET DLLs that are registered in the GAC:

```

<configuration>
  <runtime>
    <assemblyBinding xmlns="urn:schemas-microsoft-com:asm.v1">
      <dependentAssembly>
        <publisherPolicy apply="no" />
        <assemblyIdentity name="Oracle.ManagedDataAccess"
publicKeyToken="89b483f429c47342" culture="neutral" />
        <bindingRedirect oldVersion="4.122.0.0 - 4.65535.65535.65535"
newVersion="4.122.19.1" />
      </dependentAssembly>
    </assemblyBinding>
  </runtime>
</configuration>

```

The equivalent for unmanaged ODP.NET is as follows:

```

<configuration>
  <runtime>
    <assemblyBinding xmlns="urn:schemas-microsoft-com:asm.v1">
      <dependentAssembly>
        <publisherPolicy apply="no" />
        <assemblyIdentity name="Oracle.DataAccess" publicKeyToken="89b483f429c47342"
culture="neutral" />
        <bindingRedirect oldVersion="4.122.0.0 - 4.65535.65535.65535"
newVersion="4.122.19.1" />
      </dependentAssembly>
    </assemblyBinding>
  </runtime>
</configuration>

```

Oracle Data Provider for .NET, Unmanaged Driver Configuration

The following sections explain how to configure ODP.NET, Unmanaged Driver.

ODP.NET can be configured using an XML file named `web.config`, `app.config`, or `machine.config`. These config files contain sections specific to ODP.NET configuration.

For unmanaged ODP.NET, developers use either the traditional `<oracle.dataaccess.client>` section or the newer `<oracle.unmanageddataaccess.client>` section. Oracle recommends applications use `<oracle.unmanageddataaccess.client>` when possible. For managed ODP.NET, developers use `<oracle.manageddataaccess.client>`.

`<oracle.unmanageddataaccess.client>` is a superset of `<oracle.manageddataaccess.client>` as unmanaged ODP.NET supports some features not available in the managed driver. For features both providers have in common, they share the same structure, properties, and nearly all values. Programmers will find using either provider interchangeably or migrating between unmanaged and managed ODP.NET is easier with the shared format.

This documentation section covers unmanaged ODP.NET configuration settings in the Windows registry, `<oracle.dataaccess.client>`, or unique `<oracle.unmanageddataaccess.client>` settings. For shared settings with `<oracle.manageddataaccess.client>`.



See Also:

[Oracle Data Provider for .NET, Managed Driver Configuration](#)

Supported Configuration Settings

ODP.NET, Unmanaged Driver supports the configuration of an attribute as follows:

- In the Windows registry.
- In an XML file.
- Through a different mechanism such as a connection string or programmatically through an ODP.NET class, if applicable.

[Table 2-3](#) describes each configurable attribute that is supported by ODP.NET. In the table, the term Configuration Support is followed by the types of configuration support (Windows registry, XML file, and so on) that are available for that attribute.

The table describes valid values as well as the default for each attribute.



Note:

The default values shown are the values used for an attribute if the registry key does not exist or if it is not configured anywhere.

Table 2-3 Configuration Attributes

Attribute/Setting Name	Description
CheckConStatus	<p>Specifies whether the status of the connection is checked or not before putting the connection back into the connection pool. This registry entry is not created by the installation of ODP.NET. However, the default value 1 is used.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>1: Check the status of the connection. 0: Do not check the status of the connection.</p> <p>Default: 1</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
DbNotificationPort	<p>Specifies the port number which ODP.NET listens to, for all notifications sent by the database for change notification, HA, or RLB features. ODP.NET does not throw any errors if an invalid or used port number is specified. The port can also be set to override the Windows registry and XML configuration file by setting the <code>OracleDependency.Port</code> static field.</p> <p>Configuration Support: XML file, and ODP.NET class</p> <p>Valid Values: -1: Open a random unused port to listen to. $n \geq 0$: Listen on port n.</p> <p>Default: -1</p>
DemandOraclePermission	<p>Specifies whether ODP.NET demands <code>OraclePermission</code> from the .NET application that is trying to access the database using ODP.NET.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0: Disables demands for <code>OraclePermission</code>. 1: Enables demands for <code>OraclePermission</code></p> <p>Default: 0</p>
DllPath	<p>Specifies the location where dependent unmanaged Oracle Client binaries load from.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: The path where dependent unmanaged Oracle Client binaries reside.</p> <p>Default: <code>ORACLE_BASE\ORACLE_HOME\bin</code></p>
DynamicEnlistment	<p>Due to a behavior change with the ODAC 12c Release 3 version of ODP.NET connection string attribute <code>enlist=dynamic</code>, <code>DynamicEnlistment</code> has no operation now.</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
FetchSize	<p>Specifies the total memory size, in bytes, that ODP.NET allocates to cache the data fetched from a database round-trip. This value can be set on the <code>OracleCommand</code> and the <code>OracleDataReader</code> <code>FetchSize</code> property as well.</p> <p>Configuration Support: Windows Registry, XML file, and ODP.NET class</p> <p>Valid Values: $0 \leq n \leq \text{int.MaxValue}$: n is the size of the cache in bytes.</p> <p>Default: 131072</p>
LegacyEntireLobFetch	<p>Returns either <code>OracleBlob</code> and <code>OracleClob</code> types or <code>OracleBinary</code> and <code>OracleString</code> types from Oracle Database BLOB and CLOB columns. This setting only applies when <code>InitialLobFetchSize</code> is set to -1.</p> <p>Valid Values: 0: Returns <code>OracleBlob</code> and <code>OracleClob</code> 1: Returns <code>OracleBinary</code> and <code>OracleString</code></p> <p>Default: 0</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
LegacyTransactionBindingBehavior	<p>Specifies when a database connection detaches from a <code>System.Transactions</code> transaction. By default, connections detach from a transaction only when explicitly unbound as is the case when the connection closes or implicitly unbound when the transaction is disposed. Alternatively, this attribute can be set so that the connection detaches whenever the transaction ends (commits, aborts, or times out), the connection closes, or the transaction is disposed.</p> <p>In ODP.NET 11.2.0.3.20 and earlier releases, the latter was the default behavior. Oracle recommends using the current default behavior.</p> <p>In the earlier default behavior, when the timeout elapses before the transaction completes, the connection unbinds itself from the transaction and all subsequent executions on this connection execute in <code>AutoCommit</code> mode. Any operations prior to the timeout roll back, but operations performed after the timeout commit.</p> <p>In the current default setting, users receive an exception when the transaction times out and additional operations execute on the connection.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0: Connections detach from transaction when the connection closes or the transaction is disposed.</p> <p>1: Connections detach from transaction when the connection closes, the transaction is disposed, or the transaction completes (commits, rolls back, times out).</p> <p>Default: 0</p>
MaxStatementCacheSize	<p>Specifies the maximum number of statements that can be cached when self-tuning is enabled.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0 to <code>System.Int32.MaxValue</code>.</p> <p>Default: <code>OPEN_CURSORS</code> setting value of the database</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
MetaDataXml	<p>Specifies the name of the XML file that customizes the queries to obtain the metadata the ADO.NET 2.0 <code>GetSchema</code> method returns. MetaDataXml can only be set in a configuration file.</p> <p>Configuration Support: XML file only</p> <p>Valid Values: A complete file name for the XML file.</p> <p>Default: <i>none</i></p>
PerformanceCounters	<p>Enables or disables publishing performance counters for connection pooling. Multiple performance counters can be obtained by adding the valid values.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <ul style="list-style-type: none"> 0: Not Enabled 1: Number of sessions being established with Oracle Database every second. 2: Number of sessions being severed from Oracle Database every second. 4: Number of active connections originating from connection pools every second. 8: Number of active connections going back to the connection pool every second. 16: Total number of active connections. 32: Number of inactive connection pools. 64: Total number of connections in use. 128: Total number of connections available for use in all the connection pools. 256: Total number of pooled active and free connections. 512: Number of non-pooled active connections 1024: Number of connections which were garbage-collected implicitly. 2048: Number of connections that will be soon available in the pool. User has closed these connections, but they are currently awaiting actions, such transaction completion, before they can be placed back into the pool as free connections. 4095: All the above <p>Default: 0</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
PromotableTransaction	<p>Specifies the type of transaction to use when the first connection participates in the TransactionScope object.</p> <p>Configuration Support: Windows Registry, XML file, and <i>promotable transaction</i> connection string attribute</p> <p>Valid Values:</p> <p>local: The first connection opened in the TransactionScope object uses a local transaction.</p> <p>promotable: The first connection and all subsequent connections opened in the same TransactionScope object enlist in the same distributed transaction.</p> <p>Default: promotable</p> <p><i>This property has been deprecated in 12.2.0.1. It will be desupported in a future release.</i></p>
SelfTuning	<p>Specifies whether self-tuning is enabled for an ODP.NET application.</p> <p>Configuration Support: Windows Registry, XML file, and Self Tuning connection string attribute</p> <p>Valid Values:</p> <p>0: Self Tuning is disabled. Used in the registry or XML file.</p> <p>false: Self Tuning is disabled. Used for the Self Tuning connection string attribute.</p> <p>1: Self Tuning is enabled. Used in the registry or XML file.</p> <p>true: Self Tuning is enabled. Used for the Self Tuning connection string attribute.</p> <p>Default: 1</p>
StatementCacheSize	<p>Specifies the number of cursors or statements to be cached on the database for each connection. This setting corresponds to <i>Statement Cache Size</i> attribute in the connection string. A value greater than zero also enables statement caching.</p> <p>Configuration Support: Windows Registry, XML file, and <i>Statement Cache Size</i> connection string attribute</p> <p>Valid Values:</p> <p>0 <= <i>n</i> <= the value of OPEN_CURSORS parameter set in <i>init.ora</i> database config file.</p> <p><i>n</i> is the number to set.</p> <p>Default: 0</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
StatementCacheWithUdts	<p>Specifies whether or not Oracle UDTs retrieved by executing a <code>SELECT</code> statement are cached along with the statement in the statement cache. This setting affects the memory usage and performance of the application.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0: Oracle UDTs are not cached with statements.</p> <p>1: Oracle UDTs are cached along with statements.</p> <p>Default: 1</p>
ThreadPoolMaxSize	<p>Specifies the default maximum size of worker threads for each available processor in a process. This value may affect the performance of ODP.NET connection creation, command execution timeout, and external procedures (<code>extproc</code>) that use the thread pool. However, unnecessarily increasing thread pool maximum size can also cause performance problems.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>$0 \leq n \leq \text{int.MaxValue}$: Allows ODP.NET to reset thread pool maximum size with the value n. The ODP.NET reset operation may be ignored if the value is invalid. For example, if n is less than the number of available processors of the system. In this case, the result is the same as the value -1.</p> <p>-1: Leave the thread pool max size as is.</p> <p>Default: -1 (this registry entry is not created by default)</p> <p>Note that prior to ODAC 2007 or version 11.1.0.6.20, ODP.NET resets the thread pool maximum size to <code>int.MaxValue</code> when the <code>OracleCommand.CommandTimeout</code> property is set to a value greater than 0. This erroneous behavior has been corrected.</p> <p><code>OracleCommand.CommandTimeout</code> does not change thread pool maximum size.</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
TraceFileName	<p>Specifies the file name to be used for logging trace information.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: Any valid directory location and file name.</p> <p>Default: c:\odpnet2.trc (for .NET Framework 2.0)</p>
TraceLevel	<p>Specifies the level of tracing in ODP.NET. Because tracing all the entry and exit calls for all the objects can be excessive, <code>TraceLevel</code> is provided to limit tracing to certain areas of the provider. Each valid value indicates a possible tracing level. Compounded tracing levels can be obtained by adding the valid values.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0: None 1: Entry, exit, and SQL statement information 2: Connection pooling statistics 4: Distributed transactions (enlistment and delistment) 8: User-mode dump creation upon unmanaged exception 16: HA Event Information 32: Load Balancing Information 64: Self Tuning Information 127: All the above</p> <p>Default: 0</p> <p>Note: ODP.NET does bit-wise checking on the value. When tracing is enabled, logging to the trace file can affect ODP.NET performance.</p> <p>Note: The user-mode dump creation requires <code>dbghelp.dll</code> version 5.1.2600.0 or later.</p>

Table 2-3 (Cont.) Configuration Attributes

Attribute/Setting Name	Description
TraceOption	<p>Specifies whether to log trace information in single or multiple files for different threads. If a single trace file is specified, the file name specified in <code>TraceFileName</code> is used. If the multiple trace files option is requested, a Thread ID is appended to the file name provided to create a trace file for each thread.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0: Single trace file 1: Multiple trace files Default: 0</p>
UdtCacheSize	<p>Specifies the size of the object cache for each connection in kilobytes (KB) that ODP.NET uses to retrieve and manipulate Oracle UDTs.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: $0 \leq n \leq 4194303$, n is the number to set. Default: 4096</p>
UDT Mapping	<p>Specifies a mapping between a custom type and an Oracle UDT in the database. The mappings can be specified in configuration files and custom type factories. However, if the mapping is specified in both places, mappings specified in the configuration files takes precedence over mappings specified using custom type factories.</p> <p>Configuration Support: XML file and Custom Type Factory Classes</p> <p>Valid Values: Any valid mapping. Default: <i>none</i></p>

Windows Registry

Upon installation, ODP.NET creates entries for configuration and tracing within the Windows Registry. Configuration and tracing registry values apply across all ODP.NET applications running in that Oracle client installation. Individual ODP.NET applications can override some of these values by configuring them within the ODP.NET application itself (for example, `FetchSize`). Applications can also use the .NET configuration files to override some of the ODP.NET Windows Registry values.

The ODP.NET registry values are located under `HKEY_LOCAL_MACHINE\Software\Oracle\ODP.NET\version\`. There is one key for .NET Framework 3.5, and one key for .NET Framework 4 and later.

 **Note:**

32-bit applications running on an x64-based version of Windows use the registry subkey, `HKEY_LOCAL_MACHINE\Software\WOW6432node` in place of `HKEY_LOCAL_MACHINE\Software`. If such applications use Oracle Data Provider for .NET (32-bit), then the ODP.NET registry values are located under `HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\Oracle\ODP.NET\version\`.

Configuration File Support

For customers who have numerous applications on a computer that depends on a single version of ODP.NET, the Windows Registry settings for a given version of ODP.NET may not necessarily be applicable for all applications that use that version of ODP.NET. To provide more granular control, ODP.NET Configuration File Support allows developers to specify ODP.NET configuration settings in an application config, `web.config`, or a `machine.config` file.

If a computer does not require granular control beyond configuration settings at the ODP.NET version level, there is no need to specify ODP.NET configuration settings through configuration files.

The following is an example of a `web.config` file for .NET Framework 2.0 and later:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DllPath" value="C:\oracle\bin"/>
      <add name="FetchSize" value="131072"/>
      <add name="StatementCacheSize" value="10"/>
      <add name="TraceFileName" value="D:\odpnet2.trc"/>
      <add name="TraceLevel" value="63"/>
      <add name="TraceOption" value="1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

The following is an example of `app.config` for ODP.NET, Unmanaged Driver using .NET Framework 2.0, which sets some additional attributes as well as two UDT type mappings:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DbNotificationPort" value="-1"/>
      <add name="DllPath" value="C:\app\user\product\11.1.0\client_1\bin"/>
      <add name="DynamicEnlistment" value="0"/>
      <add name="FetchSize" value="131072"/>
      <add name="MetaDataXml" value="CustomMetaData.xml"/>
      <add name="PerformanceCounters" value="4095"/>
      <add name="StatementCacheSize" value="50"/>
      <add name="ThreadPoolMaxSize" value="30"/>
      <add name="TraceFileName" value="D:\odpnet2.trc"/>
      <add name="TraceLevel" value="0"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

```

    <add name="TraceOption" value="0" />
    <add name="Person" value="udtMapping factoryName='PersonFactory, Sample,
      Version=0.0.0.0, Culture=neutral, PublicKeyToken=null' typeName='PERSON'
      schemaName='SCOTT' dataSource='oracle' "/>
    <add name="Student" value="udtMapping factoryName='StudentFactory, Sample,
      Version=0.0.0.0, Culture=neutral, PublicKeyToken=null' typeName='STUDENT'
      schemaName='SCOTT' "/>
  </settings>
</oracle.dataaccess.client>
</configuration>

```

ODP.NET, Unmanaged Driver now has the option of using the same configuration file format as ODP.NET, Managed Driver. The format simplifies configuration by using a single unified scheme. To utilize this format, the existing unmanaged ODP.NET configuration section should be renamed from `<oracle.dataaccess.client>` to `<oracle.unmanageddataaccess.client>`. The existing unmanaged ODP.NET elements and values are supported within the new section using the same format as with ODP.NET, Managed Driver. To see how to set the elements and values, see ["Oracle Data Provider for .NET, Managed Driver Configuration"](#) for more information.

For example, converting the `FetchSize` element and value from the traditional to the new format would be done as follows:

```

<oracle.dataaccess.client>
  <settings>
    <add name="FetchSize" value="131072" />
  </settings>
</oracle.dataaccess.client>

<oracle.unmanageddataaccess.client>
  <version number="*">
    <settings>
      <setting name="FetchSize" value="131072" />
    </settings>
  </version>
</oracle.unmanageddataaccess.client>

```

The traditional ODP.NET, Unmanaged Driver configuration file format will continue to be supported.

SQL Translation Framework Configuration

Configuring the SQL Translation Profile

The default SQL Translation Profile can be set in the .NET config file, either for all connections across the application, or it is also possible to limit the scope of a profile based on optional `dataSource` and `userId` XML attributes. Please note that these `dataSource` and `userId` XML attributes directly correspond to the `Data Source` and `User Id` attributes in the connection string used to open a database connection.

 **Note:**

SQL Translation Profile settings are only supported in the `<oracle.unmanageddataaccess.client>` section. It is not supported in the `<oracle.dataaccess.client>` section nor the `<oracle.manageddataaccess.client>` section.

This would be used for all connections to the Data Source and User Ids.

This would be used for all connections to the specified Data Source.

This would be used for all connections to the specified User Id.

This would be used for all connections to the specified Data Source and User Id.

It is possible to configure multiple default profile entries which allow configuring default profiles for different `dataSource` and `userId` attributes, but while selecting a profile, the profile with maximum matching attributes will be selected.

In case there are 2 matching entries, one with `dataSource` only and the other with `userId` only then the entry with matching the `userId` would be given priority over the entry with matching `dataSource`.

With the above configuration, if we try to connect with a connection string which has `stf_ds` for Data Source and `stf_user` for User Id attributes, then both the entries given above will match and in such cases, we will give priority to the entry with a matching User Id attribute which means `profile_user` will be selected as the default profile.

Configuring the Error Mapping

Applications can configure the connection related error mapping in their application configuration file. The error mapping can also be scoped based on Data Source name, User Id and the profile name itself.

Here is an example of providing error mapping with all three attributes.

```
<configuration>
  <oracle.unmanageddataaccess.client>
    <version number="*">
      <sqlTranslation>
        <defaultProfiles>
          <defaultProfile dataSource="stf_ds" userId="stf_user" profile=" Profile4"/>
        </defaultProfiles>
        <ErrorMappings>
          <ErrorMapping dataSource="stf_ds" userId="stf_user" profile="Profile4">
            <add oracleErrorNumber="1017" translatedErrorCode="222" />
            <add oracleErrorNumber="1005" translatedErrorCode="888" />
          </ErrorMapping>
        </ErrorMappings>
      </sqlTranslation>
    </version>
  </oracle.unmanageddataaccess.client>
</configuration>
```

Please note that `dataSource` and `userId` attributes are optional but can be used to scope the mapping.

It is also possible to provide an error mapping which could be used for all profiles. Here is an example:

```
<ErrorMappings>
  <ErrorMapping profile="*">
    <add oracleErrorNumber="1017" translatedErrorCode="222" />
    <add oracleErrorNumber="1018" translatedErrorCode="888" />
  </ErrorMapping>
</ErrorMappings>
```

Configuring the Default Error Mapping Profile

The default error mapping profile can be configured through the `defaultErrorMappingProfile` setting. This is to be used to specify the default error mapping profile, especially in scenarios when the default profile is not specified through the .NET configuration file, but specified on the server side. In this case, if connectivity related errors occur, then ODP.NET will be able to properly use error mappings specified in the .NET configuration file for the profile specified by the `defaultErrorMappingProfile` setting.

Here is an example to configure the default error mapping profile:

```
<sqlTranslation>
  <settings>
    <add name="defaultErrorMappingProfile" value="error_mapping_profile" />
  </settings>
</sqlTranslation>
```

Configuring the SQL Translation Framework Statement Cache Size

Client can configure the number of translated statements that ODP.NET can cache internally to avoid translations, which can be an expensive operation.

Here is an example to configure default error mapping profile:

```
<sqlTranslation>
  <settings>
    <add name="translatedStatementCacheSize" value="50" />
  </settings>
</sqlTranslation>
```

Sample SQL Translation Framework configuration file

Here is a sample configuration file with all possible elements that can be used:

```
<sqlTranslation>
  <settings>
    <add name="translatedStatementCacheSize" value="50" />
    <add name="defaultErrorMappingProfile" value="def_Profile" />
  </settings>
  <defaultProfiles>
    <defaultProfile profile="STF.NO_DS_NO_USERID"/>
    <defaultProfile userId="stf" profile="STF_NO_DS"/>
    <defaultProfile dataSource="stf_inst" profile="STF_NO_USERID"/>
    <defaultProfile dataSource="stf_inst" userId="stf" profile="STF.STF_X"/>
  </defaultProfiles>
  <ErrorMappings>
    <ErrorMapping profile="def_profile">
      <add oracleErrorNumber="1017" translatedErrorCode="444" />
    </ErrorMapping>
    <ErrorMapping dataSource="stf_inst" userId="stf" profile=" STF.STF_X ">
```

```

        <add oracleErrorNumber="1018" translatedErrorCode="88888" />
    </ErrorMapping>
</ErrorMappings>
</sqlTranslation>

```

Example 2-1 Setting the profile which could be used for all connections

```

<configuration>
  <oracle.unmanageddataaccess.client>
    <version number="*">
      <sqlTranslation>
        <defaultProfiles>
          <defaultProfile profile="Profile1"/>
        </defaultProfiles>
      </sqlTranslation>
    </version>
  </oracle.unmanageddataaccess.client>
</configuration>

```

Example 2-2 Setting the Profile for a Specific Data Source

```

<defaultProfiles>
  <defaultProfile dataSource="stf_ds" profile="Profile2"/>
</defaultProfiles>

```

Example 2-3 Setting the Profile for a Specific User Id

```

<defaultProfiles>
  <defaultProfile userId="stf_user" profile="Profile3"/>
</defaultProfiles>

```

Example 2-4 Setting the Profile for a Specific Data Source and User Id'

```

<defaultProfiles>
  <defaultProfile dataSource="stf_ds" userId="stf_user" profile="Profile4"/>
</defaultProfiles>

```

Example 2-5 Configuring Multiple Default Profile Entries

```

<defaultProfiles>
  <defaultProfile dataSource="stf_ds" profile="profile_ds"/>
  <defaultProfile userId="stf_user" profile="profile_user"/>
</defaultProfiles>

```

Specifying UDT Mappings with Unified Configuration for Unmanaged ODP.NET

As UDT mapping is not currently supported by ODP.NET, Managed Driver, a new section within the `<version>` section is used to support custom UDT mappings for unmanaged ODP.NET in the unified configuration format. This new section is identified as `<udtmappings>` and each mapping is identified using a `<udtmapping>` element. The following attributes may be specified for each `udtMapping` element:

- `typeName` (required)
- `factoryName` (required)
- `dataSource` (optional)
- `schemaName` (optional)

These elements retain the same name and meaning as when used with the traditional configuration format.

Example of converting traditional format to unified format:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="Person" value="udtMapping factoryName='PersonFactory, Sample,
Version=0.0.0.0, Culture=neutral, PublicKeyToken=null' typeName='PERSON'
schemaName='SCOTT' dataSource='oracle' " />
    </settings>
  </oracle.dataaccess.client>
</configuration>

<configuration>
  <oracle.unmanageddataaccess.client>
    <udtmappings>
      <udtmapping typename="PERSON" factoryname="PersonFactory, Sample,
Version=0.0.0.0, Culture=neutral, PublicKeyToken=null" schemaname="SCOTT"
datasource="oracle" />
    </udtmappings>
  </oracle.unmanageddataaccess.client>
</configuration>
```



See Also:

[Oracle User-Defined Types \(UDTs\) and .NET Custom Types](#)

Oracle Data Provider for .NET, Managed Driver Configuration

ODP.NET, Managed Driver supports .NET configuration file-based settings in `machine.config`, `app.config`, and `web.config`. It does not support Windows registry based configuration. ODP.NET, Managed Driver settings in .NET configuration files are similar to ODP.NET, Unmanaged Driver settings to make porting easier.

The ODP.NET, Managed Driver configuration file section name is `<oracle.manageddataaccess.client>`. The `<oracle.manageddataaccess.client>` settings and values are also supported in unmanaged ODP.NET configuration file: `<oracle.unmanageddataaccess.client>`. While this documentation section discusses managed ODP.NET configuration, it is also applicable to `<oracle.unmanageddataaccess.client>`. The `<oracle.unmanageddataaccess.client>` settings are actually a superset of `<oracle.manageddataaccess.client>`. The `<oracle.unmanageddataaccess.client>` settings not available in managed ODP.NET are documented in "[Oracle Data Provider for .NET, Unmanaged Driver Configuration](#)". A typical .NET config that uses ODP.NET, Managed Driver has some or all of the following subsections nested within a `<version>` subsection under `<oracle.manageddataaccess.client>` section. Note the tag names are case sensitive, while the attribute names are case insensitive.

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.manageddataaccess.client>
    <version number="*">
      <dataSources>
        ...
```

```

    ...
  </dataSources>
  <settings>
    ...
    ...
  </settings>
  <LDAPsettings>
    ...
    ...
  </LDAPsettings>
  <implicitRefCursor>
    ...
    ...
  </implicitRefCursor>
  <edmMappings>
    ...
    ...
  <edmMappings>
</version>
<version number="4.121.2.0">
  <dataSources>
    ...
    ...
  </dataSources>
  <settings>
    ...
    ...
  </settings>
  <LDAPsettings>
    ...
    ...
  </LDAPsettings>
  <implicitRefCursor>
    ...
    ...
  </implicitRefCursor>
  <edmMappings>
    ...
    ...
  <edmMappings>
</version>
</oracle.manageddataaccess.client>
</configuration>

```

The ODP.NET, Managed Driver configuration and settings are described in the following sections. Many of the attributes are the same as ODP.NET, Unmanaged Driver. See [Table 2-3](#) for detailed attribute descriptions.

version Section

All the information required by an application should be grouped under the `version` subsections. Each `<version number="X">` section contains parameters applicable for version `x` of the ODP.NET, Managed Driver. For example, `<version number="4.121.2.0">` section parameters will be applicable only for those applications using ODP.NET, Managed Driver assembly 4.121.2.0.

Apart from version specific sections, there can also be a generic section `<version number="*">`. This section's parameters are applicable for all ODP.NET, Managed

Driver versions. Parameters in the version specific section take precedence over the parameters of the generic section. The following is an example of a `version` section:

```
<oracle.manageddataaccess.client>
  <version number="*">
    <settings>
      <setting name="TraceOption" value="1"/>
      <setting name="PerformanceCounters" value="0" />
    </settings>
  </version>
  <version number="4.121.2.0">
    <settings>
      <setting name="PerformanceCounters" value="4095" />
    </settings>
  </version>
</oracle.manageddataaccess.client>
```

An application referencing ODP.NET, Managed Driver 4.121.2.0 has the following values set:

- TraceOption = 1
- PerformanceCounters= 4095

dataSources Section

This section can appear only under a `<version>` section. The mapping between the different data source aliases and corresponding data descriptors should appear in this section. The following is an example.

```
<dataSources>
  <dataSource alias="inst1" descriptor="(DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)
(HOST=sales-server).....))"/>
  <dataSource alias="inst2" descriptor="(DESCRIPTION= .....))"/>
</dataSources>
```

Note:

The `data source` connection string attribute can alternatively be set to a full descriptor or Easy Connect syntax rather than a data source alias.

Requirements for connecting to a local database *without* specifying "data source" connection string attribute:

- The listener must be up and running.
- ORACLE_SID environment variable must be set appropriately.

Note:

When `data source` connection string attribute is not specified, protocol defaults to 'tcp' and port defaults to '1521'.

The ODP.NET managed driver reads and caches all the alias entries from the `app.config`, `web.config`, `machine.config`, and from a `tnsnames.ora` file that is found at application start-up time. However, aliases that are defined in LDAP servers are resolved and cached on demand. This means for each unique alias that is used by the application, an alias resolution query is executed against an LDAP server and the full descriptor associated with the alias will be cached once it is fetched.

For developers that need to change or add alias settings while developing applications, one may consider using

`OracleDataSourceEnumerator.GetDataSources()` rather than restarting the application. Invoking this method will first wipe out existing cache entries that were read from the `tnsnames.ora` file and all aliases obtained from the LDAP Server. Then, the `tnsnames.ora` is re-parsed and all its entries will be cached again. Please note that the `app.config`, `web.config`, and `machine.config` entries are read only once at application start-up time and thus their contents are maintained and not re-parsed even if `OracleDataSourceEnumerator.GetDataSources()` is invoked.

The `OracleDataSourceEnumerator.GetDataSources()` method invocation has an impact on the connection pool. This is because a connection pool, which is created for each unique connection string, will cache the resolved full descriptor information after the first connection is created for a given connection pool. After that, the connection pool uses the cached full descriptor information for all subsequent connection creations. Thus, for applications that have their `tnsnames.ora` or LDAP entries modified during the execution of an application where an alias points to a different database than before, one should call the

`OracleDataSourceEnumerator.GetDataSources()` method to remove old cached entries. This should be followed by the invocation of the `ClearPool(OracleConnection)` instance method or the `ClearAllPools()` static method to remove existing connections and also have it obtain a new full descriptor value that was read by the invocation of `OracleDataSourceEnumerator.GetDataSources()`. Following this scheme will assure that *all* the connections in the connection pool uses the new full descriptor that is now associated with the alias and all connections in a connection pool is established to the same database.

The following keywords are supported within the descriptor setting:

- ADDRESS
- ADDRESS_LIST (Note: only failover supported)
Oracle recommends using SCAN listener and Runtime Load Balancing to balance the load when connecting to an Oracle RAC database.
- DESCRIPTION
- DESCRIPTION_LIST (Note: Failover supported; Address_list load balancing not supported)
- HOST (Note: <hostname>, <IPv6 literal>, and <IPv4 literal> are supported)
- HTTPS_PROXY
- HTTPS_PROXY_PORT
- IP (Note: "loopback" is supported)
- PROTOCOL (Note: tcp and tcps are supported)
- RETRY_COUNT: Specifies the number of times an ADDRESS list is traversed before the connection attempt is terminated and times out.

- `RETRY_DELAY`: Specifies the delay in seconds between subsequent retries for a connection.

`RETRY_COUNT` and `RETRY_DELAY` are timeout parameters that work at the Oracle networking layer. They are intended to be used in conjunction with each other. When these parameters are used, ODP.NET will attempt to connect with one of the addresses in the `ADDRESS_LIST`. If there is no successful connection after going through the entire list, then ODP.NET will wait for the number of seconds specified by `RETRY_DELAY` before traversing the address list again. It will repeat this behavior until there is a successful connection or the `RETRY_COUNT` limit is hit.

For example, let's assume `RETRY_COUNT=2` and `RETRY_DELAY=4` when ODP.NET cannot successfully connect to any address on the list. The following sequence is triggered:

1. Traverse address list to connect.
2. Wait four seconds for next set of retry attempts.
3. Traverse the address list again. This is first set of retry attempts.
4. Wait four seconds for the next retry attempt.
5. Traverse the address list again. This is the second and final set of retry attempts.
6. Timeout

These timeout parameters function independent of ODP.NET application timeouts, such as the `Connection Timeout` connection string attribute. If the `Connection Timeout` is set to a low value, then it may trigger before the `RETRY_COUNT` and `RETRY_DELAY` attempt cycle completes.

- `SDU` (Note: 256 to 65536 are supported)
- `SECURITY: SSL_VERSION` (Note: overrides `sqlnet.ora:ssl_version`)
- `TRANSPORT_CONNECT_TIMEOUT` (Note: overrides `tcp.connect_timeout`)

Note:

- SSL is now supported via method MCS and FILE.
- Both Kerberos5 and NTS authentication are supported. RADIUS is not supported.
- Only NTS authentication is supported. No RADIUS nor Kerberos5 authentication.
- Only Net Services, Easy Connect naming, and LDAP (namely, Active Directory and Oracle Internet Directory) are supported.
- No bequeath (`beq`) support. Default address is instead TCP loopback with port 1521 and Oracle service name from environment (`ORACLE_SID`)

 **See Also:**

Oracle Database Net Services Reference for a detailed description of the attributes.

Though managed ODP.NET does not support TNS descriptor based load balancing, it does support failover through both an `ADDRESS_LIST` and `DESCRIPTION_LIST`.

Note that you need not specify either the `LOAD_BALANCE` or the `FAILOVER` directive, because only failover is supported. The directives are ignored.

The following examples demonstrate TNS descriptors utilizing failover:

```
(DESCRIPTION=
  (ADDRESS_LIST=
    (ADDRESS=(PROTOCOL=tcp)(HOST=host1)(PORT=1630))
    (ADDRESS=(PROTOCOL=tcp)(HOST=host2)(PORT=1630))
    (ADDRESS=(PROTOCOL=tcp)(HOST=host3)(PORT=1521)))
  (CONNECT_DATA=(SERVICE_NAME=Sales.us.example.com)))

(DESCRIPTION_LIST=
  (DESCRIPTION=
    (ADDRESS_LIST=
      (ADDRESS=(PROTOCOL=tcp)(HOST=sales1a-svr)(PORT=1521))
      (ADDRESS=(PROTOCOL=tcp)(HOST=sales1b-svr)(PORT=1521)))
    (CONNECT_DATA=(SERVICE_NAME=sales1.example.com)))
  (DESCRIPTION=
    (ADDRESS_LIST=
      (ADDRESS=(PROTOCOL=tcp)(HOST=sales2a-svr)(PORT=1521))
      (ADDRESS=(PROTOCOL=tcp)(HOST=sales2b-svr)(PORT=1521)))
    (CONNECT_DATA=(SERVICE_NAME=sales2.us.example.com))))
```

settings section

This section can appear only under a `<version>` section. Any ODP.NET, Managed Driver specific settings should appear in this section. The following is an example of a settings section:

```
<settings>
  <setting name="TraceLevel" value="7" />
  <setting name="TraceOption" value="1"/>
  <setting name="TNS_ADMIN" value="C:\oracle\work"/>
</settings>
```

A new default behavior has been introduced for ODP.NET Release 12.1.0.2 and later when `InitialLobFetchSize` is set to `-1`. The new default value is `LegacyEntireLOBFetch = 0`. To use the old behavior, set `LegacyEntireLobFetch = 1` in the ODP.NET configuration. Refer to "[Setting InitialLONGFetchSize to -1](#)" for more information.

ODP.NET, Managed Driver configuration settings that are supported:

- `BindByName`
- `CPVersion`: Determines whether ODP.NET, Unmanaged Driver uses the traditional connection pool implementation (`Default=1.0`) or the more modern connection pool implementation with better high availability support (`2.0`). In addition, the

more modern connection pool (2.0) is required if the application uses Database Resident Connection Pooling (DRCP), or hosts multiple pluggable databases or editions in the same pool. Possible values: 1.0 or 2.0.

ODP.NET, Managed Driver only uses the more modern connection pool implementation. This setting can only be used for ODP.NET, Unmanaged Driver for .NET Framework 4 and higher. It cannot be used for earlier versions of unmanaged ODP.NET, which will always use the traditional connection pool implementation.

If `CPVersion` is set explicitly, then that setting will be used across processes for all connection strings.

If `CPVersion` is left unmodified (or contains an invalid value) and an application's first unmanaged ODP.NET established connection for a given connection string uses DRCP, pluggable databases, or editions by modifying one these features' properties or configuration settings, then `CPVersion` will be implicitly modified to use the newer connection pool implementation (2.0).

If a `CPVersion 1.0` pool attempts to use DRCP, pluggable database, or edition settings, then ODP.NET will raise an exception when the application attempts to open a connection.

When `CPVersion 2.0` is used explicitly or implicitly and the "proxy user id" is not specified in the connection string, then a proxy connection will not be created, even if "proxy password" is supplied.

When `CPVersion 2.0` is used by ODP.NET, Unmanaged Driver, the connection pool behavior will be the same as the more modern connection pool as implementation that ODP.NET, Managed Driver uses.

- `DbNotificationPort`
- `DemandOraclePermission`
- `Disable_Oob`: Interrupts database query execution via either TCP/IP urgent data or normal TCP/IP data, called out of band data (default) or in band data, respectively. (Default=off).

All Oracle database clients support interrupting database query execution, such as through an ODP.NET command timeout. Windows-based database servers only support in band breaks, whereas all other (predominantly UNIX-based) database servers can support out of band (OOB) or in band breaks. ODP.NET, Managed Driver uses OOB breaks by default with database servers that support it. For certain network topologies, the routers or firewalls involved in the route to the database may have been configured to drop urgent data or in band the data. If the routers or firewalls can not be changed to handle urgent data appropriately, then the ODP.NET, Managed Driver can be configured to utilize in band breaks by setting the .NET configuration parameter `Disable_Oob` to on.

- `DRCPConnectionClass`: Specifies a logical name that identifies the DRCP connection pool that the ODP.NET connection will use. It will be used as a default if the `DRCPConnectionClass` property on the `OracleConnection` object is not set. It will be ignored for non-DRCP connections.

Valid Values: the connection class name is string at max 1024 characters. The default is null.

- `FetchSize`

- **LDAP_ADMIN:** Specifies the `ldap.ora` location. The `LDAP_ADMIN` setting works in conjunction with the `TNS_ADMIN` setting to set `ldap.ora` search order.

`ldap.ora` is searched in the following order:

- `TNS_ADMIN` in `app.config` or `web.config`
- `LDAP_ADMIN` in `app.config` or `web.config`
- current working directory
- `%ORACLE_HOME%\network\admin`
- `%ORACLE_HOME%\ldap\admin`
- `LegacyEntireLOBFetch`
- `MaxStatementCacheSize`
- `MetaDataXml`
- **NAMES.DIRECTORY_PATH:** The default search order is `TNSNAMES` and `EZCONNECT`. `TNSNAMES`, `LDAP`, and `EZCONNECT` are the only name resolution methods supported, but their order of precedence can be modified.
- `NAMES.LDAP_AUTHENTICATE_BIND`
- `NAMES.LDAP_CONN_TIMEOUT`
- `NODELAY`
- **ORA_DEBUG_JDWP:** Allows Oracle PL/SQL Debugger and database to connect automatically without application code changes. Value is set as `host=<IP_address or host_name>;port=<debugging port number>`. Ex. `host=localhost;port=1234`
- `ORACLE_SID`
- `PerformanceCounters`
- **RECEIVE_BUF_SIZE:** Sets `TCP SO_RECVBUF`, the total buffer space associated with the local side of a TCP socket
- `SelfTuning`
- **SEND_BUF_SIZE:** Sets `TCP SO_SENDBUF`, the total buffer space associated with the local side of a TCP socket
- `ServiceRelocationConnectionTimeout`

In seconds. (Default = 90).

Whenever a database service becomes unavailable, such as due to a service being relocated, an application can encounter numerous connectivity errors during this time. To avoid unnecessary connection attempts to an unavailable service which will result in an error, ODP.NET, Managed and Unmanaged Drivers block any connection attempts until the service is up or until this property's specified time limit expires from the time when the service DOWN event was received, whichever comes first. Once the specified time elapses, all the connection attempts to the specific service which is known to be down will no longer be blocked. Those requests will be sent to the server. `ServiceRelocationConnectionTimeout` is only operational in conjunction with Oracle Fast Connection Failover (`HA Events = true`). Once Fast Connection Failover is enabled for the .NET application, Service Relocation Connection Timeout is automatically enabled. It will use its default value if no `ServiceRelocationConnectionTimeout` value has been explicitly set. It works with planned and unplanned outages.

When connecting to Oracle Data Guard in Oracle Database 12c Release 2 or later, database administrators can set their own timeout value, `drain_timeout`, to indicate the number of seconds allowed for resource draining to be completed. This setting can be optionally used by the ODP.NET

`ServiceRelocationConnectionTimeout` value as the intent behind `drain_timeout` and `ServiceRelocationConnectionTimeout` are the same.

If `ServiceRelocationConnectionTimeout` and `drain_timeout` are not set, then the default `ServiceRelocationConnectionTimeout` value is used (90 seconds). If only `drain_timeout` is set, then that value will be used for the service relocation connection timeout. If only `drain_timeout` is set and is set to 0, then also default `ServiceRelocationConnectionTimeout` value is used (90 seconds). If both are set, then the value of `ServiceRelocationConnectionTimeout` will override the value of `drain_timeout`.

`ServiceRelocationConnectionTimeout` itself can be set based upon the value of `drain_timeout`. For example, if ODP.NET administrators desire the service relocation connection timeout to be `drain_timeout` plus 50 seconds, then they would set `ServiceRelocationConnectionTimeout` in the following manner:

```
<setting name="ServiceRelocationConnectionTimeout" value="drain_timeout + 50"/>
```

Service Relocation Connection Timeout is not supported in pools that connect to more than one pluggable database.

- `SQLNET.AUTHENTICATION_SERVICES`: Supported values are `Kerberos5`, `NTS`, `TCPS`, or `NONE`.

Managed ODP.NET supports `NTS`, `Kerberos5`, and `TCPS` external authentication methods. This setting should be set based on the desired database authentication method. If internal database authentication is desired, then the setting should be set to `NONE`. Default value is `NONE`. The value(s) must be enclosed in parentheses. Example settings made in `sqlnet.ora` are:

```
SQLNET.AUTHENTICATION_SERVICES = (TCPS)
SQLNET.AUTHENTICATION_SERVICES = (NTS)
SQLNET.AUTHENTICATION_SERVICES = (Kerberos5, NTS)
SQLNET.AUTHENTICATION_SERVICES = (NONE)
```

Note:

The `NTS` external authentication methodology is only supported on a Windows-based client and server.

`SQLNET.AUTHENTICATION_SERVICES` default values are different for managed ODP.NET and unmanaged ODP.NET. Managed ODP.NET defaults to `NONE` and unmanaged defaults to `ALL` when no value is set.

- `SQLNET.CRYPTO_CHECKSUM_CLIENT`: Specifies the desired data integrity behavior when this client connects to a server. Supported values are `accepted`, `rejected`, `requested`, or `required`. Default = `accepted`.
- `SQLNET.CRYPTO_CHECKSUM_TYPES_CLIENT`: Specifies the data integrity algorithms that this client uses. Supported values are `SHA512`, `SHA384`, `SHA256`, and `SHA1`.

- `SQLNET.USE_HTTPS_PROXY`
- `StatementCacheSize`
- `SSL_SERVER_DN_MATCH`: To enforce the distinguished name (DN) for the database server matches its service name. (Default=no).

If you enforce the match verification, then SSL/TLS ensures that the certificate is from the server. If you select to not enforce the match verification, then SSL/TLS performs the check but allows the connection, regardless if there is a match. Not enforcing the match allows the server to potentially fake its identify.

Supported values: `yes` | `on` | `true` to enforce a match.

Supported values: `no` | `off` | `false` to not enforce a match.

`SSL_SERVER_DN_MATCH` is often used together with `SSL_SERVER_CERT_DN`. `SSL_SERVER_CERT_DN` specifies the distinguished name (DN) of the database server. It can be set in the connect descriptor.

```
net_service_name=
  (DESCRIPTION=
    (ADDRESS=(PROTOCOL=tcp)(HOST=sales1-svr)(PORT=1521))
    (ADDRESS=(PROTOCOL=tcp)(HOST=sales2-svr)(PORT=1521))
    (CONNECT_DATA=
      (SERVICE_NAME=sales.us.acme.com))
      (SECURITY=
        (SSL_SERVER_CERT_DN="cn=sales,cn=OracleContext,dc=us,dc=acme,dc=com")))
```

The client uses this information to obtain the list of DNs it expects for each of the servers, enforcing the database server DN to match its service name. Use this parameter with `SSL_SERVER_DN_MATCH` to enable server DN matching.

- `SSL_VERSION`: Sets the version of the SSL/TLS connection. By default, all supported versions are enabled, in the order 3.0, 1.0, 1.1, and 1.2.

The client and server negotiate to the highest version among the common conversions specified in their configurations. The versions from lowest to highest are: 3.0 (lowest), 1.0, 1.1, and 1.2 (highest).

- `TNS_ADMIN`: Location where either one or more of `tnsnames.ora`, `ldap.ora`, and `sqlnet.ora` are located. Locations can consist of either absolute or relative directory paths.
- `TraceFileLocation`: Trace file destination directory, for example, `D:\traces`. The default `TraceFileLocation` is `<Windows user temporary folder>\ODP.NET\managed\trace`.
- `TraceLevel`: 1 = public APIs; 2 = private APIs; 4 = network APIs/data. These values can be `ORED`. To enable everything, set `TraceLevel` to 7. Errors will always be traced.
- `TraceOption`
- `TCP.CONNECT_TIMEOUT`
- `WALLET_LOCATION`: Microsoft Certificate Store (MCS) and file system wallets are supported.
- `SQLNET.ENCRYPTION_CLIENT` = Negotiates whether to turn on encryption. Supported values are `accepted`, `rejected`, `requested`, or `required`.
- `SQLNET.ENCRYPTION_TYPES_CLIENT` = Encryption algorithm(s) to use.

The following table lists the valid encryption algorithms for ODP.NET, Managed Driver.

Table 2-4 Encryption Algorithms for ODP.NET, Managed Driver

Algorithm Name	Legal Value
AES 128-bit key	AES128
AES 192-bit key	AES192
AES 256-bit key	AES256
2-key 3DES	3DES112
3-key 3DES	3DES168

For more information on data encryption settings, refer to the *Oracle Database Security Guide*.



See Also:

Oracle Database Net Services Reference

LDAPsettings section

This section can appear only under a <version> section. Any ODP.NET, Managed Driver specific LDAP settings should appear in this section. The following is an example of a <LDAPsetting> subsection under the <LDAPsettings> section:

```
<LDAPsettings>
  <LDAPsetting name="DIRECTORY_TYPE" value="AD" />
  <LDAPsetting name="DEFAULT_ADMIN_CONTEXT" value="dc=Oracle,dc=com"/>
</LDAPsettings>
```

Lightweight Directory Access Protocol

ODP.NET, Managed Driver supports TNS alias resolution through a LDAP server/ service, specifically Microsoft Active Directory and Oracle Internet Directory (OID). TNS alias resolution occurs when using the LDAPsettings section or ldap.ora file settings. The LDAPsettings section settings take precedence over ldap.ora settings.

For Active Directory, only the DIRECTORY_TYPE and DEFAULT_ADMIN_CONTEXT parameters are required in ldap.ora. When the DIRECTORY_SERVERS parameter is missing or has no value, the default LDAP server for the current domain will be used.

For OID, all ldap.ora parameters must be set with valid values to complete configuration.

ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver support the same level of security when using LDAP for name resolution.

Table 2-5 Microsoft Active Directory: Encryption Types and Authentication Credentials For Connecting and Binding

No Encryption	SSL Encryption
Anonymous authentication	Anonymous authentication
Domain User authentication	Domain User authentication

Table 2-6 Oracle Internet Directory: Encryption Types and Authentication Credentials For Connecting and Binding

No Encryption	SSL Encryption
Anonymous authentication	Anonymous authentication
-	Wallet based authentication <i>Note: Wallet based authentication for Oracle Internet Directory is not supported for this release</i>

See Also:

- *Oracle Database Net Services Reference* for more information on Directory Usage Parameters.
- *Oracle Database Net Services Administrator's Guide* for more information on Managing Network Address.

implicitRefCursor section

This section can appear only under a `<version>` section. Any information about `REF CURSOR` parameters that need to be bound implicitly should appear in this section. The following is an example of an `<implicitRefCursor>` section:

```
<implicitRefCursor>
  <storedProcedure schema="USERREFCUR" name="TestProc1">
    <refCursor name="Param3">
      <bindInfo mode="Output"/>
      <metadata columnOrdinal="0" columnName="DEPTNO" baseColumnName="DEPTNO"
baseSchemaName="USERREFCUR" baseTableName="DEPT" nativeDataType="number"
providerType="Int32" dataType="System.Int16" columnSize="2" allowDBNull="true" />
      <metadata columnOrdinal="1" columnName="DNAME" baseColumnName="DNAME"
baseSchemaName="USERREFCUR" baseTableName="DEPT" nativeDataType="varchar2"
providerDbType="String" columnSize="30" />
    </refCursor>
    <refCursor name="param2">
      <bindInfo mode="Output"/>
      <metadata columnOrdinal="0" columnName="EMPNO" baseColumnName="EMPNO"
baseSchemaName="USERREFCUR" baseTableName="EMP" nativeDataType="number"
providerType="Int32" dataType="System.Int16" columnSize="4" allowDBNull="false" />
    </refCursor>
  </storedProcedure>

  <!--Next stored procedure information-->
```

```

    <storedProcedure name="TestProc2">
        ...
        ...
    </storedProcedure>
</implicitRefCursor>

```

distributedTransaction section

This section can appear only under a `<version>` section. Any information about distributed transactions should appear in this section. The following is an example of a `distributedTransaction` section:

```

<distributedTransaction>
  <setting name="OMTSRECO_IP_ADDRESS" value="my-pc" />
  <setting name="OMTSRECO_PORT" value="2040" />
  <setting name="ORAMTS_SESS_TXNTIMETOLIVE" value="240" />
</distributedTransaction>

```

- `OMTSRECO_IP_ADDRESS`: Specifies the machine name (or IP address) that the OraMTS Recovery service will be running on to resolve database in-doubt transactions. The default is the local machine name.
- `OMTSRECO_PORT`: Specifies the port that the OraMTS Recovery service will be listening on to resolve database in-doubt transactions. The default is 2030.
- `ORAMTS_SESS_TXNTIMETOLIVE` : Specifies the time in seconds that the transaction can remain inactive after it has been detached or delisted from the database. Once this time expires, the transaction is automatically terminated by the provider. The default is 120 seconds.
- `UseManagedDTC`: When set to `false` and using .NET Framework 4.5.2 or higher, ODP.NET uses .NET Framework for distributed transaction support. In all other instances, ODP.NET uses Oracle Services for Microsoft Transaction Server to support distributed transactions. Boolean (Default = `false`) for ODP.NET, Managed Driver only.
- `UseOraMTSManaged`: When set to `true` and using .NET Framework 4.5.2 or higher, ODP.NET uses managed code for distributed transactions. If set to `true`, but .NET 4.5.1 or lower is used, an exception will be thrown. If set to `false`, ODP.NET uses Oracle Services for Microsoft Transaction Server to support distributed transactions. Boolean (Default = `false`) for ODP.NET, Unmanaged Driver only.

connectionPools section

This section can appear only under a `<version>` section. This section allows setting a string identifier for each set of monitored connection counters. Refer to [Connection Performance Counters](#) documentation section for more details.

edmMappings section

This section can appear only under a `<version>` section. Any information related to EDM mappings should appear in this section. Refer to [Oracle Number Default Data Type Mapping and Customization](#) for more examples on `edmMappings` section.

onsConfig section

Oracle Notification Service (ONS) can be configured using either local or remote configuration. Remote configuration is the preferred configuration for standalone client applications. For releases earlier than Oracle Database 12c, this section is mandatory for ODP.NET to receive ONS notifications. With Oracle Database 12c and later, this section is optional and the information about the ONS daemons is received from the server itself. However, ODP.NET will also listen for events from any <host:port> pairs that is provided by the user in this section in addition to the <host:port> pairs received from the server.

For local configuration, please ensure that ONS is configured and available on the node where ODP.NET is running, so that ODP.NET can receive events directly from the local ONS daemon. The following is a sample format for the local configuration:

```
<onsConfig configFile="C:\temp\test.config" mode="local">
</onsConfig>
```

Note:

The `configFile` specified in .NET config should contain the same `localport` and `remoteport` values as specified in the `ons.config` used by the local ONS daemon. This will enable the application to receive events from the local ONS daemon.

Remote configuration is used in scenarios where the application directly receives ONS events from the ONS daemons running on remote machines. One of the advantages of this configuration is that no ONS daemon is needed on the client end and, therefore, there is no need to manage this process.

The following is a sample format for remote configuration:

```
<onsConfig mode="remote">
  <ons database="db1">
    <add name="nodeList" value="racnode1:4100, racnode2:4200" />
  </ons>
  <ons database="db2">
    <add name="nodeList" value=" racnode3:4100, racnode4:4200" />
  </ons>
</onsConfig>
```

In case of remote configuration, the application has to specify the <host>:<port> values for every potential database that it can connect to. The <host>:<port> value pairs represent the ports on the the different Oracle RAC nodes where the ONS daemons are talking to their remote clients.

See Also:

[Client Side ONS Daemon Configuration](#) for information about client side ONS daemon configuration

ONS TCPS and Wallets

ODP.NET enables ONS communications to occur over TCP/IP with SSL/TLS (TCPS), which is more secure than just TCP/IP. As TCPS requires using a wallet for storing keys and certificates, ODP.NET can use one wallet for both ONS and ODP.NET connections or have separate wallets for each.

TCPS provides more secure ONS communication, gives administrators flexibility in how to configure their wallets, and enables cloud database connections.

oracle.manageddataaccess.client configuration section sample

```
<oracle.manageddataaccess.client>
  <version number="*">
    <onsConfig mode="remote">
      <settings>
        <setting name="Protocol" value="TCPS" />
        <setting name="WALLET_LOCATION" value="D:\user\ONS_SSLWallet" />
      </settings>
      <ons database="acdb183">
        <add name="nodeList" value="slcai611:6205,slcai610:6205,slcai612:6205" />
      </ons>
    </onsConfig>
  </settings>
  <setting name="WALLET_LOCATION" value=" D:\user\DBWallet" />
</settings>
</version>
</oracle.manageddataaccess.client>
```

The protocol and wallet location properties are often used together.

If an ONS wallet location is set, ODP.NET will use the wallet for ONS to connect via TCP/IP with SSL/TLS regardless of the protocol setting.

If the protocol is set to "TCPS", ODP.NET first tries to use the wallet in the ONS configuration wallet location to connect via TCP/IP with SSL/TLS. If no wallet is present, ODP.NET next tries to use the wallet from the database wallet location. If no wallet is found, the connection fails.

Administrators can choose between having the ONS connection use its own independent wallet or share the database's wallet for ease of use.

If the protocol is set to "TCP" and no ONS wallet location is set, ODP.NET ONS will connect with TCP/IP.

ODP.NET ONS TCPS works with any Oracle Database version that supports ONS TCPS on the server side.

Client Side ONS Daemon Configuration

ONS configuration is controlled by the ONS configuration file, *ORACLE_HOME/opmn/conf/ons.config*. This file tells the ONS daemon how it should behave. The *SRVCTL* utility can be used to start and stop the ONS daemon. It is installed on each node by default during server install.

Configuration information within *ons.config* is defined in simple name and value pairs. An example of *ONS.config* is given below

```
# This is an example ons.config file
#
# The first three values are required
localport=4100
remoteport=4200
nodes=racnode1.example.com:4200,racnode2.example.com:4200
```

Some parameters in the ons.config file are required and some are optional. Table [Table 2-7](#) lists the required ONS configuration parameters and [Table 2-8](#) lists the optional ONS configuration parameters.

Table 2-7 Required ONS Configuration Parameters

Parameter	Explanation
localport	The port that ONS binds to on the local host interface to talk to local clients. For example, localport=4100
remoteport	The port that ONS binds to on all interfaces for talking to other ONS daemons. For example, remoteport=4200
nodes	A list of other ONS daemons to talk to. Node values are given as a comma-delimited list of either host names or IP addresses plus ports. The port value that is given is the remote port that each ONS instance is listening on. In order to maintain an identical file on all nodes, the host:port of the current ONS node can also be listed in the nodes list. It will be ignored when reading the list. For example, nodes=myhost.example.com:4200,123.123.123.123:4200 The nodes listed in the nodes line correspond to the individual nodes in the Oracle RAC instance. Listing the nodes ensures that the middle-tier node can communicate with the Oracle RAC nodes. At least one middle-tier node and one node in the Oracle RAC instance must be configured to see one another. As long as one node on each side is aware of the other, all nodes are visible. You need not list every single cluster and middle-tier node in the ONS configuration file of each Oracle RAC node. In particular, if one ONS configuration file cluster node is aware of the middle tier, then all nodes in the cluster are aware of it.

Table 2-8 Optional ONS Configuration Parameters

Parameter	Description
loglevel	The level of messages that should be logged by ONS. This value is an integer that ranges from 1, which indicates least messages logged, to 9, which indicates most messages logged. The default value is 3. For example, loglevel=3
logfile	A log file that ONS should use for logging messages. The default value for log file is \$ORACLE_HOME/opmn/logs/ons.log. For example, logfile=C:\app\user\product\12.1.0\opmn\logs\myons.log

Table 2-8 (Cont.) Optional ONS Configuration Parameters

Parameter	Description
walletfile	<p>The wallet file used by the Oracle Secure Sockets Layer (SSL) to store SSL certificates. If a wallet file is specified to ONS, then it uses SSL when communicating with other ONS instances and require SSL certificate authentication from all ONS instances that try to connect to it. This means that if you want to turn on SSL for one ONS instance, then you must turn it on for all instances that are connected. This value should point to the directory where your <code>ewallet.p12</code> file is located.</p> <p>For example, <code>walletfile=C:\app\user\product\12.1.0\opmn\conf\ssl.wlt\default</code></p>
useocr	<p>The value, reserved for use on the server-side, to indicate ONS whether it should store all Oracle RAC nodes and port numbers in Oracle Cluster Registry (OCR) instead of the ONS configuration file or not. A value of <code>useocr=on</code> is used to store all Oracle RAC nodes and port numbers in Oracle Cluster Registry (OCR).</p> <p>Do not use this option on the client-side.</p>

The `ons.config` file allows blank lines and comments on lines that begin with the number sign (#).



See Also:

Oracle Real Application Clusters Administration and Deployment Guide for more information about the `SRVCTL` utility.

Relative Windows Path and Windows Environment Variable Configuration Settings

The following managed ODP.NET configuration settings support relative Windows path and environment variables:

- `TraceFileLocation`
- `WALLET_LOCATION`

File locations for the above config parameters can now be set using relative Windows paths. The `."` notation informs ODP.NET to use the current working directory. Sub-directories can be added by appending them. For example, `.\mydir` refers to the sub-directory `mydir` in the current working directory. To navigate to a parent directory, use the `.."` notation.

For web applications, the current working directory is the application directory. For Windows applications, the `.EXE` location is the current working directory.

Windows paths can also be set using Windows environment variable names within `"%"` characters.

For example, %tns_admin%, c:\%dir%\my_app_location, c:\%top_level_dir%\%bottom_level_dir% etc.

 **Note:**

- If the environment variable that is used by the configuration parameter is not set to anything, then an exception will be thrown.
- A directory name cannot partially be using an environment variable. For example, c:\my_app_%id%
- Multiple variables can be used in given directory location. For example, c:\%top_level_dir%\%bottom_level_dir%.

 **See Also:**

Oracle Database Net Services Reference chapters covering `sqlnet.ora` parameters, `tnsnames.ora` local naming parameters, and `listener.ora` Oracle Net Listener parameters, for more information about these Oracle client settings.

Oracle Data Provider for .NET Core Configuration

ODP.NET Core developers can assign application settings in .NET Configuration API, `sqlnet.ora` file, and `tnsnames.ora` file.

.NET Configuration API

.NET Core does not support application configuration via .NET configuration files, that is, `web.config`. Instead, it uses .NET Configuration API in lieu of a configuration file. ODP.NET Core supports Configuration API via the static class `OracleConfiguration`, for application level provider settings. The `OracleDataSourceCollection` class supports adding and deleting net services names, that is, TNS entries. The `OracleOnsServerCollection` class supports adding to and deleting from a list of nodes where the Oracle Notification Service (ONS) daemons are talking to their remote clients.

All configurations settings through `OracleConfiguration` should be done before opening any connection in the application. Once a connection is opened, any updates to configuration properties will result in `InvalidOperationException`; with only exception of trace settings that are still allowed to change during application runtime.

Example 2-6 Code Sample

```
using System;
using Oracle.ManagedDataAccess.Client;

namespace ODP_Core_Config_API
{
    class odp_core_config
```

```
{
    static void Main(string[] args)
    {
        // This sample demonstrates how to use ODP.NET Core Configuration API

        // Add connect descriptors and net service names entries.
        OracleConfiguration.OracleDataSources.Add("orclpdb",
            "(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=<hostname or IP>)(PORT=1521))
            (CONNECT_DATA=(SERVICE_NAME=<service name>)(SERVER=dedicated)))");
        OracleConfiguration.OracleDataSources.Add("orcl",
            "(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=<hostname or IP>)(PORT=1521))
            (CONNECT_DATA=(SERVICE_NAME=<service name>)(SERVER=dedicated)))");

        // Set default statement cache size to be used by all connections.
        OracleConfiguration.StatementCacheSize = 25;

        // Disable self tuning by default.
        OracleConfiguration.SelfTuning = false;

        // Bind all parameters by name.
        OracleConfiguration.BindByName = true;

        // Set default timeout to 60 seconds.
        OracleConfiguration.CommandTimeout = 60;

        // Set default fetch size as 1 MB.
        OracleConfiguration.FetchSize = 1024 * 1024;

        // Set tracing options
        OracleConfiguration.TraceOption = 1;
        OracleConfiguration.TraceFileLocation = @"D:\traces";
        // Uncomment below to generate trace files
        //OracleConfiguration.TraceLevel = 7;

        // Set network properties
        OracleConfiguration.SendBufferSize = 8192;
        OracleConfiguration.ReceiveBufferereSize = 8192;
        OracleConfiguration.DisableOOB = true;

        OracleConnection orclCon = null;

        try
        {
            // Open a connection
            orclCon = new OracleConnection("user id=hr; password=<password>
data source=orclpdb");
            orclCon.Open();

            // Execute simple select statement that returns first 10 names from
EMPLOYEES table
            OracleCommand orclCmd = orclCon.CreateCommand();
            orclCmd.CommandText = "select first_name from employees where rownum
<= 10 ";

            OracleDataReader rdr = orclCmd.ExecuteReader();

            while (rdr.Read())
                Console.WriteLine("Employee Name: " + rdr.GetString(0));

            Console.ReadLine();

            rdr.Dispose();
        }
    }
}
```

```
        orclCmd.Dispose();
    }
    finally
    {
        // Close the connection
        if (null != orclCon)
            orclCon.Close();
    }
}
}
```

Oracle Configuration Files

ODP.NET Core supports the `sqlnet.ora` and `tnsnames.ora` parameters below. These settings can be used in conjunction with .NET Configuration API.

- BindByName
- DbNotificationPort
- Disable_Oob – `sqlnet.ora`
- DRCPConnectionClass
- FetchSize
- MaxStatementCacheSize
- NAMES.DIRECTORY_PATH – `sqlnet.ora`
- NODELAY – `sqlnet.ora`
- RETRY_COUNT
- RETRY_DELAY
- RECEIVE_BUF_SIZE – `sqlnet.ora` **OR** `tnsnames.ora`
- **SelfTuning**
- SEND_BUF_SIZE – `sqlnet.ora` **OR** `tnsnames.ora`
- ServiceRelocationConnectionTimeout
- SQLNET.AUTHENTICATION_SERVICES – `sqlnet.ora`
- SQLNET.CRYPTO_CHECKSUM_CLIENT – `sqlnet.ora`
- SQLNET.CRYPTO_CHECKSUM_TYPES_CLIENT – `sqlnet.ora`
- StatementCacheSize
- SSL_SERVER_DN_MATCH – `sqlnet.ora`
- SSL_VERSION – `sqlnet.ora`
- TNS_ADMIN
- TraceFileLocation
- TraceLevel
- TraceOption
- TCP.CONNECT_TIMEOUT – `sqlnet.ora`
- SQLNET.ENCRYPTION_CLIENT – `sqlnet.ora`

- `SQLNET.ENCRYPTION_TYPES_CLIENT` – `sqlnet.ora`

ODP.NET Core will look for `sqlnet.ora` and `tnsnames.ora` files in the following precedence order:

1. Directory set in `OracleConfiguration.TnsAdmin` property
2. Directory of the running ODP.NET Core assembly
3. Current working directory

See Also:

- [OracleConfiguration Class](#)
- [OracleDataSourceCollection Class](#)

Distributed Transactions

A distributed transaction includes one or more statements that, individually or as a group, update data on two or more distinct nodes of a distributed database.

ODP.NET, Managed and Unmanaged Drivers integrate with Microsoft Distributed Transaction Coordinator (MSDTC) and Oracle databases. MSDTC coordinates with all the resource managers that are enlisted to the same `System.Transactions` object, to perform a 2-phase commit or rollback atomically. With that, Oracle distributed transactions can then be committed or rolled back across networks properly.

ODP.NET only supports the read committed isolation level for distributed transactions.

Note:

ODP.NET Core does not support Distributed Transactions.

Microsoft Distributed Transaction Coordinator Integration

Managed ODP.NET includes a native fully managed implementation that supports integration with MSDTC for distributed transactions enlistments, commits, and rollbacks.

For unmanaged ODP.NET, Oracle Services for Microsoft Transaction (OraMTS) provides MSDTC integration that allows client components to participate in Oracle database distributed transactions. OraMTS act as a proxy for the Oracle database to MSDTC to ensure that Oracle distributed database transactions commit or rollback together with the rest of the distributed transaction.

Unmanaged ODP.NET can use either a managed or unmanaged OraMTS implementation. Oracle recommends using the managed OraMTS for applications requiring high availability from Oracle RAC or Data Guard.

If a failure occurs in a distributed transaction, such as a network failure or server hardware failure, then it can leave an in-process transaction in-doubt. Both managed

and unmanaged ODP.NET use the OraMTS recovery service to resolve these in-doubt transactions. This recovery service runs as a Windows service. Administrators must install and configure the OraMTS Windows recovery service to manage recovery scenarios whether they use managed or unmanaged ODP.NET. Only one recovery service is needed per machine.

It is required to install the OraMTS Recovery Service on all the client machines where ODP.NET is running and participating in MSDTC. As a machine may have multiple IP addresses, administrators for managed ODP.NET applications can specify the host machine name or IP address that has the running recovery service in the application's .NET configuration file. ODP.NET, Unmanaged Driver resolves the IP/machine name for the recovery service automatically.

Table 2-9 Supported ODP.NET Type and .NET Framework Version for Distributed Transaction

ODP.NET Type	.NET Framework Version	Distributed Transaction Support
Managed	4.5.2 and higher	.NET Framework's native managed implementation for distributed transactions.
Unmanaged	4.5.2 and higher	OraMTS (default) or managed OraMTS implementation. Oracle recommends using managed OraMTS for unmanaged ODP.NET applications requiring high availability from Oracle RAC or Data Guard.
Unmanaged	3.5	OraMTS

 **Note:**

.NET Framework 4.5.1 and lower within the .NET Framework 4 family are no longer supported by Microsoft and Oracle.

 **See Also:**

Manually Creating an Oracle MTS Recovery Service in *Oracle Services for Microsoft Transaction Server Developer's Guide for Microsoft Windows*.

ODP.NET, Managed Driver Setup

This section explains the setup and configuration steps required for using distributed transactions with ODP.NET, Managed Driver. Follow these steps to configure distributed transactions in these .NET Framework versions:

1. Create and setup the OraMTS recovery service or make sure an existing recovery service is running.
2. Set the value of `OMTSRECO_PORT` in the .NET configuration to specify the port number that the OraMTS recovery service is running.

ODP.NET, Unmanaged Driver Setup

This section explains the setup and configuration steps required for using distributed transactions with ODP.NET, Unmanaged Driver.

For .NET Framework 4.5.2 and higher, ODP.NET, Unmanaged Driver includes managed OraMTS in its assembly. OraMTS is the default option for ODP.NET, Unmanaged Driver, to ensure implementation continuity during upgrades. However, Oracle recommends the managed OraMTS option when using any high availability FAN operations (HA Events = true) with Oracle Real Application Clusters or Oracle Data Guard. The managed OraMTS option support high availability functionality, while the traditional OraMTS does not.

Applications can set OraMTS (default) or managed OraMTS usage through the `UseOraMTSManaged` parameter in the .NET configuration file.

Install and configure OraMTS, including its recovery service to use traditional OraMTS implementation for ODP.NET, Unmanaged Driver.

To set managed OraMTS up, perform the following steps:

1. Set `UseOraMTSManaged` to `true` in the .NET configuration file.
2. Create and setup the OraMTS recovery service or make sure an existing recovery service is running.



See Also:

[distributedTransaction](#) section for more information about .NET configuration setup

Configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver

[Table 2-10](#) lists other configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver.

Table 2-10 Configuration Differences between ODP.NET, Unmanaged Driver and ODP.NET, Managed Driver

Feature Category	Difference compared to ODP.NET, Unmanaged Driver
Configuration	The older, traditional ODP.NET, Unmanaged Driver configuration file format is different. The new format allows both providers to share the same format. See "Oracle Data Provider for .NET, Managed Driver Configuration."
Configuration	<code>ConfigSchema.xsd</code> file, shipped with ODP.NET, Managed Driver (when included as part of the schema (XML->Schemas) in Visual Studio) enables <code>app.config</code> intelli-sense.
Configuration	Windows Registry based configuration is not supported

Table 2-10 (Cont.) Configuration Differences between ODP.NET, Unmanaged Driver and ODP.NET, Managed Driver

Feature Category	Difference compared to ODP.NET, Unmanaged Driver
Configuration	Oracle High Availability (HA) & Oracle RAC Load Balancing (RLB) notifications use Oracle Notification Service (ONS). Thus, to use HA or RLB, configure database and client to use ONS, rather than Oracle Database Advanced Queuing (AQ). Note that Continuous Query Notification will continue to use AQ.
Configuration Parameter	Edition is not supported.
Configuration Parameter	CheckConStatus is not supported.
Configuration Parameter	DllPath is not supported.
Configuration Parameter	StatementCacheWithUdts is not supported.
Configuration Parameter	ThreadPoolMaxSize is not supported.
Configuration Parameter	TraceFileName is not supported.
Configuration Parameter	UdtCacheSize is not supported.
Configuration Parameter	<i>UDT Mapping</i> is not supported.
Configuration Parameter	UseManagedDTC is supported by ODP.NET, Managed Driver only.
Configuration Parameter	UseOraMTSManaged is not supported.
Connection String	Context Connection is not supported.
Connection String	LegacyTransactionBindingBehavior setting will be ignored. It will always be set to the default value of 1.
Connection String	Promotable Transaction setting will be ignored. It will always be set to promotable and always support promotions.
Connection String	Statement Cache Purge is not supported.
Connectivity	Connection to Oracle Times Ten Database is not supported.
Performance Monitor	NumberOfStatisConnections performance counter is not supported.
Performance Monitor	Performance monitor category name is "ODP.NET, Managed Driver"
Provider Types	Provider Types accept (via constructors) and generate (via ToString() methods) only culture-invariant strings
Tracing	Dynamic tracing is enabled by changing the TraceLevel setting in the app/web/machine.config. NOTE: For ASP.NET applications, doing so will recycle the application domain.

Configuring for Entity Framework Code First

Developers must configure applications to use the Oracle Entity Framework functionality. This consists of creating two entries in the `app.config` or `web.config` file and adding an assembly reference:

- Add entries in the .NET config file
 - Connection string

A standard ADO.NET connection string is used rather than the Entity Framework connection string used by Database First or Model First paths. The connection string name should match the application context name. The

connection string entry is an element of the `connectionStrings` section in the configuration file.

- Provider registration

Entity Framework uses the provider registration to determine the assembly to use for Oracle Entity Framework functionality. The provider registration is an element of the `providers` section within the `entityFramework` section in the application configuration file.

- Add Assembly reference

Add Oracle Entity Framework assembly to the project references.

 **Note:**

When using the official ODP.NET, NuGet installation, these preceding sections are created automatically, if they do not already exist. After the NuGet install, the ODP.NET connection string will need to be customized to the application's specific settings.

When using the Oracle Universal Installer or xcopy install, the preceding sections must all be configured manually.

Examples of connection strings are as follows:

- ODP.NET, Unmanaged Driver

```
<add name="TestContext" providerName="Oracle.DataAccess.Client"
connectionString="User Id=test;Password=testpassword;Data Source=efctest" />
```

- ODP.NET, Managed Driver

```
<add name="TestContext" providerName="Oracle.ManagedDataAccess.Client"
connectionString="User Id=test;Password=testpassword;Data Source=efctest" />
```

Examples of Oracle provider registration are as follows:

- ODP.NET, Unmanaged Driver

```
<provider invariantName="Oracle.DataAccess.Client"
type="Oracle.DataAccess.EntityFramework.EFOracleProviderServices,
Oracle.DataAccess.EntityFramework, Version=6.121.2.0, Culture=neutral,
PublicKeyToken=89b483f429c47342" />
```

- ODP.NET, Managed Driver

```
<provider invariantName="Oracle.ManagedDataAccess.Client"
type="Oracle.ManagedDataAccess.EntityFramework.EFOracleProviderServices,
Oracle.ManagedDataAccess.EntityFramework, Version=6.121.2.0, Culture=neutral,
PublicKeyToken=89b483f429c47342" />
```

Entity Framework 6 Code-Based Registration

Entity Framework 6 allows an application to register with an Entity Framework provider without using any configuration file. With ODP.NET, Managed Driver, the code will look as follows:

```
// C#
using Oracle.ManagedDataAccess.EntityFramework;
```

```

...
public class ModelConfiguration : DbConfiguration
{
    public ModelConfiguration()
    {
        SetProviderServices("Oracle.ManagedDataAccess.Client",
EFOracleProviderServices.Instance);
    }
}

```

For ODP.NET, Unmanaged Driver, replace occurrences of `ManagedDataAccess` with `DataAccess` in the preceding code.

If you are using code-based registration, then the configuration file should not include the registration. The configuration file based registration overrides the code-based registration.

Migrating from ODP.NET, Unmanaged Driver to ODP.NET, Managed Driver

To ease migration, the APIs of ODP.NET, Managed Driver are a complete subset of the APIs of ODP.NET, Unmanaged Driver. As long as the existing unmanaged ODP.NET applications use currently available managed ODP.NET APIs, migration is straightforward and simple.

In future versions, the managed driver will support more APIs of ODP.NET, Unmanaged Driver. Both drivers will continue to be enhanced to support the latest Oracle Database and .NET Framework features.

To migrate from unmanaged to managed ODP.NET, perform the following steps:

1. Add a Reference to `Oracle.ManagedDataAccess.dll` in the .NET project.
2. Change the existing ODP.NET, Unmanaged Driver namespace references to ODP.NET, Managed Driver references.

```

// C#
using Oracle.ManagedDataAccess.Client;
using Oracle.ManagedDataAccess.Types;

// VB
Imports Oracle.ManagedDataAccess.Client
Imports Oracle.ManagedDataAccess.Types

```

3. Some provider configuration settings may need to be migrated because ODP.NET, Managed Driver supports very few Windows Registry settings and a different .NET configuration setting format.

See Also:

[Configuring Oracle Data Provider for .NET](#) for more information.

Configuring a Port to Listen for Database Notifications

Oracle Data Provider for .NET opens a port to listen for database notifications when the following features are used:

- HA Events
- Load Balancing
- Continuous Query Notification
- AQ Notifications

All these features share the same port, which can be configured centrally by setting the `db notification` port in an application or web configuration file.

If the configuration file does not exist or the `db notification` port is not specified, ODP.NET uses a valid, random port number. The configuration file may also request for a random port by specifying a `db notification` port value of `-1`. To specify a particular port in ODP.NET, Unmanaged Driver, for example, 1200, an application or web configuration file can be used as follows:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DbNotificationPort" value="1200"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

To specify a particular port in ODP.NET, Managed Driver, an application or web configuration file can be used as follows:

```
<configuration>
  <oracle.manageddataaccess.client>
    <version number="*">
      <settings>
        <setting name="DbNotificationPort" value="1200"/>
      </settings>
    </version>
  </oracle.manageddataaccess.client>
</configuration>
```

The port number should be unique for each process running on a computer. Thus, the port number should be set uniquely for each application either programmatically or through an application config file. Note that if the specified port number is already in use or invalid, ODP.NET does not provide any errors.

When the process using ODP.NET starts, the application reads the `db notification` port number and listens on that port. Once the port is opened, the port number cannot be changed during the lifetime of the process.

 **See Also:**

- ["Fast Application Notification"](#)
- ["Runtime Connection Load Balancing"](#)
- ["Continuous Query Notification Support "](#)
- ["Oracle Database Advanced Queuing Support"](#)

General .NET Programming Recommendations and Tips for ODP.NET

- `Thread.Abort()` should not be used, as unmanaged resources may remain unreleased, which can potentially cause memory leaks and hangs.
- To optimize resource usage, ODP.NET objects, such as `OracleConnection` and `OracleCommand`, should be explicitly closed or disposed, or both, when they are no longer needed. This should be done rather than relying on the .NET Framework garbage collector to reclaim resources. Many users have found that under stress conditions, explicit `Close` or `Dispose` calls result in much lower resource usage.
- It is recommended not to proceed with application execution if the application encounters exceptions that are associated with possible memory corruption, such as `System.AccessViolationException` and `System.Runtime.InteropServices.SEHException`.
- If the `HKEY_LOCAL_MACHINE\Software\Oracle\NLS_LANG` registry entry is set to `NA`, ODP.NET encounters `ORA-12705` errors. To eliminate this problem, remove the `HKEY_LOCAL_MACHINE\Software\Oracle\NLS_LANG` registry entry.
- .NET requires certain special characters, such as backslash `\` and double quotation mark `"`, to be escaped when used within a string. In a connection string or a class property, .NET requires using the escape character, backslash, before the special character. To represent a backslash in a string, use a double backslash `\\`. To represent a double quotation mark in a string, use a backslash followed by a double quotation mark `\"`. Alternatively, use the at sign `@` to mark the entire string as a verbatim string literal, in which case .NET ignores special characters.

3

Features of Oracle Data Provider for .NET

This section describes Oracle Data Provider for .NET provider-specific features and how to use them to develop .NET applications.

This section contains the following topics:

- [Base Classes and Provider Factory Classes](#)
- [Code Access Security](#)
- [Connecting to Oracle Database](#)
- [Real Application Clusters and Global Data Services](#)
- [Using Transaction Guard to Prevent Logical Corruption](#)
- [Application Continuity](#)
- [Database Sharding](#)
- [OracleCommand Object](#)
- [ODP.NET Types Overview](#)
- [Obtaining Data from an OracleDataReader Object](#)
- [PL/SQL REF CURSOR and OracleRefCursor](#)
- [Implicit REF CURSOR Binding](#)
- [LOB Support](#)
- [ODP.NET XML Support](#)
- [Oracle User-Defined Types \(UDTs\) and .NET Custom Types](#)
- [Bulk Copy](#)
- [Oracle Database Advanced Queuing Support](#)
- [Continuous Query Notification Support](#)
- [OracleDataAdapter Safe Type Mapping](#)
- [OracleDataAdapter Requery Property](#)
- [Guaranteeing Uniqueness in Updating DataSet to Database](#)
- [Globalization Support](#)
- [Debug Tracing](#)
- [Database Application Migration: SQL Translation Framework](#)

Base Classes and Provider Factory Classes

With ADO.NET, data classes derive from the base classes defined in the `System.Data.Common` namespace. Developers can create provider-specific instances of these base classes using provider factory classes.

Provider factory classes allow generic data access code to access multiple data sources with a minimum of data source-specific code. This reduces much of the conditional logic currently used by applications accessing multiple data sources.

Using Oracle Data Provider for .NET, the `OracleClientFactory` class can be returned and instantiated, enabling an application to create instances of the following ODP.NET classes that inherit from the base classes:

Table 3-1 ODP.NET Classes that Inherit from ADO.NET 2.0 Base Classes

ODP.NET Classes	Inherited from ADO.NET 2.0 Base Class
<code>OracleClientFactory</code>	<code>DbProviderFactory</code>
<code>OracleCommand</code>	<code>DbCommand</code>
<code>OracleCommandBuilder</code>	<code>DbCommandBuilder</code>
<code>OracleConnection</code>	<code>DbConnection</code>
<code>OracleConnectionStringBuilder</code>	<code>DbConnectionStringBuilder</code>
<code>OracleDataAdapter</code>	<code>DbDataAdapter</code>
<code>OracleDataReader</code>	<code>DbDataReader</code>
<code>OracleDataSourceEnumerator</code>	<code>DbDataSourceEnumerator</code>
<code>OracleException</code>	<code>DbException</code>
<code>OracleParameter</code>	<code>DbParameter</code>
<code>OracleParameterCollection</code>	<code>DbParameterCollection</code>
<code>OracleTransaction</code>	<code>DbTransaction</code>

In general, applications still require Oracle-specific connection strings, SQL or stored procedure calls, and declare that a factory from ODP.NET is used.



Note:

ODP.NET Core does not support factory classes.



See Also:

[OracleClientFactory Class](#)

Code Access Security

ODP.NET implements code access security through the `OraclePermission` class. This ensures that application code trying to access the database has the requisite permission to do so.

When a .NET assembly tries to access Oracle Database through ODP.NET, ODP.NET demands `OraclePermission`. The .NET runtime security system checks to see whether the calling assembly, and all other assemblies in the call stack, have

`OraclePermission` granted to them. If all assemblies in the call stack have `OraclePermission` granted to them, then the calling assembly can access the database. If any one of the assemblies in the call stack does not have `OraclePermission` granted to it, then a security exception is thrown.

 **Note:**

ODP.NET Core does not support Code Access Security.

Configuring `OraclePermission`

The `DemandOraclePermission` configuration attribute is used to enable or disable `OraclePermission` demand for an ODP.NET API. The `DemandOraclePermission` value can be specified in the Windows registry for unmanaged ODP.NET only, or an individual application configuration file for both unmanaged and managed ODP.NET.

The following Windows registry key is used to configure the `DemandOraclePermission` configuration attribute:

```
HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version\DemandOraclePermission
```

Here `Assembly_Version` is the full assembly version number of `Oracle.DataAccess.dll`. The `DemandOraclePermission` key is of type `REG_SZ`. It can be set to either 1 (enabled) or 0 (disabled).

You can also enable `OraclePermission` demand for an individual application using its application configuration file. The following example enables the `DemandOraclePermission` property in an application configuration file for ODP.NET, Unmanaged Driver:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DemandOraclePermission" value="1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

Similarly, you can use `DemandOraclePermission` to configure ODP.NET, Managed Driver under the settings section for managed provider configuration. See also "[settings section](#)" for more information.

An application or assembly can successfully access the database if `OraclePermission` has been added to the permission set associated with the assembly's code group. A system administrator can modify the appropriate permission set manually or by using the Microsoft .NET configuration tool (`Mscorcfg.msc`).

Administrators may also use an appropriate .NET Framework Tool, such as the Code Access Security Policy Tool (`Caspol.exe`), to modify security policy at the machine, user, and enterprise levels for including `OraclePermission`.

`OracleConnection` makes security demands using the `OraclePermission` object when `OraclePermission` demand has been enabled using `DemandOraclePermission` configuration attribute. Application developers should make sure that their code has sufficient permission before using `OracleConnection`.

 **See Also:**

- ["OraclePermission Class"](#)
- ["OraclePermissionAttribute Class"](#)

Configuring OraclePermission for Web Applications with High or Medium Trust Levels

For Web applications operating under high or medium trust, `OraclePermission` needs to be configured in the appropriate `web_TrustLevel.config` file, so that the application does not encounter any security errors.

`OraclePermission` can be configured using the `OraProvCfg` tool. `OraProvCfg.exe` adds appropriate entries to the `web_hightrust.config` and `web_mediumtrust.config` files associated with the specified .NET framework version. The following example illustrates using the `OraProvCfg` tool for configuring `OraclePermission` in a .NET 2.0 Web application:

```
OraProvCfg.exe /action:config /product:odp /component:oraclepermission  
/frameworkversion:v2.0.50727  
/providerpath:full_path_of_Oracle.DataAccess.dll
```

On running the preceding command, the following entry is added to the `web_hightrust.config` and `web_mediumtrust.config` files under the ASP.NET permission set:

```
<IPermission class="Oracle.DataAccess.Client.OraclePermission, Oracle.DataAccess,  
Version=2.112.2.0, Culture=neutral, PublicKeyToken=89b483f429c47342" version="1"  
Unrestricted="true" />
```

`OraProvCfg` can also be used to remove these entries from the `.config` files when required. The following example illustrates this:

```
OraProvCfg.exe /action:unconfig /product:odp /component:oraclepermission  
/frameworkversion:v2.0.50727  
/providerpath:full_path_of_Oracle.DataAccess.dll
```

Configuring OraclePermission for Windows Applications Running in a Partial Trust Environment

For Windows applications operating in a partial trust environment, the `OraclePermission` entry should be specified under the appropriate permission set in the `security.config` file. The `security.config` file is available in the `%windir%\Microsoft.NET\Framework\{version}\CONFIG` folder.

The following example specifies the `OraclePermission` entry for a .NET 2.0 Windows application:

```
<IPermission class="Oracle.DataAccess.Client.OraclePermission, Oracle.DataAccess,  
Version=2.112.2.0, Culture=neutral, PublicKeyToken=89b483f429c47342" version="1"  
Unrestricted="true" />
```

Connecting to Oracle Database

Oracle Data Provider for .NET can connect to Oracle Database in a number of ways, such as using a user name and password, Windows Native Authentication, Kerberos, and Transport Layer Security/Secure Sockets Layer. This section describes `OracleConnection` provider-specific features, including:

- [Connecting to Oracle Database Cloud Service](#)
- [Connection String Attributes](#)
- [Connection String Builder](#)
- [Specifying the Data Source Attribute](#)
- [Using Transport Layer Security and Secure Sockets Layer](#)
- [Using Secure External Password Store](#)
- [Using Kerberos](#)
- [Using Windows Native Authentication \(NTS\)](#)
- [Network Data Encryption and Integrity](#)
- [Schema Discovery](#)
- [Connection Pooling](#)
- [Connection Pool Management](#)
- [Connection Performance Counters](#)
- [Database Resident Connection Pooling](#)
- [Oracle Multitenant and Pluggable Databases](#)
- [Edition-Based Redefinition](#)
- [Operating System Authentication](#)
- [Privileged Connections](#)
- [Connection Pooling with OracleCredential](#)
- [Password Expiration](#)
- [Proxy Authentication](#)
- [Dynamic Distributed Transaction Enlistment](#)
- [Client Identifier and End-to-End Tracing](#)
- [Transparent Application Failover \(TAF\) Callback Support](#)

Connecting to Oracle Database Cloud Service

ODP.NET Core, managed, and unmanaged drivers all support connectivity with Oracle Database Cloud Services, including Oracle Autonomous Database.

Set-up Instructions

Oracle recommends using the latest ODP.NET version available when connecting to Oracle Database Cloud Services. You will find instructions about how to download, install, and configure ODP.NET and Oracle Developer Tools for Visual Studio below.

Oracle Autonomous Database: <https://www.oracle.com/technetwork/topics/dotnet/tech-info/default-5032178.html>

Oracle Database as a Service: <https://www.oracle.com/technetwork/topics/dotnet/dotnetdbaas-3208838.html>

Connection String Attributes

Table 3-2 lists the supported connection string attributes.

Table 3-2 Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Application Continuity	Enables database requests to automatically replay transactional or non-transactional operations in a non-disruptive and rapid manner in the event of a severed database session, which results in a recoverable error. <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>	true
Connection Lifetime	Minimum life time (in seconds) of the connection.	0
Connection Timeout	The time to wait (in seconds) for a new connection or an idle connection from the connection pool before a connection time out error can occur.	15
Context Connection	Returns an implicit database connection if set to true. <i>Supported in a .NET stored procedure only</i>	false
Data Source	Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.	empty string
DBA Privilege	Administrative privileges: SYSDBA or SYSOPER.	empty string
Decr Pool Size	Number of connections that are closed when an excessive amount of established connections are unused.	1
Enlist	Controls the enlistment behavior and capabilities of a connection in context of COM+ transactions or System.Transactions.	true
HA Events	Enables ODP.NET connection pool to proactively remove connections from the pool when an Oracle database service, service member, instance, or node goes down. Works with Oracle Global Data Services, including Oracle RAC, Data Guard, GoldenGate, and some single instance deployments.	true

Table 3-2 (Cont.) Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Load Balancing	Enables ODP.NET connection pool to balance work requests across Oracle database instances based on the load balancing advisory and service goal. Works with Oracle Global Data Services, including Oracle RAC, Active Data Guard, and GoldenGate.	true
Incr Pool Size	Number of new connections to be created when all connections in the pool are in use.	5
Max Pool Size	Maximum number of connections in a pool.	100
Metadata Pooling	Caches metadata information.	True
Min Pool Size	Minimum number of connections in a pool.	1
Password	Password for the user specified by User Id.	empty string
Persist Security Info	Retrieval of the password in the connection string.	false
Pooling	Connection pooling.	true
Promotable Transaction	Indicates whether or not a transaction is local or distributed throughout its lifetime.	promotable
Proxy User Id	User name of the proxy user.	empty string
Proxy Password	Password of the proxy user.	empty string
Self Tuning	Enables or disables self-tuning for a connection.	true
Statement Cache Purge	Statement cache purged when the connection goes back to the pool.	false
Statement Cache Size	Statement cache enabled and cache size, that is, the maximum number of statements that can be cached.	0
User Id	Oracle user name.	empty string
Validate Connection	Validation of connections coming from the pool.	false

The following example uses connection string attributes to connect to Oracle Database:

```
// C#

using System;
using Oracle.DataAccess.Client;

class ConnectionSample
{
    static void Main()
    {
```

```
OracleConnection con = new OracleConnection();

//using connection string attributes to connect to Oracle Database
con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
con.Open();
Console.WriteLine("Connected to Oracle" + con.ServerVersion);

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
Console.WriteLine("Disconnected");
}
}
```

 **See Also:**

- ["OracleConnection Properties"](#) for detailed information on connection attributes
- ["OracleCommand Object"](#) for detailed information on statement caching

Connection String Builder

The `OracleConnectionStringBuilder` class makes creating connection strings less error-prone and easier to manage.

Using this class, developers can employ a configuration file to provide the connection string and/or dynamically set the values through the key/value pairs. One example of a configuration file entry follows:

```
<configuration>
  <connectionStrings>
    <add name="Publications" providerName="Oracle.DataAccess.Client"
        connectionString="User Id=scott;Password=tiger;Data Source=inst1" />
  </connectionStrings>
</configuration>
```

Connection string information can be retrieved by specifying the connection string name, in this example, `Publications`. Then, based on the `providerName`, the appropriate factory for that provider can be obtained. This makes managing and modifying the connection string easier. In addition, this provides better security against string injection into a connection string.

 **See Also:**

[OracleConnectionStringBuilder Class](#)

Specifying the Data Source Attribute

This section describes different ways of specifying the data source attribute.

The following example shows a connect descriptor mapped to a TNS alias called `sales` in the `tnsnames.ora` file:

```
sales=
  (DESCRIPTION=
    (ADDRESS= (PROTOCOL=tcp)(HOST=sales-server)(PORT=1521))
    (CONNECT_DATA=
      (SERVICE_NAME=sales.us.acme.com)))
```

The connection pool will maintain the full descriptor of an alias so that subsequent connection requests with the same connection string will not need to resolve the alias again. This applies to `tnsnames.ora`, `.NET` config data sources, and LDAP aliases. To flush out the cached full descriptor maintained by the connection pool, invoke `OracleDataSourceEnumerator.GetDataSources()` followed by `OracleConnection.ClearPool()` or `OracleConnection.ClearAllPools()`.

If connection pooling is not used, the alias will need to be resolved to the full descriptor for each request. In the case of LDAP, the LDAP server is contacted for each connection request.

Using the TNS Alias

To connect as `scott/tiger` using the TNS Alias, a valid connection appears as follows:

```
"user id=scott;password=tiger;data source=sales";
```

Using the Connect Descriptor

ODP.NET also allows applications to connect without the use of the `tnsnames.ora` file. To do so, the entire connect descriptor can be used as the "data source".

The connection string appears as follows:

```
"user id=scott;password=tiger;data source=" +
  "(DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)" +
  "(HOST=sales-server)(PORT=1521))(CONNECT_DATA="+
  "(SERVICE_NAME=sales.us.acme.com)))"
```

Easy Connect and Easy Connect Plus Naming Methods

The Easy Connect and Easy Connect Plus naming methods enable clients to connect to a database without any configuration.

To use the Easy Connect naming method, ensure that `EZCONNECT` is specified by the `NAMES.DIRECTORY_PATH` parameter in the `sqlnet.ora` file as follows:

```
NAMES.DIRECTORY_PATH= (TNSNAMES, EZCONNECT)
```

With this enabled, ODP.NET allows applications to specify the Data Source attribute in the form of:

```
//host:[port]/[service_name]
```

Using the same example, some valid connection strings follow:

```
"user id=scott;password=tiger;data source=//sales-server:1521/sales.us.acme.com"
"user id=scott;password=tiger;data source=//sales-server/sales.us.acme.com"
"user id=scott;password=tiger;data source=sales-server/sales.us.acme.com"
```


If the port number is not specified, 1521 is used by default.

Easy Connect has been enhanced in ODP.NET 19c to support a wider application breadth, including clustered or cloud databases, and for ease of use. These improvements are called Easy Connect Plus and its features include:

- TCP/IP with SSL/TLS
- Any SQL*Net description level parameter can be used
- Multiple hosts and ports
- A straightforward name-value pair format

The syntax uses the question mark symbol ? to indicate the name-value pairs start and the ampersand symbol & to delimit each name-value pair. The entire connect string must be specified as a single string. Leading and trailing white spaces are ignored within parameter values. If whitespace is required as part of the value, it should be placed within double-quotes.

Easy Connect Plus syntax:

```
[[protocol:]]host1{,host12}[:port1]{,host2:port2}[/service_name][:server][/  
instance_name][?parameter_name=value{&parameter_name=value}]
```

Easy Connect Plus samples:

- `tcps://salesserver1:1521/sales.us.example.com`
- `salesserver1:1521,salesserver2,salesserver3:1522/sales.us.example.com`
- `tcps://salesserver1:1521/sales.us.example.com?wallet_location=D:/oracle`
- `tcps://salesserver1:1521/sales.us.example.com?
ssl_server_cert_dn=cn=sales,cn=OracleContext,dc=us,dc=example,dc=com`
- `tcps://salesserver1:1521/sales.us.example.com?https_proxy=www-
proxy.mycompany.com&https_proxy_port=80`
- `salesserver1:1521/sales.us.example.com?
connect_timeout=60&transport_connect_timeout=30&retry_count=3`

See Also:

Oracle Database Net Services Administrator's Guide for details and requirements in the section *Using Easy Connect Naming Method*

Using LDAP

ODP.NET can connect with connect identifiers mapped to connect descriptors in an LDAP-compliant directory server, such as Oracle Internet Directory and Microsoft Active Directory.

To configure LDAP for ODP.NET, Unmanaged Driver, follow these Oracle documentation instructions in *Configuring the Directory Naming Method* in *Oracle Database Net Services Administrator's Guide*.

To configure LDAP for ODP.NET, Managed Driver, follow the instructions in "[settings section](#)" and "[LDAPsettings section](#)."

Beginning with Oracle Database release 18c, version 18.1, organizations can use centrally managed users (CMUs) with Active Directory. This feature is designed for organizations who prefer to use Active Directory as their centralized identity management solution. Organizations can use Kerberos, PKI, or password authentication with CMU and Active Directory.

 **See Also:**

Oracle Database Net Services Administrator's Guide and *Oracle Database Security Guide* for details and requirements in the section Using LDAP

Data Source Enumerator

The data source enumerator enables the application to generically obtain a collection of the Oracle data sources that the application can connect to.

 **See Also:**

["OracleDataSourceEnumerator Class"](#)

Using Transport Layer Security and Secure Sockets Layer

Transport Layer Security (TLS) and its predecessor, Secure Sockets Layer (SSL), are industry standard protocols for securing network connections. Both managed and unmanaged ODP.NET support SSL for database and transport authentication.

Secure Sockets Layer and Transport Layer Security Differences

Although SSL was primarily developed by Netscape Communications Corporation, the Internet Engineering Task Force (IETF) took over development of it, and renamed it Transport Layer Security (TLS).

Essentially, TLS is an incremental improvement to SSL version 3.0.

ODP.NET, Managed Driver supports SSL 3.0 and TLS 1.0, 1.1, and 1.2. ODP.NET, Unmanaged Driver supports the same SSL and TLS versions as the Oracle Database Client version it is certified with.

The SSL/TLS client can ensure that the distinguished name (DN) is correct for the database server it is trying to connect to. Parameters for DN Matching are `SSL_SERVER_DN_MATCH` (`sqlnet.ora`) and `SSL_SERVER_CERT_DN` (`tnsnames.ora`), which can be defined in the .NET config file as well.

To turn DN Match on, set `SSL_SERVER_DN_MATCH` to True (or On or Yes).

`SSL_SERVER_CERT_DN` is optional. It allows the administrator to specify exactly the DN they want to match. If the `SSL_SERVER_CERT_DN` is not set, then the match is done by comparing the `SERVICE_NAME` value to the Common Name (CN) portion of the server certificate's DN.

 **See Also:**

- The TLS Protocol Version 1.0 [RFC 2246] at the IETF Web site, which can be found at:
<http://www.ietf.org>
- SSL_VERSION in the "[settings section](#)."

 **Note:**

To simplify the discussion, this section uses the term SSL where either SSL or TLS may be appropriate because SSL is the most widely recognized term. However, where distinctions occur between how you use or configure these protocols, this section specifies what is appropriate for either SSL or TLS.

ODP.NET Secure Sockets Layer Configuration

When you configure Secure Sockets Layer on the client, you must confirm that the wallet is created and use TCP/IP with SSL on the client. Optionally, you can perform additional steps to enhance the configuration.

SSL Configuration Topics:

- [Step 1: Confirm Client Wallet Creation](#)
- [Step 2: Use TCP/IP with SSL on the Client](#)
- [Step 3: Specify Required Client SSL Configuration \(Wallet Location\)](#)
- [Step 4: Set the Required SSL Version on the Client \(Optional\)](#)
- [Step 5: Set SSL as an Authentication Service on the Client \(Optional\)](#)

Step 1: Confirm Client Wallet Creation

Before proceeding to the next step, you must confirm that a wallet has been created on the client and that the client has a valid certificate.

ODP.NET, Managed Driver supports file and Microsoft Certificate Store (MCS) based wallets.

- For file-based wallets, use Oracle Wallet Manager to check that the wallet has been created. See [Step 1A: Confirm Wallet Creation on the Server](#) in *Oracle Database Security Guide* for information about checking a wallet.
- For MCS, the Windows domain credentials will be used for the client credentials. Thus, a valid domain logon must be used while running the ODP.NET application. ODP.NET, Managed Driver will retrieve the credentials from the MY or Personal certificate store. Note that the server must also be configured to use MCS wallets. See [Microsoft Certificate Services](#) in *Oracle Database Platform Guide for Microsoft Windows* for information about setting up the server for MCS.

Step 2: Use TCP/IP with SSL on the Client

The ODP.NET Data Source must be modified to use SSL. Specifically, the transport protocol must be changed to use TCP/IP with SSL or what Oracle calls "tcps". An example ODP.NET Data Source for use with SSL is:

```
finance = (DESCRIPTION=
  (ADDRESS = (PROTOCOL=tcps) (HOST=finance_server) (PORT=1575) )
  (CONNECT_DATA = (SERVICE_NAME=Finance.us.example.com) ) )
```

Step 3: Specify Required Client SSL Configuration (Wallet Location)

Edit the `sqlnet.ora` or `.NET` application configuration to specify the wallet location.

- An example of setting the SSL wallet location for file based wallets, where `<wallet_location>` is the specified location where the client wallet is stored:

```
wallet_location = (SOURCE=(METHOD= File)
  (METHOD_DATA=(DIRECTORY=<wallet_location>)))
```

- An example of setting the SSL wallet location for MCS based wallets is:

```
wallet_location = (SOURCE=(METHOD= MCS))
```

Step 4: Set the Required SSL Version on the Client (Optional)

The `SSL_VERSION` parameter can be set through the `sqlnet.ora` or the `.NET` `application.config`, `web.config`, or `machine.config` file. Normally, it is not necessary to set this parameter. The default setting for this parameter is `any`, which allows the database server to apply any necessary restrictions to the SSL version accepted. An example setting in the `sqlnet.ora` is:

```
SSL_VERSION=3.0
```

Step 5: Set SSL as an Authentication Service on the Client (Optional)

Set the `SQLNET.AUTHENTICATION_SERVICES` parameter in the `sqlnet.ora` or `application.config`, `web.config`, or `machine.config` file to allow SSL to be used as a database external authentication methodology.

Note that SSL can be used as just a transport encryption vehicle. Hence, the "optional" designation for this setting.

If SSL is to be used as a database external Authentication Service, then a database externally authenticated user matching the client certificate must be created.

An example setting allowing SSL external authentication in the `sqlnet.ora` is:

```
SQLNET.AUTHENTICATION_SERVICES = (TCPS)
```

 **Note:**

Prior to ODAC 12c Release 4, ODP.NET, Managed Driver SSL connections would be redirected to dynamic (ephemeral) port on the database server machine. With ODAC 12c Release 4 and later, managed ODP.NET SSL connections will now continue to the original socket connection to the Oracle Listener. Hence, firewalls will now only need to allow access to the Oracle Listener's port (e.g., 1521).

 **See Also:**

- Enabling Secure Sockets Layer in *Oracle Database Security Guide* for more information about TLS/SSL and configuration with Oracle database.
- Creating a User Who Is Authenticated Externally in *Oracle Database Security Guide* for more information about creating externally identified database users.

Troubleshooting TLS/SSL Setup

This section discusses commonly encountered issues and their typical resolution steps.

Common TLS/SSL Wallet Errors

Microsoft Windows now restricts wallets from using the MD5 algorithm. Oracle wallets may have been generated with this algorithm as that was the default option in Oracle Public Key Infrastructure (`orapki`) utility 12.1 and earlier.

`Orapki` refers to `orapki.exe`. This utility is part of full Oracle client (administrator) installations. It is not included with Oracle Instant Client. The utility is only needed to setup up the wallet; it is not necessary to deploy it with the wallet.

When you setup TLS/SSL and encounter an "ORA-0052: Failure during SSL handshake" error combined with a 0x80004005 error code and first inner exception "A SSPI-call failed" and second inner exception "A token sent to the function is invalid", then it is very likely that Microsoft Security Support Provider Interface (SSPI) rejected your Oracle Wallet, such as when MD5 is used. This is a failure on the handshake. You can resolve this error by using the SHA-2 algorithm instead.

If the second inner exception instead indicates "The credentials supplied to the package were not recognized", it is possible the user certificate was generated without a certificate authority (CA). You can resolve this error by using `orapki` to generate a CA/root certificate and then regenerating your user wallet/certificate to point to this new CA/root certificate.

The steps below will regenerate your Oracle Wallet using `orapki` and SHA-2. Any `orapki` version can be used to generate the wallet with these instructions.

1. Create root wallet, for example, a CA wallet.

```
orapki wallet create -wallet ./root -pwd <password>
```

2. Add a self-signed certificate (CA certificate) to the root wallet.

```
orapki wallet add -wallet ./root -dn 'CN=<my root>' -keysize 1024 -self_signed -validity 3650 -pwd <password> -sign_alg sha512
```

3. Export the self-signed certificate from the wallet.

```
orapki wallet export -wallet ./root -dn 'CN=<my root>' -cert ./root/b64certificate.txt -pwd <password>
```

4. Create a user wallet, for example, a customer wallet.

```
orapki wallet create -wallet ./user -pwd <password> -auto_login
```

5. Add a certificate request.

```
orapki wallet add -wallet ./user -dn 'CN=<client's hostname>' -keysize 1024 -pwd <password> -sign_alg sha512
```

6. Export the certificate request.

```
orapki wallet export -wallet ./user -dn 'CN=<client's hostname>' -request ./user/creq.txt -pwd <password>
```

7. Create a certificate issued by a CA.

```
orapki cert create -wallet ./root -request ./user/creq.txt -cert ./user/cert.txt -validity 3650 -pwd <password> -sign_alg sha512
```

8. Add a trusted certificate (CA certificate) to the wallet. This example assumes the same CA for both the client and server wallets.

```
orapki wallet add -wallet ./user -trusted_cert -cert ./root/b64certificate.txt -pwd <password>
```

9. Add a user certificate.

```
orapki wallet add -wallet ./user -user_cert -cert ./user/cert.txt -pwd <password> -sign_alg sha512
```

10. Display contents of user wallet.

```
orapki wallet display -wallet ./user -pwd <password>
```

11. Create a server wallet.

```
orapki wallet create -wallet ./server -pwd <password> -auto_login
```

12. Add a server certificate request.

```
orapki wallet add -wallet ./server -dn 'CN=<server's hostname>' -  
keysize 1024 -pwd <password> -sign_alg sha512
```

13. Export the certificate request.

```
orapki wallet export -wallet ./server -dn 'CN=<server's hostname>' -  
request ./server/creq.txt -pwd <password>
```

14. Create a server certificate issued by a CA.

```
orapki cert create -wallet ./root -request ./server/creq.txt -cert ./  
server/cert.txt -validity 3650 -pwd <password> -sign_alg sha512
```

15. Add a trusted certificate (CA certificate) to the server wallet. This example assumes the same CA for both the client and server wallets.

```
orapki wallet add -wallet ./server -trusted_cert -cert ./root/  
b64certificate.txt -pwd <password>
```

16. Add an user_cert certificate for the server wallet.

```
orapki wallet add -wallet ./server -user_cert -cert ./server/cert.txt -  
pwd <password> -sign_alg sha512
```

17. Display contents of server wallet.

```
orapki wallet display -wallet ./server -pwd <password>
```

HTTPS Proxy for Cloud Connections

ODP.NET supports HTTPS proxy configuration. The feature enables tunneling secure connections over forward HTTP proxy using the HTTP CONNECT method.

HTTPS proxy improves public cloud database service access as it eliminates requiring the client side firewall to open an outbound port.

This feature only works when using TCP/IP with SSL/TLS, which can be enabled in the connect descriptor (e.g. PROTOCOL=TCPS in `tnsnames.ora`). It is similar to the web browser setting for intranet users who connect to internet hosts.

To configure HTTPS proxy, use the following for each provider type:

- **ODP.NET Core** - OracleConfiguration `HttpsProxy`, `HttpsProxyPort`, and `UseHttpsProxy` properties
- **Managed ODP.NET** - .NET configuration file properties `HTTPS_PROXY`, `HTTPS_PROXY_PORT`, and `USE_HTTPS_PROXY`
- **Unmanaged ODP.NET** – modify the `tnsnames.ora`, `HTTPS_PROXY`, and `HTTPS_PROXY_PORT` values and `SQLNET.USE_HTTPS_PROXY` value, such as

```
(DESCRIPTION=ADDRESS=(  
HTTPS_PROXY= www-proxy.mycompany.com)(HTTPS_PROXY_PORT=8080)(PROTOCOL=TCPS)
```

```
(HOST=sales2-svr)(PORT=443)  
(CONNECT_DATA=(SERVICE_NAME=sales.us.example.com))
```

SQLNET.USE_HTTPS_PROXY should be set to on.

Using Secure External Password Store

The Secure External Password Store (SEPS) is the use of a client-side wallet for securely storing the password credentials. Both ODP.NET, Managed Driver and Unmanaged Driver can be configured to use the external password store.

An Oracle wallet is a container that securely stores authentication and signing credentials. Wallets can simplify large-scale deployments that rely on password credentials for database connections. Applications no longer need embedded user names and passwords, which reduces security risk.

Note:

ODP.NET Core supports SEPS on Windows only.

Configuring Secure External Password Store (SEPS)

Steps for configuring SEPS:

- [Step 1. Create the wallet file](#)
- [Step 2. Point the configuration to the client wallet](#)
- [Step 3. Turn on SEPS](#)

Step 1. Create the wallet file

Use the `mkstore` utility to create the wallet file and insert the credentials.

Step 1a. Create a wallet on the client by using the following syntax at the command line:

```
mkstore -wrl wallet_location -create
```

For example:

```
mkstore -wrl c:\oracle\product\12.1.0\db_1\wallets -create  
Enter password: password
```

Step 1b. Create database connection credentials in the wallet by using the following syntax at the command line:

```
mkstore -wrl wallet_location -createCredential db_connect_string username  
Enter password: password
```

For example:

```
mkstore -wrl c:\oracle\product\12.1.0\db_1\wallets -createCredential orcl system  
Enter password: password
```


Step 2. Point the configuration to the client wallet

In the client `sqlnet.ora` file, enter the `WALLET_LOCATION` parameter and set it to the directory location of the wallet you created in Step 1.

For example, if you created the wallet in `$ORACLE_HOME/network/admin` and your Oracle home is set to `C:\app\client\<user>\product\<version>\client_1\`, then you need to enter the following into your client `sqlnet.ora` file:

```
WALLET_LOCATION =
  (SOURCE =(METHOD = FILE)
   (METHOD_DATA =
    (DIRECTORY = C:\app\client\<user>\product\<version>\client_1\Network
    \Admin) ) )
```

Step 3. Turn on SEPS

Step 3. Turn on SEPS

```
SQLNET.WALLET_OVERRIDE = TRUE
```

This setting causes all `CONNECT /@db_connect_string` statements to use the information in the wallet at the specified location to authenticate to databases.

When external authentication is in use, an authenticated user with such a wallet can use the `CONNECT /@db_connect_string` syntax to access the previously specified databases without providing a user name and password. Note however, that the wallet file needs to be kept up to date with the database credentials. If the database credentials change, but the wallet file is not changed appropriately, then the connections will fail.

See Also:

- [Oracle Data Provider for .NET, Managed Driver Configuration](#) for more details about the wallet settings.
- [Managing the Secure External Password Store for Password Credentials in Oracle Database Security Guide](#) for more information about secure external password store and configuration with Oracle database.

Using Kerberos

Kerberos is a network authentication service for security in distributed environments. ODP.NET applications can use Kerberos for single sign-on and centralized user authentication. ODP.NET, Unmanaged Driver and Managed Driver both support Kerberos for external authentication to the database server.

 **Note:**

ODP.NET Core does not support Kerberos
Managed ODP.NET does not support Kerberos constrained delegation

File Based Credential Cache and MSLSA

ODP.NET supports both a file-based Kerberos client credential cache (CC) and the ability to use Windows logon credentials as Kerberos client credentials. The latter is called MSLSA-based Kerberos authentication.

In order to utilize a file based Kerberos client credential cache (CC), the following executables associated with the full Oracle Call Interface (OCI) install are needed:

- `okinit.exe`
- `oklist.exe`
- `okdstry.exe`

The executables are required in order to acquire the Kerberos5 credentials and store them in the file based credential cache (CC). However, after credential cache creation, as long as the credentials remain valid, the above executables are then unneeded by the ODP.NET application at run-time.

ODP.NET, Managed Driver Dependency on MIT Kerberos

To use Kerberos5 database authentication in conjunction with ODP.NET, Managed Driver, download and install MIT Kerberos for Windows 4.0.1 on the same machine as ODP.NET, Managed Driver from the following location:

<http://web.mit.edu/kerberos/dist/>

 **See Also:**

Configuring Kerberos Authentication in *Oracle Database Security Guide* for more information about Kerberos and configuration with Oracle database.

Configuring Kerberos Authentication with ODP.NET

Please reference the following "key" when viewing the below Kerberos configuration examples:

- `oracleclient` = Kerberos/Windows Domain user ID used by the Oracle database client program to represent the Oracle Client user on the domain
- `oracleserver` = Kerberos/Windows Domain user ID used by the Oracle database server
- `DOMAIN.COMPANY.COM` = Kerberos/Windows domain
- `dbhost.company.com` = Oracle database server machine hostname

- `kerberos_service_name` = Kerberos service name
- `dc.company.com` = hostname for Kerberos Key Distribution Center (KDC) and Windows Domain Controller

Configuring Kerberos Authentication Topics:

- Step 1. Update Windows services file to include a "kerberos5" entry
- Step 2. Create client and server Kerberos users (Windows domain users for MSLSA)
- Step 3. Associate the DB server's Kerberos principal name with the DB server's Kerberos Service (SPN mapping) and generate the server keytab file
- Step 4. Confirm the mapping of server user to service principal
- Step 5. Setup server `sqlnet.ora` to point to the keytab file generated in step 2
- Step 6. Create a kerberos configuration file that points to the Kerberos KDC (Windows Domain Controller for MSLSA)
- Step 7. Configure the Oracle database client and server `sqlnet.ora` or `.NET` config to point to the above Kerberos configuration file
- Step 8. Point the client `sqlnet.ora` or `.NET` config to a credential cache file or to MSLSA
- Step 9. Set the client and server authentication services in the `sqlnet.ora` or `.NET` config to Kerberos5
- Step 10. Setup an externally authenticated database user that matches the Kerberos client user setup in step 1 (note the case)
- Step 11. Login to the client machine via the Windows Domain client user (for MSLSA) or perform an `okinit` to authenticate the client Kerberos user (for file based CC):

Step 1. Update Windows services file to include a "kerberos5" entry

Change the Kerberos entry in the Windows service file (`C:\windows\system32\drivers\etc\services`) from:

```
kerberos 88/tcp          krb5 kerberos-sec      #Kerberos
```

to:

```
kerberos 88/tcp kerberos5 krb5 kerberos-sec      #Kerberos
```

Step 2. Create client and server Kerberos users (Windows domain users for MSLSA)

As noted in the above "key", we will use `oracleclient` and `oracleserver` as our client and server Kerberos user IDs, respectively.

ODP.NET supports MSLSA using Windows domain users which have the following attributes:

- "Kerberos DES" unchecked
- "Kerberos AES 128 bit" checked
- "Kerberos AES 256 bit" checked
- "Kerberos preauthentication not required" checked

Step 3. Associate the DB server's Kerberos principal name with the DB server's Kerberos Service (SPN mapping) and generate the server keytab file

Run the following commands on the Kerberos KDC (Windows Domain Controller for MSLSA) as an administrator:

```
> ktpass -princ kerberos_service_name/dbhost.company.com@DOMAIN.COMPANY.COM /crypto
all /mapuser oracleserver@DOMAIN.COMPANY.COM /pass <oracleserver password> /out
v5srvtab

> setspn -A kerberos_service_name/dbhost.company.com@DOMAIN.COMPANY.COM oracleserver
```

Step 4. Confirm the mapping of server user to service principal

Also on the Kerberos KDC, run the following command, noting the output:

```
> setspn -L oracleserver

Registered ServicePrincipalNames for
CN=oracleserver,CN=Users,DC=domain,DC=company,DC=com:
    kerberos_service_name/dbhost.company.com
kerberos_service_name/dbhost.company.com@DOMAIN.COMPANY.COM
```

Step 5. Setup server sqlnet.ora to point to the keytab file generated in step 2

Add the following line to the server sqlnet.ora:

```
sqlnet.kerberos5_keytab = c:\krb\v5srvtab
```

Step 6. Create a kerberos configuration file that points to the Kerberos KDC (Windows Domain Controller for MSLSA)

An example kerberos configuration file (krb.conf):

```
[libdefaults]
default_realm = DOMAIN.COMPANY.COM

[realms]
DOMAIN.COMPANY.COM = {
    kdc = dc.company.com
}

[domain_realm]
.domain.company.com = DOMAIN.COMPANY.COM
domain.company.com = DOMAIN.COMPANY.COM
.DOMAIN.COMPANY.COM = DOMAIN.COMPANY.COM
DOMAIN.COMPANY.COM = DOMAIN.COMPANY.COM
```

Step 7. Configure the Oracle database client and server sqlnet.ora or .NET config to point to the above Kerberos configuration file

Edit the client or server sqlnet.ora to include:

```
sqlnet.kerberos5_conf = C:\krb\krb.conf
```

Or edit the client application config to include (in the [settings](#) section):

```
<setting name="sqlnet.kerberos5_conf" value="C:\krb\krb.conf" />
```

Step 8. Point the client sqlnet.ora or .NET config to a credential cache file or to MSLSA

Example pointing to Credential Cache file:

```
sqlnet.kerberos5_cc_name = c:\krb\krb.cc
```

Example pointing to MSLSA:

```
sqlnet.kerberos5_cc_name = MSLSA:
```

Step 9. Set the client and server authentication services in the sqlnet.ora or .NET config to Kerberos5

```
sqlnet.authentication_services=(Kerberos5)
```

Step 10. Setup an externally authenticated database user that matches the Kerberos client user setup in step 1 (note the case)

```
create user "ORACLECLIENT@DOMAIN.COMPANY.COM" identified externally;  
grant connect, create session to "ORACLECLIENT@DOMAIN.COMPANY.COM";
```

Step 11. Login to the client machine via the Windows Domain client user (for MSLSA) or perform an okinit to authenticate the client Kerberos user (for file based CC):

```
okinit oracleclient
```

Step 12. Run the ODP.NET application

Note:

- After configuring the client and server, the last 2 steps are the only steps required on an ongoing basis to run the ODP.NET application.
- A Microsoft Visual C Run-Time Library (MSVCRT.DLL) bug can cause ODP.NET, Managed Driver's setting of the Kerberos5 configuration to be ignored by the Microsoft run-time. In such a case, you will encounter the error message:

```
OracleInternal.Network.NetworkException (0x80004005): NA Kerberos5:  
Authentication handshake failure at stage: krb5_sname_to_principal:  
default realm not found. Please set SQLNET.Kerberos5_conf.
```

To workaround this error, manually set KRB5_CONFIG in the ODP.NET application's run-time environment to point to the Kerberos5 configuration file pointed to by SQLNET.Kerberos5_conf. For example,

```
set KRB5_CONFIG=c:\oracle\network\admin\krb5.ini
```

 **See Also:**

Configuring Kerberos Authentication in *Oracle Database Security Guide* for more information about Kerberos and configuration with Oracle database.

Using Windows Native Authentication (NTS)

With the Windows native authentication adapter, Oracle users can authenticate to the database using just their Windows user login credentials. It provides a way to enable single sign-on and to simplify user and role credential management. Windows native authentication is also known as Windows Native authentication (NTS).

 **Note:**

- ODP.NET Core supports Windows Native Authentication on Windows only
- Due to a limitation in the Microsoft .NET APIs, ODP.NET, Managed Driver only supports Windows Native authentication (NTS) via Microsoft NT LAN Manager (NTLM) instead of Kerberos-based credentials. Normally, this limitation would be invisible to the ODP.NET, Managed Driver application, since the Windows domain and the Oracle database server will transparently support both NTLM and Kerberos domain credentials by default.

Configuring Windows Native Authentication (NTS) for the ODP.NET Client

Steps in configuring the NTS for the ODP.NET Client:

- [Step 1. Ensure OSAUTH_PREFIX_DOMAIN is set correctly](#)
- [Step 2. Setup the externally identified database user](#)
- [Step 3. Setup the client configuration to utilize NTS as the authentication methodology](#)

Step 1. Ensure OSAUTH_PREFIX_DOMAIN is set correctly

Make sure OSAUTH_PREFIX_DOMAIN is set appropriately. If you desire the externally identified user ID to include the domain, set it to true, otherwise false. The parameter is a registry setting that can be found at HKLM/software/oracle/HOME<ORACLE_SID>. For example, if your ORACLE_SID is r1, it is located at HKLM/software/oracle/HOMEr1.

Step 2. Setup the externally identified database user

Assuming a Step 0 setting of true, use the following commands to setup the externally identified database user associated with the desired Windows domain user:

```
create user "MYDOMAIN\MYUSER" identified externally;  
grant connect, create session to "MYDOMAIN\MYUSER";
```

Step 3. Setup the client configuration to utilize NTS as the authentication methodology

Edit the client `sqlnet.ora` or app config to add NTS to the `Sqlnet.authentication_services`. For example.

```
sqlnet.authentication_services = (NTS)
```

Note:

After configuring the client and server, the last 2 steps are the only steps required on an ongoing basis to run the ODP.NET application.

See Also:

Authenticating Database Users with Windows in *Oracle Database Platform Guide for Microsoft Windows* for Windows for more information about Windows native authentication.

Network Data Encryption and Integrity

ODP.NET enables data encryption and integrity over a network for both intranet and cloud deployments. This ensures that data is disguised to all, except authorized users, and guarantees the original message contents are not altered. In earlier releases, these features were known as Oracle Advanced Security Option (ASO) encryption. Starting with Oracle Database 12c, Oracle ASO is not required to use network data encryption and data integrity.

Using Data Encryption

Managed and unmanaged ODP.NET support the following encryption standards and algorithms:

- Advanced Encryption Standard (AES)
 - AES 128-bit
 - AES 192-bit
 - AES 256-bit
- Triple-DES (3DES)
 - 112-bit
 - 168-bit

ODP.NET, Managed Driver uses the following settings to configure network encryption:

- `SQLNET.ENCRYPTION_CLIENT`
- `SQLNET.ENCRYPTION_TYPES_CLIENT`

**See Also:**

[settings section](#) for definition and information on usage.

Using Data Integrity

Managed and unmanaged ODP.NET support the following data integrity algorithms:

- SHA-1
- SHA-2
 - SHA-256
 - SHA-384
 - SHA-512

**See Also:**

- For more information on network encryption and integrity or configuring them for ODP.NET, Unmanaged Driver, refer to the *Oracle Database Security Guide*.
- To configure network encryption or data integrity in ODP.NET, Managed Driver, refer to the `SQLNET.CRYPTO_CHECKSUM_CLIENT` and `SQLNET.CRYPTO_CHECKSUM_TYPES_CLIENT` settings in "Oracle Data Provider for .NET, Managed Driver Configuration." On the database server machine, you will likely have to configure the `SQLNET.CRYPTO_CHECKSUM_SERVER` and `SQLNET.CRYPTO_CHECKSUM_TYPES_SERVER` parameters in the `sqlnet.ora` file.

Schema Discovery

ADO.NET exposes five different types of metadata collections through the `OracleConnection.GetSchema` API. This permits application developers to customize metadata retrieval on an individual-application basis, for any Oracle data source. Thus, developers can build a generic set of code to manage metadata from multiple data sources.

The following types of metadata are exposed:

- `MetaDataCollections`

A list of metadata collections that is available from the data source, such as tables, columns, indexes, and stored procedures.

- `Restrictions`

The restrictions that apply to each metadata collection, restricting the scope of the requested schema information.

- `DataSourceInformation`

Information about the instance of the database that is currently being used, such as product name and version.

- `DataTypes`

A set of information about each data type that the database supports.

- `ReservedWords`

Reserved words for the Oracle query language.



See Also:

[Oracle Schema Collections](#)

User Customization of Metadata

ODP.NET provides a comprehensive set of database schema information. Developers can extend or customize the metadata that is returned by the `GetSchema` method on an individual application basis.

To do this, developers must create a customized metadata file and provide the file name to the application as follows:

1. Create a customized metadata file and put it in the `CONFIG` subdirectory where the .NET framework is installed. This is the directory that contains `machine.config` and the security configuration settings.

This file must contain the entire set of schema configuration information, not just the changes. Developers provide changes that modify the behavior of the schema retrieval to user-specific requirements. For instance, a developer can filter out internal database tables and just retrieve user-specific tables

2. Add an entry in the `app.config` file of the application, similar to the following, to provide the name of the metadata file, in name-value pair format.

```
<oracle.dataaccess.client>
  <settings>
    <add name="MetaDataXml" value="CustomMetaData.xml" />
  </settings>
</oracle.dataaccess.client>
```

When the `GetSchema` method is called, ODP.NET checks the `app.config` file for the name of the customized metadata XML file. First, the `GetSchema` method searches for an entry in the file with a element named after the provider, in this example, `oracle.dataaccess.client`. In this XML element, the value that corresponds to the name `MetaDataXml` is the name of the customized XML file, in this example, `CustomMetaData.xml`.

If the metadata file is not in the correct directory, then the application loads the default metadata XML file, which is part of ODP.NET.



See Also:

["GetSchema"](#)

Connection Pooling

ODP.NET connection pooling is enabled and disabled using the `Pooling` connection string attribute. By default, connection pooling is enabled. The following are `ConnectionString` attributes that control the behavior of the connection pooling service:

- `Connection Lifetime`
- `Connection Timeout`
- `Decr Pool Size`
- `HA Events`
- `Incr Pool Size`
- `Load Balancing`
- `Max Pool Size`
- `Min Pool Size`
- `Pooling`
- `Validate Connection`

Connection Pooling Example

The following example opens a connection using `ConnectionString` attributes related to connection pooling.

```
// C#

using System;
using Oracle.DataAccess.Client;

class ConnectionPoolingSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Open a connection using ConnectionString attributes
        //related to connection pooling.
        con.ConnectionString =
            "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min Pool Size=10;Connection Lifetime=100000;Connection Timeout=60;" +
            "Incr Pool Size=5; Decr Pool Size=2";
        con.Open();
        Console.WriteLine("Connection pool successfully created");

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Connection is placed back into the pool.");
    }
}
```

Using Connection Pooling

When connection pooling is enabled (the default), the `Open` and `Close` methods of the `OracleConnection` object implicitly use the connection pooling service, which is responsible for pooling and returning connections to the application.

The connection pooling service creates connection pools by using the `ConnectionString` property as a signature, to uniquely identify a pool.

In managed and Core versions of ODP.NET, connection strings themselves must be an exact match in their entirety. If keywords are supplied in a different order or a space is added to the connection string, a new pool is created. If a pool already exists with the requested signature, a connection is returned to the application from that pool.

In unmanaged ODP.NET, a new pool is created only when connection string attribute values change. Extra spaces or changing keyword order do not create a new pool.

When a connection pool is created, the connection pooling service initially creates the number of connections defined by the `Min Pool Size` attribute of the `ConnectionString` property. This number of connections is always maintained by the connection pooling service for the connection pool, except when Fast Connection Failover removes invalid connections or `Connection Lifetime` is exceeded. In these two cases, the connection number could drop below the `Min Pool Size`. ODP.NET would then attempt to restore the minimum pool size level upon the next connection request.

At any given time, these connections are in use by the application or are available in the pool.

The `Incr Pool Size` attribute of the `ConnectionString` property defines the number of new connections to be created by the connection pooling service when more connections are needed in the connection pool.

When the application closes a connection, the connection pooling service determines whether or not the connection lifetime has exceeded the value of the `Connection Lifetime` attribute. If so, the connection pooling service destroys the connection; otherwise, the connection goes back to the connection pool. The connection pooling service enforces the `Connection Lifetime` only when `Close()` or `Dispose()` is invoked.

The `Max Pool Size` attribute of the `ConnectionString` property sets the maximum number of connections for a connection pool. If a new connection is requested, but no connections are available and the limit for `Max Pool Size` has been reached, then the connection pooling service waits for the time defined by the `Connection Timeout` attribute. If the `Connection Timeout` time has been reached, and there are still no connections available in the pool, the connection pooling service raises an exception indicating that the connection pool request has timed-out. Upon a connection timeout, ODP.NET distinguishes whether the timeout occurred due to the database server failing to deliver a connection in the allotted time or no connection being available in the pool due to the maximum pool size having been reached. The exception text returned will either be "Connection request timed out" in the case of the former or "Pooled connection request timed out" in the case of the latter.

The `Validate Connection` attribute validates connections coming out of the pool. This attribute should be used only when absolutely necessary, because it causes a round-trip to the database to validate each connection immediately before it is provided to the application. If invalid connections are uncommon, developers can create their own

event handler to retrieve and validate a new connection, rather than using the `Validate Connection` attribute. This generally provides better performance.

The connection pooling service closes connections when they are not used; connections are closed every 3 minutes. The `Decr Pool Size` attribute of the `ConnectionString` property provides connection pooling service for the maximum number of connections that can be closed every 3 minutes.

Beginning with Oracle Data Provider for .NET release 11.1.0.6.20, enabling connection pooling by setting `"pooling=true"` in the connection string (which is the case by default) will also pool operating system authenticated connections.

Connection Pool Management

ODP.NET connection pool management provides explicit connection pool control to ODP.NET applications. Applications can explicitly clear connections in a connection pool.

Using connection pool management, applications can do the following:

Note:

These APIs are not supported in a .NET stored procedure.

- Clear connections from connection pools using the `ClearPool` method.
- Clear connections in all the connection pools in an application domain, using the `ClearAllPools` method.

See Also:

- `"ClearPool"`
- `"ClearAllPools"`

Connection Performance Counters

Installing Oracle Data Provider for .NET creates a set of performance counters on the target system. All ODP.NET provider types (Core, managed, and unmanaged) publish these performance counters for each of their client applications. These performance counters can be viewed using Windows Performance Monitor (Perfmon) or the `PerformanceCounter` class in the `System.Diagnostics` namespace.

Note:

ODP.NET performance counters are available on Windows platforms only.

As ODP.NET performance counters are not enabled nor registered after installation, administrators must register the counters, then enable the specific counters of interest before being able to monitor them.

Registering Performance Counters

After installation, ODP.NET performance counters must be registered so that tools, such as `Perfmon`, can consume them. Registration requires running a PowerShell script for the respective provider.

ODP.NET installs six scripts for counters that must be run from PowerShell to take effect

- `register_odpc_perfmon_counters.ps1` – Registers ODP.NET Core counters
- `register_odpm_perfmon_counters.ps1` – Registers managed ODP.NET counters
- `register_odpu_perfmon_counters.ps1` – Registers unmanaged ODP.NET counters
- `unregister_odpc_perfmon_counters.ps1` – Unregisters ODP.NET Core counters
- `unregister_odpm_perfmon_counters.ps1` – Unregisters managed ODP.NET counters
- `unregister_odpu_perfmon_counters.ps1` – Unregisters unmanaged ODP.NET counters

These scripts are located in the `ORACLE_HOME\odp.net\PerfCounters` directory for Oracle Universal Installer and NuGet deployments, in the `<INSTALLATION_DIRECTORY>\odp.net\PerfCounters` directory for xcopy deployments, and `<VISUAL_STUDIO_SOLUTION_DIRECTORY>\packages\Oracle.ManagedDataAccess.<VERSION>\PerfCounters` directory for MSI deployments.

Windows Administrator privileges are required when running these PowerShell scripts.

To unregister, run the unregister PowerShell script that matches the ODP.NET provider type you wish to unregister.

Previously, the `OraProvCfg.exe` utility was included with ODP.NET for registering and unregistering counters. These PowerShell scripts replace the utility. If you registered ODP.NET counters with this utility, then unregister with the same `OraProvCfg.exe` version.

Enabling Performance Counters

ODP.NET enables monitoring many different connection counters, including pooled and non-pooled connections. These counters can be monitored individually or together. Developers can set which counters to monitor prior to application startup using the `PerformanceCounters` setting in the `<settings>` section of the .NET config file, which is available in managed and unmanaged ODP.NET, or Windows Registry, which is available in unmanaged ODP.NET only. For ODP.NET Core, developers can set the `OracleConfiguration.PerformanceCounters` property.

[Table 3-3](#) lists the connection performance counters with their setting values.

Table 3-3 Performance Counters for Connection Pooling

Performance Counter	Valid Values	Description
None	0	Not enabled (Default)
HardConnectsPerSecond	1	Number of sessions being established with the Oracle Database every second.
HardDisconnectsPerSecond	2	Number of sessions being severed from the Oracle Database every second.
SoftConnectsPerSecond	4	Number of active connections originating from connection pools every second.
SoftDisconnectsPerSecond	8	Number of active connections going back to the connection pool every second.
NumberOfActiveConnectionPools	16	Total number of active connection pools.
NumberOfInactiveConnectionPools	32	Number of inactive connection pools.
NumberOfActiveConnections	64	Total number of connections in use.
NumberOfFreeConnections	128	Total number of connections available for use in all the connection pools.
NumberOfPooledConnections	256	Total number of pooled active and free connections.
NumberOfNonPooledConnections	512	Number of non-pooled active connections.
NumberOfReclaimedConnections	1024	Number of connections which were garbage-collected implicitly.
NumberOfStasisConnections	2048	No operation. This counter is no longer supported.

These settings are bitwise ORed in order to monitor more than one counter. For example, to collect counters for `SoftConnectsPerSecond (4)`, `SoftDisconnectsPerSecond (8)`, and `NumberOfActiveConnectionPools (16)`, set `PerformanceCounters` to 28 (i.e. $4 + 8 + 12$).

Setting Performance Counters in .NET Configuration Files

Performance counters can be set using an .NET configuration file, such as `web.config` or `app.config`, in managed and unmanaged ODP.NET only. Since .NET configuration entries take precedence over Windows Registry settings, they can be used for a specific application.

As earlier described, populating the `PerformanceCounters` setting in the `<settings>` section enables individual performance counters to be monitored. Windows Perfmon

uses very long and not easily human readable application instance names. To make identifying each application easier administrators can assign an identifier name in the <connectionPools> section of the .NET configuration file. This section supports the following settings:

- `connectionString`: This setting identifies the connections or pool to monitor using the connection string as the unique identifier. The connection string entered here must match the target connection string to be monitored, but without the password attribute.
- `poolName` (optional): Connection strings can be very long and hard to read with many that look similar. `poolName` allows using an arbitrary string to easily identify which pool is being monitored.

The following examples show how to use these settings.

ODP.NET, Managed Driver

```
<oracle.manageddataaccess.client>
  <version number="*">
    <connectionPools>
      .
      .
      <connectionPool connectionString="[connection string without password]"
poolName="[Pool Name]" > </connectionPool>
      .
      .
    </connectionPools>
  </version>
</oracle.manageddataaccess.client>
```

ODP.NET, Unmanaged Driver can use the same pool name setting and format as listed above by replacing the <oracle.manageddataaccess.client> tags with <oracle.unmanageddataaccess.client> tags. Alternatively, the legacy <oracle.dataaccess.client> format is available for unmanaged ODP.NET.

ODP.NET, Unmanaged Driver

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      .
      .
      <add name="[connection string without password]" value="connectionPool
name='[Pool Name]'" />
      .
      .
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

Setting Performance Counters in Windows Registry

Publication of individual unmanaged ODP.NET performance counters is enabled or disabled using the Windows Registry value `PerformanceCounters` of type `REG_SZ`. This registry value is under:

```
HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version
```

where *Assembly_Version* is the full assembly version number of `Oracle.DataAccess.dll`.

Similarly to the .NET config file, multiple performance counters can be obtained by adding the valid values. For example, if `PerformanceCounters` is set to 3, then both `HardConnectsPerSecond` and `HardDisconnectsPerSecond` are enabled.

Publishing Performance Counters

Commonly, ODP.NET performance counters are monitored using Perfmon. The counters are published under the following Category Names:

- ODP.NET, Core Driver
- ODP.NET, Managed Driver
- ODP.NET, Unmanaged Driver

Administrators can choose the individual ODP.NET counters to monitor after selecting one or more of these categories. PerfMon shows all ODP.NET counters, but only the explicitly enabled counters generate statistics.

After choosing the counters to monitor, administrators then select the running instance(s) to monitor. ODP.NET instances must be actively running for them to appear in PerfMon. Otherwise, no instances will appear available to monitor. After instance selection occurs, they are added to PerfMon as counters to monitor.

Performance counters can monitor at the application domain, pool, or database instance level. Database instance level monitoring only applies if load balancing or Fast Connection Failover features are enabled.

The instance name format is as follows:

`<Application Domain Name> [<Process Id>, <Application Domain Id>]
[<Connection String/Pool Name>][<Instance Name>]`. The entry is limited to 127 characters. There is a restriction length on every field in the instance name. The following table shows the maximum number of characters allocated for each field:

Table 3-4 Field Names of Performance Counters and Maximum Number of Characters

Field Name	Maximum Number of Characters
Application Domain	40
Pool Name/Connection String	70
Database Instance Name	16

When the length of a field value exceeds the length limit, the string is truncated and appended with ". . ." to fit within the length limit and indicate the continuation. For example, for a given application called `Program.exe` with a connection string `user id=hr;Password=<password>;data source=inst1;max pool size=125;min pool size=50`, one may see the following similar to the following for a process that has two application domains:

- `Program.exe [123, 1]`
- `Program.exe [123, 1][user id=hr;data source=inst1;max pool siz...]`

- `Program.exe [123, 1][user id=hr;data source=inst1;max pool siz...]
[instA]`
- `Domain 2[123, 2]`
- `Domain 2[123, 2][user id=hr;data source=inst1;max pool siz...]`
- `Domain 2[123, 2][user id=hr;data source=inst1;max pool siz...]
[instB]`
- `Domain 2[123, 2][user id=hr;data source=inst1;max pool siz...]
[instC]`

Since connection pool attributes can be similar in their first 70 characters, applications can set a Pool Name to uniquely identify each one in the monitoring tool. For example, when using Pool Name, the process will show up as follows:

```
Domain 2[123, 2][Pool Name][instC]
```

Database Resident Connection Pooling

Client side connection pooling can be very efficient for middle tier machines. However, it can consume a great deal of database server resources if there are numerous middle tier servers with idle connections. While the intent is to keep the number of idle connections to a minimum, it becomes difficult as the number of middle tier servers increase, each possibly having idle connections that cannot be shared across applications.

Database Resident Connection Pooling (DRCP) is intended to optimize resource usage by pooling connections at the database server level, which can then be shared across many applications. The benefit is better scalability and lower resource usage at the database server level.

Managed and unmanaged ODP.NET have been enhanced to support DRCP, which allows it to dispense and release DRCP connections to better utilize database server resources.

About DRCP

DRCP pools server processes, each of which is the equivalent to a dedicated server process and database session combined. These are called pooled servers. Pooled servers can be shared by multiple applications running on the same or multiple hosts.

When DRCP is configured for Oracle Database Real Application Clusters (Oracle RAC), the pool configuration is applied to each database instance. Starting or stopping the pool on one instance starts or stops the pool on all instances.

DRCP and ODP.NET

DRCP is a server side pool that complements ODP.NET client side pooling. These two pools can be used together.

In a typical dedicated server mode, client side connection pooling saves both on server round trips and socket/session creation. In a connection open/close sequence, a server round trip is involved only upon the first `Open()`. For subsequent open/close sequences on the same connection, no client to server interaction is required because the connection is pooled locally in the client address space.

With DRCP enabled, when the client creates a connection, the connection is assigned a pooled server when needed. When the connection is closed, the database server releases the DRCP server session back to the server side pool, effectively making the DRCP server session available for reuse. This server session can be reused by the same pool or a different pool on the same or different middle tier hosts.

Configuring DRCP and ODP.NET

The following section describe how DRCP can be configured on the client side and the server side.

- **Configuring DRCP on the Client Side**

ODP.NET developers can enable DRCP on the client side by using (SERVER=POOLED) in the connect descriptor.

Sample Descriptor:

```
(DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=myhost)(PORT=1521))
(CONNECT_DATA=(SERVICE_NAME=sales.example.com)(SERVER=POOLED)))
```

- **Configuring DRCP on the Server Side**

Oracle database includes a default connection pool called SYS_DEFAULT_CONNECTION_POOL. By default, this pool is created, but not started. To enable database resident connection pooling, you must explicitly start the connection pool.

You must be a database administrator (DBA) and must log on as SYSDBA to start and end a pool.

```
SQL> EXECUTE DBMS_CONNECTION_POOL.START_POOL();
```

If an application will share the DRCP connection pool across multiple middle tier servers, then the application has the option of setting the OracleConnection.DRCPConnectionClass property to a string value that uniquely identifies the server pool. If a DRCP connection is opened with this property populated, ODP.NET will direct DRCP to use a connection from that specific server pool. This capability allows the database server to scale easily across multiple middle tier servers.

Example 3-1 Using Database Resident Connection Pooling: Sample Code

```
// This application uses the following connect descriptor:
// oracle = (DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=<hostname>)
(PORT=1521))(CONNECT_DATA=(SERVICE_NAME=<service name>)(SERVER=POOLED)))

using System;
using Oracle.ManagedDataAccess.Client;

class DRCP
{
    static void Main()
    {
        string constr = "user id=hr;password=hr;data source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.DRCPConnectionClass = "GroupA";
    }
}
```

```
        con.Open();  
  
        con.Dispose();  
    }  
}
```

 **Note:**

To use DRCP with ODP.NET, Unmanaged Driver,:

- the .NET configuration setting, `CPVersion`, must be set to 2.0, or,
- have `CPVersion` not set at all, but have `(SERVER=POOLED)` in the TNS full descriptor that is used by the application.

Refer to [settings section](#) for more information.

 **See Also:**

Oracle Database Administrator's Guide for more information on configuring the default connection pool or end pool.

DRCP for Oracle Multitenant

DRCP cannot be created on the PDB. DRCP can only be created on the CDB and is shared among all the PDBs.

ODP.NET has one DRCP for the entire CDB and it can be configured and managed (start, stop, or reconfigure) only by connecting to root container.

To configure, set a session to point to the CDB and start the DRCP pool. For example:

```
alter session set container = cdb$root;  
execute dbms_connection_pool.configure_pool('SYS_DEFAULT_CONNECTION_POOL');  
execute dbms_connection_pool.start_pool();
```

DRCP for Oracle Real Application Clusters (RAC)

In an Oracle Real Application Clusters (RAC) environment, when a user creates a DRCP on an instance, that DRCP is replicated on all the instances of an Oracle RAC database and you can use any instance to manage the connection pool. Any changes you make to the pool configuration are applicable on all Oracle RAC instances.

DRCP Restrictions for ODP.NET

ODP.NET does not support the following features with DRCP:

- Open the proxy connection with end user authentication
- Open the `sysoper` connection
- Open using `OpenWithNewPassword`

- Set the `SQLNET.AUTHENTICATION_SERVICES` parameter value to `nts`, which enables Microsoft Windows native operating system authentication
- .NET Framework versions earlier than .NET Framework 4

Oracle Multitenant and Pluggable Databases

Oracle Database 12c introduced Oracle Multitenant, which enables an Oracle database to contain a portable collection of schemas, schema objects, and nonschema objects that appears to ODP.NET as a separate database. This self-contained collection is called a pluggable database (PDB).

Oracle Multitenant is a database architecture that enables customers to easily consolidate multiple pluggable databases without changing their application. This architecture delivers all the benefits of managing many databases as one, yet retains the isolation and resource prioritization of separate databases. In addition, Oracle Multitenant enables rapid provisioning and upgrades, and fully complements other Oracle database options.

Managed and unmanaged ODP.NET fully support Oracle Multitenant. In addition to being able to connect to individual pluggable databases, ODP.NET has been enhanced so that applications can request and obtain connections to specific PDBs from the same connection pool. The application can connect to any of the PDBs that are part of the same container database (CDB) and they must have the same common user. Moreover, if connections span multiple instances, such as with Oracle Real Application Clusters, then every instance must uniformly have the same exact PDBs and services for the common user to connect to. If these conditions are met, then ODP.NET will be able to connect to or implicitly switch connections from one PDB to another within the same pool in a highly performant manner.

To obtain a connection to a specific PDB (as a common user) set the `OracleConnections` properties, `PDBName` and `ServiceName`, and then call `OracleConnection.Open()` to obtain the a connection to the specified PDB and `Service name`. `PDBName` and `ServiceName` identify the PDB and service that the connection needs to be established to or switched to if using an existing idle connection from the connection pool. They are the pluggable database name and database service name, respectively. If only the `PDBName` property is set and the service name is not set by the user, then the provider will return a connection that uses the default (administrative) service.

Note:

For ODP.NET, Unmanaged Driver to be able to switch PDB connections within the same pool:

- the .NET configuration setting, `CPVersion`, must be set to 2.0, or,
- have `CPVersion` not set at all, but set `PDBName` and/or `ServiceName` to a non-null/non-empty value for the first connection request for a given connection string.

Refer to [settings section](#) for more information.

Example 3-2 Using Pluggable Database: Sample Code

```
// C#
using System;
using Oracle.ManagedDataAccess.Client;

class PDB
{
    static void Main()
    {
        string constr = "user id=hr;password=hr;data source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.PDBName = "pdb1";
        con.ServiceName = "dbl.company.com";
        con.Open();
        con.Close();
    }
}
```

ODP.NET keeps track of the `PDBName` and `ServiceName` to which the pooled connections are established to. Upon the application requesting for a connection with a specified `PDBName` and `ServiceName`, ODP.NET will return a connections that matches that request. However, if a matching connection is not found, ODP.NET will create a new connection and/or alter the session to switch to the requested `PDBName` and `ServiceName`. If the `PDBName` and/or `ServiceName` has been altered, then the `SwitchedConnection` property will return true if called with the `Open()` method invocation.

ODP.NET does not support usage of the `ALTER SESSION` statement to modify the Edition in Edition-Based Redefinition during the lifetime of a process. If using PDBs with Oracle Continuous Query Notification, you must connect to Oracle Database 12c Release 2 or higher. Hosting connections to multiple PDBs from the same pool requires ODP.NET for .NET Framework 4 or higher.

 **Note:**

When the connection is implicitly being switched from one PDB/Service to another, Service Relocation Connection Timeout(SRCT) will not take effect.

 **See Also:**

Managing Pluggable Databases in *Oracle Database Administrator's Guide*

Edition-Based Redefinition

Edition-based redefinition enables you to upgrade the database component of an application even while the application is being used. This minimizes or eliminates downtime for the application.

ODP.NET does not support usage of the `ALTER SESSION` statement to modify the Edition during the lifetime of a process.

Managed and unmanaged ODP.NET can connect to a database edition, and also have the ability to host connections to multiple Editions from within the same pool. An ODP.NET application can obtain a connection that is associated with a specified database edition by setting the `OracleConnection.DatabaseEditionName` property to the name of the database edition that the connection should be associated with. To use a single pool, the same user must be able to connect to both Editions. Applications will perform better and more efficiently when using Editions because ODP.NET can use the same connection pool and even share the same `OracleConnection` object by only changing Edition-specific properties.

Example 3-3 Using Edition-Based Redefinition: Sample Code

```
using System;
using Oracle.ManagedDataAccess.Client;

class Editions
{
    static void Main()
    {
        // Create a connection
        string constr = "user id=hr;password=hr;data source=oracle";
        OracleConnection con = new OracleConnection(constr);

        // Obtain a connection associated with EditionX
        con.DatabaseEditionName = "EditionX";
        con.Open();

        // Obtain a connection associated with EditionY
        con.Close();
        con.DatabaseEditionName = "EditionY";
        con.Open();
        con.Dispose();
    }
}
```

Changing the edition name through `DatabaseEditionName` while the connection is open is not allowed. It must be changed while the connection is in a closed state.

ODP.NET supports Editions when connecting to Oracle Database 11g Release 2 or later. Hosting multiple Editions in the same pool is available only in ODP.NET for .NET Framework 4 and above.

 **Note:**

To use this Edition-Based Redefinition feature with unmanaged ODP.NET connection pools:

- the .NET configuration setting, `CPVersion`, must be set to 2.0, or,
- have `CPVersion` not set at all, but set the `DatabaseEditionName` property to a non-null/non-empty value for the first connection request for a given connection string.

Refer to [settings section](#) for more information.

Applications can specify an Edition at deployment time using the registry or configuration file. An application can create the following registry entry of type `REG_SZ`:

```
HKLM\Software\Oracle\ODP.NET\version\Edition
```

Here `version` is the version of ODP.NET, and `Edition` is a valid Edition string value.

An application can alternatively use the `web.config` or `application.config` configuration file to specify the Edition at deployment time. The `machine.config` configuration file can be used to specify the Edition for all applications that use a particular version of the .NET framework.

The following example sets the Edition to `E1` in a .NET configuration file for ODP.NET, Unmanaged Driver:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="Edition" value="E1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

To summarize, the Edition name can be set by the `DatabaseEditionName` property, in the .NET configuration file, or in the Windows Registry. If `DatabaseEditionName` is set, then it takes precedence over the other two settings. If the .NET configuration file has an Edition set, then it takes precedence over the registry.

 **See Also:**

For more information on Editions refer to the *Oracle Database Administrator's Guide* and *Oracle Database Development Guide*

Operating System Authentication

Oracle Database can use Windows user login credentials to authenticate database users. To open a connection using Windows user login credentials, the `User Id` connection string attribute must be set to a slash (/). If the `Password` attribute is provided, it is ignored.

 **Note:**

Operating system authentication is not supported in a .NET stored procedure.

ODP.NET Core supports operating system authentication for Windows only.

All ODP.NET, Unmanaged Driver connections, including those using operating system authentication, can be pooled. ODP.NET, Managed Driver supports operating system authentication, except when the Windows domain is constrained to only support Kerberos-based domain authentication. Connections are pooled by default, and no configuration is required, as long as pooling is enabled.

The following example shows the use of operating system authentication:

```
/* Create an OS-authenticated user in the database
   Assume init.ora has OS_AUTHENT_PREFIX set to "" and <OS_USER>
   is any valid OS or DOMAIN user.

   create user <OS_USER> identified externally;
   grant connect, resource to <OS_USER>;

   Login through OS Authentication and execute the sample. See Oracle
   documentation for details on how to configure an OS-Authenticated user
*/

// C#

using System;
using Oracle.DataAccess.Client;

class OSAuthenticationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Establish connection using OS Authentication
        con.ConnectionString = "User Id=;/Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}
```

 **See Also:**

Oracle Database Administrator's Reference for Microsoft Windows for information on how to set up Oracle Database to authenticate database users using Windows user login credentials

Privileged Connections

Oracle allows database administrators to connect to Oracle Database with either SYSDBA or SYSOPER privileges. This is done through the DBA Privilege attribute of the ConnectionString property.

The following example connects scott/tiger as SYSDBA:

```
// C#

using System;
using Oracle.DataAccess.Client;

class PrivilegedConnectionSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Connect scott/tiger as SYSDBA
        con.ConnectionString = "User Id=scott;Password=tiger;" +
            "DBA Privilege=SYSDBA;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}
```



See Also:

DBA Privilege "[Table 6-47](#)" for further information on privileged connections in the database

Connection Pooling with OracleCredential

To better secure passwords, all ODP.NET applications can use `OracleCredential` to store user names and passwords outside of the connection string. `OracleCredential` mitigates the possibility of exposing user credentials in a page file swap or in a crash dump.

`OracleCredential` can be used with or without connection pooling.

When using the `OracleCredential` object, one should be aware of the connection pool algorithm that has been modified to take this new feature into consideration, when opening connection to the Oracle database. With earlier implementations of ODP.NET connection pool algorithm, the uniqueness of connection string attribute values were used to decide if a new connection pool needs to be created or an existing connection pool can be used to dispense connections. But with the introduction of `OracleCredential`, the reference of this object is also used to decide which connection pool that `OracleConnection` object is associated with.

The decision to create a new connection pool now depends on two factors, first is the uniqueness of connection string (as in earlier releases) and the second is the reference comparison of the `OracleCredential` provided to the `OracleConnection` object while opening a new connection. If either of these is different, a separate pool is used.

Here is an example to clarify the new algorithm:

```
using System;
using Oracle.DataAccess.Client;
//using Oracle.ManagedDataAccess.Client;

class Test
{
    static void Main()
    {
        string connStr1 = "user id=hr; password=hr; data source=oracle";
        string connStr2 = "data source=oracle";

        SecureString secPwd = new SecureString();
        secPwd.AppendChar('h');
        secPwd.AppendChar('r');

        OracleCredential oc1 = new OracleCredential ("hr", secPwd);
        OracleCredential oc2 = new OracleCredential ("hr", secPwd);
        OracleCredential oc3 = new OracleCredential ("hr", secPwd);

        // con1 and con2 are associated with the same connection pool since both are
        using the same
        // connection string and OracleCredential remains null in both cases.
        OracleConnection con1 = new OracleConnection (connStr1)
        OracleConnection con2 = new OracleConnection (connStr1, null)

        // con3 and con4 use the same connection string but different OracleCredential
        objects
        // (although same contents) so they are associated with different connection
        pools.
        OracleConnection con3 = new OracleConnection (connStr2, oc1)
        OracleConnection con4 = new OracleConnection (connStr2, oc2)

        // con5 and con6 use the same connection string and same OracleCredential object
        // so they are associated with the same connection pool.
        OracleConnection con5 = new OracleConnection (connStr2, oc3)
        OracleConnection con6 = new OracleConnection (connStr2, oc3)

        // Please note that con1, con3, con4, and con5 are all associated
        // with a different connection pool.
    }
}
```

 **Note:**

`OracleCredential` does not support double quotes around a `SecureString` password. Double quotes can be used within a password, however.

**See Also:**[OracleCredential Class](#)

Password Expiration

Oracle allows users passwords to expire. ODP.NET lets applications handle the password expiration by providing a new method, `OpenWithNewPassword`, that opens the connection with a new password.

The following example uses the `OracleConnection.OpenWithNewPassword` method to connect with a new password of `panther`:

```
/* Database Setup
connect / as sysdba;
drop user testexpire cascade;
-- create user "testexpire" with password "testexpire"
grant connect , resource to testexpire identified by testexpire;
alter user testexpire password expire;
*/

// C#

using System;
using Oracle.DataAccess.Client;

class PasswordExpirationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        try
        {
            con.ConnectionString =
                "User Id=testexpire;Password=testexpire;Data Source=oracle";
            con.Open();
            Console.WriteLine("Connected to Oracle" + con.ServerVersion);
        }
        catch (OracleException ex)
        {
            Console.WriteLine(ex.Message);

            //check the error number
            //ORA-28001 : the password has expired
            if (ex.Number == 28001)
            {
                Console.WriteLine("\nChanging password to panther");
                con.OpenWithNewPassword("panther");
                Console.WriteLine("Connected with new password.");
            }
        }
        finally
        {
            // Close and Dispose OracleConnection object
            con.Close();
        }
    }
}
```

```
        con.Dispose();  
        Console.WriteLine("Disconnected");  
    }  
}
```

 **Note:**

- The `OpenWithNewPassword` method should be used only when the user password has expired, not for changing the password.
- If connection pooling is enabled, then invoking the `OpenWithNewPassword` method also clears the connection pool. This closes all idle connections created with the old password.

 **See Also:**

["OpenWithNewPassword\(String\)"](#)

Proxy Authentication

With proper setup in the database, proxy authentication enables middle-tier applications to control the security by preserving database user identities and privileges, and auditing actions taken on behalf of these users. This is accomplished by creating and using a proxy database user that connects and authenticates against the database on behalf of a database user (that is, the *real* user) or database users.

Proxy authentication can then be used to provide better scalability with connection pooling. When connection pooling is used in conjunction with proxy authentication, the proxy authenticated connections can be shared among different real users. This is because only the connection and session established for the proxy is cached. An additional session is created for the real user when a proxy authenticated connection is requested, but it will be destroyed appropriately when the proxy authenticated connection is placed back into the pool. This design enables the application to scale well without sacrificing security.

ODP.NET applications can use proxy authentication by setting the "Proxy User Id" and "Proxy Password" attributes in the connection string. The real user is specified by the "User Id" attribute. Optionally, to enforce greater security, the real user's password can be provided through the "Password" connection string attribute. When using distributed transactions in conjunction with proxy authentication, the real user's password is no longer optional, and it must be supplied.

The following example illustrates the use of ODP.NET proxy authentication:

```
/* Log on as DBA (SYS or SYSTEM) that has CREATE USER privilege.  
   Create a proxy user and modified scott to allow proxy connection.  
  
   create user appserver identified by eagle;  
   grant connect, resource to appserver;  
   alter user scott grant connect through appserver;  
*/
```

```
// C#

using System;
using Oracle.DataAccess.Client;

class ProxyAuthenticationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        // Connecting using proxy authentication
        con.ConnectionString = "User Id=scott;Password=tiger;" +
            "Data Source=oracle;Proxy User Id=appserver;Proxy Password=eagle; ";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}
```

 **See Also:**

- *Oracle Database SQL Language Reference* for the description and syntax of the proxy clause for the ALTER USER statement
- *Oracle Database Security Guide* for information about how auditing works for SQL statements and privileges in a multitier environment

Dynamic Distributed Transaction Enlistment

For those applications that dynamically enlist in distributed transactions through the `EnlistDistributedTransaction` of the `OracleConnection` object, the "Enlist" connection string attribute must be set to a value of "true". If "Enlist=true", the connection enlists in a transaction when the `Open` method is called on the `OracleConnection` object, if it is within the context of a COM+ transaction or a `System.Transactions`. If not, the `OracleConnection` object does not enlist in a distributed transaction, but it can later enlist explicitly using the `EnlistDistributedTransaction` or the `EnlistTransaction` method. If "Enlist" is equal to "false" or "dynamic", the connection cannot enlist in the transaction. ODP.NET, Unmanaged Driver in ODAC 12c Release 3 first introduced this new behavior for "Enlist=dynamic".

 **See Also:**

- ["Connection String Attributes"](#)
- ["EnlistDistributedTransaction"](#)

Client Identifier and End-to-End Tracing

The client identifier is a predefined attribute from the Oracle application context namespace `USERENV`. It is similar to proxy authentication because it can enable tracking of user identities. However, client identifier does not require the creation of two sessions (one for the proxy user and another for the end user) as proxy authentication does. In addition, the client identifier does not have to be a database user. It can be set to any string. But most importantly, by using client identifier, ODP.NET developers can use application context and Oracle Label Security, and configure Oracle Virtual Private Database (VPD) more easily. To set the client identifier, ODP.NET applications can set the `ClientId` property on the `OracleConnection` object after opening a connection. If connection pooling is enabled in unmanaged ODP.NET, then the `ClientId` is reset to null whenever a connection is placed back into the pool. In managed ODP.NET, the `ClientId` is reset to null (assuming no new value is provided) upon the first database round trip after a connection is placed back into the pool.

The client identifier can also be used for end-to-end application tracing. End-to-end tracing simplifies the process of diagnosing performance problems in multitier environments. In multitier environments, a request from an end client is routed to different database sessions by the middle tier making it difficult to track a client across different database sessions. End-to-end tracing uses the client identifier to uniquely trace a specific end-client through all tiers to the database server.

ODP.NET exposes the `ActionName`, `ClientId`, `ClientInfo`, and `ModuleName` write-only properties on the `OracleConnection` object. These properties correspond to the following end-to-end tracing attributes:

- `Action` - Specifies an action, such as an `INSERT` or `UPDATE` operation, in a module
- `ClientId` - Specifies an end user based on the logon ID, such as `HR.HR`
- `Client info` - Specifies user session information
- `Module` - Specifies a functional block, such as Accounts Receivable or General Ledger, of an application

See Also:

- ["OracleConnection Properties"](#)
- *Oracle Database SQL Tuning Guide* for an overview of End-to-End Application Tracing
- *Oracle Database Security Guide*

Transparent Application Failover (TAF) Callback Support

[Transparent Application Failover \(TAF\)](#) is a feature in Oracle Database that provides high availability.

**Note:**

ODP.NET, Managed Driver and ODP.NET Core do not support TAF nor TAF callbacks.

TAF enables an application connection to automatically reconnect to another database instance if the connection gets severed. Active transactions roll back, but the new database connection, made by way of a different node, is identical to the original. This is true regardless of how the connection fails.

With TAF, a client notices no loss of connection as long as there is one instance left serving the application. The database administrator controls which applications run on which instances, and also creates a failover order for each application.

When a session fails over to another database, the NLS settings that were initially set on the original session are not carried over to the new session. Therefore, it is the responsibility of the application to set these NLS settings on the new session.

TAF Notification

Given the delays that failovers can cause, applications may wish to be notified by a TAF callback. ODP.NET supports the TAF callback function through the `Failover` event of the `OracleConnection` object, which allows applications to be notified whenever a failover occurs. To receive TAF callbacks, an event handler function must be registered with the `Failover` event.

When Failover Occurs

When a failover occurs, the `Failover` event is raised and the registered event handler is invoked several times during the course of reestablishing the connection to another Oracle instance.

The first call to the event handler occurs when Oracle Database first detects an instance connection loss. This allows the application to act accordingly for the upcoming delay for the failover.

If the failover is successful, the `Failover` event is raised again when the connection is reestablished and usable. At this time, the application can resynchronize the `OracleGlobalization` session setting and inform the application user that a failover has occurred. No significant database operation should occur immediately after a `FailoverEvent.Begin` event. SQL and major database operations should wait until the `FailoverEvent.End` event. `FailoverEvent.Begin` is primarily used to reject failover or to trace it. `FailoverEvent.Begin` can also be used for non-database application operations, such as informing the end user a failover is in progress and to wait until it completes before proceeding. Transactions can be used in the `FailoverEvent.End` callback phase, such as to file fault tickets or audit. These transactions must be committed before the callback completes.

If failover is unsuccessful, the `Failover` event is raised to inform the application that a failover did not take place.

The application can determine whether or not the failover is successful by checking the `OracleFailoverEventArgs` object that is passed to the event handler.

Registering an Event Handler for Failover

The following example registers an event handler method called `OnFailover`:

```
// C#

using System;
using Oracle.DataAccess.Client;

class TAFCallbackSample
{
    public static FailoverReturnCode OnFailover(object sender,
                                                OracleFailoverEventArgs eventArgs)
    {
        switch (eventArgs.FailoverEvent)
        {
            case FailoverEvent.Begin :
                Console.WriteLine(
                    "\nFailover Begin - Failing Over ... Please standby \n");
                Console.WriteLine(
                    " Failover type was found to be " + eventArgs.FailoverType);
                break;

            case FailoverEvent.Abort :
                Console.WriteLine(" Failover aborted. Failover will not take place.\n");
                break;

            case FailoverEvent.End :
                Console.WriteLine(" Failover ended ...resuming services\n");
                break;

            case FailoverEvent.Reauth :
                Console.WriteLine(" Failed over user. Resuming services\n");
                break;

            case FailoverEvent.Error :
                Console.WriteLine(" Failover error gotten. Sleeping...\n");
                return FailoverReturnCode.Retry;

            default :
                Console.WriteLine("Bad Failover Event: %d.\n", eventArgs.FailoverEvent);
                break;
        }
        return FailoverReturnCode.Success;
    } /* OnFailover */

    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
        con.Open();
        con.Failover += new OracleFailoverEventHandler(OnFailover);
        Console.WriteLine("Event Handler is successfully registered");

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}
```


The `Failover` event invokes only one event handler. If multiple `Failover` event handlers are registered with the `Failover` event, only the event handler registered last is invoked.



Note:

Distributed transactions are not supported in an environment where failover is enabled.



See Also:

- *Oracle Database Net Services Administrator's Guide*
- ["OracleFailoverEventHandler Delegate"](#)
- ["OracleFailoverEventArgs Class"](#)

Real Application Clusters and Global Data Services

This section discusses optimizations for the following products:

- Oracle Real Application Clusters (Oracle RAC) is a cluster database with a shared cache architecture that overcomes the limitations of traditional shared-nothing and shared-disk approaches to provide highly scalable and available database solutions for business applications.
- Oracle Data Guard provides one or more standby databases to protect Oracle data from failures, disasters, human error, and data corruptions for high availability in mission critical applications.
- Oracle GoldenGate replicates data among heterogeneous data environments. It enables high availability solutions, real-time data integration, transactional change data capture, data replication, transformations, and verification between operational and analytical enterprise systems.
- Global Data Services (GDS), new in Oracle Database 12c, provides database workload management features across replicated databases, such as Data Guard and GoldenGate.

ODP.NET supports Oracle Real Application Clusters (Oracle RAC), Data Guard, and GoldenGate transparently, meaning you do not need to change ODP.NET code to use these Oracle components. To further take advantage of these technologies, ODP.NET offers connection pooling optimization features for achieving better application high availability and performance. You can do this through configuring ODP.NET to receive, respond, and send database status messages to .NET applications.

These optimization configurations include the use of features such as Fast Application Notification (FAN), Runtime Connection Load Balancing, and Fast Connection Failover (FCF).

These connection pooling optimizations can improve high availability and performance for Oracle Real Application Clusters and Global Data Services products:

- [Fast Application Notification](#)
- [Runtime Connection Load Balancing](#)
- [Fast Connection Failover \(FCF\)](#)

 **See Also:**

- *Oracle Real Application Clusters Administration and Deployment Guide.*
- *Oracle Data Guard Concepts and Administration.*
- *Oracle Database High Availability Overview.*

Fast Application Notification

Fast Application Notification (FAN) is a high availability and load balancing notification mechanism that Oracle RAC, Data Guard, and GoldenGate use to notify ODP.NET applications about cluster configuration and service-level information, including status changes such as UP or DOWN events and server load. FAN UP and DOWN events can apply to instances, services, and nodes. Based on information received, ODP.NET can adjust its connection pool accordingly to improve application availability and performance.

With FAN, Oracle RAC, Data Guard, and GoldenGate use one of two Oracle messaging infrastructures to send notifications to ODP.NET applications:

- Oracle Notification Service (ONS)
- Oracle Database Advanced Queueing (AQ).

[Table 3-5](#) describes when each messaging system is used and the ODP.NET-related client configuration.

Table 3-5 Configurations for ODP.NET Driver Types

ODP.NET Driver Type	Database Server Version	FAN Infrastructure	Configuration	Manual ONS Configuration Locations
managed	12.1 and later	ONS	Automatic or Manual	Either of these two files: <ul style="list-style-type: none"> • .NET configuration file • ONS configuration file
managed	11.2 and earlier	ONS	Manual	Either of these two files: <ul style="list-style-type: none"> • .NET configuration file • ONS configuration file
unmanaged	12.1 and later	ONS	Automatic or Manual	oraaccess.xml file
unmanaged	11.2 and earlier	AQ	Automatic	N/A

For automatic ONS configuration, developers can add more nodes and ports for ODP.NET to listen to, in addition to the nodes and ports that ODP.NET obtains from the database automatically.

ODP.NET applications do not require code changes to migrate from the AQ to ONS FAN infrastructure. However, some ODP.NET client configuration changes may be necessary when migrating to ONS, a newer database server version, or from ODP.NET, Unmanaged Driver to the managed driver, as documented above.

On the database server side, FAN must be set up and configured.

Using FAN Messages from the database, ODP.NET can do the following:

- With Runtime Connection Load Balancing, ODP.NET load balances connections among Oracle RAC nodes, services, and service members and GDS resources. This feature improves ODP.NET response time and ensures better resource allocation of server resources.
- With the Fast Connection Failover (FCF) feature, Oracle RAC, Data Guard, and GoldenGate can inform the ODP.NET connection pool if database nodes, services, service members, or the databases have gone down. These DOWN messages indicate which connections in the pool are invalid and must be removed.

See Also:

- [onsConfig section](#) to configure the .NET configuration file.
- [Client Side ONS Daemon Configuration](#) to configure the ONS configuration file.
- [Configuring a Port to Listen for Database Notifications](#) for more information on AQ configuration for FAN.
- [Runtime Connection Load Balancing](#)
- *Oracle Real Application Clusters Administration and Deployment Guide* for more information about FAN.
- *Oracle Call Interface Programmer's Guide* to configure `oraaccess.xml`.
- *Oracle Database Development Guide*

Runtime Connection Load Balancing

With Runtime Connection Load Balancing, Oracle Data Provider for .NET balances work requests across Oracle RAC instances based on the load balancing advisory and service goal. Because workloads can constantly change, load balancing occurs when the application requests a new connection. Thus, ODP.NET optimizes service levels by connecting users to the least loaded nodes in real-time.

In Oracle Database 12c, Runtime Connection Load Balancing has been extended to Oracle Data Guard and Oracle GoldenGate so that ODP.NET 12c connections can be load balanced with these two database services as part of Global Data Services. No ODP.NET applications require code changes to use Global Data Services if they are already using Runtime Connection Load Balancing.

When Runtime Connection Load Balancing is enabled:

- The ODP.NET connection pool dispenses connections based on the load balancing advisory and service goal.

- The ODP.NET connection pool also balances the number of connections to each service member providing the service, based on the load balancing advisory and service goal.

By default, ODP.NET is enabled to receive Runtime Connection Load Balancing FAN messages from the server. The feature has been enabled via the "Load Balancing=true" and "pooling=true" settings in the connection string, which are the default values. This feature can only be used if "pooling=true". In order to use Runtime Connection Load Balancing, specific Oracle server configurations must be set.

The following connection string example enables Runtime Connection Load Balancing:

```
"user id=scott;password=tiger;data source=erp;load balancing=true;"
```

See Also:

- [Table 3-2](#)
- ["Configuring a Port to Listen for Database Notifications"](#)
- *Oracle Database Net Services Administrator's Guide* to set up the Oracle Net configuration that Runtime Connection Load Balancing requires
- *Oracle Real Application Clusters Administration and Deployment Guide* for the required Oracle RAC configuration
- *Oracle Database Global Data Services Concepts and Administration Guide*

Fast Connection Failover (FCF)

When an Oracle RAC service, service member, node, or a Data Guard database fails, the severed ODP.NET connection objects may continue to exist in the application. If users attempt to use these invalid connections, they will encounter errors. FCF enables ODP.NET to free these severed connections proactively and quickly. Users then will be able to use the application after a server side failure without manual intervention from an administrator.

In Oracle Database 12c, FCF has been extended to Oracle Data Guard and Oracle GoldenGate for ODP.NET 12c connections through Global Data Services. No ODP.NET applications require code changes to use Global Data Services if they already use FCF.

ODP.NET applications can enable FCF through the High Availability Events, "HA Events", connection string attribute. When HA Events are enabled:

- ODP.NET connection pool proactively removes connections from the pool when a Global Data Service or Oracle RAC service, service member, node, or database goes down.
- ODP.NET proactively forces threads waiting for responses from the downed database to exit out from the existing call to avoid any hangs. When such a connection is then returned to the pool, any resource associated with that connection is freed.

- ODP.NET establishes connections to existing Oracle instances if the removal of severed connections brings the total number of connections below the "min pool size", upon the next connection request.

By default, ODP.NET is enabled to receive FCF FAN messages from the server. This feature have been enabled via the `HA Events=true` and `pooling=true` settings in the connection string, which are the default values.

The following connection string example enables HA Events:

```
"user id=scott;password=tiger;data source=erp;HA events=true;"
```

See Also:

- [Table 3-2](#)
- [Configuring a Port to Listen for Database Notifications](#)
- *Oracle Database Net Services Administrator's Guide* to set up the Oracle Net configuration that FCF requires
- *Oracle Real Application Clusters Administration and Deployment Guide* for the required Oracle RAC configuration
- *Oracle Database Global Data Services Concepts and Administration Guide*

Using FCF Planned Outage to Minimize Service Disruption

FCF not only provides high availability services for unplanned outages, such as node failures, but also for planned outages, such as server repairs, upgrades, and changes, to minimize service disruption to ODP.NET application users.

When a database service is set to be stopped or relocated, a FAN message is published with a planned reason code. A FCF-aware ODP.NET connection pool (`HA Events=true`) receives the notification and commences to close idle connections, no longer allowing new connections to that specific database service. Active connections to that specific database service remain until users complete their tasks and the connection is returned to the pool. Thus, no users must stop work mid-stream due to a planned outage.

Eventually, all users complete their tasks and no connections remain to that database service. The database administrator can then stop the service for the planned outage task. This feature allows the database service to be stopped as quickly as possible without end user disruption.

Oracle planned outage support works with Oracle Real Application Clusters (Oracle RAC), Oracle Data Guard, and some single instance scenarios.

Oracle RAC Planned Outage

A typical planned outage scenario for Oracle RAC follows below. Note that the database server commands apply to Oracle RAC 12c Release 2 or higher. Commands for earlier releases may be different.

1. There is a need to upgrade, patch, or repair a software or hardware issue on a database server. Stop the instance gracefully such that existing users experience no to few errors. You can wait until all users complete their work before doing so. Business requirements will dictate whether you wait for all users to log out or begin the planned outage after a set time. An administrator could issue the following command line operation using Oracle Server Control Utility (`srvctl`):

```
srvctl relocate service -database <unique database name> -service <service name>  
-drain_timeout 120 -stopoption IMMEDIATE -oldinst <existing instance>
```

This command relocates the database service from the existing instance to any instance it is configured to run on. Oracle Cluster Ready Services (CRS) will choose this instance, as the command line specifies no target. CRS will wait 120 seconds (`-drain_timeout 120`) for any active sessions to drain, after which any sessions remaining on the existing instance will be forcibly disconnected (`-stopoption IMMEDIATE`). If Application Continuity is used in conjunction with planned outage, an attempt is made to recover these killed sessions, masking the outage from end users.

The relocate operation starts the service in the new location prior to stopping the service in its existing location. Immediate relocation allows draining with no brownout. If the service cannot be started, it is not stopped at the original location to maintain availability.

2. Meanwhile in the connection pool, the FAN planned DOWN event clears idle sessions for the instance being shutdown from the ODP.NET connection pool immediately and marks that instance's active sessions to be released at the next check-in. These FAN actions drain the sessions from this instance without disrupting the users.

Existing connections on other instances remain usable, and new connections can be opened to these other instances.

3. Not all sessions will check their connections into the pool immediately. The timeout period specified by `-drain_timeout` after which the instance is forcibly shut down, evicting any remaining client connections. Administrators can check whether any active sessions to the instance remain by querying the `v$session` table.
4. Once the upgrade, patch, or repair is complete, restart the instance and the service on the original node. The FAN UP event will inform the ODP.NET pool that it can now use the original machine again.

See Also:

Oracle Database High Availability Best Practices

Oracle Data Guard Planned Outage

Oracle Data Guard performs switchovers from primary databases to standby databases in planned failover scenarios. During the switchover, administrators will want to limit end user disruptions. In Oracle Database 12c Release 2 and higher, these administrators can use the Data Guard command-line interface (DGMGRL) command to switch roles between primary and standby databases:

```
SWITCHOVER TO <database name> [WAIT <timeout in seconds> ];
```

The `WAIT` option specifies to wait for sessions to drain before proceeding with the switchover.

Similar to the Oracle RAC scenario, FAN informs the ODP.NET to remove idle connections from the pool. Connections subsequently checked in are destroyed until no active connections remain to that primary database, which will allow the switchover to begin.

When switchover to the standby completes, a FAN UP event informs ODP.NET that it can start creating connections to the standby instance.

During the Data Guard service relocation process, new incoming connection requests will not be accepted until the service has fully relocated. Incoming connection requests arriving during the interim, such as in the middle of an Oracle Data Guard switchover, will receive connectivity errors.

To prevent these errors, ODP.NET can pause connection attempts until the new database service is available. ODP.NET, Managed and Unmanaged Drivers block any connection attempts until the service is up or until the configured time limit expires from the time when the service DOWN event was received. This feature is useful for planned outages and service relocations. It works with Oracle RAC and Oracle Data Guard.

This time limit is the `ServiceRelocationConnectionTimeout` setting, which can be set in the `.NET` configuration file.



See Also:

[ServiceRelocationConnectionTimeout](#)

Pool Behavior in an Oracle RAC Database

When connection pools are created for a single-instance database, pool size attributes are applied to the single service. Similarly, when connection pools are created for an Oracle RAC database, the pool size attributes are applied to a service and not to service members. For example, if "Min Pool Size" is set to N , then ODP.NET does not create N connections for each service member. Instead, it creates, at minimum, N connections for the entire service, where N connections are distributed among the service members.

The following pool size connection string attributes are applied to a service.

- Min Pool Size
- Max Pool Size
- Incr Pool Size
- Decr Pool Size

ODP.NET connects to the same Oracle RAC node when required by a distributed transaction that has already begun on a particular node, by an Oracle runtime connection load balancing advisory, or by Oracle RAC load balancing gravitation in which connections will gravitate to an under utilized node. If the connection pool has no idle connections to this particular node, then ODP.NET will create a new

connection to this node. Node affinity is honored even when the connection pool runs out of idle connections to dispense.

Using Transaction Guard to Prevent Logical Corruption

Transaction Guard allows managed and unmanaged ODP.NET applications to use at-most-once execution in case of planned and unplanned outages and repeated submissions. Without Transaction Guard, applications that attempt to retry operations following outages can cause logical corruption by committing duplicate transactions.

After an outage, one of the traditional problems for recovering applications had been the non-durable commit message sent back to the client. If there is a break between the client and the server, the client sees an error message indicating that the communication failed, also known as a recoverable error. This error does not inform the application if the submission executed any commit operations, or if a procedural call ran to completion while executing all expected commits. The error also does not indicate session state changes or intermittent failures. The client is left wondering if the transaction committed and if it fully completed.

These recoverable errors may require end users or applications to attempt replay by issuing duplicate transaction submissions or other forms of logical corruption. The transaction cannot be validly resubmitted if the non-transactional state is incorrect or if it is committed. Continuing to process a committed but not completed call can result in the application using a database session that is in the wrong state.

ODP.NET and Transaction Guard

Transaction Guard allows ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver to eliminate duplicate transactions automatically and transparently, and in a manner that scales.

When a failure occurs, such as a node, network, or database failure, ODP.NET applications can deterministically conclude whether the transaction committed by querying its status, if the database service is up. Oracle retains the transaction status automatically, even after one of these failures.

In ODAC 12c Release 4, using Transaction Guard application development has been streamlined, reducing the application logic needed to determine the transaction outcome. Moreover, these benefits are available to both managed and unmanaged ODP.NET.

When a recoverable error is raised by a Transaction Guard enabled database service upon a database commit or upon a SQL or PL/SQL execution, which could have called a commit, then an ODP.NET `OracleException` is created with an `OracleLogicalTransaction` instance. `OracleLogicalTransaction` is always non-null. The database maintains the outcome of the logical transaction for the retention period specified by the administrator. ODP.NET automatically queries the database on behalf of the application when a recoverable error occurs so that the `OracleLogicalTransaction` object instance on the `OracleException` object can indicate whether the transaction has committed or not and whether the user call has completed or not.

If the status is committed, then the transaction has completed successfully. No other action is likely needed by the administrator.

If not committed, then ODP.NET applications can learn the current transaction state, whether it is recoverable, and whether it can be retried using `OracleLogicalTransaction`. If the error is recoverable, then the transaction is safe to re-submit. If the error is not recoverable, the application will need to determine the transaction outcome using an alternative mechanism.

**Note:**

Transaction Guard supports only local transactions. It does not support distributed transactions.

The Transaction Guard feature is enabled or disabled through the Oracle service-level configuration through the `COMMIT_OUTCOME` setting. By default, it is not enabled. This setting can be changed without bringing down the database. Only new connections created against the service will use the new setting.

Here's an example of setting the `COMMIT_OUTCOME` using `SRVCTL`:

```
srvctl modify service -d orcl -s GOLD -commit_outcome TRUE
```

**Note:**

Grant the `EXECUTE` privilege on the `DBMS_APP_CONT` package to the database users that retrieve the transaction status:

```
GRANT EXECUTE ON DBMS_APP_CONT TO <user name> ;
```

The following is an example ODP.NET Transaction Guard application scenario:

An ODP.NET application receives a Fast Application Notification (FAN) down event or error. FAN automatically aborts the dead session and the application receives an `OracleException`. A Transaction Guard application built to handle errors transparently would do the following:

1. `OracleException.OracleLogicalTransaction.LogicalTransactionId` property

The value returned by this property will be non-null if

- Transaction Guard is enabled,
- Transparent Application Failover (TAF) is not enabled on the connection, and
- ODP.NET was not able to determine the outcome of the transaction.

For a given `OracleException` object, if `OracleLogicalTransaction.Committed` and `OracleLogicalTransaction.UserCallCompleted` return all nulls, then the error is either a non-recoverable error, Transaction Guard is not enabled, or TAF is enabled on the connection. In any of these cases, the application should rollback then re-submit the transaction.

The `LogicalTransactionId` property will return null even if Transaction Guard is enabled and a recoverable error happens, if `OracleLogicalTransaction.Committed` is true or false.

2. `OracleException.OracleLogicalTransaction.Committed` property

This property returns true or false, depending on whether the transaction has been committed or not. If it returns null, then

- ODP.NET could not determine the outcome of the transaction,
- Error is not recoverable,
- Transaction Guard was not enabled, or
- TAF is enabled on the connection.

3. OracleException.OracleLogicalTransaction.UserCallCompleted property

This property returns true if the user call has completed, else it returns false. This property returns null if

- Transaction Guard was not enabled,
- Error is not recoverable,
- TAF is enabled on the connection, or
- ODP.NET is not able to determine if the user call has completed or not.

See the following table for the implications of what `Committed` and `UserCallCompleted` values mean.

Table 3-6 Implication of Committed and UserCallCompleted Values

Committed Value	UserCallCompleted Value	Outcome
True	True	The transaction was successful. The result can be returned to the application.
False	False	The transaction was not successful. The application can resubmit the transaction again.
True	False	The transaction committed, but there may be additional state, such as row counts or nested PL/SQL logic, that prevents the application from continuing as expected.

Example 3-4 Using Transaction Guard: Sample Code

```
using System;
using Oracle.DataAccess.Client;
//alternatively can use using Oracle.ManagedDataAccess.Client;

class TransactionGuardSample
{
    static void Main()
    {
        bool bReadyToCommit = false;

        string constr = "user id=hr;password=hr;data source=oracle";
        OracleConnection con = new OracleConnection(constr);
        OracleTransaction txn = null;
```

```
OracleCommand cmd = null;

try
{
    string sql = " update employees set salary=10000 where
employee_id=103";
    con.Open();
    txn = con.BeginTransaction();
    cmd = new OracleCommand(con, sql);
    cmd.ExecuteNonQuery();
    bReadyToCommit = true;
}
catch (Exception ex)
{
    // rollback here as the SQL execution is unsuccessful
    txn.Rollback();
    Console.WriteLine(ex.ToString());
}

try
{
    if (bReadyToCommit)
        txn.Commit();
}
catch (Exception ex)
{
    if (ex is OracleException)
    {
        // It's safe to re-submit the work if the error is
recoverable and the transaction has not been committed
        if (ex.IsRecoverable &&
ex.OracleLogicalTransaction.Committed == false)
        {
            // safe to re-submit work
        }
        else
        {
            // do not re-submit work
        }
    }
}
finally
{
    // dispose all objects
    txn.Dispose();
    cmd.Dispose();
    con.Dispose(); // place the connection back to the connection
pool
}
}
```

Transaction Guard is not supported when Transparent Application Failover (TAF) is enabled for the service. As such, when TAF is enabled, the `LogicalTransactionId` will always be null and the transaction outcome will not be determined.

 **See Also:**

- ["OracleLogicalTransaction Class"](#)
- *Oracle Database Development Guide* for more information on Transaction Guard

Application Continuity

Oracle Application Continuity enables database requests to automatically replay transactional or non-transactional operations in a non-disruptive and rapid manner in the event of a severed database session, which results in a recoverable error. Application Continuity improves end-user experience by masking planned and unplanned related errors. Applications can be developed without complex logic to handle exceptions, while automatically replaying database operations upon a recoverable error.

Without Application Continuity, it is almost impossible to mask outages in a safe and reliable manner. Common issues encountered include:

- The client state remains at present time, with entered data, returned data, and variables cached, while the database state changes are lost.
- If a transaction commit has occurred, the commit message is not durable. Moreover, checking a lost request does not guarantee that it will not commit after being checked.
- Non-transactional database session state is lost.
- If the request can continue, the database and the client session must be synchronized.

Application Continuity is available with Oracle Database Enterprise Edition with a Real Application Clusters or Active Data Guard option license.

ODP.NET and Application Continuity

ODP.NET, Unmanaged Driver first supported Application Continuity with version 12.2. While Application Continuity was first introduced in Oracle Database 12c Release 1 (12.1), ODP.NET requires a minimum of Oracle Database 12c Release 2 (12.2) server.

 **Note:**

ODP.NET, Managed Driver and ODP.NET Core do not support Application Continuity.

With Application Continuity enabled, ODP.NET ensures all the application's executed statements are logged appropriately so that they can be replayed upon a recoverable error. This applies for all application SQL and PL/SQL, as well as any internal ODP.NET operations.

On the client side, Application Continuity is enabled by setting the ODP.NET connection string attribute, `Application Continuity=true`.

If `Application Continuity` is set to `true`, but the database server does not enable `Application Continuity`, ODP.NET will still create new connections. However, these connections will not be `Application Continuity` enabled.

See Also:

- *Oracle Call Interface Programmer's Guide*
- *Oracle Real Application Clusters Administration and Deployment Guide*

Database Sharding

Sharding is a data tier architecture, where data is horizontally partitioned across independent databases. Each database in such a configuration is called a shard. All shards together make up a single logical database, which is referred to as a sharded database. Sharding is a shared-nothing database architecture. The independent physical databases do not share CPU, memory, or storage devices. However, from the perspective of an application, the collection of physical databases looks like a single logical database.

Sharding uses Global Data Services (GDS), where GDS routes a client request to an appropriate database based on parameters such as availability, load, network latency, and replication lag. A GDS pool is a set of replicated databases that offers the same global service. The databases in a GDS pool can be located in multiple data centers across different regions. A sharded GDS pool contains all shards of a sharded database and their replicas, and appears as a single sharded database to database clients.

Applications can connect to multiple databases (shards) where data is partitioned based on one or more sharding strategies. The strategy can be hash based, range based, or list based. Each time a database operation is required, the application needs to determine which shard it must connect to.

A sharding key provides the partitioning key that determines in which shard a row of data is stored. A table can be partitioned using a sharding key.

A super sharding key is a collection of shard chunks, where only those chunks, which have a specific value of the super shard key identifier, are stored. A super sharding key is used for distributing data across database groups. Specifying super sharding keys are a way through which user-controlled data partitioning is possible.

ODP.NET Sharding

Starting from version 12.2, ODP.NET and Oracle Database both support sharding.

 **Note:**

ODP.NET, Managed Driver and ODP.NET Core do not support sharding.

ODP.NET applications must provide the sharding key and super sharding key information before opening the database connection for single shard queries. These sharding values cannot be set or changed after opening the connection. If any of the shard key values need to be modified, a new connection must be created with the new values and then opened.

If shard keys are set after the connection has been opened, the ODP.NET connection will not use these new shard key values until after the next `OracleConnection.Open()` call.

The `OracleShardingKey` object stores one or more key values. Multiple keys can be set to create a composite key. ODP.NET recognizes the sharding key(s) specified and connects to the correct shard and chunk.

Sharding is supported with or without connection pooling. The ODP.NET connection pool maintains connections to different shards and chunks of the sharded GDS database within the same shared pool.

The shard key (`SHARD_KEY`) and super sharding key (`GROUP_KEY`) can be specified in the TNS connect descriptor, rather than in the application code. The .NET developer then chooses the connect descriptor applicable to the shard that the application will use.

The data distribution across the shards and chunks in the database is transparent to the end user. ODP.NET minimizes the end user impact of chunk resharding within GDS.

To perform cross-shard queries, no ODP.NET shard APIs are used. Instead, applications connect to the GDS catalog service, allowing access to all the sharded databases. The SQL query is specifically constructed to iterate over all the necessary shards. For example, the non-shard database query `select count(*) from employees` is equivalent to the cross-shard query `select sum(c) from (Iterator(select count(*) c from employees(i)))`.

ODP.NET Single Shard Query Example

```
using System;
using Oracle.DataAccess.Client;

class Sharding
{
    static void Main()
    {
        OracleConnection con = new OracleConnection("user id=hr;password=hr;Data
Source=orcl;");
        //Setting a shard key
        OracleShardingKey shardingKey = new OracleShardingKey(OracleDbType.Int32, 123);
        //Setting a second shard key value for a composite key
        shardingKey.SetShardingKey(OracleDbType.Varchar2, "gold");
        //Creating and setting the super shard key
        OracleShardingKey superShardingKey = new OracleShardingKey();
        superShardingKey.SetShardingKey(OracleDbType.Int32, 1000);
    }
}
```

```
//Setting super sharding key and sharding key on the connection
con.SetShardingKey(shardingKey, superShardingKey);
con.Open();

//perform SQL query
}
}
```

 **See Also:**

- [OracleShardingKey Class](#)
- [SetShardingKey\(OracleShardingKey, OracleShardingKey\)](#)

OracleCommand Object

The `OracleCommand` object represents SQL statements or stored procedures executed on Oracle Database.

 **Note:**

Optimizer hint syntax in the form `--+ ...` is not supported. ODP.NET supports this syntax: `/*+ ... */`.

This section includes the following topics:

- [Transactions](#)
- [System.Transactions and Promotable Transactions](#)
- [Parameter Binding](#)
- [Batch Processing](#)
- [Statement Caching](#)
- [Self-Tuning](#)

Transactions

Oracle Database starts a transaction only in the context of a connection. Once a transaction starts, all the successive command execution on that connection run in the context of that transaction. Transactions can be started only on an `OracleConnection` object, and the read-only `Transaction` property on the `OracleCommand` object is implicitly set by the `OracleConnection` object. Therefore, the application cannot set the `Transaction` property, nor does it need to.

 **Note:**

Transactions are not supported in a .NET stored procedure.

Explicit transactions are required with SQL statements containing "FOR UPDATE" and "RETURNING" clauses. This is not necessary if global transactions are used.

System.Transactions and Promotable Transactions

ODP.NET supports `System.Transactions`. A local transaction is created for the first connection opened in the `System.Transactions` scope to Oracle Database 11g release 1 (11.1), or higher. When a second connection is opened, this transaction is automatically promoted to a distributed transaction. This functionality provides enhanced performance and scalability.

Connections created within a transaction context, such as `TransactionScope` or `ServicedComponent`, can be established to different versions of Oracle Database. However, in order to enable the local transaction to be promotable, the following must be true:

- The first connection in the transaction context must be established to an Oracle Database 11g release 1(11.1) instance or higher.
- All connections opened within the transaction context must have the "Promotable Transaction" setting set to "promotable". If you try to open a subsequent connection in the same transaction context with the "Promotable Transaction" setting set to "local", an exception is thrown.
- Promoting local transactions requires Oracle Services for Microsoft Transaction Server 11.1.0.7.20, or higher. If this requirement is not met, then a second connection request in the same transaction context throws an exception.

Transaction promotion will throw an ORA-24797 error when the database transaction is already distributed due to the use of database links.

Setting "local" as the value of "PromotableTransaction" in the registry, configuration file (machine/Web/application), or the "Promotable Transaction" connection string attribute allows only one connection to be opened in the transaction context, which is associated with a local transaction. Such local transactions cannot be promoted. Starting with ODP.NET 12.1.0.2, connections with the `Promotable Transaction` setting set to `local` will begin as and remain a local transaction. If a second connection attempts to join the transaction, an exception will be thrown.

If applications use `System.Transactions`, it is required that the `enlist` connection string attribute is set to either `true` (default) or `dynamic`. However, `enlist=dynamic` cannot be used with `TransactionScope` because auto-enlistment requires `enlist=true`.

ODP.NET supports the following `System.Transactions` programming models for applications using distributed transactions.

- [Implicit Transaction Enlistment Using TransactionScope](#)
- [Explicit Transaction Enlistment Using CommittableTransaction](#)
- [Local Transaction Support for Older Databases](#)

 **See Also:**

- For applications connecting to a pre-Oracle Database 11g release 1 (11.1) instance, refer to "[Local Transaction Support for Older Databases](#)". This section describes how ODP.NET behavior can be controlled using the "Promotable Transaction" setting.
- ODP.NET Core does not support distributed transactions

Implicit Transaction Enlistment Using TransactionScope

The `TransactionScope` class provides a mechanism to write transactional applications where the applications do not need to explicitly enlist in transactions. To accomplish this, the application uses the `TransactionScope` object to define the transactional code. Connections created within this transactional scope will enlist in a local transaction that can be promoted to a distributed transaction.

 **Note:**

If the first connection is opened to a pre-Oracle Database 11g release 1 (11.1) instance, then the connection enlists as a distributed transaction, by default.

You can optionally create the transaction as a local transaction by using the procedure described in "[Local Transaction Support for Older Databases](#)". However, these transactions cannot be promoted to distributed transactions.

Note that the application must call the `Complete` method on the `TransactionScope` object to commit the changes. Otherwise, the transaction is aborted by default.

```
// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;
using System.Data.Common;
using System.Transactions;

class psfTxnScope
{
    static void Main()
    {
        int retVal = 0;
        string providerName = "Oracle.DataAccess.Client";
        string constr =
            @"User Id=scott;Password=tiger;Data Source=oracle;enlist=true";

        // Get the provider factory.
        DbProviderFactory factory = DbProviderFactories.GetFactory(providerName);

        try
        {
```

```

// Create a TransactionScope object, (It will start an ambient
// transaction automatically).
using (TransactionScope scope = new TransactionScope())
{
    // Create first connection object.
    using (DbConnection conn1 = factory.CreateConnection())
    {
        // Set connection string and open the connection. this connection
        // will be automatically enlisted in a promotable local transaction.
        conn1.ConnectionString = constr;
        conn1.Open();

        // Create a command to execute the sql statement.
        DbCommand cmd1 = factory.CreateCommand();
        cmd1.Connection = conn1;
        cmd1.CommandText = @"insert into emp (empno, ename, job) values
                               (1234, 'emp1', 'dev1')";

        // Execute the SQL statement to insert one row in DB.
        retVal = cmd1.ExecuteNonQuery();
        Console.WriteLine("Rows to be affected by cmd1: {0}", retVal);

        // Close the connection and dispose the command object.
        conn1.Close();
        conn1.Dispose();
        cmd1.Dispose();
    }

    // The Complete method commits the transaction. If an exception has
    // been thrown or Complete is not called then the transaction is
    // rolled back.
    scope.Complete();
}
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
}

```

Explicit Transaction Enlistment Using CommittableTransaction

The instantiation of the `CommittableTransaction` object and the `EnlistTransaction` method provides an explicit way to create and enlist in a transaction. Note that the application must call `Commit` or `Rollback` on the `CommittableTransaction` object.

```

// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;
using System.Data.Common;
using System.Transactions;

class psfEnlistTransaction
{
    static void Main()
    {

```

```
int retVal = 0;
string providerName = "Oracle.DataAccess.Client";
string constr =
    @"User Id=scott;Password=tiger;Data Source=oracle;enlist=dynamic";

// Get the provider factory.
DbProviderFactory factory = DbProviderFactories.GetFactory(providerName);

try
{
    // Create a committable transaction object.
    CommittableTransaction cmtTx = new CommittableTransaction();

    // Open a connection to the DB.
    DbConnection conn1 = factory.CreateConnection();
    conn1.ConnectionString = constr;
    conn1.Open();

    // enlist the connection with the committable transaction.
    conn1.EnlistTransaction(cmtTx);

    // Create a command to execute the sql statement.
    DbCommand cmd1 = factory.CreateCommand();
    cmd1.Connection = conn1;
    cmd1.CommandText = @"insert into emp (empno, ename, job) values
                        (1234, 'emp1', 'dev1')";

    // Execute the SQL statement to insert one row in DB.
    retVal = cmd1.ExecuteNonQuery();
    Console.WriteLine("Rows to be affected by cmd1: {0}", retVal);

    // commit/rollback the transaction.
    cmtTx.Commit(); // commits the txn.
    //cmtTx.Rollback(); // rolls back the txn.

    // close and dispose the connection
    conn1.Close();
    conn1.Dispose();
    cmd1.Dispose();
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
```

**See Also:**["EnlistTransaction"](#)

Local Transaction Support for Older Databases

If the first connection in a `TransactionScope` is opened to a pre-Oracle Database 11g release 1 (11.1) instance, then the connection creates a distributed transaction, by

default. You can optionally have the first connection create a local transaction by using the procedure described in this section.

To create local transactions in a `System.Transactions` scope, either the `PromotableTransaction` setting in the registry, machine/Web/application configuration file, or the "Promotable Transaction" connection string attribute must be set to "local".

If "local" is specified, the first connection opened in the `TransactionScope` uses a local transaction. If any subsequent connections are opened within the same `TransactionScope`, an exception is thrown. If there are connections already opened in the `TransactionScope`, and an `OracleConnection` with "Promotable Transaction=local" attempts to open within the same `TransactionScope`, an exception is thrown.

If "promotable" is specified, the first and all subsequent connections opened in the same `TransactionScope` enlist in the same distributed transaction.

If both the registry and the connection string attribute are used and set to different values, the connection string attribute overrides the registry entry value. If neither are set, "promotable" is used. This is the default value and is equivalent to previous versions of ODP.NET which only supported distributed transactions.

The registry entry for a particular version of ODP.NET applies for all applications using that version of ODP.NET.

Parameter Binding

When the `DbType` property of an `OracleParameter` object is set, the `OracleDbType` property of the `OracleParameter` object changes accordingly, or vice versa. The parameter set last prevails. An application can bind the data and have ODP.NET infer both the `DbType` and `OracleDbType` properties from the .NET type of the parameter value. ODP.NET allows applications to obtain an output parameter as either a .NET Framework type or an ODP.NET type. The application can specify which type to return for an output parameter by setting the `DbType` property of the output parameter (.NET type) or the `OracleDbType` property (ODP.NET type) of the `OracleParameter` object. For example, if the output parameter is set as a `DbType.String` type by setting the `DbType` property, the output data is returned as a .NET `String` type. On the other hand, if the parameter is set as an `OracleDbType.Char` type by setting the `OracleDbType` property, the output data is returned as an `OracleString` type. If both `DbType` and `OracleDbType` properties are set before the command execution, the last setting takes affect.

ODP.NET populates `InputOutput`, `Output`, and `ReturnValue` parameters with the Oracle data, through the execution of the following `OracleCommand` methods:

- `ExecuteReader`
- `ExecuteNonQuery`
- `ExecuteScalar`

An application should not bind a value for output parameters; it is the responsibility of ODP.NET to create the value object and populate the `OracleParameter Value` property with the object.

When binding by position (default) to a function, ODP.NET expects the return value to be bound first, before any other parameters.

This section describes the following:

- [OracleDbType Enumeration Type](#)
- [Inference of DbType, OracleDbType, and .NET Types](#)
- [PL/SQL Associative Array Binding](#)
- [Array Binding](#)



See Also:

["OracleDbType Enumeration"](#)

Command Timeouts

The `OracleCommand.CommandTimeout` property limits how long a command is allowed to execute before terminating with an exception. This setting prevents long running commands from consuming excessive resources or from blocking other necessary operations from occurring.

The database server can be interrupted via either TCP/IP urgent data or normal TCP/IP data, called out of band (OOB) or in band data, respectively. Windows-based database servers only support in band breaks, whereas all other (predominantly UNIX-based) database servers can support OOB or in band breaks.

ODP.NET, Managed Driver uses OOB breaks by default with database servers that support it. For certain network topologies, the routers or firewalls involved in the route to the database may have been configured to drop urgent data or in band the data. If the routers or firewalls can not be changed to handle urgent data appropriately, then the ODP.NET, Managed Driver can be configured to utilize in band breaks by setting the .NET configuration parameter `Disable_Oob` to on.



See Also:

[settings section](#) in the [Oracle Data Provider for .NET, Managed Driver Configuration](#) section for more information.

OracleDbType Enumeration Type

`OracleDbType` enumerated values are used to explicitly specify the `OracleDbType` value of an `OracleParameter` object.

[Table 3-7](#) lists all the `OracleDbType` enumeration values with a description of each enumerated value.

Table 3-7 OracleDbType Enumeration Values

Member Name	Description
Array	Oracle Collection (VArray or Nested Table) <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
BFile	Oracle BFILE type
BinaryFloat	Oracle BINARY_FLOAT type
BinaryDouble	Oracle BINARY_DOUBLE type
Blob	Oracle BLOB type
Boolean	Oracle BOOLEAN type
Byte	byte type
Char	Oracle CHAR type
Clob	Oracle CLOB type
Date	Oracle DATE type
Decimal	Oracle NUMBER type
Double	8-byte FLOAT type
Int16	2-byte INTEGER type
Int32	4-byte INTEGER type
Int64	8-byte INTEGER type
IntervalDS	Oracle INTERVAL DAY TO SECOND type
IntervalYM	Oracle INTERVAL YEAR TO MONTH type
Long	Oracle LONG type
LongRaw	Oracle LONG RAW type
NChar	Oracle NCHAR type
Object	Oracle Object type <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
NClob	Oracle NCLOB type
NVarchar2	Oracle NVARCHAR2 type
Raw	Oracle RAW type
Ref	Oracle REF type <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
RefCursor	Oracle REF CURSOR type
Single	4-byte FLOAT type
TimeStamp	Oracle TIMESTAMP type
TimeStampLTZ	Oracle TIMESTAMP WITH LOCAL TIME ZONE type
TimeStampTZ	Oracle TIMESTAMP WITH TIME ZONE type
Varchar2	Oracle VARCHAR2 type
XmlType	Oracle XMLType type

**Note:**

PL/SQL LONG, LONG RAW, RAW, and VARCHAR data types can be bound with a size up to 32512 bytes.

Inference of DbType, OracleDbType, and .NET Types

This section explains the inference from the `System.Data.DbType`, `OracleDbType`, and `Value` properties in the `OracleParameter` class.

In the `OracleParameter` class, `DbType`, `OracleDbType`, and `Value` properties are linked. Specifying the value of any of these properties infers the value of one or more of the other properties.

Inference of DbType from OracleDbType

In the `OracleParameter` class, specifying the value of `OracleDbType` infers the value of `DbType` as shown in [Table 3-8](#).

Table 3-8 Inference of System.Data.DbType from OracleDbType

OracleDbType	System.Data.DbType
Array	Object
BFile	Object
Blob	Object
BinaryFloat	Single
BinaryDouble	Double
Boolean	Boolean
Byte	Byte
Char	StringFixedLength
Clob	Object
Date	Date
Decimal	Decimal
Double	Double
Int16	Int16
Int32	Int32
Int64	Int64
IntervalDS	Object
IntervalYM	Int64
Long	String
LongRaw	Binary
NChar	StringFixedLength
NClob	Object

Table 3-8 (Cont.) Inference of System.Data.DbType from OracleDbType

OracleDbType	System.Data.DbType
NVarChar2	String
Object	Object
Raw	Binary
Ref	Object
RefCursor	Object
Single	Single
TimeStamp	DateTime
TimeStampLTZ	DateTime
TimeStampTZ	DateTime
Varchar2	String
XmlType	String

Inference of OracleDbType from DbType

In the `OracleParameter` class, specifying the value of `DbType` infers the value of `OracleDbType` as shown in [Table 3-9](#).

Table 3-9 Inference of OracleDbType from DbType

System.Data.DbType	OracleDbType
Binary	Raw
Boolean	Boolean
Byte	Byte
Currency	<i>Not Supported</i>
Date	Date
DateTime	TimeStamp
Decimal	Decimal
Double	Double
Guid	<i>Not Supported</i>
Int16	Int16
Int32	Int32
Int64	Int64
Object	Object
Sbyte	<i>Not Supported</i>
Single	Single
String	Varchar2
StringFixedLength	Char

Table 3-9 (Cont.) Inference of OracleDbType from DbType

System.Data.DbType	OracleDbType
Time	TimeStamp
UInt16	<i>Not Supported</i>
UInt32	<i>Not Supported</i>
UInt64	<i>Not Supported</i>
VarNumeric	<i>Not Supported</i>

Inference of DbType and OracleDbType from Value

In the `OracleParameter` class, `Value` is an object type that can be of any .NET Framework data type or ODP.NET type. If the `OracleDbType` and `DbType` properties of the `OracleParameter` class are not specified, the `OracleDbType` property is inferred from the type of the `Value` property.

[Table 3-10](#) shows the inference of `DbType` and `OracleDbType` properties from the `Value` property when the type of `Value` is one of the .NET Framework data types.

Table 3-10 Inference of DbType and OracleDbType from Value (.NET Datatypes)

Value (.NET Datatypes)	System.Data.DbType	OracleDbType
Boolean	Boolean	Boolean
Byte	Byte	Byte
Byte[]	Binary	Raw
Char / Char []	String	Varchar2
DateTime	DateTime	TimeStamp
Decimal	Decimal	Decimal
Double	Double	Double
Float	Single	Single
Int16	Int16	Int16
Int32	Int32	Int32
Int64	Int64	Int64
IOracleCustomType	Object	Object
Single	Single	Single
String	String	Varchar2
TimeSpan	Object	IntervalDS

 **Note:**

Using other .NET Framework data types as values for the `OracleParameter` class without specifying either the `DbType` or the `OracleDbType` properties raises an exception because inferring `DbType` and `OracleDbType` properties from other .NET Framework data types is not supported.

Table 3-11 shows the inference of `DbType` and `OracleDbType` properties from the `Value` property when type of `Value` is one of `Oracle.DataAccess.Types`.

Table 3-11 Inference of DbType and OracleDbType from Value (ODP.NET Types)

Value (Oracle.DataAccess.Types)	System.Data.DbType	OracleDbType
OracleBFile	Object	BFile
OracleBinary	Binary	Raw
OracleBlob	Object	Blob
OracleBoolean	Boolean	Boolean
OracleClob	Object	Clob
OracleDate	Date	Date
OracleDecimal	Decimal	Decimal
OracleIntervalDS	Object	IntervalDS
OracleIntervalYM	Int64	IntervalYM
OracleRef	Object	Ref
OracleRefCursor	Object	RefCursor
OracleString	String	Varchar2
OracleTimeStamp	DateTime	TimeStamp
OracleTimeStampLTZ	DateTime	TimeStampLTZ
OracleTimeStampTZ	DateTime	TimeStampTZ
OracleXmlType	String	XmlType

PL/SQL Associative Array Binding

ODP.NET supports PL/SQL Associative Arrays (formerly known as PL/SQL Index-By Tables) binding.

An application can bind an `OracleParameter` object, as a PL/SQL Associative Array, to a PL/SQL stored procedure. The following `OracleParameter` properties are used for this feature:

- `CollectionType`

This property must be set to `OracleCollectionType.PLSQLAssociativeArray` to bind a PL/SQL Associative Array.

- `ArrayBindSize`

This property is ignored for the fixed-length element types (such as `Int32`).

For variable-length element types (such as `Varchar2`), each element in the `ArrayBindSize` property specifies the size of the corresponding element in the `Value` property.

For `Output` parameters, `InputOutput` parameters, and return values, this property must be set for variable-length variables.

If the database server supports up to 32 KB `VARCHAR2`, then each ODP.NET array element can store up to 32 KB characters or binary data. If the database server supports up to 4 KB `VARCHAR2`, then each ODP.NET array element can store up to 4 KB characters or 2 KB binary data.
- `ArrayBindStatus`

This property specifies the execution status of each element in the `OracleParameter.Value` property.
- `Size`

This property specifies the maximum number of elements to be bound in the PL/SQL Associative Array.
- `Value`

This property must be set to an array of values, `null`, or the `DBNull.Value` property.

ODP.NET supports binding parameters of PL/SQL Associative Arrays which contain the following data types.

- `BINARY_FLOAT`
- `CHAR`
- `DATE`
- `NCHAR`
- `NUMBER`
- `NVARCHAR2`
- `RAW`
- `ROWID`
- `UROWID`
- `VARCHAR2`

Using unsupported data types with associative arrays can cause an ORA-600 error.

Example of PL/SQL Associative Arrays

This example binds three `OracleParameter` objects as PL/SQL Associative Arrays: `Param1` as an `In` parameter, `Param2` as an `InputOutput` parameter, and `Param3` as an `Output` parameter.

PL/SQL Package: `MYPACK`

```
/* Setup the tables and required PL/SQL:
```

```
connect scott/tiger@oracle
CREATE TABLE T1(COL1 number, COL2 varchar2(20));

CREATE or replace PACKAGE MYPACK AS
  TYPE AssocArrayVarchar2_t is table of VARCHAR(20) index by BINARY_INTEGER;
  PROCEDURE TestVarchar2(
    Param1 IN AssocArrayVarchar2_t,
    Param2 IN OUT AssocArrayVarchar2_t,
    Param3 OUT AssocArrayVarchar2_t);
END MYPACK;
/

CREATE or REPLACE package body MYPACK as
  PROCEDURE TestVarchar2(
    Param1 IN AssocArrayVarchar2_t,
    Param2 IN OUT AssocArrayVarchar2_t,
    Param3 OUT AssocArrayVarchar2_t)
  IS
    i integer;
  BEGIN
    -- copy a few elements from Param2 to Param1\n
    Param3(1) := Param2(1);
    Param3(2) := NULL;
    Param3(3) := Param2(3);
    -- copy all elements from Param1 to Param2\n
    Param2(1) := Param1(1);
    Param2(2) := Param1(2);
    Param2(3) := Param1(3);
    -- insert some values to db\n
    FOR i IN 1..3 LOOP
      insert into T1 values(i,Param2(i));
    END LOOP;
  END TestVarchar2;
END MYPACK;
/
*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class AssociativeArraySample
{
  static void Main()
  {
    OracleConnection con = new OracleConnection();

    con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
    con.Open();
    Console.WriteLine("Connected to Oracle" + con.ServerVersion);

    OracleCommand cmd = new OracleCommand(
      "begin MyPack.TestVarchar2(:1, :2, :3); end;", con);

    OracleParameter Param1 = cmd.Parameters.Add("1", OracleDbType.Varchar2);
    OracleParameter Param2 = cmd.Parameters.Add("2", OracleDbType.Varchar2);
    OracleParameter Param3 = cmd.Parameters.Add("3", OracleDbType.Varchar2);

    Param1.Direction = ParameterDirection.Input;
```

```
Param2.Direction = ParameterDirection.InputOutput;
Param3.Direction = ParameterDirection.Output;

// Specify that we are binding PL/SQL Associative Array
Param1.CollectionType = OracleCollectionType.PLSQLAssociativeArray;
Param2.CollectionType = OracleCollectionType.PLSQLAssociativeArray;
Param3.CollectionType = OracleCollectionType.PLSQLAssociativeArray;

// Setup the values for PL/SQL Associative Array
Param1.Value = new string[3] {
    "First Element", "Second Element ", "Third Element "
};
Param2.Value = new string[3] {
    "First Element", "Second Element ", "Third Element "
};
Param3.Value = null;

// Specify the maximum number of elements in the PL/SQL Associative Array
Param1.Size = 3;
Param2.Size = 3;
Param3.Size = 3;

// Setup the ArrayBindSize for Param1
Param1.ArrayBindSize = new int[3] { 13, 14, 13 };

// Setup the ArrayBindStatus for Param1
Param1.ArrayBindStatus = new OracleParameterStatus[3] {
    OracleParameterStatus.Success, OracleParameterStatus.Success,
    OracleParameterStatus.Success};

// Setup the ArrayBindSize for Param2
Param2.ArrayBindSize = new int[3] { 20, 20, 20 };

// Setup the ArrayBindSize for Param3
Param3.ArrayBindSize = new int[3] { 20, 20, 20 };

// execute the cmd
cmd.ExecuteNonQuery();

//print out the parameter's values
Console.WriteLine("parameter values after executing the PL/SQL block");
for (int i = 0; i < 3; i++)
    Console.WriteLine("Param2[{0}] = {1} ", i,
        (cmd.Parameters[1].Value as Array).GetValue(i));

for (int i = 0; i < 3; i++)
    Console.WriteLine("Param3[{0}] = {1} ", i,
        (cmd.Parameters[2].Value as Array).GetValue(i));

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
Console.WriteLine("Disconnected");
}
}
```

Array Binding

The array bind feature enables applications to bind arrays of a type using the `OracleParameter` class. Using the array bind feature, an application can insert multiple rows into a table in a single database round-trip.

The following example inserts three rows into the `Dept` table with a single database round-trip. The `OracleCommand` `ArrayBindCount` property defines the number of elements of the array to use when executing the statement.

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected successfully");

        int[] myArrayDeptNo = new int[3] { 10, 20, 30 };
        OracleCommand cmd = new OracleCommand();

        // Set the command text on an OracleCommand object
        cmd.CommandText = "insert into dept(deptno) values (:deptno)";
        cmd.Connection = con;

        // Set the ArrayBindCount to indicate the number of values
        cmd.ArrayBindCount = 3;

        // Create a parameter for the array operations
        OracleParameter prm = new OracleParameter("deptno", OracleDbType.Int32);

        prm.Direction = ParameterDirection.Input;
        prm.Value = myArrayDeptNo;

        // Add the parameter to the parameter collection
        cmd.Parameters.Add(prm);

        // Execute the command
        cmd.ExecuteNonQuery();
        Console.WriteLine("Insert Completed Successfully");

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}
```

**See Also:**

"Value " for more information

OracleParameter Array Bind Properties

The `OracleParameter` class provides two properties for granular control when using the array bind feature:

- `ArrayBindSize`

The `ArrayBindSize` property is an array of integers specifying the maximum size for each corresponding value in an array. The `ArrayBindSize` property is similar to the `Size` property of an `OracleParameter` object, except the `ArrayBindSize` property specifies the size for each value in an array.

Before the execution, the application must populate the `ArrayBindSize` property; after the execution, ODP.NET populates it.

The `ArrayBindSize` property is used only for parameter types that have variable length such as `Clob`, `Blob`, and `Varchar2`. The size is represented in bytes for binary data types, and characters for the Unicode string types. The count for string types does not include the terminating character. The size is inferred from the actual size of the value, if it is not explicitly set. For an output parameter, the size of each value is set by ODP.NET. The `ArrayBindSize` property is ignored for fixed-length data types.

The maximum `ArrayBindSize` size is 2 GB for both character and binary data.

- `ArrayBindStatus`

The `ArrayBindStatus` property is an array of `OracleParameterStatus` values that specify the status of each corresponding value in an array for a parameter. This property is similar to the `Status` property of the `OracleParameter` object, except that the `ArrayBindStatus` property specifies the status for each array value.

Before the execution, the application must populate the `ArrayBindStatus` property. After the execution, ODP.NET populates the property. Before the execution, an application using the `ArrayBindStatus` property can specify a `NULL` value for the corresponding element in the array for a parameter. After the execution, ODP.NET populates the `ArrayBindStatus` property, indicating whether the corresponding element in the array has a `null` value, or if data truncation occurred when the value was fetched.

Error Handling for Array Binding

If an error occurs during an array bind execution, it can be difficult to determine which element in the `Value` property caused the error. ODP.NET provides a way to determine the row where the error occurred, making it easier to find the element in the row that caused the error.

When an `OracleException` object is thrown during an array bind execution, the `OracleErrorCollection` object contains one or more `OracleError` objects. Each of these `OracleError` objects represents an individual error that occurred during the execution, and contains a provider-specific property, `ArrayBindIndex`, which indicates the row number at which the error occurred.

The following example demonstrates error handling for array binding:

```
/* Database Setup
connect scott/tiger@oracle
drop table depttest;
create table depttest(deptno number(2));
*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindExceptionSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
        con.Open();

        OracleCommand cmd = new OracleCommand();

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(IsolationLevel.ReadCommitted);

        try
        {
            int[] myArrayDeptNo = new int[3] { 10, 200000, 30 };
            // int[] myArrayDeptNo = new int[3]{ 10,20,30};

            // Set the command text on an OracleCommand object
            cmd.CommandText = "insert into depttest(deptno) values (:deptno)";
            cmd.Connection = con;

            // Set the ArrayBindCount to indicate the number of values
            cmd.ArrayBindCount = 3;

            // Create a parameter for the array operations
            OracleParameter prm = new OracleParameter("deptno", OracleDbType.Int32);

            prm.Direction = ParameterDirection.Input;
            prm.Value = myArrayDeptNo;

            // Add the parameter to the parameter collection
            cmd.Parameters.Add(prm);

            // Execute the command
            cmd.ExecuteNonQuery();
        }
        catch (OracleException e)
        {
            Console.WriteLine("OracleException {0} occurred", e.Message);
            if (e.Number == 24381)
                for (int i = 0; i < e.Errors.Count; i++)
                    Console.WriteLine("Array Bind Error {0} occurred at Row Number {1}",
                        e.Errors[i].Message, e.Errors[i].ArrayBindIndex);

            txn.Commit();
        }
    }
}
```



```
cmd.Parameters.Clear();  
cmd.CommandText = "select count(*) from depttest";  
  
decimal rows = (decimal)cmd.ExecuteScalar();  
  
Console.WriteLine("{0} row have been inserted", rows);  
con.Close();  
con.Dispose();  
}  
}
```

**See Also:**

["ArrayBindIndex"](#) for more information

OracleParameterStatus Enumeration Types

[Table 3-12](#) lists `OracleParameterStatus` enumeration values.

Table 3-12 OracleParameterStatus Members

Member Names	Description
Success	For input parameters, indicates that the input value has been assigned to the column. For output parameters, indicates that the provider assigned an intact value to the parameter.
NullFetched	Indicates that a NULL value has been fetched from a column or an OUT parameter.
NullInsert	Indicates that a NULL value is to be inserted into a column.
Truncation	Indicates that truncation has occurred when fetching the data from the column.

Batch Processing

The `OracleDataAdapter.UpdateBatchSize` property enables batch processing when the `OracleDataAdapter.Update` method is called. `UpdateBatchSize` is a numeric property that indicates how many `DataSet` rows to update the Oracle database for each round-trip.

This enables the developer to reduce the number of round-trips to the database.

**See Also:**

["UpdateBatchSize"](#)

Statement Caching

Statement caching eliminates the need to parse each SQL or PL/SQL statement before execution by caching server cursors created during the initial statement execution. Subsequent executions of the same statement can reuse the parsed information from the cursor, and then execute the statement without reparsing, for better performance.

In order to see performance gains from statement caching, Oracle recommends caching only those statements that will be repeatedly executed. Furthermore, SQL or PL/SQL statements should use parameters rather than literal values. Doing so takes full advantage of statement caching, because parsed information from parameterized statements can be reused even if the parameter values change in subsequent executions. However, if the literal values in the statements are different, the parsed information cannot be reused unless the subsequent statements also have the same literal values.

Statement Caching Connection String Attributes

The following connection string attributes control the behavior of the ODP.NET statement caching feature:

- `Statement Cache Size`

This attribute enables or disables ODP.NET statement caching. By default, this attribute is set to 0 (disabled). If it is set to a value greater than 0, ODP.NET statement caching is enabled and the value specifies the maximum number of statements that can be cached for a connection. Once a connection has cached up to the specified maximum cache size, the least recently used cursor is freed to make room to cache the newly created cursor.

If self tuning is enabled, then statement caching is enabled as well. The `Statement Cache Size` is configured automatically in such cases.

- `Statement Cache Purge`

This attribute provides a way for connections to purge all statements that are cached when a connection is closed or placed back into the connection pool. By default, this attribute is set to `false`, which means that cursors are not freed when connections are placed back into the pool.

Enabling Statement Caching through the Registry

To enable statement caching by default for all ODP.NET applications running in a system, without changing the application, set the registry key of `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version\StatementCacheSize` to a value greater than 0. This value specifies the number of cursors that are to be cached on the server.

The default value for the system can be overridden at the connection pool level. The `Statement Cache Size` attribute can be set to a different size than the registry value or it can be turned off. The `Statement Cache Size` can also be configured through an XML configuration file.

**See Also:**

[Configuring Oracle Data Provider for .NET](#) for more details.

Statement Caching Methods and Properties

The following property and method are relevant only when statement caching is enabled:

- `OracleCommand.AddToStatementCache` property
If statement caching is enabled, having this property set to `true` (default) adds statements to the cache when they are executed. If statement caching is disabled or if this property is set to `false`, the executed statement is not cached.
- `OracleConnection.PurgeStatementCache` method
This method purges all the cached statements by closing all open cursors on the database that are associated with the particular connection. Note that statement caching remains enabled after this call.

Connections and Statement Caching

Statement caching is managed separately for each connection. Therefore, executing the same statement on different connections requires parsing once for each connection and caching a separate cursor for each connection.

Pooling and Statement Caching

Pooling and statement caching can be used in conjunction. If connection pooling is enabled and the `Statement Cache Purge` attribute is set to `false`, statements executed on each separate connection are cached throughout the lifetime of the pooled connection.

If the `Statement Cache Purge` attribute is set to `true`, all the cached cursors are freed when the connection is placed back into the pool. When connection pooling is disabled, cursors are cached during the lifetime of the connection, but the cursors are closed when the `OracleConnection` object is closed or disposed of.

Self-Tuning

ODP.NET applications can be self-tuned for performance optimization. ODP.NET dynamically monitors application queries during runtime.

**Note:**

Self-tuning for applications does not take place if the `Pooling` connection string attribute is set to `false`. Self-tuning is also not supported inside .NET stored procedures.

The statement cache size ([StatementCacheSize](#)) is tuned automatically by monitoring the statements that are executed by the application. The following sections discuss self-tuning in applications:

- [Self-Tuning Statement Caching](#)
- [Enabling or Disabling Self-Tuning for Applications](#)
- [Tracing Optimization Changes](#)

Self-Tuning Statement Caching

Statement caching helps improve performance by eliminating the need to re-parse each SQL or PL/SQL statement before execution.

If self-tuning is enabled for an application, then ODP.NET continuously monitors application behavior in order to determine the optimum value for the statement cache size. Any statement cache size value specified in the connection string, configuration file, or registry is ignored.

When the application first initializes, it uses the default value of statement cache size. As the application executes statements, ODP.NET collects statistics that are used to self-tune the value of statement cache size. Self-tuning of statement cache size results in increased performance.

Note:

To take full advantage of statement caching, you should not dynamically generate statements, with different inline values, for every statement execution. Instead, use parameterized commands to minimize the number of unique statements that need to be executed and cached. This is because only one statement needs to be cached for every unique command text, regardless of the parameter values and the number of times that the statement is executed.

The maximum number of statements that can be cached per connection is determined by the `MaxStatementCacheSize` configuration attribute. The `MaxStatementCacheSize` value can be specified in the Windows registry or XML configuration file.

The `MaxStatementCacheSize` setting is useful in limiting the number of cached statements, as well as the number of open cursors. This is because a cached statement equates to a cursor being opened on the server. For this reason, you should not set `MaxStatementCacheSize` to a value that is greater than the database `OPEN_CURSORS` setting.

The following Windows registry key is used to configure the `MaxStatementCacheSize` configuration attribute:

```
HKLM\Software\Oracle\ODP.NET\version\MaxStatementCacheSize
```

The `MaxStatementCacheSize` key is of type `REG_SZ`. It can be set to an integer value between 0 and `System.Int32.MaxValue`.

The following example sets the `MaxStatementCacheSize` property in an ADO.NET 2.0, or above, configuration file:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="MaxStatementCacheSize" value="300"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

If self-tuning is disabled for an application, then the value of statement cache size is determined by the settings in the connection string, configuration file, or the registry. If statement cache size is not specified in any of these sources, then the default value of statement cache size is set to 0. To have ODP.NET configured with the same default settings as previous releases of ODP.NET, disable self-tuning and set the `StatementCacheSize` value to 10.



See Also:

["Statement Caching"](#)

Enabling or Disabling Self-Tuning for Applications

Self-tuning for ODP.NET applications is enabled by default. An application can enable or disable self-tuning using one of the following methods:

- Self-Tuning Connection String Attribute

An application can modify the `Self Tuning` connection string attribute to enable or disable self-tuning for a particular connection pool. The default value for `Self Tuning` is `true`.

- Windows Registry

An application can enable or disable self-tuning for a particular version of ODP.NET by modifying the following registry entry:

```
HKLM\Software\Oracle\ODP.NET\version\SelfTuning
```

The `SelfTuning` key is of type `REG_SZ`. It can be set to either 1 (enabled) or 0 (disabled).

- Configuration File

An ODP.NET application can modify the application configuration file (`app.config`) or Web configuration file (`web.config`) to enable or disable self-tuning.

The following example shows how to enable self-tuning in an ADO.NET 2.0 application configuration file:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="SelfTuning" value="1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

 **Note:**

If the optimal statement cache size is known for an application, then you can disable self-tuning and set `StatementCacheSize` to its optimum value in the registry, configuration file, or the application. If self-tuning is disabled and `StatementCacheSize` is not set at all, then the default value of 0 is used for `StatementCacheSize`.

Tracing Optimization Changes

Applications can trace optimization changes made by self-tuning. All changes to `StatementCacheSize` are traced. Errors, if any, are also traced.

The `TraceLevel` used for tracing self-tuning is 64.

 **See Also:**

[Table 2-3](#) for details on `TraceLevel` values

ODP.NET Types Overview

ODP.NET types represent Oracle native data types and PL/SQL data types as a structure or as a class. ODP.NET type structures follow [value semantics](#), while ODP.NET type classes follow [reference semantics](#). ODP.NET types provide safer and more efficient ways of obtaining Oracle native data and PL/SQL data types in a .NET application than .NET types. For example, an `OracleDecimal` structure holds up to 38 digits of precision, while a .NET `Decimal` only holds up to 28.

[Table 3-13](#) lists data types supported by ODP.NET and their corresponding ODP.NET types: data types in the first column refer to both Oracle native data types and PL/SQL data types of that name. Those data types that exist only in PL/SQL are indicated by (PL/SQL only) after the data type name. The entries for the PL/SQL data types also represent the subtypes of the data types, if any. The third column lists the .NET Framework data type that corresponds to the `Value` property of each ODP.NET type.

Table 3-13 Value Property Type of ODP.NET Type

Oracle Native Data Type or PL/SQL Data Type	ODP.NET Type	.NET Framework Data Types
BFILE	OracleBFile class	System.Byte[]
BINARY_DOUBLE	OracleDecimal structure	System.Decimal
BINARY_FLOAT	OracleDecimal structure	System.Decimal
BINARY_INTEGER (PL/SQL only)	OracleDecimal structure	System.Decimal
BLOB	OracleBlob class	System.Byte[]

Table 3-13 (Cont.) Value Property Type of ODP.NET Type

Oracle Native Data Type or PL/SQL Data Type	ODP.NET Type	.NET Framework Data Types
BOOLEAN (PL/SQL only)	OracleBoolean structure	System.Boolean
CHAR	OracleString structure	System.String
CLOB	OracleClob class	System.String
DATE	OracleDate structure	System.DateTime
INTERVAL DAY TO SECOND	OracleIntervalDS structure	System.TimeSpan
INTERVAL YEAR TO MONTH	OracleIntervalYM structure	System.Int64
LONG	OracleString structure	System.String
LONG RAW	OracleBinary structure	System.Byte[]
NCHAR	OracleString structure	System.String
NCLOB	OracleClob class	System.String
NUMBER	OracleDecimal structure	System.Decimal
NVARCHAR2	OracleString structure	System.String
PLS_INTEGER (PL/SQL only)	OracleDecimal Structure	System.Decimal
RAW	OracleBinary structure	System.Byte[]
REF	OracleRef class	System.String
REF CURSOR (PL/SQL only)	OracleRefCursor class	Not Applicable
ROWID	OracleString structure	System.String
TIMESTAMP	OracleTimeStamp structure	System.DateTime
TIMESTAMP WITH LOCAL TIME ZONE	OracleTimeStampLTZ structure	System.DateTime
TIMESTAMP WITH TIME ZONE	OracleTimeStampTZ structure	System.DateTime
UROWID	OracleString structure	System.String
VARCHAR2	OracleString structure	System.String
XMLType	OracleXmlType class	System.String

Obtaining Data from an OracleDataReader Object

The `ExecuteReader` method of the `OracleCommand` object returns an `OracleDataReader` object, which is a read-only, forward-only result set.

This section provides the following information about the `OracleDataReader` object:

- [Typed OracleDataReader Accessors](#)

- [Obtaining LONG and LONG RAW Data](#)
- [Obtaining LOB Data](#)
- [Controlling the Number of Rows Fetched in One Database Round-Trip](#)

Typed OracleDataReader Accessors

The `OracleDataReader` class provides two types of typed accessors:

- [.NET Type Accessors](#)
- [ODP.NET Type Accessors](#)

.NET Type Accessors

[Table 3-14](#) lists all the Oracle native database types that ODP.NET supports, and the corresponding .NET types that can represent the Oracle native type. If more than one .NET type can be used to represent an Oracle native type, the first entry is the .NET type that best represents the Oracle native type. The third column indicates the valid typed accessor that can be invoked for an Oracle native type to be obtained as a .NET type. If an invalid typed accessor is used for a column, an `InvalidCastException` is thrown. Oracle native data types depend on the version of the database; therefore, some data types are not available in earlier versions of Oracle Database.

See Also:

- ["OracleDataAdapter Class"](#)
- ["OracleDataReader Class"](#)

Table 3-14 .NET Type Accessors

Oracle Native Data Type	.NET Type	Typed Accessor
BFILE	<code>System.Byte[]</code>	<code>GetBytes</code>
BINARY_DOUBLE	<code>System.Double</code>	<code>GetDouble</code>
BINARY_FLOAT	<code>System.Single</code>	<code>GetFloat</code>
BLOB	<code>System.Byte[]</code>	<code>GetBytes</code>
CHAR	<code>System.String</code> <code>System.Char[]</code>	<code>GetString</code> <code>GetChars</code>
CLOB	<code>System.String</code> <code>System.Char[]</code>	<code>GetString</code> <code>GetChars</code>
DATE	<code>System.DateTime</code>	<code>GetDateTime</code>
INTERVAL DAY TO SECOND	<code>System.Timespan</code>	<code>GetTimeSpan</code>
INTERVAL YEAR TO MONTH	<code>System.Int64</code>	<code>GetInt64</code>
LONG	<code>System.String</code> <code>System.Char[]</code>	<code>GetString</code> <code>GetChars</code>

Table 3-14 (Cont.) .NET Type Accessors

Oracle Native Data Type	.NET Type	Typed Accessor
LONG RAW	System.Byte[]	GetBytes
NCHAR	System.String	GetString
	System.Char[]	GetChars
NCLOB	System.String	GetString
	System.Char[]	GetChars
NUMBER	System.Decimal	GetDecimal
	System.Byte	GetByte
	System.Int16	GetInt16
	System.Int32	GetInt32
	System.Int64	GetInt64
	System.Single	GetFloat
NVARCHAR2	System.String	GetString
	System.Char[]	GetChars
RAW	System.Byte[]	GetBytes
REF	System.String	GetString
ROWID	System.String	GetString
	System.Char[]	GetChars
TIMESTAMP	System.DateTime	GetDateTime
TIMESTAMP WITH LOCAL TIME ZONE	System.DateTime	GetDateTime
TIMESTAMP WITH TIME ZONE	System.DateTime	GetDateTime
UROWID	System.String	GetString
	System.Char[]	GetChars
VARCHAR2	System.String	GetString
	System.Char[]	GetChars
XMLType	System.String	GetString
	System.Xml.XmlReader	GetXmlReader

Certain methods and properties of the `OracleDataReader` object require ODP.NET to map a `NUMBER` column to a .NET type based on the precision and scale of the column. These members are:

- `Item` property
- `GetFieldType` method
- `GetValue` method
- `GetValues` method

ODP.NET determines the appropriate .NET type by considering the following .NET types in order, and selecting the first .NET type from the list that can represent the entire range of values of the column:

- `System.Byte`
- `System.Int16`
- `System.Int32`
- `System.Int64`
- `System.Single`
- `System.Double`
- `System.Decimal`

If no .NET type exists that can represent the entire range of values of the column, then an attempt is made to represent the column values as a `System.Decimal` type. If the value in the column cannot be represented as `System.Decimal`, then an exception is raised.

For example, consider two columns defined as `NUMBER(4,0)` and `NUMBER(10,2)`. The first .NET types from the previous list that can represent the entire range of values of the columns are `System.Int16` and `System.Double`, respectively. However, consider a column defined as `NUMBER(20,10)`. In this case, there is no .NET type that can represent the entire range of values on the column, so an attempt is made to return values in the column as a `System.Decimal` type. If a value in the column cannot be represented as a `System.Decimal` type, then an exception is raised.

The `Fill` method of the `OracleDataAdapter` class uses the `OracleDataReader` object to populate or refresh a `DataTable` or `DataSet` with .NET types. As a result, the .NET type used to represent a `NUMBER` column in the `DataTable` or `DataSet` also depends on the precision and scale of the column.

See Also:

- ["OracleDataReader Class"](#)
- ["OracleDataAdapter Class "](#)
- ["Item "](#)
- ["GetFieldType "](#)
- ["GetValues "](#)
- ["GetValue "](#)

ODP.NET Type Accessors

ODP.NET exposes provider-specific types that natively represent the data types in the database. In some cases, these ODP.NET types provide better performance and functioning than the corresponding .NET types. The ODP.NET types can be obtained from the `OracleDataReader` object by calling their respective typed accessor.

[Table 3-15](#) lists the valid type accessors that ODP.NET uses to obtain ODP.NET types for an Oracle native type.

Table 3-15 ODP.NET Type Accessors

Oracle Native Data Type	ODP.NET Type	Typed Accessor
BFILE	OracleBFile	GetOracleBFile
BINARY_DOUBLE	OracleDecimal	GetOracleDecimal
BINARY_FLOAT	OracleDecimal	GetOracleDecimal
BLOB	OracleBlob	GetOracleBlob
	OracleBlob	GetOracleBlobForUpdate
	OracleBinary	GetOracleBinary
CHAR	OracleString	GetOracleString
CLOB	OracleClob	GetOracleClob
	OracleClob	GetOracleClobForUpdate
	OracleString	GetOracleString
DATE	OracleDate	GetOracleDate
INTERVAL DAY TO SECOND	OracleIntervalDS	GetOracleIntervalDS
INTERVAL YEAR TO MONTH	OracleIntervalYM	GetOracleIntervalYM
LONG	OracleString	GetOracleString
LONG RAW	OracleBinary	GetOracleBinary
NCHAR	OracleString	GetOracleString
NCLOB	OracleString	GetOracleString
NUMBER	OracleDecimal	GetOracleDecimal
NVARCHAR2	OracleString	GetOracleString
RAW	OracleBinary	GetOracleBinary
REF	OracleRef	GetOracleRef
ROWID	OracleString	GetOracleString
TIMESTAMP	OracleTimeStamp	GetOracleTimeStamp
TIMESTAMP WITH LOCAL TIME ZONE	OracleTimeStampLTZ	GetOracleTimeStampLTZ
TIMESTAMP WITH TIME ZONE	OracleTimeStampTZ	GetOracleTimeStampTZ
UROWID	OracleString	GetOracleString
VARCHAR2	OracleString	GetOracleString
XMLType	OracleString	GetOracleString
	OracleXmlType	GetOracleXmlType

**See Also:**

["ODP.NET Types Overview"](#) for a list of all ODP.NET types

Obtaining LONG and LONG RAW Data

ODP.NET fetches and caches rows from the database during the `Read` method invocations on the `OracleDataReader` object. The amount of LONG and LONG RAW column data that is retrieved from this operation is determined by `InitialLONGFetchSize`. The different behaviors observed when `InitialLONGFetchSize` is set to 0, greater than 0, and -1 are explained in the following sections.

 **Note:**

ODP.NET does not support the `CommandBehavior.SequentialAccess` enumeration value. Therefore, LONG and LONG RAW data can be fetched randomly.

Setting InitialLONGFetchSize to Zero or a Value Greater than Zero

The specified amount of `InitialLONGFetchSize` characters or bytes for LONG or LONG RAW column data is retrieved into the cache during the `Read` method invocations on the `OracleDataReader` object.

By default, `InitialLONGFetchSize` is set to 0. In this case, ODP.NET does not fetch any LONG or LONG RAW column data during the `Read` method invocations on the `OracleDataReader` object. The LONG or LONG RAW data is fetched when the typed accessor method is explicitly invoked for the LONG or LONG RAW column, which incurs a database round-trip because no data is cached.

If `InitialLONGFetchSize` is set to a value greater than 0, that amount of specified data is cached by ODP.NET during the `Read` method invocations on the `OracleDataReader` object. If the application requests an amount of data less than or equal to the `InitialLONGFetchSize` through the typed accessor methods, no database round-trip is incurred. However, an additional database round-trip is required to fetch data beyond `InitialLONGFetchSize`.

To obtain data beyond the `InitialLONGFetchSize` characters or bytes, one of the following must be in the select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a NOT NULL constraint defined on it)

To be able to fetch the entire LONG or LONG RAW data without having a primary key column, a ROWID, or unique columns in the select list, set the size of the `InitialLONGFetchSize` property on the `OracleCommand` object to equal or greater than the number of characters or bytes needed to be retrieved.

The LONG or LONG RAW data is returned when the appropriate typed accessor method (`GetChars`, `GetOracleString`, or `GetString` for LONG or `GetOracleBinary` or `GetBytes` for LONG RAW) is called on the `OracleDataReader` object.

Setting InitialLONGFetchSize to -1

By setting `InitialLONGFetchSize` to -1, it is possible to fetch the entire `LONG` or `LONG RAW` data from the database for a select query, without requiring a primary key, `ROWID`, or unique column in the select list.

When `InitialLONGFetchSize` is set to -1, the entire `LONG` or `LONG RAW` data is retrieved and cached during `Read` method invocations on the `OracleDataReader` object. Calls to `GetString`, `GetOracleString`, `GetChars`, `GetBytes`, or `GetOracleBinary` in the `OracleDataReader` return the entire column data.

Obtaining LOB Data

ODP.NET fetches and caches rows from the database during the `Read` method invocations on the `OracleDataReader` object. The amount of LOB column data that is retrieved from this operation is determined by `InitialLOBFetchSize`.

The following is a complete list of typed accessor methods that an application can call for the `CLOB` and `BLOB` columns, if `InitialLOBFetchSize` is set to 0, greater than 0, or -1:

- Methods callable for `BLOB` column
 - `GetBytes`
 - `GetValue`
 - `GetValues`
 - `GetOracleBinary`
 - `GetOracleBlob`
 - `GetOracleBlobForUpdate`
 - `GetOracleValue`
 - `GetOracleValues`
- Methods callable for `CLOB` column
 - `GetChars`
 - `GetString`
 - `GetValue`
 - `GetValues`
 - `GetOracleString`
 - `GetOracleClob`
 - `GetOracleClobForUpdate`
 - `GetOracleValue`
 - `GetOracleValues`

The following sections explain the different behaviors observed when `InitialLOBFetchSize` is set to 0, greater than 0, and -1.

Setting InitialLOBFetchSize to Zero

By default, the `InitialLOBFetchSize` property is 0. This value dictates to ODP.NET that any LOBs selected will have their client LOB data fetches deferred until after the `OracleDataReader Read`, such as when using the an accessor. Each LOB value is retrieved only at the point it is individually accessed.

The advantage of using this retrieval strategy is that it conserves client memory and bandwidth. If the LOBs selected are either very large or not necessary to be immediately consumed by the end user, or both, then the application can perform better if LOBs are retrieved as needed, rather than all at once.

Setting InitialLOBFetchSize to a Value Greater than Zero

If `InitialLOBFetchSize` is set to a value greater than 0, ODP.NET caches LOB data up to `InitialLOBFetchSize` characters or bytes for each LOB selected during the `Read` method invocations on the `OracleDataReader` object. The maximum value is 2,147,483,647 (2GB). If the total size of a selected LOB is less than this number, the entire LOB data will be read.

By pre-fetching all LOB entries in one or more database round trips, applications can perform faster by reducing round trips. This approach is most advantageous when most LOBs are either small in size, or consumed by the end user almost immediately, or both. The down side of a large fetch size is higher memory consumption.

This section discusses the ways to fetch beyond the `InitialLOBFetchSize` characters or bytes that are cached.

The remaining LOB data is returned when a typed accessor is invoked, regardless of the value set to the `InitialLOBFetchSize` property. Primary key, ROWID, or unique columns are not required to be in the query select list to obtain data beyond the specified `InitialLOBFetchSize`.

The `GetOracleBlob`, `GetOracleClob`, `GetOracleBlobForUpdate`, and `GetOracleClobForUpdate` methods can now be invoked even if `InitialLOBFetchSize` is greater than 0.

Setting InitialLOBFetchSize to -1

To fetch all LOB data selected during the read operation and not be bound by a set limit per LOB, set `InitialLOBFetchSize` to -1. A new default behavior has been introduced for ODP.NET Release 12.1.0.2 and higher when `InitialLobFetchSize` is set to -1.

When `LegacyEntireLOBFetch = 0`, which is the default value, the following operations are invoked for a LOB column:

- `OracleDataReader.GetOracleClob()`: returns `OracleClob` object
- `OracleDataReader.GetOracleBlob()` : returns `OracleBlob` object
- `OracleDataReader.GetOracleClobForUpdate()`: returns `OracleClob` object
- `OracleDataReader.GetOracleBlobForUpdate()`: returns `OracleBlob` object
- `OracleDataReader.GetOracleValue()`: returns `OracleClob` object for a CLOB column

- `OracleDataReader.GetOracleValue()`: returns `OracleBlob` object for a BLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleClob` for a CLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleBlob` for a BLOB column

To use the old behavior, set `LegacyEntireLobFetch = 1` in the ODP.NET configuration.

When `LegacyEntireLobFetch = 1` and `InitialLOBFetchSize = -1`, `GetOracleClob`, `GetOracleClobForUpdate`, `GetOracleBlob`, and `GetOracleBlobForUpdate` methods are not supported. The following operations are invoked for a LOB column in this scenario:

- `OracleDataReader.GetOracleClob()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleBlob()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleClobForUpdate()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleBlobForUpdate()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleValue()`: returns `OracleString` object for a CLOB column
- `OracleDataReader.GetOracleValue()`: returns `OracleBinary` object for a BLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleString` for a CLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleBinary` for a BLOB column

For releases prior to ODP.NET 12.1.0.2, by setting `InitialLOBFetchSize` to `-1`, it is possible to fetch the entire LOB data from the database for a select query, without requiring a primary key, ROWID, or unique column in the select list. When `InitialLOBFetchSize` is set to `-1`, the entire LOB column data is fetched and cached during the `Read` method invocations on the `OracleDataReader` object. Calls to `GetString`, `GetOracleString`, `GetChars`, `GetBytes`, or `GetOracleBinary` in the `OracleDataReader` allow retrieving all data.

Methods Supported for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1

This section lists supported and not supported methods for the CLOB and BLOB data types when the `InitialLOBFetchSize` property is set to `-1` and `LegacyEntireLobFetch` property is set to `1`.

[Table 3-16](#) lists supported and not supported methods for the CLOB data types.

Table 3-16 Supported OracleDataReader CLOB Methods for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1

OracleDataReader CLOB Methods	Supported
<code>GetChars</code>	Yes
<code>GetString</code>	Yes

Table 3-16 (Cont.) Supported OracleDataReader CLOB Methods for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1

OracleDataReader CLOB Methods	Supported
GetValue	Yes
GetValues	Yes
GetOracleString	Yes
GetOracleValue	Yes
GetOracleValues	Yes
GetOracleClob	No
GetOracleClobForUpdate	No

[Table 3-17](#) lists supported and not supported methods for the BLOB data types.

Table 3-17 Supported OracleDataReader BLOB Methods for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1

OracleDataReader BLOB Methods	Supported
GetBytes	Yes
GetValue	Yes
GetValues	Yes
GetOracleBinary	Yes
GetOracleValue	Yes
GetOracleValues	Yes
GetOracleBlob	No
GetOracleBlobForUpdate	No

Performance Considerations Related to the InitialLOBFetchSize Property

This section discusses the advantages and disadvantages of the various `InitialLOBFetchSize` property settings in different situations.

An application does not have to choose between performance and `OracleBlob` and `OracleClob` functionality. Setting the `InitialLOBFetchSize` property results in a performance boost and still gives the flexibility to use the `OracleBlob` and `OracleClob` objects.

If the size of the LOB data is unknown or if the LOB data size varies irregularly, then it is better to leave the `InitialLOBFetchSize` property to its default value of 0. This still gives better performance in most cases.

Setting the `InitialLOBFetchSize` property to a size equal to or greater than the LOB data size for most rows improves performance. It is generally recommended that the `InitialLOBFetchSize` property be set to a value larger than the size of the LOB data for more than 80% of the rows returned by the query. For example, if the size of the

LOB data is less than 1 KB in 80% of the rows, and more than 1 MB for 20% of the rows, set the `InitialLOBFetchSize` property to 1 KB.



See Also:

- ["LOB Support"](#)
- ["InitialLOBFetchSize"](#)
- ["InitialLONGFetchSize"](#)

Controlling the Number of Rows Fetched in One Database Round-Trip

Application performance depends on the number of rows the application needs to fetch, and the number of database round-trips that are needed to retrieve them.

Use of FetchSize

The `FetchSize` property represents the total memory size in bytes that ODP.NET allocates to cache the data fetched from a database round-trip.

The `FetchSize` property can be set on the `OracleCommand`, `OracleDataReader`, or `OracleRefCursor` object, depending on the situation. It controls the fetch size for filling a `DataSet` or `DataTable` using an `OracleDataAdapter`.

If the `FetchSize` property is set on the `OracleCommand` object, then the newly created `OracleDataReader` object inherits the `FetchSize` property of the `OracleCommand` object. This inherited `FetchSize` value can be left as is, or modified to override the inherited value. The `FetchSize` property of the `OracleDataReader` object can be changed before the first `Read` method invocation, which allocates memory specified by the `FetchSize` property. All subsequent fetches from the database use the same cache allocated for that `OracleDataReader` object. Therefore, changing the `FetchSize` value after the first `Read` method invocation has no effect.

Fine-Tuning FetchSize

By fine-tuning the `FetchSize` property, applications can control memory usage and the number of rows fetched in one database round-trip for better performance.

For example, if a query returns 100 rows and each row takes 1024 bytes, then setting the `FetchSize` property to 102400 takes just one database round-trip to fetch 100 rows. For the same query, if the `FetchSize` property is set to 10240, it takes 10 database round-trips to retrieve 100 rows. If the application requires all the rows to be fetched from the result set, the first scenario is faster than the second. However, if the application requires just the first 10 rows from the result set, the second scenario can perform better because it fetches only 10 rows, not 100 rows. When the next 10 rows are fetched, then the memory allocated for rows 1-10 is reused for rows 11-20.

The larger the `FetchSize`, the more system memory is used. Developers should not set large fetch sizes if their client systems have limited memory resources.

Using the RowSize Property

The `RowSize` property of the `OracleCommand` or `OracleRefCursor` object is populated with the row size (in bytes) after an execution of a `SELECT` statement. The `FetchSize` property can then be set to a value relative to the `RowSize` property by setting it to the result of multiplying the `RowSize` value times the number of rows to fetch for each database round-trip.

For example, setting the `FetchSize` to `RowSize * 10` forces the `OracleDataReader` object to fetch exactly 10 rows for each database round-trip. Note that the `RowSize` value does not change due to the data length in each individual column. Instead, the `RowSize` value is determined strictly from the metadata information of the database table(s) that the `SELECT` statement is executed against.

The `RowSize` property can be used to set the `FetchSize` property at design time or at run time, as described in the following sections.

Setting FetchSize Value in the Registry

The `HKLM\Software\Oracle\ODP.NET\ version\FetchSize` registry entry can be set to specify the default result set fetch size (in bytes) for all applications that use that particular version of ODP.NET or the `FetchSize` attribute in the application configuration or `web.config` file can specify the default value for a given application. By default, the fetch size is 131072 bytes. This value can be overridden programmatically by having the applications set the `FetchSize` property on either the `OracleCommand` or the `OracleDataReader` at run time.

Setting FetchSize Value at Design Time

If the row size for a particular `SELECT` statement is already known from a previous execution, the `FetchSize` value of the `OracleCommand` object can be set at design time to the result of multiplying that row size times the number of rows the application wishes to fetch for each database round-trip. The `FetchSize` value set on the `OracleCommand` object is inherited by the `OracleDataReader` object that is created by the `ExecuteReader` method invocation on the `OracleCommand` object. Rather than setting the `FetchSize` value on the `OracleCommand` object, the `FetchSize` value can also be set on the `OracleDataReader` object directly. In either case, the `FetchSize` value is set at design time, without accessing the `RowSize` property value at run time.

Setting FetchSize Value at Run Time

Applications that do not know the row size at design time can use the `RowSize` property of the `OracleCommand` object to set the `FetchSize` property of the `OracleDataReader` object. The `RowSize` property provides a dynamic way of setting the `FetchSize` property based on the size of a row.

After an `OracleDataReader` object is obtained by invoking the `ExecuteReader` method on the `OracleCommand` object, the `RowSize` property is populated with the size of the row (in bytes). By using the `RowSize` property, the application can dynamically set the `FetchSize` property of the `OracleDataReader` object to the product of the `RowSize` property value multiplied by the number of rows the application wishes to fetch for each database round-trip. In this scenario, the `FetchSize` property is set by accessing the `RowSize` property at run time.

PL/SQL REF CURSOR and OracleRefCursor

The `REF CURSOR` is a data type in the Oracle PL/SQL language. It represents a cursor or a result set in Oracle Database. The `OracleRefCursor` object is a corresponding ODP.NET type for the `REF CURSOR` type.

This section discusses the following aspects of using the `REF CURSOR` data type and `OracleRefCursor` objects:

- [Obtaining an OracleRefCursor Object](#)
- [Obtaining a REF CURSOR Data Type](#)
- [Populating an OracleDataReader from a REF CURSOR](#)
- [Populating the DataSet from a REF CURSOR](#)
- [Populating an OracleRefCursor from a REF CURSOR](#)
- [Updating a DataSet Obtained from a REF CURSOR](#)
- [Behavior of ExecuteScalar Method for REF CURSOR](#)
- [Passing a REF CURSOR to a Stored Procedure](#)

Obtaining an OracleRefCursor Object

There are no constructors for `OracleRefCursor` objects. They can be acquired only as parameter values from PL/SQL stored procedures, stored functions, or anonymous blocks.

An `OracleRefCursor` object is a connected object. The connection used to execute the command returning an `OracleRefCursor` object is required for its lifetime. Once the connection associated with an `OracleRefCursor` object is closed, the `OracleRefCursor` object cannot be used.

Obtaining a REF CURSOR Data Type

A `REF CURSOR` data type can be obtained as an `OracleDataReader`, `DataSet`, or `OracleRefCursor` object. If the `REF CURSOR` data type is obtained as an `OracleRefCursor` object, it can be used to create an `OracleDataReader` object or populate a `DataSet` from it. When accessing a `REF CURSOR` data type, always bind it as an `OracleDbType.RefCursor` parameter.

Populating an OracleDataReader from a REF CURSOR

A `REF CURSOR` data type can be obtained as an `OracleDataReader` object by calling the `ExecuteReader` method of the `OracleCommand` object. The output parameter with the `OracleDbType` property set is bound to `OracleDbType.RefCursor`. None of the output parameters of type `OracleDbType.RefCursor` is populated after the `ExecuteReader` method is invoked.

If there are multiple output `REF CURSOR` parameters, use the `NextResult` method of the `OracleDataReader` object to access the next `REF CURSOR` data type. The `OracleDataReader.NextResult` method provides sequential access to the `REF CURSOR` data types; only one `REF CURSOR` data type can be accessed at a given time.

The order in which `OracleDataReader` objects are created for the corresponding `REF CURSOR` data types depends on the order in which the parameters are bound. If a PL/SQL stored function returns a `REF CURSOR` data type, then it becomes the first `OracleDataReader` object and all the output `REF CURSOR` data types follow the order in which the parameters are bound.

Populating the DataSet from a REF CURSOR

For the `Fill` method to populate the `DataSet` properly, the `SelectCommand` property of the `OracleDataAdapter` class must be bound with an output parameter of type `OracleDbType.RefCursor`. If the `Fill` method is successful, the `DataSet` is populated with a `DataTable` that represents a `REF CURSOR` data type.

If the command execution returns multiple `REF CURSOR` data types, the `DataSet` is populated with multiple `DataTable` objects.

With Oracle Data Provider for .NET release 11.1.0.6.20, the extended property, `RefCursorName`, has been introduced on the `DataTable`, to identify the `REF CURSOR` that populates the `DataTable`.

This property is particularly useful when a `DataSet` is being populated with more than one `REF CURSOR`, one or more of which is `NULL`. For example, if a `DataSet` is populated by executing a stored procedure that returns three `REF CURSOR`s and the second `REF CURSOR` is `NULL`, the `RefCursorName` property value for the first `DataTable` is `RefCursor` and for the second `DataTable`, `RefCursor2`. No `DataTable` is populated for the `NULL REF CURSOR`.

Populating an OracleRefCursor from a REF CURSOR

When the `ExecuteNonQuery` method is invoked on a command that returns one or more `REF CURSOR` data types, each of the `OracleCommand` parameters that are bound as an `OracleDbType.RefCursor` gets a reference to an `OracleRefCursor` object.

To create an `OracleDataReader` object from an `OracleRefCursor` object, invoke the `GetDataReader` method from the `OracleRefCursor` object. Subsequent calls to the `GetDataReader` method return a reference to the same `OracleDataReader` object.

To populate a `DataSet` with an `OracleRefCursor` object, the application can invoke a `Fill` method of the `OracleDataAdapter` class that takes an `OracleRefCursor` object. Similar to the `OracleDataReader` object, an `OracleRefCursor` object is forward-only. Therefore, once a row is read from an `OracleRefCursor` object, that same row cannot be obtained again from it unless it is populated again from a query.

When multiple `REF CURSOR` data types are returned from a command execution as `OracleRefCursor` objects, the application can choose to create an `OracleDataReader` object or populate a `DataSet` with a particular `OracleRefCursor` object. All the `OracleDataReader` objects or `DataSet` objects created from the `OracleRefCursor` objects are active at the same time, and can be accessed in any order.

Updating a DataSet Obtained from a REF CURSOR

`REF CURSOR` types cannot be updated. However, data that is retrieved into a `DataSet` can be updated. Therefore, the `OracleDataAdapter` class requires a custom SQL statement to flush any `REF CURSOR` data updates to the database.

The `OracleCommandBuilder` object cannot be used to generate SQL statements for REF CURSOR updates.

Behavior of ExecuteScalar Method for REF CURSOR

The `ExecuteScalar` method returns the value of the first column of the first row of the REF CURSOR if it is one of the following:

- A return value of a stored function execution
- The first bind parameter of a stored procedure execution

See Also:

Oracle Database SecureFiles and Large Objects Developer's Guide for more information

Passing a REF CURSOR to a Stored Procedure

An application can retrieve a REF CURSOR type from a PL/SQL stored procedure or function and pass it to another stored procedure or function. This feature is useful in scenarios where a stored procedure or a function returns a REF CURSOR type to the .NET application, and based on the application logic, the application passes this REF CURSOR to another stored procedure for processing. Note that if you retrieve the data from a REF CURSOR type in the .NET application, you cannot pass it back to another stored procedure.

The following example demonstrate passing a REF CURSOR:

```
/*
connect scott/tiger@oracle
create table test (coll number);
insert into test(coll) values (1);
commit;

create or replace package testPkg as type empCur is REF Cursor;
end testPkg;
/

create or replace procedure testSP(param1 IN testPkg.empCur, param2 OUT NUMBER)
as
begin
FETCH param1 into param2;
end;
/
*/

// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;

class InRefCursorParameterSample
```

```
{
    static void Main()
    {
        OracleConnection conn = new OracleConnection
            ("User Id=scott; Password=tiger; Data Source=oracle");

        conn.Open(); // Open the connection to the database

        // Command text for getting the REF Cursor as OUT parameter
        String cmdTxt1 = "begin open :1 for select coll from test; end;";

        // Command text to pass the REF Cursor as IN parameter
        String cmdTxt2 = "begin testSP (:1, :2); end;";

        // Create the command object for executing cmdTxt1 and cmdTxt2
        OracleCommand cmd = new OracleCommand(cmdTxt1, conn);

        // Bind the Ref cursor to the PL/SQL stored procedure
        OracleParameter outRefPrm = cmd.Parameters.Add("outRefPrm",
            OracleDbType.RefCursor, DBNull.Value, ParameterDirection.Output);

        cmd.ExecuteNonQuery(); // Execute the anonymous PL/SQL block

        // Reset the command object to execute another anonymous PL/SQL block
        cmd.Parameters.Clear();
        cmd.CommandText = cmdTxt2;

        // REF Cursor obtained from previous execution is passed to this
        // procedure as IN parameter
        OracleParameter inRefPrm = cmd.Parameters.Add("inRefPrm",
            OracleDbType.RefCursor, outRefPrm.Value, ParameterDirection.Input);

        // Bind another Number parameter to get the REF Cursor column value
        OracleParameter outNumPrm = cmd.Parameters.Add("outNumPrm",
            OracleDbType.Int32, DBNull.Value, ParameterDirection.Output);

        cmd.ExecuteNonQuery(); //Execute the stored procedure

        // Display the out parameter value
        Console.WriteLine("out parameter is: " + outNumPrm.Value.ToString());
    }
}
```

Implicit REF CURSOR Binding

ODP.NET enables applications to run stored procedures with REF CURSOR parameters without using explicit binding for these parameters in the .NET code. ODP.NET unmanaged and managed drivers support REF CURSOR implicit binding through configuration done in .NET configuration files.

For a read-only result set, such as a REF CURSOR using `OracleDataReader`, REF CURSOR schema information is retrieved automatically.

For some scenarios, such as when updateable REF CURSORS or Entity Framework is used, developers need to define the REF CURSOR schema information so that the application can bind the implicit REF CURSOR. Entity Framework applications use implicit REF CURSOR binding to instantiate complex types from REF CURSOR data. Applications must specify REF CURSOR bind and metadata information in the `app.config`, `web.config`, or `machine.config` .NET configuration file.

The attributes supplied in the .NET configuration file are also used when the application requests for schema information from the `OracleDataReader` object that represents a `REF CURSOR`. This means that for `REF CURSOR`s that are created using a `SELECT` from a single table, the application can update that table through the use of `OracleDataAdapter` and `OracleCommandBuilder`.

When using the Entity Framework, function imports can return an implicitly-bound `REF CURSOR`. The `REF CURSOR` can be returned as a collection of complex types or entity types. To return a complex type collection, the .NET configuration file needs to define the `REF CURSOR` bind and metadata information. To return an entity type collection, only the bind information needs to be defined in the .NET configuration file.

This section contains the following topics:

- [Specifying REF CURSOR Bind and Metadata Information in the .NET Configuration File](#)
- [Sample Configuration File and Application](#)
- [Usage Considerations](#)

Specifying REF CURSOR Bind and Metadata Information in the .NET Configuration File

Specify the `REF CURSOR` information in the `oracle.dataaccess.client` configuration section of the .NET configuration file. Use an `<add>` element for each piece of information. The `add` element uses `name-value` attributes to specify `REF CURSOR` information. Use the following format to specify bind information:

```
<add
name="SchemaName.PackageName.StoredProcedureName.RefCursor.RefCursorParameterPosition
OrName"
value="implicitRefCursor bindinfo='mode=InputOutput|Output|ReturnValue' " />
```

Use the following format to specify metadata information:

```
<add
name="SchemaName.PackageName.StoredProcedureName.RefCursorMetaData.RefCursorParameter
PositionOrName.Column.ColumnOrdinal"
value="implicitRefCursor metadata=AttributesList" />
```

Each `REF CURSOR` column needs to have an `add` element defined for it. For example, if you have a `REF CURSOR` returning five columns, then you need to define five `add` elements in the config file.

Each `add` element contains the `name` and `value` attributes. The `value` attribute must begin with the word `implicitRefCursor` followed by the `bindinfo` or `metadata` attribute for specifying bind or metadata information.

The `bindinfo` information is used by ODP.NET for binding `REF CURSOR` parameters. The `metadata` information is used by ODP.NET to associate the schema information with the appropriate `REF CURSOR`. The `metadata` comprises of an attributes list that includes parameters together with their values.

The `SchemaName`, `PackageName`, and `StoredProcedureName` are case-sensitive. In order to run a stored procedure with implicit `REF CURSOR` binding, the `SchemaName.PackageName.StoredProcedureName` portion of the `name` attribute must exactly match the name specified in the data dictionary for that stored procedure.

 **Note:**

If the application uses implicit REF CURSOR binding feature outside of Entity Framework, then the .NET configuration file and `OracleCommand.CommandText` do not require the schema name concatenated before the stored procedure name.

If any schema, package, or stored procedure name in the database contains lowercase characters, then it must be enclosed within double quotation marks (") in the config file to preserve the case. Double quotation marks are used within the `name` attribute by using `"` when needed. For example, if the schema name is `HrSchema`, the package name is `HrPackage`, and the stored procedure name is `HrStoredProcedure` in the database, the config file should use the following:

```
<add
name="&quot;HrSchema&quot;.&quot;HrPackage&quot;.&quot;HrStoredProcedure&quot;.RefCursorMetaData . . . />
```

By default, Oracle Database stores these names as uppercase characters. ODP.NET assumes default behavior, and converts all names to uppercase characters unless you explicitly preserve the case by using double quotation marks.

 **Note:**

The *SchemaName*, *PackageName*, *StoredProcedureName*, or *ParameterName* cannot contain a period (".") in the name. For example, `P.0` is an unacceptable parameter name.

Depending on whether the application uses bind-by-name or bind-by-position, the *RefCursorParameterPositionOrName* portion of the name attribute must be set with the correct parameter position (for bind by position) or parameter name (for bind by name). For functions, the position is 0-based, where the position 0 represents the return value. For procedures, the position is 1-based, as there are no return values for procedures. For example, if a stored procedure accepts five parameters, returning only two REF CURSORS in the third and fifth parameter positions, then the .NET config REF CURSOR bind information should contain one entry for position 3 and one entry for position 5.

If bind-by-name is used, the attribute name is used to identify the REF CURSOR parameter. The `name` should use the same name and case as the one specified in the data dictionary for that stored procedure.

For `bindinfo`, the `mode` specifies the parameter direction of the parameter. The `mode` must be either `InputOutput`, `Output`, or `ReturnValue`.

 **Note:**

Implicit REF CURSOR binding for an input REF CURSOR parameter is not supported.

An exception is thrown at runtime if the .NET configuration file contains an entry for a REF CURSOR whose mode is set to Input.

For metadata, The *AttributesList* contains the list of parameters. [Table 3-18](#) describes the parameters that can be included in the *AttributesList*.

[Example 3-5](#) shows a sample add element that uses *bindinfo*. Here, the schema name is SCOTT and the stored procedure name is TESTPROC. The parameter name is parameter1. The mode is output.

[Example 3-6](#) shows a sample add element that uses *metadata*.

Table 3-18 Allowed Parameters in Attributes List

Name	Type	Required/Optional for Entity Framework	Description
ColumnName	System.String	Required	The name of the column.
ProviderType	Oracle.DataAccess.Client.OracleDbType	Required	The database column type (OracleDbType) of the column
NativeDataType	System.String	Required	The Oracle type. For example, NCLOB.
BaseColumnName	System.String	Optional	The name of the column in the database if an alias is used for the column.
BaseSchemaName	System.String	Optional	The name of the schema in the database that contains the column.
BaseTableName	System.String	Optional	The name of the table or view in the database that contains the column.
ColumnSize	System.Int64	Optional	The maximum possible length of a value in the column
NumericPrecision	System.Int16	Optional	The maximum precision of the column, if the column is a numeric data type.
NumericScale	System.Int16	Optional	The maximum scale of the column, if the column is a numeric data type.
IsUnique	System.Boolean	Optional	Indicates whether or not the column is unique.

Table 3-18 (Cont.) Allowed Parameters in Attributes List

Name	Type	Required/Optional for Entity Framework	Description
IsKey	System.Boolean	Optional	Indicates whether or not the column is a key column. For a table to be updated with the REF CURSOR information, at least one of the columns in the REF CURSOR metadata should have this value set to true
IsRowID	System.Boolean	Optional	true if the column is a ROWID, otherwise false.
DataType	System.RuntimeType	Optional	Maps to the common language runtime type.
AllowDBNull	System.Boolean	Optional	true if null values are allowed, otherwise false
IsAliased	System.Boolean	Optional	true if the column is an alias; otherwise false.
IsByteSemantic	System.Boolean	Optional	IsByteSemantic is: <ul style="list-style-type: none"> true if the ColumnSize value uses bytes semantics false if ColumnSize uses character semantics
IsExpression	System.Boolean	Optional	true if the column is an expression, else false.
IsHidden	System.Boolean	Optional	true if the column is hidden, else false.
IsReadOnly	System.Boolean	Optional	true if the column is read-only, else false
IsLong	System.Boolean	Optional	true if the column is of LONG, LONG RAW, BLOB, CLOB, or BFILE type, else false.
UdtTypeName	System.String	Optional	The type name of the UDT.
ProviderDbType	System.Data.DbType	Optional	System.Data.DbType
ObjectName	System.String	Optional	Represents the name of the object.

Some of the attributes, listed in [Table 3-18](#), automatically have their values set using the result set's metadata. Developers can override these default values by setting a value explicitly.

You may have to explicitly define some attributes listed as optional for certain operations. For example, updateable REF CURSOR requires the developer to define key information.

Example 3-5 Using the add Element with bindinfo

```
<add name="SCOTT.TESTPROC.RefCursor.parameter1" value="implicitRefCursor
  bindinfo='mode=Output'" />
```

Example 3-6 Using the add Element with metadata

```
<add name="scott.TestProc.RefCursorMetaData.parameter1.Column.0"
value="implicitRefCursor metadata='ColumnName=EMPNO;BaseColumnName=EMPNO;
BaseSchemaName=SCOTT;BaseTableName=EMP;NativeDataType=number;
ProviderType=Int32;DataType=System.Int32;ColumnSize=4;AllowDBNull=false;
IsKey=true'" />
```

Sample Configuration File and Application

This section builds a sample application to illustrate implicit REF CURSOR binding. It contains the following topics:

- [Sample Stored Procedure and Function](#)
- [Sample Application Configuration File](#)
- [Sample Application That Uses the Configuration File](#)

Sample Stored Procedure and Function

```
CREATE OR REPLACE FUNCTION GETEMP (
  EMPID IN NUMBER) return sys_refcursor is
  emp sys_refcursor;
BEGIN
  OPEN emp FOR SELECT empno, ename FROM emp where empno = EMPID;
  return emp;
END;
/

CREATE OR REPLACE PROCEDURE "GetEmpAndDept" (
  EMPS OUT sys_refcursor,
  DEPTS OUT sys_refcursor) AS
BEGIN
  OPEN EMPS for SELECT empno, ename from emp;
  OPEN DEPTS for SELECT deptno, dname from dept;
END;
/
```

Sample Application Configuration File

```
<?xml version="1.0" encoding="utf-8"?>
<configuration>
  <oracle.dataaccess.client>
    <settings>

      <!-- The following is for SCOTT.GETEMP -->
      <add name="SCOTT.GETEMP.RefCursor.0"
        value="implicitRefCursor bindinfo='mode=ReturnValue'" />

      <!-- The following is for SCOTT.GETEMP's REF CURSOR metadata -->
      <add name="SCOTT.GETEMP.RefCursorMetaData.0.Column.0"
        value="implicitRefCursor metadata='ColumnName=EMPNO;
        BaseColumnName=EMPNO;BaseSchemaName=SCOTT;BaseTableName=EMP;
        NativeDataType=number;ProviderType=Int32;ProviderDbType=Int32;
        DataType=System.Int32;ColumnSize=4;NumericPrecision=10;
```

```

        NumericScale=3;AllowDBNull=false;IsKey=true' " />

<add name="SCOTT.GETEMP.RefCursorMetaData.0.Column.1"
    value="implicitRefCursor metadata='ColumnName=ENAME;
    BaseColumnName=ENAME;BaseSchemaName=SCOTT;BaseTableName=EMP;
    NativeDataType=varchar2;ProviderType=Varchar2;
    ProviderDbType=String;DataType=System.String;
    ColumnSize=10;AllowDBNull=true' " />

<!-- The following is for "SCOTT"."GetEmpAndDept" -->
<add name="SCOTT.&quot;GetEmpAndDept&quot;.RefCursor.EMPS"
    value="implicitRefCursor bindinfo='mode=Output' " />

<!-- The following is for SCOTT.GETEMP's EMPS REF CURSOR metadata -->
<add name="SCOTT.&quot;GetEmpAndDept&quot;.
    .RefCursorMetaData.EMPS.Column.0"
    value="implicitRefCursor metadata='ColumnName=EMPNO;
    BaseColumnName=EMPNO;BaseSchemaName=SCOTT;BaseTableName=EMP;
    NativeDataType=number;ProviderType=Int32;ProviderDbType=Int32;
    DataType=System.Int32;ColumnSize=4;NumericPrecision=10;
    NumericScale=3;AllowDBNull=false;IsKey=true' " />

<add name="SCOTT.&quot;GetEmpAndDept&quot;.
    .RefCursorMetaData.EMPS.Column.1"
    value="implicitRefCursor metadata='ColumnName=ENAME;
    BaseColumnName=ENAME;BaseSchemaName=SCOTT;BaseTableName=EMP;
    NativeDataType=varchar2;ProviderType=Varchar2;
    ProviderDbType=String;DataType=System.String;
    ColumnSize=10;AllowDBNull=true' " />

<!-- The following is for SCOTT.GETEMP's DEPTS REF CURSOR metadata -->
<add name="SCOTT.&quot;GetEmpAndDept&quot;.RefCursor.DEPTS"
    value="implicitRefCursor bindinfo='mode=Output' " />

<add name="SCOTT.&quot;GetEmpAndDept&quot;.
    .RefCursorMetaData.DEPTS.Column.0"
    value="implicitRefCursor metadata='ColumnName=DEPTNO;
    BaseColumnName=DEPTNO;BaseSchemaName=SCOTT;BaseTableName=DEPT;
    NativeDataType=number;ProviderType=Int32;ProviderDbType=Int32;
    DataType=System.Int32;ColumnSize=4;NumericPrecision=10;
    NumericScale=3;AllowDBNull=false;IsKey=true' " />

<add name="SCOTT.&quot;GetEmpAndDept&quot;.
    .RefCursorMetaData.DEPTS.Column.1"
    value="implicitRefCursor metadata='ColumnName=DNAME;
    BaseColumnName=DNAME;BaseSchemaName=SCOTT;BaseTableName=DEPT;
    NativeDataType=varchar2;ProviderType=Varchar2;
    ProviderDbType=String;DataType=System.String;
    ColumnSize=10;AllowDBNull=true' " />
</settings>
</oracle.dataaccess.client>
</configuration>

```

Sample Application That Uses the Configuration File

```

using System;
using System.Data;
using Oracle.DataAccess.Client;

class Program
{

```

```
static void Main(string[] args)
{
    try
    {
        // Open a connection
        string constr =
            "User Id=scott;Password=tiger;Data Source=inst1";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Use implicit REF CURSOR binding
        // to execute SCOTT.GETEMP function
        // Use bind by position as configured
        // in app.config for SCOT.GETEMP
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "SCOTT.GETEMP";
        cmd.CommandType = CommandType.StoredProcedure;
        cmd.BindByName = false;
        OracleParameter empid = cmd.Parameters.Add("empid",
            OracleDbType.Int32, ParameterDirection.Input);
        empid.Value = 7654;

        // Populate the DataSet
        OracleDataAdapter adapter = new OracleDataAdapter(cmd);
        DataSet ds = new DataSet();
        adapter.Fill(ds);
        Console.WriteLine("Retrieved {0} row from EMP",
            ds.Tables[0].Rows.Count);

        // Use implicit REF CURSOR binding
        // to execute "SCOTT"."GetEmpAndDept" procedure
        // Use bind by name as configured
        // in app.config for "SCOTT"."GetEmpAndDept"
        cmd = con.CreateCommand();
        cmd.CommandText = "\"SCOTT\".\"GetEmpAndDept\"";
        cmd.CommandType = CommandType.StoredProcedure;
        cmd.BindByName = true;
        adapter = new OracleDataAdapter(cmd);
        adapter.Fill(ds);
        Console.WriteLine("Retrieved {0} rows from DEPT",
            ds.Tables[1].Rows.Count);
    }
    catch (Exception ex)
    {
        // Output the message
        Console.WriteLine(ex.Message);
        if (ex.InnerException != null)
        {
            // If any details are available regarding
            // errors in the app.config, print them out
            Console.WriteLine(ex.InnerException.Message);
            if (ex.InnerException.InnerException != null)
            {
                Console.WriteLine(
                    ex.InnerException.InnerException.Message);
            }
        }
    }
}
```

Usage Considerations

This section discusses the following usage considerations when using implicit REF CURSOR:

- [CommandText Property Considerations](#)
- [Bind Considerations](#)
- [Overloaded Stored Procedures](#)
- [Type Initialization Exceptions](#)
- [Using Stored Functions with Function Import](#)

CommandText Property Considerations

ODP.NET applications should ensure that the stored procedure name and the `OracleCommand.CommandText` match exactly. Let's take a scenario where the stored procedure name in the database is `SCOTT.TESTPROC`. Now, if the `CommandText` uses `TESTPROC`, ODP.NET will look for entries matching `TESTPROC` only. The current schema name will not be automatically appended to `TESTPROC`. So, the correct `CommandText` to use in this scenario would be `SCOTT.TESTPROC`.

Also, the `CommandText` is case-sensitive and must use the same case as the stored procedure name in the database. So if the stored procedure name in the database is `SCOTT.Testproc`, then the `CommandText` must use `SCOTT.Testproc`.

Bind Considerations

If information about a REF CURSOR parameter has been added to the configuration file, then applications should not try to explicitly bind the REF CURSOR parameter to `OracleCommand`. ODP.NET automatically binds the REF CURSOR parameter at the appropriate locations based on the information provided in the configuration file. If the application stored procedure also has non-REF CURSOR parameters, then these parameters must still be explicitly bound to `OracleCommand`.

If the information specified in the configuration file for a stored procedure identifies the REF CURSOR parameter by name, then all the other non-REF CURSOR parameters should also be bound by name. Also the `BindByName` property for the `OracleCommand` object should be set to `true` in this case. Entity Framework always uses `BindByName` to run stored procedures. Your .NET configuration file parameter names must use the same case that was used when creating the stored procedure in the database.

If the `OracleCommand.BindByName` property is set to `false` (default), then ODP.NET assumes that the parameters have been bound based on their position, and all parameters have been specified in the correct order. For such cases, the parameters specified in the configuration file are bound in the same order in which they appear in the configuration file.

Overloaded Stored Procedures

ODP.NET does not support multiple stored procedures with the same name inside the configuration file. If an ODP.NET application uses an overloaded stored procedure, the application can store only one overloaded stored procedure information in the configuration file.

Type Initialization Exceptions

Type initialization exceptions can be caused by invalid .NET configuration file entries. Evaluate the exception that is caught as well as its inner exceptions to determine the .NET configuration file entry or the attribute setting that is causing the exception.

ODP.NET tracing logs the valid and invalid .NET configuration file entries that ODP.NET has parsed. To look for .NET configuration file related entries, set the `TraceLevel` to the *Entry, exit, and SQL statement information* level setting. Trace entries related to implicit `REF CURSOR` binding have a `(REFCURSOR)` entry along with `(ERROR)`, if any errors are encountered.

Using Stored Functions with Function Import

Function Import only supports stored procedures, and does not support functions. When using the **Add Function Import** dialog for the Entity Data Model that you have created, the **Get Column Information** button does not return the metadata information for the `REF CURSOR` that is being returned by a stored function, even if it is configured properly in the .NET configuration file.

LOB Support

ODP.NET provides an easy and optimal way to access and manipulate large object (LOB) data types.



Note:

SecureFiles can be used with existing ODP.NET LOB classes.

This section includes the following topics:

- [Large Character and Large Binary Data Types](#)
- [Oracle Data Provider for .NET LOB Objects](#)
- [Updating LOBs Using a DataSet](#)
- [Updating LOBs Using OracleCommand and OracleParameter](#)
- [Updating LOBs Using ODP.NET LOB Objects](#)
- [Temporary LOBs](#)

Large Character and Large Binary Data Types

Oracle Database supports large character and large binary data types.

Large Character Data Types

- `CLOB` - Character data can store up to 4 gigabytes.
- `NCLOB` - Unicode National character set data can store up to 4 gigabytes.

Large Binary Data Types

- `BLOB` - Unstructured binary data can store up to 4 gigabytes.
- `BFILE` - Binary data stored in external file can store up to 4 gigabytes.

Note:

`LONG` and `LONG RAW` data types are made available for backward compatibility in Oracle9i, but should not be used in new applications.

Oracle Data Provider for .NET LOB Objects

ODP.NET provides three objects for manipulating LOB data: `OracleBFile`, `OracleBlob`, and `OracleClob`.

Table 3-19 shows the proper ODP.NET object to use for a particular Oracle LOB type.

Table 3-19 ODP.NET LOB Objects

Oracle LOB Type	ODP.NET LOB Object
<code>BFILE</code>	<code>OracleBFile</code>
<code>BLOB</code>	<code>OracleBlob</code>
<code>CLOB</code>	<code>OracleClob</code>
<code>NCLOB</code>	<code>OracleClob</code>

The ODP.NET LOB objects can be obtained by calling the proper typed accessor on the `OracleDataReader` object, or by calling the proper typed accessor as an output parameter on a command execution with the proper bind type.

All ODP.NET LOB objects inherit from the .NET `Stream` class to provide generic `Stream` operations. The LOB data (except for `BFILE` types) can be updated using the ODP.NET LOB objects by using methods such as `Write`. Data is not cached in the LOB objects when read and write operations are carried out. Therefore, each read or write request incurs a database round-trip. The `OracleClob` object overloads the `Read` method, providing two ways to read data from a `CLOB`. The `Read` method that takes a `byte[]` as the buffer populates it with `CLOB` data as Unicode byte array. The `Read` method that takes a `char[]` as the buffer populates it with Unicode characters.

Additional methods can also be found on the `OracleBFile` object. An `OracleBFile` object must be explicitly opened using the `OpenFile` method before any data can be read from it. To close a previously opened `BFILE`, use the `CloseFile` method.

Every ODP.NET LOB object is a connected object and requires a connection during its lifetime. If the connection associated with a LOB object is closed, then the LOB object is not usable and should be disposed of.

If an ODP.NET LOB object is obtained from an `OracleDataReader` object through a typed accessor, then its `Connection` property is set with a reference to the same `OracleConnection` object used by the `OracleDataReader` object. If a LOB object is obtained as an output parameter, then its `Connection` property is set with a reference

to the same `OracleConnection` property used by the `OracleCommand` object. If a LOB object is obtained by invoking an ODP.NET LOB object constructor to create a temporary LOB, the `Connection` property is set with a reference to the `OracleConnection` object provided in the constructor.

The ODP.NET LOB object `Connection` property is read-only and cannot be changed during its lifetime. In addition, the ODP.NET LOB types object can be used only within the context of the same `OracleConnection` referenced by the ODP.NET LOB object. For example, the ODP.NET LOB `Connection` property must reference the same connection as the `OracleCommand` object if the ODP.NET LOB object is a parameter of the `OracleCommand`. If that is not the case, ODP.NET raises an exception when the command is executed.

See Also:

Oracle Database SecureFiles and Large Objects Developer's Guide for complete information about Oracle Database 10g LOBs and how to use them

Updating LOBs Using a DataSet

`BFILE` and `BLOB` data are stored in the `DataSet` as byte arrays while `CLOB` and `NCLOB` data are stored as strings. In a similar manner to other types, an `OracleDataAdapter` object can be used to fill and update LOB data changes along with the use of the `OracleCommandBuilder` object for automatically generating SQL.

Note that an Oracle LOB column can store up to 4 GB of data. When the LOB data is fetched into the `DataSet`, the actual amount of LOB data the `DataSet` can hold for a LOB column is limited to the maximum size of a .NET string type, which is 2 GB. Therefore, when fetching LOB data that is greater than 2 GB, ODP.NET LOB objects must be used to avoid any data loss.

Updating LOBs Using OracleCommand and OracleParameter

To update LOB columns, LOB data can be bound as a parameter for SQL statements, anonymous PL/SQL blocks, or stored procedures. The parameter value can be set as a .NET Framework type, ODP.NET type, or as an ODP.NET LOB object type. For example, when inserting .NET string data into a LOB column in an Oracle9i database or later, that parameter can be bound as `OracleDbType.Varchar2`. For a parameter whose value is set to an `OracleClob` object, the parameter should be bound as `OracleDbType.Clob`.

Updating LOBs Using ODP.NET LOB Objects

Oracle `BFILES` cannot be updated; therefore, `OracleBFile` objects do not allow updates to `BFILE` columns.

Two requirements must be met to update LOB data using ODP.NET LOB objects:

1. A transaction must be started before a LOB column is selected.

The transaction must be started using the `BeginTransaction` method on the `OracleConnection` object before the command execution, so that the lock can be released when the `OracleTransaction.Commit` or `Rollback` method is invoked.

2. The row in which the LOB column resides must be locked; as part of an entire result set, or on a row-by-row basis.
 - a. Locking the entire result set

Add the `FOR UPDATE` clause to the end of the `SELECT` statement. After execution of the command, the entire result set is locked.
 - b. Locking the row - there are two options:
 - Invoke one of the `OracleDataReader` typed accessors (`GetOracleClobForUpdate` or `GetOracleBlobForUpdate`) on the `OracleDataReader` object to obtain an ODP.NET LOB object, while also locking the current row.

This approach requires a primary key, unique column(s), or a `ROWID` in the result set because the `OracleDataReader` object must uniquely identify the row to re-select it for locking.
 - Execute an `INSERT` or an `UPDATE` statement that returns a LOB in the `RETURNING` clause.

Temporary LOBs

Temporary LOBs can be instantiated for `BLOB`, `CLOB`, and `NCLOB` objects. To instantiate an ODP.NET LOB object that represents a temporary LOB, the `OracleClob` or the `OracleBlob` constructor can be used.

Temporary ODP.NET LOB objects can be used for the following purposes:

- To initialize and populate a LOB column with empty or non-empty LOB data.
- To pass a LOB type as an input parameter to a SQL statement, an anonymous PL/SQL block, or a stored procedure.
- To act as the source or the destination of data transfer between two LOB objects as in the `CopyTo` operation.

Note:

Temporary LOBs are not transaction aware. Commit and rollback operations do not affect the data referenced by a temporary LOB.

ODP.NET XML Support

ODP.NET allows the extraction of data from relational and object-relational tables and views as XML documents. The use of XML documents for insert, update, and delete operations to the database is also allowed. Oracle Database supports XML natively in the database, through Oracle XML DB, a distinct group of technologies related to high-performance XML storage and retrieval. Oracle XML DB is an evolution of the database that encompasses both SQL and XML data models in a highly interoperable manner, providing native XML support.

ODP.NET, Managed Driver follows XPath 1.0 specification and hence it does not support default XML namespaces. XML namespaces must be explicitly added to search or update nodes. This behavior differs from ODP.NET, Unmanaged Driver.

For samples related to ODP.NET XML support in ODAC installations done using Oracle Universal Installer, see the following directory:

```
ORACLE_BASE\ORACLE_HOME\ODACsamples
```

This section includes these topics:

- [Supported XML Features](#)
- [OracleXmlType and Connection Dependency](#)
- [Updating XMLType Data in the Database](#)
- [Updating XML Data in OracleXmlType](#)
- [Characters with Special Meaning in XML](#)
- [Retrieving Query Result Set as XML](#)
- [Data Manipulation Using XML](#)

Supported XML Features

XML support in ODP.NET provides the ability to do the following:

- Store XML data natively in the database as the Oracle database native type, `XMLType`.
- Access relational and object-relational data as XML data from an Oracle Database instance into the Microsoft .NET environment, and process the XML using the Microsoft .NET Framework.
- Save changes to the database using XML data.
- Execute XQuery statements.

For the .NET application developer, these features include the following:

- Enhancements to the `OracleCommand`, `OracleConnection`, and `OracleDataReader` classes.
- The following XML-specific classes:
 - `OracleXmlType`
`OracleXmlType` objects are used to retrieve Oracle native `XMLType` data.
 - `OracleXmlStream`
`OracleXmlStream` objects are used to retrieve XML data from `OracleXmlType` objects as a read-only .NET Stream object.
 - `OracleXmlQueryProperties`
`OracleXmlQueryProperties` objects represent the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Query`.
 - `OracleXmlSaveProperties`

`OracleXmlSaveProperties` objects represent the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.

See Also:

- ["XQuery Support"](#)
- ["OracleCommand Class"](#)
- ["OracleXmlType Class"](#)
- ["OracleXmlStream Class"](#)
- ["OracleXmlQueryProperties Class"](#)
- ["OracleXmlSaveProperties Class"](#)
- *Oracle XML DB Developer's Guide*

XQuery Support

ODP.NET supports the XQuery language through a native implementation of SQL/XML functions, `XMLQuery` and `XMLTable`. When executing XQuery statements, Oracle XML DB generally evaluates XQuery expressions by compiling them into the same underlying structures as relational queries. Queries are optimized, leveraging both relational-database and XQuery-specific optimization technologies, so that Oracle XML DB serves as a native XQuery engine. The treatment of all XQuery expressions, whether natively compiled or evaluated functionally, is transparent: programmers do not need to change their code to take advantage of XQuery optimizations.

See Also:

Oracle XML DB Developer's Guide to learn more about Oracle's XQuery support

OracleXmlType and Connection Dependency

The read-only `Connection` property of the `OracleXmlType` class holds a reference to the `OracleConnection` object used to instantiate the `OracleXmlType` class.

How the `OracleXmlType` object obtains a reference to an `OracleConnection` object depends on how the `OracleXmlType` class is instantiated:

- Instantiated from an `OracleDataReader` class using the `GetOracleXmlType`, `GetOracleValue`, or `GetOracleValues` method:

The `Connection` property is set with a reference to the same `OracleConnection` object used by the `OracleDataReader` object.

- Instantiated by invoking an `OracleXmlType` constructor with one of the parameters of type `OracleConnection`:

The `Connection` property is set with a reference to the same `OracleConnection` object provided in the constructor.

- Instantiated by invoking an `OracleXmlType(OracleClob)` constructor:

The `Connection` property is set with a reference to the `OracleConnection` object used by the `OracleClob` object.

An `OracleXmlType` object that is associated with one connection cannot be used with a different connection. For example, if an `OracleXmlType` object is obtained using `OracleConnection A`, that `OracleXmlType` object cannot be used as an input parameter of a command that uses `OracleConnection B`. By checking the `Connection` property of the `OracleXmlType` objects, the application can ensure that `OracleXmlType` objects are used only within the context of the `OracleConnection` referenced by its `connection` property. Otherwise, ODP.NET raises an exception.

Updating XMLType Data in the Database

Updating `XMLType` columns does not require a transaction. However, encapsulating the entire database update process within a transaction is highly recommended. This allows the updates to be rolled back if there are any errors.

`XMLType` columns in the database can be updated using Oracle Data Provider for .NET in a few ways:

- [Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder](#)
- [Updating with OracleCommand and OracleParameter](#)

Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder

If the `XMLType` column is fetched into the `DataSet`, the `XMLType` data is represented as a .NET String.

Modifying `XMLType` data in the `DataSet` does not require special treatment. `XMLType` data can be modified in the same way as any data that is stored in the `DataSet`. When a change is made and the `OracleDataAdapter.Update` method is invoked, the `OracleDataAdapter` object ensures that the `XMLType` data is handled properly. The `OracleDataAdapter` object uses any custom SQL `INSERT`, `UPDATE`, or `DELETE` statements that are provided. Otherwise, valid SQL statements are generated by the `OracleCommandBuilder` object as needed to flush the changes to the database.

Updating with OracleCommand and OracleParameter

The `OracleCommand` class provides a powerful way of updating `XMLType` data, especially with the use of an `OracleParameter` object. To update columns in a database table, the new value for the column can be passed as an input parameter of a command.

Input Binding

To update an `XMLType` column in the database, a SQL statement can be executed using static values. In addition, input parameters can be bound to SQL statements, anonymous PL/SQL blocks, or stored procedures to update `XMLType` columns. The parameter value can be set as .NET Framework Types, ODP.NET Types, or `OracleXmlType` objects.

While `XMLType` columns can be updated using an `OracleXmlType` object, having an instance of an `OracleXmlType` class does not guarantee that the `XMLType` column in the database can be updated.

Setting XMLType Column to NULL Value

Applications can set an `XMLType` column in the database to a `NULL` value, with or without input binding, as follows:

- Setting `NULL` values in an `XMLType` column with input binding

To set the `XMLType` column to `NULL`, the application can bind an input parameter whose value is `DBNull.Value`. This indicates to the `OracleCommand` object that a `NULL` value is to be inserted.

Passing in a null `OracleXmlType` object as an input parameter does not insert a `NULL` value into the `XMLType` column. In this case, the `OracleCommand` object raises an exception.

- Setting `NULL` Values in an `XMLType` Column without input binding

The following example demonstrates setting `NULL` values in an `XMLType` column without input binding:

```
// Create a table with an XMLType column in the database
CREATE TABLE XML_TABLE(NUM_COL number, XMLTYPE_COL xmltype);
```

An application can set a `NULL` value in the `XMLType` column by explicitly inserting a `NULL` value or by not inserting anything into that column as in the following examples:

```
insert into xml_table(xmltype_col) values(NULL);

update xml_table t set t.xmltype_col=NULL;
```

Setting XMLType Column to Empty XML Data

The `XMLType` column can be initialized with empty XML data, using a SQL statement:

```
// Create a table with an XMLType column in the database
CREATE TABLE XML_TABLE(NUM_COL number, XMLTYPE_COL xmltype);

INSERT INTO XML_TABLE (NUM_COL, XMLTYPE_COL) VALUES (4,
    XMLType.createxml('<DOC/>'));
```

Updating XML Data in OracleXmlType

The following are ways that XML data can be updated in an `OracleXmlType` object.

- The XML data can be updated by passing an XPATH expression and the new value to the `Update` method on the `OracleXmlType` object.
- The XML data can be retrieved on the client side as the `.NET Framework XmlDocument` object using the `GetXmlDocument` method on the `OracleXmlType` object. This XML data can then be manipulated using suitable `.NET Framework` classes. A new `OracleXmlType` can be created with the updated XML data from the `.NET Framework` classes. This new `OracleXmlType` is bound as an input parameter to an update or insert statement.

Characters with Special Meaning in XML

The following characters in [Table 3-20](#) have special meaning in XML. For more information, refer to the XML 1.0 specifications

Table 3-20 Characters with Special Meaning in XML

Character	Meaning in XML	Entity Encoding
<	Begins an XML tag	<
>	Ends an XML tag	>
"	Quotation mark	"
'	Apostrophe or single quotation mark	'
&	Ampersand	&

When these characters appear as data in an XML element, they are replaced with their equivalent entity encoding.

Also certain characters are not valid in XML element names. When SQL identifiers (such as column names) are mapped to XML element names, these characters are converted to a sequence of hexadecimal digits, derived from the Unicode encoding of the character, bracketed by an introductory underscore, a lowercase *x* and a trailing underscore. A blank space is not a valid character in an XML element name. If a SQL identifier contains a space character, then in the corresponding XML element name, the space character is replaced by `_x0020_`, which is based on Unicode encoding of the space character.

Retrieving Query Result Set as XML

This section discusses retrieving the result set from a SQL query as XML data.

Handling Date and Time Format

The generated XML `DATE` and `TIMESTAMP` formats are based on the standard XML Schema formats.



See Also:

<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats> for more information on the XML Schema specification.

Characters with Special Meaning in Column Data

If the data in any of the select list columns in the query contains any characters with special meaning in XML (see [Table 3-20](#)), these characters are replaced with their corresponding entity encoding in the result XML document.

The following examples demonstrate how ODP.NET handles the angle bracket characters in the column data:

```
/* Database Setup
connect scott/tiger@oracle
drop table specialchars;
create table specialchars ("id" number, name varchar2(255));
insert into specialchars values (1, '<Jones>');
commit;
*/

// C#

using System;
using System.Data;
using System.Xml;
using Oracle.DataAccess.Client;

class QueryResultAsXMLSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();

        // Create the command
        OracleCommand cmd = new OracleCommand("", con);

        // Set the XML command type to query.
        cmd.XmlCommandType = OracleXmlCommandType.Query;

        // Set the SQL query
        cmd.CommandText = "select * from specialchars";

        // Set command properties that affect XML query behavior.
        cmd.BindByName = true;

        // Set the XML query properties
        cmd.XmlQueryProperties.MaxRows = -1;

        // Get the XML document as an XmlReader.
        XmlReader xmlReader = cmd.ExecuteXmlReader();
        XmlDocument xmlDocument = new XmlDocument();

        xmlDocument.PreserveWhitespace = true;
        xmlDocument.Load(xmlReader);
        Console.WriteLine(xmlDocument.OuterXml);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}
```

The following XML document is generated for that table: The XML entity encoding that represents the angle brackets appears in bold.

```
<?xml version = '1.0'?>
<ROWSET>
```



```

<ROW>
  <id>1</id >
  <NAME>&lt;Jones&gt;</NAME>
</ROW>
</ROWSET>

```

Characters in Table or View Name

If a table or view name has any non-alphanumeric characters other than an underscore (`_`), the table or view name must be enclosed in quotation marks.

For example, to select all entries from a table with the name `test'ing`, the `CommandText` property of the `OracleCommand` object must be set to the following string:

```
"select * from \"test'ing\"";
```

Case-Sensitivity in Column Name to XML Element Name Mapping

The mapping of SQL identifiers (column names) to XML element names is case-sensitive, and the element names are in exactly the same case as the column names of the table or view.

However, the root tag and row tag names are case-insensitive. The following example demonstrates case-sensitivity in this situation:

```

//Create the following table
create table casesensitive_table ("Id" number, NAME varchar2(255));

//insert name and id
insert into casesensitive_table values(1, 'Smith');

```

The following XML document is generated:

```

<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
      <Id>1</Id>
      <NAME>Smith</NAME>
    </ROW>
  </ROWSET>

```

Note that the element name for the `Id` column matches the case of the column name.

Column Name to XML Element Name Mapping

For each row generated by the SQL query, the SQL identifier (column name) maps to an XML element in the generated XML document, as shown in the following example:

```

// Create the following table
create table emp_table (EMPLOYEE_ID NUMBER(4), LAST_NAME varchar2(25));
// Insert some data
insert into emp_table values(205, 'Higgins');

```

The SQL query, `SELECT * FROM EMP_TABLE`, generates the following XML document:

```

<?XML version="1.0"?>
  <ROWSET>

```

```
<ROW>
  <EMPLOYEE_ID>205</EMPLOYEE_ID>
  <LAST_NAME>Higgins</LAST_NAME>
</ROW>
</ROWSET>
```

The `EMPLOYEE_ID` and `LAST_NAME` database columns of the `employees` table map to the `EMPLOYEE_ID` and `LAST_NAME` elements of the generated XML document.

This section demonstrates how Oracle database handles the mapping of SQL identifiers to XML element names, when retrieving query results as XML from the database. The demonstration uses the `specialchars` table involving the `some id` column.

```
// Create the specialchars table
create table specialchars ("some id" number, name varchar2(255));
```

Note that the `specialchars` table has a column named `some id` that contains a blank space character. The space character is not allowed in an XML element name.

When retrieving the query results as XML, the SQL identifiers in the query select list can contain characters that are not valid in XML element names. When these SQL identifiers (such as column names) are mapped to XML element names, each of these characters is converted to a sequence of hexadecimal digits, derived from the Unicode encoding of the characters, bracketed by an introductory underscore, a lowercase `x`, and a trailing underscore.

Thus, the SQL query in the following example can be used to get a result as an XML document from the `specialchars` table:

```
select "some id", name from specialchars;
```



See Also:

["Characters with Special Meaning in XML"](#)

Improving Default Mapping

You can improve the default mapping of SQL identifiers to XML element names by using the following techniques:

- Modify the source. Create an object-relational view over the source schema, and make that view the new source.
- Use cursor subqueries and cast-multiset constructs in the SQL query.
- Create an alias for the column or attribute names in the SQL query. Prefix the aliases with an at sign (`@`) to map them to XML attributes instead of XML elements.
- Modify the XML document. Use [Extensible Stylesheet Language Transformation \(XSLT\)](#) to transform the XML document. Specify the XSL document and parameters. The transformation is done automatically after the XML document is generated from the relational data. Note that this may have an impact on performance.
- Specify the name of the root tag and row tag used in the XML document.

Object-Relational Data

ODP.NET can generate an XML document for data stored in object-relational columns, tables, and views, as shown in the following example:

```
// Create the following tables and types
CREATE TYPE "EmployeeType" AS OBJECT (EMPNO NUMBER, ENAME VARCHAR2(20));
/
CREATE TYPE EmployeeListType AS TABLE OF "EmployeeType";
/
CREATE TABLE mydept (DEPTNO NUMBER, DEPTNAME VARCHAR2(20),
                     EMPLIST EmployeeListType)
                     NESTED TABLE EMPLIST STORE AS EMPLIST_TABLE;
INSERT INTO mydept VALUES (1, 'depta',
                           EmployeeListType("EmployeeType"(1, 'empa')));
```

The following XML document is generated for the table:

```
<?xml version = "1.0"?>
<ROWSET>
  <ROW>
    <DEPTNO>1</DEPTNO>
    <DEPTNAME>depta</DEPTNAME>
    <EMPLIST>
      <EmployeeType>
        <EMPNO>1</EMPNO>
        <ENAME>empa</ENAME>
      </EmployeeType>
    </EMPLIST>
  </ROW>
</ROWSET>
```

ODP.NET encloses each item in a collection element, with the database type name of the element in the collection. The `mydept` table has a collection in the `EMPLIST` database column and each item in the collection is of type `EmployeeType`. Therefore, in the XML document, each item in the collection is enclosed in the type name `EmployeeType`, which appears in bold in the example.

NULL Values

If any database row has a column with a `NULL` value, then that column does not appear for that row in the generated XML document.

Data Manipulation Using XML

This section discusses making changes to the database data using XML.

Handling Date and Time Format

The generated XML `DATE` and `TIMESTAMP` formats are based on the standard XML Schema formats.

 **See Also:**

<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats> for more information on the XML Schema specification.

Saving Changes Using XML

Changes can be saved to database tables and views using XML data. However, insert, update, and delete operations cannot be combined in a single XML document. ODP.NET cannot accept a single XML document and determine which are insert, update, or delete changes.

The insert change must be in an XML document containing only rows to be inserted, the update changes only with rows to be updated, and the delete changes only with rows to be deleted.

For example, using the `employees` table that comes with the HR sample schema, you can specify the following query:

```
select employee_id, last_name from employees where employee_id = 205;
```

The following XML document is generated:

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <EMPLOYEE_ID>205</EMPLOYEE_ID>
    <LAST_NAME>Higgins</LAST_NAME>
  </ROW>
</ROWSET>
```

To change the name of employee 205 from **Higgins** to **Smith**, specify the `employees` table and the XML data containing the changes as follows:

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <EMPLOYEE_ID>205</EMPLOYEE_ID>
    <LAST_NAME>Smith</LAST_NAME>
  </ROW>
</ROWSET>
```

Characters with Special Meaning in Column Data

If the data in any of the elements in the XML document contains characters that have a special meaning in XML (see [Table 3-20](#)), these characters must be replaced with appropriate entity encoding, or be preceded by an escape character in the XML document, so that the data is stored correctly in the database table column. Otherwise, ODP.NET throws an exception.

The following example demonstrates how ODP.NET handles the angle bracket special characters in the column data, using entity encoding:

```
// Create the following table
create table specialchars ("id" number, name varchar2(255));
```

The following XML document can be used to insert values (1, '<Jones>') into the `specialchars` table. The XML entity encoding that represents the angle brackets appears in bold.

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <id>1</id >
    <NAME>&lt;Jones&gt;</NAME>
  </ROW>
</ROWSET>
```

Characters with Special Meaning in Table or View Name

If a table or view name has any non-alphanumeric characters other than an underscore (`_`), the table or view name must be enclosed in quotation marks.

For example, to save changes to a table with the name `test'ing`, the `OracleCommand.XmlSaveProperties.TableName` property must be set to `"\"test'ing\""`.

Case-Sensitivity in XML Element Name to Column Name Mapping

For each XML element that represents a row of data in the XML document, the child XML elements map to database column names. The mapping of the child element name to the column name is always case-sensitive, but the root tag and row tag names are case-insensitive. The following example demonstrates this case-sensitivity:

```
//Create the following table
create table casesensitive_table ("Id" number, NAME varchar2(255));
```

The following XML document can be used to insert values (1, Smith) into the `casesensitive_table`:

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <Id>1</Id>
    <NAME>Smith</NAME>
  </ROW>
</ROWSET>
```

Note that the element name for the `Id` column matches the case of the column name.

XML Element Name to Column Name Mapping

This section describes how Oracle database handles the mapping of XML element names to column names when using XML for data manipulation in the database. The following `specialchars` table involving the `some id` column demonstrates this handling.

```
// Create the specialchars table
create table specialchars ("some id" number, name varchar2(255));
```

Note that the `specialchars` table has a column named `some id` that contains a blank space character. The space character is not allowed in an XML element name.

Saving Changes to a Table Using an XML Document

When an XML document is used to save changes to a table or view, the `OracleCommand.XmlSaveProperties.UpdateColumnsList` property is used to specify the list of columns to update or insert.

When an XML document is used to save changes to a column in a table or view, and the corresponding column name contains any of the characters that are not valid in an XML element name, the escaped column name must be specified in the `UpdateColumnsList` property as in the following example.

The following XML document can be used to insert values (2, <Jones>) into the `specialchars` table:

```
<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
      <some_x0020_id>2</some_x0020_id>
      <NAME>&lt;Jones&gt;</NAME>
    </ROW>
  </ROWSET>
```

The following example specifies the list of columns to update or insert:

```
/* Database Setup
connect scott/tiger@oracle
drop table specialchars;
create table specialchars ("some id" number, name varchar2(255));
insert into specialchars values (1, '<Jones>');
commit;
*/

// C#

using System;
using System.Data;
using System.Xml;
using Oracle.DataAccess.Client;

class InsertUsingXmlDocSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected Successfully");

        // Create the command
        OracleCommand cmd = new OracleCommand("", con);

        // Set the XML command type to query.
        cmd.XmlCommandType = OracleXmlCommandType.Insert;

        // Set the XML document
        cmd.CommandText = "<?xml version = '1.0'?>\n" + "<ROWSET>\n" + "<ROW>\n" +
            "<some_x0020_id>2</some_x0020_id>\n" + "<NAME>&lt;Jones&gt;</NAME>\n" +
            "</ROW>\n" + "</ROWSET>\n";
```

```
cmd.XmlSaveProperties.Table = "specialchars";

string[] ucols = new string[2];

ucols[0] = "some_x0020_id";
ucols[1] = "NAME";
cmd.XmlSaveProperties.UpdateColumnsList = ucols;

// Insert rows
int rows = cmd.ExecuteNonQuery();

Console.WriteLine("Number of rows inserted successfully : {0} ", rows);

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
}
}
```

Improving Default Mapping

You can improve the default mapping by using the following techniques:

- Modify the target. Create an object-relational view over the target schema, and make the view the new target.
- Modify the XML document. Use XSLT to transform the XML document. Specify the XSL document and parameters. The transformation is done before the changes are saved. Note that this may have an impact on performance.
- Specify the name of the row tag used in the XML document.

Object-Relational Data

Changes in an XML document can also be saved to object-relational data. Each item in a collection can be specified in one of the following ways in the XML document:

- By enclosing the database type name of the item as the XML element name.
- By enclosing the name of the database column holding the collection with `_ITEM` appended as the XML element name.

Multiple Tables

Oracle Database does not save changes to multiple relational tables that have been joined together. Oracle recommends that you create a view on those relational tables, and then update that view. If the view cannot be updated, triggers can be used instead.



See Also:

Oracle Database SQL Language Reference for the description and syntax of the `CREATE VIEW` statement

Commit Transactions

When the changes in an XML document are made, either all the changes are committed, or if an error occurs, all changes are rolled back.

Oracle User-Defined Types (UDTs) and .NET Custom Types

ODP.NET has the ability to represent Oracle UDTs found in the database as custom types in .NET applications. UDTs are useful in representing complex entities as a single object that can be shared among applications. Oracle products, such as Oracle Spatial and Oracle XML DB, use their own complex types frequently.

To represent Oracle UDTs as .NET custom types, applications must apply .NET attributes to custom classes and structs, and to their public fields and properties.

 **Note:**

ODP.NET, Managed Driver and ODP.NET Core do not support UDTs and .NET Custom Types

To convert between UDTs and custom types, ODP.NET uses custom interfaces.

This section discusses the following topics:

- [Oracle User-Defined Types \(UDTs\)](#)
- [Custom Types](#)
- [Specifying Custom Type Mappings](#)
- [Converting Between Custom Types and Oracle UDTs](#)
- [Oracle UDT Attribute Mappings](#)
- [Oracle UDT Retrieval from OracleDataReader](#)
- [Oracle UDT Metadata Retrieval from OracleDataReader](#)
- [Oracle UDT Parameter Binding with OracleParameter](#)
- [Populating the DataSet with Oracle UDTs](#)
- [UDT Method Invocation](#)
- [Configuration Settings for Oracle UDTs](#)

Oracle User-Defined Types (UDTs)

Oracle Data Provider for .NET supports Oracle object types or user-defined types (UDTs), which are defined in the Oracle database.

There are two kinds of UDTs:

- Object types (Oracle Object)

- Collection types (which can be `VARRAY` types or nested table types)

Additionally, ODP.NET supports references (`REF`) to object types.

The term UDT is used interchangeably with Oracle object types and abstract data types (ADTs).

The name of the Oracle UDT is case-sensitive and must be in the form `schema_name.type_name`.

UDT samples in installations done using ODAC Oracle Universal Installer are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples\UDT` directory.



See Also:

- ["OracleRef Class"](#)
- *Oracle Database Object-Relational Developer's Guide* for complete descriptions of object types

Custom Types

Oracle Data Provider for .NET supports UDTs by representing Oracle UDTs defined in the database as .NET types, that is, custom types. For every Oracle UDT that the application wishes to fetch and manipulate, one custom type factory and one custom type are needed. The custom factory class is solely responsible for instantiating the custom type. ODP.NET uses the interfaces implemented on the custom factory classes to instantiate custom types at run time. Custom types define the mapping between the Oracle UDT attributes or elements to the .NET members. ODP.NET uses the interfaces implemented on the custom type instances to transfer values between the Oracle UDT and the custom type at run time.

Custom types can be .NET classes or structures. They can represent either Oracle Objects or Oracle Collections. Custom types can be implemented manually by the application developer or generated through an ODP.NET code generation tool.

Once the factory class and the custom type are defined and meet the implementation requirements, the application may set ODP.NET to automatically discover the mapping between the Oracle UDT and the custom type. This discovery process is based on the attribute that is applied on the custom factory class. Alternatively, the application can provide an explicit mapping through a configuration file.

Oracle Collections can be represented as an array of .NET Types. For example, an Oracle Collection type of `NUMBER` can be mapped to an `int[]`. Moreover, an Oracle Collection type of an Oracle UDT can be mapped to an array of the custom type.

Custom types must adhere to certain requirements in order for ODP.NET to represent Oracle UDTs as custom types. These requirements are as follows:

Required Custom Type Implementations

This section lists the required implementations for a custom .NET class or structure.

- `Oracle.DataAccess.Types.IOracleCustomType` interface implementation

This interface is used for conversions between custom types and Oracle UDTs.

The interface methods are implemented using the static methods of the `OracleUdt` class.

- Custom Type Factories

A custom type factory is used to create an instance of a custom type. A custom type factory is an implementation of either the `IOracleCustomTypeFactory` interface, the `IOracleArrayTypeFactory` interface, or both interfaces, as follows:

- To create a custom type that represents an Oracle Object, the custom type or a separate custom type factory class must implement the `Oracle.DataAccess.Types.IOracleCustomTypeFactory` interface.
- To create a custom type that represents an Oracle Collection, the custom type or a separate custom type factory class must implement the `Oracle.DataAccess.Types.IOracleCustomTypeFactory` interface and the `Oracle.DataAccess.Types.IOracleArrayTypeFactory` interface.
- To create an array type that represents an Oracle Collection, a custom type factory class must implement the `Oracle.DataAccess.Types.IOracleArrayTypeFactory` interface.

- Custom Type Member Mapping Attributes

The custom type member mapping attributes specify the mapping between custom type members and either Oracle object attributes or Oracle collection elements.

There are two types of custom type member mapping attributes:

- `OracleObjectMappingAttribute`

This attribute specifies the mapping between custom type members and Oracle object attributes for custom types that represent Oracle objects. This attribute must be applied to each custom type member (either field or property) that represents an Oracle Object attribute.

 **Note:**

Not all Oracle object attributes need to be mapped to custom type members. If there is no `OracleObjectMappingAttribute` for a particular object attribute, ODP.NET ignores that object attribute when converting between Oracle objects and custom types.

- `OracleArrayMappingAttribute`

This attribute specifies the custom type member that stores the elements of an Oracle collection for custom types representing Oracle collections. The attribute must be specified on only one of the custom type members.

- `Oracle.DataAccess.Types.INullable` interface implementation

This interface is used to determine if an instance of a custom type represents a null UDT. The `IsNull` property of the interface enables applications and ODP.NET to determine whether or not the UDT is null.

- Static Null field

The public static `Null` property is used to return a null UDT. This property returns a custom type with an `IsNull` property that returns true.

Optional Custom Type Implementations

The following are optional:

- `IXMLSerializable`

The `IXMLSerializable` interface is used in the .NET 2.0 framework to enable conversion between the custom type and its XML representation. This interface is only used if the serialization and deserialization of a custom type is needed in the `DataSet`.

- `Static Parse` and `Public ToString` methods

These methods enable conversion between the custom type and its string representation.

These methods are invoked when a `DataGrid` control is used to accept changes and display instance values.

- `Type Inheritance`

Type Inheritance refers to the process of deriving an Oracle UDT in the database from a super type.

If the custom type represents an Oracle UDT that is derived from a super type, the custom class should follow the same type hierarchy, that is, the custom class should be derived from another custom class that represents the super type defined in the database.

- `OracleCustomTypeMappingAttribute`

The `OracleCustomTypeMappingAttribute` object specifies the mapping between a custom type (or an array type) and an Oracle UDT.

There must be a unique custom type factory for each Oracle UDT used by the application as follows:

- `Oracle Object Types`:

The custom type factory must return a custom type that only represents the specified Oracle Object Type.

- `Oracle Collection Types`:

The custom type factory may return a custom type that can be used by other Oracle Collection Types. This is common when an array type is used to represent an Oracle Collection, for example, when an `int[]` is used to represent a collection of `NUMBERS`.

If the `OracleCustomTypeMappingAttribute` is not specified, then custom type mappings must be specified through XML configuration files, that is, `machine.config`, and either `app.config` for Windows applications or `web.config` for web applications.

 **See Also:**

- ["IOracleCustomType Interface"](#)
- ["OracleRef Class"](#)
- ["IOracleCustomTypeFactory Interface"](#)

Specifying Custom Type Mappings

After creating a custom type, the application must specify a custom type mapping that maps the custom type to an Oracle UDT in the database. This can be done using a custom type factory or XML in configuration files.

Using XML to specify custom type mappings has priority, if both techniques have been implemented. At run time, if ODP.NET finds custom type mappings specified in configuration files, it ignores any custom type mappings specified through the `OracleCustomTypeMappingAttribute` object. If a .NET application dynamically loads .NET assemblies, which contain .NET classes that Oracle UDTs are mapped to, then the mapping between .NET classes and Oracle UDTs must be configured using a .NET config file.

Custom type mappings cannot be specified using synonyms, regardless of whether or not the mapping is provided through the `OracleCustomTypeMappingAttribute` object or the XML configuration file.

 **See Also:**

Oracle Developer Tools for Visual Studio help sections on User-Defined Types Node under Server Explorer in Visual Studio for further information on UDT mapping.

This section contains these topics:

- ["Using a Custom Type Factory to Specify Custom Type Mappings"](#)
- ["Using XML in Configuration Files to Specify Custom Type Mappings"](#)

Using a Custom Type Factory to Specify Custom Type Mappings

The application can specify a custom type mapping using a custom type factory. The application supplies the name of the Oracle UDT, in the format `schema_name.type_name`, to an `OracleCustomTypeMappingAttribute` object and applies the name to the corresponding custom type factory. A custom type factory is a class or struct that implements either or both the `IOracleCustomTypeFactory` and `IOracleArrayTypeFactory` interfaces.

Note that for each Oracle UDT used by the application, there must be a unique custom type factory. Additionally, for Oracle Object Types, the custom type factory must return a custom type that uniquely represents the specified Oracle Object Type. For Oracle Collection Types, the custom type factory returns a custom type that can be used by

other Oracle Collection Types. This is common when an custom type that is an array type represents an Oracle Collection, that is, when an `int[]` is used to represent a collection of `NUMBERS`.

At run time, using reflection programming, ODP.NET discovers all the custom type mappings specified by the application through the `OracleCustomTypeMappingAttribute` object.

**Note:**

The UDT name that is specified in the `OracleCustomTypeMappingAttribute` may not contain a period.

Using XML in Configuration Files to Specify Custom Type Mappings

The application can specify a custom type mapping with XML in configuration files, for example: using `machine.config`, and either `app.config` for Windows applications or `web.config` for web applications.

The custom type mappings must be specified in the `oracle.dataaccess.client` configuration section group. Each custom type mapping must be added to the collection of custom type mappings using the XML element `<add>`.

Each custom type mapping is consists of a name attribute and a value attribute. The name attribute may be any user-specified name that represents the custom type mapping. The value attribute must begin with `udtMapping` and be followed by the required and optional attributes listed below.

Required Attributes

- `factoryName`
The case-sensitive assembly qualified name of the custom type factory class or struct.
If the assembly that defines the custom type factory does not have a strong name, then a partial assembly name consisting of just the assembly name is sufficient. In the case of strongly named assemblies, a complete assembly name is required. It must include the assembly name, the `Version`, `Culture`, `PublicKeyToken`.
- `typeName`
The case-sensitive name of the UDT defined in the database. By default all UDTs are created in the database with upper case names
- `schemaName`
The case-sensitive schema in which the UDT is defined in the database. By default all schemas are created in the database with upper case names

Optional Attributes

- `dataSource`

If specified, indicates that the custom type mapping applies only to Oracle UDTs defined in the database that the application connects to, as specified by the TNS name alias.

The Data Source is case-insensitive.

The following is an example of the format of the XML that can be specified in the configuration file for .NET 2.0:

```
<oracle.dataaccess.client>
  <settings>
    <add name="Person" value="udtMapping factoryName='Sample.PersonFactory,
      Sample, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null'
      typeName='PERSON' schemaName='SCOTT' dataSource='oracle'"/>
    <add name="Student" value="udtMapping factoryName='Sample.StudentFactory,
      Sample, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null'
      typeName='STUDENT' schemaName='SCOTT'"/>
  </settings>
</oracle.dataaccess.client>
```

Using Custom Type Mappings

During data retrieval, the application uses the custom type mappings to convert an Oracle UDT to a custom type. When data is provided back to the database through an input or input/output parameter, or by an update through an Oracle REF, the application uses the mappings to convert the custom type to an Oracle UDT.

In the case of input and input/output parameters, the application must also set the `OracleParameter.UdtTypeName` property to the user-defined type name of the parameter.

In certain cases, where Oracle UDTs are part of a type hierarchy, the custom type must be instantiated as a specific type in the type hierarchy. The Oracle UDT provided by the custom type mapping must be a subtype of the Oracle UDT specified by the `OracleParameter.UdtTypeName` property.

For example, the parameter for a stored procedure is of type, `SCOTT.PERSON` and has a subtype, `SCOTT.STUDENT`. The application has a custom class instance that represents `SCOTT.STUDENT`. The `UdtTypeName` is set to `SCOTT.PERSON`, but the custom type mapping indicates that the custom class is mapped to `SCOTT.STUDENT` and overrides the `UdtTypeName` when it instantiates the Oracle UDT. Thus, ODP.NET instantiates and binds Oracle UDTs appropriately when the custom object represents an Oracle UDT that is a subtype of the parameter type.

Converting Between Custom Types and Oracle UDTs

ODP.NET can convert between Oracle UDTs and custom types, if the proper attribute mappings are specified and the custom types are defined properly.

ODP.NET performs a conversion whenever an Oracle UDT is fetched as:

- In, out, in/out parameters bound for SQL or PL/SQL execution

The `DbType` property of `OracleParameter` must be set to `DbType.Object` or the `OracleDbType` property must be set to `OracleDbType.Object` or `OracleDbType.Array`.

For parameters that are user-defined types, the `UdtTypeName` property of the `OracleParameter` object must be always set to the parameter type.

Note: The `UdtTypeName` may differ from the Oracle UDT specified in the custom type mapping. This is the case when the parameter type is a super type of the Oracle UDT that the custom type represents.

- Column value retrieved from an `OracleDataReader` object

If the application requests for the value either through the `GetValue`, `GetValues`, `GetOracleValue`, `GetOracleValues`, `GetProviderSpecificValue`, or `GetProviderSpecificValues` methods or the `Item[]` property for a UDT column, ODP.NET finds the corresponding custom type that represents the Oracle UDT and carries out the proper conversion.

- Part of a Resultset that populates the `DataSet`

If the application populates the `DataSet` with a result that contains UDTs using the `Fill` method on the `OracleDataAdapter`, the `DataSet` is populated with custom types that represent Oracle UDTs. With ADO.NET 2.0, the `DataSet` is populated with custom types for UDT columns regardless of whether the `ReturnProviderSpecificTypes` on the `OracleDataAdapter` is set to `true` or `false`.

- A Object referenced through a REF

When an Object referenced by a REF is retrieved, the custom type that represents the Oracle UDT is returned.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned as follows:

- If the `OracleUdtFetchOption.Cache` option is specified and a cached copy of the object exists, the cached copy is immediately returned. If no cached copy exists, the latest object copy from the database is cached and returned.
- If the `OracleUdtFetchOption.Server` option is specified, the latest object copy from the database is cached and returned. If the object is already cached, the latest object copy overwrites the existing one.
- If the `OracleUdtFetchOption.TransactionCache` option is specified, there are two possibilities within the same transaction:
 - * If the object copy was previously retrieved using the `Server` or `TransactionCache` option, the `TransactionCache` option behavior becomes equivalent to the `Cache` option behavior.
 - * If the object copy was not previously retrieved using the `Server` or `TransactionCache` option, the `TransactionCache` option behavior becomes equivalent to the `Server` option behavior.

Oracle UDT Attribute Mappings

[Table 3-21](#) lists valid mappings of attributes (for objects) and elements (for collections), between Oracle UDT types and custom object types which can be either .NET types or Oracle provider-specific types (ODP.NET types).

Oracle collections do not have to map to a custom class. They can map to arrays of a specific type. [Table 3-21](#) indicates those collections with elements of a specified Oracle type that can map to arrays of a .NET Type or a provider-specific type. For example, if an Oracle Collection is a `VARRAY` of `NUMBER(8)`, it can map to a `typeof(int[])`. This eliminates the need to construct a class that only holds an `int[]`.

For .NET 2.0, Oracle Collections can be mapped to Nullable types. This allows .NET 2.0 applications to obtain a nullable `int[]` which can hold null values in the `int[]`.

Note that Oracle UDT attributes and elements cannot be mapped to `object` or `object[]`.

Table 3-21 Attribute Mappings Between UDTs and Custom Object Types

Type of UDT Attribute or Element	.NET Type	ODP.NET Type
BFILE #1	System.Byte[]	OracleBFile
BINARY FLOAT	System.Byte, System.Int16, System.Int32, System.Int64, System.Single, System.Double, System.Decimal	OracleDecimal
BINARY DOUBLE	System.Byte, System.Int16, System.Int32, System.Int64, System.Single, System.Double, System.Decimal	OracleDecimal
BLOB	System.Byte[]	OracleBlob
CHAR	System.Char[], System.String	OracleString
CLOB	System.Char[], System.String	OracleClob
DATE	System.DateTime	OracleDate
INTERVAL DAY TO SECOND	System.TimeSpan,	OracleIntervalDS
INTERVAL YEAR TO MONTH	System.Int64	OracleIntervalYM
LONG RAW	System.Byte[]	OracleBinary
NCHAR	System.Char[], System.String	OracleString
NCLOB	System.Char[], System.String	OracleClob
Nested Table	<i>custom type, .NET type[], or custom type[]</i>	<i>ODP Type[]</i>
NUMBER	System.Byte, System.Int16, System.Int32, System.Int64, System.Single, System.Double, System.Decimal	OracleDecimal

Table 3-21 (Cont.) Attribute Mappings Between UDTs and Custom Object Types

Type of UDT Attribute or Element	.NET Type	ODP.NET Type
NVARCHAR2	System.Char[], System.String	OracleString
Object Type	<i>custom type</i>	N/A
RAW	System.Byte[]	OracleBinary
REF	System.String	OracleRef
TIMESTAMP	System.DateTime	OracleTimeStamp
TIMESTAMP WITH LOCAL TIME ZONE	System.DateTime	OracleTimeStampLT Z
TIMESTAMP WITH TIME ZONE	System.DateTime	OracleTimeStampTZ
VARCHAR2	System.Char[], System.String	OracleString
VARRAY	<i>custom type</i> , <i>.NET type[]</i> , or <i>custom type[]</i>	<i>ODP Type[]</i>

Notes:

1. Conversion from a `System.Byte[]` to a `BFILE` is not supported, and therefore, `System.Byte[]` only represents a `BFILE` in read-only scenarios.

Oracle UDT Retrieval from OracleDataReader

In order to retrieve Oracle UDTs from the `OracleDataReader`, an application must specify a custom type mapping that determines the type that will represent the Oracle UDT. Once a custom type mapping has been specified and any necessary custom types have been created, the application can retrieve Oracle UDTs.

[Table 3-22](#) shows the type and value returned from an `OracleDataReader` object based on the method invoked, the column type, and whether or not there is a valid Custom type mapping.

**Note:**

PS Object refers to a provider-specific object.

Table 3-22 Type and Value Returned from OracleDataReader Object

OracleDataReader method/ property invocation	Column Data Type	Custom Type Mapping	Value Returned for Oracle UDT	NULL Value Returned for Oracle UDT
Item[index], Item[name], GetValue(), GetValues()	Object, Collection	none	Exception thrown	Exception thrown

Table 3-22 (Cont.) Type and Value Returned from OracleDataReader Object

OracleDataReader method/ property invocation	Column Data Type	Custom Type Mapping	Value Returned for Oracle UDT	NULL Value Returned for Oracle UDT
Item[index], Item[name], GetValue(), GetValues()	Object	<i>schema.type</i>	<i>custom object</i>	DBNull.Value
Item[index], Item[name], GetValue(), GetValues()	Collection	<i>schema.type</i>	<i>custom object</i> <i>custom object[]</i> <i>.NET Type[]</i> <i>PS</i> <i>object[]</i>	DBNull.Value
Item[index], Item[name], GetValue(), GetValues()	REF	none <i>schema.type</i>	<i>string</i> (HEX)	DBNull.Value
GetString()	REF	none <i>schema.type</i>	<i>string</i> (HEX)	Exception thrown
GetProviderSpecificVal ue(), GetProviderSpecificVal ues(), GetOracleValue(), GetOracleValues()	Object, Collection	<i>schema.type</i>	<i>custom object</i>	<i>custom</i> <i>type.Null</i>
GetProviderSpecificVal ue(), GetProviderSpecificVal ues(), GetOracleValue(), GetOracleValues()	Collection	<i>schema.type</i>	<i>custom object[]</i> <i>.NET Type[]</i> <i>PS</i> <i>object[]</i>	null
GetProviderSpecificVal ue(), GetProviderSpecificVal ues(), GetOracleValue(), GetOracleValues(), GetOracleRef()	REF	none <i>schema.type</i>	OracleRef	OracleRef.Null
GetOracleString()	REF	none <i>schema.type</i>	OracleString (HEX)	OracleString.N ull



See Also:

["Obtaining Data from an OracleDataReader Object"](#)

Oracle UDT Metadata Retrieval from OracleDataReader

An `OracleDataReader` object can return metadata used to determine the custom type that represents an Oracle UDT when a .NET Type or Provider-Specific Type accessor is invoked. The same custom type is used when populating the `DataSet` using the `OracleDataAdapter.Fill` method.

[Table 3-23](#) shows the values returned from the `OracleDataReader` `GetFieldType` and `GetProviderSpecificFieldType` methods that specify the .NET type of the column.

Table 3-23 Values Returned from OracleDataReader Methods

OracleDataReader Method/Property invocation	Column Data Type	Custom Type Mapping	Return Value
GetFieldType(index)	Object, Collection	none	Exception thrown
GetFieldType(index)	Object	<i>schema.type</i>	<code>typeof(custom type)</code>
GetFieldType(index)	Collection	<i>schema.type</i>	<code>typeof(custom type) typeof(custom type[]) typeof(.NET type[]) typeof(PS type[])</code>
GetFieldType(index)	REF	none <i>schema.type</i>	<code>typeof(string)</code>
GetProviderSpecificFieldType(index)	Object, Collection	none	Exception thrown
GetProviderSpecificFieldType(index)	Object,	<i>schema.type</i>	<code>typeof(custom type)</code>
GetProviderSpecificFieldType(index)	Collection	<i>schema.type</i>	<code>typeof(custom type) typeof(custom type[]) typeof(.NET type[]) typeof(PS type[])</code>
GetProviderSpecificFieldType(index)	REF	none <i>schema.type</i>	<code>typeof(OracleRef)</code>

Oracle UDT Parameter Binding with OracleParameter

This section discusses using UDT output and input parameter bindings with an `OracleParameter` object.



See Also:

["Parameter Binding"](#)

This section contains these topics:

- [Guidelines for Binding UDT Input and Output Parameters](#)
- [UDT Input Parameter Binding with OracleParameters](#)
- [UDT Output Parameter Binding with OracleParameters](#)

Guidelines for Binding UDT Input and Output Parameters

Developers must consider the following when using UDT parameter bindings with an `OracleParameter` object.

- The `UdtTypeName` property must be set. Binding is based on the `UdtTypeName` property regardless of the parameter direction.

 **Note:**

The `UdtTypeName` may differ from the Oracle UDT specified in the custom type mapping. This occurs when the parameter type is a super type of the Oracle UDT that the custom type represents.

- In case of Input/Output binding, the behavior is the same as Input and Output parameters.
- For Input parameter values, the bind value is converted to the UDT specified by the custom type mapping.
- For Output parameters:
 - If the value being returned is an Oracle Object or Collection, it is converted to a custom type or array type as specified by the custom type mapping. The value returned is always a custom type or an array type, regardless of whether the property most recently set was `DbType` or `OracleDbType`.
 - If the value being returned is a `REF`, then no custom type mapping is required.

UDT Input Parameter Binding with OracleParameters

Only certain combinations of these `OracleParameter` property values, `DbType`, `OracleDbType`, and `UdtTypeName`, can exist on the `OracleParameter` object. `OracleParameter` objects cannot be set to combinations that are not listed.

[Table 3-24](#) describes the valid ways of binding input parameters for Oracle UDTs.

The last column indicates the Oracle type that ODP.NET converts the `OracleParameter` value to before binding.

Table 3-24 Valid Ways to Bind Input Parameters for Oracle UDTs

OracleParameter. Value	OracleParameter. DbType or OracleParameter. OracleDbType	OracleParameter .UdtTypeName	Custom Type Mappings	Oracle Type converted to before Binding
<i>custom object</i> <i>custom object[]</i> <i>.NET object[]</i> <i>PS object[]</i> String (HEX) OracleString(HEX) OracleRef	DbType.Object OracleDbType.Object OracleDbType.Array OracleDbType.Ref	not set	none <i>schema.type</i>	Exception thrown
<i>custom object[]</i> <i>.NET object[]</i> <i>PS object[]</i>	DbType.Object OracleDbType.Object OracleDbType.Array	<i>schema.type</i>	none	Exception thrown

Table 3-24 (Cont.) Valid Ways to Bind Input Parameters for Oracle UDTs

OracleParameter. Value	OracleParameter. DbType or OracleParameter. OracleDbType	OracleParameter . UdtTypeName	Custom Type Mappings	Oracle Type converted to before Binding
<i>custom object</i>	DbType.Object	<i>schema.type</i>	<i>schema.type</i>	Specified UDT is instantiated. Value is bound as Object or Collection, based on the UdtTypeName property
<i>custom object</i>	OracleDbType.Object	<i>schema.type</i>	<i>schema.type</i>	Specified UDT is instantiated. <i>schema.type</i> must represent an object.
<i>custom object</i>	OracleDbType.Array	<i>schema.type</i>	<i>schema.type</i>	Specified UDT is instantiated. <i>schema.type</i> must represent a collection.
<i>.NET object[] PS object[] custom object[]</i>	DbType.Object OracleDbType.Array	<i>schema.type</i>	<i>schema.type</i>	UDT specified by OracleParameter.UdtTypeName is instantiated.
<i>.NET object[] PS object[] custom object[]</i>	OracleDbType.Object	<i>schema.type</i>	none <i>schema.type</i>	Exception thrown
<i>custom object .NET object[] PS object[] custom object[]</i>	OracleDbType.Ref	<i>schema.type</i>	none <i>schema.type</i>	Exception thrown
<i>String (HEX) OracleString (HEX) OracleRef</i>	DbType.Object OracleDbType.Object OracleDbType.Array	<i>schema.type</i>	none <i>schema.type</i>	Exception thrown
<i>Char[] (HEX) String (HEX) OracleString (HEX) OracleRef</i>	OracleDbType.Ref	<i>schema.type</i>	none <i>schema.type</i>	A REF

UDT Output Parameter Binding with OracleParameters

Only certain combinations of these OracleParameter property values, DbType, OracleDbType, and UdtTypeName, can exist on the OracleParameter object. OracleParameter objects cannot be set to combinations that are not listed.

Table 3-25 shows the supported ODP.NET output parameter bindings of Oracle database objects.

The last column indicates the type that ODP.NET converts the OracleParameter value to before binding.

Table 3-25 Valid Ways to Bind Output Parameters for Oracle UDTs

Type returned from Oracle	OracleParameter.DbType	OracleParameter.UdtTypeName	Custom Type Mappings	Type converted to
Object/ Collection/REF	DbType.Object OracleDbType.Object OracleDbType.Array OracleDbType.Ref	not set	none <i>schema.type</i>	Exception thrown
Object/ Collection	DbType.Object OracleDbType.Object OracleDbType.Array	<i>schema.type</i>	none	Exception thrown
Object	DbType.Object OracleDbType.Object	<i>schema.type</i>	<i>schema.type</i>	<i>custom object</i>
Object	OracleDbType.Array OracleDbType.Ref	<i>schema.type</i>	none <i>schema.type</i>	Exception thrown
Collection	OracleDbType.Array DbType.Object	<i>schema.type</i>	<i>schema.type</i>	<i>custom object</i> <i>custom object[]</i> <i>.NET object[]</i> <i>PS object[]</i>
Collection	OracleDbType.Ref OracleDbType.Object	<i>schema.type</i>	none <i>schema.type</i>	Exception thrown
REF	DbType.Object OracleDbType.Object OracleDbType.Array	<i>schema.type</i>	none <i>schema.type</i>	Exception thrown
REF	OracleDbType.Ref	<i>schema.type</i>	none <i>schema.type</i>	OracleRef

 **See Also:**

- ["Parameter Binding"](#)
- ["Typed OracleDataReader Accessors"](#)

Populating the DataSet with Oracle UDTs

The `DataSet` is a disconnected result set. With ADO.NET 2.0, both .NET types and provider-specific types can be used to populate the `DataSet`. This section describes the types used to populate the `DataSet` when the column is an Oracle UDT.

[Table 3-26](#) lists the types that populate the `DataSet` column, based on the Oracle column type, the `ReturnProviderSpecificTypes` property of the `DataAdapter`, the existence of a custom type mapping, the `DataSet` column type, the `DataSet` column value, and the `DataSet` column null value.

Table 3-26 Types that Populate the DataSet with ADO.NET 2.0

Oracle Column Type	ReturnProvider-SpecificTypes Property	Custom Type Mappings	DataSet Column Type	DataSet Column Value	DataSet Column Null Value
Object / Collection	False/True	none	Exception thrown	Exception thrown	Exception thrown
Object / Collection	False	schema.type	typeof(custom type)	custom object	DBNull.Value
Object / Collection	True	schema.type	typeof(custom type)	custom object	custom object.Null
Collection	False	schema.type	typeof(custom type[]) typeof(.NET type[]) typeof(PS type[])	.NET type[] PS object[] custom object[]	DBNull.Value
Collection	True	schema.type	typeof(custom type[]) typeof(.NET type[]) typeof(PS type[])	.NET type[] PS object[] custom object[]	null
REF	False	none schema.type	typeof(string)	string/HEX	DBNull.Value
REF	True	none schema.type	typeof(OracleRef)	OracleRef	OracleRef.Null

UDT Method Invocation

ODP.NET supports invocation of methods defined for a UDT on the database. This can be accomplished by doing the following:

1. Set the `CommandType` as `CommandType.StoredProcedure`.
2. Set the `CommandText` as `"type_name.procedure_name"`
3. Execute the command using any of the `Execute` methods on the `OracleCommand` object.

For instance functions, the parameters are as follows:

- The first parameter must be the return value.
- The second parameter must be the UDT instance on which the instance method is invoked, which is the instance of the .NET custom object.
- Subsequent parameters are for the function.

For instance procedures, the first parameter must be the UDT instance.

For static methods, the UDT instance is not needed.

Configuration Settings for Oracle UDTs

ODP.NET exposes two configuration settings to determine how ODP.NET handles Oracle UDTs.

- [StatementCacheWithUdts](#)
- [UdtCacheSize](#)

These configuration settings can be specified as machine-wide settings for a particular version of ODP.NET, using the registry key with the name that exists under `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version`. The configuration settings specified in the registry can be overridden if an entry is created in the `machine.config` for .NET framework-wide settings, or in the `app.config` or `web.config` for application-specific settings.



See Also:

[Configuring Oracle Data Provider for .NET](#) for details on configuring ODP.NET.

StatementCacheWithUdts

`StatementCacheWithUdts` specifies whether or not ODP.NET caches Oracle UDTs retrieved by a `SELECT` statement along with the statement when it is returned to the statement cache. Possible values are 1 - Yes (the default) or 0 - No.

For the value of 1, the Oracle UDTs are cached along with the statements. Therefore, the memory that contained the UDTs can be re-used; subsequent executions of the same statement do not require additional memory. This may result in an overall higher performance.

For the value of 0, ODP.NET frees the memory for the retrieved Oracle UDTs before the statement is returned to the statement cache. This may result in poorer performance because subsequent executions will require new memory allocations.

UdtCacheSize

`UdtCacheSize` specifies the size of the object cache for each connection that ODP.NET uses when retrieving and manipulating Oracle UDTs. The value for this setting must be specified in kilobytes (KB) with the default 4096KB, equivalent to 4 MB.

This configuration setting is used to determine how frequently the objects in the object cache will be purged (using an LRU approach) as the limit of the object cache size approaches.

Bulk Copy

ODP.NET provides a Bulk Copy feature which enables applications to efficiently load large amounts of data from a table in one database to another table in the same or a different database.

The ODP.NET Bulk Copy feature uses a direct path load approach, which is similar to, but not the same as Oracle SQL*Loader. Using direct path load is faster than conventional loading (using conventional SQL `INSERT` statements). Conventional loading formats Oracle data blocks and writes the data blocks directly to the data files. Bulk Copy eliminates considerable processing overhead.

The ODP.NET Bulk Copy feature can load data into older Oracle databases.

 **Note:**

ODP.NET, Managed Driver and ODP.NET Core do not support Bulk Copy.

The ODP.NET Bulk Copy feature is subject to the same basic restrictions and integrity constraints for direct path loads, as discussed in the next few sections.

 **See Also:**

"[System Requirements](#)" to learn which versions of the Oracle Database ODP.NET interoperates with

Data Types Supported by Bulk Copy

Bulk Copy supports the following Oracle database data types:

- NUMBER
- BINARY_DOUBLE
- BINARY_FLOAT
- CHAR
- NCHAR
- VARCHAR2
- NVARCHAR2
- LONG
- CLOB
- BLOB
- DATE
- TIMESTAMP
- TIMESTAMP WITH TIME ZONE
- TIMESTAMP WITH LOCAL TIME ZONE
- INTERVAL YEAR TO MONTH
- INTERVAL DAY TO SECOND

Bulk copy does not support overwrites.

Restrictions on Oracle Bulk Copy of a Single Partition

- The table that contains the partition cannot have any global indexes defined on it.
- The tables that the partition is a member of cannot have referential and check constraints enabled.
- Enabled triggers are not allowed.

Integrity Constraints Affecting Oracle Bulk Copy

During a Oracle bulk copy, some integrity constraints are automatically enabled or disabled, as follows:

Enabled Constraints

During an Oracle bulk copy, the following constraints are automatically enabled by default:

- NOT NULL
- UNIQUE
- PRIMARY KEY (unique-constraints on not-null columns)

NOT NULL constraints are checked at column array build time. Any row that violates the NOT NULL constraint is rejected.

UNIQUE constraints are verified when indexes are rebuilt at the end of the load. The index is left in an Index Unusable state if it violates a UNIQUE constraint.

Disabled Constraints

During an Oracle bulk copy, the following constraints are automatically disabled by default:

- CHECK constraints
- Referential constraints (FOREIGN KEY)

If the `EVALUATE CHECK_CONSTRAINTS` clause is specified, then CHECK constraints are not automatically disabled. The CHECK constraints are evaluated during a direct path load and any row that violates the CHECK constraint is rejected.

Database Insert Triggers

Table insert triggers are disabled when a direct path load begins. After the rows are loaded and indexes rebuilt, any triggers that were disabled are automatically reenabled. The log file lists all triggers that were disabled for the load. There should be no errors reenabling triggers.

Unlike integrity constraints, insert triggers are not reapplied to the whole table when they are enabled. As a result, insert triggers do not fire for any rows loaded on the direct path. When using the direct path, the application must ensure that any behavior associated with insert triggers is carried out for the new rows.

Field Defaults

Default column specifications defined in the database are not available with direct path loading. Fields for which default values are desired must be specified with the `DEFAULTIF` clause. If a `DEFAULTIF` clause is not specified and the field is `NULL`, then a null value is inserted into the database.



See Also:

[Oracle Data Provider for .NET Bulk Copy Classes](#)

Oracle Database Advanced Queuing Support

Oracle Database Advanced Queuing (AQ) provides database-integrated message queuing functionality. Oracle Database AQ leverages the functions of Oracle Database so that messages can be stored persistently, propagated between queues on different computers and databases, and transmitted using Oracle Net Services and HTTP(S).



Note:

ODP.NET, Managed Driver and ODP.NET Core do not support the AQ .NET classes.

As Oracle Database AQ is implemented in database tables, all operational benefits of high availability, scalability, and reliability are also applicable to queue data. Oracle Database AQ supports standard database features such as recovery, restart, and security.

The following items discuss Oracle Database AQ concepts:

- **Queues and Queue Tables**

Messages enqueued in a queue are stored in a queue table. A queue table must be created before creating a queue based on it. Use the `DBMS_AQADM` PL/SQL package or Oracle Developer Tools for Visual Studio to create and administer queue tables and queues.

Queues are represented by `OracleAQQueue` objects.
- **Single-Consumer and Multiple-Consumer Queues**

A single-consumer queue is created based on a single consumer queue table. Messages enqueued in a single-consumer queue can be dequeued by only a single consumer.

A multiple-consumer queue is based on a multiple-consumer queue table. This queue supports queue subscribers and message recipients.
- **Message Recipients**

A message producer can submit a list of recipients when enqueueing a message. This allows for a unique set of recipients for each message in the queue. The

recipient list associated with the message overrides the subscriber list, if any, associated with the queue. The recipients need not be in the subscriber list. However, recipients can be selected from among the subscribers. The `Recipients` property of an `OracleAQMessage` can be used to specify the recipients to a specific message in terms of `OracleAQAgent` objects.

- **Enqueue**

Messages are enqueued when producer applications push the messages into a queue. This is accomplished by calling the `Enqueue` method on an `OracleAQQueue` object. Multiple messages can be enqueued using the `EnqueueArray` method.

- **Dequeue**

Messages are dequeued when consumer applications pull the messages from a queue. This is accomplished by calling the `Dequeue` method on an `OracleAQQueue` object. Multiple messages can be dequeued using the `DequeueArray` method.

- **Listen**

Subscriber applications can use a `Listen` call to monitor multiple queues for subscriptions on different queues. This is a more scalable solution for cases where a subscriber application has subscribed to many queues and wishes to receive messages that arrive in any of the queues. This is accomplished by calling the `Listen` method of the `OracleAQQueue` class, passing the list of subscriptions in form of an array.

- **Notification**

Subscriber applications can utilize the notification mechanism to get notifications about message availability in a queue. The applications can decide to skip or dequeue the message from the queue based on the information received.

A subscriber application must register for event notification on the queues from which it wants to receive notifications. This is represented by the `MessageAvailable` event on `OracleAQQueue`. The event is triggered when messages matching the subscriptions arrive.

Notifications can be registered as regular or grouping notifications. A time out value for these notifications can also be specified. Various notification options can be set using the `OracleAQQueue.Notification` property. Notifications set on an `OracleAQQueue` object gets cancelled automatically when the object gets disposed.

- **Buffered Messaging**

In buffered messaging, messages reside in a shared memory area. This makes it faster than persistent messaging. The messages are written to disk only when the total memory consumption of buffered messages approaches the available shared memory limit. Buffered messaging is ideal for applications that do not require the reliability and transaction support of Oracle Database AQ persistent messaging.

Buffered and persistent messages use the same single-consumer or multi-consumer queues, and the same administrative and operational interfaces. They are distinguished from each other by a delivery mode parameter. When an application enqueues a message to an Oracle Database AQ queue, it sets the delivery mode parameter as well.

The delivery mode parameter can be set on `OracleAQMessage` by modifying the `DeliveryMode` property. Buffered messaging is supported in all queue tables created with compatibility 8.1 or higher.

 **See Also:**

- ["OracleAQQueue Class"](#)
- ["Recipients"](#)
- ["OracleAQAgent Class"](#)
- ["Enqueue"](#)
- ["EnqueueArray"](#)
- ["Dequeue"](#)
- ["DequeueArray"](#)
- ["Listen"](#)
- ["MessageAvailable Event"](#)
- ["Notification"](#)
- ["DeliveryMode"](#)
- *Oracle Database Advanced Queuing User's Guide*

Using ODP.NET for Advanced Queuing

.NET applications can use ODP.NET to access all the operational features of AQ such as Enqueuing, Dequeuing, Listen, and Notification.

[Table 3-27](#) maps the AQ features to their corresponding ODP.NET implementation.

Table 3-27 Mapping AQ Features with their ODP.NET Implementation

Functionality	ODP.NET Implementation
Create a Message	Create an <code>OracleAQMessage</code> object
Enqueue a single message	Specify the message as <code>OracleAQMessage</code> , queue as <code>OracleAQQueue</code> and enqueue options on <code>OracleAQQueue</code> , call <code>OracleAQQueue.Enqueue</code>
Enqueue multiple messages	Specify the messages as an <code>OracleAQMessage</code> array in <code>OracleAQQueue.EnqueueArray</code>
Dequeue a single message	Specify dequeue options on <code>OracleAQQueue</code> and call <code>OracleAQQueue.Dequeue</code>
Dequeue multiple messages	Call <code>OracleAQQueue.DequeueArray</code>
Listen for messages on Queue(s)	Call <code>OracleAQQueue.Listen</code> . To listen on multiple queues use static <code>Listen</code> method of <code>OracleAQQueue</code>
Message Notifications	Use <code>OracleAQQueue.MessageAvailable Event</code> along with the <code>NotificationConsumers</code> property

 **Note:**

AQ samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples` directory in ODAC installations done using Oracle Universal Installer.

Enqueuing and Dequeuing Example

The following example demonstrates enqueuing and dequeuing messages using a single consumer queue. The first part of the example performs the requisite database setup for the database user, SCOTT. The second part of the example demonstrates enqueuing and dequeuing messages.

```
-- Part I: Database setup required for this demo

-----
-- SQL to grant appropriate privilege to database user, SCOTT
-----
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
SQL> GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PL/SQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PL/SQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
  DBMS_AQADM.STOP_QUEUE('scott.test_q');

  DBMS_AQADM.DROP_QUEUE(
    queue_name => 'scott.test_q',
    auto_commit => TRUE);

  DBMS_AQADM.DROP_QUEUE_TABLE(
    queue_table => 'scott.test_q_tab',
    force => FALSE,
    auto_commit => TRUE);
END;
/
-- End of Part I, database setup.
```

```
//Part II: Enqueuing and dequeuing messages
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

namespace ODPSample
{
    /// <summary>
    /// Demonstrates Enqueuing and Dequeuing raw message
    /// using a single consumer queue
    /// </summary>
    class EnqueueDequeue
    {
        static void Main(string[] args)
        {
            // Create connection
            string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
            OracleConnection con = new OracleConnection(constr);

            // Create queue
            OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

            try
            {
                // Open connection
                con.Open();

                // Begin txn for enqueue
                OracleTransaction txn = con.BeginTransaction();

                // Set message type for the queue
                queue.MessageType = OracleAQMessageType.Raw;

                // Prepare message and RAW payload
                OracleAQMessage enqMsg = new OracleAQMessage();
                byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
                enqMsg.Payload = bytePayload;

                // Prepare to Enqueue
                queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;

                // Enqueue message
                queue.Enqueue(enqMsg);

                Console.WriteLine("Enqueued Message Payload      : "
                    + ByteArrayToString(enqMsg.Payload as byte[]));
                Console.WriteLine("MessageId of Enqueued Message : "
                    + ByteArrayToString(enqMsg.MessageId));

                // Enqueue txn commit
                txn.Commit();

                // Begin txn for Dequeue
                txn = con.BeginTransaction();

                // Prepare to Dequeue
                queue.DequeueOptions.Visibility = OracleAQVisibilityMode.OnCommit;
                queue.DequeueOptions.Wait = 10;
            }
            catch { }
        }
    }
}
```

```
// Dequeue message
OracleAQMessage deqMsg = queue.Dequeue();

Console.WriteLine("Dequeued Message Payload      : "
    + ByteArrayToString(deqMsg.Payload as byte[]));
Console.WriteLine("MessageId of Dequeued Message : "
    + ByteArrayToString(deqMsg.MessageId));

// Dequeue txn commit
txn.Commit();
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queue.Dispose();
    con.Close();
    con.Dispose();
}
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
    for (int n = 0; n < byteArray.Length; n++)
    {
        sb.Append((int.Parse(byteArray[n].ToString()).ToString("X"));
    }
    return sb.ToString();
}
}
```

Continuous Query Notification Support

Oracle Data Provider for .NET provides a notification framework that supports Continuous Query Notification, enabling applications to receive client-side notifications when there is a change in a query result set, schema objects, or the state of the database, even if no Oracle Data Provider for .NET database connection exists. Using Continuous Query Notification, an application can maintain the validity of the client-side cache (for example, the ADO.NET `DataSet`) easily. Continuous Query Notification was previously known as Database Change Notification.

Note:

Continuous Query Notification is not supported in a .NET stored procedure.

Using the notification framework, applications can specify a query result set as a registered query for notification request on the database, and create this notification registration to maintain the validity of the query result set. When there is a change on

the database that could affect the client-side cache's query results, the notification framework notifies the application.

 **Note:**

The content of a change notification is referred to as an *invalidation message*. It indicates that the query result set is now invalid and provides information about the changes.

Based on the information provided by the invalidation message, the application can then act accordingly. For example, the application might need to refresh its own copy of the data for the registered query that is stored locally in the application.

 **Note:**

If a registered object is dropped from the database and a new one is created with the same name in the same schema, re-registration is required to receive notifications for the newly created object.

 **See Also:**

Firewalls, such as Windows Firewall, may be set up to block TCP network ports, which blocks incoming database notifications. Ensure the firewall is configured so that database applications can use the designated port for Continuous Query Notification.

Beginning with Oracle Database 11g and ODP.NET 11g (11.1), Continuous Query Notification queries can be query-based (default) or object-based. The query-based registrations allow ODP.NET to notify applications when the selected rows have changed in the database. The object-based registrations allow ODP.NET to notify applications for any changes that occur in the table(s) containing the selected rows.

Query-based registrations have two modes: guaranteed mode and best-effort mode. In guaranteed mode, any continuous query notification ensures that a change occurred to something contained in the queried result set. However, if a query is complex, then it cannot be registered in guaranteed mode. Best-effort mode is used in such cases.

Best-effort mode simplifies the query for query-based registration. No notifications are lost from the simplification. However, the simplification may cause false positives, as the simpler version's query result could change when the original query result would not. There still remain some restrictions on which queries can have best-effort mode query-based registrations. In such cases, developers can use object-based registrations, which can register most query types. Object-based registrations generate notifications when the query object changes, even if the actual query result does not. This also means that object-based registrations are more prone to false positives than query-based registrations. Developers should be aware of the relative strengths and weaknesses of each continuous query notification option and choose the one that best suits their requirements.

If a large number of rows are modified at once, consuming significant shared pool resources, the application will not receive any change notifications with specific row information that had undergone changes. Rather, it will receive a notification with `OracleNotificationEventArgs.Info` property set to `OracleNotificationInfo.Error`.

This section contains the following topics:

- [Continuous Query Notification Classes](#)
- [Supported Operations](#)
- [Requirements of Notification Registration](#)
- [Using Continuous Query Notification](#)
- [Best Practice Guidelines and Performance Considerations](#)

See Also:

- ["Configuring a Port to Listen for Database Notifications"](#)
- *Oracle Database Platform Guide for Microsoft Windows* for details on configuring the Windows Firewall
- *Oracle Database Development Guide* for more information on Continuous Query Notification

Continuous Query Notification Classes

The following classes are associated with Continuous Query Notification Support:

- `OracleDependency`

Represents a dependency between an application and an Oracle database based on the database events which the application is interested in. It contains information about the dependency and provides the mechanism to notify the application when specified database events occurs. The `OracleDependency` class is also responsible for creating the notification listener to listen for database notifications. There is only one database notification listener for each application domain. This notification listener terminates when the application process terminates.

The dependency between the application and the database is not established when the `OracleDependency` object is created. The dependency is established when the command that is associated with this `OracleDependency` object is executed. That command execution creates a continuous query notification registration in the database.

When a change has occurred in the database, the `HasChanges` property of the `OracleDependency` object is set to `true`. Furthermore, if an event handler was registered with the `OnChange` event of the `OracleDependency` object, the registered event handler function will be invoked.

- `OracleNotificationRequest`

Represents a notification request to be registered in the database. It contains information about the request and the properties of the notification.

- `OracleNotificationEventArgs`
Represents the [invalidation message](#) generated for a notification when a specified database event occurs and contains details about that database event.

 **See Also:**

- ["OracleDependency Class"](#)
- ["OracleNotificationRequest Class"](#)
- ["OracleNotificationEventArgs Class"](#)

Supported Operations

The ODP.NET notification framework in conjunction with Continuous Query Notification supports the following activities:

- Creating a notification registration by:
 - Creating an `OracleDependency` instance and binding it to an `OracleCommand` instance.
- Grouping multiple notification requests into one registration by:
 - Using the `OracleDependency.AddCommandDependency` method.
 - Setting the `OracleCommand.Notification` request using the same `OracleNotificationRequest` instance.
- Registering for Continuous Query Notification by:
 - Executing the `OracleCommand`. If either the notification property is null or `NotificationAutoEnlist` is false, the notification will not be made.
- Removing notification registration by:
 - Using the `OracleDependency.RemoveRegistration` method.
 - Setting the `Timeout` property in the `OracleNotificationRequest` instance before the registration is created.
 - Setting the `IsNotifiedOnce` property to true in the `OracleNotificationRequest` instance before the registration is created. The registration is removed once a database notification is sent.
- Ensuring Change Notification Persistence by:
 - Specifying whether or not the invalidation message is queued persistently in the database before delivery. If an invalidation message is to be stored persistently in the database, then the change notification is guaranteed to be sent. If an invalidation message is stored in an in-memory queue, the change notification can be received faster, however, it could be lost upon database shutdown or crashes.
- Retrieving notification information including:
 - The changed object name.
 - The schema name of the changed object.

- Database events that cause the notification, such as insert, delete, and so on.
- The `RowID` of the modified object row.

In Oracle SQL, the `ROWIDTOCHAR(ROWID)` and `ROWIDTONCHAR(ROWID)` functions convert a `ROWID` value to `VARCHAR2` and `NVARCHAR` data types, respectively. If these functions are used within a SQL statement, `ROWIDS` are not returned in the `OracleNotificationEventArgs` object that is passed to the continuous query notification callback.

- Defining the listener port number.

By default, the static `OracleDependency.Port` property is set to `-1`. This indicates that the ODP.NET listens on a port that is randomly picked when ODP.NET registers a continuous query notification request for the first time during the execution of an application.

ODP.NET creates only one listener that listens on one port within an application domain. Once ODP.NET starts the listener, the port number cannot be changed; Changes to the static `OracleDependency.Port` property will generate an error if a listener has already been created.

See Also:

- ["OracleCommand Class"](#)
- ["Notification"](#)
- ["NotificationAutoEnlist"](#)
- ["OracleDependency Class"](#)
- ["OracleNotificationEventArgs Class"](#)

Requirements of Notification Registration

The connected user must have the `CHANGE NOTIFICATION` privilege to create a notification registration.

This SQL statement grants the `CHANGE NOTIFICATION` privilege:

```
grant change notification to user name
```

This SQL statement revokes the `CHANGE NOTIFICATION` privilege:

```
revoke change notification from user name
```

Using Continuous Query Notification

This section describes what the application should do, and the flow of the process, when an application uses Continuous Query Notification to receive notifications for any changes in the registered query result set.

Application Steps

The application should do the following:

1. Create an `OracleDependency` instance.
2. Assign an event handler to the `OracleDependency.OnChange` event property if the application wishes to have an event handler invoked when database changes are detected. Otherwise, the application can choose to poll on the `HasChanges` property of the `OracleDependency` object. This event handler is invoked when the change notification is received.
3. Set the port number for the listener to listen on. The application can specify the port number for one notification listener to listen on. If the application does not specify a port number, a random one is used by the listener.
4. Bind the `OracleDependency` instance to an `OracleCommand` instance that contains the actual query to be executed. Internally, the Continuous Query Notification request (an `OracleNotificationRequest` instance) is created and assigned to the `OracleCommand.Notification` property.

Flow of Notification Process

1. When the command associated with the notification request is executed, the notification registration is created in the database. The command execution must return a result set, or contain one or more `REF` cursors for a PL/SQL stored procedure.
2. ODP.NET starts the application listener on the first successful notification registration.
3. When a change related to the registration occurs in the database, the application is notified through the event delegate assigned to the `OracleDependency.OnChange` event property, or the application can poll the `OracleDependency.HasChanges` property.

The following example demonstrates the continuous query notification feature.

```
// Database Setup
// NOTE: unless the following SQL command is executed,
// ORA-29972 will be obtained from running this sample
/*
grant change notification to scott;
*/
using System;
using System.Threading;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

//This sample shows the continuous query notification feature in ODP.NET.
//Application specifies to get a notification when emp table is updated.
//When emp table is updated, the application will get a notification
//through an event handler.
namespace NotificationSample
{
    public class MyNotificationSample
    {
        public static bool IsNotified = false;

        public static void Main(string[] args)
        {
            //To Run this sample, make sure that the change notification privilege
            //is granted to scott.
        }
    }
}
```

```
string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = null;
OracleDependency dep = null;

try
{
    con = new OracleConnection(constr);
    OracleCommand cmd = new OracleCommand("select * from emp", con);
    con.Open();

    // Set the port number for the listener to listen for the notification
    // request
    OracleDependency.Port = 1005;

    // Create an OracleDependency instance and bind it to an OracleCommand
    // instance.
    // When an OracleDependency instance is bound to an OracleCommand
    // instance, an OracleNotificationRequest is created and is set in the
    // OracleCommand's Notification property. This indicates subsequent
    // execution of command will register the notification.
    // By default, the notification request is using the Database Change
    // Notification.
    dep = new OracleDependency(cmd);

    // Add the event handler to handle the notification. The
    // OnMyNotification method will be invoked when a notification message
    // is received from the database
    dep.OnChange +=
        new OnChangeEventHandler(MyNotificationSample.OnMyNotificaton);

    // The notification registration is created and the query result sets
    // associated with the command can be invalidated when there is a
    // change. When the first notification registration occurs, the
    // notification listener is started and the listener port number
    // will be 1005.
    cmd.ExecuteNonQuery();

    // Updating emp table so that a notification can be received when
    // the emp table is updated.
    // Start a transaction to update emp table
    OracleTransaction txn = con.BeginTransaction();
    // Create a new command which will update emp table
    string updateCmdText =
        "update emp set sal = sal + 10 where empno = 7782";
    OracleCommand updateCmd = new OracleCommand(updateCmdText, con);
    // Update the emp table
    updateCmd.ExecuteNonQuery();
    //When the transaction is committed, a notification will be sent from
    //the database
    txn.Commit();
}
catch (Exception e)
{
    Console.WriteLine(e.Message);
}

con.Close();
// Loop while waiting for notification
while(MyNotificationSample.IsNotified == false)
{
    Thread.Sleep(100);
}
```

```
    }  
  }  
  
  public static void OnMyNotificaton(object src,  
    OracleNotificationEventArgs arg)  
  {  
    Console.WriteLine("Notification Received");  
    DataTable changeDetails = arg.Details;  
    Console.WriteLine("Data has changed in {0}",  
      changeDetails.Rows[0]["ResourceName"]);  
    MyNotificationSample.IsNotified = true;  
  }  
}
```

Best Practice Guidelines and Performance Considerations

This section provides guidelines for working with Continuous Query Notification and the ODP.NET notification framework, and discusses the performance impacts. Every change notification registration consumes database memory, storage or network resources, or some combination thereof. The resource consumption further depends on the volume and size of the [invalidation message](#). In order to scale well with a large number of mid-tier clients, Oracle recommends that the client implement these best practices:

- Few and mostly read-only tables
There should be few registered objects, and these should be mostly read-only, with very infrequent invalidations. If an object is extremely volatile, then a large number of invalidation notifications are sent, potentially requiring a lot of space (in memory or on disk) in the invalidation queue. This is also true if a large number of objects are registered.
- Few rows updated for each table
Transactions should update (or insert or delete) only a small number of rows within the registered tables. Depending on database resources, a whole table could be invalidated if too many rows are updated within a single transaction, for a given table.

This policy helps to contain the size of a single invalidation message, and reduces disk storage for the invalidation queue.



See Also:

Oracle Database Development Guide for further information on Continuous Query Notification

OracleDataAdapter Safe Type Mapping

The ODP.NET `OracleDataAdapter` class provides the Safe Type Mapping feature to ensure that the following Oracle data types do not lose data when converted to their closely related .NET types in the `DataSet`:

- NUMBER

Table 3-29 Oracle Date to .NET DateTime Comparisons

Value Limits	Oracle Date	.NET DateTime
Maximum	Dec 31, 9999 AD	Dec 31, 9999 AD 23:59:59.9999999
Minimum	Jan 1, 4712 BC	Jan 1, 0001 AD 00:00:00.0000000

Oracle TimeStamp Type to .NET DateTime Type

Similar to the `DATE` data type, the Oracle `TimeStamp` data type can represent a date in BC, and a `.NET DateTime` type cannot. If a `TimeStamp` that goes to BC is retrieved into a `.NET DateTime` type, it loses data. The Oracle `TimeStamp` type can represent values in units of e-9; the `.NET DateTime` type can represent only values in units of e-7. The Oracle `TimeStamp` with time zone data type can store time zone information, and the `.NET DateTime` type cannot.

[Table 3-30](#) lists the maximum and minimum values for Oracle `TimeStamp` and `.NET DateTime` types.

Table 3-30 Oracle TimeStamp to .NET DateTime Comparisons

Value Limits	Oracle TimeStamp	.NET DateTime
Maximum	Dec 31, 9999 AD 23:59:59.999999999	Dec 31, 9999 AD 23:59:59.9999999
Minimum	Jan 1, 4712 BC 00:00:00.000000000	Jan 1, 0001 AD 00:00:00.0000000

Oracle INTERVAL DAY TO SECOND to .NET TimeSpan

The Oracle data type `INTERVAL DAY TO SECOND` can hold up to 9 precision, and the `.NET TimeSpan` type can hold up to 7 precision. If an `INTERVAL DAY TO SECOND` data type that has more than 7 precision is retrieved into a `.NET TimeSpan` type, it loses precision. The Oracle `INTERVAL DAY TO SECOND` type can represent values in units of e-9, and the `.NET TimeSpan` type can represent only values in units of e-7.

[Table 3-31](#) lists the maximum and minimum values for Oracle `INTERVAL DAY TO SECOND` and `.NET DateTime` types.

Table 3-31 Oracle INTERVAL DAY TO SECOND to .NET TimeSpan Comparisons

Value Limits	Oracle INTERVAL DAY TO SECOND	.NET TmeSpan
Maximum	+999999999 23:59:59.999999999	+10675199 02:48:05.4775807
Minimum	-999999999 23:59:59.999999999	-10675199 02:48:05.4775808

SafeMapping Property

The `OracleDataAdapter Safe Type Mapping` feature prevents data loss when populating Oracle data for any of these types into a `.NET DataSet`. By setting the

SafeMapping property appropriately, these types can be safely represented in the DataSet, as either of the following:

- .NET byte[] in Oracle format
- .NET String

By default, Safe Type Mapping is disabled.

Using Safe Type Mapping

To use the Safe Type Mapping feature, the `OracleDataAdapter.SafeMapping` property must be set with a hash table of key-value pairs. The key-value pairs must map database table column names (of type `string`) to a .NET type (of type `Type`). ODP.NET supports Safe Type Mapping to `byte[]` and `String` types. Any other type mapping causes an exception.

In situations where the column names are not known at design time, an asterisk ("*") can be used to map all occurrences of database types to a safe .NET type. If both the valid column name and the asterisk are present, the column name is used.

Note:

- Database table column names are case-sensitive.
- Column names in the hash table that correspond to invalid column names are ignored.

Safe Type Mapping as a string is more readable without further conversion. Converting certain Oracle data types to a string requires extra conversion, which can be slower than converting it to a `byte[]`. Conversion of .NET strings back to ODP.NET types relies on the formatting information of the session.

SafeTyping Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class SafeMappingSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";

        // In this SELECT statement, EMPNO, HIREDATE and SALARY must be
        // preserved using safe type mapping.
        string cmdstr = "SELECT EMPNO, ENAME, HIREDATE, SAL FROM EMP";

        // Create the adapter with the selectCommand txt and the connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Get the connection from the adapter
        OracleConnection connection = adapter.SelectCommand.Connection;
```

```
// Create the safe type mapping for the adapter
// which can safely map column data to byte arrays, where
// applicable. By executing the following statement, EMPNO, HIREDATE AND
// SALARY columns will be mapped to byte[]
adapter.SafeMapping.Add("*", typeof(byte[]));

// Map HIREDATE to a string
// If the column name in the EMP table is case-sensitive,
// the safe type mapping column name must be case-sensitive.
adapter.SafeMapping.Add("HIREDATE", typeof(string));

// Map EMPNO to a string
// If the column name in the EMP table is case-sensitive,
// the safe type mapping column name must also be case-sensitive.
adapter.SafeMapping.Add("EMPNO", typeof(string));
adapter.SafeMapping.Add("SAL", typeof(string));

// Create and fill the DataSet using the EMP
DataSet dataset = new DataSet();
adapter.Fill(dataset, "EMP");

// Get the EMP table from the dataset
DataTable table = dataset.Tables["EMP"];

// Get the first row from the EMP table
DataRow row = table.Rows[0];

// Print out the row info
Console.WriteLine("EMPNO Column: type = " + row["EMPNO"].GetType() +
    "; value = " + row["EMPNO"]);
Console.WriteLine("ENAME Column: type = " + row["ENAME"].GetType() +
    "; value = " + row["ENAME"]);
Console.WriteLine("HIREDATE Column: type = " + row["HIREDATE"].GetType()+
    "; value = " + row["HIREDATE"]);
Console.WriteLine("SAL Column: type = " + row["SAL"].GetType() +
    "; value = " + row["SAL"]);
    }
}
```

**See Also:**

["SafeMapping"](#)

OracleDataAdapter Requery Property

The `OracleDataAdapter Requery` property controls whether or not queries are reexecuted for `OracleDataAdapter Fill` calls after the initial `Fill` call.

The `OracleDataAdapter Fill` method allows appending or refreshing data in the `DataSet`. When appending the `DataSet` using the same query with subsequent `Fill` calls, reexecuting the query may not be desirable.

When the `Requery` property is set to `true`, each subsequent `Fill` call reexecutes the query and fills the `DataSet`. This is an expensive operation, and if the reexecution is

not required, set `Requery` to `false`. If any of the `SelectCommand` properties or associated parameters must be changed, `Requery` must be set to `true`.

When the `Requery` property is set to `false`, the `DataSet` has all the data as a snapshot at a particular time. The query is executed only for the first `Fill` call; subsequent `Fill` calls fetch the data from a cursor opened with the first execution of the query. This feature is supported only for forward-only fetches. `Fill` calls that try to fetch rows before the last fetched row raise an exception. The connection used for the first `Fill` call must be available for subsequent `Fill` calls.

When filling a `DataSet` with an `OracleRefCursor` object, the `Requery` property can be used in a similar manner. When the `Requery` property is set to `false`, both the connection used for the first `Fill` call and the `OracleRefCursor` object must be available for the subsequent `Fill` calls.

See Also:

- ["Requery"](#)
- ["SelectCommand"](#)

Guaranteeing Uniqueness in Updating DataSet to Database

This section describes how the `OracleDataAdapter` object configures the `PrimaryKey` and `Constraints` properties of the `DataTable` object which guarantee uniqueness when the `OracleCommandBuilder` object is updating `DataSet` changes to the database.

Using the `OracleCommandBuilder` object to dynamically generate DML statements to be executed against the database is one of the ways to reconcile changes made in a single `DataTable` object with the database.

In this process, the `OracleCommandBuilder` object must not be allowed to generate DML statements that may affect (update or delete) more than a single row in the database when reconciling a single `DataRow` change. Otherwise the `OracleCommandBuilder` could corrupt data in the database.

To guarantee that each `DataRow` object change affects only a single row, there must be a set of `DataColumn` objects in the `DataTable` for which all rows in the `DataTable` have a unique set of values. The set of `DataColumn` objects indicated by the properties `DataTable.PrimaryKey` and `DataTable.Constraints` meets this requirement. The `OracleCommandBuilder` object determines uniqueness in the `DataTable` by checking if the `DataTable.PrimaryKey` is not a null value or if there exists a `UniqueConstraint` object in the `DataTable.Constraints` collection.

This discussion first explains what constitutes uniqueness in `DataRow` objects and then explains how to maintain that uniqueness while updating, through the `DataTable` property configuration.

This section includes the following topics:

- [What Constitutes Uniqueness in DataRow Objects?](#)
- [Configuring PrimaryKey and Constraints Properties](#)

- [Updating Without PrimaryKey and Constraints Configuration](#)

What Constitutes Uniqueness in DataRow Objects?

This section describes the minimal conditions that must be met to guarantee uniqueness of `DataRow` objects. The condition of uniqueness must be guaranteed before the `DataTable.PrimaryKey` and `DataTable.Constraints` properties can be configured, as described in the next section.

Uniqueness is guaranteed in a `DataTable` object if any one of the following is true:

- All the columns of the primary key are in the select list of the `OracleDataAdapter.SelectCommand` property.
- All the columns of a unique constraint are in the select list of the `OracleDataAdapter.SelectCommand` property, with at least one involved column having a `NOT NULL` constraint defined on it.
- All the columns of a unique index are in the select list of the `OracleDataAdapter.SelectCommand` property, with at least one of the involved columns having a `NOT NULL` constraint defined on it.
- A `ROWID` is present in the select list of the `OracleDataAdapter.SelectCommand` property.

Note:

A set of columns, on which a unique constraint has been defined or a unique index has been created, requires at least one column that cannot be null for the following reason: if all the columns of the column set can be null, then multiple rows could exist that have a `NULL` value for each column in the column set. This would violate the uniqueness condition that each row has a unique set of values for the column set.

Configuring PrimaryKey and Constraints Properties

If the minimal conditions described in "[What Constitutes Uniqueness in DataRow Objects?](#)" are met, then the `DataTable.PrimaryKey` or `DataTable.Constraints` properties can be set.

After these properties are set, the `OracleCommandBuilder` object can determine uniqueness in the `DataTable` by checking the `DataTable.PrimaryKey` property or the presence of a `UniqueConstraint` object in the `DataTable.Constraints` collection. Once uniqueness is determined, the `OracleCommandBuilder` object can safely generate DML statements to update the database.

The `OracleDataAdapter.FillSchema` method attempts to set these properties according to this order of priority:

1. If the primary key is returned in the select list, it is set as the `DataTable.PrimaryKey` property.
2. If a set of columns that meets the following criteria is returned in the select list, it is set as the `DataTable.PrimaryKey` property.

Criteria: The set of columns has a unique constraint defined on it or a unique index created on it, with each column having a NOT NULL constraint defined on it.

3. If a set of columns that meets the following criteria is returned in the select list, a `UniqueConstraint` object is added to the `DataTable.Constraints` collection, but the `DataTable.PrimaryKey` property is not set.

Criteria: The set of columns has a unique constraint defined on it or a unique index created on it, with at least one column having a NOT NULL constraint defined on it.

4. If a ROWID is part of the select list, it is set as the `DataTable.PrimaryKey` property.

Additionally, the `OracleDataAdapter.FillSchema` method performs as follows:

- Setting the `DataTable.PrimaryKey` property implicitly creates a `UniqueConstraint` object.
- If a column is part of the `DataTable.PrimaryKey` property or the `UniqueConstraint` object, or both, it will be repeated for each occurrence of the column in the select list.

Updating Without PrimaryKey and Constraints Configuration

If the `DataTable.PrimaryKey` or `Constraints` properties have not been configured, for example, if the application has not called the `OracleDataAdapter.FillSchema` method, the `OracleCommandBuilder` object directly checks the select list of the `OracleDataAdapter.SelectCommand` property to determine if it guarantees uniqueness in the `DataTable`. However this check results in a database round-trip to retrieve the metadata for the `SELECT` statement of the `OracleDataAdapter.SelectCommand`.

Note that `OracleCommandBuilder` object cannot update a `DataTable` created from PL/SQL statements because they do not return any key information in their metadata.

Globalization Support

ODP.NET globalization support enables applications to manipulate culture-sensitive data appropriately. This feature ensures proper string format, date, time, monetary, numeric, sort order, and calendar conventions depending on the Oracle globalization settings.

Note:

- ODP.NET, Managed Driver and ODP.NET Core are not `NLS_LANG` sensitive. They are only .NET locale sensitive.
- ODP.NET, Managed Driver and ODP.NET Core do not support thread-based globalization.

See Also:

["OracleGlobalization Class"](#)

This section includes the following:

- [Globalization Settings](#)
- [Globalization-Sensitive Operations](#)

Globalization Settings

An `OracleGlobalization` object can be used to represent the following:

- [Client Globalization Settings](#)
- [Session Globalization Settings](#)
- [Thread-Based Globalization Settings](#)

Client Globalization Settings

Client globalization settings are derived from the Oracle globalization setting (`NLS_LANG`) in the Windows registry of the local computer. The client globalization parameter settings are read-only and remain constant throughout the lifetime of the application. These settings can be obtained by calling the `OracleGlobalization.GetClientInfo` static method.

The following example retrieves the client globalization settings:

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ClientGlobalizationSample  
{  
    static void Main()  
    {  
        OracleGlobalization ClientGlob = OracleGlobalization.GetClientInfo();  
  
        Console.WriteLine("Client machine language: " + ClientGlob.Language);  
        Console.WriteLine("Client characterset: " + ClientGlob.ClientCharacterSet);  
    }  
}
```

The properties of the `OracleGlobalization` object provide the Oracle globalization value settings.

Session Globalization Settings

Session globalization parameters are initially identical to client globalization settings. Unlike client settings, session globalization settings can be updated. However, they can be obtained only after establishing a connection against the database. The session globalization settings can be obtained by calling the `GetSessionInfo` method on the `OracleConnection` object. Invoking this method returns an instance of an `OracleGlobalization` class whose properties represent the globalization settings of the session.

When the `OracleConnection` object establishes a connection, it implicitly opens a session whose globalization parameters are initialized with those values specified by the client computer's Oracle globalization (or (NLS)) registry settings. The session settings can be updated and can change during its lifetime.

The following example changes the date format setting on the session:

```
// C#

using System;
using Oracle.DataAccess.Client;

class SessionGlobalizationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();

        OracleGlobalization SessionGlob = con.GetSessionInfo();

        // SetSessionInfo updates the Session with the new value
        SessionGlob.DateFormat = "YYYY/MM/DD";
        con.SetSessionInfo(SessionGlob);
        Console.WriteLine("Date Format successfully changed for the session");

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}
```

Thread-Based Globalization Settings

Thread-based globalization parameter settings are specific to each thread. Initially, these settings are identical to the client globalization parameters, but they can be changed as specified by the application. When ODP.NET Types are converted to and from strings, the thread-based globalization parameters are used, if applicable.

Thread-based globalization parameter settings are obtained by invoking the `GetThreadInfo` static method of the `OracleGlobalization` class. The `SetThreadInfo` static method of the `OracleGlobalization` class can be called to set the thread's globalization settings.

ODP.NET classes and structures rely solely on the `OracleGlobalization` settings when manipulating culture-sensitive data. They do not use .NET thread culture information. If the application uses only .NET types, `OracleGlobalization` settings have no effect. However, when conversions are made between ODP.NET types and .NET types, `OracleGlobalization` settings are used where applicable.

Note:

Changes to the `System.Threading.Thread.CurrentThread.CurrentCulture` property do not impact the `OracleGlobalization` settings of the thread or the session, or the reverse.

The following example shows how the thread's globalization settings are used by the ODP.NET Types:


```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ThreadBasedGlobalizationSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat for the OracleDate constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleDate from a string using the DateFormat specified.
        OracleDate date = new OracleDate("1999-DEC-01");

        // Set a different DateFormat for the thread
        info.DateFormat = "MM/DD/YYYY";
        OracleGlobalization.SetThreadInfo(info);

        // Print "12/01/1999"
        Console.WriteLine(date.ToString());
    }
}
```

The `OracleGlobalization` object validates property changes made to it. If an invalid value is used to set a property, an exception is thrown. Note that changes made to the `Territory` and `Language` properties change other properties of the `OracleGlobalization` object implicitly.

See Also:

Oracle Database Globalization Support Guide for more information on the properties affected by `Territory` and `Language` globalization settings

Globalization-Sensitive Operations

This section lists ODP.NET types and operations that are dependent on or sensitive to globalization settings.

Operations Dependent on Client Computer's Globalization Settings

The `OracleString` structure depends on the `OracleGlobalization` settings of the client computer. The client character set of the local computer is used when it converts a Unicode string to a `byte[]` in the `GetNonUnicode` method and when it converts a `byte[]` of ANSI characters to Unicode in the `OracleString` constructor that accepts a `byte[]`.

Operations Dependent on Thread Globalization Settings

The thread globalization settings are used by ODP.NET types whenever they are converted to and from .NET string types, where applicable. Specific thread

globalization settings are used in most cases, depending on the ODP.NET type, by the following:

- The `ToString` method
- The `Parse` static method
- Constructors that accept .NET string data
- Conversion operators to and from .NET strings

For example, the `OracleDate` type uses the `DateFormat` property of the thread globalization settings when the `ToString` method is invoked on it. This returns a `DATE` as a string in the format specified by the thread's settings.

The thread globalization settings also affect data that is retrieved into the `DataSet` as a string using Safe Type Mapping. If the type is format-sensitive, the strings are always in the format specified by the thread globalization settings.

For example, `INTERVAL DAY TO SECOND` data is not affected by thread settings because no format is applicable for this type. However, the `DateFormat` and `NumericCharacters` properties can impact the string representation of `DATE` and `NUMBER` types, respectively, when they are retrieved as strings into the `DataSet` through Safe Type Mapping.

See Also:

- The remarks in [OracleGlobalization Class](#) for more details on the ODP.NET type methods that convert between ODP.NET types and .NET string types, and to identify which thread globalization settings are used for that particular method.
- [OracleDataAdapter Safe Type Mapping](#)
- [Oracle Data Provider for .NET Types Structures](#)

Operations Sensitive to Session Globalization Parameters

Session globalization settings affect any data that is retrieved from or sent to the database as a string.

For example, if a `DATE` column is selected with the `TO_CHAR` function applied on it, the `DATE` column data will be a string in the date format specified by the `DateFormat` property of the session globalization settings. Transmitting data in the other direction, the string data that is to be inserted into the `DATE` column, must be in the format specified by the `DateFormat` property of the session globalization settings.

ODP.NET Drivers Differences

ODP.NET drivers set the default session time zone differently. While the session time zone for unmanaged ODP.NET uses an hour offset, managed ODP.NET and ODP.NET Core use the region identifier for setting their respective session time zone. As a result, managed and Core ODP.NET is sensitive to daylight savings in scenarios where the timestamp LTZ values have to be converted from or to the session time zone.

There are two methods to resolve this difference if needed. For ODP.NET, Unmanaged Driver, the application explicitly sets the region identifier with the environment variable `ORA_SDTZ`. For example, set `ORA_SDTZ = <Region ID>`. If `ORA_SDTZ` variable is set, Oracle Client considers this value as the session time zone. The second method is to execute an alter session command to set the session time zone property to the region identifier.

Debug Tracing

ODP.NET provides debug tracing support, which allows logging of all the ODP.NET activities into a trace file. Different levels of tracing are available.

The provider can record the following information:

- Entry and exit information for the ODP.NET public methods
- User-provided SQL statements as well as SQL statements modified by the provider
- Connection pooling statistics such as enlistment and delistment
- Thread ID (entry and exit)
- HA Events and Load Balancing information
- Distributed Transactions
- Self-tuning information
- User-mode dumps upon unmanaged exceptions

To enable ODP.NET for tracing, `TraceFileLocation`, `TraceLevel`, and `TraceOption` must be set appropriately either in the Windows Registry or in an XML configuration file. ODP.NET, Managed and Unmanaged Drivers support the XML configuration file. Windows Registry settings are available for ODP.NET, Unmanaged Driver only.

In ODAC 12c Release 4, ODP.NET now uses new directories to write trace files to by default.

- ODP.NET, Managed Driver: `<Windows user temporary folder>\ODP.NET\managed\trace`
- ODP.NET, Unmanaged Driver: `<Windows user temporary folder>\ODP.NET\unmanaged\trace`

The Windows user temporary folder is determined by your local Windows settings, such as your Windows `TMP` or `TEMP` environment variable. Typically, it can be `C:\temp` or `C:\Users\<user name>\AppData\Local\Temp`. ODP.NET will create an entry in the Windows event log where the trace was created anytime it creates a trace file. ODP.NET Core does not support writing to the Windows event log.

For ODP.NET, Unmanaged Driver specifically, `TraceFileLocation` is now supported similar to ODP.NET, Managed Driver. `TraceFileLocation` defines the directory where the trace files will be created. Neither `TraceFileName` nor `TraceFileLocation` will be created by default in the Windows Registry.

 **See Also:**

"[Configuring Oracle Data Provider for .NET](#)" for further details

Database Application Migration: SQL Translation Framework

A key part of migrating non-Oracle database applications to an Oracle Database requires converting non-Oracle SQL statements to SQL statements that can be processed by an Oracle Database. SQL conversion is generally a manual and laborious process. To minimize the effort, Oracle Database 12c introduces SQL Translation Framework which takes non-Oracle SQL statements from client applications and then translates them at run-time for the Oracle Database to execute.

The SQL Translation Framework can be used to map non-Oracle stored procedure to Oracle stored procedures to ensure successful execution of those stored procedures when migrating to Oracle Database.

Currently, SQL Translation Framework is available for Sybase Adaptive Server Enterprise and Microsoft SQL Server. There is limited support for IBM DB2.

 **Note:**

SQL Translation Framework is only supported by ODP.NET, Unmanaged Driver. ODP.NET, Managed Driver and ODP.NET Core do not support this feature.

The SQL Translation Profile

The SQL Translation Profile is a database object that contains the set of captured non-Oracle SQL statements, and their translations or translation errors. The SQL Translation Profile is used to review, approve, and modify translations. A profile is associated to a single translator. However, a translator can be used in one or more SQL Translation Profiles. Typically, there is one SQL Translation Profile per application, otherwise applications can share translated queries. You can export profiles among various databases.

1. Configuring the SQL Translation Profile Name

The default translation profile name for SQL Translation Framework can be configured through the `app/web/machine` .NET configuration file. If configured, connections, by default will automatically be set to the specified profile when the connection is initially created.

2. Changing the SQL Translation Profile Name

ODP.NET supports setting the profile name through the .NET config file, logon trigger, or database service. ODP.NET does not support using `ALTER SESSION` from an application to set the profile name.

3. Forcing Translation

Applications are strictly prohibited to execute the following SQL which forces translation of all SQL's on the database:

```
ALTER SESSION SET events = '10601 trace name context forever, level 32'
```

4. Connection Related Error Mapping

Connection Related Error Mapping can be configured through the .NET configuration file. Please note that this error mapping strictly applies to errors which could be thrown before the connection is successfully established. Once the database connection is established successfully, then these error mapping will be completely ignored and further error translation will be provided through the error mapping configured in the database.

The rules to choose an error mapping section in the configuration file are as follows:

- a. ODP.NET uses the error mapping section which matches the configured `userId`, `dataSource`, and `profile`, where `userId` and `dataSource` matches the corresponding values in the connection string and `profile` matches the `defaultProfile` configuration setting.
 - b. If no error mapping section is found from 4.a.), then ODP.NET uses the error mapping section which matches the `userId`, `dataSource`, and `profile` similar to 4.a.), but with the `profile` that matches with the `defaultErrorMappingProfile` configuration setting.
 - c. If still no error mapping section is found, then ODP.NET uses the global mapping, that is, `<ErrorMapping profile="*">`, if configured.
5. Stored Procedure Mapping.

Application must map their native stored procedure names to the corresponding Oracle stored procedure names on the translation profile in the database. The following procedure can be used to setup the mapping in the database.

```
DBMS_SQL_TRANSLATOR.REGISTER_SQL_TRANSLATION(
  PROFILE_NAME  VARCHAR2  IN
  SQL_TEXT      CLOB      IN
  TRANSLATED_TEXT CLOB      IN      DEFAULT
  ENABLE        BOOLEAN   IN      DEFAULT)
```

Example of stored procedure mapping:

```
DBMS_SQL_TRANSLATOR.REGISTER_SQL_TRANSLATION('profile_name',
  'native_sp_name',
  'oracle_sp_name');
```

See Also:

Chapter 2, SQL Translation Framework Overview and Architecture, of the *Oracle Database Migration Guide* for more information.

4

ADO.NET Entity Framework and LINQ to Entities

This section describes ADO.NET Entity Framework and LINQ to Entities. Entity Framework is a framework for providing object-relational mapping service on data models.

This section contains these topics:

- [Overview of Entity Framework](#)
- [Language Integrated Query and Entity SQL](#)
- [Mapping Oracle Data Types to EDM Types](#)
- [Oracle Number Default Data Type Mapping and Customization](#)
- [Migrating Existing Entity Framework 5 Applications to Entity Framework 6](#)
- [Code First](#)
- [Unsupported Entity Framework Features](#)

Note:

ADO.NET Entity Framework and LINQ to Entities is not supported by ODP.NET Core.

Overview of Entity Framework

ODP.NET 11.2.0.3.0 and higher includes support for the ADO.NET Entity Framework and LINQ to Entities. ODP.NET also supports Entity SQL.

Entity Framework is a framework for providing object-relational mapping service on data models. Entity Framework addresses the impedance mismatch between the relational database format and the client's preferred object format.

Entity Framework and LINQ provides productivity benefits for the .NET developer. It abstracts the database's data model from the application's data model. Working with object-relational data becomes easier with Entity Framework's tools. Oracle's integration with Entity Framework and LINQ enables Oracle .NET developers to take advantage of all these productivity benefits.

 **Note:**

- Entity Framework and LINQ to Entities support is included in ODP.NET for .NET Framework 4. ODP.NET for .NET Framework 2.0 does not support the ADO.NET Entity Framework and LINQ to Entities.
- Code First is supported starting with Entity Framework 6 and higher.
- Binding scalar parameters is supported with ODP.NET and Entity Framework. In Entity Framework, parameter binding by name is supported. Binding by position is not supported.

Entity data models can be generated from Oracle database schemas. Schemas can be generated from entity data models. These Oracle entity data models can be queried and manipulated using Visual Studio and ODP.NET. Oracle supports Code First, Database First, and Model First modeling approaches. Specifying filters on the Visual Studio Server Explorer data connection enables the Entity Data Model Wizard to also filter Oracle database objects that are fetched and displayed.

LINQ to Entities can perform queries on the Oracle Database using ODP.NET, including using LINQ to Entities built-in functions. `INSERTS`, `UPDATES`, and `DELETES` can be executed using Oracle stored procedures, or by using the `ObjectContext.SaveChanges` method.

ODP.NET supports function import of Oracle stored procedures that Entity Framework can then execute. These Oracle function imports can return a collection of scalar, complex, and entity types, including returning an Oracle implicit result set as an entity type. Implicit result set binding is supported using Oracle `REF CURSOR`.

 **See Also:**

- [Implicit REF CURSOR Binding](#).
- For a tutorial on how to use Entity Framework, Language Integrated Query (LINQ), and generate Data Definition Language (DDL) scripts using Model First, refer to:

<http://www.oracle.com/webfolder/technetwork/tutorials/obe/db/dotnet/EntityFrameworkOBE/EntityFrameworkOBE.htm>

Language Integrated Query and Entity SQL

Language Integrated Query (LINQ) defines a set of operators that can be used to query, project, and filter data in arrays, enumerable classes, XML, relational databases, and other data sources. One form of LINQ, LINQ to Entities, allows querying of Entity Framework data sources. ODP.NET supports Entity Framework such that the Oracle database can participate in object-relational modeling and LINQ to Entities queries.

Entity SQL is a language that enables querying of Entity Framework conceptual models. It allows querying Entity Framework entities and relationships in a format that is similar to SQL. ODP.NET supports querying Oracle databases through Entity SQL.

LINQ and Entity SQL syntax are generally data source neutral.

Mapping Oracle Data Types to EDM Types

The ODP.NET manifest file describes the primitive types, such as `VARCHAR2` and `Number`, and the Entity Data Model (EDM) types, such as `string` and `Int32`, that they map to. It also includes the facets for each EDM type.

ODP.NET does not support Time literals and canonical functions related to the Time type.

Oracle considers both `NULL` and empty strings to be `NULL` strings and are considered to be equal. Operations, such as `Equals()`, `Length()`, and `Trim()` on such strings will result in a `NULL` string.

[Table 4-1](#) maps the Oracle data types to their corresponding EDM types. The table also includes details about provider type attributes and the EDM type facets associated with each Oracle data type.

Table 4-1 Mapping of Oracle Data Types and EDM Types

Oracle Data Types	EDM Types (Primitive-TypeKind)	Provider Type Attributes: Name and Value	EDM Type Facets
Bfile	Binary	<ul style="list-style-type: none"> Equal Comparable: False Order Comparable: False 	EDM Type Facets for Bfile
Binary_Double	Double	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Binary_Float	Single	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Binary_Integer	Int32	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Blob	Binary	<ul style="list-style-type: none"> Equal Comparable: False Order Comparable: False 	EDM Type Facets for Blob
Char	String	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Char

Table 4-1 (Cont.) Mapping of Oracle Data Types and EDM Types

Oracle Data Types	EDM Types (Primitive-TypeKind)	Provider Type Attributes: Name and Value	EDM Type Facets
Clob	String	<ul style="list-style-type: none"> Equal Comparable: False Order Comparable: False 	EDM Type Facets for Clob
Date	DateTime	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Date
Float	Decimal	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Float
Int	Int32	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Interval Day To Second	Decimal	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Interval Day To Second
Interval Year To Month	Decimal	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Interval Year To Month
Long	String	<ul style="list-style-type: none"> Equal Comparable: False Order Comparable: False 	EDM Type Facets for Long
Long Raw	Binary	<ul style="list-style-type: none"> Equal Comparable: False Order Comparable: False 	EDM Type Facets for Long Raw
NChar	String	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for NChar
NClob	String	<ul style="list-style-type: none"> Equal Comparable: False Order Comparable: False 	EDM Type Facets for NClob
Nested Table		Not Applicable	Not Applicable and Not Supported

Table 4-1 (Cont.) Mapping of Oracle Data Types and EDM Types

Oracle Data Types	EDM Types (Primitive-TypeKind)	Provider Type Attributes: Name and Value	EDM Type Facets
Number(1,0) Number(2,0) Number(3,0) Number(4,0) Number(5,0)	Int16	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Number(6,0) Number(7,0) Number(8,0) Number(9,0) Number(10,0)	Int32	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Number(11,0) Number(12,0) Number(13,0) Number(14,0) Number(15,0) Number(16,0) Number(17,0) Number(18,0) Number(19,0)	Int64	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Number (all other cases)	Decimal	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Number
NVarchar2	String	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for NVarchar2
Object		Not Applicable	Not Applicable and Not Supported
Raw	Binary	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Raw
Raw(16)	Guid	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Ref		Not Applicable	Not Applicable and Not Supported

Table 4-1 (Cont.) Mapping of Oracle Data Types and EDM Types

Oracle Data Types	EDM Types (Primitive-TypeKind)	Provider Type Attributes: Name and Value	EDM Type Facets
ROWID	String	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for ROWID
Smallint	Int16	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	Not Applicable
Timestamp	DateTime	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Timestamp
Timestamp with Local Time Zone	DateTime	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Timestamp with Local Time Zone
Timestamp with Time Zone	DateTimeOffset	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Timestamp with Time Zone
UROWID (size)	Binary	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for UROWID
Varchar2	String	<ul style="list-style-type: none"> Equal Comparable: True Order Comparable: True 	EDM Type Facets for Varchar2
VArray		Not Applicable	Not Applicable and Not Supported
XMLType	String	<ul style="list-style-type: none"> Equal Comparable: False Order Comparable: False 	EDM Type Facets for XMLType

EDM Type Facets

The following sections enumerate the EDM type facets for the preceding Oracle data types. The first column of each table displays the EDM type facet names for the Oracle data type. Subsequent columns list the facet attribute names and displays their respective values.

EDM Type Facets for Bfile

Table 4-2 EDM Type Facets for Bfile

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 2147483648 Constant: True
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for Blob

Table 4-3 EDM Type Facets for Blob

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 2147483648 Constant: True
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for Char

Table 4-4 EDM Type Facets for Char

Facet Name	Attributes Name and Value
MaxLength	Minimum: 1 Maximum: 2000 DefaultValue: 2000 Constant: False
Unicode	DefaultValue: False Constant: True
FixedLength	DefaultValue: True Constant: True

EDM Type Facets for Clob

Table 4-5 EDM Type Facets for Clob

Facet Name	Attributes Name and Value
MaxLength	DefaultValue: 2147483647 Constant: True

Table 4-5 (Cont.) EDM Type Facets for Clob

Facet Name	Attributes Name and Value
Unicode	DefaultValue: False Constant: True
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for Date**Table 4-6 EDM Type Facets for Date**

Facet Name	Attributes Name and Value
Precision	Constant: True DefaultValue: 0

EDM Type Facets for Float**Table 4-7 EDM Type Facets for Float**

Facet name	Attributes Name and Value
Precision	Minimum: 0 Maximum: 126 DefaultValue: 0 Constant: False
Scale	Minimum: 0 Maximum: 38 DefaultValue: 0 Constant: False

EDM Type Facets for Interval Day To Second**Table 4-8 EDM Type Facets for Interval Day To Second**

Facet name	Attributes Name and Value
Precision	Minimum: 1 Maximum: 251 DefaultValue: 251 Constant: False

Table 4-8 (Cont.) EDM Type Facets for Interval Day To Second

Facet name	Attributes Name and Value
Scale	Minimum: 0 Maximum: 9 DefaultValue: 0 Constant: False

 **Note:**

EDM types do not support `TimeSpan`.

Use `Decimal` to represent the total number of seconds. An application can obtain a `TimeSpan` by using the `TimeSpan.FromSeconds` static method.

EDM Type Facets for Interval Year To Month

Table 4-9 EDM Type Facets for Interval Year To Month

Facet name	Attributes Name and Value
Precision	Minimum: 1 Maximum: 250 DefaultValue: 250 Constant: False
Scale	Minimum: 0 Maximum: 9 DefaultValue: 0 Constant: False

EDM Type Facets for Long

Table 4-10 EDM Type Facets for Long

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 2147483647 Constant: True
Unicode	DefaultValue: False Constant: True
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for Long Raw**Table 4-11 EDM Type Facets for Long Raw**

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 2147483647 Constant: True
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for NChar**Table 4-12 EDM Type Facets for NChar**

Facet name	Attributes Name and Value
MaxLength	Minimum: 1 Maximum: 1000 DefaultValue: 1000 Constant: False
Unicode	DefaultValue: True Constant: True
FixedLength	DefaultValue: True Constant: True

 **Note:**

For `NChar`, the actual data is subject to the maximum byte limit of 2000.

The value of 1000 for `Maximum` and `DefaultValue` allows the EDM wizard to display columns of `NCHAR(1000)`, where 1000 is the maximum number of characters allowed in DDL.

EDM Type Facets for NClob**Table 4-13 EDM Type Facets for NClob**

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 2147483647 Constant: True
Unicode	DefaultValue: True Constant: True

Table 4-13 (Cont.) EDM Type Facets for NClob

Facet name	Attributes Name and Value
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for Number

Table 4-14 EDM Type Facets for Number

Facet name	Attributes Name and Value
Precision	Minimum: 1 Maximum: 38 DefaultValue: 38 Constant: False
Scale	Minimum: 0 Maximum: 38 DefaultValue: 0 Constant: False

EDM Type Facets for NVarchar2

Table 4-15 EDM Type Facets for NVarchar2

Facet name	Attributes Name and Value
MaxLength	Minimum: 1 Maximum: 2000 DefaultValue: 2000 Constant: False
Unicode	DefaultValue: True Constant: True
FixedLength	DefaultValue: False Constant: True

 **Note:**

For NVARCHAR2, the actual data is subject to the maximum byte limit of 4000.

The value of 2000 for Maximum and DefaultValue allows the EDM wizard to display columns of NVARCHAR2(2000), where 2000 is the maximum number of characters allowed in DDL.

EDM Type Facets for Raw

Table 4-16 EDM Type Facets for Raw

Facet name	Attributes Name and Value
MaxLength	Minimum: 1 Maximum: 2000 Constant: False
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for ROWID

Table 4-17 EDM Type Facets for ROWID

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 18 Constant: True
Unicode	DefaultValue: False Constant: True
FixedLength	DefaultValue: True Constant: True

EDM Type Facets for Timestamp

Table 4-18 EDM Type Facets for Timestamp

Facet name	Attributes Name and Value
Precision	Minimum: 0 Maximum: 9 DefaultValue: 6 Constant: False

EDM Type Facets for Timestamp with Local Time Zone

Table 4-19 EDM Type Facets for Timestamp with Local Time Zone

Facet name	Attributes Name and Value
Precision	Minimum: 0 Maximum: 9 DefaultValue: 6 Constant: False

EDM Type Facets for Timestamp with Time Zone

Table 4-20 EDM Type Facets for Timestamp with Time Zone

Facet name	Attributes Name and Value
Precision	Minimum: 0 Maximum: 9 DefaultValue: 6 Constant: False

EDM Type Facets for UROWID

Table 4-21 EDM Type Facets for UROWID

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 4000 Constant: True
FixedLength	DefaultValue: True Constant: True

EDM Type Facets for Varchar2

Table 4-22 EDM Type Facets for Varchar2

Facet name	Attributes Name and Value
MaxLength	Minimum: 1 Maximum: 4000 DefaultValue: 4000 Constant: False
Unicode	DefaultValue: False Constant: True
FixedLength	DefaultValue: False Constant: True

EDM Type Facets for XMLType

Table 4-23 EDM Type Facets for XMLType

Facet name	Attributes Name and Value
MaxLength	DefaultValue: 2147483647 Constant: True
Unicode	DefaultValue: True Constant: True
FixedLength	DefaultValue: False Constant: True

Oracle Number Default Data Type Mapping and Customization

This section describes the default number mapping behavior and how to customize it for your application. You can configure a custom mapping in the .NET configuration file to override the default mapping for each Oracle `NUMBER(p,0)`, which represents integer values.

Oracle `NUMBER` data types that represent integers do not have a matching .NET integer data type with exactly the same range of acceptable values. ODP.NET uses a default mapping that ensures any .NET integer type values can be stored within the Oracle database without requiring custom data type mapping. However, it is possible that Oracle `NUMBER(p,0)` column data can be larger than what a .NET data type can hold when retrieving values from the database.

For example, in Entity Framework 6, Oracle `NUMBER(3,0)` has a default mapping to .NET `Byte`. Oracle `NUMBER(3,0)` can store a value up to 999, while a .NET `Byte` can store up to the value of 255. If you expect the Oracle data to exceed 255, modify the mapping to a larger numeric data type, such as a .NET `Int16`. Setting up this custom mapping allows you to consume the data in .NET without encountering an error. When such a custom mapping is used, be cautious not to insert a .NET `Int16` value beyond what an Oracle `NUMBER(3,0)` column can hold. Trying to insert `Int16.MaxValue` (i.e. 32,767) into a `NUMBER(3,0)` column will cause an Oracle Database error.

Entity Framework 5 and Earlier Mapping and Customization

[Example 4-1](#) shows an ODP.NET, Unmanaged Driver sample `app.config` file that uses custom mapping to map the `Number(1,0)` Oracle data type to the `bool` EDM type. For example, `Number(1,0)`, which is mapped to `Int16` by default, can be custom mapped to the .NET `Bool` or .NET `Byte` type. This example maps `Number(3,0)` to `byte`, and sets the maximum precisions for the `Int16`, `Int32`, and `Int64` data types to 4, 9, and 18 respectively.

[Example 4-2](#) shows the same changes as [Example 4-1](#), but using the traditional ODP.NET, Unmanaged Driver `app.config` format.

[Example 4-3](#) shows a ODP.NET, Managed Driver sample `app.config` file.

Example 4-1, Example 4-2, and Example 4-3 customizes the mappings as follows:

Oracle Type	Default EDM Type	Custom EDM Type
Number(1,0)	Int16	bool
Number(2,0) to Number(3,0)	Int16	byte
Number(4,0)	Int16	Int16
Number(5,0)	Int16	Int32
Number(6,0) to Number(9,0)	Int32	Int32
Number(10,0)	Int32	Int64
Number(11,0) to Number(18,0)	Int64	Int64
Number(19,0)	Int64	Decimal

Custom mapping configures the maximum precision of the Oracle `Number` type that would map to the .NET/EDM type. So, for example, the preceding custom application configuration file configures ODP.NET to map `Number(10,0)` through `Number(18,0)` to `Int64`, as opposed to the default range of `Number(11,0)` through `Number(19,0)` for `Int64`.

 **Note:**

- Custom mapping does not require you to map all the .NET/EDM types. For example, if custom mapping is required just for `Int16`, then having a single entry for `Int16` is sufficient. Default mapping gets used for the other types.
- When using Model First, a `Byte` attribute is mapped to `Number(3,0)` by default. However, when a model is generated for a `Number(3,0)` column, it gets mapped to `Int16` by default unless custom mapping for `Byte` is specified.

You must make sure that your mappings allow the data to fit within the range of the .NET/EDM type and the `Number(p, s)` type. If you select a .NET/EDM type with a range too small for the Oracle `Number` data, then errors will occur during data retrieval. Also, if you select a .NET/EDM type, and the corresponding data is too big for the Oracle `Number` column, then INSERTs and UPDATEs to the Oracle database will error out.

Example 4-1 First Sample ODP.NET, Unmanaged Driver Application Configuration File to Custom Map the Number (p,0) Data Type

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.unmanageddataaccess.client>
    <version number="*">
      <edmMappings>
        <edmMapping dataType="number">
```

```

        <add name="bool" precision="1"/>
        <add name="byte" precision="3" />
        <add name="int16" precision="4" />
        <add name="int32" precision="9" />
        <add name="int64" precision="18" />
    </edmMapping>
</edmMappings>
</version>
</oracle.unmanageddataaccess.client>
</configuration>

```

Example 4-2 Second Sample ODP.NET, Unmanaged Driver Application Configuration File to Custom Map the Number (p,0) Data Type

```

<?xml version="1.0" encoding="utf-8"?>
<configuration>
  <connectionStrings>
  </connectionStrings>
  <oracle.dataaccess.client>
    <settings>
      <add name="bool" value="edmmapping number(1,0)" />
      <add name="byte" value="edmmapping number(3,0)" />
      <add name="int16" value="edmmapping number(4,0)" />
      <add name="int32" value="edmmapping number(9,0)" />
      <add name="int64" value="edmmapping number(18,0)" />
    </settings>
  </oracle.dataaccess.client>
</configuration>

```

Example 4-3 Sample ODP.NET, Managed Driver Application Configuration File to Custom Map the Number Data Type

```

<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.manageddataaccess.client>
    <version number="*">
      <edmMappings>
        <edmMapping dataType="number">
          <add name="bool" precision="1"/>
          <add name="byte" precision="3" />
          <add name="int16" precision="4" />
          <add name="int32" precision="9" />
          <add name="int64" precision="18" />
        </edmMapping>
      </edmMappings>
    </version>
  </oracle.manageddataaccess.client>
</configuration>

```

Entity Framework 6 Mapping and Customization

ODP.NET 12.1.0.2 introduces a new .NET configuration setting format for both managed and unmanaged ODP.NET. This new setting format applies only for use with Entity Framework 6 and Entity Data Model mappings, including Code First, Database First, and Model First use cases. Developers can continue using the existing ODP.NET format for non-Entity Framework 6 applications.

This new format unifies how ODP.NET, Managed and Unmanaged Drivers sets their configuration values and supports auto-completion.

The following is an example of an `edmMappings` section for ODP.NET, Managed Driver:

```
<oracle.manageddataaccess.client>
  <version number="*">
    <edmMappings>
      <edmNumberMapping>
        <add NETType="bool" MinPrecision="1" MaxPrecision="1" DBType="Number" />
        <add NETType="byte" MinPrecision="2" MaxPrecision="3" DBType="Number" />
        <add NETType="int16" MinPrecision="4" MaxPrecision="5" DBType="Number" />
        <add NETType="int32" MinPrecision="6" MaxPrecision="10" DBType="Number" />
        <add NETType="int64" MinPrecision="11" MaxPrecision="19" DBType="Number" />
      </edmNumberMapping>
    </edmMappings>
  </version>
</oracle.manageddataaccess.client>
```

Where:

- `DBType` is the Oracle Database data type
- `NETType` is the .NET data type that the Oracle data type maps to
- `MinPrecision` is the minimum range the Oracle data type will map to the .NET type
- `MaxPrecision` is the maximum range the Oracle data type will map to the .NET type

The following is an example of an `edmmappings` section for ODP.NET, Unmanaged Driver. It is exactly same format as the managed driver with the exception of the opening and closing tags.

```
<oracle.unmanageddataaccess.client>
  <version number="*">
    <edmMappings>
      <edmNumberMapping>
        <add NETType="bool" MinPrecision="1" MaxPrecision="1" DBType="Number" />
        <add NETType="byte" MinPrecision="2" MaxPrecision="3" DBType="Number" />
        <add NETType="int16" MinPrecision="4" MaxPrecision="5" DBType="Number" />
        <add NETType="int32" MinPrecision="6" MaxPrecision="10" DBType="Number" />
        <add NETType="int64" MinPrecision="11" MaxPrecision="19" DBType="Number" />
      </edmNumberMapping>
    </edmMappings>
  </version>
</oracle.unmanageddataaccess.client>
```

New Default Mappings

For Entity Framework 6, ODP.NET 12.1.0.2 introduces new default mappings that apply to Code First, Database First, and Model First scenarios. These changes were necessary to support Code First interoperability.

- .NET Booleans map to Oracle `Number(1,0)` and vice-versa by default
- .NET Bytes map to Oracle `Number(2,0)` and `Number(3,0)` and vice-versa by default

This default behavior can be changed by providing an alternative data type mapping by configuring the section of the .NET config file.

Data Type Mapping and Customization Process

To enable custom mapping, add the mapping information to the .NET config file *prior* to EDM creation.

If the EDM was created already before providing the mapping information, then you can *modify* the mappings either through the Visual Studio tools or manually. Using Visual Studio, go to the EDM Model Browser page. Right-click on the table(s) requiring new data type mapping and select **Table Mapping** from the pop-up menu. The **Mapping Details** window will appear usually at the bottom of your screen. Update **Column Mappings** as desired.

If you need to *add* or *delete* mappings, find the **Type** values in the CSDL mapping section of your project's existing EDMX file. Add or delete those **Type** values to the .NET data types you want the application to use. In the example below, the property name types for `BOOLCOL` and `BYTECOL` are added to the CSDL and mapped to Boolean and Byte, respectively.

Example Mapping Before CSDL Customization:

```
<Property Name="INT16COL" Type="Int16" Nullable="false" />
```

Example Mapping After CSDL Customization:

```
<Property Name="BOOLCOL" Type="Boolean" Nullable="false" />
<Property Name="BYTECOL" Type="Byte" Nullable="false" />
<Property Name="INT16COL" Type="Int16" Nullable="false" />
```

You can employ combinations of these customization possibilities depending on your planned mapping changes. If *many* tables and *many* columns require mapping changes, it is most efficient to delete the EDMX file and regenerate the data model. If a *few* tables and *many* columns require changes, then delete the affected tables, save the EDMX file, and select **Update Model from Database...** to include those tables again. If only a *single* table and *one* or *two* columns require changes, then modify the EDMX either manually or by using the **Mapping Details** window.

Note:

When using the EDM wizard to create a complex type from a function import, any custom EDM type mappings specified will not be applied automatically. The EDM wizard uses the default type mappings. Developers must then manually edit the resulting complex type. Developers begin this process after the complex type is generated. Any type declaration (field, property, constructor parameter, etc.) in the complex object which has an undesired type mapping, such as Decimal rather than Boolean, should be manually edited to the desired type.

StoreGeneratedPattern Enumeration

The following sections describe the Identity attribute and the Virtual column.

Identity Attribute

Oracle Database 12c (12.1) and later versions support table or view Identity attribute columns. Oracle has three Identity attribute types. When the EDM wizard generates a data model from an Oracle Identity attribute-containing table or view, ODP.NET will set the value of `StoreGeneratedPattern` to `Identity` in the `.edmx` file for any of three Oracle Identity types. The Identity attribute-associated column will use the server-generated value during `INSERT`; hence, application developers no longer need to create a sequence nor trigger. If the .NET application attempts to set the Identity attribute itself, this value will be ignored.

For Oracle Database 11g Release 2 (11.2) and earlier versions that do not support Identity columns, application developers can manually set `StoreGeneratedPattern` to `Identity` in columns through the entity model designer Properties after model generation, then create an `INSERT` trigger. Depending on the data type, a sequence may not be necessary if a server function, such as `sys_guid()`, can generate the value for the column.

Virtual Column

Oracle Database 11g (11.1) and later versions can store expressions directly in base tables as Virtual columns, also known as Generated columns. Virtual columns cannot be inserted into or updated. ODP.NET will not automatically set `StoreGeneratedPattern` to `Computed` in the EF model for Virtual columns. To avoid errors, application developers need to add or change the value of `StoreGeneratedPattern` to `Computed` for Virtual columns after the model generation. Once done, Virtual columns are excluded from `INSERTS` and `UPDATES` upon calling `SaveChanges()`.

Resolving Compilation Errors When Using Custom Mapping

If the custom mapping in a .NET configuration file has changed, then regenerate the data model to solve compilation errors introduced by the changes.

Under certain scenarios, custom mapping may cause compilation errors when a project that uses custom mapping is loaded by Visual Studio. One specific scenario is when Visual Studio opens a project with an existing custom mapping that now generates errors when those errors did not exist before. You may use the following workaround for such scenarios:

1. Open Visual Studio Help, About Microsoft Visual Studio. Click **OK** to exit the dialog box.
Alternatively, open the to-be-used connection in Server Explorer.
2. Compile the project again to eliminate the compilation errors.

Mapping Boolean and Guid Parameters in Custom INSERT, UPDATE, and DELETE Stored Procedures

When using your custom `INSERT`, `UPDATE`, or `DELETE` stored procedure in Stored Procedure Mapping, the following error might occur:

```
Error 2042: Parameter Mapping specified is not valid.
```


This can happen if a `Number` parameter has been mapped to a `Boolean` attribute, or if a `RAW` parameter has been mapped to a `Guid` attribute.

The solution is to manually add `Precision="1"` for the `Number` parameter, and `MaxLength="16"` for the `RAW` parameter of your stored procedure in the SSDL.

Migrating Existing Entity Framework 5 Applications to Entity Framework 6

To migrate existing Database First Entity Framework 5 applications to Entity Framework 6, use the following instructions. The first four steps are generic to all Entity Framework applications. The last four steps are specific to Oracle deployments.

1. Uninstall Entity Framework 5 in Visual Studio Package Manager Console. For example,

```
Uninstall-Package EntityFramework
```

2. Install Entity Framework 6 in Package Manager Console. For example,

```
Install-Package EntityFramework -Version 6.0.2
```

This step adds Entity Framework 6 to the `configSections` entry and adds a new section called `entityFramework`.

3. Delete the following namespaces from your application:

```
// C#
using System.Data.EntityClient;
using System.Data.Objects;
```

4. Add the following namespaces to your application:

```
// C#
using System.Data.Entity.Core.EntityClient;
using System.Data.Entity.Core.Objects;
```

5. Add the Oracle Entity Framework 6 provider configuration information to the .NET config file in the `providers` section. Modify the ODP.NET version if using a version besides 6.121.2.0. If you installed the ODP.NET NuGet package, you can skip this step as the NuGet install has already added made this change.

```
<provider invariantName="Oracle.DataAccess.Client"
type="Oracle.DataAccess.EntityFramework.EFOracleProviderServices,Oracle.DataAccess
s.EntityFramework, Version=6.121.2.0, Culture=neutral,
PublicKeyToken=89b483f429c47342" />
```

```
<provider invariantName="Oracle.ManagedDataAccess.Client"
type="Oracle.ManagedDataAccess.EntityFramework.EFOracleProviderServices,Oracle.Ma
nagedDataAccess.EntityFramework, Version=6.121.2.0, Culture=neutral,
PublicKeyToken=89b483f429c47342" />
```

6. Add the `Oracle.ManagedDataAccess.EntityFramework` or `Oracle.DataAccess.EntityFramework` assembly as a reference to the project.
7. Modify the Oracle data type to .NET data type mappings as required by your application. See "[Entity Framework 6 Mapping and Customization](#)" for more details.
8. Rebuild the application.

Code First

Using the Entity Framework Code First modeling path, developers define the application domain model using source code rather than working directly with a designer or an XML-based configuration file. The classes defined within the source code become the model. The Code First model path offers an alternative to the existing Entity Framework Database First and Model First paths. Within Code First, the classes defined in code that comprise the model are known as Plain Old CLR Objects (POCOs). This name derives from the fact that these classes have no dependency upon Entity Framework itself and are independent of it.

Oracle's support for the Code First modeling path enables .NET developers to take advantage of Oracle Database benefits.



See Also:

[Configuring for Entity Framework Code First](#)

Mapping of .NET Types to Oracle Types

When using the Code First path, the model is defined by the application's classes and properties. The property data types need to be mapped to the Oracle Database table data types. The following table lists the default mapping of supported .NET types to Oracle types as well as how to map a String property to non-default Oracle types:

Table 4-24 Mapping of .NET Data Types to Oracle Data Types

.NET Data Type	Oracle Data Type	Mapping Method
Boolean	number(1, 0)	Use EDM Mapping Note: Requires use of EDM Mapping configuration. Reference the EDM Mapping sections in the documentation for additional information.
Byte	number(3, 0)	Use EDM Mapping Note: Requires use of EDM Mapping configuration. Reference the EDM Mapping sections in the documentation for additional information.
Byte[]	blob	Default
Int16	number(5, 0)	Default Note: The default mapping of integer types may be specified in the EDM Mapping configuration. Reference the EDM Mapping sections in the documentation for additional information.

Table 4-24 (Cont.) Mapping of .NET Data Types to Oracle Data Types

.NET Data Type	Oracle Data Type	Mapping Method
Int32	number(10, 0)	Default Note: The default mapping of integer types may be specified in the EDM Mapping configuration. Reference the EDM Mapping sections in the documentation for additional information.
Int64	number(19, 0)	Default Note: The default mapping of integer types may be specified in the EDM Mapping configuration. Reference the EDM Mapping sections in the documentation for additional information.
Decimal	number(18, 2)	Default
Single	binary_float	Default
Double	binary_double	Default
Guid	raw(16)	Default
DateTime	date	Default
DateTimeOffset	timestamp with time zone	Default
String	nclob	Default
String	clob	Set Unicode to false using IsUnicode() fluent API
String	nvarchar2	Set Max Length to <= 2000 using HasMaxLength() fluent API or MaxLength data annotation
String	varchar2	Set Max Length to <= 4000 using HasMaxLength() fluent API or MaxLength data annotation and set Unicode to false using IsUnicode() fluent API
String	nchar	Set Max Length to <= 1000 using HasMaxLength() fluent API or MaxLength annotation and Set Column Type to NCHAR using HasColumnType() fluent API or Column data annotation

Table 4-24 (Cont.) Mapping of .NET Data Types to Oracle Data Types

.NET Data Type	Oracle Data Type	Mapping Method
String	char	Set Max Length to <= 2000 using <code>HasMaxLength()</code> fluent API or <code>MaxLength</code> annotation and Set Column Type to CHAR using <code>HasColumnType()</code> fluent API or Column data annotation
String	Long	Set Column Type to LONG using <code>HasColumnType()</code> fluent API or Column data annotation Note: The long data type is deprecated and not recommended.
String	rowid	Set Column Type to ROWID using <code>HasColumnType()</code> fluent API or Column data annotation
String	urowid	Set Column Type to UROWID using <code>HasColumnType()</code> fluent API or Column data annotation

 **Note:**

The character based columns, namely, CHAR, NCHAR, VARCHAR2, NVARCHAR2 will be created using character semantics to be able to store the specified Max Length amount of characters. However, due to the Oracle database limit, these columns can store only up to 4000 bytes. As such, these columns may not be able to store 4000 characters even if Max Length is set to 4000 characters since one character may require multiple number of bytes of storage, depending on the data and the database character set. If the character data can be longer than 4000 bytes, it may be more appropriate to use CLOB or NCLOB column.

Influencing the Oracle Data Type Characteristics

The type mappings listed in the previous table represent the mappings that occur by default or what is known as convention in Entity Framework. As illustrated with the `String` type, you can influence the resulting Oracle Data Type for a property as well as characteristics of that data type. There are two Entity Framework methods to influence the resulting Oracle Data Type: Data Annotations and the Code First Fluent API. Data Annotations permit you to explicitly mark a class property with one or more attributes, whereas the Code First Fluent API permits you to use code rather than attributes to achieve the same goal. For additional information regarding the use of Data

Annotations and the Code First Fluent API refer to the MSDN Entity Framework documentation.

The following table illustrates the available functionality:

Table 4-25 Mapping of Data Annotations and the Code First Fluent APIs

Data Annotation	Fluent API	Purpose	Applies To
Key	HasKey	Set a property as the Primary Key.	All Scalar Types
Required	IsRequired	Set the database column as NOT NULL.	All
MaxLength	HasMaxLength	Specifies the maximum length of the property.	String
NotMapped	Ignore	Indicates the property is not mapped to a database column.	All
ConcurrencyCheck	IsConcurrencyToken	Indicates the column should be used for optimistic concurrency checking. Note: Do not use with an unbounded (no maximum length specified) string property as this will create a LOB column. Use of a LOB column in the concurrency check will result in an ORA-00932: inconsistent datatypes error.	All
TimeStamp	IsRowVersion	Indicates to create the column as a rowversion column.	Not Supported
Column	HasColumnType	Indicates the provider-specific type to use for the database column. Note: Must be a legal compatible type. For example a Date property is not legal to map to a number column. Use the TypeName property with the Column Data Annotation to specify the type.	All

Table 4-25 (Cont.) Mapping of Data Annotations and the Code First Fluent APIs

Data Annotation	Fluent API	Purpose	Applies To
N/A	IsUnicode	Indicates to create the column as an N-type, that is, nvarchar2 or ncllob. Default is true. Note: There is no Data Annotation equivalent for IsUnicode.	String
N/A	HasPrecision	Indicates the precision and scale for a decimal property. Note: There is no Data Annotation equivalent for HasPrecision.	Decimal

Code First Migrations

The Oracle Data Provider for .NET supports Code First Migrations functionality. The use of Code First Migrations with Oracle Database is supported through the Package Manager Console window migrations commands. For information on these commands, refer to the MSDN Code First Migrations documentation:

<http://msdn.microsoft.com/en-us/data/jj591621.aspx>

Code First Migrations utilizes a table known as the Migration History table for tracking migration operations as well as model changes. ODP.NET creates this table, by default, in the user schema specified in the context connection string. This table is named **__MigrationHistory**.

This table can be created in another user schema besides the user specified in the context connection string. This is accomplished through a process known as Migration History Table Customization, which is described in the following MSDN documentation.

<http://msdn.microsoft.com/en-us/data/dn456841>

Note:

- Changing the user schema for the table is the only supported customization.
- Code First Automatic Migrations is limited to working with the `dbo` schema only. Due to this limitation it is recommended to use code-based migrations, that is, add explicit migrations through the Add-Migration command.

Code First Migrations With No Supporting Code Migration File

When using Code First Migrations with ODP.NET, the migration history table may be dropped if no supporting code migration file existed prior to updating the database. Developers should ensure the supporting code migration file has been added prior to updating the database.

The following steps can remove the migration history table:

1. Execute application to create database objects
2. **Enable-Migrations** in the Package Manager Console
3. Make code change to POCO
4. **Update-Database** in the Package Manager Console

The following steps ensure the code migration file is created:

1. Execute application to create database objects
2. **Enable-Migrations** in the Package Manager Console
3. Make code change to POCO
4. **Add-Migration** in the Package Manager Console. This step will create the necessary code migration file.
5. **Update-Database** in the Package Manager Console

Code First Database Initialization

ODP.NET supports the following Code First Database Initializer methods:

- `CreateDatabaseIfNotExists` (default if none specified)
- `DropCreateDatabaseAlways`
- `DropCreateDatabaseIfModelChanges`
- `NullDatabaseInitializer`
- `MigrateDatabaseToLatestVersion`

These methods are documented on MSDN.

Due to differences in how Oracle and SQL Server define a database, database initialization actions work on all of the Oracle objects in the model. An Oracle Database is not created or dropped, rather the objects that compose the model are considered to be the database for these operations.

Oracle Database Object Creation

In order to support the client application, ODP.NET will create and maintain the required database objects. The following are the database objects created and maintained by the provider:

- Table
- Table Column
- Primary Key

- Foreign Key
- Index
- Sequence
- Trigger

 **Note:**

Sequences and triggers may be created in Oracle Database 11g Release 2 and earlier databases to support identity columns.

For objects which directly relate to a client application object, namely, a table which represents an application class and a table column which represents a class property, the object names used are those provided by the client. These object names must conform to the object identifier length limits for Oracle Database. For example, if a class name length exceeds the valid object identifier length in Oracle Database then the `ORA-00972: identifier is too long` exception will be raised at object creation time.

For the remaining objects, ODP.NET utilizes a name generation algorithm if the supplied name length exceeds the database identifier length limit. If the supplied name length does not exceed the database limit the name is used as-is. In all cases, the object name is created as a quoted identifier in order to preserve case and any special characters which may be part of the identifier.

In cases where the provider generates a name to comply with database identifier length limits, the name is composed of the following underscore separated elements:

- A substring of the original name (from the first character)
- A numeric suffix value calculated from the original name

The following example illustrates the results of the name generation algorithm using a simple POCO in the client application:

```
public class LongSamplePocoTestClassName
{
    [Key]
    public int Id { get; set; }

    [MaxLength(64)]
    public string Name { get; set; }
}
```

The default name for the Primary Key for the resulting table will be:

```
PK_LongSamplePocoTestClassNames
```

As this name contains 31 characters (single byte per character), it violates the database identifier restrictions. The rewritten Primary Key name will resemble the following value:

```
PK_LongSamplePocoTes_730795129
```

The algorithm is designed to utilize as many characters as possible from the original name such that the new name does not violate the identifier length restrictions.

Controlling Table Name and Owner

Through the use of Data Annotations or the Entity Framework Fluent API you may control the table name, as well as the table owner. For example, you may choose to explicitly set the table name to conform to your organization's naming standards or if you do not wish to, use the name Entity Framework provides. The `Table` Data Annotation is used to control both the table name and the owner. When using the Fluent API, the `ToTable` method is used to control the table name and the owner within the `OnModelCreating` override in your class which derives from `DbContext`.

The following examples use an incomplete class definition to illustrate these actions.

Setting the table name using a Data Annotation:

```
[Table("Employee")]
public class Employee
```

Setting the table name using the Fluent API:

```
protected override void OnModelCreating(DbModelBuilder modelBuilder)
{
    modelBuilder.Entity<Employee>().ToTable("Employee");
}
```

Setting the table name and the owner using a Data Annotation:

```
[Table("Employee ", Schema="TESTUSER")]
public class Employee
```

Setting the table name and the owner using the Fluent API:

```
protected override void OnModelCreating(DbModelBuilder modelBuilder)
{
    modelBuilder.Entity<Employee>().ToTable("Employee", "TESTUSER");
}
```

Note:

When using Data Annotations or the Fluent API as above to set the owner, it is required to also set the name.

Setting the Default Table Owner

Rather than set the table owner for each user table, Entity Framework 6 and higher allows you to set the default owner to be used. This is done by invoking the `HasDefaultSchema` method within the `OnModelCreating` override in your class, which derives from `DbContext`.

For example, the following code will cause all user tables to be created within the `TESTUSER` schema by default:

```
protected override void OnModelCreating(DbModelBuilder modelBuilder)
{
    modelBuilder.HasDefaultSchema("TESTUSER");
}
```

 **Note:**

The owner name is case-sensitive.

 **See Also:**

Oracle Database Administrator's Guide.

Using the Default Connection Factory

The default connection factory allows ODP.NET connections to be created by providing an Oracle connection string to the `DbContext` constructor. For example, the following entry could be used to configure the ODP.NET, Managed Driver default connection factory:

```
<defaultConnectionFactory
type="Oracle.ManagedDataAccess.EntityFramework.OracleConnectionFactory,
Oracle.ManagedDataAccess.EntityFramework,
Version=6.121.2.0,
Culture=neutral,
PublicKeyToken=89b483f429c47342" />
```

When using the default connection factory, the application supplies an Oracle connection string to the `DbContext` base constructor as follows:

```
public class TestContext : DbContext
{
    public TestContext()
        : base("<connection string>")
    {
    }
}
```

Where `<connection string>` is the ODP.NET connection string. This allows the application to connect to the database using code similar to the following:

```
using (var ctx = new TestContext())
{
    ...
}
```

For additional information please see the MSDN documentation for the `IDbConnectionFactory` interface:

<http://msdn.microsoft.com/en-us/library/system.data.entity.infrastructure.idbconnectionfactory%28v=vs.113%29.aspx>

Unsupported Entity Framework Features

The following items are not supported by the current release of the provider:

- Mapping Code First Insert, Update, Delete operations to Stored Procedures

- TimeStamp/RowVersion properties
- Custom Configuration
- Spatial Types
- Table-valued functions
- Asynchronous Query and Save
- Connection Resiliency
- Oracle synonyms

5

Oracle Data Provider for .NET Stored Procedures

This section discusses server-side features provided by Oracle Data Provider for .NET.

With the support for .NET stored procedures in Oracle Databases for Windows that Oracle Database Extensions for .NET provides, ODP.NET can be used to access Oracle data through the [implicit database connection](#) that is available from the context of the .NET stored procedure execution. Explicit user connections can also be created to establish connections to the database that hosts the .NET stored procedure or to other Oracle Databases.

See Also:

Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows

This section contains these topics:

- [Introducing .NET Stored Procedure Execution Using ODP.NET](#)
- [Limitations and Restrictions on ODP.NET Within .NET Stored Procedure](#)
- [Porting Client Application to .NET Stored Procedure](#)

Introducing .NET Stored Procedure Execution Using ODP.NET

Oracle Data Provider for .NET classes and APIs provide data access to the Oracle Database from a .NET client application and from .NET stored procedures and functions.

However, some limitations and restrictions exist when Oracle Data Provider for .NET is used within a .NET stored procedure. These are discussed in the next section.

The following is a simple .NET stored procedure example.

```
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

public class CLRLibrary1
{
    // .NET Stored Function returning the DEPTNO of the employee whose
    // EMPNO is 'empno'
    public static uint GetDeptNo(uint empno)
    {
```

```

uint deptno = 0;

// Create and open a context connection
OracleConnection conn = new OracleConnection();
if( OracleConnection.IsAvailable == true )
{
    conn.ConnectionString = "context connection=true";
}
else
{
    //set connection string for a normal client connection
    conn.ConnectionString = "user id=scott;password=tiger;" +
        "data source=oracle";
}
conn.Open();

// Create and execute a command
OracleCommand cmd = conn.CreateCommand();
cmd.CommandText = "SELECT DEPTNO FROM EMP WHERE EMPNO = :1";
cmd.Parameters.Add(":1",OracleDbType.Int32,empno,
System.Data.ParameterDirection.Input);
OracleDataReader rdr = cmd.ExecuteReader();
if (rdr.Read())
    deptno = (uint)rdr.GetInt32(0);
rdr.Close();
cmd.Dispose();
conn.Close();
return deptno;
} // GetDeptNo
} // CLRLibrary1

```

See Also:

- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows* for more information about how to create .NET Stored procedures
- [Table 5-1](#)

Limitations and Restrictions on ODP.NET Within .NET Stored Procedure

This section covers important concepts that apply when Oracle Data Provider for .NET is used within a .NET stored procedure.

Note:

ODP.NET, Managed Driver and ODP.NET Core do not support .NET stored procedures.

Implicit Database Connection

Within a .NET stored procedure, an implicit database connection is available for use to access Oracle data. This implicit database connection should be used rather than establishing a user connection because the [implicit database connection](#) is already established by the caller of the .NET stored procedure, thereby minimizing resource usage.

To obtain an `OracleConnection` object in a .NET stored procedure that represents the implicit database connection, set the `ConnectionString` property of the `OracleConnection` object to `"context connection=true"` and invoke the `Open` method. No connection string attributes can be used with `"context connection=true"`, except the `Statement Cache Size` attribute.

The availability of the implicit database connection can be checked at run time through the static `OracleConnection.IsAvailable` property. This property always returns `true` when Oracle Data Provider for .NET is used within a .NET stored procedure. Otherwise, `false` is returned.

Note:

DBLinks are not supported in .NET stored procedures.

Only one implicit database connection is available within a .NET stored procedure invocation. To establish more connections in addition to the implicit database connection, an explicit connection must be created. When the `Close` method is invoked on the `OracleConnection` that represents the implicit database connection, the connection is not actually closed. Therefore, the `Open` method of the same or another `OracleConnection` object can be invoked to obtain the connection that represents the implicit database connection.

The implicit database connection can only be acquired by the `Open` method invocation by a native Oracle thread that initially invokes the .NET stored procedure. However, threads spawned from the native Oracle thread can use implicit database connections that are obtained by the native Oracle thread.

See Also:

["IsAvailable"](#)

Transaction Support

The .NET stored procedure execution automatically inherits the current transaction on the implicit database connection. No explicit transaction can be started, committed, or rolled back inside a .NET stored procedure on a Context connection. However, explicit transaction can be started, committed, or rolled back inside a .NET stored procedure on a Client connection.

For example, `OracleConnection.BeginTransaction` is not allowed inside a .NET stored procedure for a context connection, but is allowed for a client connection. .NET stored procedures do not support distributed transactions. If you have enlisted a client connection in a distributed transaction and call a .NET stored procedure or function, an error occurs.

If a .NET stored procedure or function performs operations on the database that are required to be part of a transaction, the transaction must be started prior to calling the .NET stored procedure. Any desired commit or rollback must be performed after returning from the .NET stored procedure or function.

The following example consists of a client application and a .NET stored procedure, `InsertRecordSP`, that inserts an employee record into an `EMP` table.

Example (.NET Stored Procedure)

```
using System;
using System.Data;
using Oracle.DataAccess.Client;
// This class represents an Oracle .NET stored procedure that inserts
// an employee record into an EMP table of SCOTT schema.
public class InsertRecordSP
{
    // This procedure will insert a row into the emp database
    // For simplicity we are using only two parameters, the rest are hard coded
    public static void InsertRecord( int EmpNo, string EmpName )
    {
        if(OracleConnection.IsAvailable == true )
        {
            OracleConnection conn = new OracleConnection(
                "context connection=true");
            conn.Open();
            // Create new command object from connection context
            OracleCommand Cmd = conn.CreateCommand();
            Cmd.CommandText = "INSERT INTO EMP( EMPNO, ENAME, JOB, " +
                "MGR, HIREDATE, SAL, COMM, DEPTNO ) " +
                "VALUES ( :1, :2, 'ANALYST', 7566, " +
                "'06-DEC-04', 5000, 0, 20 )";
            Cmd.Parameters.Add( ":1", OracleDbType.Int32,
                EmpNo, ParameterDirection.Input );
            Cmd.Parameters.Add( ":2", OracleDbType.Varchar2,
                EmpName, ParameterDirection.Input );
            Cmd.ExecuteNonQuery();
        }
    }
}
```

Example (Client Application)

The example enters new employee, Bernstein, employee number 7950, into the `EMP` table.

```
// C#
// This sample demonstrates how to start the transaction with ODP.NET client
// application and execute an Oracle .NET stored procedure that performs
// a DML operation. Since .NET stored procedure inherits the current
// transaction from the implicit database connection, DML operation
// in .NET stored procedure will not be in auto-committed mode.
// Therefore, it is up to the client application to do a COMMIT or ROLLBACK
// after returning from .NET stored procedure
using System;
```

```

using System.Data;
using Oracle.DataAccess.Client;
// In this class we are starting a transaction on the client side and
// executing a .NET stored procedure, which inserts a record into EMP
// table and then verifies record count before and after COMMIT statement
class TransactionSample
{
    static void Main(string[] args)
    {
        OracleConnection Conn = null;
        OracleTransaction Txn = null;
        OracleCommand Cmd = null;
        try
        {
            Console.WriteLine( "Sample: Open DB connection in non auto-committed "
                + "mode," +
                "DML operation performed by .NET stored " +
                "procedure doesn't have an effect before COMMIT " +
                "is called." );
            // Create and Open oracle connection
            Conn = new OracleConnection();
            Conn.ConnectionString = "User Id=scott;Password=tiger;" +
                "Data Source=oracle;";
            Conn.Open();
            // Start transaction
            Txn = Conn.BeginTransaction( IsolationLevel.ReadCommitted );
            // Create command object
            Cmd = new OracleCommand();
            Cmd.Connection = Conn;
            Cmd.CommandType = CommandType.StoredProcedure;
            Cmd.CommandText = "InsertRecord"; // .NET Stored procedure
            // Parameter settings
            OracleParameter EmpNoPrm = Cmd.Parameters.Add(
                "empno", OracleDbType.Int32 );
            EmpNoPrm.Direction = ParameterDirection.Input;
            EmpNoPrm.Value = 7950;
            OracleParameter EmpNamePrm = Cmd.Parameters.Add(
                "ename", OracleDbType.Varchar2, 10 );
            EmpNamePrm.Direction = ParameterDirection.Input;
            EmpNamePrm.Value = "Bernstein";
            // Execute .NET stored procedure
            Cmd.ExecuteNonQuery();
            Console.WriteLine( "Number of record(s) before COMMIT {0}",
                RecordCount() );
            Txn.Commit();
            Console.WriteLine( "Number of record(s) after COMMIT {0}",
                RecordCount() );
        }
        catch( OracleException OE )
        {
            Console.WriteLine( OE.Message );
        }
        finally
        {
            // Cleanup objects
            if( null != Txn )
                Txn.Dispose();
            if( null != Cmd )
                Cmd.Dispose();
            if( null != Conn && Conn.State == ConnectionState.Open )
                Conn.Close();
        }
    }
}

```



```

    }
}
static int RecordCount()
{
    int EmpCount = 0;
    OracleConnection Conn = null;
    OracleCommand Cmd = null;
    try
    {
        Conn = new OracleConnection( "User Id=scott;Password=tiger;" +
            "Data Source=oracle;" );
        Conn.Open();
        Cmd = new OracleCommand( "SELECT COUNT(*) FROM EMP", Conn );
        Object o = Cmd.ExecuteScalar();
        EmpCount = Convert.ToInt32(o.ToString());
    }
    catch( OracleException OE )
    {
        Console.WriteLine( OE.Message );
    }
    finally
    {
        if( null != Cmd )
            Cmd.Dispose();
    }
    return EmpCount;
}
}

```

Unsupported SQL Commands

Transaction controls commands such as `COMMIT`, `ROLLBACK`, and `SAVEPOINT` are not supported in a .NET stored procedure.

Data definition commands such as `CREATE` and `ALTER` are not supported with an implicit database connection, but they are supported with an explicit user connection in a .NET stored procedure.

Oracle User-Defined Type (UDT) Support

UDTs are not supported within a context connection but they are supported with a client connection. UDTs are not supported as parameters to .NET stored procedures.

Porting Client Application to .NET Stored Procedure

All classes and class members provide the same functionality for both client applications and .NET stored procedures, unless it is otherwise stated.

[Table 5-1](#) lists those classes or class members that have different behavior depending on whether or not they are used in a client application or in a .NET stored procedure.

Column Headings

The column headings for this table are:

Client application: The client application.

Implicit connection: The implicit database connections in a .NET stored procedure.

Explicit connection: The explicit user connections in a .NET stored procedure.

Table 5-1 API Support Comparison Between Client Application and .NET Stored Procedure

Class or Class Members	Client Application	Implicit Connection/Explicit Connection
OnChangeEventHandler Delegate -all members	Yes	No/No
OracleDependency Class -all members	Yes	No/No
OracleNotificationEventArgs Class -all members	Yes	No/No
OracleNotificationRequest Class -all members	Yes	No/No
OracleFailoverEventArgs Class -all members	Yes	No/No
OracleFailoverEventHandler Delegate -all members	Yes	No/No
OracleTransaction Class -all members	Yes	No/No
OracleCommand Class -Transaction Property	Yes	No: Always returns null /No: Always returns null.
OracleConnection Class -ConnectionTimeout Property	Yes	Yes: Implicit database connection always returns 0/Yes
-DataSource Property	Yes	Yes: Implicit database connection always returns an empty string/Yes
-BeginTransaction Method	No	No/Yes
-ChangeDatabase Method	Yes	No/No
-Clone Method	Yes	No/Yes
-EnlistDistributedTransaction Method	Yes	No/No
-	Yes	No/Yes
OpenWithNewPassword(String) Method	Yes	No/No
-Failover Event		No/Yes
-OracleFailoverEventHandler Delegate		No/No

Table 5-1 (Cont.) API Support Comparison Between Client Application and .NET Stored Procedure

Class or Class Members	Client Application	Implicit Connection/Explicit Connection
ODP.NET Enumerations	Yes	No/No
-FailoverEvent Enumeration	Yes	No/No
-FailoverReturnCode Enumeration	Yes	No/No
-FailoverType Enumeration	Yes	No/No
-OracleNotificationInfo Enumeration	Yes	No/No
-OracleNotificationSource Enumeration		
-OracleNotificationType Enumeration		

6

Oracle Data Provider for .NET Classes

This chapter describes the following Oracle Data Provider for .NET classes.

- [OracleClientFactory Class](#)
- [OracleCommand Class](#)
- [OracleCommandBuilder Class](#)
- [OracleConnection Class](#)
- [OracleConfiguration Class](#)
- [OracleConnectionOpenEventArgs Class](#)
- [OracleConnectionOpenEventHandler Delegate](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleCredential Class](#)
- [OracleDataAdapter Class](#)
- [OracleDatabase Class](#)
- [OracleDataReader Class](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceEnumerator Class](#)
- [OracleError Class](#)
- [OracleErrorCollection Class](#)
- [OracleException Class](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventHandler Delegate](#)
- [OracleLogicalTransaction Class](#)
- [OracleOnsServerCollection Class](#)
- [OracleParameter Class](#)
- [OracleParameterCollection Class](#)
- [OraclePermission Class](#)
- [OraclePermissionAttribute Class](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventHandler Delegate](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventHandler Delegate](#)
- [OracleShardingKey Class](#)
- [OracleTransaction Class](#)

- [OracleConnectionType Enumeration](#)
- [OracleCollectionType Enumeration](#)
- [OracleDBAPrivilege Enumeration](#)
- [OracleDBShutdownMode Enumeration](#)
- [OracleDBStartupMode Enumeration](#)
- [OracleDbType Enumeration](#)
- [OracleDRCPurity Enumeration](#)
- [OracleIdentityType Enumeration](#)
- [OracleParameterStatus Enumeration](#)

OracleClientFactory Class

An `OracleClientFactory` object allows applications to instantiate ODP.NET classes in a generic way.

Class Inheritance

`System.Object`

`System.Data.Common.DbProviderFactory`

`Oracle.DataAccess.Client.OracleClientFactory`

Declaration

```
// C#
public sealed class OracleClientFactory : DbProviderFactory
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class FactorySample
```

```
{
    static void Main()
    {
        string constr = "user id=scott;password=tiger;data source=oracle";

        DbProviderFactory factory =
            DbProviderFactories.GetFactory("Oracle.DataAccess.Client");

        DbConnection conn = factory.CreateConnection();

        try
        {
            conn.ConnectionString = constr;
            conn.Open();

            DbCommand cmd = factory.CreateCommand();
            cmd.Connection = conn;
            cmd.CommandText = "select * from emp";

            DbDataReader reader = cmd.ExecuteReader();
            while (reader.Read())
                Console.WriteLine(reader["EMPNO"] + " : " + reader["ENAME"]);
        }
        catch (Exception ex)
        {
            Console.WriteLine(ex.Message);
            Console.WriteLine(ex.StackTrace);
        }
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Members](#)
- [OracleClientFactory Field](#)
- [OracleClientFactory Constructor](#)
- [OracleClientFactory Public Properties](#)
- [OracleClientFactory Public Methods](#)

OracleClientFactory Members

OracleClientFactory members are listed in the following tables.

OracleClientFactory Field

The OracleClientFactory field is listed in [Table 6-1](#)

Table 6-1 OracleClientFactory Field

Property	Description
Instance	Gets an instance of the OracleClientFactory class

OracleClientFactory Constructor

The OracleClientFactory constructor is listed in [Table 6-2](#)

Table 6-2 OracleClientFactory Constructor

Property	Description
OracleClientFactory Constructor	Instantiates a new instance of OracleClientFactory class

OracleClientFactory Public Properties

The OracleClientFactory public properties are listed in [Table 6-3](#).

Table 6-3 OracleClientFactory Public Properties

Property	Description
CanCreateDataSourceEnumerator	Indicates whether or not the CreateDataSourceEnumerator method is supported

OracleClientFactory Public Methods

OracleClientFactory Public Methods are listed in [Table 6-4](#).

Table 6-4 OracleClientFactory Public Method

Method	Description
CreateCommand	Returns a DbCommand object that represents an OracleCommand object
CreateCommandBuilder	Returns a DbCommandBuilder object that represents an OracleCommandBuilder object
CreateConnection	Returns a DbConnection object that represents an OracleConnection object
CreateConnectionStringBuilder	Returns a DbConnectionStringBuilder object that represents an OracleConnectionStringBuilder object
CreateDataAdapter	Returns a DbDataAdapter object that represents an OracleDataAdapter object
CreateDataSourceEnumerator	Returns a DbDataSourceEnumerator object that represents an OracleDataSourceEnumerator object

Table 6-4 (Cont.) OracleClientFactory Public Method

Method	Description
CreateParameter	Returns a DbParameter object that represents an OracleParameter object
CreatePermission	Returns a CodeAccessPermission object that represents an OraclePermission object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)

OracleClientFactory Field

The OracleClientFactory field is listed in [Table 6-5](#)

Table 6-5 OracleClientFactory Field

Property	Description
Instance	Gets an instance of the OracleClientFactory class

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

Instance

The Instance field gets an instance of the OracleClientFactory class. This can be used to retrieve strongly typed data objects.

Declaration

```
// C#  
public static readonly OracleClientFactory Instance
```


 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

OracleClientFactory Constructor

The `OracleClientFactory` constructor creates a new instances of the `OracleClientFactory` class.

Declaration

```
// C#  
public OracleClientFactory();
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

OracleClientFactory Public Properties

The `OracleClientFactory` public properties are listed in [Table 6-6](#).

Table 6-6 OracleClientFactory Public Properties

Property	Description
CanCreateDataSourceEnumerator	Indicates whether or not the <code>CreateDataSourceEnumerator</code> method is supported

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CanCreateDataSourceEnumerator

This property indicates whether or not the `CreateDataSourceEnumerator` method is supported.

Declaration

```
// C#
public override bool CanCreateDataSourceEnumerator { get; }
```

Property Value

Returns true.

Remarks

ODP.NET supports the `OracleDataSourceEnumerator` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

OracleClientFactory Public Methods

The `OracleClientFactory` public method is listed in [Table 6-7](#).

Table 6-7 OracleClientFactory Public Method

Method	Description
CreateCommand	Returns a <code>DbCommand</code> object that represents an <code>OracleCommand</code> object
CreateCommandBuilder	Returns a <code>DbCommandBuilder</code> object that represents an <code>OracleCommandBuilder</code> object
CreateConnection	Returns a <code>DbConnection</code> object that represents an <code>OracleConnection</code> object
CreateConnectionStringBuilder	Returns a <code>DbConnectionStringBuilder</code> object that represents an <code>OracleConnectionStringBuilder</code> object
CreateDataAdapter	Returns a <code>DbDataAdapter</code> object that represents an <code>OracleDataAdapter</code> object
CreateDataSourceEnumerator	Returns a <code>DbDataSourceEnumerator</code> object that represents an <code>OracleDataSourceEnumerator</code> object

Table 6-7 (Cont.) OracleClientFactory Public Method

Method	Description
CreateParameter	Returns a DbParameter object that represents an OracleParameter object
CreatePermission	Returns a CodeAccessPermission object that represents an OraclePermission object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateCommand

This method returns a DbCommand object that represents an OracleCommand object.

Declaration

```
// C#  
public override DbCommand CreateCommand();
```

Return Value

A DbCommand object that represents an OracleCommand object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateCommandBuilder

This method returns a DbCommandBuilder object that represents an OracleCommandBuilder object.

Declaration

```
// C#  
public override DbCommandBuilder CreateCommandBuilder();
```

Return Value

A `DbCommandBuilder` object that represents an `OracleCommandBuilder` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateConnection

This method returns a `DbConnection` object that represents an `OracleConnection` object.

Declaration

```
// C#  
public override DbConnection CreateConnection();
```

Return Value

A `DbConnection` object that represents an `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateConnectionStringBuilder

This method returns a `DbConnectionStringBuilder` object that represents an `OracleConnectionStringBuilder` object.

Declaration

```
// C#  
public override DbConnectionStringBuilder CreateConnectionStringBuilder();
```

Return Value

A `DbConnectionStringBuilder` object that represents an `OracleConnectionStringBuilder` object.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateDataAdapter

This method returns a `DbDataAdapter` object that represents an `OracleDataAdapter` object.

Declaration

```
// C#  
public override DbDataAdapter CreateDataAdapter();
```

Return Value

A `DbDataAdapter` object that represents an `OracleDataAdapter` object.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateDataSourceEnumerator

This method returns a `DbDataSourceEnumerator` object that represents an `OracleDataSourceEnumerator` object.

Declaration

```
// C#  
public override DbDataSourceEnumerator CreateDataSourceEnumerator();
```

Return Value

A `DbDataSourceEnumerator` object that represents an `OracleDataSourceEnumerator` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)
- ["OracleDataSourceEnumerator Class"](#)

CreateParameter

This method returns a `DbParameter` object that represents an `OracleParameter` object.

Declaration

```
// C#  
public override DbParameter CreateParameter();
```

Return Value

A `DbParameter` object that represents an `OracleParameter` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreatePermission

This method returns a `CodeAccessPermission` object that represents an `OraclePermission` object.

Declaration

```
// C#  
public override System.Security.CodeAccessPermission CreatePermission(  
    System.Security.Permissions.PermissionState state);
```

Parameter

- *state*
A `PermissionState` object.

Return Value

A `CodeAccessPermission` object that represents an `OraclePermission` object.

Remarks

This method enables users, writing provider-independent code, to get a `CodeAccessPermission` instance that represents an `OraclePermission` object.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

OracleCommand Class

An `OracleCommand` object represents a SQL command, a stored procedure, or a table name. The `OracleCommand` object is responsible for formulating the request and passing it to the database. If results are returned, `OracleCommand` is responsible for returning results as an `OracleDataReader`, a `.NET XmlReader`, a `.NET Stream`, a scalar value, or as output parameters.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.ComponentModel.Component`

`System.Data.Common.DbCommand`

`Oracle.DataAccess.Client.OracleCommand`

Declaration

```
// C#  
public sealed class OracleCommand : DbCommand, ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The execution of any transaction-related statements from an `OracleCommand` is not recommended because it is not reflected in the state of the `OracleTransaction` object represents the current local transaction, if one exists.

`ExecuteXmlReader`, `ExecuteStream`, and `ExecuteToStream` methods are only supported for XML operations.

`ExecuteReader` and `ExecuteScalar` methods are not supported for XML operations.

To minimize the number of open server cursors, `OracleCommand` objects should be explicitly disposed.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleCommandSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        string cmdQuery = "select ename, empno from emp";

        // Create the OracleCommand
        OracleCommand cmd = new OracleCommand(cmdQuery);

        cmd.Connection = con;
        cmd.CommandType = CommandType.Text;

        // Execute command, create OracleDataReader object
        OracleDataReader reader = cmd.ExecuteReader();
    }
}
```



```

while (reader.Read())
{
    // output Employee Name and Number
    Console.WriteLine("Employee Name : " + reader.GetString(0) + " , " +
        "Employee Number : " + reader.GetDecimal(1));
}

// Clean up
reader.Dispose();
cmd.Dispose();
con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Members](#)
- [OracleCommand Constructors](#)
- [OracleCommand Static Methods](#)
- [OracleCommand Properties](#)
- [OracleCommand Public Methods](#)

OracleCommand Members

OracleCommand members are listed in the following tables.

OracleCommand Constructors

OracleCommand constructors are listed in [Table 6-8](#).

Table 6-8 OracleCommand Constructors

Constructor	Description
OracleCommand Constructors	Instantiates a new instance of OracleCommand class (Overloaded)

OracleCommand Static Methods

The OracleCommand static method is listed in [Table 6-9](#).

Table 6-9 OracleCommand Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleCommand Properties

OracleCommand properties are listed in [Table 6-10](#).

Table 6-10 OracleCommand Properties

Property	Description
AddRowid	Adds the ROWID as part of the select list
AddToStatementCache	Causes executed statements to be cached, when the property is set to <code>true</code> and statement caching is enabled
ArrayBindCount	Specifies if the array binding feature is to be used and also specifies the maximum number of array elements to be bound in the <code>Value</code> property
ArrayBindRowsAffected	Returns the number of affected rows for each iteration while executing a DML using array binding
BindByName	Specifies the binding method in the collection
CommandText	Specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database
CommandTimeout	Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception
CommandType	Specifies the command type that indicates how the <code>CommandText</code> property is to be interpreted
Connection	Specifies the <code>OracleConnection</code> object that is used to identify the connection to execute a command
<code>Container</code>	Inherited from <code>System.ComponentModel.Component</code>
DesignTimeVisible	Specifies whether or not the <code>OracleCommand</code> object is visible on designer controls.
FetchSize	Specifies the size of <code>OracleDataReader</code> 's internal cache to store result set data
ImplicitRefCursors	Specifies an array of <code>OracleRefCursors</code> mapped to an implicit resultset returned by the stored procedure. <i>Not Available in the ODP.NET, Managed Driver and ODP.NET Core</i>
InitialLOBFetchSize	Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LOB columns
InitialLONGFetchSize	Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LONG and LONG RAW columns
Notification	Indicates that there is a notification request for the command
NotificationAutoEnlist	Indicates whether or not to register for a continuous query notification with the database automatically when the command is executed
Parameters	Specifies the parameters for the SQL statement or stored procedure

Table 6-10 (Cont.) OracleCommand Properties

Property	Description
RowSize	Specifies the amount of memory needed by the <code>OracleDataReader</code> internal cache to store one row of data
Site	Inherited from <code>System.ComponentModel.Component</code>
Transaction	Specifies the <code>OracleTransaction</code> object in which the <code>OracleCommand</code> executes <i>Not supported in a .NET stored procedure</i>
UpdatedRowSource	Specifies how query command results are applied to the row being updated <i>Not supported in a .NET stored procedure</i>
UseEdmMapping	Indicates whether or not the command object utilizes the Entity Data Model mapping configuration values
XmlCommandType	Specifies the type of XML operation on the <code>OracleCommand</code>
XmlQueryProperties	Specifies the properties that are used when an XML document is created from the result set of a SQL query statement
XmlSaveProperties	Specifies the properties that are used when an XML document is used to save changes to the database

OracleCommand Public Methods

`OracleCommand` public methods are listed in [Table 6-11](#).

Table 6-11 OracleCommand Public Methods

Public Method	Description
Cancel	Attempts to cancel a command that is currently executing on a particular connection
Clone	Creates a copy of <code>OracleCommand</code> object
<code>CreateObjRef</code>	Inherited from <code>System.MarshalByRefObject</code>
CreateParameter	Creates a new instance of <code>OracleParameter</code> class
Dispose	Releases any resources or memory allocated by the object
<code>Equals</code>	Inherited from <code>System.Object (Overloaded)</code>
ExecuteNonQuery	Executes a SQL statement or a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the number of rows affected
ExecuteReader	Executes a command (Overloaded)
ExecuteScalar	Returns the first column of the first row in the result set returned by the query

Table 6-11 (Cont.) OracleCommand Public Methods

Public Method	Description
ExecuteStream	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the results in a new <code>Stream</code> object
ExecuteToStream	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and appends the results as an XML document to the existing <code>Stream</code>
ExecuteXmlReader	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the result as an XML document in a .NET <code>XmlTextReader</code> object
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
Prepare	<i>This method is a no-op</i>
<code>ToString</code>	Inherited from <code>System.Object</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)

OracleCommand Constructors

`OracleCommand` constructors instantiate new instances of `OracleCommand` class.

Overload List:

- [OracleCommand\(\)](#)
This constructor instantiates a new instance of `OracleCommand` class.
- [OracleCommand\(string\)](#)
This constructor instantiates a new instance of `OracleCommand` class using the supplied SQL command or stored procedure, and connection to the Oracle database.
- [OracleCommand\(string, OracleConnection\)](#)
This constructor instantiates a new instance of `OracleCommand` class using the supplied SQL command or stored procedure, and connection to the Oracle database.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand()

This constructor instantiates a new instance of `OracleCommand` class.

Declaration

```
// C#  
public OracleCommand();
```

Remarks

Default constructor.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand(string)

This constructor instantiates a new instance of `OracleCommand` class using the supplied SQL command or stored procedure, and connection to the Oracle database.

Declaration

```
// C#  
public OracleCommand(string cmdText);
```

Parameters

- *cmdText*
The SQL command or stored procedure to be executed.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand(string, OracleConnection)

This constructor instantiates a new instance of `OracleCommand` class using the supplied SQL command or stored procedure, and connection to the Oracle database.

Declaration

```
// C#
public OracleCommand(string cmdText, OracleConnection OracleConnection);
```

Parameters

- *cmdText*
The SQL command or stored procedure to be executed.
- *OracleConnection*
The connection to the Oracle database.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand Static Methods

The `OracleCommand` static method is listed in [Table 6-12](#).

Table 6-12 OracleCommand Static Method

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand Properties

OracleCommand properties are listed in [Table 6-13](#).

Table 6-13 OracleCommand Properties

Property	Description
AddRowid	Adds the ROWID as part of the select list
AddToStatementCache	Causes executed statements to be cached, when the property is set to <code>true</code> and statement caching is enabled
ArrayBindCount	Specifies if the array binding feature is to be used and also specifies the maximum number of array elements to be bound in the <code>Value</code> property
ArrayBindRowsAffected	Returns the number of affected rows for each iteration while executing a DML using array binding
BindByName	Specifies the binding method in the collection
CommandText	Specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database
CommandTimeout	Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception
CommandType	Specifies the command type that indicates how the <code>CommandText</code> property is to be interpreted
Connection	Specifies the <code>OracleConnection</code> object that is used to identify the connection to execute a command
<code>Container</code>	Inherited from <code>System.ComponentModel.Component</code>
DesignTimeVisible	Specifies whether or not the <code>OracleCommand</code> object is visible on designer controls.
FetchSize	Specifies the size of <code>OracleDataReader</code> 's internal cache to store result set data
ImplicitRefCursors	Specifies an array of <code>OracleRefCursors</code> mapped to an implicit resultset returned by the stored procedure. <i>Not Available in the ODP.NET, Managed Driver and ODP.NET Core</i>
InitialLOBFetchSize	Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LOB columns

Table 6-13 (Cont.) OracleCommand Properties

Property	Description
InitialLONGFetchSize	Specifies the amount that of data the <code>OracleDataReader</code> initially fetches for LONG and LONG RAW columns
Notification	Indicates that there is a notification request for the command
NotificationAutoEnlist	Indicates whether or not to register for a continuous query notification with the database automatically when the command is executed
Parameters	Specifies the parameters for the SQL statement or stored procedure
RowSize	Specifies the amount of memory needed by the <code>OracleDataReader</code> internal cache to store one row of data
Site	Inherited from <code>System.ComponentModel.Component</code>
Transaction	Specifies the <code>OracleTransaction</code> object in which the <code>OracleCommand</code> executes <i>Not supported in a .NET stored procedure</i>
UpdatedRowSource	Specifies how query command results are applied to the row being updated <i>Not supported in a .NET stored procedure</i>
UseEdmMapping	Indicates whether or not the command object utilizes the Entity Data Model mapping configuration values
XmlCommandType	Specifies the type of XML operation on the <code>OracleCommand</code>
XmlQueryProperties	Specifies the properties that are used when an XML document is created from the result set of a SQL query statement
XmlSaveProperties	Specifies the properties that are used when an XML document is used to save changes to the database

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

AddRowid

This property adds the ROWID as part of the select list.

Declaration

```
// C#  
public bool AddRowid {get; set;}
```

Property Value

bool

Remarks

Default is `false`.

This `ROWID` column is hidden and is not accessible by the application. To gain access to the `ROWIDS` of a table, the `ROWID` must explicitly be added to the select list without the use of this property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["LOB Support"](#) for further information on how this property used with LOBs

AddToStatementCache

This property causes executed statements to be cached when the property is set to `true` and statement caching is enabled. If statement caching is disabled or if this property is set to `false`, the executed statement is not cached.

Declaration

```
// C#  
public bool AddToStatementCache{get; set;}
```

Return Value

Returns `bool` value. A value of `true` indicates that statements are being added to the cache, `false` indicates otherwise.

Property Value

A `bool` value that indicates that the statements will be cached when they are executed, if statement caching is enabled.

Remarks

Default is `true`.

AddToStatementCache is ignored if statement caching is disabled. Statement caching is enabled by setting the Statement Cache Size connection string attribute to a value greater than 0.

When statement caching is enabled, however, this property provides a way to selectively add statements to the cache.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class AddToStatementCacheSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle;" +
            "statement cache size=10";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand("select * from emp", con);

        if (cmd.AddToStatementCache)
            Console.WriteLine("Added to the statement cache:" + cmd.CommandText);
        else
            Console.WriteLine("Not added to the statement cache:" + cmd.CommandText);

        // The execution of "select * from emp" will be added to the statement cache
        // because statement cache size is greater than 0 and OracleCommand's
        // AddToStatementCache is true by default.
        OracleDataReader readerEmp = cmd.ExecuteReader();

        // Do not add "select * from dept" to the statement cache
        cmd.CommandText = "select * from dept";
        cmd.AddToStatementCache = false;

        if (cmd.AddToStatementCache)
            Console.WriteLine("Added to the statement cache:" + cmd.CommandText);
        else
            Console.WriteLine("Not added to the statement cache:" + cmd.CommandText);

        // The execution of "select * from dept" will not be added to the
        // statement cache because AddToStatementCache is set to false.
        OracleDataReader readerDept = cmd.ExecuteReader();

        // Clean up
        con.Dispose();
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Statement Caching"](#)
- [ConnectionString](#)

ArrayBindCount

This property specifies if the array binding feature is to be used and also specifies the number of array elements to be bound in the `OracleParameter.Value` property.

Declaration

```
// C#  
public int ArrayBindCount {get; set;}
```

Property Value

An `int` value that specifies number of array elements to be bound in the `OracleParameter.Value` property.

Exceptions

`ArgumentException` - The `ArrayBindCount` value specified is invalid.

Remarks

Default = 0.

If `ArrayBindCount` is equal to 0, array binding is not used; otherwise, array binding is used and `OracleParameter.Value` property is interpreted as an array of values. The value of `ArrayBindCount` must be specified to use the array binding feature.

If neither `DbType` nor `OracleDbType` is set, it is strongly recommended that you set `ArrayBindCount` before setting the `OracleParameter.Value` property so that inference of `DbType` and `OracleDbType` from `Value` can be correctly done.

Array binding is not used by default.

If the `XmlCommandType` property is set to any value other than `None`, this property is ignored.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#)
- ["Value "](#)

ArrayBindRowsAffected

This property returns the number of affected rows for each iteration while executing a DML using array binding.

Declaration

```
// C#  
public long[] ArrayBindRowsAffected ;
```

Property Value

A long type

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#)
- ["Value "](#)

BindByName

This property specifies the binding method in the collection.

Declaration

```
// C#  
public bool BindByName {get; set;}
```

Property Value

Returns `true` if the parameters are bound by name; returns `false` if the parameters are bound by position.

Remarks

Default = false.

BindByName is ignored under the following conditions:

- The value of the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.
- The value of the `XmlCommandType` property is `Query`, but there are no parameters set on the `OracleCommand`.

If the `XmlCommandType` property is `OracleXmlCommandType.Query` and any parameters are set on the `OracleCommand`, the `BindByName` property must be set to `true`.

Otherwise, the following `OracleCommand` methods throw an `InvalidOperationException`.

- `ExecuteNonQuery`
- `ExecuteXmlReader`
- `ExecuteStream`
- `ExecuteToStream`



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#)
- ["Value "](#)

CommandText

This property specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database.

Declaration

```
// C#  
public override string CommandText {get; set;}
```

Property Value

A string.

Implements

`IDbCommand`

Remarks

The default is an empty string.

When the `CommandType` property is set to `StoredProcedure`, the `CommandText` property is set to the name of the stored procedure. The command calls this stored procedure when an `Execute` method is called.

The effects of `XmlCommandType` values on `CommandText` are:

- `XmlCommandType = None`.
`CommandType` property determines the contents of `CommandText`.
- `XmlCommandType = Query`.
`CommandText` must be a SQL query. The SQL query should be a select statement. `CommandType` property is ignored.
- `XmlCommandType` property is `Insert`, `Update`, or `Delete`.
`CommandText` must be an XML document. `CommandType` property is ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

CommandTimeout

This property specifies the minimum number of seconds that the command is allowed to execute before terminating with an exception.

Declaration

```
// C#  
public override int CommandTimeout {get; set;}
```

Property Value

int

Implements

`IDbCommand.CommandTimeout`

Exceptions

`InvalidArgument` - The specified value is less than 0.

Remarks

Default is 0 seconds, which enforces no time limit.

When the specified timeout value expires before a command execution finishes, ODP.NET will begin the process of canceling the command. If cancellation is successful, then an exception is thrown with the message `ORA-01013: user requested cancel of current operation`. Other possible exceptions thrown after a

command timeout expiration occurs include `ORA-00936` and `ORA-00604`. If the command is executed in time without any errors, then no exceptions are thrown.

ODP.NET does not guarantee a command will be cancelled at the exact moment the timeout value is reached. The timeout value is the minimum time to allow a command to complete before the cancellation process begins. It is possible for commands to complete after the timeout value expires.

In a situation where multiple `OracleCommand` objects use the same connection, the timeout expiration on one of the `OracleCommand` objects may terminate any of the executions on the single connection. To make the timeout expiration of a `OracleCommand` cancel only its own command execution, simply use one `OracleCommand` for each connection if that `OracleCommand` sets the `CommandTimeout` property to a value greater than 0.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework feature

CommandType

This property specifies the command type that indicates how the `CommandText` property is to be interpreted.

Declaration

```
// C#  
public override CommandType CommandType {get; set;}
```

Property Value

A `CommandType`.

Exceptions

`ArgumentException` - The value is not a valid `CommandType` such as: `CommandType.Text`, `CommandType.StoredProcedure`, `CommandType.TableDirect`.

Remarks

Default = `CommandType.Text`

If the value of the `XmlCommandType` property is not `None`, then the `CommandType` property is ignored.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

Connection

This property specifies the `OracleConnection` object that is used to identify the connection to execute a command.

Declaration

```
// C#  
public OracleConnection Connection {get; set;}
```

Property Value

An `OracleConnection` object.

Implements

`IDbCommand`

Remarks

Default = null

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

DesignTimeVisible

This property specifies whether or not the `OracleCommand` object is visible on designer controls.

Declaration

```
// C#  
public override bool DesignTimeVisible { get; set; }
```


Property Value

A value that indicate whether or not `OracleCommand` object is visible in a control. The default is `true`.

Remarks

This property is used by developers to indicate whether or not `OracleCommand` object is visible in a control.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

FetchSize

This property specifies the size of `OracleDataReader`'s internal cache to store result set data.

Declaration

```
// C#  
public long FetchSize {get; set;}
```

Property Value

A `long` that specifies the size (in bytes) of the `OracleDataReader`'s internal cache.

Exceptions

`ArgumentException` - The `FetchSize` value specified is invalid.

Remarks

Default = 131072.

The `FetchSize` property is inherited by the `OracleDataReader` that is created by a command execution returning a result set. The `FetchSize` property on the `OracleDataReader` object determines the amount of data the `OracleDataReader` fetches into its internal cache for each database round-trip.

If the `XmlCommandType` property is set to any value other than `None`, this property is ignored.

The `RowSize` and `FetchSize` properties handle UDT and `XMLType` data differently than other scalar data types. Because only a reference to the UDT and `XMLType` data is stored in the ODP.NET's internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and `XMLType` data. Thus, applications can inadvertently fetch a large number of

UDT or `XMLType` instances from the database in a single database round-trip. This is because the actual size of UDT and `XMLType` data do not count against the `FetchSize`, and it would require numerous UDT and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of UDT and `XMLType` instances that are to be fetched, rather than the amount of the actual UDT and `XMLType` data to be fetched.

NOTE: For LOB and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- `OracleDataReader` ["FetchSize"](#)

ImplicitRefCursors

This property returns an array of `OracleRefCursors`, where each `OracleRefCursor` maps to an implicit resultset returned by the stored procedure.

Declaration

```
// C#  
public OracleRefCursor[] ImplicitRefCursors {get; set;}
```

Property Value

An array of `OracleRefCursors`.

Remarks

This property is populated only when the stored procedure is executed through `ExecuteNonQuery` and it does not get populated in any other scenarios.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

InitialLOBFetchSize

This property specifies the amount of data that the `OracleDataReader` initially fetches for LOB columns.

Declaration

```
// C#  
public int InitialLOBFetchSize {get; set;}
```

Property Value

An `int` specifying the number of characters or bytes to fetch initially.

Exceptions

`ArgumentException` - The `InitialLOBFetchSize` value specified is invalid.

Remarks

The value of `InitialLOBFetchSize` specifies the initial amount of LOB data that is immediately fetched by the `OracleDataReader`. The property value specifies the number of characters for `CLOB` and `NLOB` data, and the number of bytes for `BLOB` data.

The `InitialLOBFetchSize` value is used to determine the length of the LOB column data to fetch, if the LOB column is in the select list. If the select list does not contain a LOB column, the `InitialLOBFetchSize` value is ignored.

When `InitialLOBFetchSize` is set to `-1`, the entire LOB data is prefetched and stored in the fetch array.

Default = 0.

The maximum value supported for `InitialLOBFetchSize` is 2 GB.

`GetOracleBlob` and `GetOracleClob` methods can be used to retrieve any LOBs no matter the `InitialLOBFetchSize` value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Obtaining LOB Data"](#) for more information on setting `InitialLOBFetchSize` values

InitialLONGFetchSize

This property specifies the amount of data that the `OracleDataReader` initially fetches for `LONG` and `LONG RAW` columns.

Declaration

```
// C#  
public int InitialLONGFetchSize {get; set;}
```

Property Value

An int specifying the amount.

Exceptions

ArgumentException - The InitialLONGFetchSize value specified is invalid.

Remarks

The maximum value supported for InitialLONGFetchSize is 32767. If this property is set to a higher value, the provider resets it to 32767.

The value of InitialLONGFetchSize specifies the initial amount of LONG or LONG RAW data that is immediately fetched by the OracleDataReader. The property value specifies the number of characters for LONG data and the number of bytes for LONG RAW. To fetch more than the specified InitialLONGFetchSize amount, one of the following must be in the select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a NOT NULL constraint defined on it)

The InitialLONGFetchSize value is used to determine the length of the LONG and LONG RAW column data to fetch if one of the two is in the select list. If the select list does not contain a LONG or a LONG RAW column, the InitialLONGFetchSize value is ignored.

When InitialLONGFetchSize is set to -1, the entire LONG or LONG RAW data is prefetched and stored in the fetch array. Calls to GetString, GetChars, or GetBytes in OracleDataReader allow retrieving the entire data.

Default = 0.

Setting this property to 0 defers the LONG and LONG RAW data retrieval entirely until the application specifically requests it.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Obtaining LONG and LONG RAW Data"](#) for further information

Notification

This instance property indicates that there is a notification request for the command.

Declaration

```
// C#  
public OracleNotificationRequest Notification {set; get;}
```

Property Value

A notification request for the command.

Remarks

When a changed notification is first registered, the client listener is started in order to receive any database notification. The listener uses the port number defined in the `OracleDependency.Port` static field. Subsequent change notification registrations use the same listener in the same client process and do not start another listener.

When `Notification` is set to an `OracleNotificationRequest` instance, a notification registration is created (if it has not already been created) when the command is executed. Once the registration is created, the properties of the `OracleNotificationRequest` instance cannot be modified. If the notification registration has already been created, the result set that is associated with the command is added to the existing registration.

When `Notification` is set to `null`, subsequent command executions do not require a notification request. If a notification request is not required, set the `Notification` property to `null`, or set the `NotificationAutoEnlist` property to `false`.

For Continuous Query Notification, a notification request can be used for multiple command executions. In that case, any query result set associated with different commands can be invalidated within the same registration.

When the `OracleDependency.OnChange` event is fired, if the `ROWID` column is explicitly included in the query (or `AddRowid` property is set to `true`), then the `Rowid` column contains `ROWID` values in the `DataTable` referenced by the `OracleNotificationEventArgs.Details` property. This behavior can be overridden by explicitly requesting for an inclusion and exclusion of `ROWID` values in the `OracleNotificationEventArgs` by setting the `OracleDependency.RowidInfo` to `OracleRowidInfo.Include` or `OracleRowidInfo.Exclude`, respectively.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Continuous Query Notification Support "](#)
- [Continuous Query Notification Classes](#)

NotificationAutoEnlist

This instance property indicates whether or not to register for a continuous query notification with the database automatically when the command is executed.

Declaration

```
// C#  
public bool NotificationAutoEnlist {set; get;}
```

Property Value

A `bool` value indicating whether or not to make a continuous query notification request automatically, when the command is executed. If `NotificationAutoEnlist` is set to `true`, and the `Notification` property is set appropriately, a continuous query notification request is registered automatically; otherwise, no continuous query notification registration is made.

Default value: `true`

Remarks

A notification request can be used for multiple command executions using the same `OracleCommand` instance. In that case, set the `NotificationAutoEnlist` property to `true`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Continuous Query Notification Support "](#)
- [Continuous Query Notification Classes](#)

Parameters

This property specifies the parameters for the SQL statement or stored procedure.

Declaration

```
// C#  
public OracleParameterCollection Parameters {get;}
```

Property Value

`OracleParameterCollection`

Implements

`IDbCommand`

Remarks

Default value = an empty collection

The number of the parameters in the collection must be equal to the number of parameter placeholders within the command text, or an error is raised.

If the command text does not contain any parameter tokens (such as `:1`, `:2`), the values in the `Parameters` property are ignored.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

RowSize

This property specifies the amount of memory needed by the `OracleDataReader` internal cache to store one row of data.

Declaration

```
// C#  
public long RowSize {get;}
```

Property Value

A `long` that indicates the amount of memory (in bytes) that an `OracleDataReader` needs to store one row of data for the executed query.

Remarks

Default value = 0

The `RowSize` property is set to a nonzero value after the execution of a command that returns a result set. This property can be used at design time or dynamically during runtime, to set the `FetchSize`, based on number of rows. For example, to enable the `OracleDataReader` to fetch `N` rows for each database round-trip, the `OracleDataReader FetchSize` property can be set dynamically to `RowSize * N`. Note that for the `FetchSize` to take effect appropriately, it must be set after `OracleCommand.ExecuteReader()` but before `OracleDataReader.Read()`.

ODP.NET now supports values up to 32K for `VARCHAR2`, `NVARCHAR2` or `RAW` type columns in its calculation of `RowSize` value.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- [OracleDataReader "FetchSize"](#)

Transaction

This property specifies the `OracleTransaction` object in which the `OracleCommand` executes.

Declaration

```
// C#  
public OracleTransaction Transaction {set; get;}
```

Property Value

`OracleTransaction`

Implements

`IDbCommand`

Remarks

Default value = `null`

`Transaction` returns a reference to the transaction object associated with the `OracleCommand` connection object. Thus the command is executed in whatever transaction context its connection is currently in.

 **Note:**

When this property is accessed through an `IDbCommand` reference, its `set` accessor method is not operational.

Remarks (.NET Stored Procedure)

Always returns `null`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

UpdatedRowSource

This property specifies how query command results are applied to the row to be updated.

Declaration

```
// C#  
public override UpdateRowSource UpdatedRowSource {get; set;}
```

Property Value

An UpdateRowSource.

Implements

IDbCommand

Exceptions

`ArgumentException` - The UpdateRowSource value specified is invalid.

Remarks

Always returns UpdateRowSource,

Set accessor throws an `ArgumentException` if the value is other than `UpdateRowSource.None`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

UseEdmMapping

This property Indicates whether or not the `OracleCommand` object utilizes the Entity Data Model mapping configuration values.

Declaration

```
// C#  
public bool UseEdmMapping
```

Property Value

A bool.

Remarks

Default is false.

The `UseEdmMapping` property allows user to explicitly specify that the `OracleCommand` object should use the Entity Data Model mapping configuration values. This enables use of Entity Framework Multiple Result Sets feature.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

XmlCommandType

This property specifies the type of XML operation on the `OracleCommand`.

Declaration

```
// C#  
public OracleXmlCommandType XmlCommandType {get; set;}
```

Property Value

An `OracleXmlCommandType`.

Remarks

Default value is `None`.

`XmlCommandType` values and usage:

- `None` - The `CommandType` property specifies the type of operation.
- `Query` - `CommandText` property must be set to a SQL select statement. The query is executed, and the results are returned as an XML document. The SQL select statement in the `CommandText` and the properties specified by the `XmlQueryProperties` property are used to perform the operation. The `CommandType` property is ignored.
- `Insert, Update, or Delete` - `CommandText` property is an XML document containing the changes to be made. The XML document in the `CommandText` and the

properties specified by the `XmlSaveProperties` property are used to perform the operation. The `CommandType` property is ignored.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

XmlQueryProperties

This property specifies the properties that are used when an XML document is created from the result set of a SQL query statement.

Declaration

```
// C#  
public OracleXmlQueryProperties XmlQueryProperties {get; set;}
```

Property Value

`OracleXmlQueryProperties`.

Remarks

When a new instance of `OracleCommand` is created, an instance of `OracleXmlQueryProperties` is automatically available on the `OracleCommand` instance through the `OracleCommand.XmlQueryProperties` property.

A new instance of `OracleXmlQueryProperties` can be assigned to an `OracleCommand` instance. Assigning an instance of `OracleXmlQueryProperties` to the `XmlQueryProperties` of an `OracleCommand` instance creates a new instance of the given `OracleXmlQueryProperties` instance for the `OracleCommand`. This way each `OracleCommand` instance has its own `OracleXmlQueryProperties` instance.

Use the default constructor to get a new instance of `OracleXmlQueryProperties`.

Use the `OracleXmlQueryProperties.Clone()` method to get a copy of an `OracleXmlQueryProperties` instance.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

XmlSaveProperties

This property specifies the properties that are used when an XML document is used to save changes to the database.

Declaration

```
// C#
public OracleXmlSaveProperties XmlSaveProperties {get; set;}
```

Property Value

OracleXmlSaveProperties.

Remarks

When a new instance of `OracleCommand` is created, an instance of `OracleXmlSaveProperties` is automatically available on the `OracleCommand` instance through the `OracleCommand.XmlSaveProperties` property.

A new instance of `OracleXmlSaveProperties` can be assigned to an `OracleCommand` instance. Assigning an instance of `OracleXmlSaveProperties` to the `XmlSaveProperties` of an `OracleCommand` instance creates a new instance of the given `OracleXmlSaveProperties` instance for the `OracleCommand`. This way each `OracleCommand` instance has its own `OracleXmlSaveProperties` instance.

Use the default constructor to get a new instance of `OracleXmlSaveProperties`.

Use the `OracleXmlSaveProperties.Clone()` method to get a copy of an `OracleXmlSaveProperties` instance.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand Public Methods

`OracleCommand` public methods are listed in [Table 6-14](#).

Table 6-14 OracleCommand Public Methods

Public Method	Description
Cancel	Attempts to cancel a command that is currently executing on a particular connection
Clone	Creates a copy of <code>OracleCommand</code> object
<code>CreateObjRef</code>	Inherited from <code>System.MarshalByRefObject</code>

Table 6-14 (Cont.) OracleCommand Public Methods

Public Method	Description
CreateParameter	Creates a new instance of <code>OracleParameter</code> class
Dispose	Releases any resources or memory allocated by the object
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
ExecuteNonQuery	Executes a SQL statement or a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the number of rows affected
ExecuteReader	Executes a command (Overloaded)
ExecuteScalar	Returns the first column of the first row in the result set returned by the query
ExecuteStream	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the results in a new <code>Stream</code> object
ExecuteToStream	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and appends the results as an XML document to the existing <code>Stream</code>
ExecuteXmlReader	Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the result as an XML document in a .NET <code>XmlTextReader</code> object
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
Prepare	<i>This method is a no-op</i>
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

Cancel

This method attempts to cancel a command that is currently executing on a particular connection.

Declaration

```
// C#  
public override void Cancel();
```

Implements

```
IDbCommand.Cancel
```

Remarks

If cancellation of the command succeeds, an exception is thrown. If cancellation is not successful, no exception is thrown. If there is no command being executed at the time of the `Cancel` invocation, `Cancel` does nothing. Invoking the `Cancel` method does not guarantee that the command executing at the time will always be cancelled. The execution may complete before it can be terminated. In such cases, no exception is thrown.

When multiple `OracleCommand` objects share the same connection, only one command can be executed on that connection at any one time. When it is invoked, the `Cancel` method attempts to cancel the statement currently running on the connection that the `OracleCommand` object is using to execute the command. However, when multiple `OracleCommand` objects execute statements on the same connection simultaneously, issuing a `Cancel` method invocation may cancel any of the issued commands. This is because the command designated for cancellation may complete before the `Cancel` invocation is effective. If this happens, a command executed by a different `OracleCommand` could be cancelled instead.

There are several ways to avoid this non-deterministic situation that the `Cancel` method can cause:

- The application can create just one `OracleCommand` object for each connection. Doing so assures that the `Cancel` invocation only cancels commands executed by the `OracleCommand` object using a particular connection.
- Command executions in the application are synchronized between `OracleCommand` objects that use the same connection.

These suggestions do not apply if `Cancel` is not used in the application.

Because the termination on the currently running execution is non-deterministic, it is recommended that any *non-atomic* SQL or PL/SQL execution be started within a transaction. When the command execution successfully terminates with an exception of `ORA-01013: user requested cancel of current operation`, the transaction can be rolled back for data integrity. Other possible exceptions thrown after a command cancellation occurs include `ORA-00936` and `ORA-00604`. Examples of non-atomic execution are collections of DML command executions that are executed one-by-one and multiple DML commands that are part of a PL/SQL stored procedure or function.

Example

```
// C#  
  
// This example shows how command executions can be cancelled in a  
// deterministic way even if multiple commands are executed on a single  
// connection. This is accomplished by synchronizing threads through events.  
// Since the Cancel method terminates the currently running operation on the  
// connection, threads must be serialized if multiple threads are using the
```

```
// same connection to execute server round-trip incurring operations.
// Furthermore, the example shows how the execution and cancel threads should
// be synchronized so that nth iteration of the command execution does not
// inappropriately cancel the (n+1)th command executed by the same thread.

using System;
using System.Data;
using Oracle.DataAccess.Client;
using System.Threading;

class CancelSample
{
    private OracleCommand cmd;
    Thread t1, t2;
    // threads signal following events when assigned operations are completed

    private AutoResetEvent ExecuteEvent = new AutoResetEvent(false);
    private AutoResetEvent CancelEvent = new AutoResetEvent(false);
    private AutoResetEvent FinishedEvent = new AutoResetEvent(false);
    AutoResetEvent[] ExecuteAndCancel = new AutoResetEvent[2];

    // Default constructor
    CancelSample()
    {
        cmd = new OracleCommand("select * from all_objects",
            new OracleConnection("user id=scott;password=tiger;data source=oracle"));
        ExecuteAndCancel[0] = ExecuteEvent;
        ExecuteAndCancel[1] = CancelEvent;
    }

    // Constructor that takes a particular command and connection
    CancelSample(string command, OracleConnection con)
    {
        cmd = new OracleCommand(command, con);
        ExecuteAndCancel[0] = ExecuteEvent;
        ExecuteAndCancel[1] = CancelEvent;
    }

    // Execution of the command
    public void Execute()
    {
        OracleDataReader reader = null;
        try
        {
            Console.WriteLine("Execute.");
            reader = cmd.ExecuteReader();
            Console.WriteLine("Execute Done.");
            reader.Close();
        }
        catch(Exception e)
        {
            Console.WriteLine("The command has been cancelled.", e.Message);
        }
        Console.WriteLine("ExecuteEvent.Set()");
        ExecuteEvent.Set();
    }

    // Canceling of the command
    public void Cancel()
    {
        try
```

```
{
    // cancel query if it takes longer than 100 ms to finish execution
    System.Threading.Thread.Sleep(100);
    Console.WriteLine("Cancel.");
    cmd.Cancel();
}
catch (Exception e)
{
    Console.WriteLine(e.ToString());
}
Console.WriteLine("Cancel done.");
Console.WriteLine("CancelEvent.Set()");
CancelEvent.Set();
}

// Execution of the command with a potential of cancelling
public void ExecuteWithinLimitedTime()
{
    for (int i = 0; i < 5; i++)
    {
        Monitor.Enter(typeof(CancelSample));
        try
        {
            Console.WriteLine("Executing " + this.cmd.CommandText);
            ExecuteEvent.Reset();
            CancelEvent.Reset();
            t1 = new Thread(new ThreadStart(this.Execute));
            t2 = new Thread(new ThreadStart(this.Cancel));
            t1.Start();
            t2.Start();
        }
        finally
        {
            WaitHandle.WaitAll(ExecuteAndCancel);
            Monitor.Exit(typeof(CancelSample));
        }
    }
    FinishedEvent.Set();
}
[MTAThread]
static void Main()
{
    try
    {
        AutoResetEvent[] ExecutionCompleteEvents = new AutoResetEvent[3];

        // Create the connection that is to be used by three commands
        OracleConnection con = new OracleConnection("user id=scott;" +
            "password=tiger;data source=oracle");
        con.Open();

        // Create instances of CancelSample class
        CancelSample test1 = new CancelSample("select * from all_objects", con);
        CancelSample test2 = new CancelSample("select * from all_objects, emp",
            con);
        CancelSample test3 = new CancelSample("select * from all_objects, dept",
            con);

        // Create threads for each CancelSample object instance
        Thread t1 = new Thread(new ThreadStart(test1.ExecuteWithinLimitedTime));
        Thread t2 = new Thread(new ThreadStart(test2.ExecuteWithinLimitedTime));
```



```
Thread t3 = new Thread(new ThreadStart(test3.ExecuteWithinLimitedTime));

// Obtain a handle to an event from each object
ExecutionCompleteEvents[0] = test1.FinishedEvent;
ExecutionCompleteEvents[1] = test2.FinishedEvent;
ExecutionCompleteEvents[2] = test3.FinishedEvent;

// Start all threads to execute three commands using a single connection
t1.Start();
t2.Start();
t3.Start();

// Wait for all three commands to finish executing/canceling before
//closing the connection
WaitHandle.WaitAll(ExecutionCompleteEvents);
con.Close();
}
catch (Exception e)
{
    Console.WriteLine(e.ToString());
}
}
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework feature

Clone

This method creates a copy of an `OracleCommand` object.

Declaration

```
// C#
public object Clone();
```

Return Value

An `OracleCommand` object.

Implements

`ICloneable`

Remarks

The cloned object has the same property values as that of the object being cloned.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

CreateParameter

This method creates a new instance of `OracleParameter` class.

Declaration

```
// C#  
public OracleParameter CreateParameter();
```

Return Value

A new `OracleParameter` with default values.

Implements

`IDbCommand`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`

Remarks

The `Dispose` method also closes the `OracleCommand` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

ExecuteNonQuery

This method executes a SQL statement or a command using the `XmlCommandType` and `CommandText` properties and returns the number of rows affected.

Declaration

```
// C#  
public override int ExecuteNonQuery();
```

Return Value

The number of rows affected.

Implements

IDbCommand

Exceptions

`InvalidOperationException` - The command cannot be executed.

Remarks

`ExecuteNonQuery` returns the number of rows affected, for the following:

- If the command is `UPDATE`, `INSERT`, or `DELETE` and the `XmlCommandType` property is set to `OracleXmlCommandType.None`.
- If the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, `OracleXmlCommandType.Delete`.

For all other types of statements, the return value is `-1`.

`ExecuteNonQuery` is used for either of the following:

- Catalog operations (for example, querying the structure of a database or creating database objects such as tables).
- Changing the data in a database without using a `DataSet`, by executing `UPDATE`, `INSERT`, or `DELETE` statements.
- Changing the data in a database using an XML document.

Although `ExecuteNonQuery` does not return any rows, it populates any output parameters or return values mapped to parameters with data.

If the `XmlCommandType` property is set to `OracleXmlCommandType.Query` then `ExecuteNonQuery` executes the select statement in the `CommandText` property, and if

successful, returns -1. The XML document that is generated is discarded. This is useful for determining if the operation completes successfully without getting the XML document back as a result.

If the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, or `OracleXmlCommandType.Delete`, then the value of the `CommandText` property is an XML document. `ExecuteNonQuery` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. The return value is the number of rows that are processed in the XML document. Also, each row in the XML document could affect multiple rows in the database, but the return value is still the number of rows in the XML document.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteNonQuerySample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand(
            "select sal from emp where empno=7934", con);

        object sal = cmd.ExecuteScalar();
        Console.WriteLine("Employee sal before update: " + sal);

        cmd.CommandText = "update emp set sal = sal + .01 where empno=7934";

        // Auto-commit changes
        int rowsUpdated = cmd.ExecuteNonQuery();

        if (rowsUpdated > 0)
        {
            cmd.CommandText = "select sal from emp where empno=7934";
            sal = cmd.ExecuteScalar();
            Console.WriteLine("Employee sal after update: " + sal);
        }

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```

Requirements

For XML support, this method requires Oracle9i XML Developer's Kits (Oracle XDK) or later, to be installed in the database. Oracle XDK can be downloaded from Oracle Technology Network (OTN).

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://www.oracle.com/technetwork/index.html>

ExecuteReader

Overload List:

`ExecuteReader` executes a command specified in the `CommandText`.

- [ExecuteReader\(\)](#)

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object.

- [ExecuteReader\(CommandBehavior\)](#)

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object, using the specified `CommandBehavior` value.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

ExecuteReader()

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object.

Declaration

```
// C#  
public OracleDataReader ExecuteReader();
```

Return Value

An `OracleDataReader`.

Implements

`IDbCommand`

Exceptions

`InvalidOperationException` - The command cannot be executed.

Remarks

When the `CommandType` property is set to `CommandType.StoredProcedure`, the `CommandText` property should be set to the name of the stored procedure.

The specified command executes this stored procedure when `ExecuteReader` is called. If parameters for the stored procedure consist of `REF CURSOR` objects, behavior differs depending on whether `ExecuteReader()` or `ExecuteNonQuery()` is called. If `ExecuteReader()` is invoked, `REF CURSOR` objects can be accessed through the `OracleDataReader` that is returned. If more than one `REF CURSOR` is returned from a single execution, subsequent `REF CURSOR` objects can be accessed sequentially by the `NextResult` method on the `OracleDataReader`. If the `ExecuteNonQuery` method is invoked, the output parameter value can be cast to a `OracleRefCursor` type and the `OracleRefCursor` object then can be used to either populate a `DataSet` or create an `OracleDataReader` object from it. This approach provides random access to all the `REF CURSOR` objects returned as output parameters.

The value of 100 is used for the `FetchSize`. If 0 is specified, no rows are fetched. For further information, see ["Obtaining LONG and LONG RAW Data"](#).

If the value of the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, `OracleXmlCommandType.Delete`, or `OracleXmlCommandType.Query` then the `ExecuteReader` method throws an `InvalidOperationException`.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteReaderSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand("select ename from emp", con);

        OracleDataReader reader = cmd.ExecuteReader();

        while (reader.Read())
        {
            Console.WriteLine("Employee Name : " + reader.GetString(0));
        }

        // Clean up
        reader.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}
```

```
}  
}
```

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["OracleRefCursor Class"](#)

ExecuteReader(CommandBehavior)

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object, using the specified behavior.

Declaration

```
// C#  
public OracleDataReader ExecuteReader(CommandBehavior behavior);
```

Parameters

- *behavior*
The expected behavior.

Return Value

An `OracleDataReader`.

Implements

`IDbCommand`

Exceptions

`InvalidOperationException` - The command cannot be executed.

Remarks

A description of the results and the effect on the database of the query command is indicated by the supplied *behavior* that specifies command behavior.

For valid `CommandBehavior` values and for the command behavior of each `CommandBehavior` enumerated type, read the .NET Framework documentation.

When the `CommandType` property is set to `CommandType.StoredProcedure`, the `CommandText` property should be set to the name of the stored procedure. The command executes this stored procedure when `ExecuteReader()` is called.

If the stored procedure returns stored `REF CURSORS`, read the section on `OracleRefCursors` for more details. See ["OracleRefCursor Class"](#).

The value of 100 is used for the `FetchSize`. If 0 is specified, no rows are fetched. For more information, see "[Obtaining LONG and LONG RAW Data](#)".

If the value of the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, `OracleXmlCommandType.Delete`, or `OracleXmlCommandType.Query` then the `ExecuteReader` method throws an `InvalidOperationException`.

See Also:

- "[Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces](#)"
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- "[OracleRefCursor Class](#)"

ExecuteScalar

This method executes the query using the connection, and returns the first column of the first row in the result set returned by the query.

Declaration

```
// C#  
public override object ExecuteScalar();
```

Return Value

An object which represents the value of the first row, first column.

Implements

`IDbCommand`

Exceptions

`InvalidOperationException` - The command cannot be executed.

Remarks

Extra columns or rows are ignored. `ExecuteScalar` retrieves a single value (for example, an aggregate value) from a database. This requires less code than using the `ExecuteReader()` method, and then performing the operations necessary to generate the single value using the data returned by an `OracleDataReader`.

If the query does not return any row, it returns `null`.

The `ExecuteScalar` method throws an `InvalidOperationException`, if the value of the `XmlCommandType` property is set to one of the following `OracleXmlCommandType` values: `Insert`, `Update`, `Delete`, `Query`.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteScalarSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand("select count(*) from emp", con);

        object count = cmd.ExecuteScalar();

        Console.WriteLine("There are {0} rows in table emp", count);

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

ExecuteStream

This method executes a command using the `XmlCommandType` and `CommandText` properties and returns the result as an XML document in a new `Stream` object.

Declaration

```
// C#
public Stream ExecuteStream();
```

Return Value

A `Stream`.

Remarks

The behavior of `ExecuteStream` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`
`ExecuteStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`
`ExecuteStream` executes the select statement in the `CommandText` property, and if successful, returns an `OracleClob` object containing the XML document that was generated. `OracleClob` contains Unicode characters.

If the SQL query does not return any rows, then `ExecuteStream` returns an `OracleClob` object containing an empty XML document.
- `XmlCommandType = OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, or `OracleXmlCommandType.Delete`.

The value of the `CommandText` property is an XML document. `ExecuteStream` saves the data in that XML document to the table or view that is specified in the `XmlSaveProperties` property and an empty `OracleClob` is returned.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- [Oracle XML DB Developer's Guide](#)
- <http://www.oracle.com/technetwork/index.html>

ExecuteToStream

This method executes a command using the `XmlCommandType` and `CommandText` properties and appends the result as an XML document to the existing `Stream` provided by the application.

Declaration

```
// C#  
public void ExecuteToStream(Stream outputStream);
```

Parameters

- `outputStream`
A `Stream`.

Remarks

The behavior of `ExecuteToStream` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`
`ExecuteToStream` throws an `InvalidOperationException`.

- `XmlCommandType = OracleXmlCommandType.Query`
`ExecuteToStream` executes the select statement in the `CommandText` property, and if successful, appends the XML document that was generated to the given `Stream`.
If the SQL query does not return any rows, then nothing is appended to the given `Stream`. The character set of the appended data is Unicode.
- `XmlCommandType = OracleXmlCommandType.Insert, OracleXmlCommandType.Update, Or OracleXmlCommandType.Delete`
The value of the `CommandText` property is an XML document. `ExecuteToStream` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. Nothing is appended to the given `Stream`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- [Oracle XML DB Developer's Guide](#)
- <http://www.oracle.com/technetwork/index.html>

ExecuteXmlReader

This method executes the command using the `XmlCommandType` and `CommandText` properties and returns the result as an XML document in a .NET `XmlTextReader` object.

Declaration

```
// C#  
public XmlReader ExecuteXmlReader();
```

Return Value

An `XmlReader`.

Remarks

The behavior of `ExecuteXmlReader` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`
`ExecuteStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`
`ExecuteXmlReader` executes the select statement in the `CommandText` property, and if successful, returns a .NET `XmlTextReader` object containing the XML document that was generated.

If the XML document is empty, which can happen if the SQL query does not return any rows, then an empty .NET `XmlTextReader` object is returned.

- `XmlCommandType = OracleXmlCommandType.Insert, OracleXmlCommandType.Update, or OracleXmlCommandType.Delete.`

The value of the `CommandText` property is an XML document, and `ExecuteXmlReader` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. An empty .NET `XmlTextReader` object is returned.

See Also:

- "Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"
- OracleCommand Class
- OracleCommand Members
- *Oracle XML DB Developer's Guide*
- <http://www.oracle.com/technetwork/index.html>

Prepare

This method is not supported.

See Also:

- "Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"
- OracleCommand Class
- OracleCommand Members

OracleCommandBuilder Class

An `OracleCommandBuilder` object provides automatic SQL generation for the `OracleDataAdapter` when updates are made to the database.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.ComponentModel.Component`

`System.Data.Common.DbCommandBuilder`

`Oracle.DataAccess.Client.OracleCommandBuilder`

Declaration

```
// C#
public sealed class OracleCommandBuilder : DbCommandBuilder
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

`OracleCommandBuilder` automatically generates SQL statements for single-table updates when the `SelectCommand` property of the `OracleDataAdapter` is set. An exception is thrown if the `DataSet` contains multiple tables. The `OracleCommandBuilder` registers itself as a listener for `RowUpdating` events whenever its `DataAdapter` property is set. Only one `OracleDataAdapter` object and one `OracleCommandBuilder` object can be associated with each other at one time.

To generate `INSERT`, `UPDATE`, or `DELETE` statements, the `OracleCommandBuilder` uses `ExtendedProperties` within the `DataSet` to retrieve a required set of metadata. If the `SelectCommand` is changed after the metadata is retrieved (for example, after the first update), the `RefreshSchema` method should be called to update the metadata.

`OracleCommandBuilder` first looks for the metadata from the `ExtendedProperties` of the `DataSet`; if the metadata is not available, `OracleCommandBuilder` uses the `SelectCommand` property of the `OracleDataAdapter` to retrieve the metadata.

Example

The following example performs an update on the `EMP` table. It uses the `OracleCommandBuilder` object to create the `UpdateCommand` for the `OracleDataAdapter` object when `OracleDataAdapter.Update()` is called.

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleCommandBuilderSample
{
    static void Main()
    {
```

```
string constr = "User Id=scott;Password=tiger;Data Source=oracle";
string cmdstr = "SELECT empno, sal from emp";

// Create the adapter with the selectCommand txt and the
// connection string
OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

// Create the builder for the adapter to automatically generate
// the Command when needed
OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

// Create and fill the DataSet using the EMP
DataSet dataset = new DataSet();
adapter.Fill(dataset, "EMP");

// Get the EMP table from the dataset
DataTable table = dataset.Tables["EMP"];

// Indicate DataColumn EMPNO is unique
// This is required by the OracleCommandBuilder to update the EMP table
table.Columns["EMPNO"].Unique = true;

// Get the first row from the EMP table
DataRow row = table.Rows[0];

// Update the salary
double sal = double.Parse(row["SAL"].ToString());
row["SAL"] = sal + .01;

// Now update the EMP using the adapter
// The OracleCommandBuilder will create the UpdateCommand for the
// adapter to update the EMP table
adapter.Update(dataset, "EMP");

Console.WriteLine("Row updated successfully");
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Members](#)
- [OracleCommandBuilder Constructors](#)
- [OracleCommandBuilder Static Methods](#)
- [OracleCommandBuilder Properties](#)
- [OracleCommandBuilder Public Methods](#)
- [OracleCommandBuilder Events](#)

OracleCommandBuilder Members

OracleCommandBuilder members are listed in the following tables.

OracleCommandBuilder Constructors

OracleCommandBuilder constructors are listed in [Table 6-15](#).

Table 6-15 OracleCommandBuilder Constructors

Constructor	Description
OracleCommandBuilder Constructors	Instantiates a new instance of OracleCommandBuilder class (Overloaded)

OracleCommandBuilder Static Methods

OracleCommandBuilder static methods are listed in [Table 6-16](#).

Table 6-16 OracleCommandBuilder Static Methods

Method	Description
DeriveParameters	Queries for the parameters of a stored procedure or function, represented by a specified OracleCommand, and populates the OracleParameterCollection of the command with the return values
Equals	Inherited from System.Object (Overloaded)

OracleCommandBuilder Properties

OracleCommandBuilder properties are listed in [Table 6-17](#).

Table 6-17 OracleCommandBuilder Properties

Property	Description
Container	Inherited from System.ComponentModel.Component
CaseSensitive	Indicates whether or not double quotes are used around Oracle object names when generating SQL statements
CatalogLocation	<i>Not Supported</i>
CatalogSeparator	<i>Not Supported</i>
ConflictOption	<i>Not Supported</i>
DataAdapter	Indicates the OracleDataAdapter for which the SQL statements are generated
QuotePrefix	Specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words
QuoteSuffix	Specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words
SchemaSeparator	Specifies the character to be used for the separator between the schema identifier and other identifiers
Site	Inherited from System.ComponentModel.Component

OracleCommandBuilder Public Methods

OracleCommandBuilder public methods are listed in [Table 6-18](#).

Table 6-18 OracleCommandBuilder Public Methods

Public Method	Description
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Inherited from System.ComponentModel.Component
Equals	Inherited from System.Object (Overloaded)
GetDeleteCommand	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database (Overloaded)
GetHashCode	Inherited from System.Object
GetInsertCommand	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database (Overloaded)
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
GetUpdateCommand	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform updates on the database (Overloaded)
InitializeLifetimeService	Inherited from System.MarshalByRefObject
QuoteIdentifier	Returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped
RefreshSchema	Refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements
UnquoteIdentifier	Returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier
ToString	Inherited from System.Object

OracleCommandBuilder Events

The OracleCommandBuilder event is listed in [Table 6-19](#).

Table 6-19 OracleCommandBuilder Events

Event Name	Description
Disposed	Inherited from System.ComponentModel.Component

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)

OracleCommandBuilder Constructors

`OracleCommandBuilder` constructors create new instances of the `OracleCommandBuilder` class.

Overload List:

- [OracleCommandBuilder\(\)](#)
This constructor creates an instance of the `OracleCommandBuilder` class.
- [OracleCommandBuilder\(OracleDataAdapter\)](#)
This constructor creates an instance of the `OracleCommandBuilder` class and sets the `DataAdapter` property to the provided `OracleDataAdapter` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder()

This constructor creates an instance of the `OracleCommandBuilder` class.

Declaration

```
// C#  
public OracleCommandBuilder();
```

Remarks

Default constructor.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder(OracleDataAdapter)

This constructor creates an instance of the `OracleCommandBuilder` class and sets the `DataAdapter` property to the provided `OracleDataAdapter` object.

Declaration

```
// C#
public OracleCommandBuilder(OracleDataAdapter da);
```

Parameters

- *da*
The `OracleDataAdapter` object provided.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder Static Methods

`OracleCommandBuilder` static methods are listed in [Table 6-20](#).

Table 6-20 OracleCommandBuilder Static Methods

Method	Description
DeriveParameters	Queries for the parameters of a stored procedure or function, represented by a specified <code>OracleCommand</code> , and populates the <code>OracleParameterCollection</code> of the command with the return values
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

DeriveParameters

This method queries for the parameters of a stored procedure or function, represented by a specified `OracleCommand`, and populates the `OracleParameterCollection` of the command with the return values.

Declaration

```
// C#  
public static void DeriveParameters(OracleCommand command);
```

Parameters

- *command*

The command that represents the stored procedure or function for which parameters are to be derived.

Exceptions

`InvalidOperationException` - The `CommandText` is not a valid stored procedure or function name, the `CommandType` is not `CommandType.StoredProcedure`, or the `Connection.State` is not `ConnectionState.Open`.

Remarks

When `DeriveParameters` is used to populate the `Parameter` collection of an `OracleCommand` Object that represents a stored function, the return value of the function is bound as the first parameter (at position 0 of the `OracleParameterCollection`).

`DeriveParameters` can only be used for stored procedures or functions, not for anonymous PL/SQL blocks.

`DeriveParameters` incurs a database round-trip to retrieve parameter metadata prior to executing the stored procedure/function. It should only be used during design time. To avoid unnecessary database round-trips in a production environment, the `DeriveParameters` method itself should be replaced with the explicit parameter settings that were returned by the `DeriveParameters` method at design time.

`DeriveParameters` can only preserve the case of the stored procedure or function name if it is encapsulated by double-quotes. For example, if the stored procedure in the database is named `GetEmployees` with mixed-case, the `CommandText` property on the `OracleCommand` object must be set appropriately as in the following example:

```
cmd.CommandText = "\"GetEmployees\"";
```

Stored procedures and functions in a package must be provided in the following format:

```
<package name>.<procedure or function name>
```

For example, to obtain parameters for a stored procedure named `GetEmployees` (mixed-case) in a package named `EmpProcedures` (mixed-case), the name provided to the `OracleCommand` is:

```
"\"EmpProcedures\".\"GetEmployees\""
```

`DeriveParameters` cannot be used for object type methods.

The derived parameters contain all the metadata information that is needed for the stored procedure to execute properly. The application must provide the value of the parameters before execution, if required. The application may also modify the metadata information of the parameters before execution. For example, the `Size` property of the `OracleParameter` may be modified for PL/SQL character and string types to optimize the execution of the stored procedure.

The output values of derived parameters return as .NET Types by default. To obtain output parameters as provider types, the `OracleDbType` property of the parameter must be set explicitly by the application to override this default behavior. One quick way to do this is to set the `OracleDbType` to itself for all output parameters that should be returned as provider types.

The `BindByName` property of the supplied `OracleCommand` is left as is, but the application can change its value.

If the specified stored procedure or function is overloaded, the first overload is used to populate the parameters collection.

```
// Database Setup
/*
connect scott/tiger@oracle
CREATE OR REPLACE PROCEDURE MyOracleStoredProc (arg_in IN VARCHAR2,
    arg_out OUT VARCHAR2) IS
BEGIN
    arg_out := arg_in;
END;
/
*/

// C#
using System;
using System.Data;
using Oracle.DataAccess.Client;

class DeriveParametersSample
{
    static void Main()
    {
        // Create the PL/SQL Stored Procedure MyOracleStoredProc as indicated in
        // the preceding Database Setup

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand
```

```
OracleCommand cmd = new OracleCommand("MyOracleStoredProc", con);
cmd.CommandType = CommandType.StoredProcedure;

// Derive Parameters
OracleCommandBuilder.DeriveParameters(cmd);
Console.WriteLine("Parameters Derived");

// Prints "Number of Parameters for MyOracleStoredProc = 2"
Console.WriteLine("Number of Parameters for MyOracleStoredProc = {0}",
    cmd.Parameters.Count);

// The PL/SQL stored procedure MyOracleStoredProc has one IN and
// one OUT parameter. Set the Value for the IN parameter.
cmd.Parameters[0].Value = "MyText";

// The application may modify the other OracleParameter properties also
// This sample uses the default Size for the IN parameter and modifies
// the Size for the OUT parameter

// The default size for OUT VARCHAR2 is 4000
// Prints "cmd.Parameters[1].Size = 4000"
Console.WriteLine("cmd.Parameters[1].Size = " + cmd.Parameters[1].Size);

// Set the Size for the OUT parameter
cmd.Parameters[1].Size = 6;

// Execute the command
cmd.ExecuteNonQuery();

// Prints "cmd.Parameters[1].Value = MyText"
Console.WriteLine("cmd.Parameters[1].Value = " + cmd.Parameters[1].Value);

con.Close();
con.Dispose();
}
}
```

Example

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)
- [OracleCommand Class](#)
- [OracleParameter Class](#)
- [OracleParameterCollection Class](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework feature

OracleCommandBuilder Properties

OracleCommandBuilder properties are listed in [Table 6-21](#).

Table 6-21 OracleCommandBuilder Properties

Property	Description
Container	Inherited from <code>System.ComponentModel.Component</code>
CaseSensitive	Indicates whether or not double quotes are used around Oracle object names when generating SQL statements
CatalogLocation	<i>Not Supported</i>
CatalogSeparator	<i>Not Supported</i>
ConflictOption	<i>Not Supported</i>
DataAdapter	Indicates the <code>OracleDataAdapter</code> for which the SQL statements are generated
QuotePrefix	Specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words
QuoteSuffix	Specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words
SchemaSeparator	Specifies the character to be used for the separator between the schema identifier and other identifiers
Site	Inherited from <code>System.ComponentModel.Component</code>

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

CaseSensitive

This property indicates whether or not double quotes are used around Oracle object names (for example, tables or columns) when generating SQL statements.

Declaration

```
// C#  
bool CaseSensitive {get; set;}
```

Property Value

A `bool` that indicates whether or not double quotes are used.

Remarks

Default = false



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

CatalogLocation

This property is not supported.

Declaration

```
// C#  
public override CatalogLocation CatalogLocation {get; set;}
```

Exceptions

NotSupportedException - This property is not supported.

Remarks

This property is not supported.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

CatalogSeparator

This property is not supported.

Declaration

```
// C#  
public override string CatalogSeparator {get; set;}
```

Exceptions

NotSupportedException - This property is not supported.

Remarks

This property is not supported.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

ConflictOption

This property is not supported.

Declaration

```
// C#  
public override string ConflictOption {get; set;}
```

Exceptions

NotSupportedException - This property is not supported.

Remarks

This property is not supported.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

DataAdapter

This property indicates the `OracleDataAdapter` object for which the SQL statements are generated.

Declaration

```
// C#  
OracleDataAdapter DataAdapter{get; set;}
```

Property Value

An `OracleDataAdapter` object.

Remarks

Default = null



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

QuotePrefix

This property specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words.

Declaration

```
// C#  
public override string QuotePrefix {get; set;}
```

Property Value

The beginning character or characters to use. The default value is "\".

Remarks

This property is independent of any `OracleConnection` or `OracleCommand` objects.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

QuoteSuffix

This property specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words.

Declaration

```
// C#  
public override string QuoteSuffix {get; set;}
```

Property Value

The ending character or characters to use. The default value is "\".

Remarks

This property is independent of any `OracleConnection` or `OracleCommand` objects.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

SchemaSeparator

This property specifies the character to be used for the separator between the schema identifier and other identifiers.

Declaration

```
// C#  
public override string SchemaSeparator {get; set; }
```

Property Value

The character to be used as the schema separator.

Exceptions

`NotSupportedException` - The input value is not a dot (.).

Remarks

The default schema separator is a dot (.). The only acceptable value for this property is a dot (.).

This property is independent of any `OracleConnection` or `OracleCommand` objects.

Example

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;  
  
class SchemaSeperatorSample  
{  
    static void Main(string[] args)  
    {  
        try
```

```

{
    OracleCommandBuilder cmdBuilder = new OracleCommandBuilder();

    //schemaSeparator is dot(.)
    Console.WriteLine("schemaSeparator is {0}",
        cmdBuilder.SchemaSeparator);

    //set the schemaseparator, only '.' is allowed.
    cmdBuilder.SchemaSeparator = ".";

    // the only acceptable value for this property is a dot (.)
    // Hence the following line will throw NotSupportedException
    cmdBuilder.SchemaSeparator = "!";
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
}

```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder Public Methods

OracleCommandBuilder public methods are listed in [Table 6-22](#).

Table 6-22 OracleCommandBuilder Public Methods

Public Method	Description
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Inherited from System.ComponentModel.Component
Equals	Inherited from System.Object (Overloaded)
GetDeleteCommand	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database (Overloaded)
GetHashCode	Inherited from System.Object
GetInsertCommand	Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database (Overloaded)
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object

Table 6-22 (Cont.) OracleCommandBuilder Public Methods

Public Method	Description
GetUpdateCommand	Gets the automatically generated <code>OracleCommand</code> object that has the SQL statement (<code>CommandText</code>) perform updates on the database (Overloaded)
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
QuoteIdentifier	Returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped
RefreshSchema	Refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements
UnquoteIdentifier	Returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier
<code>ToString</code>	Inherited from <code>System.Object</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetDeleteCommand

Gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database

Overload List

- [GetDeleteCommand\(\)](#)
This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database when an application calls `Update()` on the `OracleDataAdapter`.
- [GetDeleteCommand\(bool\)](#)
This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database when an application calls `Update()` on the `OracleDataAdapter`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetDeleteCommand()

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetDeleteCommand();
```

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetDeleteCommand(bool)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetDeleteCommand(bool useColumnsForParameterNames);
```

Parameters

- `useColumnsForParameterNames`

If `true`, the method generates parameter names matching column names if possible. If `false`, the method binds parameters by position.

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

Remarks

If the `bool` is `true`, the method generates parameter names matching column names if possible. If `false`, the method binds parameters by position.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetInsertCommand

Gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform insertions on the database

Overload List

- [GetInsertCommand\(\)](#)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform insertions on the database when an application calls `Update()` on the `OracleDataAdapter`.

- [GetInsertCommand\(bool\)](#)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform insertions on the database when an application calls `Update()` on the `OracleDataAdapter`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetInsertCommand()

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform insertions on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetInsertCommand();
```

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetInsertCommand(bool)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform insertions on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetInsertCommand(bool useColumnsForParameterNames);
```

Parameters

- `useColumnsForParameterNames`

If `true`, the method generates parameter names matching column names if possible. If `false`, the method binds parameters by position.

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

Remarks

If the bool is `true`, the method generates parameter names matching column names if possible. If `false`, the method binds parameters by position.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetUpdateCommand

Gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database

Overload List

- [GetUpdateCommand\(\)](#)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

- [GetUpdateCommand\(bool\)](#)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetUpdateCommand()

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetUpdateCommand();
```

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetUpdateCommand(bool)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetUpdateCommand(bool useColumnsForParameterNames);
```

Parameters

- `useColumnsForParameterNames`

If true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

Remarks

If the bool is true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

QuoteIdentifier

This method returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped.

Declaration

```
// C#  
public override string QuoteIdentifier(string unquotedIdentifier);
```

Parameters

- `UnquotedIdentifier`
An unquoted identifier string.

Return Value

The quoted version of the identifier. Embedded quotes within the identifier are properly escaped.

Exceptions

ArgumentNullException - The input parameter is null.

Remarks

This method is independent of any `OracleConnection` or `OracleCommand` objects.

Example

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;  
  
class QuoteIdentifierSample  
{  
    static void Main(string[] args)  
    {  
        OracleCommandBuilder builder = new OracleCommandBuilder();  
        string quoteIdentifier = builder.QuoteIdentifier("US\"ER");  
  
        //quoteIdentifier for "US\"ER" is (\\"US\\"ER\\")  
        Console.WriteLine("quoteIdentifier is {0}" , quoteIdentifier);  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

RefreshSchema

This method refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements.

Declaration

```
// C#  
public override void RefreshSchema();
```

Remarks

An application should call `RefreshSchema` whenever the `SelectCommand` value of the `OracleDataAdapter` object changes.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

UnquoteIdentifier

This method returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier.

Declaration

```
// C#  
public override string UnquoteIdentifier(string quotedIdentifier);
```

Parameters

- *quotedIdentifier*
The quoted string identifier.

Return Value

The unquoted identifier, with escape notation for any embedded quotes removed.

Exceptions

ArgumentNullException - The input parameter is null.

ArgumentException - The input parameter is empty.

Remarks

This method is independent of any *OracleConnection* or *OracleCommand* objects.

Example

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;  
  
class UnQuoteIdentifierSample  
{  
    static void Main(string[] args)  
    {  
        //create an OracleCommandBuilder object.  
        OracleCommandBuilder builder = new OracleCommandBuilder();  
  
        string identifier = "US\"ER\"";  
        Console.WriteLine("Identifier is {0}", identifier);  
    }  
}
```

```

// quote the identifier
string quoteIdentifier = builder.QuoteIdentifier(identifier);

//quoteIdentifier of "US\ER" is (\US\ER)
Console.WriteLine("QuotedIdentifier is {0}" , quoteIdentifier);
string unquoteIdentifier = builder.UnquoteIdentifier(quoteIdentifier);

//And its unquoteIdentifier is US\ER
Console.WriteLine("UnquotedIdentifier is {0}" , unquoteIdentifier);
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder Events

The OracleCommandBuilder event is listed in [Table 6-23](#).

Table 6-23 OracleCommandBuilder Event

Event Name	Description
Disposed	Inherited from System.ComponentModel.Component

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleConfiguration Class

An OracleConfiguration is a static class for setting ODP.NET Core configuration data using a single programming interface.

Class Inheritance

System.Object

Oracle.ManagedDataAccess.Client.OracleConfiguration

Declaration

```
// C#
public sealed class OracleConfiguration
```

Requirements

Provider	ODP.NET Core
Assembly	Oracle.ManagedDataAccess.dll
Namespace	Oracle.ManagedDataAccess.Client
.NET Framework	4.6.1 or higher
.NET Core	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.ManagedDataAccess.Client;

namespace ODP_Core_Config_API
{
    class odp_core_config
    {
        static void Main(string[] args)
        {
            // This sample demonstrates how to use ODP.NET Core Configuration API

            // Add connect descriptors and net service names entries.
            OracleConfiguration.OracleDataSources.Add("orclpdb",
"(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=<hostname or IP>)(PORT=1521))
(CONNECT_DATA=(SERVICE_NAME=<service name>)(SERVER=dedicated)))");
            OracleConfiguration.OracleDataSources.Add("orcl",
"(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=<hostname or IP>)(PORT=1521))
(CONNECT_DATA=(SERVICE_NAME=<service name>)(SERVER=dedicated)))");

            // Set default statement cache size to be used by all connections.
            OracleConfiguration.StatementCacheSize = 25;

            // Disable self tuning by default.
            OracleConfiguration.SelfTuning = false;

            // Bind all parameters by name.
            OracleConfiguration.BindByName = true;

            // Set default timeout to 60 seconds.
            OracleConfiguration.CommandTimeout = 60;

            // Set default fetch size as 1 MB.
            OracleConfiguration.FetchSize = 1024 * 1024;
        }
    }
}
```

```
// Set tracing options
OracleConfiguration.TraceOption = 1;
OracleConfiguration.TraceFileLocation = @"D:\traces";
// Uncomment below to generate trace files
//OracleConfiguration.TraceLevel = 7;

// Set network properties
OracleConfiguration.SendBufferSize = 8192;
OracleConfiguration.ReceiveBufferSize = 8192;
OracleConfiguration.DisableOOB = true;

OracleConnection orclCon = null;

try
{
    // Open a connection
    orclCon = new OracleConnection("user id=hr; password=<password>;
data source=orclpdb");
    orclCon.Open();

    // Execute simple select statement that returns first 10 names from
EMPLOYEES table
OracleCommand orclCmd = orclCon.CreateCommand();
orclCmd.CommandText = "select first_name from employees where rownum
<= 10 ";

OracleDataReader rdr = orclCmd.ExecuteReader();

while (rdr.Read())
    Console.WriteLine("Employee Name: " + rdr.GetString(0));

Console.ReadLine();

rdr.Dispose();
orclCmd.Dispose();
}
finally
{
    // Close the connection
    if (null != orclCon)
        orclCon.Close();
}
}
```

 See Also:

- "Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"
- OracleConfiguration Members
- OracleConfiguration Connection Properties
- OracleConfiguration Secure Connection Properties
- OracleConfiguration Command Properties
- OracleConfiguration High Availability Properties
- OracleConfiguration Performance Properties
- OracleConfiguration Debug Tracing Properties

OracleConfiguration Members

OracleConfiguration members are listed in the following tables.

OracleConfiguration Connection Properties

OracleConfiguration Connection properties are listed in [Table 6-24](#).

Table 6-24 OracleConfiguration Connection Properties

Property	Description
DatabaseEditionName	Specifies the Oracle edition name for the connection object
DisableOOB	Specifies whether to enable Oracle Net Services to send or receive out-of-band break messages using urgent data provided by the underlying protocol
DrpcConnectionClass	Specifies a logical name that identifies the DRCP connection pool that the ODP.NET connection will use
HostnameDefaultServiceIsHost	Specifies whether to default the service name to the hostname in Oracle Easy Connect Naming so that the service name does not need to be specified
NamesDirectoryPath	Specifies the naming method order used for client name resolution lookups
OracleDataSources	Returns a collection of TNS entries added through OracleConfiguration
TcpConnectTimeout	Specifies the time, in seconds, for a client to establish a TCP connection (PROTOCOL=tcp in the TNS connect address) to the database server before it can time out
TnsAdmin	Specifies the tnsnames.ora and/or sqlnet.ora directory location

OracleConfiguration Secure Connection Properties

OracleConfiguration Secure Connection Properties are listed in [Table 6-25](#).

Table 6-25 OracleConfiguration Secure Connection Properties

Property	Description
HttpsProxy	Specifies HTTP proxy host name for tunneling SSL client connections
HttpsProxyPort	Specifies the forward HTTP proxy host port for tunneling TLS/SSL client connections
SqlNetAuthenticationServices	Enables one or more authentication services, such as TCP/IP with SSL
SqlNetEncryptionClient	Specifies the encryption client behavior
SqlNetEncryptionTypesClient	Specifies encryption algorithms that the client can use
SqlNetCryptoChecksumClient	Specifies the checksum client behavior
SqlNetCryptoChecksumTypesClient	Specifies the crypto-checksum algorithms the client can use
SqlNetWalletOverride	Specifies whether the client overrides the strong authentication credential with the stored wallet password credential for the database connection
SSLServerDNMatch	Enforces the database server distinguished name (DN) matches its service name
SSLVersion	Enforces the connection to use a specific SSL/TLS version
UseHttpsProxy	Enables forward HTTP proxy tunneling client connections
WalletLocation	Specifies the location of wallets

OracleConfiguration Command Properties

OracleConfiguration Command properties are listed in [Table 6-26](#).

Table 6-26 OracleConfiguration Command Properties

Property	Description
BindByName	Specifies whether the binding method used for the parameter collection is by name or by position
CommandTimeout	Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception

OracleConfiguration Directories Properties

OracleConfiguration Directories properties are listed in [Table 6-27](#).

Table 6-27 OracleConfiguration Directories Properties

Property	Description
DefaultAdminContext	Specifies the default directory entry that contains a LDAP Oracle Context from which connect identifiers can be created, modified, or looked up

Table 6-27 (Cont.) OracleConfiguration Directories Properties

Property	Description
DirectoryServers	Lists the host names and port numbers of the primary and alternate LDAP directory servers
DirectoryType	Specifies the directory server type used, such as Oracle Internet Directory or Microsoft Active Directory
LdapAdmin	Specifies the <code>ldap.ora</code> directory location
NamesLdapAuthenticateBind	Specifies whether the LDAP naming adapter should attempt to authenticate using a specified wallet when it connects to the LDAP directory to resolve the name in the connect string
NamesLdapConnTimeout	specifies the non-blocking connection timeout to the LDAP server

OracleConfiguration High Availability Properties

OracleConfiguration High Availability properties are listed in [Table 6-28](#).

Table 6-28 OracleConfiguration High Availability Properties

Property	Description
DbNotificationAddress	Specifies the address that the provider listens to for all notifications sent by the database for continuous query notification feature.
DbNotificationPort	Specifies the port number that the provider listens to for all notifications sent by the database for continuous query notification, Fast Connection Failover, and/or Runtime Connection Load Balancing features
HAEvents	Enables the application to receive Fast Connection Failover events for maintaining application high availability
OnsConfigFile	Specifies the configuration file to define Oracle Notification Service (ONS) behavior
OnsMode	Specifies the ONS daemon mode as either <code>local</code> or <code>remote</code>
OnsProtocol	Defines whether the ONS connection uses TCP/IP or TCP/IP with SSL/TLS
OnsWalletLocation	Specifies the directory location of the ONS wallets
OracleOnsServers	Returns a collection of logical ONS servers added through OracleConfiguration
ServiceRelocationConnectionTimeout	Specifies the time to wait before retrying connecting to a service that becomes unavailable.

OracleConfiguration Performance Properties

OracleConfiguration Performance properties are listed in [Table 6-29](#).

Table 6-29 OracleConfiguration Performance Properties

Property	Description
FetchSize	Specifies the total memory size, in bytes, that the provider allocates to cache data fetched in one database round-trip
LoadBalancing	Enables the application to receive runtime connection load balancing information
MaxStatementCacheSize	Specifies the maximum number of statements that can be cached when self-tuning is enabled
PerformanceCounters	Specifies the ODP.NET connection performance counters to publish so that they can be monitored
ReceiveBufferSize	Specifies the buffer space limit for receive operations of sessions
SelfTuning	Specifies whether self-tuning is enabled for an ODP.NET application
SendBufferSize	Specifies the buffer space limit for send operations of sessions
StatementCacheSize	Specifies the number of cursors or statements to be cached for each database connection
TcpNoDelay	Preempts delays in buffer flushing within the TCP/IP protocol stack

OracleConfiguration Debug Tracing Properties

OracleConfiguration Debug Tracing properties are listed in [Table 6-30](#).

Table 6-30 OracleConfiguration Debug Tracing Properties

Property	Description
TraceFileLocation	Specifies the destination directory to output provider traces
TraceLevel	Specifies the generated trace level to trace ODP.NET calls and diagnose provider issues
TraceOption	Specifies whether to generate a single trace file or multiple trace files for multithreaded applications

OracleConfiguration Connection Properties

OracleConfiguration Connection properties are listed in [Table 6-31](#).

Table 6-31 OracleConfiguration Connection Properties

Property	Description
DatabaseEditionName	Specifies the Oracle edition name for the connection object

Table 6-31 (Cont.) OracleConfiguration Connection Properties

Property	Description
DisableOOB	Specifies whether to enable Oracle Net Services to send or receive out-of-band break messages using urgent data provided by the underlying protocol
DrpcConnectionClass	Specifies a logical name that identifies the DRCP connection pool that the ODP.NET connection will use
HostnameDefaultServiceIsHost	Specifies whether to default the service name to the hostname in Oracle Easy Connect Naming so that the service name does not need to be specified
NamesDirectoryPath	Specifies the naming method order used for client name resolution lookups
OracleDataSources	Returns a collection of TNS entries added through OracleConfiguration
TcpConnectTimeout	Specifies the time, in seconds, for a client to establish a TCP connection (PROTOCOL=tcp in the TNS connect address) to the database server before it can time out
TnsAdmin	Specifies the tnsnames.ora and/or sqlnet.ora directory location

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DatabaseEditionName

This property specifies the Oracle edition name for the connection object. This property is used with the Oracle Edition-Based Redefinition feature.

Declaration

```
// C#
public static string DatabaseEditionName { get; set; }
```

Property Type

System.String

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DisableOOB

This property specifies whether to enable Oracle Net Services to send or receive out-of-band break messages using urgent data provided by the underlying protocol. Default is `false`.

Declaration

```
// C#  
public static bool DisableOOB { get; set; }
```

Property Type

`System.Boolean`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DrcpConnectionClass

This property specifies a logical name that identifies the DRCP connection pool that the ODP.NET connection will use. It will be used as a default if the `DrcpConnectionClass` property on the `OracleConnection` object is not set. It will be ignored for non-DRCP connections. Default value is `null`.

Declaration

```
// C#  
public static string DrcpConnectionClass { get; set; }
```

Property Type

`System.String`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

HostnameDefaultServiceIsHost

This property specifies whether to default the service name to the hostname in Oracle Easy Connect Naming so that the service name does not need to be specified.

Declaration

```
// C#  
public static bool HostnameDefaultServiceIsHost { get; set; }
```

Property Type

System.Boolean

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

NamesDirectoryPath

This property specifies the naming method order used for client name resolution lookups.

Declaration

```
// C#  
public static string NamesDirectoryPath { get; set; }
```

Property Type

System.String

Example

```
C#  
OracleConfiguration.NamesDirectoryPath = "(tnsnames, ldap)";
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleDataSources

This property returns a collection of TNS entries added through `OracleConfiguration`.

Declaration

```
// C#  
public static OracleDataSourceCollection OracleDataSources
```

Property

Type: `Oracle.ManagedDataAccess.Client.OracleDataSourceCollection`

Returns a static `OracleDataSourceCollection` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)
- [OracleDataSourceCollection Class](#)

TcpConnectTimeout

This property specifies the time, in seconds, for a client to establish a TCP connection (`PROTOCOL=tcp` in the TNS connect address) to the database server before it can time out. Default value is 60 seconds.

Declaration

```
// C#  
public static string TcpConnectTimeout { get; set; }
```

Property Type

`System.String`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

TnsAdmin

This property specifies the `tnsnames.ora` and/or `sqlnet.ora` directory location.

Declaration

```
// C#
public static string TnsAdmin { get; set; }
```

Property Type

`System.String`

The backslash (\) is a special character in .NET that represents the beginning of an escape sequence. To specify a directory location, use any one of the following formats in .NET so that backslashes are correctly represented in a directory location:

```
// C#
OracleConfiguration.TnsAdmin = "D:\\oracle\\client\\admin";
OracleConfiguration.TnsAdmin = @"D:\oracle\client\admin";
OracleConfiguration.TnsAdmin = "D:/oracle/client/admin";
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleConfiguration Secure Connection Properties

`OracleConfigurationSecure` Connection properties are listed in [Table 6-32](#).

Table 6-32 OracleConfiguration Secure Connection Properties

Property	Description
HttpsProxy	Specifies HTTP proxy host name for tunneling SSL client connections
HttpsProxyPort	Specifies the forward HTTP proxy host port for tunneling TLS/SSL client connections

Table 6-32 (Cont.) OracleConfiguration Secure Connection Properties

Property	Description
SqlNetAuthenticationServices	Enables one or more authentication services, such as TCP/IP with SSL
SqlNetEncryptionClient	Specifies the encryption client behavior
SqlNetEncryptionTypesClient	Specifies encryption algorithms that the client can use
SqlNetCryptoChecksumClient	Specifies the checksum client behavior
SqlNetCryptoChecksumTypesClient	Specifies the crypto-checksum algorithms the client can use
SqlNetWalletOverride	Specifies whether the client overrides the strong authentication credential with the stored wallet password credential for the database connection
SSLServerDNMatch	Enforces the database server distinguished name (DN) matches its service name
SSLVersion	Enforces the connection to use a specific SSL/TLS version
UseHttpsProxy	Enables forward HTTP proxy tunneling client connections
WalletLocation	Specifies the location of wallets

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

HttpsProxy

This property specifies HTTP proxy host name for tunneling SSL client connections.

Declaration

```
// C#
public static string HttpsProxy { get; set; }
```

Property Type

System.String

Values

HTTP proxy host name or IP address that can make an outbound connection to the internet hosts. Default is none.

Usage Notes

Clients can tunnel secure connections over forward HTTP proxy using HTTP CONNECT method. This helps in accessing the public cloud database service as it eliminates the requirement to open an outbound port on a client side firewall. This parameter is applicable only to TCP/IP connections with SSL/TLS.

This value takes effect only when `SQLNET.USE_HTTPS_PROXY=on` is set in `sqlnet.ora`. Increase the forward web proxy read timeout for requests to a higher value depending on client queries. Otherwise, the forward web proxy closes the connection assuming that no requests are made from the client.

This parameter is applicable with Oracle Connection Manager on the database server side.

Example

```
//C#  
HttpsProxy=www-proxy.mycompany.com
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

HttpsProxyPort

This property specifies the forward HTTP proxy host port for tunneling TLS/SSL client connections.

Declaration

```
// C#  
public static int HttpsProxyPort { get; set; }
```

Property Type

System.Int32

Values

Proxy port number. Default is none.

Usage Notes

This property forwards the HTTP proxy host port that receives HTTP CONNECT method. This parameter should be used along with `HTTPS_PROXY`. It takes effect only when `SQLNET.USE_HTTPS_PROXY=on` is set in `sqlnet.ora`.

Example

```
//C#  
HttpsProxyPort=80
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SqlNetAuthenticationServices

This property enables one or more authentication services, such as TCP/IP with SSL.

Declaration

```
// C#  
public static string SqlNetAuthenticationServices { get; set; }
```

Property Type

System.String

Valid Values: NTS, TCPS, or NONE.

Example

```
//C#  
OracleConfiguration.SqlNetAuthenticationServices = "(nts, tcps)";
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SqlNetEncryptionClient

This property specifies the encryption client behavior.

Declaration

```
// C#  
public static string SqlNetEncryptionClient { get; set; }
```

Property Type

System.String

Default value is accepted.

Valid Values:

- `accepted` - to enable the security service if required or requested by the database.
- `rejected` - to disable the security service, even if required by the database.
- `requested` - to enable the security service if the database allows it.
- `required` - to enable the security service and disallow the connection if the database is not enabled for the security service.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SqlNetEncryptionTypesClient

This property specifies encryption algorithms that the client can use.

Declaration

```
// C#  
public static string SqlNetEncryptionTypesClient { get; set; }
```

Property Type

System.String

Valid Values:

- `AES128`
- `AES192`
- `AES256`
- `3DES112`
- `3DES168`

Example

```
C#  
OracleConfiguration.SqlNetEncryptionTypesClient = "(aes128, aes192)";
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SqlNetCryptoChecksumClient

This property specifies the checksum client behavior.

Declaration

```
// C#  
public static string SqlNetCryptoChecksumClient { get; set; }
```

Property Type

System.String

Default value is accepted.

Valid Values:

- `accepted` - to enable the security service if required or requested by the database.
- `rejected` - to disable the security service, even if required by the database.
- `requested` - to enable the security service if the database allows it.
- `required` - to enable the security service and disallow the connection if the database is not enabled for the security service.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SqlNetCryptoChecksumTypesClient

This property specifies the crypto-checksum algorithms the client can use.

Declaration

```
// C#  
public static string SqlNetCryptoChecksumTypesClient { get; set; }
```

Property Type

System.String

Valid Values:

- SHA1
- SHA256
- SHA384
- SHA512

Example

```
C#  
OracleConfiguration.SqlNetCryptoChecksumTypesClient = "(SHA1, SHA256, SHA512)";
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SqlNetWalletOverride

This property specifies whether the client overrides the strong authentication credential with the stored wallet password credential for the database connection.

Declaration

```
// C#  
public static bool SqlNetWalletOverride { get; set; }
```

Property Type

System.Boolean

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SSLServerDNMatch

This property enforces the database server distinguished name (DN) matches its service name. Default value is `false`.

Declaration

```
// C#  
public static bool SSLServerDNMatch { get; set; }
```

Property Type

`System.Boolean`

Valid Values:

- `true` - to enforce a match. If the DN matches the service name, then the connection succeeds. If the DN does not match the service name, then the connection fails.
- `false` - to not enforce a match. If the DN does not match the service name, then the connection is successful, but an error is logged to the `sqlnet.log` file.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SSLVersion

This property enforces the connection to use a specific SSL/TLS version. The default value is an undetermined version.

Declaration

```
// C#  
public static string SSLVersion { get; set; }
```

Property Type

`System.String`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

UseHttpsProxy

This property enables forward HTTP proxy tunneling client connections.

Declaration

```
// C#  
public static String UseHttpsProxy { get; set; }
```

Property Type

System.String

Values

Valid values are on, off, 0, or 1. Default is off.

Usage Notes

If turned on, ODP.NET can tunnel secure connections over forward HTTP proxy using HTTP CONNECT method. This helps in accessing the public cloud database service as it eliminates the requirement to open an outbound port on a client side firewall.

This parameter is applicable with Oracle Connection Manager on the server side.

Example

```
//C#  
SQLNET.USE_HTTPS_PROXY=on
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

WalletLocation

This property specifies the location of wallets. Wallets are certificates, keys, and trustpoints processed by SSL/TLS.

Declaration

```
// C#
public static string WalletLocation { get; set; }
```

Property Type

System.String

Remarks

Microsoft Certificate Store (MCS) and file system wallets are supported.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleConfiguration Command Properties

OracleConfiguration Command properties are listed in [Table 6-33](#).

Table 6-33 OracleConfiguration Command Properties

Property	Description
BindByName	Specifies whether the binding method used for the parameter collection is by name or by position
CommandTimeout	Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

BindByName

This property specifies whether the binding method used for the parameter collection is by name or by position. Default value (`false`) is bind by position.

Declaration

```
// C#  
public static bool BindByName { get; set; }
```

Property Type

System.Boolean

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

CommandTimeout

This property specifies the number of seconds the command is allowed to execute before terminating the execution with an exception. Default value is 0 seconds, which results in no time limit.

Declaration

```
// C#  
public static int CommandTimeout { get; set; }
```

Property Type

System.System.Int32.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleConfiguration Directories Properties

OracleConfiguration Directories properties are listed in [Table 6-34](#) .

Table 6-34 OracleConfiguration Directories Properties

Property	Description
DefaultAdminContext	Specifies the default directory entry that contains a LDAP Oracle Context from which connect identifiers can be created, modified, or looked up
DirectoryServers	Lists the host names and port numbers of the primary and alternate LDAP directory servers
DirectoryType	Specifies the directory server type used, such as Oracle Internet Directory or Microsoft Active Directory
LdapAdmin	Specifies the <code>ldap.ora</code> directory location
NamesLdapAuthenticateBind	Specifies whether the LDAP naming adapter should attempt to authenticate using a specified wallet when it connects to the LDAP directory to resolve the name in the connect string
NamesLdapConnTimeout	specifies the non-blocking connection timeout to the LDAP server

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DefaultAdminContext

This property specifies the default directory entry that contains a LDAP Oracle Context from which connect identifiers can be created, modified, or looked up.

Declaration

```
// C#
public static string DefaultAdminContext { get; set; }
```

Property Type

System.String

Values

Valid distinguished name

Example

```
// C#
OracleConfiguration.DefaultAdminContext=@"o=OracleSoftware,c=US";
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DirectoryServers

This property lists the host names and port numbers of the primary and alternate LDAP directory servers.

Declaration

```
// C#  
public static string DirectoryServers { get; set; }
```

Property Type

System.String

Use the following format to list the host names and port numbers:

```
<HOST>:<PORT>[:<TLS/SSL PORT>]
```

Example

```
// C#  
OracleConfiguration.DirectoryServers="(ldap-server1:389, ldap-server2:400:636)";
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DirectoryType

This property specifies the directory server type used, such as Oracle Internet Directory or Microsoft Active Directory.

Declaration

```
// C#  
public static string DirectoryType { get; set; }
```

Property Type

System.String

Values

- *oid* for Oracle Internet Directory
- *ad* for Microsoft Active Directory

Example

```
// C#  
OracleConfiguration.DefaultAdminContext=@"oid";
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

LdapAdmin

This property specifies the `ldap.ora` directory location.

Declaration

```
// C#  
public static string LdapAdmin { get; set; }
```

Property Type

`System.String`

The `LdapAdmin` setting works in conjunction with the `TnsAdmin` setting to determine the `ldap.ora` search order.

Example

```
// C#  
OracleConfiguration.LdapAdmin=@"D:\user\ldap\";
```

Remarks

ODP.NET will search for `ldap.ora` using the following location search order:

1. `TnsAdmin` setting
2. `LdapAdmin` setting
3. Directory of the running ODP.NET Core assembly
4. Current working directory

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

NamesLdapAuthenticateBind

This property specifies whether the LDAP naming adapter should attempt to authenticate using a specified wallet when it connects to the LDAP directory to resolve the name in the connect string.

Declaration

```
// C#  
public static bool NamesLdapAuthenticateBind { get; set; }
```

Property Type

System.Boolean

If the parameter is set to `true`, then the LDAP connection is authenticated using a wallet whose location must be specified in the `OracleConfiguration.WalletLocation` property.

If the parameter is set to `false`, then the LDAP connection is established using an anonymous bind.

Default value is `false`.

Example

```
// C#  
OracleConfiguration.NamesLdapAuthenticateBind = true;
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

NamesLdapConnTimeout

This property specifies the non-blocking connection timeout to the LDAP server.

Declaration

```
// C#
public static Int32 NamesLdapConnTimeout { get; set; }
```

Property Type

```
System.Int32
```

This property sets the time to wait (in seconds) for a LDAP server connection before a time out error can occur.

The minimum value is -1, which indicates no connection timeout. The default value is 15 seconds.

Example

```
// C#
OracleConfiguration.NamesLdapConnTimeout = -1;
```

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleConfiguration High Availability Properties

OracleConfiguration High Availability properties are listed in [Table 6-35](#).

Table 6-35 OracleConfiguration High Availability Properties

Property	Description
DbNotificationAddress	Specifies the address that the provider listens to for all notifications sent by the database for continuous query notification feature
DbNotificationPort	Specifies the port number that the provider listens to for all notifications sent by the database for continuous query notification, Fast Connection Failover, and/or Runtime Connection Load Balancing features
HAEvents	Enables the application to receive Fast Connection Failover events for maintaining application high availability
OnsConfigFile	Specifies the configuration file to define Oracle Notification Service (ONS) behavior
OnsMode	Specifies the ONS daemon mode as either local or remote

Table 6-35 (Cont.) OracleConfiguration High Availability Properties

Property	Description
OnsProtocol	Defines whether the ONS connection uses TCP/IP or TCP/IP with SSL/TLS
OnsWalletLocation	Specifies the directory location of the ONS wallets
OracleOnsServers	Returns a collection of logical ONS servers added through <code>OracleConfiguration</code>
ServiceRelocationConnectionTimeout	Specifies the time to wait before retrying connecting to a service that becomes unavailable.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DbNotificationAddress

This property specifies the address that the provider listens to for all notifications sent by the database for continuous query notification feature.

Declaration

```
// C#
public static string DbNotificationAddress { get; set; }
```

Property Type

`System.String`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

DbNotificationPort

This property specifies the port number that the provider listens to for all notifications sent by the database for continuous query notification, Fast Connection Failover,

and/or Runtime Connection Load Balancing features. A value of -1 allows directs the provider to use a random port.

Declaration

```
// C#  
public static int DbNotificationPort { get; set; }
```

Property Type

System.Int32.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

HAEvents

This property enables the application to receive Fast Connection Failover events for maintaining application high availability. Default is `true`.

Declaration

```
// C#  
public static bool HAEvents { get; set; }
```

Property Type

System.Boolean



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OnsConfigFile

This property specifies the configuration file to define Oracle Notification Service (ONS) behavior. The file specified should contain the same local port and remote port values as specified in the `ons.config` file used by the local ONS daemon. This will enable the application to receive events from the local ONS daemon.

Declaration

```
// C#  
public static string OnsConfigFile { get; set; }
```

Property Type

System.String

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OnsMode

This property specifies the ONS daemon mode as either "local" or "remote".

For local configuration, configure and make available ONS on the node where ODP.NET is running so that ODP.NET can receive events directly from the local ONS daemon.

Remote configuration is used when the application directly receives ONS events from the ONS daemons running on remote machines. One of the advantages of this configuration is that no ONS daemon is needed on the client end and; therefore, there is no need to manage this process.

Declaration

```
// C#  
public static OnsConfigMode OnsMode { get; set; }
```

Property Type

System.String

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OnsProtocol

This property defines whether the ONS connection uses TCP/IP or TCP/IP with SSL/TLS.

Declaration

```
// C#  
public static string OnsProtocol { get; set; }
```

Property Type

System.String

Usage Notes

Valid values are TCP or TCPS. Default value is TCP.

Example

```
OracleConfiguration.OnsProtocol=TCPS
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OnsWalletLocation

This property specifies the directory location of the ONS wallets. Wallets are certificates, keys, and trustpoints processed by SSL/TLS.

Declaration

```
// C#  
public static string OnsWalletLocation { get; set; }
```

Property Type

System.String

Usage Notes

Default value is none.

Example

```
OracleConfiguration.OnsWalletLocation=@"D:\user\wallets\"
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleOnsServers

This property returns a collection of logical ONS servers added through OracleConfiguration.

Declaration

```
// C#  
public static OracleOnsServerCollection OracleOnsServers
```

Property

Type:Oracle.ManagedDataAccess.Client.OracleOnsServerCollection

Returns a static OracleOnsServerCollection object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)
- [OracleDataSourceCollection Class](#)

ServiceRelocationConnectionTimeout

This property specifies the time to wait before retrying connecting to a service that becomes unavailable. Default value is 90 seconds. Whenever a database service becomes unavailable, such as due to a service being relocated, an application can encounter numerous connectivity errors during this time. To avoid unnecessary connection attempts to an unavailable service which will result in an error, the driver will block any connection attempts until the service is up or until this property's specified time limit expires from the time when the service DOWN event was received, whichever comes first.

Declaration

```
// C#  
public static string ServiceRelocationConnectionTimeout { get; set; }
```

Property Type

System.String

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleConfiguration Performance Properties

OracleConfiguration Performance properties are listed in [Table 6-36](#).

Table 6-36 OracleConfiguration Performance Properties

Property	Description
FetchSize	Specifies the total memory size, in bytes, that the provider allocates to cache data fetched in one database round-trip
LoadBalancing	Enables the application to receive runtime connection load balancing information
MaxStatementCacheSize	Specifies the maximum number of statements that can be cached when self-tuning is enabled
PerformanceCounters	Specifies the ODP.NET connection performance counters to publish so that they can be monitored
ReceiveBufferSize	Specifies the buffer space limit for receive operations of sessions
SelfTuning	Specifies whether self-tuning is enabled for an ODP.NET application
SendBufferSize	Specifies the buffer space limit for send operations of sessions
StatementCacheSize	Specifies the number of cursors or statements to be cached for each database connection
TcpNoDelay	Preempts delays in buffer flushing within the TCP/IP protocol stack

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

FetchSize

This property specifies the total memory size, in bytes, that the provider allocates to cache data fetched in one database round-trip. Default value is 131072.

Declaration

```
// C#  
public static int FetchSize { get; set; }
```

Property Type

System.Int32

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

LoadBalancing

This property enables the application to receive runtime connection load balancing information. Default is `true`.

Declaration

```
// C#  
public static bool LoadBalancing { get; set; }
```

Property Type

System.Boolean

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

MaxStatementCacheSize

This property specifies the maximum number of statements that can be cached when self-tuning is enabled. Default value is 100.

Declaration

```
// C#  
public static int MaxStatementCacheSize { get; set; }
```

Property Type

System.Int32

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

PerformanceCounters

This property specifies the ODP.NET connection performance counters to publish so that they can be monitored.

Declaration

```
// C#  
public static Int64 PerformanceCounters { get; set; }
```

Property Type

System.Int64

Remarks

ODP.NET enables monitoring many different connection counters, including pooled and non-pooled connections. These counters can be monitored individually or together. Developers can set which counters to monitor prior to application startup using the `PerformanceCounters` property.

By default, performance counters are not enabled.

 **See Also:**

- [Connection Performance Counters](#) for more information on setting up and configuring counters.
- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

ReceiveBufferSize

This property specifies the buffer space limit for receive operations of sessions.

Declaration

```
// C#  
public static int ReceiveBufferSize { get; set; }
```

Property Type

System.Int32

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SelfTuning

This property specifies whether self-tuning is enabled for an ODP.NET application. By default, self-tuning (`true`) is enabled.

Declaration

```
// C#  
public static bool SelfTuning { get; set; }
```

Property Type

System.Boolean

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

SendBufferSize

This property specifies the buffer space limit for send operations of sessions.

Declaration

```
// C#  
public static int SendBufferSize { get; set; }
```

Property Type

System.Int32

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

StatementCacheSize

This property specifies the number of cursors or statements to be cached for each database connection. This setting corresponds to the connection string Statement Cache Size attribute. A value greater than zero enables statement caching. Default value is zero.

Declaration

```
// C#  
public static int StatementCacheSize { get; set; }
```

Property Type

System.Int32

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

TcpNoDelay

This property preempts delays in buffer flushing within the TCP/IP protocol stack. Default value is `true`.

Declaration

```
// C#
public static bool TcpNoDelay { get; set; }
```

Property Type

`System.Boolean`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleConfiguration Debug Tracing Properties

OracleConfiguration Debug Tracing properties are listed in [Table 6-37](#).

Table 6-37 OracleConfiguration Debug Tracing Properties

Property	Description
TraceFileLocation	Specifies the destination directory to output provider traces
TraceLevel	Specifies the generated trace level to trace ODP.NET calls and diagnose provider issues
TraceOption	Specifies whether to generate a single trace file or multiple trace files for multithreaded applications

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

TraceFileLocation

This property specifies the destination directory to output provider traces.

Declaration

```
// C#  
public static string TraceFileLocation { get; set; }
```

Property Type

System.String

Remarks

On Windows, the default TraceFileLocation is *<Windows user temporary folder>\ODP.NET\core\trace*. On Linux, the default is *<current user temporary folder>/ODP.NET/core/trace*. If you modify the trace file location, then do not use a write-protected directory, such as *C:* on Windows. Write-protection may prevent ODP.NET from being able to write a trace file to that particular directory location.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

TraceLevel

This property specifies the generated trace level to trace ODP.NET calls and diagnose provider issues. Errors will always be traced. Default value is 0 indicating tracing is disabled.

Declaration

```
// C#  
public static int TraceLevel { get; set; }
```

Property Type`System.Int32`

Valid Values:

- 1 = public APIs
- 2 = private APIs
- 4 = network APIs/data

These values can be bitwise ORed. To enable all traces, set `TraceLevel` to 7.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

TraceOption

This property specifies whether to generate a single trace file or multiple trace files for multithreaded applications. Default value is 0 indicating single trace file for all application threads.

Declaration

```
// C#  
public static int TraceOption { get; set; }
```

Property Type`System.Int32` **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConfiguration Class](#)
- [OracleConfiguration Members](#)

OracleConnection Class

An `OracleConnection` object represents a connection to an Oracle database.

Class Inheritance

System.Object

System.MarshalByRefObject

System.ComponentModel.Component

System.Data.Common.DbConnection

Oracle.DataAccess.Client.OracleConnection

Declaration

```
// C#
public sealed class OracleConnection : DbConnection, IDbConnection, ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleConnectionSample
{
    static void Main()
    {
        // Connect
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Execute a SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select * from emp";
        OracleDataReader reader = cmd.ExecuteReader();

        // Print all employee numbers
        while (reader.Read())
```

```

        Console.WriteLine(reader.GetInt32(0));

        // Clean up
        reader.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}

```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Members](#)
- [OracleConnection Constructors](#)
- [OracleConnection Static Properties](#)
- [OracleConnection Static Methods](#)
- [OracleConnection Properties](#)
- [OracleConnection Public Methods](#)
- [OracleConnection Events](#)

OracleConnection Members

OracleConnection members are listed in the following tables.

OracleConnection Constructors

OracleConnection constructors are listed in [Table 6-38](#).

Table 6-38 OracleConnection Constructors

Constructor	Description
OracleConnection Constructors	Instantiates a new instance of the OracleConnection class (Overloaded)

OracleConnection Static Properties

The OracleConnection static property is listed in [Table 6-40](#).

Table 6-39 OracleConnection Static Property

Property	Description
IsAvailable	Indicates whether or not the implicit database connection is available for use

OracleConnection Static Methods

The `OracleConnection` static methods are listed in [Table 6-40](#).

Table 6-40 OracleConnection Static Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>ClearPool</code>	Clears the connection pool that is associated with the provided <code>OracleConnection</code> object <i>Not supported in a .NET stored procedure</i>
<code>ClearAllPools</code>	Clears all connections from all the connection pools <i>Not supported in a .NET stored procedure</i>

OracleConnection Properties

`OracleConnection` properties are listed in [Table 6-41](#).

Table 6-41 OracleConnection Properties

Property	Description
<code>ActionName</code>	Specifies the action name for the connection
<code>ClientId</code>	Specifies the client identifier for the connection
<code>ClientInfo</code>	Specifies the client information for the connection
<code>ConnectionString</code>	Specifies connection information used to connect to an Oracle database
<code>ConnectionTimeout</code>	Indicates the maximum amount of time that the <code>Open</code> method can take to obtain a pooled connection before the request is terminated
<code>ConnectionType</code>	Determines whether a particular connection object is associated with a TimesTen database connection, an Oracle database connection, or no physical connection <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
<code>Container</code>	Inherited from <code>System.ComponentModel.Component</code>
<code>Credential</code>	Used to get or set an <code>OracleCredential</code> object on the connection
<code>Database</code>	<i>Not Supported</i>
<code>DatabaseDomainName</code>	Specifies the name of the database domain to which the connection is set
<code>DatabaseEditionName</code>	Sets or gets the edition name for the <code>OracleConnection</code> object
<code>DatabaseName</code>	Specifies the name of the database to which the connection is set

Table 6-41 (Cont.) OracleConnection Properties

Property	Description
DataSource	Specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect
DRCPClass	Specifies a logical name that identifies the DRCP connection pool that the ODP.NET connection will use
DRCPPurity	Specifies whether an application can reuse a pooled session (<code>Pooled</code>) or must use a new session (<code>New</code>)
HostName	Specifies the name of the host to which the connection is set
InstanceName	Specifies the name of the instance to which the connection is set
ModuleName	Specifies the module name for the connection
PDBName	Used to set and get the name of the pluggable database to which the session is connected to
ServerVersion	Specifies the version number of the Oracle database to which the <code>OracleConnection</code> has established a connection
ServiceName	Specifies the name of the service to which the connection is set
<code>Site</code>	Inherited from <code>System.ComponentModel.Component</code>
State	Specifies the current state of the connection
StatementCacheSize	Specifies the current size of the statement cache associated with this connection
SwitchedConnection	If the returned pooled connection changed its service name (<code>ServiceName</code>) or pluggable database (<code>PDBName</code>) in order to connect to the desired pluggable database, then this property will consider the connection switched

OracleConnection Public Methods

`OracleConnection` public methods are listed in [Table 6-42](#).

Table 6-42 OracleConnection Public Methods

Public Method	Description
BeginTransaction	Begins a local transaction (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i>
ChangeDatabase	<i>Not Supported</i>

Table 6-42 (Cont.) OracleConnection Public Methods

Public Method	Description
Clone	Creates a copy of an OracleConnection object <i>Not supported in a .NET stored procedure</i>
Close	Closes the database connection
CreateCommand	Creates and returns an OracleCommand object associated with the OracleConnection object
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Inherited from System.ComponentModel.Component
EnlistDistributedTransaction	Enables applications to explicitly enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure and .NET Core</i>
EnlistTransaction	Enables applications to enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i>
Equals	Inherited from System.Object (Overloaded)
FlushCache	Flushes all updates and deletes made through REF objects retrieved using this connection <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetSchema	Returns schema information for the data source of the OracleConnection
GetSessionInfo	Returns or refreshes the property values of the OracleGlobalization object that represents the globalization settings of the session (Overloaded)
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
Open	Opens a database connection with the property settings specified by the ConnectionString
OpenWithNewPassword	Opens a new connection with the new password (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i>
PurgeStatementCache	Flushes the Statement Cache by closing all open cursors on the database, when statement caching is enabled
SetSessionInfo	Alters the session's globalization settings with the property values provided by the OracleGlobalization object

Table 6-42 (Cont.) OracleConnection Public Methods

Public Method	Description
SetShardingKey(OracleShardingKey, OracleShardingKey)	Enables applications to set the sharding key and super sharding key before requesting a connection <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
ToString	Inherited from <code>System.Object</code>

OracleConnection Events

OracleConnection events are listed in [Table 6-43](#).

Table 6-43 OracleConnection Events

Event Name	Description
ConnectionOpen	This event is triggered upon the <code>OracleConnection.Open()</code> method
Disposed	Inherited from <code>System.ComponentModel.Component</code>
Failover	An event that is triggered when an Oracle failover occurs <i>Not supported in a .NET stored procedure</i> <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
HAEvent	An event that is triggered when an HA event occurs
InfoMessage	An event that is triggered for any message or warning sent by the database
StateChange	An event that is triggered when the connection state changes

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)

OracleConnection Constructors

OracleConnection constructors instantiate new instances of the OracleConnection class.

Overload List:

- [OracleConnection\(\)](#)

This constructor instantiates a new instance of the `OracleConnection` class using default property values.

- [OracleConnection\(string\)](#)

This constructor instantiates a new instance of the `OracleConnection` class with the provided connection string.

- [OracleConnection\(string, OracleCredential\)](#)

This constructor instantiates a new `OracleConnection` class instance using the provided connection string and `OracleCredential` class.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection()

This constructor instantiates a new instance of the `OracleConnection` class using default property values.

Declaration

```
// C#  
public OracleConnection();
```

Remarks

The properties for `OracleConnection` are set to the following default values:

- `ConnectionString` = empty string
- `ConnectionTimeout` = 15 (default value of 0 is used for the implicit database connection)
- `DataSource` = empty string
- `ServerVersion` = empty string

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection(string)

This constructor instantiates a new instance of the `OracleConnection` class with the provided connection string.

Declaration

```
// C#  
public OracleConnection(string connectionString);
```

Parameters

- `connectionString`

The connection information used to connect to the Oracle database.

Remarks

The `ConnectionString` property is set to the supplied `connectionString`. The `ConnectionString` property is parsed and an exception is thrown if it contains invalid connection string attributes or attribute values.

The properties of the `OracleConnection` object default to the following values unless they are set by the connection string:

- `ConnectionString` = empty string
- `ConnectionTimeout` = 15 (default value of 0 is used for the implicit database connection)
- `DataSource` = empty string
- `ServerVersion` = empty string

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection(string, OracleCredential)

This constructor instantiates a new `OracleConnection` class instance using the provided connection string and `OracleCredential` class.

Declaration

```
// C#  
public OracleConnection(string connectionString, OracleCredential orclCredential);
```

Parameters

- `connectionString`

connection string that does not contain any of user id, password, DBA Privilege, proxy user id, nor proxy password.

- *orclCredential*

OracleCredential object containing user credentials. If this parameter is passed as null then the behavior of OracleConnection will be same as OracleConnection with normal connection string.

Remarks

Use this constructor to create a new OracleConnection object with an OracleCredential object containing user credentials and a connection string that does not contain any of user id, password, DBA Privilege, proxy user id, nor proxy password.

Exceptions

InvalidOperationException is raised when non-null OracleCredential object is used with a connection string containing any of user id, password, DBA Privilege, proxy user id, or proxy password.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection Static Properties

The OracleConnection static property is listed in [Table 6-44](#).

Table 6-44 OracleConnection Static Property

Property	Description
IsAvailable	Indicates whether or not the implicit database connection is available for use



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

IsAvailable

This property indicates whether or the implicit database connection is available for use.

Declaration

```
// C#  
public static bool IsAvailable {get;}
```

Property Value

Returns `true` if the implicit database connection is available for use.

Remarks

The availability of the implicit database connection can be checked at runtime through this static property. When Oracle Data Provider for .NET is used within a .NET stored procedure, this property always returns `true`. Otherwise, `false` is returned.

To obtain an `OracleConnection` object in a .NET stored procedure that represents the implicit database connection, set the `ConnectionString` property of the `OracleConnection` object to `"context connection=true"` and invoke the `Open` method.

Note that not all features that are available for an explicit user connection are available for an implicit database connection. See ["Implicit Database Connection"](#) for details.

Example

```
// C# (Library/DLL)  
using System;  
using Oracle.DataAccess.Client;  
  
public class IsAvailableSample  
{  
    static void MyStoredProcedure()  
    {  
        OracleConnection con = new OracleConnection();  
        if (OracleConnection.IsAvailable)  
        {  
            // This function is invoked as a stored procedure  
            // Obtain the implicit database connection by setting  
            // "context connection=true" in the connection string  
            con.ConnectionString = "context connection=true";  
        }  
        else  
        {  
            // This function is not invoked as a stored procedure  
            // Set the connection string for a normal client connection  
            con.ConnectionString = "user id=scott;password=tiger;data source=oracle";  
        }  
  
        con.Open();  
        Console.WriteLine("connected!");  
    }  
}
```

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection Static Methods

The `OracleConnection` static methods are listed in [Table 6-45](#).

Table 6-45 OracleConnection Static Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>ClearPool</code>	Clears the connection pool that is associated with the provided <code>OracleConnection</code> object. <i>Not supported in a .NET stored procedure</i>
<code>ClearAllPools</code>	Clears all connections from all the connection pools <i>Not supported in a .NET stored procedure</i>

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ClearPool

This method clears the connection pool that is associated with the provided `OracleConnection` object.

Declaration

```
// C#  
public static void ClearPool(OracleConnection connection);
```

Remarks

When this method is invoked, all idle connections are closed and freed from the pool. Currently used connections are not discarded until they are returned to the pool.

Beginning with ODP.NET 12c Release 1 (12.1), `ClearPool` does not automatically repopulate the pool with new connections. This prevents the pool from being

repopulated with invalid connections if client remains unable to connect with the database server. Developers programmatically control when the pool is repopulated by calling `OracleConnection.Open()`, which will repopulate the pool with at least the `Min Pool Size` number of connections.

Connections created after this method invocation are not cleared unless another invocation is made.

This method can be invoked with an `OracleConnection` object before opening the connection as well as after, provided the `ConnectionString` is properly set.

Exceptions

`InvalidOperationException` – Either the connection pool cannot be found or the provided connection string is invalid.

Example

```
// C#
// Sample demonstrating the use of ClearPool API in OracleConnection class

using System;
using Oracle.DataAccess.Client;

class ClearPoolSample
{
    static void Main()
    {
        Console.WriteLine("Running ClearPool sample..." );
        // Set the connection string
        string strConn = "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min pool size=5;";
        OracleConnection conn = new OracleConnection(strConn);

        // Open the connection
        conn.Open();

        // Clears the connection pool associated with connection 'conn'
        OracleConnection.ClearPool (conn);

        // This connection will be placed back into the pool
        conn.Close ();

        // Open the connection again to create additional connections in the pool
        conn.Open();

        // Create a new connection object
        OracleConnection connNew = new OracleConnection(strConn);

        // Clears the pool associated with Connection 'connNew'
        // Since the same connection string is set for both the connections,
        // connNew and conn, they will be part of the same connection pool.
        // We need not do an Open() on the connection object before calling
        // ClearPool
        OracleConnection.ClearPool (connNew);

        // cleanup
        conn.Close();
        Console.WriteLine("Done!");
    }
}
```


 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ClearAllPools

This method clears all connections from all the connection pools.

Declaration

```
// C#  
public static void ClearAllPools();
```

Remarks

This call is analogous to calling `ClearPool` for all the connection pools that are created for the application.

Exceptions

`InvalidOperationException` – No connection pool could be found for the application.

Example

```
// C#  
// Sample demonstrating the use of ClearAllPools API in OracleConnection class  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ClearAllPoolsSample  
{  
    static void Main()  
    {  
        Console.WriteLine("Running ClearAllPools sample..." );  
        // Set the connection string  
        string strConn = "User Id=scott;Password=tiger;Data Source=oracle;" +  
            "Min pool size=5";  
        OracleConnection conn = new OracleConnection(strConn);  
  
        // Create another connection object with a different connection string  
        string strConnNew = "User Id=scott;Password=tiger;Data Source=oracle;";  
        OracleConnection connNew = new OracleConnection(strConnNew);  
  
        // Open the connections. Separate pools are created for conn and connNew  
        conn.Open();  
        connNew.Open();  
  
        // Clears the pools associated with conn and connNew  
        OracleConnection.ClearAllPools ();  
  
        // cleanup
```

```

conn.Close();
connNew.Close();
Console.WriteLine("Done!");
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["ClearPool"](#)

OracleConnection Properties

OracleConnection properties are listed in [Table 6-46](#)

Table 6-46 OracleConnection Properties

Property	Description
ActionName	Specifies the action name for the connection
ClientId	Specifies the client identifier for the connection
ClientInfo	Specifies the client information for the connection
ConnectionString	Specifies connection information used to connect to an Oracle database
ConnectionTimeout	Indicates the maximum amount of time that the Open method can take to obtain a pooled connection before the request is terminated
ConnectionType	Determines whether a particular connection object is associated with a TimesTen database connection, an Oracle database connection, or no physical connection <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
Container	Inherited from System.ComponentModel.Component
Credential	Used to get or set an OracleCredential object on the connection
Database	<i>Not Supported</i>
DatabaseDomainName	Specifies the name of the database domain to which the connection is set
DatabaseEditionName	Sets or gets the edition name for the OracleConnection object

Table 6-46 (Cont.) OracleConnection Properties

Property	Description
DatabaseName	Specifies the name of the database to which the connection is set
DataSource	Specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect
DRCPConnectionClass	Specifies a logical name that identifies the DRCP connection pool that the ODP.NET connection will use
DRCPpurity	Specifies whether an application can reuse a pooled session (<code>Pooled</code>) or must use a new session (<code>New</code>)
HostName	Specifies the name of the host to which the connection is set
InstanceName	Specifies the name of the instance to which the connection is set
ModuleName	Specifies the module name for the connection
PDBName	Used to set and get the name of the pluggable database to which the session is connected to
ServerVersion	Specifies the version number of the Oracle database to which the <code>OracleConnection</code> has established a connection
ServiceName	Specifies the name of the service to which the connection is set
<code>Site</code>	Inherited from <code>System.ComponentModel.Component</code>
State	Specifies the current state of the connection
StatementCacheSize	Specifies the current size of the statement cache associated with this connection
SwitchedConnection	If the returned pooled connection changed its service name (<code>ServiceName</code>) or pluggable database (<code>PDBName</code>) in order to connect to the desired pluggable database, then this property will consider the connection switched.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ActionName

This property specifies the action name for the connection.

Declaration

```
// C#  
public string ActionName {set;}
```

Property Value

The string to be used as the action name.

Remarks

The default value is `null`.

Using the `ActionName` property allows the application to set the action name in the application context for a given `OracleConnection` object.

In unmanaged ODP.NET, the `ActionName` property is reset to `null` when the `Close` or `Dispose` method is called on the `OracleConnection` object. In managed ODP.NET, it is reset to `null` (assuming no new value is assigned) upon the next database round trip following a `Close` or `Dispose` method call on the `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#)
- [Oracle Database Security Guide](#)

ClientId

This property specifies the client identifier for the connection.

Declaration

```
// C#  
public string ClientId {set;}
```

Property Value

The string to be used as the client identifier.

Remarks

The default value is `null`.

Using the `ClientId` property allows the application to set the client identifier in the application context for a given `OracleConnection` object.

In unmanaged ODP.NET, the `ClientId` property is reset to null when the `Close` or `Dispose` method is called on the `OracleConnection` object. In managed ODP.NET, it is reset to null (assuming no new value is assigned) upon the next database round trip following a `Close` or `Dispose` method call on the `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#)
- *Oracle Database Security Guide*

ClientInfo

This property specifies the client information for the connection.

Declaration

```
// C#  
public string ClientInfo {set;}
```

Property Value

The string to be used as the client information.

Remarks

The default value is `null`.

Using the `ClientInfo` property allows the application to set the client information in the application context for a given `OracleConnection` object.

In unmanaged ODP.NET, the `ClientInfo` property is reset to null when the `Close` or `Dispose` method is called on the `OracleConnection` object. In managed ODP.NET, it is reset to null (assuming no new value is assigned) upon the next database round trip following a `Close` or `Dispose` method call on the `OracleConnection` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#)
- *Oracle Database Security Guide*

ConnectionString

This property specifies connection information used to connect to an Oracle database.

Declaration

```
// C#  
public override string ConnectionString{get; set;}
```

Property Value

If the connection string is supplied through the constructor, this property is set to that string.

Implements

IDbConnection

Exceptions

ArgumentException - An invalid syntax is specified for the connection string.

InvalidOperationException - ConnectionString is being set while the connection is open.

Remarks

The default value is an empty string.

ConnectionString must be a string of attribute name and value pairings, separated by a semi-colon, for example:

```
"User Id=scott;password=tiger;data source=oracle"
```

If the ConnectionString is not in a proper format, an exception is thrown. All spaces are ignored unless they are within double quotes.

When the ConnectionString property is set, the OracleConnection object immediately parses the string for errors. An ArgumentException is thrown if the ConnectionString contains invalid attributes or invalid values. Attribute values for User Id, Password, Proxy User Id, Proxy Password, and Data Source (if provided) are not validated until the Open method is called.

The connection must be closed to set the `ConnectionString` property. When the `ConnectionString` property is reset, all previously set values are reinitialized to their default values before the new values are applied.

Starting with ODP.NET 11.1, password and proxy password connection string attribute values are accepted as case-sensitive strings. Thus, they are passed to the database for authentication in the case provided in the connection string. Therefore, if the database is configured to support case-sensitive passwords, passwords must be passed in the correct case.

If a connection string attribute is set more than once, the last setting takes effect and no exceptions are thrown.

Boolean connection string attributes can be set to either `true`, `false`, `yes`, or `no`.

Remarks (.NET Stored Procedure)

To obtain an `OracleConnection` object in a .NET stored procedure that represents the implicit database connection, set the `ConnectionString` property of the `OracleConnection` object to `"context connection=true"` and invoke the `Open` method. Other connection string attributes cannot be used in conjunction with `"context connection"` when it is set to `true`.

Supported Connection String Attributes

Table 6-47 lists the supported connection string attributes.

Table 6-47 Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Application Continuity	Enables database requests to automatically replay transactional or non-transactional operations in a non-disruptive and rapid manner in the event of a severed database session, which results in a recoverable error. <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>	true
Connection Lifetime	Minimum life time (in seconds) of the connection. This attribute specifies the lifetime of the connection in seconds. Before the <code>Connection</code> is placed back into the pool upon a <code>Close()</code> or <code>Dispose()</code> call, the lifetime of the connection is checked. If the lifetime of the connection exceeds this property value, then the connection is destroyed. If this property value is 0, then the connection lifetime is never checked.	0

Table 6-47 (Cont.) Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Connection Timeout	<p>The time to wait (in seconds) for a new connection or an idle connection from the connection pool before a connection time out error can occur.</p> <p>This attribute specifies the minimum amount of time (in seconds) that the <code>Open()</code> method must take to obtain a pooled connection before it terminates the request. This value comes into effect only if no free connection is available from the connection pool and the <code>Max Pool Size</code> is reached. If a free connection is not available within the specified time, an exception is thrown. <code>Connection Timeout</code> does not limit the time required to open new connections.</p> <p>This attribute value takes effect for pooled connection requests and not for new connection requests.</p> <p>(The default value is 0 for the implicit database connection in a .NET stored procedure.)</p>	15
Context Connection	<p>Returns an implicit database connection if set to true.</p> <p>An implicit database connection can only be obtained from within a .NET stored procedure. Other connection string attributes cannot be used in conjunction with "context connection" when it is set to true.</p> <p><i>Supported in a .NET stored procedure only</i></p>	false
Data Source	Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.	empty string
DBA Privilege	<p>Administrative privileges <code>SYSDBA</code> or <code>SYSOPER</code>.</p> <p>This connection string attribute only accepts <code>SYSDBA</code> or <code>SYSOPER</code> as the attribute value. It is case-insensitive.</p>	empty string
Decr Pool Size	<p>Number of connections that are closed when an excessive amount of established connections are unused.</p> <p>This connection string attribute controls the maximum number of unused connections that are closed when the pool regulator makes periodic checks. The regulator thread is spawned every 3 minutes and closes up to <code>Decr Pool Size</code> amount of pooled connections if they are not used. The pool regulator never takes the total number of connections below the <code>Min Pool Size</code> by closing pooled connections.</p>	1

Table 6-47 (Cont.) Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Enlist	<p>Controls the enlistment behavior and capabilities of a connection in context of COM+ transactions or System.Transactions.</p> <p>If this attribute is set to <code>true</code>, the connection is automatically enlisted in the thread's transaction context. If this attribute is <code>false</code>, no enlistments are made. If this attribute is set to <code>dynamic</code>, applications can dynamically enlist in distributed transactions. This attribute can be set to <code>true</code>, <code>false</code>, <code>yes</code>, <code>no</code>, or <code>dynamic</code>.</p>	<code>true</code>
HA Events	<p>Enables ODP.NET connection pool to proactively remove connections from the pool when an Oracle database service, service member, or node goes down.</p> <p>This feature can be used with Global Data Services, including Oracle RAC, Data Guard, GoldenGate, and single instance deployments. "pooling=true" must also be set</p> <p>This attribute can be set to <code>true</code>, <code>false</code>, <code>yes</code>, or <code>no</code>.</p>	<code>true</code>
Load Balancing	<p>Enables ODP.NET connection pool to balance work requests across Oracle database instances based on the load balancing advisory and service goal.</p> <p>This feature can be used with Global Data Services, including Oracle RAC, Active Data Guard, and GoldenGate. "pooling=true" must also be set.</p> <p>This attribute can be set to <code>true</code>, <code>false</code>, <code>yes</code>, or <code>no</code>.</p>	<code>true</code>
Incr Pool Size	<p>Number of new connections to be created when all connections in the pool are in use.</p> <p>This connection string attribute determines the number of new connections that are established when a pooled connection is requested, but no unused connections are available and Max Pool Size is not reached. If new connections have been created for a pool, the regulator thread skips a cycle and does not have an opportunity to close any connections for 6 minutes. Note, however, that some connections can be still be closed during this time if their lifetime has been exceeded.</p>	5

Table 6-47 (Cont.) Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Max Pool Size	Maximum number of connections in a pool. This attribute specifies the maximum number of connections allowed in the particular pool used by that <code>OracleConnection</code> . Simply changing this attribute in the connection string does not change the <code>Max Pool Size</code> restriction on a currently existing pool. Doing so simply creates a new pool with a different <code>Max Pool Size</code> restriction. This attribute must be set to a value greater than the <code>Min Pool Size</code> . This value is ignored unless <code>Pooling</code> is turned on.	100
Metadata Pooling	Caches metadata information. This attribute indicates whether or not metadata information for executed queries are cached for improved performance.	True
Min Pool Size	Minimum number of connections in a pool. This attribute specifies the minimum number of connections to be maintained by the pool during its entire lifetime. Simply changing this attribute in the connection string does not change the <code>Min Pool Size</code> restriction on a currently existing pool. Doing so simply creates a new pool with a different <code>Min Pool Size</code> restriction. This value is ignored unless <code>Pooling</code> is turned on.	1
Password	Password for the user specified by <code>User Id</code> . This attribute specifies an Oracle user's password. <code>Password</code> is case-sensitive by default for Oracle Database 11g release 1 (11.1) and later.	empty string
Persist Security Info	Retrieval of the password in the connection string. If this attribute is set to <code>false</code> , the <code>Password</code> value setting is not returned when the application requests the <code>ConnectionString</code> after the connection is successfully opened by the <code>Open()</code> method. This attribute can be set to either <code>true</code> , <code>false</code> , <code>yes</code> , or <code>no</code> .	false

Table 6-47 (Cont.) Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Pooling	<p>Connection pooling.</p> <p>This attribute specifies whether or not connection pooling is to be used. Pools are created using an attribute value matching algorithm. This means that connection strings which only differ in the number of spaces in the connection string use the same pool. If two connection strings are identical except that one sets an attribute to a default value while the other does not set that attribute, both requests obtain connections from the same pool. This attribute can be set to either <code>true</code>, <code>false</code>, <code>yes</code>, or <code>no</code>.</p>	<code>true</code>
Promotable Transaction	<p>Promotable to distributed transaction or not.</p> <p>If "promotable" is specified, the first and all subsequent connections opened in the same <code>TransactionScope</code> enlist in the same distributed transaction. If "local" is specified, the first connection opened in the <code>TransactionScope</code> uses a local transaction.</p>	<code>promotable</code>
Proxy User Id	<p>User name of the proxy user.</p> <p>This connection string attribute specifies the middle-tier user, or the proxy user, who establishes a connection on behalf of a client user specified by the <code>User Id</code> attribute. ODP.NET attempts to establish a proxy connection if either the <code>Proxy User Id</code> or the <code>Proxy Password</code> attribute is set to a non-empty string.</p> <p>For the proxy user to connect to an Oracle database using operating system authentication, the <code>Proxy User Id</code> must be set to <code>"/</code>". The <code>Proxy Password</code> is ignored in this case. The <code>User Id</code> cannot be set to <code>"/</code>" when establishing proxy connections. The case of this attribute value is preserved.</p>	<code>empty string</code>
Proxy Password	<p>Password of the proxy user.</p> <p>This connection string attribute specifies the password of the middle-tier user or the proxy user. This user establishes a connection on behalf of a client user specified by the <code>User Id</code> attribute. ODP.NET attempts to establish a proxy connection if either the <code>Proxy User Id</code> or the <code>Proxy Password</code> attribute is set to a non-empty string.</p> <p>The case of this attribute value is preserved if it is surrounded by double quotes.</p>	<code>empty string</code>

Table 6-47 (Cont.) Supported Connection String Attributes

Connection String Attribute	Description	Default Value
Statement Cache Purge	Statement cache purged when the connection goes back to the pool. If statement caching is enabled, setting this attribute to <code>true</code> purges the Statement Cache when the connection goes back to the pool.	<code>false</code>
Statement Cache Size	Statement cache enabled and cache size set size, that is, the maximum number of statements that can be cached. A value greater than zero enables statement caching and sets the cache size to itself. This value should not be greater than the value of the <code>OPEN_CURSORS</code> parameter set in the <code>init.ora</code> database configuration file.	<code>0</code>
Self Tuning	Enables or disables self-tuning for the connection. If self-tuning is enabled, then the <code>StatementCacheSize</code> settings in the registry, configuration files, and connection string are ignored. If self-tuning is disabled, then a <code>StatementCacheSize</code> value of <code>0</code> is used unless <code>StatementCachSize</code> is specified in the registry, configuration file, or connection string.	<code>true</code>
User Id	Oracle user name. This attribute specifies the Oracle user name. The case of this attribute value is preserved if it is surrounded by double quotes. For the user to connect to an Oracle database using operating system authentication, set the <code>User Id</code> to <code>"/</code> . Any <code>Password</code> attribute setting is ignored in this case.	empty string
Validate Connection	Validation of connections coming from the pool. Validation causes a round-trip to the database for each connection. Therefore, it should only be used when necessary.	<code>false</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ConnectionTimeout

This property indicates the minimum amount of time that the `Open` method can take to obtain a pooled connection before the request is terminated.

Declaration

```
// C#  
public override int ConnectionTimeout {get;}
```

Property Value

The minimum time allowed for a pooled connection request, in seconds.

Implements

`IDbConnection`

Remarks

This property indicates the connection timeout that has been set using the `ConnectionString` attribute `Connection Timeout`.

This property is read-only.

Remarks (.NET Stored Procedure)

There is no connection string specified by the application and a connection on the implicit database is always available, therefore, this property is set to 0.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ConnectionType

This property enables an ODP.NET application to determine whether a particular connection object is associated with an Oracle database connection, a TimesTen database connection, or no physical connection at all.

Declaration

```
// C#  
public OracleConnectionType ConnectionType {get;}
```

Property Value

The `OracleConnectionType` that this connection object is associated with.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [OracleConnectionType Enumeration](#)

Credential

This property is used to get or set an `OracleCredential` object on the connection.

Declaration

```
// C#  
public OracleCredential Credential { get; set; }
```

Property Value

An `OracleCredential` object to be used for opening connection.

Remarks

To obtain the `OracleCredential` object through the property getter, "persist security info" must be set to true in the connection string.

If "Persist security info" is set to false in the Connection String, then the `OracleCredential` object is not returned through the property getter after the password has been validated.

The application can set this property with an `OracleCredential` object. An `InvalidOperationException` will be raised in following scenarios:

- If connection is already open.
- If connection string has already been set on this connection and it contains any of user id, password, DBA Privilege, proxy user id or proxy password.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [OracleConnectionType Enumeration](#)

Database

This property is not supported.

Declaration

```
// C#  
public override string Database {get;}
```

Property Value

A string.

Implements

IDbConnection.Database

Remarks

This property is not supported. It always returns an empty string.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DatabaseDomainName

This property specifies the name of the database domain that this connection is connected to.

Declaration

```
// C#  
public string DatabaseDomainName {get;}
```

Property Value

The database domain that this connection is connected to.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DatabaseEditionName

`DatabaseEditionName` property sets or gets the edition name for the `OracleConnection` object.

Declaration

```
// C#  
public string DatabaseEditionName {get;set;}
```

Property Value

A string to be used as the edition name for the `OracleConnection` object.

Exceptions

- `InvalidOperationException()` - if the connection is already open.
- `InvalidOperationException()` - If `CPVersion` is set to 1.0 when the connection is opened. `DatabaseEditionName` property is supported only with `CPVersion` of 2.0 or higher.

Remarks

Property must be set before opening a connection or after closing a connection.

The edition name for the connection to use can be set in one of three places: `DatabaseEditionName` in the application code, `Edition` in the .NET configuration file, or `Edition` in the Windows Registry. The .NET configuration value overrides the Registry value and the `DatabaseEditionName` property value overrides the .NET configuration value.

`DatabaseEditionName` property value is case sensitive.

Only supported for .NET Framework 4 and higher.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DatabaseName

This property specifies the name of the database that this connection is connected to.

Declaration

```
// C#  
public string DatabaseName {get;}
```


Property Value

The database that this connection is connected to.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DataSource

This property specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect

Declaration

```
// C#  
public override string DataSource {get;}
```

Property Value

Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.

Remarks (.NET Stored Procedure)

The value of this property is always an empty string for the implicit database connection.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DRCPConnectionString

This property specifies a logical name that identifies the DRCP connection pool that the ODP.NET connection will use.

Declaration

```
// C#  
public string DRCPConnectionString {get; set;}
```

Property Value

The string to be used that uniquely identifies the DRCP server side connection pool for the ODP.NET application to use.

Exceptions

- `InvalidOperationException()` - if `CPVersion=1.0` and the `DRCPConnectionString` is set to a non-null / non-empty string. Applies to unmanaged ODP.NET only.
- `InvalidOperationException()` - if the `DRCPConnectionString` is set to a non-null / non-empty string after opening a connection.
- `InvalidOperationException()` - if DRCP is not enabled and the `DRCPConnectionString` is set to a non-null / non-empty string.

Remarks

If an application will share the a DRCP connection pool across multiple middle tier servers, then the application will have the option to set the `DRCPConnectionString` property to a string value that uniquely identifies the server pool. If a DRCP connection is opened with this property populated, ODP.NET will direct DRCP to use a connection from that specific server pool.

The default value is null. The character limit is 1024 minus the number of characters in the user id.

If this property is used, it must be set prior to opening the connection.

Only supported for .NET Framework 4 and higher.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DRCPPurity

Session purity specifies whether an application can reuse a pooled session (`Pooled`) or must use a new session (`New`).

Declaration

```
// C#  
public string DRCPPurity {get; set;}
```

Property Value

`OracleDRCPPurity` Enumeration values.

Exceptions

- `InvalidOperationException()` - if `CPVersion=1.0` and the `DRCPpurity` is set to a non-null / non-empty string. Applies to unmanaged ODP.NET only.
- `InvalidOperationException()` - if the `DRCPpurity` is set to a non-null / non-empty string after opening a connection.
- `InvalidOperationException()` - if DRCP is not enabled and the `DRCPpurity` is set to a non-null / non-empty string.

Remarks

The default value is `Pooled`.

If set to `New`, then ODP.NET will dispense a new DRCP connection, rather than try to find an existing connection from the pool. In general, this property is used by applications that want a connection without any preexisting session state set.

If set to `Pooled`, then ODP.NET will first attempt to use a preexisting connection, that already exists in the DRCP pool.

Only supported for .NET Framework 4 and higher.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [OracleDRCPpurity Enumeration](#)

HostName

This property specifies the name of the host that this connection is connected to.

Declaration

```
// C#  
public string HostName {get;}
```

Property Value

The host that this connection is connected to.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

InstanceName

This property specifies the name of the instance that this connection is connected to.

Declaration

```
// C#  
public string InstanceName {get;}
```

Property Value

The instance that this connection is connected to.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ModuleName

This property specifies the module name for the connection.

Declaration

```
// C#  
public string ModuleName {set;}
```

Property Value

The string to be used as the module name.

Remarks

The default value is null.

Using the `ModuleName` property allows the application to set the module name in the application context for a given `OracleConnection` object.

In unmanaged ODP.NET, the `ModuleName` property is reset to null when the `Close` or `Dispose` method is called on the `OracleConnection` object. In managed ODP.NET, it is

reset to null (assuming no new value is assigned) upon the next database round trip following a `Close` or `Dispose` method call on the `OracleConnection` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#)
- [Oracle Database Security Guide](#)

PDBName

This property is used to set and get the name of the pluggable database to which the session is connected to.

Declaration

```
// C#  
public string PDBName{ get; set; }
```

Property Value

`PDBName` returns a string specifying the pluggable database name for the connection.

Exceptions

- `InvalidOperationException()` - if the connection is already open.
- `InvalidOperationException()` - if the `CPVersion` is set to 1.0 and the `PDBName` property is set. Applicable only to ODP.NET, Unmanaged Driver.
- `InvalidOperationException()` - If `PDBName` value is retrieved when `CPVersion` is set to 1.0. Applicable only to ODP.NET, Unmanaged Driver.

Remarks

Pluggable databases are available in Oracle Database 12c and higher. The `ServiceName` and `PDBName` properties can be used to connect to the specified Service that is running on a particular PDB.

Property must be set before opening the connection so that a connection with requested pluggable database name is returned.

If the `PDBName` property is set before connection is opened, then the connection's pluggable database name will be the same as `PDBName` when `OracleConnection.Open()` is successfully executed.

If only the `PDBName` property is set, then the default service of the pluggable database is used as the `ServiceName` for this connection.

In unmanaged ODP.NET, if the `PDBName` property is set *and* if the .NET configuration setting, `CPVersion`, is *not* set, then the `CPVersion` attribute will be automatically set to 2.0.

`PDBName` property's value is case insensitive.

The `PDBName` property can be used to retrieve the session's pluggable database name after the connection has been opened. If it is used to get the pluggable database name before the connection is opened, then it just returns the pluggable database name provided by the application, if any.

Only supported for .NET Framework 4 and higher.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ServerVersion

This property specifies the version number of the Oracle database to which the `OracleConnection` has established a connection.

Declaration

```
// C#  
public override string ServerVersion {get;}
```

Property Value

The version of the Oracle database.

Exceptions

`InvalidOperationException` - The connection is closed.

Remarks

The default is an empty string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ServiceName

This property is used to set and get the database service name to which the session will be connected to when connecting to a pluggable database.

Declaration

```
// C#  
public string ServiceName{ get; set;}
```

Property Value

`ServiceName` returns a string specifying the service name of the connection.

Exceptions

`InvalidOperationException()` - the connection is already open.

`InvalidOperationException()` - if the `CPVersion` is set to 1.0 and the `ServiceName` property is set. Applicable only to ODP.NET, Unmanaged Driver.

Remarks

Pluggable databases are available in Oracle Database 12c and higher. The `ServiceName` and `PDBName` properties can be used to connect to the specified Service that is running on a particular PDB.

`ServiceName` must be set before opening the connection so that the correct service is used for the connection.

`PDBName` property must be set when the `ServiceName` property is set. Otherwise, an exception is thrown when the connection is opened.

If the `ServiceName` property is specified before connection is opened, then the connection's service will be the same as the specified `ServiceName` when the connection is opened.

If the service name is not changed before the connection is next opened, then the connection will continue using the `ServiceName` value that had been previously set.

In unmanaged ODP.NET, if the `ServiceName` property is set *and* if the `CPVersion` attribute is *not* set, then the `CPVersion` attribute will be automatically set to 2.0.

`ServiceName` property's value is case insensitive.

The `ServiceName` property can also be used to retrieve the session service name after opening the connection. If retrieved before opening the connection, then `ServiceName` returns the service name provided by the application, if any.

Only supported for .NET Framework 4 and higher.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

State

This property specifies the current state of the connection.

Declaration

```
// C#  
public override ConnectionState State {get;}
```

Property Value

The `ConnectionState` of the connection.

Implements

`IDbConnection`

Remarks

ODP.NET supports `ConnectionState.Closed` and `ConnectionState.Open` for this property. The default value is `ConnectionState.Closed`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

StatementCacheSize

This property specifies the current size of the statement cache associated with this connection.

Declaration

```
// C#  
public int StatementCacheSize{get;}
```

Property Value

An integer value indicating the size of the statement cache.

Remarks

If self tuning is not enabled, then the default value of this property depends upon the statement cache size specified in the connection string, application configuration file, or the registry. If none of these values are specified, then a default value of 0 is used.

If self tuning is enabled, then the property value is adjusted automatically. Any values specified in the connection string, application configuration file, or the registry are ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

SwitchedConnection

This property applies to pluggable database connections. Upon an `OracleConnection.Open()`, if the connection returned from the pool had to change its service name (`ServiceName`) or pluggable database (`PDBName`) in order to connect to the desired pluggable database, then the connection is considered switched. Thus, `SwitchedConnection` will then return `TRUE`. In all other cases, it will return `FALSE`.

Declaration

```
// C#  
public bool SwitchedConnection { get; }
```

Remarks

Applications should use this property carefully when using `DRCPConnectionString` values that are common across PDBs/Services. If the same `DRCPConnectionString` values are used across PDBs/Services, but their semantics are different, then this property value can help determine if the requested connection is returned or not.

For example, in a scenario where the same `DRCPConnectionString` that is used across PDBs/Services has a different semantic, the application should first check to see if the session has been switched or not. If it has switched between PDBs/Services, then the application should consider that the connection with a matching `DRCPConnectionString` was not dispensed.

Only supported for .NET Framework 4 and higher.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection Public Methods

OracleConnection public methods are listed in [Table 6-48](#).

Table 6-48 OracleConnection Public Methods

Public Method	Description
BeginTransaction	Begins a local transaction (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i>
ChangeDatabase	<i>Not Supported</i>
Clone	Creates a copy of an OracleConnection object <i>Not supported in a .NET stored procedure</i>
Close	Closes the database connection
CreateCommand	Creates and returns an OracleCommand object associated with the OracleConnection object
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Inherited from System.ComponentModel.Component
EnlistDistributedTransaction	Enables applications to explicitly enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure and ODP.NET Core</i>
EnlistTransaction	Enables applications to enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i>
Equals	Inherited from System.Object (Overloaded)
FlushCache	Flushes all updates and deletes made through REF objects retrieved using this connection <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetSchema	Returns schema information for the data source of the OracleConnection

Table 6-48 (Cont.) OracleConnection Public Methods

Public Method	Description
GetSessionInfo	Returns or refreshes the property values of the <code>OracleGlobalization</code> object that represents the globalization settings of the session (Overloaded)
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
Open	Opens a database connection with the property settings specified by the <code>ConnectionString</code>
OpenWithNewPassword	Opens a new connection with the new password (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i>
PurgeStatementCache	Flushes the Statement Cache by closing all open cursors on the database, when statement caching is enabled
SetSessionInfo	Alters the session's globalization settings with the property values provided by the <code>OracleGlobalization</code> object
SetShardingKey(OracleShardingKey, OracleShardingKey)	Enables applications to set the sharding key and super sharding key before requesting a connection <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
<code>ToString</code>	Inherited from <code>System.Object</code>

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

BeginTransaction

`BeginTransaction` methods begin local transactions.

Overload List

- [BeginTransaction\(\)](#)
This method begins a local transaction.
- [BeginTransaction\(IsolationLevel\)](#)
This method begins a local transaction with the specified isolation level.

BeginTransaction()

This method begins a local transaction.

Declaration

```
// C#  
public OracleTransaction BeginTransaction();
```

Return Value

An `OracleTransaction` object representing the new transaction.

Implements

`IDbConnection`

Exceptions

`InvalidOperationException` - A transaction has already been started.

Remarks

The transaction is created with its isolation level set to its default value of `IsolationLevel.ReadCommitted`. All further operations related to the transaction must be performed on the returned `OracleTransaction` object.

Remarks (.NET Stored Procedure)

Using this method in a .NET stored procedure for context connection causes a `NotSupportedException`.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

BeginTransaction(IsolationLevel)

This method begins a local transaction with the specified isolation level.

Declaration

```
// C#  
public OracleTransaction BeginTransaction(IsolationLevel isolationLevel);
```

Parameters

- *isolationLevel*
The isolation level for the new transaction.

Return Value

An `OracleTransaction` object representing the new transaction.

Implements

`IDbConnection`

Exceptions

`InvalidOperationException` - A transaction has already been started.

`ArgumentException` - The `isolationLevel` specified is invalid.

Remarks

The following isolation levels are supported: `IsolationLevel.ReadCommitted` and `IsolationLevel.Serializable`.

Although the `BeginTransaction` method supports the `IsolationLevel.Serializable` isolation level, serializable transactions are not supported when using `System.Transactions` and `TransactionScope`.

Requesting other isolation levels causes an exception.

Remarks (.NET Stored Procedure)

Using this method in a .NET stored procedure for context connection causes a `NotSupportedException`.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class BeginTransactionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(IsolationLevel.ReadCommitted);

        // Update EMP table
        cmd.CommandText = "update emp set sal = sal + 100";
        cmd.ExecuteNonQuery();

        // Rollback transaction
        txn.Rollback();
        Console.WriteLine("Transaction rolledback");
    }
}
```

```
// Clean up
txn.Dispose();
cmd.Dispose();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ChangeDatabase

This method is not supported.

Declaration

```
// C#
public override void ChangeDatabase(string databaseName);
```

Parameters

- *databaseName*
The name of the database that replaces the current database name.

Implements

IDbConnection.ChangeDatabase

Exceptions

NotSupportedException - Method not supported.

Remarks

This method is not supported and throws a `NotSupportedException` if invoked.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

Clone

This method creates a copy of an `OracleConnection` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An `OracleConnection` object.

Implements

`ICloneable`

Remarks

The cloned object has the same property values as that of the object being cloned.

Remarks (.NET Stored Procedure)

This method is not supported for an implicit database connection.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class CloneSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Need a proper casting for the return value when cloned  
        OracleConnection clonedCon = (OracleConnection)con.Clone();  
  
        // Cloned connection is always closed, regardless of its source,  
        // But the connection string should be identical  
        clonedCon.Open();  
        if (clonedCon.ConnectionString.Equals(con.ConnectionString))  
            Console.WriteLine("The connection strings are the same.");  
        else  
            Console.WriteLine("The connection strings are different.");  
  
        // Close and Dispose OracleConnection object  
        clonedCon.Dispose();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

Close

This method closes the connection to the database.

Declaration

```
// C#  
public override void Close();
```

Implements

IDbConnection

Remarks

Performs the following:

- Rolls back any pending local transactions that are not yet committed. Distributed transactions will rely on the distributed transaction coordinator on whether roll back is necessary.
- Places the connection to the connection pool if connection pooling is enabled. Even if connection pooling is enabled, the connection can be closed if it exceeds the connection lifetime specified in the connection string. If connection pooling is disabled, the connection is closed.
- Closes the connection to the database.

The connection can be reopened using `Open()`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

CreateCommand

This method creates and returns an `OracleCommand` object associated with the `OracleConnection` object.

Declaration

```
// C#  
public OracleCommand CreateCommand();
```

Return Value

The `OracleCommand` object.

Implements

`IDbConnection`

Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class CreateCommandSample  
{  
    static void Main()  
    {  
        // Connect  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Execute a SQL SELECT  
        OracleCommand cmd = con.CreateCommand();  
        cmd.CommandText = "select * from emp";  
        OracleDataReader reader = cmd.ExecuteReader();  
  
        // Print all employee numbers  
        while (reader.Read())  
            Console.WriteLine(reader.GetInt32(0));  
  
        // Clean up  
        reader.Dispose();  
        cmd.Dispose();  
        con.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

EnlistDistributedTransaction

This method enables applications to explicitly enlist in a specific distributed transaction after a connection has been opened.

Declaration

```
// C#  
public void EnlistDistributedTransaction(ITransaction transaction);
```

Parameters

- *transaction*
An `ITransaction` interface.

Exceptions

`InvalidOperationException` - The connection is part of a local transaction or the connection is closed.

Remarks

`EnlistDistributedTransaction` enables objects to enlist in a specific transaction that is passed to the method. The `ITransaction` interface can be obtained by applying an (`ITransaction`) cast to the `ContextUtil.Transaction` property within the component that started the distributed transaction.

The connection must be open before calling this method or an `InvalidOperationException` is thrown.

If a connection is part of a local transaction that was started implicitly or explicitly while attempting to enlist in a distributed transaction, the local transaction is rolled back and an exception is thrown.

By default, distributed transactions roll back, unless the method-level `AutoComplete` declaration is set.

Invoking the commit on the `ITransaction` raises an exception.

Invoking the rollback on the `ITransaction` method and calling `ContextUtil.SetComplete` on the same distributed transaction raises an exception.

Remarks (.NET Stored Procedure)

Using this method causes a Not Supported exception.

Example

Application:

```
// C#  
  
/* This is the class that will utilize the Enterprise Services  
   component. This module needs to be built as an executable.  
  
   The Enterprise Services Component DLL must be built first  
   before building this module.  
   In addition, the DLL needs to be referenced appropriately
```

```
        when building this application.
    */

using System;
using System.EnterpriseServices;
using DistribTxnSample;

class DistribTxnSample_App
{
    static void Main()
    {
        DistribTxnSample_Comp comp = new DistribTxnSample_Comp();
        comp.DoWork();
    }
}
```

Component:

```
// C#

/* This module needs to be
   1) built as a component DLL/Library
   2) built with a strong name

   This library must be built first before the application is built.
*/

using System;
using System.Data;
using Oracle.DataAccess.Client;
using System.EnterpriseServices;

namespace DistribTxnSample
{
    [Transaction(TransactionOption.RequiresNew)]
    public class DistribTxnSample_Comp : ServicedComponent
    {
        public void DoWork()
        {
            string constr =
                "User Id=scott;Password=tiger;Data Source=oracle;enlist=false";
            OracleConnection con = new OracleConnection(constr);
            con.Open();

            // Enlist in a distributed transaction
            con.EnlistDistributedTransaction((ITransaction)ContextUtil.Transaction);

            // Update EMP table
            OracleCommand cmd = con.CreateCommand();
            cmd.CommandText = "UPDATE emp set sal = sal + .01";
            cmd.ExecuteNonQuery();

            // Commit
            ContextUtil.SetComplete();

            // Dispose OracleConnection object
            con.Dispose();
        }
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["EnlistTransaction"](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework feature

EnlistTransaction

This method enlists the connection to the specified transaction.

Declaration

```
// C#  
public override void EnlistTransaction(Transaction transaction)
```

Parameters

- *transaction*
A `System.Transactions.Transaction` object.

Exceptions

`InvalidOperationException` - The connection is part of a local transaction or the connection is closed.

Remarks

Invocation of this method immediately enlists the connection to a transaction that is specified by the provided transaction parameter.

If `OracleConnection` is still associated with a distributed transaction that has not completed from a previous `EnlistTransaction` method invocation, calling this method will cause an exception to be thrown.

In general, for transaction enlistments to succeed, the "enlist" connection string attribute must be set to "true" before invoking the `Open` method. Setting the "enlist" connection string attribute to "true" will implicitly enlist the connection when the `Open` method is called, if the connection is within a transaction context. The "enlist" attribute should be set to "false" or "dynamic" only if the connection will never enlist in a transaction.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["System.Transactions and Promotable Transactions"](#)
- ["EnlistDistributedTransaction"](#)

FlushCache

This method flushes all updates and deletes made through `REF` objects retrieved using this connection.

Declaration

```
// c#  
public void FlushCache();
```

Exceptions

`InvalidOperationException` - The specified connection is not open.

Remarks

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema

`GetSchema` methods return schema information for the data source of the `OracleConnection`.

Overload List

- [GetSchema\(\)](#)

This method returns schema information for the data source of the `OracleConnection`.

- [GetSchema \(string collectionName\)](#)

This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name.

- [GetSchema \(string collectionName, string\[\] restrictions\)](#)

This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name and the specified string array for the restriction values.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema()

This method returns schema information for the data source of the `OracleConnection`.

Declaration

```
// C#  
public override DataTable GetSchema();
```

Return Value

A `DataTable` object.

Exceptions

`InvalidOperationException` – The connection is closed.

Remarks

This method returns a `DataTable` object that contains a row for each metadata collection available from the database.

The method is equivalent to specifying the `String` value `"MetaDataCollections"` when using the `GetSchema(String)` method.

Example

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;
```

```
class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();

                //Get all the schema collections and write to an XML file.
                //The XML file name is Oracle.DataAccess.Client_Schema.xml
                DataTable dtSchema = conn.GetSchema();
                dtSchema.WriteXml(ProviderName + "_Schema.xml");
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
                Console.WriteLine(ex.StackTrace);
            }
        }
    }
}
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema (string collectionName)

This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name.

Declaration

```
// C#
public override DataTable GetSchema (string collectionName);
```

Parameters

collectionName

Name of the collection for which metadata is required.

Return Value

A `DataTable` object.

Exceptions

`ArgumentException` – The requested collection is not defined.

`InvalidOperationException` – The connection is closed.

`InvalidOperationException` – The requested collection is not supported by current version of Oracle database.

`InvalidOperationException` – No population string is specified for requested collection.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle.";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();

                //Get MetaDataCollections and write to an XML file.
                //This is equivalent to GetSchema()
                DataTable dtMetadata =
                    conn.GetSchema(DbMetaDataCollectionNames.MetaDataCollections);
                dtMetadata.WriteXml(ProviderName + "_MetaDataCollections.xml");

                //Get Restrictions and write to an XML file.
                DataTable dtRestrictions =
                    conn.GetSchema(DbMetaDataCollectionNames.Restrictions);
                dtRestrictions.WriteXml(ProviderName + "_Restrictions.xml");

                //Get DataSourceInformation and write to an XML file.
                DataTable dtDataSrcInfo =
                    conn.GetSchema(DbMetaDataCollectionNames.DataSourceInformation);
                dtDataSrcInfo.WriteXml(ProviderName + "_DataSourceInformation.xml");

                //data types and write to an XML file.
                DataTable dtDataTypes =
                    conn.GetSchema(DbMetaDataCollectionNames.DataTypes);
```



```
dtDataTypes.WriteXml(ProviderName + "_DataTypes.xml");

//Get ReservedWords and write to an XML file.
DataTable dtReservedWords =
    conn.GetSchema(DbMetaDataCollectionNames.ReservedWords);
dtReservedWords.WriteXml(ProviderName + "_ReservedWords.xml");

//Get all the tables and write to an XML file.
DataTable dtTables = conn.GetSchema("Tables");
dtTables.WriteXml(ProviderName + "_Tables.xml");

//Get all the views and write to an XML file.
DataTable dtViews = conn.GetSchema("Views");
dtViews.WriteXml(ProviderName + "_Views.xml");

//Get all the columns and write to an XML file.
DataTable dtColumns = conn.GetSchema("Columns");
dtColumns.WriteXml(ProviderName + "_Columns.xml");
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema (string collectionName, string[] restrictions)

This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name and the specified string array for the restriction values.

Declaration

```
// C#
public override DataTable GetSchema (string collectionName,
    string[] restrictions);
```

Parameters

- *collectionName*
The name of the collection of metadata being retrieved.
- *restrictions*

An array of restrictions that apply to the metadata being retrieved.

Return Value

A `DataTable` object.

Exception

- `ArgumentException` – The requested collection is not defined.
- `InvalidOperationException` – One of the following conditions exist:
 - The connection is closed.
 - The requested collection is not supported by the current version of Oracle database.
 - More restrictions were provided than the requested collection supports.
 - No population string is specified for requested collection.

Remarks

This method takes the name of a metadata collection and an array of `String` values that specify the restrictions for filtering the rows in the returned `DataTable`. This returns a `DataTable` that contains only rows from the specified metadata collection that match the specified restrictions.

For example, if the `Columns` collection has three restrictions (`owner`, `tablename`, and `columnname`), to retrieve all the columns for the `EMP` table regardless of schema, the `GetSchema` method must pass in at least these values: `null`, `EMP`.

If no restriction value is passed in, default values are used for that restriction, which is the same as passing in `null`. This differs from passing in an empty string for the parameter value. In this case, the empty string (" ") is considered the value for the specified parameter.

`collectionName` is not case-sensitive, but restrictions (string values) are.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle.";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
            }
        }
    }
}
```

```
conn.Open();

//Get Restrictions
DataTable dtRestrictions =
    conn.GetSchema(DbMetaDataCollectionNames.Restrictions);

DataView dv = dtRestrictions.DefaultView;

dv.RowFilter = "CollectionName = 'Columns'";
dv.Sort = "RestrictionNumber";

for (int i = 0; i < dv.Count; i++)
    Console.WriteLine("{0} (default) {1}" ,
        dtRestrictions.Rows[i]["RestrictionName"],
        dtRestrictions.Rows[i]["RestrictionDefault"]);

//Set restriction string array
string[] restrictions = new string[3];

//Get all columns from all tables owned by "SCOTT"
restrictions[0] = "SCOTT";
DataTable dtAllScottCols = conn.GetSchema("Columns", restrictions);

// clear collection
for (int i = 0; i < 3; i++)
    restrictions[i] = null;

//Get all columns from all tables named "EMP" owned by any
//owner/schema
restrictions[1] = "EMP";
DataTable dtAllEmpCols = conn.GetSchema("Columns", restrictions);

// clear collection
for (int i = 0; i < 3; i++)
    restrictions[i] = null;

//Get columns named "EMPNO" from tables named "EMP",
//owned by any owner/schema
restrictions[1] = "EMP";
restrictions[2] = "EMPNO";
DataTable dtAllScottEmpCols = conn.GetSchema("Columns", restrictions);

// clear collection
for (int i = 0; i < 3; i++)
    restrictions[i] = null;

//Get columns named "EMPNO" from all
//tables, owned by any owner/schema
restrictions[2] = "EMPNO";
DataTable dtAllEmpNoCols = conn.GetSchema("Columns", restrictions);
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.Source);
}
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSessionInfo

`GetSessionInfo` returns or refreshes an `OracleGlobalization` object that represents the globalization settings of the session.

Overload List:

- [GetSessionInfo\(\)](#)
This method returns a new instance of the `OracleGlobalization` object that represents the globalization settings of the session.
- [GetSessionInfo\(OracleGlobalization\)](#)
This method refreshes the provided `OracleGlobalization` object with the globalization settings of the session.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSessionInfo()

This method returns a new instance of the `OracleGlobalization` object that represents the globalization settings of the session.

Declaration

```
// C#  
public OracleGlobalization GetSessionInfo();
```

Return Value

The newly created `OracleGlobalization` object.

Example

```
// C#  
using System;
```

```
using Oracle.DataAccess.Client;

class GetSessionInfoSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get session info from connection object
        OracleGlobalization info = con.GetSessionInfo();

        // Update session info
        info.DateFormat = "YYYY-MM-DD";
        con.SetSessionInfo(info);

        // Execute SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select TO_CHAR(hiredate) from emp";
        Console.WriteLine("Hire Date ({0}): {1}",
            info.DateFormat, cmd.ExecuteScalar());

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSessionInfo(OracleGlobalization)

This method refreshes the provided `OracleGlobalization` object with the globalization settings of the session.

Declaration

```
// C#
public void GetSessionInfo(OracleGlobalization oraGlob);
```

Parameters

- `oraGlob`
The `OracleGlobalization` object to be updated.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

Open

This method opens a connection to an Oracle database.

Declaration

```
// C#  
public override void Open();
```

Implements

IDbConnection

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The connection is already opened or the connection string is null or empty.

Remarks

The connection is obtained from the pool if connection pooling is enabled. Otherwise, a new connection is established.

It is possible that the pool does not contain any unused connections when the `Open()` method is invoked. In this case, a new connection is established.

If no connections are available within the specified connection timeout value, when the `Max Pool Size` is reached, an `OracleException` is thrown.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OpenWithNewPassword

`OpenWithNewPassword` opens a new connection with the new password.

Overload List:

- [OpenWithNewPassword\(String\)](#)

`OpenWithNewPassword` opens a new connection with the new password.

- [OpenWithNewPassword\(SecureString\)](#)

`OpenWithNewPassword` opens a new connection with the new password. This method will also update the password in the `OracleCredential` instance that was passed using the `OracleConnection` constructor or through the `OracleConnection.Credential` property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OpenWithNewPassword(String)

This method opens a new connection with the new password.

Declaration

```
// C#  
public void OpenWithNewPassword(string newPassword);
```

Parameters

- *newPassword*
A string that contains the new password.

Remarks

This method uses the `ConnectionString` property settings to establish a new connection. The old password must be provided in the connection string as the `Password` attribute value.

This method can only be called on an `OracleConnection` in the *closed* state.

Remarks (.NET Stored Procedure)

This method is not supported in a .NET stored procedure for context connection.

 **Note:**

If connection pooling is enabled, then invoking the `OpenWithNewPassword` method also clears the connection pool. This closes all idle connections created with the old password.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Password Expiration"](#)

OpenWithNewPassword(SecureString)

This method opens a new connection with the new password.

Declaration

```
// C#  
public void OpenWithNewPassword(SecureString newSecurePassword)
```

Parameters

- *newSecurePassword*
The `SecureString` object that contains the new password for a user id.

Remarks

Use this method to change the password for a user id. This method can only be used if an `OracleCredential` instance was passed using the `OracleConnection` constructor or through the `OracleConnection.Credential` property.

This method will also update the password in the `OracleCredential` instance that was passed using the `OracleConnection` constructor or through the `OracleConnection.Credential` property.

`OracleCredential` does not support double quotes around a `SecureString` password. Double quotes can be used within a password, however.

Exceptions

`ArgumentNullException` is raised if *newSecurePassword* is `NULL` or is not read only.

`InvalidOperationException` is raised if `OracleCredential` is not already set on the `OracleConnection` either through the `OracleConnection` constructor or through the `Credential` property of the `OracleConnection`.

InvalidOperationException is raised if the OracleConnection is already in the open state.

InvalidOperationException is raised if the connection string is NULL or of length 0.

InvalidOperationException is raised if the user id, proxy user id, password, proxy password, DBA privilege is set using the connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Password Expiration"](#)

PurgeStatementCache

This method flushes the statement cache by closing all open cursors on the database, when statement caching is enabled.

Declaration

```
// C#  
public void PurgeStatementCache();
```

Remarks

Flushing the statement cache repetitively results in decreased performance and may negate the performance benefit gained by enabling the statement cache.

Statement caching remains enabled after the call to PurgeStatementCache.

Invocation of this method purges the cached cursors that are associated with the OracleConnection. It does not purge all the cached cursors in the database.

Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class PurgeStatementCacheSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle;" +  
            "Statement Cache Size=20";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = new OracleCommand("select * from emp", con);
```

```
cmd.CommandType = CommandType.Text;
OracleDataReader reader = cmd.ExecuteReader();

// Purge Statement Cache
con.PurgeStatementCache();

// Close and Dispose OracleConnection object
Console.WriteLine("Statement Cache Flushed");
con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Statement Caching"](#)
- [ConnectionString](#)

SetSessionInfo

This method alters the session's globalization settings with all the property values specified in the provided `OracleGlobalization` object.

Declaration

```
// C#
public void SetSessionInfo(OracleGlobalization oraGlob);
```

Parameters

- `oraGlob`

An `OracleGlobalization` object.

Remarks

Calling this method is equivalent to calling an `ALTER SESSION SQL` on the session.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class SetSessionInfoSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
```

```
OracleConnection con = new OracleConnection(constr);
con.Open();

// Get session info from connection object
OracleGlobalization info = con.GetSessionInfo();

// Execute SQL SELECT
OracleCommand cmd = con.CreateCommand();
cmd.CommandText = "select TO_CHAR(hiredate) from emp";
Console.WriteLine("Hire Date ({0}): {1}",
    info.DateFormat, cmd.ExecuteScalar());

// Update session info
info.DateFormat = "MM-DD-RR";
con.SetSessionInfo(info);

// Execute SQL SELECT again
Console.WriteLine("Hire Date ({0}): {1}",
    info.DateFormat, cmd.ExecuteScalar());

// Clean up
cmd.Dispose();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

SetShardingKey(OracleShardingKey, OracleShardingKey)

This instance method enables applications to set the sharding key and the super sharding key before requesting a connection.

Declaration

```
// C#
public void SetShardingKey(OracleShardingKey shardKey, OracleShardingKey
superShardingKey);
```

Exceptions

InvalidArgumentException – An invalid Oracle sharding key is supplied.

InvalidOperationException – The method is invoked when the connection is in an **Open state**.

Remarks

This method sets the sharding key and the super sharding key that is to be used for returning the proper connection upon the `Open` method invocation.

This method can only be invoked when the connection is in a Closed state.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class Sharding
{
    static void Main()
    {
        OracleConnection con = new OracleConnection("user id=hr;password=hr;Data
Source=orcl;");
        //Setting a shard key
        OracleShardingKey shardingKey = new OracleShardingKey(OracleDbType.Int32, 123);
        //Setting a second shard key value for a composite key
        shardingKey.SetShardingKey(OracleDbType.Varchar2, "gold");
        //Creating and setting the super shard key
        OracleShardingKey superShardingKey = new OracleShardingKey();
        superShardingKey.SetShardingKey(OracleDbType.Int32, 1000);

        //Setting super sharding key and sharding key on the connection
        con.SetShardingKey(shardingKey, superShardingKey);
        con.Open();

        //perform SQL query
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [OracleShardingKey Class](#)

OracleConnection Events

OracleConnection events are listed in [Table 6-49](#).

Table 6-49 OracleConnection Events

Event Name	Description
ConnectionOpen	This event is triggered upon the OracleConnection.Open() method
Disposed	Inherited from System.ComponentModel.Component

Table 6-49 (Cont.) OracleConnection Events

Event Name	Description
Failover	An event that is triggered when an Oracle failover occurs <i>Not supported in a .NET stored procedure</i> <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
HAEvent	An event that is triggered when an HA event occurs
InfoMessage	An event that is triggered for any message or warning sent by the database
StateChange	An event that is triggered when the connection state changes

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ConnectionOpen

This event is triggered upon the `OracleConnection.Open()` method.

Declaration

```
// C#
public event OracleConnectionOpenEventHandler ConnectionOpen;
```

Event Data

The event handler receives a `OracleConnectionOpenEventArgs` object which exposes the following property containing information about the `ConnectionOpen` event.

- `Connection`
OracleConnection object on which `Open()` is called.

Exceptions

- `InvalidOperationException()` - if `CPVersion=1.0` and the `ConnectionOpen` event is used. Applies to unmanaged ODP.NET only.
- `InvalidOperationException()` - if the `ConnectionOpen` event is set after opening a connection.

Remarks

This feature requires `CPVersion=2.0` to be used.

In order to configure the connection before it is dispensed, the application should register the callback to the `ConnectionOpen` event before `Open()` is called.

Only supported for .NET Framework 4 and higher.

Example

```
// C#
// NOTE: The sample below requires CPVersion=2.0 to be configured in
the .NET configuration
using System;
using Oracle.ManagedDataAccess.Client;

class ConOpenEventSample
{
    public static void ConOpenCallback(OracleConnectionOpenEventArgs
eventArgs)
    {
        OracleCommand cmd = new OracleCommand("ALTER SESSION SET
NLS_LANGUAGE='GERMAN'", eventArgs.Connection);
        cmd.ExecuteNonQuery();
        cmd.Dispose();
    }

    static void Main(string[] args)
    {
        // Establish a connection
        string constr = "user id=hr;password=hr;data source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.ConnectionOpen += ConOpenCallback;
        con.Open();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [OracleConnectionOpenEventArgs Properties](#)
- [OracleConnectionOpenEventHandler Delegate](#)

Failover

This event is triggered when an Oracle failover occurs.

Declaration

```
// C#
public event OracleFailoverEventHandler Failover;
```

Event Data

The event handler receives an `OracleFailoverEventArgs` object which exposes the following properties containing information about the event.

- `FailoverType`
Indicates the type of the failover.
- `FailoverEvent`
Indicates the state of the failover.

Remarks

The `Failover` event is raised when a connection to an Oracle instance is unexpectedly severed. The client should create an `OracleFailoverEventHandler` delegate to listen to this event.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleFailoverEventArgs Properties"](#)
- ["OracleFailoverEventHandler Delegate"](#)

HAEvent

This event is triggered when an HA event occurs.

Declaration

```
// C#  
public static event OracleHAEventHandler HAEvent;
```

Event Data

The event handler receives an `OracleHAEventArgs` object which exposes the following properties containing information about the event.

- `Source`
Indicates the source of the event.
- `Status`
Indicates the status of the event.
- `DatabaseName`
Indicates the database name affected by this event.
- `DatabaseDomainName`

Indicates the database domain name affected by this event.

- `HostName`

Indicates the host name affected by this event.

- `InstanceName`

Indicates the instance name affected by this event.

- `ServiceName`

Indicates the service name affected by this event.

- `Time`

Indicates the time of the event.

Remarks

The `HAEvent` is static, which means that any HA Events that happen within the application domain can trigger this event. Note that in order to receive HA event notifications, `OracleConnection` objects that establish connections within the application domain must have `"ha events=true"` in the application. Otherwise, the application never receives any HA Events.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleHAEventArgs Properties"](#)
- ["OracleHAEventHandler Delegate"](#)

InfoMessage

This event is triggered for any message or warning sent by the database.

Declaration

```
// C#  
public event OracleInfoMessageEventHandler InfoMessage;
```

Event Data

The event handler receives an `OracleInfoMessageEventArgs` object which exposes the following properties containing information about the event.

- `Errors`
The collection of errors generated by the data source.
- `Message`
The error text generated by the data source.

- Source

The name of the object that generated the error.

Remarks

In order to respond to warnings and messages from the database, the client should create an `OracleInfoMessageEventHandler` delegate to listen to this event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleInfoMessageEventArgs Properties"](#)
- ["OracleInfoMessageEventHandler Delegate"](#)

StateChange

This event is triggered when the connection state changes.

Declaration

```
// C#  
public override event StateChangeEventHandler StateChange;
```

Event Data

The event handler receives a `StateChangeEventArgs` object which exposes the following properties containing information about the event.

- `CurrentState`
The new state of the connection.
- `OriginalState`
The original state of the connection.

Remarks

The `StateChange` event is raised after a connection changes state, whenever an explicit call is made to `Open`, `Close` or `Dispose`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [Microsoft ADO.NET documentation for a description of StateChangeEventHandler](#)

OracleConnectionOpenEventArgs Class

The `OracleConnectionOpenEventArgs` class provides connection information for the `OracleConnection.Open()` method. When a connection is opened, the callback registered using `ConnectionOpen` is triggered along with the `OracleConnectionOpenEventArgs` object.

Class Inheritance

```
System.Object
```

```
System.EventArgs
```


```
Oracle.DataAccess.Client.OracleConnectionOpenEventArgs
```

Declaration

```
// C#
public sealed class OracleConnectionOpenEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionOpenEventArgs Members](#)
- [OracleConnectionOpenEventArgs Properties](#)

OracleConnectionOpenEventArgs Members

OracleConnectionOpenEventArgs members are listed in the following tables.

OracleConnectionOpenEventArgsProperties

OracleConnectionOpenEventArgs properties are listed in [Table 6-50](#).

Table 6-50 OracleConnectionOpenEventArgs Properties

Property	Description
Connection	Specifies the <code>OracleConnection</code> on which connection open event has occurred

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionOpenEventArgs Class](#)

OracleConnectionOpenEventArgs Properties

OracleConnectionOpenEventArgs properties are listed in [Table 6-51](#).

Table 6-51 OracleConnectionOpenEventArgs Properties

Property	Description
Connection	Specifies the <code>OracleConnection</code> on which connection open event has occurred

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionOpenEventArgs Class](#)
- [OracleConnectionOpenEventArgs Members](#)

Connection

This property specifies the `OracleConnection` on which connection open event has occurred.

Declaration

```
// C#  
public Connection{ get;}
```

Property Value

Returns a `OracleConnection` object on which `Open()` is called.

Remarks

Only supported for .NET Framework 4 and higher.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionOpenEventArgs Class](#)
- [OracleConnectionOpenEventArgs Members](#)

OracleConnectionOpenEventHandler Delegate

The `OracleConnectionOpenEventHandler` delegate represents the signature of the method that handles `OracleConnection.ConnectionOpen` event.

Declaration

```
// C#  
public delegate void OracleConnectionOpenEventHandler (OracleConnectionOpenEventArgs  
eventArgs);
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Parameters

- *eventArgs*
The `OracleConnectionOpenEventArgs` object that contains the connection data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [ConnectionOpen](#)

OracleConnectionStringBuilder Class

An `OracleConnectionStringBuilder` object allows applications to create or modify connection strings.

Class Inheritance

`System.Object`

`System.Data.Common.DbConnectionStringBuilder`

`Oracle.DataAccess.Client.OracleConnectionStringBuilder`

Declaration

```
// C#
public sealed class OracleConnectionStringBuilder : DbConnectionStringBuilder
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Namespace	Oracle.DataAccess .Client	Oracle.ManagedDat aAccess.Client	Oracle.ManagedDat aAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The following rules must be followed for setting values with reserved characters:

- 1. Values containing characters enclosed within single quotes**

If the value contains characters that are enclosed within single quotation marks, then the entire value must be enclosed within double quotation marks.

For example, `password = "'scoTT' "` where the value is `'scoTT'`.
- 2. Values containing characters enclosed within double quotes**

Values should be enclosed in double quotation marks to preserve the case and to avoid the upper casing of values.

If the value contains characters enclosed in double quotation marks, then it must be enclosed in single quotation marks.

For example, `password = "'scoTT' "` where the value is `"scoTT"`.
- 3. Values containing characters enclosed in both single and double quotes**

If the value contains characters enclosed in both single and double quotation marks, the quotation mark used to enclose the value must be doubled each time it occurs within the value.

For example, `password = '"sco' 'TT' "` where the value is `"sco'TT"`.
- 4. Values containing spaces**

All leading and trailing spaces are ignored, but the spaces between the value are recognized. If the value needs to have leading or trailing spaces then it must be enclosed in double quotation marks.

For example, `User ID = Sco TT` where the value is `<Sco TT>`.

For example, `User ID = "Sco TT "` where the value is `<Sco TT>`.
- 5. Keywords occurring multiple times in a connection string**

If a specific keyword occurs multiple times in a connection string, the last occurrence listed is used in the value set.

For example, with `"User ID = scott; password = tiger; User ID = david"` connection string, `User ID` value is `david`.

To limit malicious access, the APIs of `OracleConnectionStringBuilder`, `Add` and `Item`, insert double quotes around connection string attributes that use special

characters. Using special characters in strings can be a format string attack method. Adding double quotes for attributes will not affect database access in most cases. However, there are attributes that require exact string matching, such as passwords. OracleConnectionStringBuilder's addition of double quotes to a password with special characters may result in a generation of a connection string that fails to authenticate against the database.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;
using System.Collections;

class ConnectionStringBuilderSample
{
    static void Main(string[] args)
    {
        bool bRet = false;

        // Create an instance of OracleConnectionStringBuilder
        OracleConnectionStringBuilder connStrBuilder =
            new OracleConnectionStringBuilder();

        // Add new key/value pairs to the connection string
        connStrBuilder.Add("User Id", "scott");
        connStrBuilder.Add("Password", "tiger");
        connStrBuilder.Add("Data Source", "oracle");
        connStrBuilder.Add("pooling", false);

        // Modify the existing value
        connStrBuilder["Data source"] = "inst1";

        // Remove an entry from the connection string
        bRet = connStrBuilder.Remove("pooling");

        //ContainsKey indicates whether or not the specific key exist
        //returns true even if the user has not specified it explicitly
        Console.WriteLine("Enlist exist: " +
            connStrBuilder.ContainsKey("Enlist"));

        //returns false
        connStrBuilder.ContainsKey("Invalid");

        // ShouldSerialize indicates whether or not a specific key
        // exists in connection string inherited from DbConnectionStringBuilder.
        // returns true if the key is explicitly added the user otherwise false;
        // this will return false as this key doesn't exists.
        connStrBuilder.ShouldSerialize("user");

        // returns false because this key is not added by user explicitly.
        connStrBuilder.ShouldSerialize("Enlist");

        // IsFixedSize [read-only property]
        Console.WriteLine("Connection String is fixed size only: "
            + connStrBuilder.IsFixedSize);
        Console.WriteLine("Key/Value Pair Count: " + connStrBuilder.Count);
    }
}
```

```
//adding a new key which is not supported by the provider
//is not allowed.
try
{
    //this will throw an exception.
    connStrBuilder.Add("NewKey", "newValue");
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
}

Console.WriteLine("Key/Value Pair Count: " + connStrBuilder.Count);

//modifying a existing key is allowed.
connStrBuilder.Add("Enlist", false);
Console.WriteLine("Key/Value Pair Count: " + connStrBuilder.Count);

// Get all the keys and values supported by the provider.
ICollection keyCollection = connStrBuilder.Keys;
ICollection valueCollection = connStrBuilder.Values;

IEnumerator keys = keyCollection.GetEnumerator();
IEnumerator values = valueCollection.GetEnumerator();

while (keys.MoveNext())
{
    values.MoveNext();
    Console.WriteLine("Key: {0}      Value: {1} \n"
        ,keys.Current ,values.Current);
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Members](#)
- [OracleConnectionStringBuilder Constructors](#)
- [OracleConnectionStringBuilder Public Properties](#)
- [OracleConnectionStringBuilder Public Methods](#)

OracleConnectionStringBuilder Members

OracleConnectionStringBuilder members are listed in the following tables.

OracleConnectionStringBuilder Constructors

OracleConnectionStringBuilder constructors are listed in [Table 6-52](#).

Table 6-52 OracleConnectionStringBuilder Constructors

Constructor	Description
OracleConnectionStringBuilder Constructors	Instantiates a new instance of OracleConnectionStringBuilder class (Overloaded)

OracleConnectionStringBuilder Public Properties

OracleConnectionStringBuilder instance properties are listed in [Table 6-53](#).

Table 6-53 OracleConnectionStringBuilder Public Properties

Properties	Description
BrowsableConnectionString	Inherited from System.Data.Common.DbConnectionStringBuilder
ConnectionLifeTime	Specifies the value corresponding to the Connection Lifetime attribute in the ConnectionString property
ConnectionString	Inherited from System.Data.Common.DbConnectionStringBuilder
ConnectionTimeout	Specifies the value corresponding to the Connection Timeout attribute in the ConnectionString property
ContextConnection	Specifies the value corresponding to the Context Connection attribute in the ConnectionString property
Count	Inherited from System.Data.Common.DbConnectionStringBuilder
DataSource	Specifies the value corresponding to the Data Source attribute in the ConnectionString property
DBAPrivilege	Specifies the value corresponding to the DBA Privilege attribute in the ConnectionString property
DecrPoolSize	Specifies the value corresponding to the Decr Pool Size attribute in the ConnectionString property
Enlist	Specifies the value corresponding to the Enlist attribute in the ConnectionString property
HAEvents	Specifies the value corresponding to the HA Events attribute in the ConnectionString property
IncrPoolSize	Specifies the value corresponding to the Incr Pool Size attribute in the ConnectionString property
IsFixedSize	Indicates whether or not the Connection String Builder has a fixed size
IsReadOnly	Inherited from System.Data.Common.DbConnectionStringBuilder
Item	Specifies the value associated with the specified attribute
Keys	Specifies a collection of attributes contained in the Connection String Builder

Table 6-53 (Cont.) OracleConnectionStringBuilder Public Properties

Properties	Description
LoadBalancing	Specifies the value corresponding to the Load Balancing attribute in the ConnectionString property
MaxPoolSize	Specifies the value corresponding to the Max Pool Size attribute in the ConnectionString property
MetadataPooling	Specifies the value that corresponds to the Metadata Pooling attribute in the ConnectionString property
MinPoolSize	Specifies the value corresponding to the Min Pool Size attribute in the ConnectionString property
Password	Specifies the value corresponding to the Password attribute in the ConnectionString property
PersistSecurityInfo	Specifies the value corresponding to the Persist Security Info attribute in the ConnectionString property
Pooling	Specifies the value corresponding to the Pooling attribute in the ConnectionString property
PromotableTransaction	Specifies the value corresponding to the PromotableTransaction attribute in the ConnectionString property <i>This property has been deprecated in 12.2.0.1. It will be desupported in a future release.</i>
ProxyPassword	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
ProxyUserId	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
SelfTuning	Specifies the value corresponding to the Self Tuning attribute in the ConnectionString property
StatementCachePurge	Specifies the value corresponding to the Statement Cache Purge attribute in the ConnectionString property
StatementCacheSize	Specifies the value corresponding to the Statement Cache Size attribute in the ConnectionString property
UserID	Specifies the value corresponding to the User Id attribute in the ConnectionString property
ValidateConnection	Specifies the value corresponding to the Validate Connection attribute in the ConnectionString property
Values	Specifies a collection of values contained in the Connection String Builder

OracleConnectionStringBuilder Public Methods

OracleConnectionStringBuilder instance methods are listed in [Table 6-54](#).

Table 6-54 OracleConnectionStringBuilder Public Methods

Methods	Description
Add	Inherited from System.Data.Common.DbConnectionStringBuilder
Clear	Clears the connection string contents
ContainsKey	Indicates whether or not a specific attribute in the connection string is supported by ODP.NET
EquivalentTo	Inherited from System.Data.Common.DbConnectionStringBuilder
Remove	Removes the entry corresponding to the specified attribute from the connection string
ShouldSerialize	Inherited from System.Data.Common.DbConnectionStringBuilder
ToString	Inherited from System.Data.Common.DbConnectionStringBuilder
TryGetValue	Returns the value corresponding to the supplied attribute, as an output parameter

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)

OracleConnectionStringBuilder Constructors

OracleConnectionStringBuilder constructors instantiate new instances of the OracleConnectionStringBuilder class.

Overload List:

- [OracleConnectionStringBuilder\(\)](#)
This constructor instantiates a new instance of OracleConnectionStringBuilder class.
- [OracleConnectionStringBuilder\(string\)](#)
This constructor instantiates a new instance of the OracleConnectionStringBuilder class with the provided connection string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleConnectionStringBuilder()

This constructor instantiates a new instance of the `OracleConnectionStringBuilder` class.

Declaration

```
// C#  
public OracleConnectionStringBuilder();
```

Remarks

The `ConnectionString` property is empty after the object is created.

 **See Also:**

["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)

OracleConnectionStringBuilder(string)

This constructor instantiates a new instance of the `OracleConnectionStringBuilder` class with the provided connection string.

Declaration

```
// C#  
public OracleConnectionStringBuilder(string connectionString);
```

Parameters

- *connectionString*
The connection information.

Exceptions

`ArgumentNullException` - The *connectionString* parameter is null.

`ArgumentException` - The *connectionString* parameter is invalid.

Remarks

The `ConnectionString` property of this instance is set to the supplied connection string.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleConnectionStringBuilder Public Properties

`OracleConnectionStringBuilder` public properties are listed in [Table 6-55](#).

Table 6-55 OracleConnectionStringBuilder Public Properties

Properties	Description
<code>BrowsableConnectionString</code>	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
ConnectionLifeTime	Specifies the value corresponding to the <code>Connection Lifetime</code> attribute in the <code>ConnectionString</code> property
<code>ConnectionString</code>	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
ConnectionTimeout	Specifies the value corresponding to the <code>Connection Timeout</code> attribute in the <code>ConnectionString</code> property
ContextConnection	Specifies the value corresponding to the <code>Context Connection</code> attribute in the <code>ConnectionString</code> property
<code>Count</code>	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
DataSource	Specifies the value corresponding to the <code>Data Source</code> attribute in the <code>ConnectionString</code> property
DBAPrivilege	Specifies the value corresponding to the <code>DBA Privilege</code> attribute in the <code>ConnectionString</code> property
DecrPoolSize	Specifies the value corresponding to the <code>Decr Pool Size</code> attribute in the <code>ConnectionString</code> property
Enlist	Specifies the value corresponding to the <code>Enlist</code> attribute in the <code>ConnectionString</code> property
HAEvents	Specifies the value corresponding to the <code>HA Events</code> attribute in the <code>ConnectionString</code> property

Table 6-55 (Cont.) OracleConnectionStringBuilder Public Properties

Properties	Description
IncrPoolSize	Specifies the value corresponding to the Incr Pool Size attribute in the ConnectionString property
IsFixedSize	Indicates whether or not the Connection String Builder has a fixed size
IsReadOnly	Inherited from System.Data.Common.DbConnectionStringBuilder
Item	Specifies the value associated with the specified attribute
Keys	Specifies a collection of attributes contained in the Connection String Builder
LoadBalancing	Specifies the value corresponding to the Load Balancing attribute in the ConnectionString property
MaxPoolSize	Specifies the value corresponding to the Max Pool Size attribute in the ConnectionString property
MetadataPooling	Specifies the value that corresponds to the Metadata Pooling attribute in the ConnectionString property
MinPoolSize	Specifies the value corresponding to the Min Pool Size attribute in the ConnectionString property
Password	Specifies the value corresponding to the Password attribute in the ConnectionString property
PersistSecurityInfo	Specifies the value corresponding to the Persist Security Info attribute in the ConnectionString property
Pooling	Specifies the value corresponding to the Pooling attribute in the ConnectionString property
PromotableTransaction	Specifies the value corresponding to the PromotableTransaction attribute in the ConnectionString property <i>This property has been deprecated in 12.2.0.1. It will be desupported in a future release.</i>
ProxyPassword	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
ProxyUserId	Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property
SelfTuning	Specifies the value corresponding to the Self Tuning attribute in the ConnectionString property
StatementCachePurge	Specifies the value corresponding to the Statement Cache Purge attribute in the ConnectionString property
StatementCacheSize	Specifies the value corresponding to the Statement Cache Size attribute in the ConnectionString property
UserID	Specifies the value corresponding to the User Id attribute in the ConnectionString property

Table 6-55 (Cont.) OracleConnectionStringBuilder Public Properties

Properties	Description
ValidateConnection	Specifies the value corresponding to the <code>ValidateConnection</code> attribute in the <code>ConnectionString</code> property
Values	Specifies a collection of values contained in the Connection String Builder

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ConnectionLifeTime

This property specifies the value corresponding to the `ConnectionLifeTime` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int ConnectionLifeTime{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than zero.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ConnectionTimeout

This property specifies the value corresponding to the `Connection Timeout` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int ConnectionTimeout{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than zero.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ContextConnection

This property specifies the value corresponding to the `Context Connection` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool ContextConnection {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

DataSource

This property specifies the value corresponding to the `Data Source` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string DataSource{get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exceptions

`ArgumentNullException` - The specified value is null.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

DBAPrivilege

This property specifies the value corresponding to the `DBA Privilege` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string DBAPrivilege{get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Possible values are `SYSDBA` or `SYSOPER`.

Exceptions

`ArgumentNullException` - The specified value is null.

`OracleException` - The specified value is invalid.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

DecrPoolSize

This property specifies the value corresponding to the `Decr Pool Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int DecrPoolSize{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 1.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Enlist

This property specifies the value corresponding to the `Enlist` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string Enlist{get; set;};
```

Property Value

A string that represents the value of the supplied attribute. Values are case-insensitive. Possible values are: `dynamic`, `true`, `false`, `yes`, and `no`.

Exceptions

`ArgumentNullException` - The specified value is null.

`OracleException` - The supplied value is not one of following: `dynamic`, `true`, `false`, `yes`, or `no`.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

HAEvents

This property specifies the value corresponding to the `HA Events` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool HAEvents{get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

IncrPoolSize

This property specifies the value corresponding to the `Incr Pool Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int IncrPoolSize{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 1.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

IsFixedSize

Indicates whether or not the Connection String Builder has a fixed size.

Declaration

```
// C#  
public override bool IsFixedSize{get;}
```

Property Value

Returns `true` if the Connection String Builder has a fixed size; otherwise, returns `false`.

Remarks

Attributes cannot be added or removed. They can only be modified for connection strings with a fixed size.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Item

This property specifies the value associated with the specified attribute.

Declaration

```
// C#  
public override object this[string keyword]{get; set;}
```

Property Value

An object value corresponding to the attribute.

Exceptions

`ArgumentNullException` - The specified attribute is null.

`OracleException` - The specified attribute is not supported or the specified value is invalid.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Keys

This property specifies a collection of attributes contained in the Connection String Builder.

Declaration

```
// C#  
public override ICollection Keys{get;}
```

Property Value

Returns an `ICollection` that represents the attributes in the Connection String Builder.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

LoadBalancing

This property specifies the value corresponding to the Load Balancing attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool LoadBalancing {get; set;}
```

Property Value

A `bool` that contains the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

MaxPoolSize

This property specifies the value corresponding to the `Max Pool Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int MaxPoolSize{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 1.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

MetadataPooling

This property specifies the value that corresponds to the `Metadata Pooling` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool MetadataPooling{get; set;};
```

Property Value

A `bool` containing the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

MinPoolSize

This property specifies the value corresponding to the `Min Pool Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int MinPoolSize{get; set;}
```

Property Value

An `int` that contains the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 0.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Password

This property specifies the value corresponding to the `Password` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string Password{get; set;}
```

Property Value

A string that contains the value of the supplied attribute.

Exception

`ArgumentNullException` - The specified value is null.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

PersistSecurityInfo

This property specifies the value corresponding to the `Persist Security Info` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool PersistSecurityInfo{get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property gets set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Pooling

This property specifies the value corresponding to the `Pooling` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool Pooling {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

PromotableTransaction

This property specifies the value corresponding to the `PromotableTransaction` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string PromotableTransaction {get; set;}
```

Property Value

A string that represents the value of the supplied attribute



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ProxyPassword

This property specifies the value corresponding to the `Proxy Password` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string ProxyPassword {get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exception

`ArgumentNullException` - The specified value is null.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ProxyUserId

This property specifies the value corresponding to the `Proxy User Id` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string ProxyUserId {get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exception

`ArgumentNullException` - The specified value is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

SelfTuning

This property specifies the value corresponding to the `Self Tuning` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool SelfTuning {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

StatementCachePurge

This property specifies the value corresponding to the `Statement Cache Purge` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool StatementCachePurge {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

StatementCacheSize

This property specifies the value corresponding to the `Statement Cache Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int StatementCacheSize{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than zero.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

UserID

This property specifies the value corresponding to the `User Id` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string UserID{get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exception

`ArgumentNullException` - The specified value is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ValidateConnection

This property specifies the value corresponding to the `Validate Connection` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool ValidateConnection{get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Values

This property specifies a collection of values contained in the Connection String Builder.

Declaration

```
// C#
public override ICollection Values{get;}
```

Property Value

Returns an `ICollection` that represents the values in the Connection String Builder.

Remarks

The order of the values in the `ICollection` is unspecified, but is the same as the associated attributes in the `ICollection` returned by the `Keys` property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleConnectionStringBuilder Public Methods

`OracleConnectionStringBuilder` public methods are listed in [Table 6-56](#).

Table 6-56 OracleConnectionStringBuilder Public Methods

Methods	Description
<code>Add</code>	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
<code>Clear</code>	Clears the connection string contents
<code>ContainsKey</code>	Indicates whether or not a specific attribute in the connection string is supported by ODP.NET

Table 6-56 (Cont.) OracleConnectionStringBuilder Public Methods

Methods	Description
EquivalentTo	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
Remove	Removes the entry corresponding to the specified attribute from the connection string
ShouldSerialize	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
ToString	Inherited from <code>System.Data.Common.DbConnectionStringBuilder</code>
TryGetValue	Returns the value corresponding to the supplied attribute, as an output parameter

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Clear

This method clears the connection string contents.

Declaration

```
// C#  
public override void Clear();
```

Remarks

All key/value pairs are removed from the `OracleConnectionStringBuilder` object and the `ConnectionString` property is set to `Empty`.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ContainsKey

This method indicates whether or not a specific attribute in the connection string is supported by ODP.NET.

Declaration

```
// C#  
public override bool ContainsKey(string keyword);
```

Parameters

- *keyword*
The attribute being verified.

Return Value

Returns `true` if the specified attribute exists; otherwise, returns `false`.

Exceptions

`ArgumentNullException` - The specified attribute is null.

Remarks

This method indicates if the attribute is part of the provider-supported attributes. It does not indicate if the user added the attribute to the connection string.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Remove

This method removes the entry corresponding to the specified attribute from the connection string.

Declaration

```
// C#  
public override bool Remove(string keyword);
```

Parameters

- *keyword*
The attribute that specifies the entry to be removed.

Return Value

Returns `true` if the attribute existed in the connection string and the corresponding entry was removed; otherwise, returns `false`.

Exceptions

`ArgumentNullException` - The specified attribute is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

TryGetValue

This method returns the value corresponding to the supplied attribute, as an output parameter.

Declaration

```
// C#  
public override bool TryGetValue(string keyword, out object value);
```

Parameters

- *keyword*
The attribute for which the value is being retrieved.
- *value*
The value of the supplied attribute.
Sets *value* to the default value if the attribute is not present in the connection string.

Return Value

Returns `true` if the value that corresponds to the attribute has been successfully retrieved; otherwise, returns `false`. If the attribute is not present in the connection string, returns `false` and sets the *value* to null.

Exceptions

`ArgumentNullException` - The specified attribute is null.

Remarks

If the function returns `false`, sets *value* to null.

If the attribute is not present in the connection string, sets *value* to the default value.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleCredential Class

OracleCredential class provides a secure way to provide password while opening connection with Oracle Database using the ODP.NET driver. Use this class to avoid providing passwords in clear text in the connection string while opening a connection with Oracle Database. One can pass user id, password and DBA Privilege specific attributes through OracleCredential constructors and thus these attributes do not need to be in the connection string.

Operating system authenticated and context connections are not supported through OracleCredential class. An ArgumentException will be thrown if "/" is passed for userId or proxyUserId arguments of OracleCredential constructor.

Class Inheritance

System.Object

Oracle.DataAccess.Client.OracleCredential

Declaration

```
// C#
public sealed class OracleCredential
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#
using System;
using System.Data;
using System.Security;
using Oracle.DataAccess.Client;
//using Oracle.ManagedDataAccess.Client;

class OracleCredentialSample
{
    static void Main()
    {
        // Connect
        string constr = "Data Source=oracle";

        SecureString secPwd = new SecureString();
        secPwd.AppendChar('h');
        secPwd.AppendChar('r');

        // Make the password read-only.
        secPwd.MakeReadOnly();

        // Create OracleCredential with userid and secure password.
        OracleCredential oc = new OracleCredential("hr", secPwd);

        OracleConnection con = new OracleConnection(constr, oc);
        con.Open();

        // Execute a SQL SELECT

        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select * from employees";

        OracleDataReader reader = cmd.ExecuteReader();

        // Print all employee numbers
        while (reader.Read())
            Console.WriteLine(reader.GetInt32(0));

        // Clean up
        reader.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Members](#)
- [OracleCredential Constructors](#)
- [OracleCredential Properties](#)
- [Connection Pooling with OracleCredential](#)

OracleCredential Members

OracleCredential members are listed in the following tables.

OracleCredential Constructors

OracleCredential constructors are listed in [Table 6-57](#).

Table 6-57 OracleCredential Constructors

Constructor	Description
OracleCredential Constructors	Instantiates a new instance of OracleCredential class (Overloaded)

OracleCredential Properties

OracleCredential properties are listed in [Table 6-58](#).

Table 6-58 OracleCredential Properties

Property	Description
DBAPrivilege	Returns the DBA Privilege used to create the OracleCredential object. OracleDBAPrivilege.None is returned if it was not provided by the user.
Password	Returns the password of the OracleCredential object
ProxyPassword	Returns the proxy user password of the OracleCredential object
ProxyUserId	Returns the proxy user id of the OracleCredential object
UserId	Returns the user id of the OracleCredential object

OracleCredential Public Methods

OracleCredential public methods are listed in [Table 6-64](#).

Table 6-59 OracleCredential Public Methods

Public Method	Description
<code>Equals(Object)</code>	Inherited from <code>System.Object</code>
<code>GetHashCode()</code>	Inherited from <code>System.Object</code>
<code>GetType()</code>	Inherited from <code>System.Object</code>
<code>ToString()</code>	Inherited from <code>System.Object</code>

OracleCredential Constructors

`OracleCredential` constructors instantiate new instances of an `OracleCredential` class.

Overload List:

- [OracleCredential\(string, SecureString\)](#)
This constructor creates an `OracleCredential` object with the user id and the secured password.
- [OracleCredential\(string, SecureString, OracleDBAPrivilege\)](#)
This constructor creates an `OracleCredential` object with the user id, the secured password, and the DBA privilege request.
- [OracleCredential\(string, SecureString, string, SecureString\)](#)
This constructor creates an `OracleCredential` object with the user id and the secured password for the end user, as well as the user id and the secured password for the proxy user.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

OracleCredential(string, SecureString)

This constructor creates an `OracleCredential` object with the user id and the secured password.

Declaration

```
// C#  
public OracleCredential(string userId, SecureString password)
```

Exceptions

- `ArgumentNullException` is raised if any parameters are passed as null.
- `ArgumentException` is raised if "/" is passed for `userId` argument.
- `ArgumentException` is raised if the `SecureString` containing the password is not read-only.
- `InvalidOperationException` is raised when `OracleCredential` object is used with any of `user id`, `password`, `proxy user id`, `proxy password` and/or `dba privilegeconnection` string attribute(s) present in the connection string.

Remarks

With this constructor, `OracleDBAPrivilege.None` is used for the DBA privilege when requesting for a connection.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

OracleCredential(string, SecureString, OracleDBAPrivilege)

This constructor creates an `OracleCredential` object with the user id, the secured password, and the DBA privilege request.

Declaration

```
// C#
public OracleCredential(string userId, SecureString password, OracleDBAPrivilege
dbaprivilege)
```

Exceptions

- `ArgumentNullException` is raised if any parameters are passed as null.
- `ArgumentException` is raised if "/" is passed for `userId` argument.
- `ArgumentException` is raised if the `SecureString` containing the password is not read-only.
- `InvalidOperationException` is raised when `OracleCredential` object is used with any of `user id`, `password`, `proxy user id`, `proxy password` and/or `dba privilegeconnection` string attribute(s) present in the connection string.

Remarks

With this constructor, the specified `dbaprivilege` is for the DBA privilege when requesting for a connection.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- [OracleDBAPrivilege Enumeration](#)

OracleCredential(string, SecureString, string, SecureString)

This constructor creates an `OracleCredential` object with the user id and the secured password for the end user, as well as the user id and the secured password for the proxy user.

Declaration

```
// C#  
public OracleCredential(string userId, SecureString password, string proxyUserId,  
SecureString proxyPassword)
```

Exceptions

- `ArgumentNullException` is raised if any parameters are passed as null.
- `ArgumentException` is raised if "/" is passed for `userId` argument.
- `ArgumentException` is raised if the `SecureString` containing the password is not read-only.
- `InvalidOperationException` is raised when `OracleCredential` object is used with any of `user id`, `password`, `proxy user id`, `proxy password` and/or `dba privilegeconnection string attribute(s)` present in the connection string.

Remarks

With this constructor, `OracleDBAPrivilege.None` is for the DBA privilege when requesting for a connection.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

OracleCredential Properties

`OracleCredential` properties are listed in [Table 6-60](#).

Table 6-60 OracleCredential Properties

Property	Description
DBAPrivilege	Returns the DBA Privilege used to create the OracleCredential object. OracleDBAPrivilege.None is returned if it was not provided by the user.
Password	Returns the password of the OracleCredential object.
ProxyPassword	Returns the proxy user password of the OracleCredential object.
ProxyUserId	Returns the proxy user id of the OracleCredential object.
UserId	Returns the user id of the OracleCredential object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

DBAPrivilege

This property returns the DBA Privilege that is associated with the user.

Declaration

```
// C#  
OracleDBAPrivilege DBAPrivilege { get; }
```

Property Value

The OracleDBAPrivilege enum value that is associated with the user.

Remarks

OracleDBAPrivilege.None is returned if it was not set by the user.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)
- [OracleDBAPrivilege Enumeration](#)

Password

This property returns the encrypted password of the user.

Declaration

```
// C#  
SecureString Password { get; }
```

Property Value

The encrypted password of the user.

OracleCredential does not support double quotes around a SecureString password. Double quotes can be used within a password, however.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

ProxyPassword

This property returns the encrypted password of the proxy user.

Declaration

```
// C#  
SecureString ProxyUserPassword { get; }
```

Property Value

The encrypted password of the proxy user.

Remarks

OracleCredential does not support double quotes around a SecureString password. Double quotes can be used within a password, however.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

ProxyUserId

This property returns the proxy user id.

Declaration

```
// C#  
string ProxyUserId { get; }
```

Property Value

The proxy user id.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

UserId

This property returns the user id.

Declaration

```
// C#  
string UserId { get; }
```

Property Value

The user id.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [OracleCredential Members](#)

OracleDataAdapter Class

An `OracleDataAdapter` object represents a data provider object that populates the `DataSet` and updates changes in the `DataSet` to the Oracle database.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.ComponentModel.Component`

`System.Data.Common.DataAdapter`

`System.Data.Common.DbDataAdapter`

`Oracle.DataAccess.Client.OracleDataAdapter`

Declaration

```
// C#
public sealed class OracleDataAdapter : DbDataAdapter, IDbDataAdapter
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

The following example uses the `OracleDataAdapter` and the dataset to update the `EMP` table:

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleDataAdapterSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        string cmdstr = "SELECT empno, sal from emp";

        // Create the adapter with the selectCommand txt and the
        // connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Create the builder for the adapter to automatically generate
        // the Command when needed
        OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

        // Create and fill the DataSet using the EMP
        DataSet dataset = new DataSet();
        adapter.Fill(dataset, "EMP");

        // Get the EMP table from the dataset
        DataTable table = dataset.Tables["EMP"];

        // Indicate DataColumn EMPNO is unique
        // This is required by the OracleCommandBuilder to update the EMP table
        table.Columns["EMPNO"].Unique = true;

        // Get the first row from the EMP table
        DataRow row = table.Rows[0];

        // Update the salary
        double sal = double.Parse(row["SAL"].ToString());
        row["SAL"] = sal + .01;

        // Now update the EMP using the adapter
        // The OracleCommandBuilder will create the UpdateCommand for the
        // adapter to update the EMP table
        adapter.Update(dataset, "EMP");

        Console.WriteLine("Row updated successfully");
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Members](#)
- [OracleDataAdapter Constructors](#)
- [OracleDataAdapter Static Methods](#)
- [OracleDataAdapter Properties](#)
- [OracleDataAdapter Public Methods](#)
- [OracleDataAdapter Events](#)

OracleDataAdapter Members

OracleDataAdapter members are listed in the following tables.

OracleDataAdapter Constructors

OracleDataAdapter constructors are listed in [Table 6-61](#).

Table 6-61 OracleDataAdapter Constructors

Constructor	Description
OracleDataAdapter Constructors	Instantiates a new instance of OracleDataAdapter class (Overloaded)

OracleDataAdapter Static Methods

The OracleDataAdapter static method is listed in [Table 6-62](#).

Table 6-62 OracleDataAdapter Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleDataAdapter Properties

OracleDataAdapter properties are listed in [Table 6-63](#).

Table 6-63 OracleDataAdapter Properties

Property	Description
AcceptChangesDuringFill	Inherited from System.Data.Common.DataAdapter
Container	Inherited from System.ComponentModel.Component

Table 6-63 (Cont.) OracleDataAdapter Properties

Property	Description
ContinueUpdateOnError	Inherited from <code>System.Data.Common.DataAdapter</code>
DeleteCommand	A SQL statement or stored procedure to delete rows from an Oracle database
IdentityInsert	Determines whether or not to insert identity column values in the <code>DataSet</code> into the database when the <code>Update</code> method is invoked. <i>Not Available in the ODP.NET, Managed Driver and ODP.NET Core</i>
IdentityUpdate	Determines whether or not to update identity column values in the <code>DataSet</code> into the database when the <code>Update</code> method is invoked. <i>Not Available in the ODP.NET, Managed Driver and ODP.NET Core</i>
InsertCommand	A SQL statement or stored procedure to insert new rows into an Oracle database
MissingMappingAction	Inherited from <code>System.Data.Common.DataAdapter</code>
MissingSchemaAction	Inherited from <code>System.Data.Common.DataAdapter</code>
Requery	Determines whether or not the <code>SelectCommand</code> is reexecuted on the next call to <code>Fill</code>
ReturnProviderSpecificTypes	Determines if the <code>Fill</code> method returns ODP.NET-specific values or .NET common language specification values
SafeMapping	Creates a mapping between column names in the result set to .NET types, to preserve the data <i>Not Available in the ODP.NET, Managed Driver and ODP.NET Core</i>
SelectCommand	A SQL statement or stored procedure that returns a single or multiple result set
Site	Inherited from <code>System.ComponentModel.Component</code>
TableMappings	Inherited from <code>System.Data.Common.DataAdapter</code>
UpdateBatchSize	Specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database
UpdateCommand	A SQL statement or stored procedure to update rows from the <code>DataSet</code> to an Oracle database

OracleDataAdapter Public Methods

OracleDataAdapter public methods are listed in [Table 6-64](#).

Table 6-64 OracleDataAdapter Public Methods

Public Method	Description
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
Dispose	Inherited from <code>System.ComponentModel.Component</code>
Equals	Inherited from <code>System.Object</code> (Overloaded)
Fill	Adds or refreshes rows in the <code>DataSet</code> to match the data in the Oracle database (Overloaded)
FillSchema	Inherited from <code>System.Data.Common.DbDataAdapter</code>
GetFillParameters	Inherited from <code>System.Data.Common.DbDataAdapter</code>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
ToString	Inherited from <code>System.Object</code>
Update	Inherited from <code>System.Data.Common.DbDataAdapter</code>

OracleDataAdapter Events

OracleDataAdapter events are listed in [Table 6-65](#).

Table 6-65 OracleDataAdapter Events

Event Name	Description
Disposed	Inherited from <code>System.ComponentModel.Component</code>
FillError	Inherited from <code>System.Data.Common.DbDataAdapter</code>
RowUpdated	This event is raised when row(s) have been updated by the <code>Update()</code> method
RowUpdating	This event is raised when row data are about to be updated to the database

OracleDataAdapter Constructors

OracleDataAdapter constructors create new instances of an OracleDataAdapter class.

Overload List:

- [OracleDataAdapter\(\)](#)
This constructor creates an instance of an OracleDataAdapter class.
- [OracleDataAdapter\(OracleCommand\)](#)

This constructor creates an instance of an `OracleDataAdapter` class with the provided `OracleCommand` as the `SelectCommand`.

- [OracleDataAdapter\(string, OracleConnection\)](#)

This constructor creates an instance of an `OracleDataAdapter` class with the provided `OracleConnection` object and the command text for the `SelectCommand`.

- [OracleDataAdapter\(string, string\)](#)

This constructor creates an instance of an `OracleDataAdapter` class with the provided connection string and the command text for the `SelectCommand`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter()

This constructor creates an instance of an `OracleDataAdapter` class with no arguments.

Declaration

```
// C#  
public OracleDataAdapter();
```

Remarks

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter(OracleCommand)

This constructor creates an instance of an `OracleDataAdapter` class with the provided `OracleCommand` as the `SelectCommand`.

Declaration

```
// C#  
public OracleDataAdapter(OracleCommand selectCommand);
```

Parameters

- *selectCommand*

The `OracleCommand` that is to be set as the `SelectCommand` property.

Remarks

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction` = `MissingMappingAction.Passthrough`
- `MissingSchemaAction` = `MissingSchemaAction.Add`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter(string, OracleConnection)

This constructor creates an instance of an `OracleDataAdapter` class with the provided `OracleConnection` object and the command text for the `SelectCommand`.

Declaration

```
// C#  
public OracleDataAdapter(string selectCommandText, OracleConnection  
    selectConnection);
```

Parameters

- *selectCommandText*

The string that is set as the `CommandText` of the `SelectCommand` property of the `OracleDataAdapter`.

- *selectConnection*

The `OracleConnection` to connect to the Oracle database.

Remarks

The `OracleDataAdapter` opens and closes the connection, if it is not already open. If the connection is open, it must be explicitly closed.

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter(string, string)

This constructor creates an instance of an `OracleDataAdapter` class with the provided connection string and the command text for the `SelectCommand`.

Declaration

```
// C#  
public OracleDataAdapter(string selectCommandText, string  
    selectConnectionString);
```

Parameters

- *selectCommandText*
The string that is set as the `CommandText` of the `SelectCommand` property of the `OracleDataAdapter`.
- *selectConnectionString*
The connection string.

Remarks

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter Static Methods

The `OracleDataAdapter` static method is listed in [Table 6-66](#).

Table 6-66 OracleDataAdapter Static Method

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter Properties

`OracleDataAdapter` properties are listed in [Table 6-67](#).

Table 6-67 OracleDataAdapter Properties

Property	Description
<code>AcceptChangesDuringFill</code>	Inherited from <code>System.Data.Common.DataAdapter</code>
<code>Container</code>	Inherited from <code>System.ComponentModel.Component</code>
<code>ContinueUpdateOnError</code>	Inherited from <code>System.Data.Common.DataAdapter</code>
DeleteCommand	A SQL statement or stored procedure to delete rows from an Oracle database
IdentityInsert	Determines whether or not to insert identity column values in the <code>DataSet</code> into the database when the <code>Update</code> method is invoked. <i>Not Available in the ODP.NET, Managed Driver and ODP.NET Core</i>
IdentityUpdate	Determines whether or not to update identity column values in the <code>DataSet</code> into the database when the <code>Update</code> method is invoked. <i>Not Available in the ODP.NET, Managed Driver and ODP.NET Core</i>
InsertCommand	A SQL statement or stored procedure to insert new rows into an Oracle database
<code>MissingMappingAction</code>	Inherited from <code>System.Data.Common.DataAdapter</code>
<code>MissingSchemaAction</code>	Inherited from <code>System.Data.Common.DataAdapter</code>

Table 6-67 (Cont.) OracleDataAdapter Properties

Property	Description
Requery	Determines whether or not the <code>SelectCommand</code> is reexecuted on the next call to <code>Fill</code>
ReturnProviderSpecificTypes	Determines if the <code>Fill</code> method returns ODP.NET-specific values or .NET common language specification values
SafeMapping	Creates a mapping between column names in the result set to .NET types, to preserve the data <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
SelectCommand	A SQL statement or stored procedure that returns a single or multiple result set
Site	Inherited from <code>System.ComponentModel.Component</code>
TableMappings	Inherited from <code>System.Data.Common.DataAdapter</code>
UpdateBatchSize	Specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database
UpdateCommand	A SQL statement or stored procedure to update rows from the <code>DataSet</code> to an Oracle database

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

DeleteCommand

This property is a SQL statement or stored procedure to delete rows from an Oracle database.

Declaration

```
// C#
public OracleCommand DeleteCommand {get; set;}
```

Property Value

An `OracleCommand` used during the `Update` call to delete rows from tables in the Oracle database, corresponding to the deleted rows in the `DataSet`.

Remarks

Default = null

If there is primary key information in the `DataSet`, the `DeleteCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

IdentityInsert

When inserting `DataSet` data into the database, this property indicates whether the database generates the inserted row's identity column value or `DataSet` supplies this value.

Declaration

```
// C#  
public bool IdentityInsert {get; set;}
```

Property Value

When set to `true`, ODP.NET inserts `DataSet` identity column values into the database. When set to `false`, the database determines the inserted identity column values.

Remarks

This property applies only to identity columns of type `GENERATED BY DEFAULT` and `GENERATED BY DEFAULT ON NULL`. Identity column of type `GENERATED ALWAYS` will ignore this property and will always use database generated values.

When set to `false`, the server will generate an identity value for the row. That generated identity value returns back to the client to update the `DataSet` value.

When this property is set to `true` for the `GENERATED BY DEFAULT` case and the application attempts to insert a `NULL` value into the database's identity column, the `NOT NULL` constraint is violated and an error occurs. ODP.NET will then allow the database to generate the identity column value and return the generated value to the `DataSet`.

The default value for this property is `false`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- [OracleIdentityType Enumeration](#)

IdentityUpdate

When updating `DataSet` data into the database, this property indicates whether to replace the database's identity column values with values of the `DataSet` or leave the current values unchanged.

Declaration

```
// C#  
public bool IdentityUpdate {get; set;}
```

Property Value

When set to true, ODP.NET updates the database identity column values with the values of the `DataSet`. When set to false, the database identity columns are left unchanged.

Remarks

This property applies only to identity columns of type `GENERATED BY DEFAULT` and `GENERATED BY DEFAULT ON NULL`. In the case of type `GENERATED ALWAYS`, this property will be ignored and the database will always retain its current identity values.

When set to false, the existing identity column value in the server is returned to the `DataSet`.

When this property is set to true for the `GENERATED BY DEFAULT` and `GENERATED BY DEFAULT ON NULL` cases and the application attempts to update the database's identity column with a `NULL` value, the `NOT NULL` constraint is violated and an error occurs. ODP.NET then does not update the identity column value and instead returns the existing identity column value of the database to the `DataSet`.

The default value for this property is `false`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- [OracleIdentityType Enumeration](#)

InsertCommand

This property is a SQL statement or stored procedure to insert new rows into an Oracle database.

Declaration

```
// C#  
public OracleCommand InsertCommand {get; set;}
```

Property Value

An `OracleCommand` used during the `Update` call to insert rows into a table, corresponding to the inserted rows in the `DataSet`.

Remarks

Default = null

If there is primary key information in the `DataSet`, the `InsertCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

Requery

This property determines whether or not the `SelectCommand` is reexecuted on the next call to `Fill`.

Declaration

```
// C#  
public Boolean Requery {get; set;}
```


Property Value

Returns `true` if the `SelectCommand` is reexecuted on the next call to `Fill`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#)

ReturnProviderSpecificTypes

This property determines if the `Fill` method returns ODP.NET-specific values or .NET common language specification compliant values.

Declaration

```
// C#  
public Boolean ReturnProviderSpecificTypes {get; set;}
```

Property Value

A value that indicates whether or not the `Fill` method returns ODP.NET-specific values.

Starting with ODP.NET 12.1.0.2, when set to `true` and `LegacyEntireLOBFetch = 0` (default), BLOB and CLOB column values are represented in the `DataTable` as `OracleBlob` and `OracleClob`, respectively.

A value of `false` indicates that the `Fill` method returns .NET common language specification compliant values. The default is `false`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

SafeMapping

This property creates a mapping between column names in the result set to .NET types that represent column values in the `DataSet`, to preserve the data.

Declaration

```
// C#  
public Hashtable SafeMapping {get; set;}
```

Property Value

A hash table.

Remarks

Default = null

The `SafeMapping` property is used, when necessary, to preserve data in the following types:

- DATE
- TimeStamp (refers to all TimeStamp objects)
- INTERVAL DAY TO SECOND
- NUMBER

Example

See the example in "[OracleDataAdapter Safe Type Mapping](#)".

See Also:

- "[Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces](#)"
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- "[OracleDataAdapter Safe Type Mapping](#)"

SelectCommand

This property is a SQL statement or stored procedure that returns single or multiple result sets.

Declaration

```
// C#  
public OracleCommand SelectCommand {get; set;}
```

Property Value

An `OracleCommand` used during the `Fill` call to populate the selected rows to the `DataSet`.

Remarks

Default = null

If the `SelectCommand` does not return any rows, no tables are added to the dataset and no exception is raised.

If the `SELECT` statement selects from a `VIEW`, no key information is retrieved when a `FillSchema()` or a `Fill()` with `MissingSchemaAction.AddWithKey` is invoked.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#)

UpdateBatchSize

This property specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database.

Declaration

```
// C#  
public virtual int UpdateBatchSize {get; set;}
```

Property Value

An integer that returns the batch size.

Exceptions

`ArgumentOutOfRangeException` - The value is set to a number < 0.

Remarks

Update batches executed with large amounts of data may encounter an "PLS-00123: Program too large" error. To avoid this error, reduce the size of `UpdateBatchSize` to a smaller value.

For each row in the `DataSet` that has been modified, added, or deleted, one SQL statement will be executed on the database.

Values are as follows:

- Value = 0
The data adapter executes all the SQL statements in a single database round-trip
- Value = 1 - Default value
This value disables batch updating and SQL statements are executed one at a time.
- Value = n where $n > 1$
The data adapter updates n rows of data per database round-trip.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["Batch Processing"](#)

UpdateCommand

This property is a SQL statement or stored procedure to update rows from the DataSet to an Oracle database.

Declaration

```
// C#  
public OracleCommand UpdateCommand {get; set;}
```

Property Value

An `OracleCommand` used during the `Update` call to update rows in the Oracle database, corresponding to the updated rows in the `DataSet`.

Remarks

Default = null

If there is primary key information in the `DataSet`, the `UpdateCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#)

OracleDataAdapter Public Methods

OracleDataAdapter public methods are listed in [Table 6-68](#).

Table 6-68 OracleDataAdapter Public Methods

Public Method	Description
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Inherited from System.ComponentModel.Component
Equals	Inherited from System.Object (Overloaded)
Fill	Adds or refreshes rows in the DataSet to match the data in the Oracle database (Overloaded)
FillSchema	Inherited from System.Data.Common.DbDataAdapter
GetFillParameters	Inherited from System.Data.Common.DbDataAdapter
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
ToString	Inherited from System.Object
Update	Inherited from System.Data.Common.DbDataAdapter

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

Fill

Fill populates or refreshes the specified `DataTable` or `DataSet`.

Overload List:

- [Fill\(DataTable, OracleRefCursor\)](#)
This method adds or refreshes rows in the specified `DataTable` to match those in the provided `OracleRefCursor` object.
- [Fill\(DataSet, OracleRefCursor\)](#)
This method adds or refreshes rows in the `DataSet` to match those in the provided `OracleRefCursor` object.
- [Fill\(DataSet, string, OracleRefCursor\)](#)
This method adds or refreshes rows in the specified source table of the `DataSet` to match those in the provided `OracleRefCursor` object.
- [Fill\(DataSet, int, int, string, OracleRefCursor\)](#)
This method adds or refreshes rows in a specified range in the `DataSet` to match rows in the provided `OracleRefCursor` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

Fill(DataTable, OracleRefCursor)

This method adds or refreshes rows in the specified `DataTable` to match those in the provided `OracleRefCursor` object.

Declaration

```
// C#  
public int Fill(DataTable dataTable, OracleRefCursor refCursor);
```

Parameters

- *dataTable*
The `DataTable` object being populated.
- *refCursor*
The `OracleRefCursor` that rows are being retrieved from.

Return Value

The number of rows added to or refreshed in the `DataTable`.

Exceptions

`ArgumentNullException` - The `dataTable` or `refCursor` parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data.

`NotSupportedException` - The `SafeMapping` type is not supported.

Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#)

Fill(DataSet, OracleRefCursor)

This method adds or refreshes rows in the `DataSet` to match those in the provided `OracleRefCursor` object.

Declaration

```
// C#  
public int Fill(DataSet dataSet, OracleRefCursor refCursor);
```

Parameters

- `dataSet`
The `DataSet` object being populated.
- `refCursor`
The `OracleRefCursor` that rows are being retrieved from.

Return Value

Returns the number of rows added or refreshed in the `DataSet`.

Exceptions

`ArgumentNullException` - The `dataSet` or `refCursor` parameter is null.

InvalidOperationException - The `OracleRefCursor` is already being used to fetch data.

InvalidOperationException - The `OracleRefCursor` is ready to fetch data.

NotSupportedException - The `SafeMapping` type is not supported.

Remarks

If there is no `DataTable` to refresh, a new `DataTable` named `Table` is created and populated using the provided `OracleRefCursor` object.

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#)

Fill(DataSet, string, OracleRefCursor)

This method adds or refreshes rows in the specified source table of the `DataSet` to match those in the provided `OracleRefCursor` object.

Declaration

```
// C#
public int Fill(DataSet dataSet, string srcTable, OracleRefCursor
    refCursor);
```

Parameters

- *dataSet*
The `DataSet` object being populated.
- *srcTable*
The name of the source table used in the table mapping.
- *refCursor*
The `OracleRefCursor` that rows are being retrieved from.

Return Value

Returns the number of rows added or refreshed into the `DataSet`.

Exceptions

`ArgumentNullException` - The *dataSet* or *refCursor* parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data or the source table name is invalid.

`NotSupportedException` - The `SafeMapping` type is not supported.

Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#)

Fill(DataSet, int, int, string, OracleRefCursor)

This method adds or refreshes rows in a specified range in the `DataSet` to match rows in the provided `OracleRefCursor` object.

Declaration

```
// C#
public int Fill(DataSet dataSet, int startRecord, int maxRecords,
    string srcTable, OracleRefCursor refCursor);
```

Parameters

- *dataSet*
The `DataSet` object being populated.
- *startRecord*
The record number to start with.
- *maxRecords*
The maximum number of records to obtain.
- *srcTable*
The name of the source table used in the table mapping.
- *refCursor*
The `OracleRefCursor` that rows are being retrieved from.

Return Value

This method returns the number of rows added or refreshed in the `DataSet`. This does not include rows affected by statements that do not return rows.

Exceptions

`ArgumentNullException` - The `dataSet` or `refCursor` parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data or the source table name is invalid.

`NotSupportedException` - The `SafeMapping` type is not supported.

Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#)

OracleDataAdapter Events

`OracleDataAdapter` events are listed in [Table 6-69](#).

Table 6-69 OracleDataAdapter Events

Event Name	Description
<code>Disposed</code>	Inherited from <code>System.ComponentModel.Component</code>
<code>FillError</code>	Inherited from <code>System.Data.Common.DbDataAdapter</code>
RowUpdated	This event is raised when row(s) have been updated by the <code>Update()</code> method
RowUpdating	This event is raised when row data are about to be updated to the database

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

RowUpdated

This event is raised when row(s) have been updated by the `Update()` method.

Declaration

```
// C#  
public event OracleRowUpdatedEventHandler RowUpdated;
```

Event Data

The event handler receives an `OracleRowUpdatedEventArgs` object which exposes the following properties containing information about the event.

- `Command`
The `OracleCommand` executed during the `Update`.
- `Errors` (inherited from `RowUpdatedEventArgs`)
The exception, if any, is generated during the `Update`.
- `RecordsAffected` (inherited from `RowUpdatedEventArgs`)
The number of rows modified, inserted, or deleted by the execution of the `Command`.
- `Row` (inherited from `RowUpdatedEventArgs`)
The `DataRow` sent for `Update`.
- `StatementType` (inherited from `RowUpdatedEventArgs`)
The type of SQL statement executed.
- `Status` (inherited from `RowUpdatedEventArgs`)
The `UpdateStatus` of the `Command`.
- `TableMapping` (inherited from `RowUpdatedEventArgs`)
The `DataTableMapping` used during the `Update`.

Example

The following example shows how to use the `RowUpdating` and `RowUpdated` events.

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class RowUpdatedSample  
{  
    // Event handler for RowUpdating event  
    protected static void OnRowUpdating(object sender,  
                                        OracleRowUpdatingEventArgs e)  
    {  
        Console.WriteLine("Row updating....");  
        Console.WriteLine("Event arguments:");  
        Console.WriteLine("Command Text: " + e.Command.CommandText);  
        Console.WriteLine("Command Type: " + e.StatementType);  
        Console.WriteLine("Status: " + e.Status);  
    }  
}
```

```
}

// Event handler for RowUpdated event
protected static void OnRowUpdated(object sender,
                                   OracleRowUpdatedEventArgs e)
{
    Console.WriteLine("Row updated....");
    Console.WriteLine("Event arguments:");
    Console.WriteLine("Command Text: " + e.Command.CommandText);
    Console.WriteLine("Command Type: " + e.StatementType);
    Console.WriteLine("Status: " + e.Status);
}

static void Main()
{
    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    string cmdstr = "SELECT EMPNO, ENAME, SAL FROM EMP";

    // Create the adapter with the selectCommand txt and the
    // connection string
    OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

    // Create the builder for the adapter to automatically generate
    // the Command when needed
    OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

    // Create and fill the DataSet using the EMP
    DataSet dataset = new DataSet();
    adapter.Fill(dataset, "EMP");

    // Get the EMP table from the dataset
    DataTable table = dataset.Tables["EMP"];

    // Indicate DataColumn EMPNO is unique
    // This is required by the OracleCommandBuilder to update the EMP table
    table.Columns["EMPNO"].Unique = true;

    // Get the first row from the EMP table
    DataRow row = table.Rows[0];

    // Update the salary
    double sal = double.Parse(row["SAL"].ToString());
    row["SAL"] = sal + .01;

    // Set the event handlers for the RowUpdated and the RowUpdating event
    // the OnRowUpdating() method will be triggered before the update, and
    // the OnRowUpdated() method will be triggered after the update
    adapter.RowUpdating += new OracleRowUpdatingEventHandler(OnRowUpdating);
    adapter.RowUpdated += new OracleRowUpdatedEventHandler(OnRowUpdated);

    // Now update the EMP using the adapter
    // The OracleCommandBuilder will create the UpdateCommand for the
    // adapter to update the EMP table
    // The OnRowUpdating() and the OnRowUpdated() methods will be triggered
    adapter.Update(dataset, "EMP");
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleRowUpdatedEventHandler Delegate"](#)

RowUpdating

This event is raised when row data are about to be updated to the database.

Declaration

```
// C#  
public event OracleRowUpdatingEventHandler RowUpdating;
```

Event Data

The event handler receives an `OracleRowUpdatingEventArgs` object which exposes the following properties containing information about the event.

- **Command**
The `OracleCommand` executed during the `Update`.
- **Errors (inherited from `RowUpdatingEventArgs`)**
The exception, if any, is generated during the `Update`.
- **Row (inherited from `RowUpdatingEventArgs`)**
The `DataRow` sent for `Update`.
- **StatementType (inherited from `RowUpdatingEventArgs`)**
The type of SQL statement executed.
- **Status (inherited from `RowUpdatingEventArgs`)**
The `UpdateStatus` of the `Command`.
- **TableMapping (inherited from `RowUpdatingEventArgs`)**
The `DataTableMapping` used during the `Update`.

Example

The example for the `RowUpdated` event also shows how to use the `RowUpdating` event. See `RowUpdated` event "[Example](#)".

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleRowUpdatingEventHandler Delegate"](#)

OracleDatabase Class

An OracleDatabase object represents an Oracle Database instance.

Class Inheritance

System.Object

Oracle.DataAccess.Client.OracleDatabase

Declaration

```
// C#
public sealed class OracleDatabase : IDisposable
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

namespace Startup
{
    class Test
    {
        static void Main()
        {
            OracleConnection con = null;
            OracleDatabase db = null;
            string constring = "dba privilege=sysdba;user id=scott;password=tiger;data
```

```
source=oracle";

    try
    {
        // Open a connection to see if the DB is up
        con = new OracleConnection(constring);
        con.Open();

        Console.WriteLine("The Oracle database is already up.");
    }
    catch (OracleException ex)
    {
        // If the database is down, start up the DB
        if (ex.Number == 1034)
        {
            Console.WriteLine("The Oracle database is down.");

            // Create an instance of an OracleDatabase object
            db = new OracleDatabase(constring);

            // Start up the database
            db.Startup();

            Console.WriteLine("The Oracle database is now up.");

            // Executing Startup() is the same as the following:
            // db.Startup(OracleDBStartupMode.NoRestriction, null, true);
            // which is also the same as:
            // db.Startup(OracleDBStartupMode.NoRestriction, null, false);
            // db.ExecuteNonQuery("ALTER DATABASE MOUNT");
            // db.ExecuteNonQuery("ALTER DATABASE OPEN");

            // Dispose the OracleDatabase object
            db.Dispose();
        }
        else
        {
            Console.WriteLine("Error: " + ex.Message);
        }
    }
    finally
    {
        // Dispose the OracleConnection object
        con.Dispose();
    }
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Members](#)
- [OracleDatabase Constructors](#)
- [OracleDatabase Properties](#)
- [OracleDatabase Public Methods](#)

OracleDatabase Members

OracleDatabase members are listed in the following tables.

OracleDatabase Constructors

The OracleDatabase constructor is listed in [Table 6-70](#).

Table 6-70 OracleDatabase Constructors

Constructor	Description
OracleDatabase Constructors	Instantiates a new instance of OracleDatabase class

OracleDatabase Properties

The OracleDatabase properties are listed in [Table 6-71](#).

Table 6-71 OracleDatabase Properties

Property	Description
ServerVersion	Specifies the database version number of the Oracle Database instance to which the connection is made

OracleDatabase Public Methods

The OracleDatabase public methods are listed in [Table 6-72](#).

Table 6-72 OracleDatabase Public Methods

Public Method	Description
Dispose	Releases any resources or memory allocated by the object.
ExecuteNonQuery	Executes the supplied non-SELECT statement against the database
Shutdown	Shuts down the database (Overloaded)
Startup	Starts up the database (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)

OracleDatabase Constructors

The `OracleDatabase` constructors instantiate a new instance of the `OracleDatabase` class.

Overload List

- [OracleDatabase Constructor\(string\)](#)
The `OracleDatabase` constructor instantiates a new instance of the `OracleDatabase` class using the supplied connection string.
- [OracleDatabase Constructor\(string, OracleCredential\)](#)
The `OracleDatabase` constructor instantiates a new instance of the `OracleDatabase` class using the supplied connection string and `OracleCredential` object .

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

OracleDatabase Constructor(string)

The `OracleDatabase` constructor instantiates a new instance of the `OracleDatabase` class using the supplied connection string.

Declaration

```
// C#  
public OracleDatabase(string connectionString);
```

Parameters

- *connectionString*
The connection information used to connect to the Oracle Database instance.

Remarks

The `connectionString` follows the same format used by the `OracleConnection` object. However, the `OracleDatabase` constructor accepts only the `user id`, `password`, `data source`, and `dba privilege` connection string attributes. All other attribute values are ignored. The supplied `connectionString` must contain the `dba privilege` connection string attribute that is set to either `SYSDBA` or `SYSOPER`.

The `OracleDatabase` object creates a connection upon construction and remains connected throughout its lifetime. The connection is destroyed when the `OracleDatabase` object is disposed. This connection is not pooled to be used by another `OracleDatabase` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

OracleDatabase Constructor(string, OracleCredential)

The `OracleDatabase` constructor instantiates a new instance of the `OracleDatabase` class using the supplied connection string and `OracleCredential` object.

Declaration

```
// C#  
public OracleDatabase(string connectionString, OracleCredential orclCredential)
```

Parameters

- `connectionString`
connection string that does not contain any of `user id`, `password`, `DBA Privilege`, `proxy user id`, nor `proxy password`.
- `orclCredential`
`OracleCredential` object containing user credentials. If this parameter is passed as null then `OracleConnection`'s behavior will be same as `OracleConnection` with normal connection string.

Exceptions

`InvalidOperationException` is raised when non-null `OracleCredential` object is used with a connection string containing any of `user id`, `password`, `DBA Privilege`, `proxy user id`, or `proxy password`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

OracleDatabase Properties

The `OracleDatabase` properties are listed in [Table 6-73](#).

Table 6-73 OracleDatabase Properties

Property	Description
ServerVersion	Specifies the database version number of the Oracle Database instance to which the connection is made

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

ServerVersion

This property returns the database version number of the Oracle Database instance to which the connection is made.

Declaration

```
Public string ServerVersion {get;}
```

Property value

Returns the database version of the Oracle Database instance.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

OracleDatabase Public Methods

The OracleDatabase public methods are listed in [Table 6-74](#).

Table 6-74 OracleDatabase Public Methods

Public Method	Description
Dispose	Releases any resources or memory allocated by the object.
ExecuteNonQuery	Executes the supplied non-SELECT statement against the database
Shutdown	Shuts down the database (Overloaded)
Startup	Starts up the database (Overloaded)

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

ExecuteNonQuery

This method executes the supplied non-`SELECT` statement against the database.

Declaration

```
// C#  
public void ExecuteNonQuery(string sql);
```

Exceptions

`OracleException` - The command execution has failed.

Remarks

This method is meant for execution of DDL statements such as `ALTER DATABASE` statements to `OPEN` and `MOUNT` the database, for example. This method should not be used to execute `SQL SELECT` statements. This method does not support any parameter binding.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

Shutdown

Shutdown methods shut down a database instance.

Overload List

- [Shutdown\(\)](#)
This method shuts down the database.
- [Shutdown\(OracleDBShutdownMode, bool\)](#)
This method shuts down the database using the specified mode.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#)

Shutdown()

This method shuts down the database.

Declaration

```
// C#  
public void Shutdown();
```

Exceptions

`OracleException` - The database shutdown request has failed.

Remarks

This method shuts down a database instance in the `OracleDBShutdownMode.Default` mode. New connections are refused, and the method waits for the existing connections to end.

 **Note:**

As the shutdown is effected using the `OracleDBShutdownMode.Default` mode, the shutdown request may remain pending if there are open connections other than the connection created by the `OracleDatabase` object.

After the connections have closed, the method closes the database, dismantles the database, and shuts down the instance using the `OracleDBShutdownMode.Final` mode.

This method does not throw exceptions for cases where the database has been already closed, dismantled, or shutdown appropriately. If other errors are encountered, then an exception is thrown.

Invoking this method against an Oracle Real Application Clusters (Oracle RAC) database shuts down only that database instance to which the `OracleDatabase` object is connected.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#)

Shutdown(OracleDBShutdownMode, bool)

This method shuts down the database instance using the specified mode.

Declaration

```
//C#  
public void Shutdown(OracleDBShutdownMode shutdownMode, bool  
bCloseDismountAndFinalize);
```

Parameters

- *shutdownMode*
A `OracleDBShutdownMode` enumeration value.
- *bCloseDismountAndFinalize*
A boolean signifying whether the database is to be closed, dismounted, and finalized.

Exceptions

`OracleException` - The database shutdown request has failed.

Remarks

This method shuts down a database instance in the specified mode. If the *bCloseDismountAndFinalize* parameter is `true`, then the method also closes the database, dismounts the database, and shuts down the instance using the `OracleDBShutdownMode.Final` mode.

If the *bCloseDismountAndFinalize* parameter is `true`, then this method does not throw exceptions for cases where the database has been already closed, dismounted, or shutdown appropriately. If other errors are encountered, then an exception is thrown.

If the *bCloseDismountAndFinalize* parameter is `false`, then the application needs to explicitly close and dismount the database. The application can then reinvoke the method using the `OracleDBShutdownMode.Final` mode to properly shut down the database. For example, if `db` is an instance of the `OracleDatabase` class, then the application invokes the following:

1. `db.Shutdown(OracleDBShutdownMode.Default, false);`
2. `db.ExecuteNonQuery("ALTER DATABASE CLOSE NORMAL");`
3. `db.ExecuteNonQuery("ALTER DATABASE DISMOUNT");`

```
4. db.Shutdown(OracleDBShutdownMode.Final);
```

 **Note:**

- The `OracleDBShutdownMode.Final` enumeration value should not be used as the `shutdownMode` for the initial method invocation. The `OracleDBShutdownMode.Final` mode should be used only if the database is already closed and dismounted. Otherwise, the method might wait indefinitely.
- If the specified `shutdownMode` is `OracleDBShutdownMode.Final`, then the value of the `bCloseDismountAndFinalize` input parameter is ignored, as the database should have been closed and dismounted already.

If the specified `shutdownMode` is `OracleDBShutdownMode.Abort`, then the value of the `bCloseDismountAndFinalize` input parameter is ignored, as the `Abort` mode requires the database to be closed, dismounted, and finalized.

Invoking this method against an Oracle Real Application Clusters (Oracle RAC) database shuts down only that database instance to which the `OracleDatabase` object is connected.

Example

```
using System;
using Oracle.DataAccess.Client;

namespace Shutdown
{
    class Test
    {
        static void Main()
        {
            OracleConnection con = null;
            OracleDatabase db = null;
            string constring = "user id=scott;password=tiger;data source=oracle;" +
                "pooling=false;dba privilege=sysdba";

            try
            {
                // Open a connection to see if the DB is up;
                con = new OracleConnection(constring);
                con.Open();

                Console.WriteLine("The Oracle database is currently up.");

                // If open succeeds, we know that the database is up.
                // We have to dispose the connection so that we can
                // shutdown the database.
                con.Dispose();

                // Shutdown the database
                db = new OracleDatabase(constring);
                db.Shutdown();

                Console.WriteLine("The Oracle database is shut down.");
            }
        }
    }
}
```



```
// Executing Shutdown() above is the same as the following:  
// db.Shutdown(OracleDBShutdownMode.Default, false);  
// db.ExecuteNonQuery("ALTER DATABASE CLOSE NORMAL");  
// db.ExecuteNonQuery("ALTER DATABASE DISMOUNT");  
// db.Shutdown(OracleDBShutdownMode.Final);  
  
// Dispose the OracleDatabase object  
db.Dispose();  
}  
catch (OracleException ex)  
{  
    Console.WriteLine("An error has occurred: {0}", ex.Message);  
}  
}  
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#)

Startup

Startup methods enable a user with database administrator privileges to start a database instance.

Overload List

- [Startup\(\)](#)
This method starts a database instance using the server-side parameter file.
- [Startup\(OracleDBStartupMode, string, bool\)](#)
This method starts a database instance using the client-side parameter file.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#)

Startup()

This method starts up the database.

Declaration

```
// C#  
public void Startup();
```

Exceptions

`OracleException` - The database startup request has failed.

Remarks

This method starts a database instance in the `OracleDbStartupMode.Normal` mode using the server-side parameter file (`spfile`). After the database is successfully started, this method also executes the `ALTER DATABASE MOUNT` and `ALTER DATABASE OPEN` statements.

This method does not throw exceptions for cases where the database is already mounted, opened, or started appropriately. If other errors are encountered, then an exception is thrown.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#)

Startup(OracleDBStartupMode, string, bool)

This method starts up the database using the specified startup mode.

Declaration

```
// C#  
public void Startup(OracleDbStartupMode startupMode, string pfile, bool  
bMountAndOpen);
```

Parameters

- `startupMode`
An `OracleDBStartupMode` enumeration value.
- `pfile`
The location and name of the client-side parameter file. For example, "c:\\admin\\init.ora".

The name of the parameter file varies depending on the operating system. For example, it can be in mixed case or lowercase, or it can have a logical name or a variation of the name `init.ora`. The default location is usually `ORACLE_HOME/dbs` or `ORACLE_HOME\database`.

- `bMountAndOpen`

A `true/false` value signifying whether the database is to be mounted and opened.

Exceptions

`OracleException` - The database startup request has failed.

Remarks

This method starts a database instance in the specified mode using the specified client-side parameter file. After the database is successfully started, and if `bMountAndOpen` input parameter is `true`, this method also executes the `ALTER DATABASE MOUNT` and `ALTER DATABASE OPEN` statements.

If `bMountAndOpen` is `true`, then this method does not throw an exception for cases where the database is already mounted, opened, or started appropriately. If other errors are encountered, then an exception is thrown.

If `bMountAndOpen` is `false`, then the database must be mounted and opened explicitly by the application. For example, if `db` is an instance of the `OracleDatabase` class, then the application invokes the following:

1. `db.Startup(OracleDBStartupMode.NoRestriction, null, false);`
2. `db.ExecuteNonQuery("ALTER DATABASE MOUNT");`
3. `db.ExecuteNonQuery("ALTER DATABASE OPEN");`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#)

OracleDataReader Class

An `OracleDataReader` object represents a forward-only, read-only, in-memory result set.

Unlike the `DataSet`, the `OracleDataReader` object stays connected and fetches one row at a time.

The following section contain related information:

- ["Obtaining LONG and LONG RAW Data"](#).

- ["Obtaining Data from an OracleDataReader Object"](#).

Class Inheritance

System.Object

System.MarshalByRefObject

System.Data.Common.DataReader

System.Data.Common.DbDataReader

Oracle.DataAccess.Client.OracleDataReader

Declaration

```
// C#
public sealed class OracleDataReader : DbDataReader, IEnumerable,
    IDataReader, IDisposable, IDataRecord
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An `OracleDataReader` instance is constructed by a call to the `ExecuteReader` method of the `OracleCommand` object. The only properties that can be accessed after the `DataReader` is closed or has been disposed, are `IsClosed` and `RecordsAffected`.

To minimize the number of open database cursors, `OracleDataReader` objects should be explicitly disposed.

Example

The following `OracleDataReader` example retrieves the data from the `EMP` table:

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
```

```
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleDataReaderSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        string cmdstr = "SELECT * FROM EMPINFO";
        OracleConnection connection = new OracleConnection(constr);
        OracleCommand cmd = new OracleCommand(cmdstr, con);

        OracleDataReader reader = cmd.ExecuteReader();

        // Declare the variables to retrieve the data in EmpInfo
        short empNo;
        string empName;
        DateTime hireDate;
        double salary;
        string jobDesc;
        byte[] byteCodes = new byte[10];

        // Read the next row until end of row
        while (reader.Read())
        {
            empNo = reader.GetInt16(0);
            Console.WriteLine("Employee number: " + empNo);
            empName = reader.GetString(1);
            Console.WriteLine("Employee name: " + empName);

            // The following columns can have NULL value, so it
            // is important to call IsDBNull before getting the column data
            if (!reader.IsDBNull(2))
            {
                hireDate = reader.GetDateTime(2);
                Console.WriteLine("Hire date: " + hireDate);
            }

            if (!reader.IsDBNull(3))
            {
                salary = reader.GetDouble(3);
                Console.WriteLine("Salary: " + salary);
            }
        }
    }
}
```

```
if (!reader.IsDBNull(4))
{
    jobDesc = reader.GetString(4);
    Console.WriteLine("Job Description: " + jobDesc);
}

if (!reader.IsDBNull(5))
{
    long len = reader.GetBytes(5, 0, byteCodes, 0, 10);

    Console.Write("Byte codes: ");
    for (int i = 0; i < len; i++)
        Console.Write(byteCodes[i].ToString("x"));

    Console.WriteLine();
}

Console.WriteLine();
}

// Clean up
reader.Dispose();
con.Dispose();
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Members](#)
- [OracleDataReader Static Methods](#)
- [OracleDataReader Properties](#)
- [OracleDataReader Public Methods](#)

OracleDataReader Members

OracleDataReader members are listed in the following tables.

OracleDataReader Static Methods

The OracleDataReader static method is listed in [Table 6-75](#).

Table 6-75 OracleDataReader Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleDataReader Properties

OracleDataReader properties are listed in [Table 6-76](#).

Table 6-76 OracleDataReader Properties

Property	Description
Depth	Gets a value indicating the depth of nesting for the current row
FetchSize	Specifies the size of OracleDataReader's internal cache
FieldCount	Gets the number of columns in the result set
HasRows	Indicates whether the OracleDataReader has one or more rows
HiddenFieldCount	Gets the number of fields in the OracleDataReader that are hidden
IsClosed	Indicates whether or not the data reader is closed
Item	Gets the value of the column (Overloaded)
InitialLOBFetchSize	Specifies the amount that the OracleDataReader initially fetches for LOB columns
InitialLONGFetchSize	Specifies the amount that the OracleDataReader initially fetches for LONG and LONG RAW columns
RecordsAffected	Gets the number of rows changed, inserted, or deleted by execution of the SQL statement
RowSize	Gets the amount of memory the internal cache of the OracleDataReader needs to store one row of data.
UseEdmMapping	Indicates whether or not the OracleDataReader utilizes the Entity Data Model mapping configuration when returning values
VisibleFieldCount	Gets the number of fields in the OracleDataReader that are not hidden

OracleDataReader Public Methods

OracleDataReader public methods are listed in [Table 6-77](#).

Table 6-77 OracleDataReader Public Methods

Public Method	Description
Close	Closes the OracleDataReader
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
Dispose	Releases any resources or memory allocated by the object
Equals	Inherited from <code>System.Object</code> (Overloaded)
GetBoolean	Returns the <code>bool</code> value of the specified numeric column
GetByte	Returns the <code>byte</code> value of the specified column
GetBytes	Populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column
GetChar	<i>Not Supported</i>

Table 6-77 (Cont.) OracleDataReader Public Methods

Public Method	Description
GetChars	Populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column
GetData	<i>Not Supported</i>
GetDataTypeName	Returns the ODP.NET type name of the specified column
GetDateTime	Returns the <code>DateTime</code> value of the specified column
GetDateTimeOffset	Returns the <code>DateTimeOffset</code> value of the specified column
GetDecimal	Returns the decimal value of the specified NUMBER column
GetDouble	Returns the double value of the specified NUMBER column or BINARY_DOUBLE column
GetEnumerator	Returns an <code>IEnumerator</code> that can be used to iterate through the collection
GetFieldType	Returns the <code>Type</code> of the specified column
GetFloat	Returns the float value of the specified NUMBER column or BINARY_FLOAT column
GetGuid	Returns the <code>Guid</code> value of the specified binary data column
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
GetInt16	Returns the <code>Int16</code> value of the specified NUMBER column
GetInt32	Returns the <code>Int32</code> value of the specified NUMBER column
GetInt64	Returns the <code>Int64</code> value of the specified NUMBER column
<code>GetLifetimeService</code>	Inherited by <code>System.MarshalByRefObject</code>
GetName	Returns the name of the specified column
GetOracleBFile	Returns an <code>OracleBFile</code> object of the specified BFILE column
GetOracleBinary	Returns an <code>OracleBinary</code> structure of the specified column
GetOracleBlob	Returns an <code>OracleBlob</code> object of the specified BLOB column
GetOracleBlobForUpdate	Returns an updatable <code>OracleBlob</code> object of the specified BLOB column <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetOracleClob	Returns an <code>OracleClob</code> object of the specified CLOB column
GetOracleClobForUpdate	Returns an updatable <code>OracleClob</code> object of the specified CLOB column <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetOracleDate	Returns an <code>OracleDate</code> structure of the specified DATE column

Table 6-77 (Cont.) OracleDataReader Public Methods

Public Method	Description
GetOracleDecimal	Returns an <code>OracleDecimal</code> structure of the specified NUMBER column
GetOracleIntervalDS	Returns an <code>OracleIntervalDS</code> structure of the specified INTERVAL DAY TO SECOND column
GetOracleIntervalYM	Returns an <code>OracleIntervalYM</code> structure of the specified INTERVAL YEAR TO MONTH column
GetOracleRef	Returns an <code>OracleRef</code> object of the specified REF column <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetOracleString	Returns an <code>OracleString</code> structure of the specified column
GetOracleTimeStamp	Returns an <code>OracleTimeStamp</code> structure of the Oracle TimeStamp column
GetOracleTimeStampLTZ	Returns an <code>OracleTimeStampLTZ</code> structure of the specified Oracle TimeStamp WITH LOCAL TIME ZONE column
GetOracleTimeStampTZ	Returns an <code>OracleTimeStampTZ</code> structure of the specified Oracle TimeStamp WITH TIME ZONE column
GetOracleXmlType	Returns an <code>OracleXmlType</code> object of the specified XMLType column
GetOracleValue	Returns the specified column value as a ODP.NET type
GetOracleValues	Gets all the column values as ODP.NET types
GetOrdinal	Returns the 0-based ordinal (or index) of the specified column name
GetProviderSpecificFieldType	Returns the provider-specific type of the specified column
GetProviderSpecificValue	Returns an object that represents the underlying provider-specific value of the specified ordinal
GetProviderSpecificValues	Returns an array of objects that represent the underlying provider-specific values
GetSchemaTable	Returns a <code>DataTable</code> that describes the column metadata of the <code>OracleDataReader</code>
GetString	Returns the string value of the specified column
GetTimeSpan	Returns the <code>TimeSpan</code> value of the specified INTERVAL DAY TO SECOND column
<code>GetType</code>	Inherited from <code>System.Object</code> class
GetValue	Returns the column value as a .NET type
GetValues	Gets all the column values as .NET types
GetXmlReader	Returns the value of an XMLType column as an instance of an .NET <code>XmlTextReader</code>
IsDBNull	Indicates whether or not the column value is null

Table 6-77 (Cont.) OracleDataReader Public Methods

Public Method	Description
NextResult	Advances the data reader to the next result set when reading the results
Read	Reads the next row in the result set
ToString	Inherited from <code>System.Object</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)

OracleDataReader Static Methods

The `OracleDataReader` static method is listed in [Table 6-78](#).

Table 6-78 OracleDataReader Static Method

Method	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

OracleDataReader Properties

`OracleDataReader` properties are listed in [Table 6-79](#).

Table 6-79 OracleDataReader Properties

Property	Description
Depth	Gets a value indicating the depth of nesting for the current row
FetchSize	Specifies the size of <code>OracleDataReader</code> 's internal cache

Table 6-79 (Cont.) OracleDataReader Properties

Property	Description
FieldCount	Gets the number of columns in the result set
HasRows	Indicates whether the <code>OracleDataReader</code> has one or more rows
HiddenFieldCount	Gets the number of fields in the <code>OracleDataReader</code> that are hidden
IsClosed	Indicates whether or not the data reader is closed
Item	Gets the value of the column (Overloaded)
InitialLOBFetchSize	Specifies the amount that the <code>OracleDataReader</code> initially fetches for LOB columns
InitialLONGFetchSize	Specifies the amount that the <code>OracleDataReader</code> initially fetches for LONG and LONG RAW columns
RecordsAffected	Gets the number of rows changed, inserted, or deleted by execution of the SQL statement
RowSize	Gets the amount of memory the internal cache of the <code>OracleDataReader</code> needs to store one row of data
UseEdmMapping	Indicates whether or not the <code>OracleDataReader</code> utilizes the Entity Data Model mapping configuration when returning values
VisibleFieldCount	Gets the number of fields in the <code>OracleDataReader</code> that are not hidden

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Depth

This property gets a value indicating the depth of nesting for the current row.

Declaration

```
// C#
public override int Depth {get;}
```

Property Value

The depth of nesting for the current row.

Implements

IDataReader

Exceptions

InvalidOperationException - The reader is closed.

Remarks

Default = 0

This property always returns zero because Oracle does not support nesting.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

FetchSize

This property specifies the size of `OracleDataReader`'s internal cache.

Declaration

```
// C#  
public long FetchSize {get; set;}
```

Property Value

A `long` that specifies the amount of memory (in bytes) that the `OracleDataReader` uses for its internal cache.

Exceptions

ArgumentException - The `FetchSize` value specified is invalid.

Remarks

Default = The `OracleCommand`'s `FetchSize` property value.

The `FetchSize` property is inherited by the `OracleDataReader` that is created by a command execution returning a result set. The `FetchSize` property on the `OracleDataReader` object determines the amount of data fetched into its internal cache for each database round-trip.

The `RowSize` and `FetchSize` properties handle UDT and `XMLType` data differently than other scalar data types. Because only a reference to the UDT and `XMLType` data is stored in the ODP.NET's internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and `XMLType` data. Thus, applications can inadvertently fetch a large number of

UDT or `XMLType` instances from the database in a single database round-trip. This is because the actual size of UDT and `XMLType` data does not count against the `FetchSize`, and it would require numerous UDT and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of UDT and `XMLType` instances that are to be fetched, rather than the amount of the actual UDT and `XMLType` data to be fetched.

NOTE: For LOB and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- OracleDataReader ["RowSize"](#)
- OracleCommand ["ExecuteReader\(\)"](#)
- OracleCommand ["RowSize"](#)

FieldCount

This property returns the number of columns in the result set.

Declaration

```
// C#  
public override int FieldCount {get;}
```

Property Value

The number of columns in the result set if one exists, otherwise 0.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

Default = 0

This property has a value of 0 for queries that do not return result sets.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

HasRows

This property indicates whether the `OracleDataReader` has one or more rows.

Declaration

```
// C#  
public override bool HasRows {get;}
```

Return Value

bool

Remarks

`HasRows` indicates whether or not the `OracleDataReader` has any rows.

The value of `HasRows` does not change based on the row position. For example, even if the application has read all the rows from the result set and the next `Read` method invocation will return false, the `HasRows` property still returns true since the result set was not empty to begin with.

Rows are fetched to determine the emptiness of the `OracleDataReader` when `HasRows` property is accessed for the first time after the creation of the `OracleDataReader` object.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class HasRowsSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = new OracleCommand(  
            "select * from emp where empno = 9999", con);  
  
        OracleDataReader reader = cmd.ExecuteReader();  
  
        if (!reader.HasRows)  
            Console.WriteLine("The result set is empty.");  
    }  
}
```

```
else
    Console.WriteLine("The result set is not empty.");
con.Dispose();
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework feature

HiddenFieldCount

This property gets the number of fields in the `OracleDataReader` that are hidden.

Declaration

```
// C#
public int HiddenFieldcount { get; }
```

Property Value

The number of fields in the `OracleDataReader` that are hidden.

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

`OracleDataReader.FieldCount` and `OracleDataReader.VisibleFieldCount` return the visible field count.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["VisibleFieldCount"](#)
- ["FieldCount "](#)

IsClosed

This property indicates whether or not the data reader is closed.

Declaration

```
// C#  
public override bool IsClosed {get;}
```

Property Value

If the `OracleDataReader` is in a closed state, returns `true`; otherwise, returns `false`.

Implements

`IDataReader`

Remarks

Default = `true`

`IsClosed` and `RecordsAffected` are the only two properties that are accessible after the `OracleDataReader` is closed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Item

This property gets the value of the column in .NET data type.

Overload List:

- [Item \[index\]](#)
This property gets the .NET `Value` of the column specified by the column index.
- [Item \[string\]](#)
This property gets the .NET `Value` of the column specified by the column name.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Item [index]

This property gets the .NET `Value` of the column specified by the column index.

Declaration

```
// C#  
public override object this[int index] {get;}
```

Parameters

- *index*
The zero-based index of the column.

Property Value

The .NET value of the specified column.

Implements

`IDataRecord`

Remarks

Default = Not Applicable

In C#, this property is the indexer for this class.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Item [string]

This property gets the .NET `Value` of the column specified by the column name.

Declaration

```
// C#  
public override object this[string columnName] {get;}
```

Parameters

- *columnName*
The name of the column.

Property Value

The .NET Value of the specified column.

Implements

IDataRecord

Remarks

Default = Not Applicable

A case-sensitive search is made to locate the specified column by its name. If this fails, then a case-insensitive search is made.

In C#, this property is the indexer for this class.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

InitialLOBFetchSize

This property specifies the amount that the `OracleDataReader` initially fetches for LOB columns.

Declaration

```
// C#  
public int InitialLOBFetchSize {get;}
```

Property Value

The size of the chunk to retrieve.

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

The maximum value supported for `InitialLOBFetchSize` is 2 GB.

Default is the `OracleCommand.InitialLOBFetchSize`, from which this value is inherited.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["InitialLOBFetchSize"](#) for further information on `OracleCommand.InitialLOBFetchSize`
- ["Obtaining LOB Data"](#)

InitialLONGFetchSize

This property specifies the amount that the `OracleDataReader` initially fetches for `LONG` and `LONG RAW` columns.

Declaration

```
// C#  
public long InitialLONGFetchSize {get;}
```

Property Value

The size of the chunk to retrieve. The default is 0.

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

The maximum value supported for `InitialLONGFetchSize` is 32767. If this property is set to a higher value, the provider resets it to 32767.

Default is `OracleCommand.InitialLONGFetchSize`, from which this value is inherited.

This property is read-only for the `OracleDataReader`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["InitialLONGFetchSize"](#) for further information on `OracleCommand.InitialLONGFetchSize`
- ["Obtaining LONG and LONG RAW Data"](#)

RecordsAffected

This property gets the number of rows changed, inserted, or deleted by execution of the SQL statement.

Declaration

```
// C#  
public int RecordsAffected {get;}
```

Property Value

The number of rows affected by execution of the SQL statement.

Implements

`IDataReader`

Remarks

Default = 0

The value of -1 is returned for `SELECT` statements.

`IsClosed` and `RecordsAffected` are the only two properties that are accessible after the `OracleDataReader` is closed.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

RowSize

This property gets the amount of memory the internal cache of the `OracleDataReader` needs to store one row of data.

Declaration

```
// C#  
public long RowSize {get;}
```

Property Value

A long that indicates the amount of memory (in bytes) that an `OracleDataReader` needs to store one row of data for the executed query.

Remarks

The `RowSize` property is set to a nonzero value when the `OracleDataReader` object is created. This property can be used at design time or dynamically during runtime, to set the `FetchSize` property, based on the number of rows. For example, to enable the `OracleDataReader` object to fetch *N* rows for each database round-trip, the `OracleDataReader FetchSize` property can be set dynamically to `RowSize * N`. Note that for the `FetchSize` property to take effect appropriately, it must be set before the first invocation of `OracleDataReader.Read()` for the particular result set.

ODP.NET now supports values up to 32K for `VARCHAR2`, `NVARCHAR2` or `RAW` type columns in its calculation of `RowSize` value



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["FetchSize "](#)

UseEdmMapping

This read-only property indicates whether or not the `OracleDataReader` utilizes the Entity Data Model mapping configuration when returning values.

Declaration

```
// C#  
public bool UseEdmMapping {get;}
```

Property Value

A boolean that indicates whether the `OracleDataReader` uses the Entity Data Model mapping configuration for returning values.

Remarks

Default is `false`.

The value is inherited from the `OracleCommand` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- [OracleCommand Class](#)

VisibleFieldCount

This property gets the number of fields in the `OracleDataReader` that are not hidden.

Declaration

```
// C#  
public override int VisibleFieldcount { get; }
```

Property Value

The number of fields that are not hidden.

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

If an application sets the `AddRowid` property on an `OracleCommand` object to `true`, then the application can access the `RowId` but it is not a visible field. If `RowId` is added in the select statement list, then it is a visible field. `OracleDataReader.VisibleFieldCount` and `OracleDataReader.FieldCount` always have the same value.

Example

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;  
  
class VisibleFieldCountSample  
{  
    static void Main(string[] args)  
    {  
        string constr = "User Id=scott; Password=tiger; Data Source=oracle";  
        DbProviderFactory factory =
```

```
        DbProviderFactories.GetFactory("Oracle.DataAccess.Client");

using (DbConnection conn = factory.CreateConnection())
{
    conn.ConnectionString = constr;
    try
    {
        conn.Open();
        OracleCommand cmd = (OracleCommand)factory.CreateCommand();
        cmd.Connection = (OracleConnection)conn;

        //to gain access to ROWIDs of the table
        cmd.AddRowid = true;
        cmd.CommandText = "select empno, ename from emp;";

        OracleDataReader reader = cmd.ExecuteReader();

        int visFC = reader.VisibleFieldCount; //Results in 2
        int hidFC = reader.HiddenFieldCount; // Results in 1

        Console.WriteLine("Visible field count: " + visFC);
        Console.WriteLine("Hidden field count: " + hidFC);

        reader.Dispose();
        cmd.Dispose();
    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.Message);
        Console.WriteLine(ex.StackTrace);
    }
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["VisibleFieldCount"](#)
- ["FieldCount "](#)

OracleDataReader Public Methods

OracleDataReader public methods are listed in [Table 6-80](#).

Table 6-80 OracleDataReader Public Methods

Public Method	Description
Close	Closes the <code>OracleDataReader</code>
<code>CreateObjRef</code>	Inherited from <code>System.MarshalByRefObject</code>
Dispose	Releases any resources or memory allocated by the object
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
GetBoolean	Returns the <code>bool</code> value of the specified numeric column
GetByte	Returns the byte value of the specified column
GetBytes	Populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column
GetChar	<i>Not Supported</i>
GetChars	Populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column
GetData	<i>Not Supported</i>
GetDataTypeName	Returns the ODP.NET type name of the specified column
GetDateTime	Returns the <code>DateTime</code> value of the specified column
GetDateTimeOffset	Returns the <code>DateTimeOffset</code> value of the specified column
GetDecimal	Returns the decimal value of the specified <code>NUMBER</code> column
GetDouble	Returns the <code>double</code> value of the specified <code>NUMBER</code> column or <code>BINARY_DOUBLE</code> column
GetEnumerator	Returns an <code>IEnumerator</code> that can be used to iterate through the collection
GetFieldType	Returns the <code>Type</code> of the specified column
GetFloat	Returns the <code>float</code> value of the specified <code>NUMBER</code> column or <code>BINARY_FLOAT</code> column
GetGuid	Returns the <code>Guid</code> value of the specified binary data column
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
GetInt16	Returns the <code>Int16</code> value of the specified <code>NUMBER</code> column
GetInt32	Returns the <code>Int32</code> value of the specified <code>NUMBER</code> column
GetInt64	Returns the <code>Int64</code> value of the specified <code>NUMBER</code> column
<code>GetLifetimeService</code>	Inherited by <code>System.MarshalByRefObject</code>
GetName	Returns the name of the specified column
GetOracleBFile	Returns an <code>OracleBFile</code> object of the specified <code>BFILE</code> column
GetOracleBinary	Returns an <code>OracleBinary</code> structure of the specified column
GetOracleBlob	Returns an <code>OracleBlob</code> object of the specified <code>BLOB</code> column

Table 6-80 (Cont.) OracleDataReader Public Methods

Public Method	Description
GetOracleBlobForUpdate	Returns an updatable OracleBlob object of the specified BLOB column <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetOracleClob	Returns an OracleClob object of the specified CLOB column
GetOracleClobForUpdate	Returns an updatable OracleClob object of the specified CLOB column <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetOracleDate	Returns an OracleDate structure of the specified DATE column
GetOracleDecimal	Returns an OracleDecimal structure of the specified NUMBER column
GetOracleIntervalDS	Returns an OracleIntervalDS structure of the specified INTERVAL DAY TO SECOND column
GetOracleIntervalYM	Returns an OracleIntervalYM structure of the specified INTERVAL YEAR TO MONTH column
GetOracleRef	Returns an OracleRef object of the specified REF column <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetOracleString	Returns an OracleString structure of the specified column
GetOracleTimeStamp	Returns an OracleTimeStamp structure of the Oracle TimeStamp column
GetOracleTimeStampLTZ	Returns an OracleTimeStampLTZ structure of the specified Oracle TimeStamp WITH LOCAL TIME ZONE column
GetOracleTimeStampTZ	Returns an OracleTimeStampTZ structure of the specified Oracle TimeStamp WITH TIME ZONE column
GetOracleXmlType	Returns an OracleXmlType object of the specified XMLType column
GetOracleValue	Returns the specified column value as a ODP.NET type
GetOracleValues	Gets all the column values as ODP.NET types
GetOrdinal	Returns the 0-based ordinal (or index) of the specified column name
GetProviderSpecificFieldType	Returns the provider-specific type of the specified column
GetProviderSpecificValue	Returns an object that represents the underlying provider-specific value of the specified ordinal
GetProviderSpecificValues	Returns an array of objects that represent the underlying provider-specific values
GetSchemaTable	Returns a DataTable that describes the column metadata of the OracleDataReader

Table 6-80 (Cont.) OracleDataReader Public Methods

Public Method	Description
GetString	Returns the string value of the specified column
GetTimeSpan	Returns the TimeSpan value of the specified INTERVAL DAY TO SECOND column
GetType	Inherited from System.Object class
GetValue	Returns the column value as a .NET type
GetValues	Gets all the column values as .NET types
GetXmlReader	Returns the value of an XMLType column as an instance of an .NET XmlTextReader
IsDBNull	Indicates whether or not the column value is null
NextResult	Advances the data reader to the next result set when reading the results
Read	Reads the next row in the result set
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Close

This method closes the OracleDataReader.

Declaration

```
// C#  
public override void Close();
```

Implements

IDataReader

Remarks

The Close method frees all resources associated with the OracleDataReader.

Example

The code example for the OracleDataReader class includes the Close method. See OracleDataReader Overview "[Example](#)".

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

The `Dispose` method also closes the `OracleDataReader`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetBoolean

This method returns the bool value of the specified numeric column.

Declaration

```
// C#  
public override bool GetBoolean(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The bool value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, Read() has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type.

Remarks

- This method can be called on any numeric database type column (NUMBER, BINARY_DOUBLE, BINARY_FLOAT, and FLOAT).
- FALSE is returned if column value is 0; TRUE otherwise.
- IsDBNull should be called to check for NULL values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetByte

This method returns the byte value of the specified column.

Declaration

```
// C#  
public override byte GetByte(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The value of the column as a byte.

Implements

IDataRecord

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetBytes

This method populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column.

Declaration

```
// C#  
public override long GetBytes(int index, long fieldOffset, byte[] buffer,  
    int bufferOffset, int length);
```

Parameters

- *index*
The zero-based column index.
- *fieldOffset*
The offset within the column from which reading begins (in bytes).
- *buffer*
The byte array that the data is read into.
- *bufferOffset*
The offset within the buffer to begin reading data into (in bytes).
- *length*
The maximum number of bytes to read (in bytes).

Return Value

The number of bytes read.

Implements

IDataRecord

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

This method returns the number of bytes read into the buffer. This may be less than the actual length of the field if the method has been called previously for the same column.

If a null reference is passed for buffer, the length of the field in bytes is returned.

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetChar

This method is not supported.

Declaration

```
// C#  
public override long GetChar(int index);
```

Parameters

- *index*
The zero based column index.

Implements

IDataRecord

Exceptions

`NotSupportedException` - This property is not supported.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetChars

This method populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column.

Declaration

```
// C#  
public override long GetChars(int index, long fieldOffset, char[] buffer,  
    int bufferOffset, int length);
```

Parameters

- *index*
The zero based column index.
- *fieldOffset*
The index within the column from which to begin reading (in characters).
- *buffer*
The character array that the data is read into.
- *bufferOffset*
The index within the buffer to begin reading data into (in characters).
- *length*
The maximum number of characters to read (in characters).

Return Value

The number of characters read.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

This method returns the number of characters read into the buffer. This may be less than the actual length of the field, if the method has been called previously for the same column.

If a null reference is passed for buffer, the length of the field in characters is returned.

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetData

This method is not supported

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDataTypeName

This method returns the ODP.NET type name of the specified column.

Declaration

```
// C#  
public override string GetDataTypeName(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The name of the ODP.NET type of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed.

IndexOutOfRangeException - The column index is invalid.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDateTime

This method returns the `DateTime` value of the specified column.

Declaration

```
// C#  
public override DateTime GetDateTime(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `DateTime` value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDateTimeOffset

This method returns the `DateTimeOffset` value of a `TIMESTAMP WITH TIME ZONE` column. `DateTimeOffset` represents a point in time. It is generally expressed as a date and time relative to Coordinated Universal Time (UTC).

Declaration

```
// C#  
public override DateTimeOffset GetDateTimeOffset(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `DateTimeOffset` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

- This method can be called only on a `TIMESTAMP WITH TIME ZONE` column.
- `IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDecimal

This method returns the decimal value of the specified `NUMBER` column.

Declaration

```
// C#  
public override decimal GetDecimal(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The decimal value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDouble

This method returns the `double` value of the specified `NUMBER` column or `BINARY_DOUBLE` column.

Declaration

```
// C#  
public override double GetDouble(int index);
```

Parameters

- `index`
The zero-based column index.

Return Value

The `double` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

`GetDouble` now supports retrieval of data from `BINARY_DOUBLE` columns.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetEnumerator

This method returns an `IEnumerator` that can be used to iterate through the collection (record set).

Declaration

```
// C#  
public override IEnumerator GetEnumerator();
```

Return Value

An `IEnumerator` that can be used to iterate through the collection (record set).

Exceptions

`InvalidOperationException` - The reader is closed.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetFieldType

This method returns the `type` of the specified column.

Declaration

```
// C#  
public override Type GetFieldType(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `type` of the default .NET type of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The reader is closed, or the specified column is a UDT but no registered custom type mapping exists for the UDT.

`IndexOutOfRangeException` - The column index is invalid.

Remarks

`GetFieldType` returns a type that corresponds to the value that the application obtains after invoking the `GetValue` accessor or `Item` property on the `OracleDataReader`. For

example, if the column is a string, this method returns a .NET Type object for a .NET string.

If the attribute is a UDT, this method may return either of the following:

- A .NET Type of the custom type if a custom type mapping exists for the Oracle object or collection.
- A .NET Type of string if the column is an Oracle REF.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetFloat

This method returns the `float` value of the specified `NUMBER` column or `BINARY_FLOAT` column.

Declaration

```
// C#  
public override float GetFloat(int index);
```

Parameters

- `index`
The zero-based column index.

Return Value

The `float` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

`GetFloat` now supports retrieval of data from `BINARY_FLOAT` columns.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetGuid

This method returns the `Guid` value of the specified binary data column. A GUID is a Globally Unique Identifier.

Declaration

```
// C#  
public override Guid GetGuid(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `Guid` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

`System.ArgumentException` - Byte array for GUID must be exactly 16 bytes long.

Remarks

- This method can be called on columns that contain binary data, such as `RAW` and `BLOB`.
- An exception will be thrown if the binary data of the column is not 16 bytes in length.
- `IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetInt16

This method returns the `Int16` value of the specified `NUMBER` column.

 **Note:**

`short` is equivalent to `Int16`.

Declaration

```
// C#  
public override short GetInt16(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `Int16` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetInt32

This method returns the `Int32` value of the specified `NUMBER` column.

 **Note:**

`int` is equivalent to `Int32`.

Declaration

```
// C#  
public override int GetInt32(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `Int32` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetInt64

This method returns the `Int64` value of the specified `NUMBER` column.

 **Note:**

`long` is equivalent to `Int64`.

Declaration

```
// C#  
public override long GetInt64(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `Int64` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetName

This method returns the name of the specified column.

Declaration

```
// C#  
public override string GetName(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The name of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed.

IndexOutOfRangeException - The column index is invalid.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBFile

This method returns an `OracleBFile` object of the specified `BFILE` column.

Declaration

```
// C#  
public OracleBFile GetOracleBFile(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleBFile` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBinary

This method returns an `OracleBinary` structure of the specified column.

Declaration

```
// C#  
public OracleBinary GetOracleBinary(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleBinary` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

`GetOracleBinary` is used on the following Oracle types:

- `BFILE`
- `BLOB`
- `LONG RAW`
- `RAW`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBlob

This method returns an `OracleBlob` object of the specified `BLOB` column.

Declaration

```
// C#  
public OracleBlob GetOracleBlob(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleBlob` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBlobForUpdate

`GetOracleBlobForUpdate` returns an updatable `OracleBlob` object of the specified BLOB column.

Overload List:

- [GetOracleBlobForUpdate\(int\)](#)
This method returns an updatable `OracleBlob` object of the specified BLOB column.
- [GetOracleBlobForUpdate\(int, int\)](#)
This method returns an updatable `OracleBlob` object of the specified BLOB column using a `WAIT` clause.

GetOracleBlobForUpdate(int)

This method returns an updatable `OracleBlob` object of the specified BLOB column.

Declaration

```
// C#  
public OracleBlob GetOracleBlobForUpdate(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

An updatable `OracleBlob` object.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

When the OracleCommand's `ExecuteReader()` method is invoked, all the data fetched by the OracleDataReader is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleBlobForUpdate()` method incurs a database round-trip to obtain a reference to the current BLOB data while also locking the row using the `FOR UPDATE` clause. This means that the OracleBlob obtained from `GetOracleBlob()` can have a different value than the OracleBlob obtained from `GetOracleBlobForUpdate()` since it is not obtained from the original snapshot.

The returned OracleBlob object can be used to safely update the BLOB because the BLOB column has been locked after a call to this method.

Invoking this method internally executes a `SELECT...FOR UPDATE` statement without a `WAIT` clause. Therefore, the statement can wait indefinitely until a lock is acquired for that row.

`IsDBNull` should be called to check for NULL values before calling this method.

Example

The following example gets the OracleBlob object for update from the reader, updates the OracleBlob object, and then commits the transaction.

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetOracleBlobForUpdateSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
```

```
OracleConnection con = new OracleConnection(constr);
con.Open();

// Get the ByteCodes for empno = 1
string cmdstr = "SELECT BYTECODES, EMPNO FROM EMPINFO where EMPNO = 1";
OracleCommand cmd = new OracleCommand(cmdstr, con);

// Since we are going to update the OracleBlob object, we will
//have to create a transaction
OracleTransaction txn = con.BeginTransaction();

// Get the reader
OracleDataReader reader = cmd.ExecuteReader();

// Declare the variables to retrieve the data in EmpInfo
OracleBlob byteCodesBlob;

// Read the first row
reader.Read();
if (!reader.IsDBNull(0))
{
    byteCodesBlob = reader.GetOracleBlobForUpdate(0);

    // Close the reader
    reader.Close();

    // Update the ByteCodes object
    byte[] addedBytes = new byte[2] {0, 0};
    byteCodesBlob.Append(addedBytes, 0, addedBytes.Length);

    // Now commit the transaction
    txn.Commit();
    Console.WriteLine("Blob Column successfully updated");
}
else
    reader.Dispose();

// Close the connection
con.Dispose();
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#)

GetOracleBlobForUpdate(int, int)

This method returns an updatable `OracleBlob` object of the specified BLOB column using a `WAIT` clause.

Declaration

```
// C#  
public OracleBlob GetOracleBlobForUpdate(int index, int wait);
```

Parameters

- *index*
The zero-based column index.
- *wait*
The number of seconds the method waits to acquire a lock.

Return Value

An updatable `OracleBlob` object.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleBlobForUpdate()` method incurs a database round-trip to obtain a reference to the current BLOB data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleBlob` obtained from `GetOracleBlob()` can have a different value than the `OracleBlob` obtained from `GetOracleBlobForUpdate()` since it is not obtained from the original snapshot.

`IsDBNull` should be called to check for `NULL` values before calling this method.

The returned `OracleBlob` object can be used to safely update the BLOB because the BLOB column has been locked after a call to this method.

Invoking this method internally executes a `SELECT . . FOR UPDATE` statement which locks the row.

Different `WAIT` clauses are appended to the statement, depending on the *wait* value. If the *wait* value is:

- 0
"NOWAIT" is appended at the end of a `SELECT . . FOR UPDATE` statement. The statement executes immediately whether the lock is acquired or not. If the lock is not acquired, an exception is thrown.
- *n*

"WAIT *n*" is appended at the end of a `SELECT...FOR UPDATE` statement. The statement executes as soon as the lock is acquired. However, if the lock cannot be acquired by *n* seconds, this method call throws an exception.

The `WAIT n` feature is only available for Oracle9i or later. For any version lower than Oracle9i, *n* is implicitly treated as -1 and nothing is appended at the end of a `SELECT...FOR UPDATE` statement.

- -1

Nothing is appended at the end of the `SELECT...FOR UPDATE`. The statement execution waits indefinitely until a lock can be acquired.

Example

The `GetOracleBlobForUpdate` methods are comparable. See "Example" for a code example demonstrating usage.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#)

GetOracleClob

This method returns an `OracleClob` object of the specified CLOB column.

Declaration

```
// C#  
public OracleClob GetOracleClob(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleClob` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#)

GetOracleClobForUpdate

`GetOracleClobForUpdate` returns an updatable `OracleClob` object of the specified CLOB column.

Overload List:

- [GetOracleClobForUpdate\(int\)](#)
This method returns an updatable `OracleClob` object of the specified CLOB column.
- [GetOracleClobForUpdate\(int, int\)](#)
This method returns an updatable `OracleClob` object of the specified CLOB column using a `WAIT` clause.

GetOracleClobForUpdate(int)

This method returns an updatable `OracleClob` object of the specified CLOB column.

Declaration

```
// C#  
public OracleClob GetOracleClobForUpdate(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

An updatable `OracleClob`.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

When the OracleCommand's ExecuteReader() method is invoked, all the data fetched by the OracleDataReader is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the GetOracleClobForUpdate() method incurs a database round-trip to obtain a reference to the current CLOB data while also locking the row using the FOR UPDATE clause. This means that the OracleClob obtained from GetOracleClob() can have a different value than the OracleClob obtained from GetOracleClobForUpdate() since it is not obtained from the original snapshot.

The returned OracleClob object can be used to safely update the CLOB because the CLOB column is locked after a call to this method.

Invoking this method internally executes a SELECT . . FOR UPDATE statement without a WAIT clause. Therefore, the statement can wait indefinitely until a lock is acquired for that row.

IsDBNull should be called to check for NULL values before calling this method.

Example

The following example gets the OracleClob object for update from the reader, updates the OracleClob object, and then commits the transaction.

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetOracleClobForUpdateSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();
    }
}
```

```
// Get the job description for empno = 1
string cmdStr = "SELECT JOBDESCRIPTION, EMPNO FROM EMPINFO where EMPNO = 1";
OracleCommand cmd = new OracleCommand(cmdStr, con);

// Since we are going to update the OracleClob object, we will
// have to create a transaction
OracleTransaction txn = con.BeginTransaction();

// Get the reader
OracleDataReader reader = cmd.ExecuteReader();

// Declare the variables to retrieve the data in EmpInfo
OracleClob jobDescClob;

// Read the first row
reader.Read();

if (!reader.IsDBNull(0))
{
    jobDescClob = reader.GetOracleClobForUpdate(0);

    // Close the reader
    reader.Close();

    // Update the job description Clob object
    char[] jobDesc = "-SALES".ToCharArray();
    jobDescClob.Append(jobDesc, 0, jobDesc.Length);

    // Now commit the transaction
    txn.Commit();
    Console.WriteLine("Clob Column successfully updated");
}
else
    reader.Close();

// Close the connection
con.Close();
}
}
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#)

GetOracleClobForUpdate(int, int)

This method returns an updatable `OracleClob` object of the specified CLOB column using a `WAIT` clause.

Declaration

```
// C#  
public OracleClob GetOracleClobForUpdate(int index, int wait);
```

Parameters

- *index*
The zero-based column index.
- *wait*
The number of seconds the method waits to acquire a lock.

Return Value

An updatable `OracleClob`.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleClobForUpdate()` method incurs a database round-trip to obtain a reference to the current `CLOB` data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleClob` obtained from `GetOracleClob()` can have a different value than the `OracleClob` obtained from `GetOracleClobForUpdate()` since it is not obtained from the original snapshot.

Invoking this method internally executes a `SELECT...FOR UPDATE` statement which locks the row.

The returned `OracleClob` object can be used to safely update the `CLOB` because the `CLOB` column is locked after a call to this method.

Different `WAIT` clauses are appended to the statement, depending on the *wait* value. If the *wait* value is:

- 0
"NOWAIT" is appended at the end of a `SELECT...FOR UPDATE` statement. The statement executes immediately whether the lock is acquired or not. If the lock is not acquired, an exception is thrown.
- *n*
"WAIT *n*" is appended at the end of a `SELECT...FOR UPDATE` statement. The statement executes as soon as the lock is acquired. However, if the lock cannot be acquired by *n* seconds, this method call throws an exception.

The `WAIT n` feature is only available for Oracle9i or later. For any version lower than Oracle9i, `n` is implicitly treated as `-1` and nothing is appended at the end of a `SELECT...FOR UPDATE` statement.

- `-1`

Nothing is appended at the end of the `SELECT...FOR UPDATE`. The statement execution waits indefinitely until a lock can be acquired.

`IsDBNull` should be called to check for `NULL` values before calling this method.

Example

The `GetOracleClobForUpdate` methods are comparable. See "Example" for a code example demonstrating usage.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#)

GetOracleDate

This method returns an `OracleDate` structure of the specified `DATE` column.

Declaration

```
// C#  
public OracleDate GetOracleDate(int index);
```

Parameters

- `index`
The zero-based column index.

Return Value

The `OracleDate` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#)

GetOracleDecimal

This method returns an `OracleDecimal` structure of the specified `NUMBER` column.

Declaration

```
// C#  
public OracleDecimal GetOracleDecimal(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleDecimal` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleIntervalDS

This method returns an `OracleIntervalDS` structure of the specified `INTERVAL DAY TO SECOND` column.

Declaration

```
// C#  
public OracleIntervalDS GetOracleIntervalDS(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleIntervalDS` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleIntervalYM

This method returns an `OracleIntervalYM` structure of the specified `INTERVAL YEAR TO MONTH` column.

Declaration

```
// C#  
public OracleIntervalYM GetOracleIntervalYM(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleIntervalYM` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleRef

This method returns an `OracleRef` object of the specified `REF` column.

Declaration

```
// C#  
public OracleRef GetOracleRef(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

The `OracleRef` object of the specified column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, the `Read` method has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleString

This method returns an `OracleString` structure of the specified column.

Declaration

```
// C#  
public OracleString GetOracleString(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleString` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

If the column is an Oracle `REF` column, the string returned is a hexadecimal value that represents the `REF` in the database.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleTimeStamp

This method returns an `OracleTimeStamp` structure of the Oracle `TimeStamp` column.

Declaration

```
// C#  
public OracleTimeStamp GetOracleTimeStamp(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleTimeStamp` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`GetOracleTimeStamp` is used with the Oracle Type `TimeStamp`.

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleTimeStampLTZ

This method returns an `OracleTimeStampLTZ` structure of the specified Oracle `TimeStamp WITH LOCAL TIME ZONE` column.

Declaration

```
// C#  
public OracleTimeStampLTZ GetOracleTimeStampLTZ(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleTimeStampLTZ` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`GetOracleTimeStampLTZ` is used with the Oracle Type `TimeStamp with Local Time Zone` columns.

`IsDBNull` should be called to check for `NULL` values before calling this method.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleTimeStampTZ

This method returns an `OracleTimeStampTZ` structure of the specified Oracle `TimeStamp WITH TIME ZONE` column.

Declaration

```
// C#  
public OracleTimeStampTZ GetOracleTimeStampTZ(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleTimeStampTZ` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

Used with the Oracle Type `TimeStamp with Local Time Zone` columns

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleXmlType

This method returns an `OracleXmlType` object of the specified `XMLType` column.

Declaration

```
// C#  
public OracleXmlType GetOracleXmlType(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleXmlType` value of the column.

Exceptions

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleValue

This method returns the specified column value as an ODP.NET type.

Declaration

```
// C#  
public object GetOracleValue(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The value of the column as an ODP.NET type.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

Remarks

If the column is an Oracle object or Oracle collection column and a custom type mapping exists, then a custom type is returned.

If the column is an Oracle `REF` column, then an `OracleRef` is returned.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleValues

This method gets all the column values as ODP.NET types.

Declaration

```
// C#  
public int GetOracleValues(object[] values);
```

Parameters

- *values*
An array of objects to hold the ODP.NET types as the column values.

Return Value

The number of ODP.NET types in the *values* array.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

Remarks

This method provides a way to retrieve all column values rather than retrieving each column value individually.

The number of column values retrieved is the minimum of the length of the *values* array and the number of columns in the result set.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#)

GetOrdinal

This method returns the 0-based ordinal (or index) of the specified column name.

Declaration

```
// C#  
public override int GetOrdinal(string name);
```

Parameters

- *name*
The specified column name.

Return Value

The index of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed.

IndexOutOfRangeException - The column index is invalid.

Remarks

A case-sensitive search is made to locate the specified column by its name. If this fails, then a case-insensitive search is made.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetProviderSpecificFieldType

This method returns the provider-specific type of the specified column.

Declaration

```
// C#public override Type GetProviderSpecificFieldType(int index);
```

Parameters

- *index*
A zero-based column index.

Return Value

The provider-specific type of the specified column. This is a member of the `Oracle.DataAccess.Types` namespace.

Exceptions

`IndexOutOfRangeException` - The column index is invalid.

`InvalidOperationException` - The reader is closed, or the specified column is a UDT but no registered custom type mapping exists for the UDT.

Remarks

`GetProviderSpecificFieldType` returns a type that corresponds to the value the application obtains after invoking the `GetProviderSpecificValue` accessor on the `OracleDataReader`. For example, if the column is a string, this method returns a .NET Type object for an `OracleString`.

If the attribute is a UDT, this method may return any of the following:

- A .NET Type of the custom type, if the column is an Oracle object or Oracle collection column and a custom type mapping exists.
- A .NET Type of `OracleRef` if the column is an Oracle REF.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetProviderSpecificValue

This method returns an object that represents the underlying provider-specific value of the specified ordinal.

Declaration

```
// C#  
public override object GetProviderSpecificValue (int index);
```

Parameters

index

A zero-based column index.

Return Value

An Object that is a representation of the underlying provider-specific field type.

Exceptions

`IndexOutOfRangeException` - The column index is invalid.

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called or all rows have been read.

Remarks

If the column is an Oracle object or collection column, and a custom type mapping exists, a custom type is returned.

If the column is an Oracle `REF` column, an `OracleRef` is returned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetProviderSpecificValues

This method returns an array of objects that represent the underlying provider-specific values.

Declaration

```
// C#  
public override int GetProviderSpecificValues(object [ ] values);
```

Parameters

- `values`
An array of objects.

Return Value

The number of `Object` instances in the array.

Exceptions

`InvalidOperationException` - The reader is closed.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetSchemaTable

This method returns a `DataTable` that describes the column metadata of the `OracleDataReader`.

Declaration

```
// C#
public override DataTable GetSchemaTable();
```

Return Value

A `DataTable` that contains the metadata of the result set.

Implements

`IDataReader`

Exceptions

`InvalidOperationException` - The connection is closed or the reader is closed.

Remarks

The `OracleDataReader.GetSchemaTable` method returns the `SchemaTable`.

OracleDataReader SchemaTable

The `OracleDataReader SchemaTable` is a `DataTable` that describes the column metadata of the `OracleDataReader`.

The value of `ColumnSize` can show value up to 32K depending on the definition of `VARCHAR2`, `NVARCHAR2`, or `RAW` type columns in the table definition.

The columns of the `SchemaTable` are in the order shown.

Table 6-81 OracleDataReader SchemaTable

Name	Name Type	Description
ColumnName	System.String	The name of the column.
ColumnOrdinal	System.Int32	The 0-based ordinal of the column.

Table 6-81 (Cont.) OracleDataReader SchemaTable

Name	Name Type	Description
ColumnSize	System.Int64	<p>The maximum possible length of a value in the column. ColumnSize value is determined as follows:</p> <ul style="list-style-type: none"> CHAR and VARCHAR2 types: <ul style="list-style-type: none"> in bytes - if IsByteSemantic boolean value is true in characters - if IsByteSemantic boolean value is false All other types: <ul style="list-style-type: none"> in bytes
NumericPrecision	System.Int16	<p>The maximum precision of the column, if the column is a numeric data type.</p> <p>This column has valid values for Oracle NUMBER, Oracle INTERVAL YEAR TO MONTH, and Oracle INTERVAL DAY TO SECOND columns. For all other columns, the value is null.</p>
NumericScale	System.Int16	<p>The scale of the column.</p> <p>This column has valid values for Oracle NUMBER, Oracle INTERVAL DAY TO SECOND, and the Oracle TIMESTAMP columns. For all other columns, the value is null.</p>
IsUnique	System.Boolean	<p>Indicates whether or not the column is unique.</p> <p>true if no two rows in the base table can have the same value in this column, where the base table is the table returned in BaseTableName.</p> <p>IsUnique is guaranteed to be true if one of the following applies in descending order of priority:</p> <ul style="list-style-type: none"> the column constitutes a base table primary key by itself and a NOT NULL constraint has been defined on the column there is a unique constraint or a unique index that applies only to this column and a NOT NULL constraint has been defined on the column the column is an explicitly selected ROWID <p>IsUnique is false if the column can contain duplicate values in the base table.</p> <p>The default is false.</p> <p>The value of this property is the same for each occurrence of the base table column in the select list.</p>

Table 6-81 (Cont.) OracleDataReader SchemaTable

Name	Name Type	Description
IsKey	System.Boolean	<p>Indicates whether or not the column is a key column.</p> <p>true if the column is one of a set of columns in the rowset that, taken together, uniquely identify the row. The set of columns with IsKey set to true must uniquely identify a row in the rowset. There is no requirement that this set of columns is a minimal set of columns.</p> <p>This set of columns can be generated from one of the following in descending order of priority:</p> <ul style="list-style-type: none"> • A base table primary key with the following condition: A NOT NULL constraint must be defined on the column or on all of the columns, in the case of a composite primary key. • Any of the unique constraints or unique indexes with the following condition: A NOT NULL constraint must be defined on the column or on all of the columns, in the case of a composite unique constraint or composite unique index. • A base table composite primary key with the following condition: A NULL constraint must be defined on at least one, but not all, of the columns. • Any of the composite unique constraints or composite unique indexes with the following condition: A NULL constraint must be defined on at least one, but not all, of the columns. <p>An explicitly selected ROWID. false if the column is not required to uniquely identify the row. The value of this property is the same for each occurrence of the base table column in the select list.</p>
IsRowID	System.Boolean	true if the column is a ROWID, otherwise false.
BaseColumnName	System.String	The name of the column in the database if an alias is used for the column.
BaseSchemaName	System.String	The name of the schema in the database that contains the column.
BaseTableName	System.String	The name of the table or view in the database that contains the column.
DataType	System.RuntimeType	Maps to the common language runtime type.
ProviderType	Oracle.DataAccess.Client.OracleDbType	The database column type (OracleDbType) of the column.
AllowDBNull	System.Boolean	true if null values are allowed, otherwise false.
IsAliased	System.Boolean	true if the column is an alias; otherwise false.
IsByteSemantic	System.Boolean	<p>IsByteSemantic is:</p> <ul style="list-style-type: none"> • true if the ColumnSize value uses bytes semantics • false if ColumnSize uses character semantics <p>This value is always true when connected to a database version earlier than Oracle9i.</p>
IsExpression	System.Boolean	true if the column is an expression; otherwise false.

Table 6-81 (Cont.) OracleDataReader SchemaTable

Name	Name Type	Description
IsHidden	System.Boolean	true if the column is hidden; otherwise false.
IsReadOnly	System.Boolean	true if the column is read-only; otherwise false.
IsLong	System.Boolean	true if the column is a LONG, LONG RAW, BLOB, CLOB, or BFILE; otherwise false.
UdtTypeName	System.String	The type name of the UDT.
IsIdentity	System.Boolean	true if the column is an identity column; otherwise false.
IsAutoIncrement	System.Boolean	true if the column assigns values to new rows in fixed increments; otherwise false. <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
IdentityType	OracleIdentityType	An OracleIdentityType enumeration value that specifies how the identity column values are generated; otherwise DbNull.Value, if the column is not an identity column. <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>

Example

This example creates and uses the SchemaTable from the reader.

```

/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetSchemaTableSample
{
    static void Main()
    {

```

```
string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

string cmdstr = "SELECT EMPNO,EMPNAME FROM EMPINFO where EMPNO = 1";
OracleCommand cmd = new OracleCommand(cmdstr, con);

//get the reader
OracleDataReader reader = cmd.ExecuteReader();

//get the schema table
DataTable schemaTable = reader.GetSchemaTable();

//retrieve the first column info.
DataRow row = schemaTable.Rows[0];

//print out the column info
Console.WriteLine("Column name: " + row["COLUMNNAME"]);
Console.WriteLine("Precision: " + row["NUMERICPRECISION"]);
Console.WriteLine("Scale: " + row["NUMERICSCALE"]);
reader.Close();

// Close the connection
con.Close();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetString

This method returns the `string` value of the specified column.

Declaration

```
// C#
public override string GetString(int index);
```

Parameters

- `index`
The zero-based column index.

Return Value

The `string` value of the column.

Implements

IDataRecord

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

Call the `IsDBNull` method to check for null values before calling this method.

If the column is an Oracle `REF` column, the string returned is a hexadecimal string that represents the `REF` in the database.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetTimeSpan

This method returns the `TimeSpan` value of the specified `INTERVAL DAY TO SECOND` column.

Declaration

```
// C#  
public TimeSpan GetTimeSpan(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `TimeSpan` value of the column.

Implements

IDataRecord

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetValue

This method returns the column value as a .NET type.

Declaration

```
// C#  
public override object GetValue(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The value of the column as a .NET type.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, all rows have been read, or no valid custom type mapping has been specified for the Oracle Object or Oracle Collection column.

`IndexOutOfRangeException` - The column index is invalid.

Remarks

If the column is an Oracle Object or an Oracle Collection column, the .NET custom type corresponding to the custom type mapping is returned.

If the column is an Oracle REF column, a hexadecimal value is returned as a .NET string that represents the REF in the database.

If the UDT is NULL, `DBNull.Value` is returned



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetValues

This method gets all the column values as .NET types.

Declaration

```
// C#  
public override int GetValues(object[ ] values);
```

Parameters

- *values*
An array of objects to hold the .NET types as the column values.

Return Value

The number of objects in the *values* array.

Implements

IDataRecord

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

Remarks

This method provides a way to retrieve all column values rather than retrieving each column value individually.

The number of column values retrieved is the minimum of the length of the values array and the number of columns in the result set.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetXmlReader

This method returns the contents of an `XMLType` column as an instance of an .NET `XmlTextReader` object.

Declaration

```
// C#  
public XmlReader GetXmlReader(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

A .NET `XmlTextReader`.

Exceptions

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

IsDBNull

This method indicates whether or not the column value is `NULL`.

Declaration

```
// C#  
public override bool IsDBNull(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

Returns `true` if the column is a `NULL` value; otherwise, returns `false`.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

Remarks

This method should be called to check for `NULL` values before calling the other accessor methods.

Example

The code example for the `OracleDataReader` class includes the `IsDBNull` method. See ["Example"](#).

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

NextResult

This method advances the data reader to the next result set.

Declaration

```
// C#  
public override bool NextResult();
```

Return Value

Returns `true` if another result set exists; otherwise, returns `false`.

Implements

`IDataReader`

Exceptions

`InvalidOperationException` - The connection is closed or the reader is closed.

Remarks

`NextResult` is used when reading results from stored procedure execution that return more than one result set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Read

This method reads the next row in the result set.

Declaration

```
// C#  
public override bool Read();
```

Return Value

Returns `true` if another row exists; otherwise, returns `false`.

Implements

`IDataReader`

Exceptions

`InvalidOperationException` - The connection is closed or the reader is closed.

Remarks

The initial position of the data reader is before the first row. Therefore, the `Read` method must be called to fetch the first row. The row that was just read is considered the *current row*. If the `OracleDataReader` has no more rows to read, it returns `false`.

Example

The code example for the `OracleDataReader` class includes the `Read` method. See ["Example"](#).



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

OracleDataSourceCollection Class

An `OracleDataSourceCollection` supports adding and deleting network service name (i.e. TNS) entries for ODP.NET's use to connect to an Oracle database.

Class Inheritance

`System.Object`

`Oracle.ManagedDataAccess.Client.OracleDataSourceCollection`

Declaration

```
// C#
public sealed class OracleDataSourceCollection
```

Requirements

Provider	ODP.NET Core
Assembly	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	4.6.1 or higher
.NET Core	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
using System;
using Oracle.ManagedDataAccess.Client;

namespace NetCoreApplication
{
    class DataSourcesExample
    {
```

```
static void Main(string[] args)
{
    // Example to configure Data Sources for the ODP.NET Core provider.

    // Add data source through Add method on OracleDataSourceCollection
    OracleConfiguration.OracleDataSources.Add("orcl1",
        "(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=host1)(PORT=1234))
        (CONNECT_DATA=(SERVICE_NAME=oracle)(SERVER=dedicated)))");

    // Add data source through indexer method on OracleDataSourceCollection
    OracleConfiguration.OracleDataSources["orcl2"] =
        "(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=host1)(PORT=1234))
        (CONNECT_DATA=(SERVICE_NAME=oracle)(SERVER=dedicated)))";

    // Get number of data sources configured
    int numDataSources = OracleConfiguration.OracleDataSources.Count;

    // Get OracleDataSourceCollection object
    OracleDataSourceCollection dsColl = OracleConfiguration.OracleDataSources;

    // Add server through Add method on OracleDataSourceCollection
    dsColl.Add("orcl3", "(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=host3)
        (PORT=1234))(CONNECT_DATA=(SERVICE_NAME=oracle)(SERVER=dedicated)))");

    // Add server through indexer method on OracleDataSourceCollection
    dsColl["orcl4"] = "(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=host4)(PORT=1234))
        (CONNECT_DATA=(SERVICE_NAME=oracle)(SERVER=dedicated)))";

    // Remove a data source
    OracleConfiguration.OracleDataSources.Remove("db2");

    // Get number of data sources configured
    numDataSources = OracleConfiguration.OracleDataSources.Count;

    // Get value corresponding to a data source.
    string dsVal = OracleConfiguration.OracleDataSources["db1"];

    OracleConnection orclCon = null;

    try
    {
        // Open a test connection
        orclCon = new OracleConnection("user id=scott; password=tiger; data
        source=orcl3");

        orclCon.Open();
        orclCon.Close();
    }
    catch (OracleException ex)
    {
        Console.WriteLine(ex);
    }
    finally
    {
        // Close the connection
        if (null != orclCon)
            orclCon.Close();
    }
}
}
```


 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Members](#)
- [OracleDataSourceCollection Methods](#)
- [OracleDataSourceCollection Properties](#)

OracleDataSourceCollection Members

OracleDataSourceCollection members are listed in the following tables.

OracleDataSourceCollection Methods

OracleDataSourceCollection methods are listed in [Table 6-82](#).

Table 6-82 OracleDataSourceCollection Methods

Method	Description
Add	Adds unique network service name (TNS) entries in the OracleDataSourceCollection using net service names and complete connect descriptors
Remove	Removes network service name entries from an OracleDataSourceCollection

OracleDataSourceCollection Properties

OracleDataSourceCollection properties are listed in [Table 6-83](#).

Table 6-83 OracleDataSourceCollection Properties

Property	Description
Count	Returns the number of OracleDataSourceCollection elements
This	Returns or sets the network service name entry with the specified network service name

OracleDataSourceCollection Methods

OracleDataSourceCollection methods are listed in [Table 6-84](#).

Table 6-84 OracleDataSourceCollection Methods

Method	Description
Add	Adds unique network service name (TNS) entries in the OracleDataSourceCollection using net service names and complete connect descriptors
Remove	Removes network service name entries from an OracleDataSourceCollection

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceCollection Members](#)

Add


This method adds unique network service name (TNS) entries in the OracleDataSourceCollection using net service names and complete connect descriptors.

Declaration

```
// C#  
public void Add(string tnsName, string tnsDescriptor)
```

Parameters

- tnsName
 - Type: System.String
 - Network service name used as the ODP.NET connection string Data Source name.
- tnsDescriptor
 - Type: System.String
 - The complete connect descriptor information for this specific net service name.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceCollection Members](#)

Remove

This method removes network service name entries from an OracleDataSourceCollection.

Declaration

```
// C#
public void Remove(string tnsName)
```

Parameter

tnsName

- **Type:** System.String
- Unique network service name to be removed from the collection.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceCollection Members](#)

OracleDataSourceCollection Properties

OracleDataSourceCollection properties are listed in [Table 6-85](#).

Table 6-85 OracleDataSourceCollection Properties

Property	Description
Count	Returns the number of OracleDataSourceCollection elements
This	Returns or sets the network service name entry with the specified network service name

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceCollection Members](#)

Count

This is a read-only property that returns the number of `OracleDataSourceCollection` elements

Declaration

```
// C#  
public int Count { get; }
```

Property Value

Type: `System.Int32`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceCollection Members](#)

This

This property returns or sets the network service name entry with the specified network service name.

Declaration

```
// C#  
public string this[string tnsName] { get; set; }
```

Parameters

- `tnsName`
 - Type: `System.String`
 - Unique network service name to be added or updated
- `Value`
 - Type: `System.String`

- Connect descriptor to be added or updated.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceCollection Members](#)

OracleDataSourceEnumerator Class

An `OracleDataSourceEnumerator` object allows applications to generically obtain a collection of data sources to connect to.

Class Inheritance

`System.Object`

`System.DbDataSourceEnumerator`

`Oracle.DataAccess.Client.OracleDataSourceEnumerator`

Declaration

```
// C#
public sealed class OracleDataSourceEnumerator : DbDataSourceEnumerator
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#
using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;
```

```

class DataSourceEnumSample
{
    static void Main()
    {
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        if (factory.CanCreateDataSourceEnumerator)
        {
            DbDataSourceEnumerator dsenum = factory.CreateDataSourceEnumerator();
            DataTable dt = dsenum.GetDataSources();

            // Print the first column/row entry in the DataTable
            Console.WriteLine(dt.Columns[0] + " : " + dt.Rows[0][0]);
            Console.WriteLine(dt.Columns[1] + " : " + dt.Rows[0][1]);
            Console.WriteLine(dt.Columns[2] + " : " + dt.Rows[0][2]);
            Console.WriteLine(dt.Columns[3] + " : " + dt.Rows[0][3]);
            Console.WriteLine(dt.Columns[4] + " : " + dt.Rows[0][4]);
        }
        else
            Console.WriteLine("Data source enumeration is not supported by provider");
    }
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceEnumerator Members](#)
- [OracleDataSourceEnumerator Constructor](#)
- [OracleDataSourceEnumerator Public Methods](#)

OracleDataSourceEnumerator Members

OracleDataSourceEnumerator members are listed in the following tables.

OracleDataSourceEnumerator Constructor

OracleDataSourceEnumerator Public Methods are listed in [Table 6-86](#).

Table 6-86 OracleDataSourceEnumerator Method

Method	Description
OracleDataSourceEnumerator Constructor	Instantiates a new instance of the OracleDataSourceEnumerator class

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceEnumerator Class](#)

OracleDataSourceEnumerator Public Methods

OracleDataSourceEnumerator Public Methods are listed in [Table 6-87](#).

Table 6-87 OracleDataSourceEnumerator Method

Method	Description
GetDataSources	Returns a DataTable object with information on all the TNS alias entries in the tnsnames.ora file and entries retrieved from the LDAP servers configured in ldap.ora if LDAP Naming is enabled

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceEnumerator Class](#)

OracleDataSourceEnumerator Constructor

OracleDataSourceEnumerator constructor creates new instances of an OracleDataSourceEnumerator class.

Declaration

```
// C#
public OracleDataSourceEnumerator();
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)

OracleDataSourceEnumerator Public Methods

The `OracleDataSourceEnumerator` static method is listed in [Table 6-88](#).

Table 6-88 OracleDataSourceEnumerator Method

Method	Description
GetDataSources	Returns a <code>DataTable</code> object with information on all the TNS alias entries in the <code>tnsnames.ora</code> file

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)

GetDataSources

This method returns a `DataTable` object with information on all the TNS alias entries in the `tnsnames.ora` file and entries retrieved from the LDAP servers configured in `ldap.ora` if LDAP naming is enabled.

Declaration

```
// C#  
public override DataTable GetDataSources();
```

Return Value

A `DataTable` object.

Remarks

This method returns a `DataTable` object for each TNS alias entry that exists in the `tnsnames.ora` file and each entry retrieved from the LDAP servers. If a `tnsnames.ora` file is not found and LDAP Naming is not configured, then the returned `DataTable` object will be empty.

This method in ODP.NET, Managed Driver can fetch all the data source aliases from an LDAP server, such as Oracle Internet Directory or Microsoft Active Directory. This method in ODP.NET, Unmanaged Driver does not support retrieving data source aliases from an LDAP server.

When Oracle Internet Directory (OID) is used for the TNS naming repository, there is a limit of 1000 TNS entries retrieved.

The following columns are returned for each row, but only the `InstanceName` column is populated.

- InstanceName (type: System.String)
- ServerName (type: System.String)
- ServiceName (type: System.String)
- Protocol (type: System.String)
- Port (type: System.String)

If the TNS and/or LDAP information changes for existing pooled connections, then calling `GetDataSources` will not return these changes unless the pools have been cleared.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)

OracleError Class

The `OracleError` class represents an error reported by Oracle.

Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleError`

Declaration

```
// C#
public sealed class OracleError
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The `OracleError` class represents a warning or an error reported by Oracle.

If there are multiple errors, ODP.NET only returns the first error message on the stack.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleErrorsSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        try
        {
            cmd.CommandText = "insert into notable values (99, 'MyText')";
            cmd.ExecuteNonQuery();
        }
        catch (OracleException ex)
        {
            Console.WriteLine("Record is not inserted into the database table.");

            foreach (OracleError error in ex.Errors)
            {
                Console.WriteLine("Error Message: " + error.Message);
                Console.WriteLine("Error Source: " + error.Source);
            }
        }
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Members](#)
- [OracleError Static Methods](#)
- [OracleError Properties](#)
- [OracleError Methods](#)

OracleError Members

OracleError members are listed in the following tables.

OracleError Static Methods

The OracleError static method is listed in [Table 6-89](#).

Table 6-89 OracleError Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleError Properties

OracleError properties are listed in [Table 6-90](#).

Table 6-90 OracleError Properties

Property	Description
ArrayBindIndex	Specifies the row number of errors that occurred during the Array Bind execution
DataSource	Specifies the Oracle service name (TNS name) that identifies the Oracle database
Message	Specifies the message describing the error
Number	Specifies the Oracle error number
Procedure	Specifies the stored procedure that causes the error
Source	Specifies the name of the data provider that generates the error

OracleError Methods

OracleError methods are listed in [Table 6-91](#).

Table 6-91 OracleError Methods

Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Returns a string representation of the OracleError

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)

OracleError Static Methods

The `OracleError` static method is listed in [Table 6-92](#).

Table 6-92 OracleError Static Method

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

OracleError Properties

`OracleError` properties are listed in [Table 6-93](#).

Table 6-93 OracleError Properties

Property	Description
ArrayBindIndex	Specifies the row number of errors that occurred during the Array Bind execution
DataSource	Specifies the Oracle service name (TNS name) that identifies the Oracle database
Message	Specifies the message describing the error
Number	Specifies the Oracle error number
Procedure	Specifies the stored procedure that causes the error
Source	Specifies the name of the data provider that generates the error

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

ArrayBindIndex

This property specifies the row number of errors that occurred during the Array Bind execution.

Declaration

```
// C#  
public int ArrayBindIndex {get;}
```

Property Value

An `int` value that specifies the row number for errors that occurred during the Array Bind execution.

Remarks

Default = 0.

This property is used for Array Bind operations only.

`ArrayBindIndex` represents the zero-based row number at which the error occurred during an Array Bind operation. For example, if an array bind execution causes two errors on the 2nd and 4th operations, two `OracleError` objects appear in the `OracleErrorCollection` with the `ArrayBindIndex` property values 2 and 4 respectively.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)
- ["Array Binding"](#)

DataSource

This property specifies the Oracle service name (TNS name) that identifies the Oracle database.

Declaration

```
// C#  
public string DataSource {get;}
```

Property Value

A string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

Message

This property specifies the message describing the error.

Declaration

```
// C#  
public string Message {get;}
```

Property Value

A string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

Number

This property specifies the Oracle error number.

Declaration

```
// C#  
public int Number {get;}
```

Property Value

An int.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

Procedure

This property specifies the stored procedure that causes the `error`.

Declaration

```
// C#  
public string Procedure {get;}
```

Property Value

The stored procedure name.

Remarks

Represents the stored procedure which creates this `OracleError` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

Source

This property specifies the name of the data provider that generates the `error`.

Declaration

```
// C#  
public string Source {get;}
```

Property Value

A `string`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

OracleError Methods

OracleError methods are listed in [Table 6-94](#).

Table 6-94 OracleError Methods

Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Returns a string representation of the OracleError

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

ToString

Overrides Object

This method returns a string representation of the OracleError.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns a string with the format Ora- error number: Class.Method name error message stack trace information.

Example

ORA-24333: zero iteration count

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleError Class](#)
- [OracleError Members](#)

OracleErrorCollection Class

An `OracleErrorCollection` class represents a collection of all errors that are thrown by the Oracle Data Provider for .NET.

Class Inheritance

`System.Object`

`System.ArrayList`

`Oracle.DataAccess.Client.OracleErrorCollection`

Declaration

```
// C#
public sealed class OracleErrorCollection : ArrayList
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

A simple `ArrayList` that holds a list of `OracleErrors`.

If there are multiple errors, ODP.NET only returns the first error message on the stack.

Example

```
// C#
```

```
using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleErrorCollectionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        try
        {
            cmd.CommandText = "insert into notable values (99, 'MyText')";
            cmd.ExecuteNonQuery();
        }
        catch (OracleException ex)
        {
            Console.WriteLine("Record is not inserted into the database table.");

            foreach (OracleError error in ex.Errors)
            {
                Console.WriteLine("Error Message: " + error.Message);
                Console.WriteLine("Error Source: " + error.Source);
            }
        }
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleErrorCollection Members](#)
- [OracleErrorCollection Static Methods](#)
- [OracleErrorCollection Properties](#)
- [OracleErrorCollection Public Methods](#)

OracleErrorCollection Members

OracleErrorCollection members are listed in the following tables.

OracleErrorCollection Static Methods

OracleErrorCollection static methods are listed in [Table 6-95](#).

Table 6-95 OracleErrorCollection Static Methods

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleErrorCollection Properties

OracleErrorCollection properties are listed in [Table 6-96](#).

Table 6-96 OracleErrorCollection Properties

Property	Description
Capacity	Inherited from System.Collections.ArrayList
Count	Inherited from System.Collections.ArrayList
IsReadOnly	Inherited from System.Collections.ArrayList
IsSynchronized	Inherited from System.Collections.ArrayList
Item	Inherited from System.Collections.ArrayList

OracleErrorCollection Public Methods

OracleErrorCollection public methods are listed in [Table 6-97](#).

Table 6-97 OracleErrorCollection Public Methods

Public Method	Description
CopyTo	Inherited from System.Collections.ArrayList
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleErrorCollection Class](#)

OracleErrorCollection Static Methods

The OracleErrorCollection static method is listed in [Table 6-98](#).

Table 6-98 OracleErrorCollection Static Method

Method	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

OracleErrorCollection Properties

OracleErrorCollection properties are listed in [Table 6-99](#).

Table 6-99 OracleErrorCollection Properties

Property	Description
Capacity	Inherited from <code>System.Collections.ArrayList</code>
Count	Inherited from <code>System.Collections.ArrayList</code>
IsReadOnly	Inherited from <code>System.Collections.ArrayList</code>
IsSynchronized	Inherited from <code>System.Collections.ArrayList</code>
Item	Inherited from <code>System.Collections.ArrayList</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

OracleErrorCollection Public Methods

OracleErrorCollection public methods are listed in [Table 6-100](#).

Table 6-100 OracleErrorCollection Public Methods

Public Method	Description
CopyTo	Inherited from <code>System.Collections.ArrayList</code>
Equals	Inherited from <code>System.Object</code> (Overloaded)
GetHashCode	Inherited from <code>System.Object</code>
GetType	Inherited from <code>System.Object</code>
ToString	Inherited from <code>System.Object</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

OracleException Class

The `OracleException` class represents an exception that is thrown when the Oracle Data Provider for .NET encounters an error. Each `OracleException` object contains at least one `OracleError` object in the `Error` property that describes the error or warning.

Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`System.Runtime.InteropServices.ExternalException`

`System.Data.Common.DbException`

`Oracle.DataAccess.Client.OracleException`

Declaration

```
// C#
public sealed class OracleException : SystemException
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Namespace	Oracle.DataAccess .Client	Oracle.ManagedDat aAccess.Client	Oracle.ManagedDat aAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

If there are multiple errors, ODP.NET only returns the first error message on the stack.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleExceptionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        try
        {
            cmd.CommandText = "insert into notable values (99, 'MyText')";
            cmd.ExecuteNonQuery();
        }
        catch (OracleException ex)
        {
            Console.WriteLine("Record is not inserted into the database table.");
            Console.WriteLine("Exception Message: " + ex.Message);
            Console.WriteLine("Exception Source: " + ex.Source);
        }
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Members](#)
- [OracleException Methods](#)
- [OracleException Static Methods](#)
- [OracleException Static Methods](#)
- [OracleException Properties](#)
- [OracleException Methods](#)

OracleException Members

OracleException members are listed in the following tables.

OracleException Static Methods

The OracleException static method is listed in [Table 6-101](#).

Table 6-101 OracleException Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleException Properties

OracleException properties are listed in [Table 6-102](#).

Table 6-102 OracleException Properties

Property	Description
DataSource	Specifies the TNS name that contains the information for connecting to an Oracle instance
Errors	Specifies a collection of one or more OracleError objects that contain information about exceptions generated by the Oracle database
HelpLink	Inherited from System.Exception
InnerException	Inherited from System.Exception
IsRecoverable	Specifies whether the current operation producing this exception can succeed if retried
Message	Specifies the error messages that occur in the exception
Number	Specifies the Oracle error number

Table 6-102 (Cont.) OracleException Properties

Property	Description
OracleLogicalTransaction	Returns an <code>OracleLogicalTransaction</code> object for a recoverable error when using Transaction Guard
Procedure	Specifies the stored procedure that cause the exception
Source	Specifies the name of the data provider that generates the error
<code>StackTrace</code>	Inherited from <code>System.Exception</code>
<code>TargetSite</code>	Inherited from <code>System.Exception</code>

OracleException Methods

OracleException methods are listed in [Table 6-103](#).

Table 6-103 OracleException Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetBaseException</code>	Inherited from <code>System.Exception</code>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
GetObjectData	Sets the serializable <code>info</code> object with information about the exception
<code>GetType</code>	Inherited from <code>System.Object</code>
ToString	Returns the fully qualified name of this exception

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)

OracleException Static Methods

The `OracleException` static method is listed in [Table 6-104](#).

Table 6-104 OracleException Static Method

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

OracleException Properties

OracleException properties are listed in [Table 6-105](#).

Table 6-105 OracleException Properties

Property	Description
DataSource	Specifies the TNS name that contains the information for connecting to an Oracle instance
Errors	Specifies a collection of one or more <code>OracleError</code> objects that contain information about exceptions generated by the Oracle database
<code>HelpLink</code>	Inherited from <code>System.Exception</code>
<code>InnerException</code>	Inherited from <code>System.Exception</code>
IsRecoverable	Specifies whether the current operation producing this exception can succeed if retried
Message	Specifies the error messages that occur in the exception
Number	Specifies the Oracle error number
OracleLogicalTransaction	Returns an <code>OracleLogicalTransaction</code> object for a recoverable error when using Transaction Guard
Procedure	Specifies the stored procedure that cause the exception
Source	Specifies the name of the data provider that generates the error
<code>StackTrace</code>	Inherited from <code>System.Exception</code>
<code>TargetSite</code>	Inherited from <code>System.Exception</code>

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

DataSource

This property specifies the TNS name that contains the information for connecting to an Oracle instance.

Declaration

```
// C#  
public string DataSource {get;}
```

Property Value

The TNS name containing the connect information.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

Errors

This property specifies a collection of one or more `OracleError` objects that contain information about exceptions generated by the Oracle database.

Declaration

```
// C#  
public OracleErrorCollection Errors {get;}
```

Property Value

An `OracleErrorCollection`.

Remarks

The `Errors` property contains at least one instance of `OracleError` objects.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

IsRecoverable

This property specifies whether the current operation producing this exception can succeed if retried.

Declaration

```
// C#  
public bool IsRecoverable {get;}
```

Property Value

A bool.

Remarks

When a database outage occurs, such as during a network failure, the session becomes unavailable and the client receives an error code. The client can have difficulty determining whether the in-flight operation committed or needs to be resubmitted. Oracle automatically determines whether an in-flight database operation can be recovered or not using the `IsRecoverable` property. If `IsRecoverable` returns true after an outage, then the application can retrieve the current operation status and complete the transaction. If `IsRecoverable` returns false, then the application can rollback the current operation and resubmit the transaction.

This property is often used in conjunction with Transaction Guard.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)
- [Using Transaction Guard to Prevent Logical Corruption](#)

Message

Overrides `Exception`

This property specifies the error messages that occur in the exception.

Declaration

```
// C#  
public override string Message {get;}
```

Property Value

A string.

Remarks

Message is a concatenation of all errors in the `Errors` collection. Each error message is concatenated and is followed by a carriage return, except the last one.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

Number

This property specifies the Oracle error number.

Declaration

```
// C#  
public int Number {get;}
```

Property Value

The error number.

Remarks

This error number can be the topmost level of error generated by Oracle and can be a provider-specific error number.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

OracleLogicalTransaction

This property will returns an `OracleLogicalTransaction` object for a recoverable error when using Transaction Guard.

Declaration

```
// C#  
public OracleLogicalTransaction OracleLogicalTransaction {get;}
```

Property Value

An `OracleLogicalTransaction`.

Remarks

`OracleLogicalTransaction` is non-null when both of the following conditions are met:

- Transaction Guard is enabled on the service
- The exception is a recoverable error

`OracleLogicalTransaction` can be used to determine the transaction outcome by looking at the two properties that it exposes: `Committed` and `UserCallCompleted`. If the outcome is not known, then `Committed` and `UserCallCompleted` will be set to null.

If the outcome of a recoverable error could not be determined by ODP.NET and the connection have not participated in a distributed transaction, then the `OracleLogicalTransactionId` property of the `OracleLogicalTransaction` object will be non-null and it can be used to determine the outcome by having the application explicitly call the `OracleLogicalTransaction.GetOutcome` static method, if the database/service is up.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)
- [OracleLogicalTransaction Class](#)

Procedure

This property specifies the stored procedure that caused the exception.

Declaration

```
// C#  
public string Procedure {get;}
```

Property Value

The stored procedure name.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

Source

Overrides `Exception`

This property specifies the name of the data provider that generates the error.

Declaration

```
// C#
public override string Source {get;}
```

Property Value

The name of the data provider.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

OracleException Methods

`OracleException` methods are listed in [Table 6-106](#).

Table 6-106 OracleException Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetBaseException</code>	Inherited from <code>System.Exception</code>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
GetObjectData	Sets the serializable <code>info</code> object with information about the exception
<code>GetType</code>	Inherited from <code>System.Object</code>
ToString	Returns the fully qualified name of this exception

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

GetObjectData

Overrides `Exception`

This method sets the serializable `info` object with information about the exception.

Declaration

```
// C#  
public override void GetObjectData(SerializationInfo info, StreamingContext  
    context);
```

Parameters

- `info`
A `SerializationInfo` object.
- `context`
A `StreamingContext` object.

Remarks

The information includes `DataSource`, `Message`, `Number`, `Procedure`, `Source`, and `StackTrace`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

ToString

Overrides `Exception`

This method returns the fully qualified name of this exception, the error message in the `Message` property, the `InnerException.ToString()` message, and the stack trace.

Declaration

```
// C#  
public override string ToString();
```

Return Value

The string representation of the exception.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ToStringSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Create an OracleCommand object using the connection object  
        OracleCommand cmd = con.CreateCommand();  
  
        try  
        {  
            cmd.CommandText = "insert into notable values (99, 'MyText')";  
            cmd.ExecuteNonQuery(); // This will throw an exception  
        }  
        catch (OracleException ex)  
        {  
            Console.WriteLine("Record is not inserted into the database table.");  
            Console.WriteLine("ex.ToString() : " + ex.ToString());  
        }  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleException Class](#)
- [OracleException Members](#)

OracleInfoMessageEventArgs Class

The `OracleInfoMessageEventArgs` class provides event data for the `OracleConnection.InfoMessage` event. When any warning occurs in the database, the `OracleConnection.InfoMessage` event is triggered along with the `OracleInfoMessageEventArgs` object that stores the event data.

Class Inheritance

System.Object

System.EventArgs

Oracle.DataAccess.Client.OracleInfoMessageEventArgs

Declaration

```
// C#
public sealed class OracleInfoMessageEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class InfoMessageSample
{
    public static void WarningHandler(object src,
        OracleInfoMessageEventArgs args)
    {
        Console.WriteLine("Source object is: " + src.GetType().Name);
        Console.WriteLine("InfoMessageArgs.Message is " + args.Message);
        Console.WriteLine("InfoMessageArgs.Source is " + args.Source);
    }
    static void Main()
    {
        OracleConnection con = new OracleConnection("User Id=scott;" +
            "Password=tiger;Data Source=oracle;");

        con.Open();

        OracleCommand cmd = con.CreateCommand();
```

```

//Register to the InfoMessageHandler
cmd.Connection.InfoMessage +=
    new OracleInfoMessageEventHandler(WarningHandler);

cmd.CommandText =
    "create or replace procedure SelectWithNoInto( " +
    " empname in VARCHAR2) AS " +
    "BEGIN " +
    " select * from emp where ename = empname; " +
    "END SelectWithNoInto;";

// Execute the statement that produces a warning
cmd.ExecuteNonQuery();

// Clean up
cmd.Dispose();
con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Members](#)
- [OracleInfoMessageEventArgs Static Methods](#)
- [OracleInfoMessageEventArgs Properties](#)
- [OracleInfoMessageEventArgs Public Methods](#)
- ["OracleConnection Class"](#)

OracleInfoMessageEventArgs Members

OracleInfoMessageEventArgs members are listed in the following tables.

OracleInfoMessageEventArgs Static Methods

The OracleInfoMessageEventArgs static methods is listed in [Table 6-107](#).

Table 6-107 OracleInfoMessageEventArgs Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleInfoMessageEventArgs Properties

The OracleInfoMessageEventArgs properties are listed in [Table 6-108](#).

Table 6-108 OracleInfoMessageEventArgs Properties

Property	Description
Errors	Specifies the collection of errors generated by the data source
Message	Specifies the error text generated by the data source
Source	Specifies the name of the object that generated the error

OracleInfoMessageEventArgs Public Methods

The `OracleInfoMessageEventArgs` methods are listed in [Table 6-109](#).

Table 6-109 OracleInfoMessageEventArgs Public Methods

Method	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)
GetHashCode	Inherited from <code>System.Object</code>
GetType	Inherited from <code>System.Object</code>
ToString	Returns the string representation of the current instance

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)

OracleInfoMessageEventArgs Static Methods

The `OracleInfoMessageEventArgs` static method is listed in [Table 6-110](#).

Table 6-110 OracleInfoMessageEventArgs Static Method

Method	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

OracleInfoMessageEventArgs Properties

The OracleInfoMessageEventArgs properties are listed in [Table 6-111](#).

Table 6-111 OracleInfoMessageEventArgs Properties

Property	Description
Errors	Specifies the collection of errors generated by the data source
Message	Specifies the error text generated by the data source
Source	Specifies the name of the object that generated the error

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

Errors

This property specifies the collection of errors generated by the data source.

Declaration

```
// C#  
public OracleErrorCollection Errors {get;}
```

Property Value

The collection of errors.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

Message

This property specifies the error text generated by the data source.

Declaration

```
// C#  
public string Message {get;}
```

Property Value

The error text.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

Source

This property specifies the name of the object that generated the error.

Declaration

```
// C#  
public string Source {get;}
```

Property Value

The object that generated the error.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

OracleInfoMessageEventArgs Public Methods

The `OracleInfoMessageEventArgs` methods are listed in [Table 6-112](#).

Table 6-112 OracleInfoMessageEventArgs Public Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>

Table 6-112 (Cont.) OracleInfoMessageEventArgs Public Methods

Method	Description
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Returns the string representation of the current instance

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

ToString

Overrides `Object`

This method returns the string representation of the current instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns the `OracleInfoMessageEventArgs` value in a string representation.

Remarks

If the current instance has a null value, the returned string is null.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

OracleInfoMessageEventHandler Delegate

The `OracleInfoMessageEventHandler` represents the signature of the method that handles the `OracleConnection.InfoMessage` event.

Declaration

```
// C#
public delegate void OracleInfoMessageEventHandler(object sender,
    OracleInfoMessageEventArgs eventArgs);
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleInfoMessageEventArgs` object that contains the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["InfoMessage"](#)

OracleLogicalTransaction Class

The `OracleLogicalTransaction` class provides detailed information about the logical transaction status. Applications can conclusively determine the outcome of the running transaction during the last database outage, then act accordingly to commit, complete, or rollback the transaction.

Class Inheritance

System.Object

System.MarshalByRefObject

Oracle.DataAccess.Client.OracleLogicalTransaction

Declaration

```
// C#
public sealed class OracleLogicalTransaction
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Members](#)
- [OracleLogicalTransaction Public Read-Only Properties](#)
- [OracleLogicalTransaction Methods](#)

OracleLogicalTransaction Members

OracleLogicalTransaction members are listed in the following tables.

OracleLogicalTransaction Public Read-Only Properties

OracleLoigcalTransaction public read-only properties are listed in [Table 6-113](#)

Table 6-113 OracleLogicalTransaction Public Read-Only Properties

Property	Description
Committed	Specifies if the transaction was committed or not
ConnectionString	Specifies a subset of the connection string used for the transaction running during the last database outage
LogicalTransactionId	The logical transaction id is used to determine the commit outcome of the last transaction open in a database session following an outage.

Table 6-113 (Cont.) OracleLogicalTransaction Public Read-Only Properties

Property	Description
UserCallCompleted	Specifies if the transaction completed and that the information returned may be incomplete and/or not all expected work was completed

OracleLogicalTransaction Methods

OracleLoigcalTransaction methods are listed in [Table 6-114](#)

Table 6-114 OracleLogicalTransaction Methods

Property	Description
Dispose	This method releases any resources or memory allocated by the object
GetOutcome	This method retrieves the transaction outcome from the database server. The method will determine whether the transaction committed and completed or not.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)

OracleLogicalTransaction Public Read-Only Properties

OracleLoigcalTransaction public read-only properties are listed in [Table 6-115](#)

Table 6-115 OracleLogicalTransaction Public Read-Only Properties

Property	Description
Committed	Specifies if the transaction was committed or not
ConnectionString	Specifies a subset of the connection string used for the transaction running during the last database outage
LogicalTransactionId	The logical transaction id is used to determine the commit outcome of the last transaction open in a database session following an outage.
UserCallCompleted	Specifies if the transaction completed and that the information returned may be incomplete and/or not all expected work was completed

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

Committed

This property specifies if the transaction was committed or not.

Declaration

```
// C#
public bool? Committed {get;}
```

Property Value

bool.

Remarks

If `GetOutcome()` is not called, the this property holds a `null` value.

Once `GetOutcome()` is called, then this property will hold either `true` or `false`.

In some cases, `OracleLogicalTransaction.GetOutcome` will be called implicitly and populate this property with a non-null value automatically.

[Table 6-116](#) describes the possible outcomes of the `Committed` and `UserCallCompleted` properties.

Table 6-116 Outcome of OracleLogicalTransaction Committed and UserCallCompleted Properties

Committed Value	UserCallCompleted Value	Outcome
false	false	The call did not execute the commit.
true	true	The call did execute the commit and there was no additional information to return and no more work to do if that call was a PL/SQL procedure.

Table 6-116 (Cont.) Outcome of OracleLogicalTransaction Committed and UserCallCompleted Properties

Committed Value	UserCallCompleted Value	Outcome
true	false	The transaction is committed, but the information returned may be incomplete and/or not all expected work was completed. Examples of incomplete information or incomplete work done include: the number of rows modified when using autocommit or commit on success, parameter and function results when calling PL/SQL procedures, or PL/SQL procedures with more work to do after the commit. In order to function correctly, .NET applications that use data returned from the commit must check the UserCallCompleted value.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

ConnectionString

This property specifies a subset of the connection string used for the transaction running during the last database outage.

Declaration

```
// C#
public string ConnectionString {get;}
```

Property Value

The data source as a string.

Remarks

This connection string can be useful if the outcome is not known at the time the exception is thrown due to a service that is down. In such a scenario, use the connection string from this property along with the LogicalTransactionId to determine the outcome of the logical transaction by invoking the static GetOutcome() method, once the database or service is back up.

The string returned by this property will contain only the following attributes: User Id, Proxy user Id (if not null/empty), Data Source, and Pooling (which will be set to false).

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

LogicalTransactionId

The logical transaction id is used to determine the commit outcome of the last transaction open in a database session following an outage.

Declaration

```
// C#  
public byte LogicalTransactionId {get;}
```

Property Value

byte[]

Remarks

This logical transaction id can be useful if the outcome is not known at the time the exception is thrown due to a service that is down. In such a scenario, use the `byte[]` returned from this property (along with the `ConnectionString`) to determine the outcome of the logical transaction by invoking the static `GetOutcome()` method, once the database or service is back up.

This property will return a non-null value *only* when the outcome is not known. For example when database or service is down, then the outcome is not known.

`LogicalTransactionId` property will return `null` if the connection has participated in a distributed transaction.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

UserCallCompleted

This property specifies if the transaction completed and that the information returned may be incomplete and/or not all expected work was completed.

Declaration

```
// C#
public bool? UserCallCompleted {get;}
```

Property Value

bool

Remarks

If `GetOutcome()` is not called, the this property holds a null value.

Once `GetOutcome()` is called, then this property will hold either `true` or `false`.

In some cases, [GetOutcome](#) will be called implicitly and populate this property with a non-null value automatically

[Table 6-116](#) describes the possible outcomes of the `Committed` and `UserCallCompleted` properties.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

OracleLogicalTransaction Methods

OracleLoigcalTransaction methods are listed in [Table 6-117](#)

Table 6-117 OracleLogicalTransaction Methods

Property	Description
Dispose	This method releases any resources or memory allocated by the object
GetOutcome	This method retrieves the transaction outcome from the database server. The method will determine whether the transaction committed and completed or not.

Dispose

This method releases any resources or memory allocated by the object

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

Remarks

The `Dispose` method also closes the `OracleLogicalTransaction` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

GetOutcome

The `GetOutcome` method retrieves the transaction outcome from the database server. The method will determine whether the transaction committed and completed or not.

Overload List:

- `GetOutcome(string constring, byte[] ltxid, out bool? bCommitted, out bool? bUserCallCompleted)`

The application can use this static method to determine the outcome if the outcome was not known when the exception was raised.

The application will need to obtain the connection string and logical transaction id from the `OracleException.OracleLogicalTransaction` object before calling this method.

The supplied connection string will be used to establish a connection to the database to determine the outcome of the provided logical transaction id.

ODP.NET implicitly calls `GetOutcome` under the following conditions:

- Transaction Guard is enabled on the service
- `OracleException` is raised
- The exception is a recoverable error

When all of the above is true, then the `OracleException.OracleLogicalTransaction` property will be non-null.

If a connection is involved in a distributed transaction, then `GetOutcome` is *not* called implicitly and the `OracleException.OracleLogicalTransaction.LogicalTransactionId` property returns null.

 **Note:**

Once one server round-trip is incurred for the `GetOutcome()` invocation, the PL/SQL `ForceOutcome` is never invoked again against the server for a given `OracleLogicalTransaction` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

OracleOnsServerCollection Class

The `OracleOnsServerCollection` class supports adding to and deleting from a collection of logical servers with their corresponding list of nodes where the Oracle Notification Service (ONS) daemons are talking to their remote clients.

In case of remote configuration, the application has to specify the `<host>:<port>` values for every potential database that it can connect to. The `<host>:<port>` value pairs represent the ports on the different nodes.

Class Inheritance

`System.Object`

`Oracle.ManagedDataAccess.Client.OracleOnsServerCollection`

Declaration

```
// C#
public static class OracleOnsServerCollection
```

Requirements

Provider	ODP.NET Core
Assembly	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	4.6.1 or higher
.NET Core	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
using System;
using Oracle.ManagedDataAccess.Client;

namespace NetCoreApplication
{
    class OnsServersExample
    {
        static void Main(string[] args)
        {
            // Example to configure ONS Servers for the ODP.NET Core provider.

            // Add server through Add method on OracleOnsServerCollection
            OracleConfiguration.OracleOnsServers.Add("db1", "nodeList=host1:port1,
host2:port2, host3:port3");

            // Add server through indexer method on OracleOnsServerCollection
            OracleConfiguration.OracleOnsServers["db2"] = "nodeList=m1:p1, m2:p2";

            // Get number of servers configured
            int numServers = OracleConfiguration.OracleOnsServers.Count;

            // Get OracleOnsServerCollection object
            OracleOnsServerCollection serverColl = OracleConfiguration.OracleOnsServers;

            // Add server through Add method on OracleOnsServerCollection
            serverColl.Add("db3", "nodeList=host1:port1, host2:port2, host3:port3");

            // Add server through indexer method on OracleOnsServerCollection
            serverColl["db4"] = "nodeList=m1:p1, m2:p2";

            // Remove a server
            OracleConfiguration.OracleOnsServers.Remove("db2");

            // Get number of servers configured
            numServers = OracleConfiguration.OracleOnsServers.Count;

            // Get value corresponding to a server.
            string serverVal = OracleConfiguration.OracleOnsServers["db1"];

            OracleConnection orclCon = null;

            try
            {
                // Open a test connection
                orclCon = new OracleConnection("user id=scott; password=tiger; data
source=oracle");

                orclCon.Open();
                orclCon.Close();
            }
            catch (OracleException ex)
            {
                Console.WriteLine(ex);
            }
            finally
            {
                // Close the connection
                if (null != orclCon)
```



```

        orclCon.Close();
    }
}
}
}

```

 **See Also:**

- "Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"
- [OracleOnsServerCollection Members](#)
- [OracleOnsServerCollection Methods](#)
- [OracleOnsServerCollection Properties](#)

OracleOnsServerCollection Members

OracleOnsServerCollection members are listed in the following tables.

OracleOnsServerCollection Methods

OracleOnsServerCollection methods are listed in [Table 6-118](#).

Table 6-118 OracleOnsServerCollection Methods

Method	Description
Add	Adds unique entries in the OracleOnsServerCollection using logical server names and it's corresponding list of nodes
Remove	Removes an entry from an OracleOnsServerCollection

OracleOnsServerCollection Properties

OracleOnsServerCollection properties are listed in [Table 6-119](#).

Table 6-119 OracleOnsServerCollection Properties

Property	Description
Count	Returns the number of OracleOnsServerCollection elements
This	Returns or sets the an entry for a unique logical server name, which is to be associated with a list of nodes

OracleOnsServerCollection Methods

OracleOnsServerCollection methods are listed in [Table 6-120](#).

Table 6-120 OracleOnsServerCollection Methods

Method	Description
Add	Adds unique entries in the OracleOnsServerCollection using logical server names and it's corresponding list of nodes
Remove	Removes an entry from an OracleOnsServerCollection

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleOnsServerCollection Class](#)
- [OracleOnsServerCollection Members](#)

Add


This method adds unique entries in the OracleOnsServerCollection using logical server names and it's corresponding list of nodes.

Declaration

```
// C#  
public void Add(string serverName, string nodeList)
```

Parameters

- `serverName`
 - Type: `System.String`
 - A unique logical name for a list of nodes to be added
- `nodeList`
 - Type: `System.String`
 - Node names and remote ports for the list of nodes that ODP.NET shares ONS communication with using the following example format:
`nodeList=racnode1:4200, racnode2:4200`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleOnsServerCollection Class](#)
- [OracleOnsServerCollection Members](#)

Remove

This method removes an entry from an `OracleOnsServerCollection`.

Declaration

```
// C#  
public void Remove(string serverName)
```

Parameters

`serverName`

- **Type:** `System.String`
- A unique logical name for a list of nodes to be removed

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleOnsServerCollection Class](#)
- [OracleOnsServerCollection Members](#)

OracleOnsServerCollection Properties

`OracleOnsServerCollection` properties are listed in [Table 6-121](#).

Table 6-121 OracleOnsServerCollection Properties

Property	Description
Count	Returns the number of <code>OracleOnsServerCollection</code> elements
This	Returns or sets the an entry for a unique logical server name, which is to be associated with a list of nodes

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDataSourceCollection Class](#)
- [OracleDataSourceCollection Members](#)

Count

This is a read-only property that returns the number of `OracleOnsServerCollection` elements.

Declaration

```
// C#  
public int Count { get; }
```

Property Value

Type: `System.Int32`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleOnsServerCollection Class](#)
- [OracleOnsServerCollection Members](#)

This

This property returns or sets the an entry for a unique logical server name, which is to be associated with a list of nodes.

Declaration

```
// C#  
public string this[string serverName] { get; set; }
```

Parameters

- `serverName`
 - Type: `System.String`
 - Unique logical server name to be added or updated
- `Value`
 - Type: `System.String`

- Node names and remote ports for the list of nodes that ODP.NET shares ONS communication with using the following example format:
nodeList=racnode1:4200, racnode2:4200

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleOnsServerCollection Class](#)
- [OracleOnsServerCollection Members](#)

OracleParameter Class

An `OracleParameter` object represents a parameter for an `OracleCommand` or a `DataSet` column.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.Data.Common.DbParameter`

`Oracle.DataAccess.Client.OracleParameter`

Declaration

```
// C#
public sealed class OracleParameter : DbParameter, IDisposable, ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Exceptions

`ArgumentException` - The type binding is invalid.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleParameterSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleParameter[] prm = new OracleParameter[3];

        // Create OracleParameter objects through OracleParameterCollection
        OracleCommand cmd = con.CreateCommand();

        cmd.CommandText = "select max(empno) from emp";
        int maxno = int.Parse(cmd.ExecuteScalar().ToString());

        prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
            maxno + 10, ParameterDirection.Input);
        prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
            "Client", ParameterDirection.Input);
        prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
            10, ParameterDirection.Input);
        cmd.CommandText =
            "insert into emp(empno, ename, deptno) values(:1, :2, :3)";
        cmd.ExecuteNonQuery();

        Console.WriteLine("Record for employee id {0} has been inserted.",
            maxno + 10);
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Members](#)
- [OracleParameter Constructors](#)
- [OracleParameter Static Methods](#)
- [OracleParameter Properties](#)
- [OracleParameter Public Methods](#)

OracleParameter Members

OracleParameter members are listed in the following tables.

OracleParameter Constructors

OracleParameter constructors are listed in [Table 6-122](#).

Table 6-122 OracleParameter Constructors

Constructor	Description
OracleParameter Constructors	Instantiates a new instance of OracleParameter class (Overloaded)

OracleParameter Static Methods

OracleParameter static methods are listed in [Table 6-123](#).

Table 6-123 OracleParameter Static Methods

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleParameter Properties

OracleParameter properties are listed in [Table 6-124](#).

Table 6-124 OracleParameter Properties

Property	Description
ArrayBindSize	Specifies the input or output size of elements in Value property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
ArrayBindStatus	Specifies the input or output status of elements in Value property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
CollectionType	Specifies whether or not the OracleParameter represents a collection, and if so, specifies the collection type
DbType	Specifies the data type of the parameter using the Data.DbType enumeration type
Direction	Specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter
IsNullable	Not supported
Offset	Specifies the offset to the Value property or offset to the elements in the Value property
OracleDbType	Specifies the Oracle data type
OracleDbTypeEx	Specifies the Oracle data type to bind the parameter as, but returns a .NET type as output

Table 6-124 (Cont.) OracleParameter Properties

Property	Description
ParameterName	Specifies the name of the parameter
Precision	Specifies the maximum number of digits used to represent the Value property
Scale	Specifies the number of decimal places to which Value property is resolved
Size	Specifies the maximum size, in bytes or characters, of the data transmitted to or from the database. For PL/SQL Associative Array Bind, Size specifies the maximum number of elements in PL/SQL Associative Array
SourceColumn	Specifies the name of the DataTable Column of the DataSet
SourceColumnNullMapping	Specifies a value which indicates whether the source column is nullable
SourceVersion	Specifies the DataRowVersion value to use when loading the Value property of the parameter
Status	Indicates the status of the execution related to the data in the Value property
UdtTypeName	Specifies the Oracle user-defined type name if the parameter is a user-defined data type
Value	Specifies the value of the Parameter

OracleParameter Public Methods

OracleParameter public methods are listed in [Table 6-125](#).

Table 6-125 OracleParameter Public Methods

Public Method	Description
Clone	Creates a shallow copy of an OracleParameter object
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Releases allocated resources
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
ResetDbType	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter
ResetOracleDbType	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter

Table 6-125 (Cont.) OracleParameter Public Methods

Public Method	Description
ToString	Returns the string representation of the current instance

 See Also:

- "Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"
- [OracleParameter Class](#)

OracleParameter Constructors

`OracleParameter` constructors instantiate new instances of the `OracleParameter` class.

Overload List:

- [OracleParameter\(\)](#)
This constructor instantiates a new instance of `OracleParameter` class.
- [OracleParameter\(string, OracleDbType\)](#)
This constructor instantiates a new instance of `OracleParameter` class using the supplied parameter name and Oracle data type.
- [OracleParameter\(string, object\)](#)
This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name and parameter value.
- [OracleParameter\(string, OracleDbType, ParameterDirection\)](#)
This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and parameter direction.
- [OracleParameter\(string, OracleDbType, object, ParameterDirection\)](#)
This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, value, and direction.
- [OracleParameter\(string, OracleDbType, int\)](#)
This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and size.
- [OracleParameter\(string, OracleDbType, int, string\)](#)
This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, and source column.
- [OracleParameter\(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object\)](#)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, direction, null indicator, precision, scale, source column, source version and parameter value.

- [OracleParameter\(string, OracleDbType, int, object, ParameterDirection\)](#)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, value, and direction.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleParameter()

This constructor instantiates a new instance of `OracleParameter` class.

Declaration

```
// C#  
public OracleParameter();
```

Remarks

Default Values:

- `DbType` - String
- `ParameterDirection` - Input
- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["OracleParameterCollection Class"](#)

OracleParameter(string, OracleDbType)

This constructor instantiates a new instance of `OracleParameter` class using the supplied parameter name and Oracle data type.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType oraType);
```

Parameters

- *parameterName*
The parameter name.
- *oraType*
The data type of the `OracleParameter`.

Remarks

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- `DbType` - `String`
- `ParameterDirection` - `Input`
- `isNullable` - `true`
- `offset` - `0`
- `OracleDbType` - `Varchar2`
- `ParameterAlias` - `Empty string`
- `ParameterName` - `Empty string`
- `Precision` - `0`
- `Size` - `0`
- `SourceColumn` - `Empty string`
- `SourceVersion` - `Current`

- `ArrayBindStatus` - Success
- `Value` - null

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["OracleParameterCollection Class"](#)

OracleParameter(string, object)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name and parameter value.

Declaration

```
// C#  
public OracleParameter(string parameterName, object obj);
```

Parameters

- *parameterName*
The parameter name.
- *obj*
The value of the `OracleParameter`.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- `DbType` - String
- `ParameterDirection` - Input
- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string

- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["OracleParameterCollection Class"](#)

OracleParameter(string, OracleDbType, ParameterDirection)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and parameter direction.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType type,  
    ParameterDirection direction);
```

Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the `OracleParameter`.
- *direction*
The direction of the `OracleParameter`.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string

- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["OracleParameterCollection Class"](#)

OracleParameter(string, OracleDbType, object, ParameterDirection)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, value, and direction.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType type, object obj,  
    ParameterDirection direction);
```

Parameters

- `parameterName`
The parameter name.
- `type`
The data type of the `OracleParameter`.
- `obj`
The value of the `OracleParameter`.
- `direction`
The `ParameterDirection` value.

Remarks

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["OracleParameterCollection Class"](#)

OracleParameter(string, OracleDbType, int)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and size.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType type,  
    int size);
```

Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the `OracleParameter`.

- *size*
The size of the OracleParameter value.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["OracleParameterCollection Class"](#)

OracleParameter(string, OracleDbType, int, string)

This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, and source column.

Declaration

```
// C#
public OracleParameter(string parameterName, OracleDbType type, int size,
    string srcColumn);
```


Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the OracleParameter.
- *size*
The size of the OracleParameter value.
- *srcColumn*
The name of the source column.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)

OracleParameter(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, direction, null indicator, precision, scale, source column, source version and parameter value.

Declaration

```
// C#
public OracleParameter(string parameterName, OracleDbType oraType,
    int size, ParameterDirection direction, bool isNullable, byte
    precision, byte scale, string srcColumn, DataRowVersion srcVersion,
    object obj);
```

Parameters

- *parameterName*
The parameter name.
- *oraType*
The data type of the `OracleParameter`.
- *size*
The size of the `OracleParameter` value.
- *direction*
The `ParameterDirection` value.
- *isNullable*
An indicator that specifies if the parameter value can be null.
- *precision*
The precision of the parameter value.
- *scale*
The scale of the parameter value.
- *srcColumn*
The name of the source column.
- *srcVersion*
The `DataRowVersion` value.
- *obj*
The parameter value.

Exceptions

`ArgumentException` - The supplied value does not belong to the type of `Value` property in any of the `OracleTypes`.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)

OracleParameter(string, OracleDbType, int, object, ParameterDirection)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, value, and direction.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType type, int size,  
    object obj, ParameterDirection direction);
```

Parameters

- *parameterName*
The parameter name.
- *type*

The data type of the `OracleParameter`.

- *size*

The size of the `OracleParameter` value.

- *obj*

The value of the `OracleParameter`.

- *direction*

The `ParameterDirection` value.

Remarks

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- `DbType` - String
- `ParameterDirection` - Input
- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["OracleParameterCollection Class"](#)

OracleParameter Static Methods

The `OracleParameter` static method is listed in [Table 6-126](#).

Table 6-126 OracleParameter Static Method

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleParameter Properties

`OracleParameter` properties are listed in [Table 6-127](#).

Table 6-127 OracleParameter Properties

Property	Description
ArrayBindSize	Specifies the input or output size of elements in <code>Value</code> property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
ArrayBindStatus	Specifies the input or output status of elements in <code>Value</code> property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution
CollectionType	Specifies whether or not the <code>OracleParameter</code> represents a collection, and if so, specifies the collection type
DbType	Specifies the data type of the parameter using the <code>Data.DbType</code> enumeration type
Direction	Specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter
IsNullable	Not supported
Offset	Specifies the offset to the <code>Value</code> property or offset to the elements in the <code>Value</code> property
OracleDbType	Specifies the Oracle data type
OracleDbTypeEx	Specifies the Oracle data type to bind the parameter as, but returns a .NET type as output
ParameterName	Specifies the name of the parameter

Table 6-127 (Cont.) OracleParameter Properties

Property	Description
Precision	Specifies the maximum number of digits used to represent the Value property
Scale	Specifies the number of decimal places to which Value property is resolved
Size	Specifies the maximum size, in bytes or characters, of the data transmitted to or from the database. For PL/SQL Associative Array Bind, Size specifies the maximum number of elements in PL/SQL Associative Array
SourceColumn	Specifies the name of the DataTable Column of the DataSet
SourceColumnNullMapping	Specifies a value which indicates whether the source column is nullable
SourceVersion	Specifies the DataRowVersion value to use when loading the Value property of the parameter
Status	Indicates the status of the execution related to the data in the Value property
UdtTypeName	Specifies the Oracle user-defined type name if the parameter is a user-defined data type
Value	Specifies the value of the Parameter

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ArrayBindSize

This property specifies the maximum size, in bytes or characters, of the data for each array element transmitted to or from the database. This property is used for Array Bind or PL/SQL Associative Array execution.

Declaration

```
// C#  
public int[] ArrayBindSize {get; set; }
```

Property Value

An array of int values specifying the size.

Remarks

Default = null.

This property is only used for variable size element types for an Array Bind or PL/SQL Associative Array. For fixed size element types, this property is ignored.

Each element in the `ArrayBindSize` corresponds to the bind size of an element in the `Value` property. Before execution, `ArrayBindSize` specifies the maximum size of each element to be bound in the `Value` property. After execution, it contains the size of each element returned in the `Value` property.

For binding a PL/SQL Associative Array, whose elements are of a variable-length element type, as an `InputOutput`, `Out`, or `ReturnValue` parameter, this property must be set properly. The number of elements in `ArrayBindSize` must be equal to the value specified in the `OracleParameter.Size` property.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindSizeSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleParameter[] prm = new OracleParameter[3];

        // Create OracleParameter objects through OracleParameterCollection
        OracleCommand cmd = con.CreateCommand();

        cmd.CommandText = "select max(empno) from emp";
        int maxno = int.Parse(cmd.ExecuteScalar().ToString());

        // Set the ArrayBindCount for Array Binding
        cmd.ArrayBindCount = 2;

        prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
            new int[2] {maxno + 10, maxno + 11}, ParameterDirection.Input);
        prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
            new string[2] {"Client1xxx", "Client2xxx"}, ParameterDirection.Input);
        prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
            new int[2] {10, 10}, ParameterDirection.Input);

        // Set the ArrayBindSize for prm[1]
        // These sizes indicate the maximum size of the elements in Value property
        prm[1].ArrayBindSize = new int[2];
        prm[1].ArrayBindSize[0] = 7; // Set ename = "Client1"
        prm[1].ArrayBindSize[1] = 7; // Set ename = "Client2"

        cmd.CommandText =
            "insert into emp(empno, ename, deptno) values(:1, :2, :3)";

        cmd.ExecuteNonQuery();

        Console.WriteLine("Record for employee id {0} has been inserted.",
            maxno + 10);
    }
}
```

```
        Console.WriteLine("Record for employee id {0} has been inserted.",
            maxno + 11);

        prm[0].Dispose();
        prm[1].Dispose();
        prm[2].Dispose();
        cmd.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount "](#)
- ["Size " and "Value " for more information on binding Associative Arrays](#)
- ["ArrayBindStatus "](#)

ArrayBindStatus

This property specifies the input or output status of each element in the `Value` property before or after an Array Bind or PL/SQL Associative Array execution.

Declaration

```
// C#
public OracleParameterStatus[] ArrayBindStatus { get; set; }
```

Property Value

An array of `OracleParameterStatus` enumerated values.

Exceptions

`ArgumentOutOfRangeException` - The `Status` value specified is invalid.

Remarks

Default = null.

`ArrayBindStatus` is used for Array Bind and PL/SQL Associative Array execution only.

Before execution, `ArrayBindStatus` indicates the bind status of each element in the `Value` property. After execution, it contains the execution status of each element in the `Value` property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount "](#)
- ["OracleParameterStatus Enumeration"](#)
- ["Value "](#) for more information on binding Associative Arrays
- ["ArrayBindSize "](#)

CollectionType

This property specifies whether or not the `OracleParameter` represents a collection, and if so, specifies the collection type.

Declaration

```
// C#  
public OracleCollectionType CollectionType { get; set; }
```

Property Value

An `OracleCollectionType` enumerated value.

Exceptions

`ArgumentException` - The `OracleCollectionType` value specified is invalid.

Remarks

Default = `OracleCollectionType.None`. If `OracleParameter` is used to bind a PL/SQL Associative Array, then `CollectionType` must be set to `OracleCollectionType.PLSQLAssociativeArray`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

DbType

This property specifies the data type of the parameter using the `Data.DbType` enumeration type.

Declaration

```
// C#  
public override DbType DbType {get; set; }
```

Property Value

A DbType enumerated value.

Implements

IDataParameter

Exceptions

ArgumentException - The DbType value specified is invalid.

Remarks

Default = DbType.String

DbType is the data type of each element in the array if the OracleParameter object is used for Array Bind or PL/SQL Associative Array Bind execution.

Due to the link between DbType and OracleDbType properties, if the DbType property is set, the OracleDbType property is inferred from DbType.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Inference of OracleDbType from DbType"](#)
- ["CollectionType"](#)

Direction

This property specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter.

Declaration

```
// C#  
public override ParameterDirection Direction { get; set; }
```

Property Value

A ParameterDirection enumerated value.

Implements

IDataParameter

Exceptions

ArgumentOutOfRangeException - The ParameterDirection value specified is invalid.

Remarks

Default = ParameterDirection.Input

Possible values: Input, InputOutput, Output, and ReturnValue.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

IsNull

This property is not supported.

Declaration

```
// C#  
public override bool IsNull { get; set; }
```

Implements

IDataParameter

Property Value

This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Offset

This property specifies the offset to the Value property.

Declaration

```
// C#  
public int Offset { get; set; }
```

Property Value

An `int` that specifies the offset.

Exceptions

`ArgumentOutOfRangeException` - The `Offset` value specified is invalid.

Remarks

Default = 0

For `Array Bind` and `PL/SQL Associative Array Bind`, `Offset` applies to every element in the `Value` property.

The `Offset` property is used for binary and string data types. The `Offset` property represents the number of bytes for binary types and the number of characters for strings. The count for strings does not include the terminating character if a `null` is referenced. The `Offset` property is used by parameters of the following types:

- `OracleDbType.BFile`
- `OracleDbType.Blob`
- `OracleDbType.LongRaw`
- `OracleDbType.Raw`
- `OracleDbType.Char`
- `OracleDbType.Clob`
- `OracleDbType.NClob`
- `OracleDbType.NChar`
- `OracleDbType.NVarchar2`
- `OracleDbType.Varchar2`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleDbType

This property specifies the Oracle data type.

Declaration

```
// C#  
public OracleDbType OracleDbType { get; set; }
```

Property Value

An `OracleDbType` enumerated value.

Remarks

Default = `OracleDbType.Varchar2`

If the `OracleParameter` object is used for Array Bind or PL/SQL Associative Array Bind execution, `OracleDbType` is the data type of each element in the array.

The `OracleDbType` property and `DbType` property are linked. Therefore, setting the `OracleDbType` property changes the `DbType` property to a supporting `DbType`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#)
- ["Inference of DbType from OracleDbType"](#)
- ["CollectionType"](#)

OracleDbTypeEx

This property specifies the Oracle data type to bind the parameter as, but returns a .NET type as output.

Declaration

```
// C#  
public OracleDbType OracleDbTypeEx { get; set; }
```

Property Value

An `OracleDbType` enumerated value.

Remarks

This property is used by applications that need to bind a parameter value as an Oracle type, but need a .NET type back for output. This property should be used with an output or input/output parameter. For an input parameter, using `OracleDbTypeEx` has the same affect as using `OracleDbType`. The .NET type that is returned for the output is the .NET type that the Oracle type closely maps to.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#)
- ["OracleDbType "](#)
- ["Inference of DbType from OracleDbType"](#)
- ["CollectionType"](#)

ParameterName

This property specifies the name of the parameter.

Declaration

```
// C#  
public override string ParameterName { get; set; }
```

Property Value

String

Implements

IDataParameter

Remarks

Default = null

Oracle supports ParameterName up to 30 characters.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Precision

This property specifies the maximum number of digits used to represent the Value property.

Declaration

```
// C#  
Public byte Precision { get; set; }
```

Property Value

byte

Remarks

Default = 0

The `Precision` property is used by parameters of type `OracleDbType.Decimal`.

Oracle supports `Precision` range from 0 to 38.

For Array Bind and PL/SQL Associative Array Bind, `Precision` applies to each element in the `Value` property.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Value "](#)

Scale

This property specifies the number of decimal places to which `Value` property is resolved.

Declaration

```
// C#  
public byte Scale { get; set; }
```

Property Value

byte

Remarks

Default = 0.

`Scale` is used by parameters of type `OracleDbType.Decimal`.

Oracle supports `Scale` between -84 and 127.

For Array Bind and PL/SQL Associative Array Bind, `Scale` applies to each element in the `Value` property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Value "](#)

Size

This property specifies the maximum size, in bytes or characters, of the data transmitted to or from the database.

Declaration

```
// C#  
public override int Size { get; set; }
```

Property Value

int

Exceptions

`ArgumentOutOfRangeException` - The `Size` value specified is invalid.

`InvalidOperationException` - The `Size = 0` when the `OracleParameter` object is used to bind a PL/SQL Associative Array.

Remarks

If `Size` is not explicitly set, it is inferred from the actual size of the specified parameter value when binding only for input parameters. Output parameters must have their size defined explicitly.

The default value is 0.

Before execution, this property specifies the maximum size to be bound in the `Value` property. After execution, it contains the size of the type in the `Value` property.

`Size` is used for parameters of the following types:

- `OracleDbType.Blob`
- `OracleDbType.Char`
- `OracleDbType.Clob`
- `OracleDbType.LongRaw`
- `OracleDbType.NChar`
- `OracleDbType.NClob`
- `OracleDbType.NVarchar2`
- `OracleDbType.Raw`

- `OracleDbType.VarChar2`

For the preceding types, the `Size` property describes the maximum amount of data transmitted to or from the database. For character data, `Size` is in number of characters and for binary data, it is in number of bytes.

For fixed length data types, the value of `Size` is ignored.

If the `Size` is not explicitly set, it is inferred from the actual size of the specified parameter value when binding.

 **Note:**

`Size` does not include the null terminating character for the string data.

If the `OracleParameter` object is used to bind a PL/SQL Associative Array, `Size` specifies the maximum number of elements in the PL/SQL Associative Array. Before the execution, this property specifies the maximum number of elements in the PL/SQL Associative Array. After the execution, it specifies the current number of elements returned in the PL/SQL Associative Array. For `Output` and `InputOutput` parameters and return values, `Size` specifies the maximum number of elements in the PL/SQL Associative Array.

ODP.NET does not support binding an empty PL/SQL Associative Array. Therefore, `Size` cannot be set to 0 when the `OracleParameter` object is used to bind a PL/SQL Associative Array.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#)
- ["CollectionType"](#)
- ["ArrayBindSize "](#)
- ["ArrayBindStatus "](#)
- ["Value "](#)

SourceColumn

This property specifies the name of the `DataTable Column` of the `DataSet`.

Declaration

```
// C#  
public override string SourceColumn { get; set; }
```

Property Value

A string.

Implements

IDataParameter

Remarks

Default = empty string

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

SourceColumnNullMapping

This property specifies a value which indicates whether the source column is nullable.

Declaration

```
// C#  
public bool SourceColumnNullMapping { get; set; }
```

Property Value

Returns `true` if the source column can be nullified; otherwise, returns `false`.

Remarks

The default value is `false`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

SourceVersion

This property specifies the `DataRowVersion` value to use when loading the `Value` property of the parameter.

Declaration

```
// C#  
public override DataRowVersion SourceVersion { get; set; }
```

Property Value

DataRowVersion

Implements

IDataParameter

Exceptions

ArgumentOutOfRangeException - The DataRowVersion value specified is invalid.

Remarks

Default = DataRowVersion.Current

SourceVersion is used by the OracleDataAdapter.UpdateCommand() during the OracleDataAdapter.Update to determine whether the original or current value is used for a parameter value. This allows primary keys to be updated. This property is ignored by the OracleDataAdapter.InsertCommand() and the OracleDataAdapter.DeleteCommand().



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Status

This property indicates the status of the execution related to the data in the Value property.

Declaration

```
// C#  
public OracleParameterStatus Status { get; set; }
```

Property Value

An OracleParameterStatus enumerated value.

Exceptions

ArgumentOutOfRangeException - The Status value specified is invalid.

Remarks

Default = `OracleParameterStatus.Success`

Before execution, this property indicates the bind status related to the `Value` property. After execution, it returns the status of the execution.

Status indicates if:

- A `NULL` is fetched from a column.
- Truncation has occurred during the fetch; then `Value` was not big enough to hold the data.
- A `NULL` is to be inserted into a database column; then `Value` is ignored, and a `NULL` is inserted into a database column.

This property is ignored for Array Bind and PL/SQL Associative Array Bind. Instead, `ArrayBindStatus` property is used.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#)
- ["ArrayBindStatus "](#)

UdtTypeName

This property specifies the Oracle user-defined type name if the parameter is a user-defined data type.

Declaration

```
// C#  
public string UdtTypeName {get; set;}
```

Property Value

Name of the Oracle UDT.

Remarks

The `UdtTypeName` property corresponds to the user-defined type name of the parameter. This property must always be specified if the parameter is a user-defined type. Note that when a custom object is provided as an input parameter value, it is converted to the Oracle UDT that is specified by the custom type mapping on the connection used to execute the command. The Oracle UDT specified by the custom type mapping and by the `OracleParameter.UdtTypeName` property differs if the application binds a custom object that represents a subtype of the parameter type.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Value

This property specifies the value of the `Parameter`.

Declaration

```
// C#  
public override object Value { get; set; }
```

Property Value

An object.

Implements

`IDataParameter`

Exceptions

`ArgumentException` - The `Value` property specified is invalid.

`InvalidArgumentException`- The `Value` property specified is invalid.

Remarks

Default = null

If the `OracleParameter` object is used for Array Bind or PL/SQL Associative Array, `Value` is an array of parameter values.

The `Value` property can be overwritten by `OracleDataAdapter.Update()`.

The provider attempts to convert any type of value if it supports the `IConvertible` interface. Conversion errors occur if the specified type is not compatible with the value.

When sending a null parameter value to the database, the user must specify `DBNull`, not `null`. The null value in the system is an empty object that has no value. `DBNull` is used to represent null values. The user can also specify a null value by setting `Status` to `OracleParameterStatus.NullValue`. In this case, the provider sends a null value to the database.

If neither `OracleDbType` nor `DbType` are set, their values can be inferred by `Value`. Please see the following for related information:

- [Tables in section "Inference of DbType and OracleDbType from Value"](#)
- ["ArrayBindCount "](#)
- ["ArrayBindSize "](#)

- ["ArrayBindStatus "](#)
- ["OracleDbType Enumeration"](#)

For input parameters the value is:

- Bound to the `OracleCommand` that is sent to the database.
- Converted to the data type specified in `OracleDbType` or `DbType` when the provider sends the data to the database.

For output parameters the value is:

- Set on completion of the `OracleCommand` (true for return value parameters also).
- Set to the data from the database, to the data type specified in `OracleDbType` or `DbType`.

When array binding is used with:

- Input parameter - `Value` should be set to an array of values. `OracleCommand.ArrayBindCount` should be set to a value that is greater than zero to indicate the number of elements to be bound.

The number of elements in the array should be equal to the `OracleCommand.ArrayBindCount` property; otherwise, their minimum value is used to bind the elements in the array.

- Output parameter - `OracleCommand.ArrayBindCount` should be set to a value that is greater than zero to indicate the number of elements to be retrieved (for `SELECT` statements).

When PL/SQL Associative Array binding is used with:

- Input parameter – `Value` should be set to an array of values. `CollectionType` should be set to `OracleCollection.PLSQLAssociativeArray`. `Size` should be set to specify the possible maximum number of array elements in the PL/SQL Associative Array. If `Size` is smaller than the number of elements in `Value`, then `Size` specifies the number of elements in the `Value` property to be bound.
- Output parameter - `CollectionType` should be set to `OracleCollection.PLSQLAssociativeArray`. `Size` should be set to specify the maximum number of array elements in PL/SQL Associative Array.

Each parameter should have a value. To bind a parameter with a null value, set `Value` to `DBNull.Value`, or set `Status` to `OracleParameterStatus.NullInsert`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount "](#)
- ["OracleParameterStatus Enumeration"](#)

OracleParameter Public Methods

OracleParameter public methods are listed in [Table 6-128](#).

Table 6-128 OracleParameter Public Methods

Public Method	Description
Clone	Creates a shallow copy of an OracleParameter object
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Releases allocated resources
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
ResetDbType	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter
ResetOracleDbType	Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter
ToString	Returns the string representation of the current instance



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Clone

This method creates a shallow copy of an OracleParameter object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleParameter object.

Implements

ICloneable

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class CloneSample
{
    static void Main()
    {
        OracleParameter prm1 = new OracleParameter();

        // Prints "prm1.ParameterName = "
        Console.WriteLine("prm1.ParameterName = " + prm1.ParameterName);

        // Set the ParameterName before cloning
        prm1.ParameterName = "MyParam";

        // Clone the OracleParameter
        OracleParameter prm2 = (OracleParameter) prm1.Clone();

        // Prints "prm2.ParameterName = MyParam"
        Console.WriteLine("prm2.ParameterName = " + prm2.ParameterName);

        prm1.Dispose();
        prm2.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Dispose

This method releases resources allocated for an OracleParameter object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ResetDbType

This method resets the type associated with the parameter so that it can infer its type from the value passed in the parameter.

Declaration

```
// C#  
public override void ResetDbType();
```

Remarks

If an application does not set the `DbType` or `OracleDbType` properties of an `OracleParameter` object, then these values are inferred from the value set by the application to that `OracleParameter` object. Calling `ResetDbType` method resets these properties so that `OracleParameter` can again infer its type from the value passed into the `OracleParameter`. Calling this method affects both the `DbType` and `OracleDbType` properties of the `OracleParameter` object.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ResetOracleDbType

This method resets the type associated with the parameter so that it can infer its type from the value passed in the parameter.

Declaration

```
// C#  
public override void ResetOracleDbType();
```

Remarks

If an application does not set the `DbType` or `OracleDbType` properties of an `OracleParameter` object, then these values are inferred from the value set by the application to that `OracleParameter` object. Calling the `ResetOracleDbType` method resets these properties so that `OracleParameter` can again infer its type from the value passed into the `OracleParameter`. Calling this method affects both the `DbType` and `OracleDbType` properties of the `OracleParameter` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ToString

Overrides `Object`

This method returns the string representation of the current instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns the `OracleParameter` value in a string representation.

Remarks

If the current instance has a null value, the returned string is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleParameterCollection Class

An `OracleParameterCollection` class represents a collection of all parameters relevant to an `OracleCommand` object and their mappings to `DataSet` columns.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.Data.Common.DbParameterCollection`

`Oracle.DataAccess.Client.OracleParameterCollection`

Declaration

```
// C#
public sealed class OracleParameterCollection : DbParameterCollection,
    IDataParameterCollection, IList, ICollection, IEnumerable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The position of an `OracleParameter` added into the `OracleParameterCollection` is the binding position in the SQL statement. Position is 0-based and is used only for positional binding. If named binding is used, the position of an `OracleParameter` in the `OracleParameterCollection` is ignored.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleParameterCollectionSample
{
    static void Main()
```

```
{
    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    OracleConnection con = new OracleConnection(constr);
    con.Open();

    OracleParameter[] prm = new OracleParameter[3];

    // Create OracleParameter objects through OracleParameterCollection
    OracleCommand cmd = con.CreateCommand();

    cmd.CommandText = "select max(empno) from emp";
    int maxno = int.Parse(cmd.ExecuteScalar().ToString());

    prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
        maxno + 10, ParameterDirection.Input);
    prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
        "Client", ParameterDirection.Input);
    prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
        10, ParameterDirection.Input);
    cmd.CommandText =
        "insert into emp(empno, ename, deptno) values(:1, :2, :3)";
    cmd.ExecuteNonQuery();

    Console.WriteLine("Record for employee id {0} has been inserted.",
        maxno + 10);

    // Remove all parameters from OracleParameterCollection
    cmd.Parameters.Clear();

    prm[0].Dispose();
    prm[1].Dispose();
    prm[2].Dispose();
    cmd.Dispose();

    con.Close();
    con.Dispose();
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Members](#)
- [OracleParameterCollection Static Methods](#)
- [OracleParameterCollection Properties](#)
- [OracleParameterCollection Public Methods](#)

OracleParameterCollection Members

OracleParameterCollection members are listed in the following tables.

OracleParameterCollection Static Methods

OracleParameterCollection static methods are listed in [Table 6-129](#).

Table 6-129 OracleParameterCollection Static Methods

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleParameterCollection Properties

OracleParameterCollection properties are listed in [Table 6-130](#).

Table 6-130 OracleParameterCollection Properties

Property	Description
Count	Specifies the number of OracleParameters in the collection
Item	Gets and sets the OracleParameter object (Overloaded)
IsFixedSize	Gets a value that indicates whether the OracleParameterCollection has a fixed size
IsReadOnly	Gets a value that indicates whether the OracleParameterCollection is read-only
IsSynchronized	Gets a value that indicates whether the OracleParameterCollection is synchronized.
SyncRoot	Gets an object that can be used to synchronize access to the OracleParameterCollection

OracleParameterCollection Public Methods

OracleParameterCollection public methods are listed in [Table 6-131](#).

Table 6-131 OracleParameterCollection Public Methods

Public Method	Description
Add	Adds objects to the collection (Overloaded)
AddRange	Adds elements to the end of the OracleParameterCollection
Clear	Removes all the OracleParameter objects from the collection
Contains	Indicates whether or not objects exist in the collection (Overloaded)
CopyTo	Copies OracleParameter objects from the collection, starting with the supplied index to the supplied array
CreateObjRef	Inherited from System.MarshalByRefObject
Equals	Inherited from System.Object (Overloaded)

Table 6-131 (Cont.) OracleParameterCollection Public Methods

Public Method	Description
GetEnumerator	Returns an enumerator that iterates through the OracleParameterCollection
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
IndexOf	Returns the index of the objects in the collection (Overloaded)
Insert	Inserts the supplied OracleParameter to the collection at the specified index
Remove	Removes objects from the collection
RemoveAt	Removes objects from the collection by location (Overloaded)
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)

OracleParameterCollection Static Methods

The OracleParameterCollection static method is listed in [Table 6-132](#).

Table 6-132 OracleParameterCollection Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

OracleParameterCollection Properties

OracleParameterCollection properties are listed in [Table 6-133](#).

Table 6-133 OracleParameterCollection Properties

Property	Description
Count	Specifies the number of OracleParameters in the collection
Item	Gets and sets the OracleParameter object (Overloaded)
IsFixedSize	Gets a value that indicates whether the OracleParameterCollection has a fixed size
IsReadOnly	Gets a value that indicates whether the OracleParameterCollection is read-only
IsSynchronized	Gets a value that indicates whether the OracleParameterCollection is synchronized.
SyncRoot	Gets an object that can be used to synchronize access to the OracleParameterCollection



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Count

This property specifies the number of OracleParameter objects in the collection.

Declaration

```
// C#  
public override int Count {get;}
```

Property Value

The number of OracleParameter objects.

Implements

ICollection

Remarks

Default = 0

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Item

Item gets and sets the `OracleParameter` object.

Overload List:

- [Item\[int\]](#)
This property gets and sets the `OracleParameter` object at the index specified by the supplied `parameterIndex`.
- [Item\[string\]](#)
This property gets and sets the `OracleParameter` object using the parameter name specified by the supplied `parameterName`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Item[int]

This property gets and sets the `OracleParameter` object at the index specified by the supplied `parameterIndex`.

Declaration

```
// C#  
public object Item[int parameterIndex] {get; set;}
```

Property Value

An object.

Implements

`IList`

Exceptions

`IndexOutOfRangeException` - The supplied index does not exist.

Remarks

The `OracleParameterCollection` class is a zero-based index.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Item[string]

This property gets and sets the `OracleParameter` object using the parameter name specified by the supplied `parameterName`.

Declaration

```
// C#  
public OracleParameter Item[string parameterName] {get; set;};
```

Property Value

An `OracleParameter`.

Implements

`IDataParameterCollection`

Exceptions

`IndexOutOfRangeException` - The supplied parameter name does not exist.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IsFixedSize

IsFixedSize gets a value that indicates whether the OracleParameterCollection has a fixed size.

Declaration

```
// C#  
public override bool IsFixedSize { get; };
```

Property Value

Returns true if the OracleParameterCollection has a fixed size; otherwise false.

Implements

ICollection

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IsReadOnly

IsReadOnly gets a value that indicates whether the OracleParameterCollection is read-only.

Declaration

```
// C#  
public override bool IsReadOnly { get; };
```

Property Value

Returns true if the OracleParameterCollection is read only; otherwise false.

Implements

ICollection

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IsSynchronized

IsSynchronized gets a value that indicates whether the OracleParameterCollection is synchronized.

Declaration

```
// C#  
public override bool IsSynchronized { get; };
```

Property Value

Returns true if the OracleParameterCollection is synchronized; otherwise false.

Implements

ICollection

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

SyncRoot

SyncRoot gets an object that can be used to synchronize access to the OracleParameterCollection.

Declaration

```
// C#  
public override Object SyncRoot { get; };
```

Property Value

An object that can be used to synchronize access to the OracleParameterCollection.

Implements

ICollection

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

OracleParameterCollection Public Methods

OracleParameterCollection public methods are listed in [Table 6-134](#).

Table 6-134 OracleParameterCollection Public Methods

Public Method	Description
Add	Adds objects to the collection (Overloaded)
AddRange	Adds elements to the end of the OracleParameterCollection
Clear	Removes all the OracleParameter objects from the collection
Contains	Indicates whether or not objects exist in the collection (Overloaded)
CopyTo	Copies OracleParameter objects from the collection, starting with the supplied index to the supplied array
CreateObjRef	Inherited from System.MarshalByRefObject
Equals	Inherited from System.Object (Overloaded)
GetEnumerator	Returns an enumerator that iterates through the OracleParameterCollection
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
IndexOf	Returns the index of the objects in the collection (Overloaded)
Insert	Inserts the supplied OracleParameter to the collection at the specified index
Remove	Removes objects from the collection
RemoveAt	Removes objects from the collection by location (Overloaded)
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add

Add adds objects to the collection.

Overload List:

- [Add\(object\)](#)
This method adds the supplied object to the collection.
- [Add\(OracleParameter\)](#)
This method adds the supplied `OracleParameter` object to the collection.
- [Add\(string, object\)](#)
This method adds an `OracleParameter` object to the collection using the supplied name and object value.
- [Add\(string, OracleDbType\)](#)
This method adds an `OracleParameter` object to the collection using the supplied name and database type.
- [Add\(string, OracleDbType, ParameterDirection\)](#)
This method adds an `OracleParameter` object to the collection using the supplied name, database type, and direction.
- [Add\(string, OracleDbType, object, ParameterDirection\)](#)
This method adds an `OracleParameter` object to the collection using the supplied name, database type, parameter value, and direction.
- [Add\(string, OracleDbType, int, object, ParameterDirection\)](#)
This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, parameter value, and direction.
- [Add\(string, OracleDbType, int\)](#)
This method adds an `OracleParameter` object to the collection using the supplied name, database type, and size.
- [Add \(string, OracleDbType, int, string\)](#)
This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, and source column.
- [Add\(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, direction, null indicator, precision, scale, source column, source version, and parameter value.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(object)

This method adds the supplied object to the collection.

Declaration

```
// C#  
public override int Add(object obj);
```

Parameters

- *obj*
The supplied object.

Return Value

The index at which the new `OracleParameter` is added.

Implements

`IList`

Remarks

`InvalidCastException` - The supplied *obj* cannot be cast to an `OracleParameter` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(OracleParameter)

This method adds the supplied `OracleParameter` object to the collection.

Declaration

```
// C#  
public OracleParameter Add(OracleParameter paramObj);
```

Parameters

- *paramObj*
The supplied `OracleParameter` object.

Return Value

The newly created `OracleParameter` object which was added to the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, object)

This method adds an `OracleParameter` object to the collection using the supplied name and object value

Declaration

```
// C#  
public OracleParameter Add(string name, object val);
```

Parameters

- *name*
The parameter name.
- *val*
The `OracleParameter` value.

Return Value

The newly created `OracleParameter` object which was added to the collection.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, OracleDbType)

This method adds an `OracleParameter` object to the collection using the supplied name and database type.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.

Return Value

The newly created `OracleParameter` object which was added to the collection.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, OracleDbType, ParameterDirection)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and direction.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType,  
    ParameterDirection direction);
```


Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.
- *direction*
The `OracleParameter` direction.

Return Value

The newly created `OracleParameter` object which was added to the collection.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#)

Add(string, OracleDbType, object, ParameterDirection)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, parameter value, and direction.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType, object val,  
    ParameterDirection dir);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.
- *val*
The `OracleParameter` value.
- *dir*
The `ParameterDirection` value.

Return Value

The newly created `OracleParameter` object which was added to the collection.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class AddSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm = cmd.Parameters.Add(
            "MyParam", OracleDbType.Decimal, 1, ParameterDirection.Input);

        // Prints "cmd.Parameters.Count = 1"
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

        prm.Dispose();
        cmd.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#)

Add(string, OracleDbType, int, object, ParameterDirection)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, parameter value, and direction.

Declaration

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, int size,
    object val, ParameterDirection dir;
```

Parameters

- *name*
The parameter name.

- *dbType*
The data type of the `OracleParameter`.
- *size*
The size of `OracleParameter`.
- *val*
The `OracleParameter` value.
- *dir*
The `ParameterDirection` value.

Return Value

The newly created `OracleParameter` object which was added to the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#)

Add(string, OracleDbType, int)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and size.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType, int size);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.
- *size*
The size of `OracleParameter`.

Return Value

The newly created `OracleParameter` object which was added to the collection.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class AddSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add parameter to the OracleParameterCollection  
        OracleParameter prm = cmd.Parameters.Add(  
            "MyParam", OracleDbType.Varchar2, 10);  
  
        // Prints "cmd.Parameters.Count = 1"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        prm.Dispose();  
        cmd.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add (string, OracleDbType, int, string)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, and source column.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType, int size,  
    string srcColumn);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.
- *size*

The size of OracleParameter.

- *srcColumn*

The name of the source column.

Return Value

An OracleParameter.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)

This method adds an OracleParameter object to the collection using the supplied name, database type, size, direction, null indicator, precision, scale, source column, source version, and parameter value.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType, int size,  
    ParameterDirection dir, bool isNullable, byte precision,  
    byte scale, string srcColumn, DataRowVersion version, object val);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the OracleParameter.
- *size*
The size of OracleParameter.
- *dir*
The ParameterDirection value.
- *isNullable*
An indicator that specifies if the parameter value can be null.
- *precision*
The precision of the parameter value.
- *scale*

The scale of the parameter value.

- *srcColumn*

The name of the source column.

- *version*

The DataRowVersion value.

- *val*

The parameter value.

Return Value

The newly created `OracleParameter` object which was added to the collection.

Exceptions

`ArgumentException` - The type of supplied *val* does not belong to the type of `Value` property in any of the ODP.NET Types.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

AddRange

This method adds elements to the end of the `OracleParameterCollection`.

Declaration

```
// C#  
public override void AddRange(Array paramArray );
```

Parameters

paramArray

An array of `OracleParameter` objects.

Exceptions

`ArgumentNullException` - The input parameter is null.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Clear

This method removes all the `OracleParameter` objects from the collection.

Declaration

```
// C#  
public override void Clear();
```

Implements

```
IList
```

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ClearSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add parameter to the OracleParameterCollection  
        OracleParameter prm = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);  
  
        // Prints "cmd.Parameters.Count = 1"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        // Clear all parameters in the OracleParameterCollection  
        cmd.Parameters.Clear();  
  
        // Prints "cmd.Parameters.Count = 0"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        prm.Dispose();  
        cmd.Dispose();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Contains

Contains indicates whether or not the supplied object exists in the collection.

Overload List:

- [Contains\(object\)](#)
This method indicates whether or not the supplied object exists in the collection.
- [Contains\(string\)](#)
This method indicates whether or not an `OracleParameter` object exists in the collection using the supplied string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Contains(object)

This method indicates whether or not the supplied object exists in the collection.

Declaration

```
// C#  
public override bool Contains(object obj)
```

Parameters

- *obj*
The object.

Return Value

A `bool` that indicates whether or not the `OracleParameter` specified is inside the collection.

Implements

ICollection

Exceptions

InvalidOperationException - The supplied *obj* is not an OracleParameter object.

Remarks

Returns true if the collection contains the OracleParameter object; otherwise, returns false.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class ContainsSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm1 = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);

        // Check if the OracleParameterCollection contains prm1
        bool bContains = cmd.Parameters.Contains(prm1);

        // Prints "bContains = True"
        Console.WriteLine("bContains = " + bContains);

        OracleParameter prm2 = new OracleParameter();

        // Check if the OracleParameterCollection contains prm2
        bContains = cmd.Parameters.Contains(prm2);

        // Prints "bContains = False"
        Console.WriteLine("bContains = " + bContains);

        prm1.Dispose();
        prm2.Dispose();
        cmd.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Contains(string)

This method indicates whether or not an `OracleParameter` object exists in the collection using the supplied string.

Declaration

```
// C#  
public override bool Contains(string name);
```

Parameters

- *name*

The name of `OracleParameter` object.

Return Value

Returns `true` if the collection contains the `OracleParameter` object with the specified parameter name; otherwise, returns `false`.

Implements

`IDataParameterCollection`

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ContainsSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add parameter to the OracleParameterCollection  
        OracleParameter prm = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);  
  
        // Check if the OracleParameterCollection contains "MyParam"  
        bool bContains = cmd.Parameters.Contains("MyParam");  
  
        // Prints "bContains = True"  
        Console.WriteLine("bContains = " + bContains);  
  
        // Check if the OracleParameterCollection contains "NoParam"  
        bContains = cmd.Parameters.Contains("NoParam");  
  
        // Prints "bContains = False"  
        Console.WriteLine("bContains = " + bContains);  
  
        prm.Dispose();  
        cmd.Dispose();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

CopyTo

This method copies `OracleParameter` objects from the collection, starting with the supplied `index` to the supplied array.

Declaration

```
// C#  
public override void CopyTo(Array array, int index);
```

Parameters

- `array`
The specified array.
- `index`
The array index.

Implements

`ICollection`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

GetEnumerator

`GetEnumerator` returns an enumerator that iterates through the `OracleParameterCollection`.

Declaration

```
// C#  
public override IEnumerator GetEnumerator();
```

Implements

IEnumerable

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IndexOf

IndexOf returns the index of the `OracleParameter` object in the collection.

Overload List:

- [IndexOf\(object\)](#)
This method returns the index of the `OracleParameter` object in the collection.
- [IndexOf\(String\)](#)
This method returns the index of the `OracleParameter` object with the specified name in the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IndexOf(object)

This method returns the index of the `OracleParameter` object in the collection.

Declaration

```
// C#  
public override int IndexOf(object obj);
```

Parameters

- *obj*
The specified object.

Return Value

Returns the index of the `OracleParameter` object in the collection.

Implements

`IList`

Exceptions

`InvalidCastException` - The supplied `obj` cannot be cast to an `OracleParameter` object.

Remarks

Returns the index of the supplied `OracleParameter obj` in the collection.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IndexOf(String)

This method returns the index of the `OracleParameter` object with the specified name in the collection.

Declaration

```
// C#  
public override int IndexOf(String name);
```

Parameters

- *name*
The name of parameter.

Return Value

Returns the index of the supplied `OracleParameter` in the collection.

Implements

`IDataParameterCollection`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Insert

This method inserts the supplied `OracleParameter` object to the collection at the specified `index`.

Declaration

```
// C#  
public override void Insert(int index, object obj);
```

Parameters

- `index`
The specified index.
- `obj`
The `OracleParameter` object.

Implements

`IList`

Remarks

An `InvalidCastException` is thrown if the supplied `obj` cannot be cast to an `OracleParameter` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Remove

This method removes the supplied `OracleParameter` from the collection.

Declaration

```
// C#  
public override void Remove(object obj);
```

Parameters

- *obj*

The specified object to remove.

Implements

IList

Exceptions

InvalidCastException - The supplied *obj* cannot be cast to an OracleParameter object.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class RemoveSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add 2 parameters to the OracleParameterCollection  
        OracleParameter prm1 = cmd.Parameters.Add("MyParam1", OracleDbType.Decimal);  
        OracleParameter prm2 = cmd.Parameters.Add("MyParam2", OracleDbType.Decimal);  
  
        // Prints "cmd.Parameters.Count = 2"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        // Remove the 1st parameter from the OracleParameterCollection  
        cmd.Parameters.Remove(prm1);  
  
        // Prints "cmd.Parameters.Count = 1"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        // Prints "cmd.Parameters[0].ParameterName = MyParam2"  
        Console.WriteLine("cmd.Parameters[0].ParameterName = " +  
            cmd.Parameters[0].ParameterName);  
  
        prm1.Dispose();  
        prm2.Dispose();  
        cmd.Dispose();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

RemoveAt

RemoveAt removes the `OracleParameter` object from the collection by location.

Overload List:

- [RemoveAt\(int\)](#)

This method removes from the collection the `OracleParameter` object located at the index specified by the supplied index.

- [RemoveAt\(String\)](#)

This method removes from the collection the `OracleParameter` object specified by the supplied name.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

RemoveAt(int)

This method removes from the collection the `OracleParameter` object located at the index specified by the supplied index.

Declaration

```
// C#  
public override void RemoveAt(int index);
```

Parameters

- *index*

The specified index from which the `OracleParameter` is to be removed.

Implements

`IList`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

RemoveAt(String)

This method removes from the collection the `OracleParameter` object specified by the supplied name.

Declaration

```
// C#  
public override void RemoveAt(String name);
```

Parameters

- *name*
The name of the `OracleParameter` object to be removed from the collection.

Implements

`IDataParameterCollection`

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

OraclePermission Class

An `OraclePermission` object enables ODP.NET to enforce imperative security and helps ensure that a user has a security level adequate for accessing data.

Class Inheritance

```
System.Object  
  
System.Security.CodeAccessPermission  
  
System.Data.Common.DBDataPermission  
  
Oracle.DataAccess.Client.OraclePermission
```

Declaration

```
// C#
public class OraclePermission: DBDataPermission
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Members](#)
- [OraclePermission Constructor](#)
- [OraclePermission Static Methods](#)
- [OraclePermission Public Properties](#)
- [OraclePermission Public Methods](#)

OraclePermission Members

OraclePermission members are listed in the following tables.

OraclePermission Constructors

The OraclePermission constructor is listed in [Table 6-135](#).

Table 6-135 OraclePermission Constructor

Constructor	Description
OraclePermission Constructor	Instantiates a new instance of the OraclePermission class.

OraclePermission Static Methods

The OraclePermission static methods are listed in [Table 6-136](#).

Table 6-136 OraclePermission Static Methods

Static Method	Description
Equals	Inherited from System.Object
ReferenceEquals	Inherited from System.Object
RevertAll	Inherited from CodeAccessPermission
RevertAssert	Inherited from CodeAccessPermission
RevertDeny	Inherited from CodeAccessPermission
RevertPermitOnly	Inherited from CodeAccessPermission

OraclePermission Public Properties

The OraclePermission public methods are listed in [Table 6-140](#).

Table 6-137 OraclePermission Public Properties

Public Properties	Description
AllowBlankPassword	Inherited from DBDataPermission OraclePermission does not support this property.

OraclePermission Public Methods

The OraclePermission public methods are listed in [Table 6-138](#).

Table 6-138 OraclePermission Public Methods

Public Method	Description
Add	Adds a new connection string fragment and a list of restricted keywords to the OraclePermission object
Assert	Inherited from CodeAccessPermission
Copy	Returns a copy of the current permission object
Demand	Inherited from CodeAccessPermission
Deny	Inherited from CodeAccessPermission
Equals	Inherited from CodeAccessPermission
FromXml	Inherited from DBDataPermission
GetHashCode	Inherited from CodeAccessPermission
GetType	Inherited from System.Object
Intersect	Inherited from DBDataPermission
IsSubsetOf	Returns a boolean value that indicates whether or not the current permission is a subset of the target permission
IsUnrestricted	Inherited from DBDataPermission

Table 6-138 (Cont.) OraclePermission Public Methods

Public Method	Description
PermitOnly	Inherited from CodeAccessPermission
ToString	Inherited from CodeAccessPermission
ToXml	Inherited from DBDataPermission
Union	Inherited from DBDataPermission

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)

OraclePermission Constructor

The OraclePermission constructor instantiates a new instance of the OraclePermission class.

Declaration

```
// C#  
public OraclePermission (PermissionState state);
```

Parameters

- *state*

The *state* parameter takes one of the following two values:
PermissionState.None OR PermissionState.Unrestricted.

Exceptions

ArgumentException - The PermissionState value is invalid.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermission Static Methods

The `OraclePermission` static methods are listed in [Table 6-139](#).

Table 6-139 OraclePermission Static Methods

Static Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
<code>ReferenceEquals</code>	Inherited from <code>System.Object</code>
<code>RevertAll</code>	Inherited from <code>CodeAccessPermission</code>
<code>RevertAssert</code>	Inherited from <code>CodeAccessPermission</code>
<code>RevertDeny</code>	Inherited from <code>CodeAccessPermission</code>
<code>RevertPermitOnly</code>	Inherited from <code>CodeAccessPermission</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermission Public Properties

The `OraclePermission` public methods are listed in [Table 6-140](#).

Table 6-140 OraclePermission Public Properties

Public Properties	Description
<code>AllowBlankPassword</code>	Inherited from <code>DBDataPermission</code> <code>OraclePermission</code> ignores the value of this property. Any value set for this property, for an <code>OraclePermission</code> object, is ignored.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermission Public Methods

The OraclePermission public methods are listed in [Table 6-141](#).

Table 6-141 OraclePermission Public Methods

Public Method	Description
Add	Adds a new connection string fragment and a list of restricted keywords to the OraclePermission object
Assert	Inherited from CodeAccessPermission
Copy	Returns a copy of the current permission object
Demand	Inherited from CodeAccessPermission
Deny	Inherited from CodeAccessPermission
Equals	Inherited from CodeAccessPermission
FromXml	Inherited from DBDataPermission
GetHashCode	Inherited from CodeAccessPermission
GetType	Inherited from System.Object
Intersect	Inherited from DBDataPermission
IsSubsetOf	Returns a boolean value that indicates whether or not the current permission is a subset of the target permission
IsUnrestricted	Inherited from DBDataPermission
PermitOnly	Inherited from CodeAccessPermission
ToString	Inherited from CodeAccessPermission
ToXml	Inherited from DBDataPermission
Union	Inherited from DBDataPermission

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

Add

This method adds a new connection string fragment and a list of restricted keywords to the OraclePermission object.

Declaration

```
// C#  
public void Add(string connStr, string keyRestrict,  
    KeyRestrictionBehavior behavior);
```

Parameters

- *connStr*
The connection string fragment.
- *keyRestrict*
The key restrictions.
- *behavior*
One of the following `KeyRestrictionBehavior` enumerations:
 - `AllowOnly`
 - `PreventUsage`

Exceptions

`ArgumentException` - The `KeyRestrictionBehavior` value or the format of the *connStr* or *keyRestrict* string is invalid.

Remarks

The `Add` method configures the connection strings allowed or disallowed by the permission object.

Opening an `OracleConnection` is allowed or denied based upon the connection string fragment, key restrictions combination, and the key restriction behavior.

In the following example, `KeyRestrictionBehavior.AllowOnly` allows connection strings that use `orcl` as the `Data Source` with any `User Id` and `Password` combination but no other connection string keywords. Connection string keywords other than `User Id` and `Password` cause security exceptions.

```
orclPermission.Add("Data Source=orcl;", "User Id=;Password=;",  
    KeyRestrictionBehavior.AllowOnly);
```

In the next example, `KeyRestrictionBehavior.PreventUsage` restricts connection strings that use the keyword `Pooling`. Use of the `Pooling` keyword causes an exception.

```
orclPermission.Add("Data Source=orcl;", "Pooling=;",  
    KeyRestrictionBehavior.PreventUsage);
```

As a general rule, in an unrestricted environment, any connection string that is not allowed is restricted and throws a security exception.

If a connection string fragment contains key-value pairs for the `password` and `proxy password` attributes, then values for these attributes are ignored. However, the presence of the attributes themselves is still checked. This means that the connection is allowed only if the `password` and `proxy` attributes keywords are allowed in the connection string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

Copy

This method returns a copy of the current permission object.

Declaration

```
// C#  
public override IPermission Copy();
```

Return Value

A copy of the `OraclePermission` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

IsSubsetOf

This method returns a boolean value that indicates whether or not the current permission is a subset of the target permission.

Declaration

```
// C#  
public override bool IsSubsetOf(IPermission target);
```

Parameters

- *target*
A permission that must be of type `OraclePermission`.

Return Value

A `bool` value that indicates whether or not the current permission is a subset of the target permission.

Exceptions

ArgumentException - The permission is not of the OraclePermission type.

Remarks

The AllowBlankPassword property is ignored when evaluating whether or not the current permission is a subset of the target permission.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermissionAttribute Class

An OraclePermissionAttribute object enables ODP.NET to enforce declarative security and helps ensure that a user has a security level adequate for accessing data.

Class Inheritance

```

System.Object
    System.Attribute
        System.Security.Permissions.SecurityAttribute
            System.Security.Permissions.CodeAccessSecurityAttribute
                System.Data.Common.DBDataPermissionAttribute
                    Oracle.DataAccess.Client.OraclePermissionAttribute

```

Declaration

```

// C#
[Serializable, AttributeUsage(AttributeTargets.Method |
AttributeTargets.Constructor | AttributeTargets.Class | AttributeTargets.Struct |
AttributeTargets.Assembly, AllowMultiple = true, Inherited = false)]
public sealed class OraclePermissionAttribute: DBDataPermissionAttribute

```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermissionAttribute Members](#)
- [OraclePermissionAttribute Constructor](#)
- [OraclePermissionAttribute Static Methods](#)
- [OraclePermissionAttribute Public Properties](#)
- [OraclePermissionAttribute Public Methods](#)

OraclePermissionAttribute Members

OraclePermissionAttribute members are listed in the following tables.

OraclePermissionAttribute Constructor

The OraclePermissionAttribute constructor is listed in [Table 6-142](#).

Table 6-142 OraclePermission Constructor

Constructor	Description
OraclePermissionAttribute Constructor	Instantiates a new instance of the OraclePermissionAttribute class.

OraclePermissionAttribute Static Methods

The OraclePermissionAttribute static methods are listed in [Table 6-143](#).

Table 6-143 OraclePermissionAttribute Static Methods

Static Methods	Description
GetCustomAttribute	Inherited from System.Attribute (Overloaded)
GetCustomAttributes	Inherited from System.Attribute(Overloaded)
IsDefined	Inherited from System.Attribute(Overloaded)
ReferenceEquals	Inherited from System.Object

OraclePermissionAttribute Public Properties

The OraclePermissionAttribute public properties are listed in [Table 6-144](#).

Table 6-144 OraclePermissionAttribute Public Properties

Public Properties	Description
Action	Inherited from SecurityAttribute
AllowBlankPassword	Inherited from DBDataPermissionAttribute. OraclePermissionAttribute ignores this property. Any value set for this property, for an OraclePermissionAttribute object, is ignored.
ConnectionString	Inherited from DBDataPermissionAttribute
KeyRestrictionBehavior	Inherited from DBDataPermissionAttribute
KeyRestrictions	Inherited from DBDataPermissionAttribute
TypeId	Inherited from System.Attribute
Unrestricted	Inherited from SecurityAttribute

OraclePermissionAttribute Public Methods

The OraclePermissionAttribute public methods are listed in [Table 6-145](#).

Table 6-145 OraclePermissionAttribute Public Methods

Public Methods	Description
CreatePermission	Returns a new OraclePermissionAttribute object that is configured based on the attributes set
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ShouldSerializeConnectionString	Inherited from DBDataPermissionAttribute
ShouldSerializeKeyRestrictions	Inherited from DBDataPermissionAttribute
ToString	Inherited from System.Object

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermissionAttribute Class](#)

OraclePermissionAttribute Constructor

The `OraclePermissionAttribute` constructor instantiates new instances of the `OraclePermissionAttribute` class.

Declaration

```
// C#
public OraclePermissionAttribute (SecurityAction action);
```

Parameters

- *action*
A `System.Security.Permissions.SecurityAction` value representing an action that can be performed using declarative security.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OraclePermissionAttribute Static Methods

The `OraclePermissionAttribute` static methods are listed in [Table 6-146](#).

Table 6-146 OraclePermissionAttribute Static Methods

Static Methods	Description
<code>GetCustomAttribute</code>	Inherited from <code>System.Attribute (Overloaded)</code>
<code>GetCustomAttributes</code>	Inherited from <code>System.Attribute(Overloaded)</code>
<code>IsDefined</code>	Inherited from <code>System.Attribute(Overloaded)</code>
<code>ReferenceEquals</code>	Inherited from <code>System.Object</code>

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OraclePermissionAttribute Public Properties

The `OraclePermissionAttribute` public properties are listed in [Table 6-147](#).

Table 6-147 OraclePermissionAttribute Public Properties

Public Properties	Description
Action	Inherited from <code>SecurityAttribute</code>
AllowBlankPassword	Inherited from <code>DBDataPermissionAttribute</code> . <code>OraclePermissionAttribute</code> ignores this property. Any value set for this property, for an <code>OraclePermissionAttribute</code> object, is ignored.
ConnectionString	Inherited from <code>DBDataPermissionAttribute</code>
KeyRestrictionBehavior	Inherited from <code>DBDataPermissionAttribute</code>
KeyRestrictions	Inherited from <code>DBDataPermissionAttribute</code>
TypeId	Inherited from <code>System.Attribute</code>
Unrestricted	Inherited from <code>SecurityAttribute</code>

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OraclePermissionAttribute Public Methods

The `OraclePermissionAttribute` public methods are listed in [Table 6-148](#).

Table 6-148 OraclePermissionAttribute Public Methods

Public Methods	Description
CreatePermission	Returns a new <code>OraclePermissionAttribute</code> object that is configured based on the attributes set
Equals	Inherited from <code>System.Attribute</code>
GetHashCode	Inherited from <code>System.Attribute</code>
GetType	Inherited from <code>System.Attribute</code>
IsDefaultAttribute	Inherited from <code>System.Attribute</code>
Match	Inherited from <code>System.Attribute</code>
ShouldSerializeConnectionString	Inherited from <code>DBDataPermissionAttribute</code>

Table 6-148 (Cont.) OraclePermissionAttribute Public Methods

Public Methods	Description
ShouldSerializeKeyRestrictions	Inherited from DBDataPermissionAttribute
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

CreatePermission

This method returns a new `OraclePermissionAttribute` object that is configured based on the attributes set.

Declaration

```
// C#  
public override IPermission CreatePermission();
```

Return Value

An `OraclePermission` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OracleRowUpdatedEventArgs Class

The `OracleRowUpdatedEventArgs` class provides event data for the `OracleDataAdapter.RowUpdated` event.

Class Inheritance

`System.Object`

`System.EventArgs`

```
System.RowUpdatedEventArgs
System.OracleRowUpdatedEventArgs
```

Declaration

```
// C#
public sealed class OracleRowUpdatedEventArgs : RowUpdatedEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

The example for the `RowUpdated` event shows how to use `OracleRowUpdatedEventArgs`. See `RowUpdated` event "[Example](#)".

See Also:

- "[Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces](#)"
- [OracleRowUpdatedEventArgs Members](#)
- [OracleRowUpdatedEventArgs Constructor](#)
- [OracleRowUpdatedEventArgs Static Methods](#)
- [OracleRowUpdatedEventArgs Properties](#)
- [OracleRowUpdatedEventArgs Public Methods](#)
- [OracleDataAdapter Class](#)

OracleRowUpdatedEventArgs Members

`OracleRowUpdatedEventArgs` members are listed in the following tables.

OracleRowUpdatedEventArgs Constructors

`OracleRowUpdatedEventArgs` constructors are listed in [Table 6-149](#).

Table 6-149 OracleRowUpdatedEventArgs Constructors

Constructor	Description
OracleRowUpdatedEventArgs Constructor	Instantiates a new instance of OracleRowUpdatedEventArgs class

OracleRowUpdatedEventArgs Static Methods

The OracleRowUpdatedEventArgs static method is listed in [Table 6-150](#).

Table 6-150 OracleRowUpdatedEventArgs Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleRowUpdatedEventArgs Properties

The OracleRowUpdatedEventArgs properties are listed in [Table 6-151](#).

Table 6-151 OracleRowUpdatedEventArgs Properties

Property	Description
Command	Specifies the OracleCommand that is used when OracleDataAdapter.Update() is called
Errors	Inherited from System.Data.Common.RowUpdatedEventArgs
RecordsAffected	Inherited from System.Data.Common.RowUpdatedEventArgs
Row	Inherited from System.Data.Common.RowUpdatedEventArgs
StatementType	Inherited from System.Data.Common.RowUpdatedEventArgs
Status	Inherited from System.Data.Common.RowUpdatedEventArgs
TableMapping	Inherited from System.Data.Common.RowUpdatedEventArgs

OracleRowUpdatedEventArgs Public Methods

The OracleRowUpdatedEventArgs properties are listed in [Table 6-152](#).

Table 6-152 OracleRowUpdatedEventArgs Public Methods

Public Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object

Table 6-152 (Cont.) OracleRowUpdatedEventArgs Public Methods

Public Method	Description
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatedEventArgs Class](#)

OracleRowUpdatedEventArgs Constructor

The `OracleRowUpdatedEventArgs` constructor creates a new `OracleRowUpdatedEventArgs` instance.

Declaration

```
// C#
public OracleRowUpdatedEventArgs(DataRow row, IDbCommand command,
    StatementType statementType, DataTableMapping tableMapping);
```

Parameters

- *row*
The `DataRow` sent for Update.
- *command*
The `IDbCommand` executed during the Update.
- *statementType*
The `StatementType` Enumeration value indicating the type of SQL statement executed.
- *tableMapping*
The `DataTableMapping` used for the Update.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventArgs Static Methods

The OracleRowUpdatedEventArgs static method is listed in [Table 6-153](#).

Table 6-153 OracleRowUpdatedEventArgs Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventArgs Properties

The OracleRowUpdatedEventArgs properties are listed in [Table 6-154](#).

Table 6-154 OracleRowUpdatedEventArgs Properties

Property	Description
Command	Specifies the OracleCommand that is used when OracleDataAdapter.Update() is called
Errors	Inherited from System.Data.Common.RowUpdatedEventArgs
RecordsAffected	Inherited from System.Data.Common.RowUpdatedEventArgs
Row	Inherited from System.Data.Common.RowUpdatedEventArgs
StatementType	Inherited from System.Data.Common.RowUpdatedEventArgs
Status	Inherited from System.Data.Common.RowUpdatedEventArgs
TableMapping	Inherited from System.Data.Common.RowUpdatedEventArgs

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

Command

This property specifies the `OracleCommand` that is used when `OracleDataAdapter.Update()` is called.

Declaration

```
// C#  
public new OracleCommand Command {get;}
```

Property Value

The `OracleCommand` executed when `Update` is called.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventArgs Public Methods

The `OracleRowUpdatedEventArgs` properties are listed in [Table 6-155](#).

Table 6-155 OracleRowUpdatedEventArgs Public Methods

Public Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>System.Object</code>

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventHandler Delegate

The `OracleRowUpdatedEventHandler` delegate represents the signature of the method that handles the `OracleDataAdapter.RowUpdated` event.

Declaration

```
// C#
public delegate void OracleRowUpdatedEventHandler(object sender,
    OracleRowUpdatedEventArgs eventArgs);
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleRowUpdatedEventArgs` object that contains the event data.

Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified after a row is updated.

In the .NET framework, the convention of an event delegate requires two parameters: the object that raises the event and the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["RowUpdated"](#)

OracleRowUpdatingEventArgs Class

The `OracleRowUpdatingEventArgs` class provides event data for the `OracleDataAdapter.RowUpdating` event.

Class Inheritance

System.Object

System.EventArgs

System.RowUpdatingEventArgs

System.OracleRowUpdatingEventArgs

Declaration

```
// C#
public sealed class OracleRowUpdatingEventArgs : RowUpdatingEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

The example for the `RowUpdated` event shows how to use `OracleRowUpdatingEventArgs`. See `RowUpdated` event "[Example](#)".

See Also:

- "[Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces](#)"
- [OracleRowUpdatingEventArgs Members](#)
- [OracleRowUpdatingEventArgs Constructor](#)
- [OracleRowUpdatingEventArgs Static Methods](#)
- [OracleRowUpdatingEventArgs Properties](#)
- [OracleRowUpdatingEventArgs Public Methods](#)
- "[OracleDataAdapter Class](#) "

OracleRowUpdatingEventArgs Members

OracleRowUpdatingEventArgs members are listed in the following tables.

OracleRowUpdatingEventArgs Constructors

OracleRowUpdatingEventArgs constructors are listed in [Table 6-156](#).

Table 6-156 OracleRowUpdatingEventArgs Constructors

Constructor	Description
OracleRowUpdatingEventArgs Constructor	Instantiates a new instance of OracleRowUpdatingEventArgs class (Overloaded)

OracleRowUpdatingEventArgs Static Methods

The OracleRowUpdatingEventArgs static methods are listed in [Table 6-157](#).

Table 6-157 OracleRowUpdatingEventArgs Static Methods

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleRowUpdatingEventArgs Properties

The OracleRowUpdatingEventArgs properties are listed in [Table 6-158](#).

Table 6-158 OracleRowUpdatingEventArgs Properties

Property	Description
Command	Specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called
Errors	Inherited from System.Data.Common.RowUpdatingEventArgs
Row	Inherited from System.Data.Common.RowUpdatingEventArgs
StatementType	Inherited from System.Data.Common.RowUpdatingEventArgs
Status	Inherited from System.Data.Common.RowUpdatingEventArgs
TableMapping	Inherited from System.Data.Common.RowUpdatingEventArgs

OracleRowUpdatingEventArgs Public Methods

The OracleRowUpdatingEventArgs public methods are listed in [Table 6-159](#).

Table 6-159 OracleRowUpdatingEventArgs Public Methods

Public Method	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatingEventArgs Class](#)

OracleRowUpdatingEventArgs Constructor

The `OracleRowUpdatingEventArgs` constructor creates a new instance of the `OracleRowUpdatingEventArgs` class using the supplied data row, `IDbCommand`, type of SQL statement, and table mapping.

Declaration

```
// C#  
public OracleRowUpdatingEventArgs(DataRow row, IDbCommand command,  
    StatementType statementType, DataTableMapping tableMapping);
```

Parameters

- *row*
The `DataRow` sent for Update.
- *command*
The `IDbCommand` executed during the Update.
- *statementType*
The `StatementType` enumeration value indicating the type of SQL statement executed.
- *tableMapping*
The `DataTableMapping` used for the Update.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventArgs Static Methods

The OracleRowUpdatingEventArgs static method is listed in [Table 6-160](#).

Table 6-160 OracleRowUpdatingEventArgs Static Method

Method	Description
Equals	Inherited from System.Object (Overloaded)

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventArgs Properties

The OracleRowUpdatingEventArgs properties are listed in [Table 6-161](#).

Table 6-161 OracleRowUpdatingEventArgs Properties

Property	Description
Command	Specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called
Errors	Inherited from System.Data.Common.RowUpdatingEventArgs
Row	Inherited from System.Data.Common.RowUpdatingEventArgs
StatementType	Inherited from System.Data.Common.RowUpdatingEventArgs
Status	Inherited from System.Data.Common.RowUpdatingEventArgs
TableMapping	Inherited from System.Data.Common.RowUpdatingEventArgs

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

Command

This property specifies the `OracleCommand` that is used when the `OracleDataAdapter.Update()` is called.

Declaration

```
// C#
public new OracleCommand Command {get; set;}
```

Property Value

The `OracleCommand` executed when `Update` is called.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventArgs Public Methods

The `OracleRowUpdatingEventArgs` public methods are listed in [Table 6-162](#).

Table 6-162 OracleRowUpdatingEventArgs Public Methods

Public Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>System.Object</code>

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventHandler Delegate

The `OracleRowUpdatingEventHandler` delegate represents the signature of the method that handles the `OracleDataAdapter.RowUpdating` event.

Declaration

```
// C#
public delegate void OracleRowUpdatingEventHandler (object sender,
    OracleRowUpdatingEventArgs eventArgs);
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleRowUpdatingEventArgs` object that contains the event data.

Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified after a row is updated.

In the .NET framework, the convention of an event delegate requires two parameters: the object that raises the event and the event data.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["RowUpdating"](#)

OracleShardingKey Class

An `OracleShardingKey` object can represent either a sharding key or a super sharding key.

Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleShardingKey`

Declaration

```
// C#
public class OracleShardingKey : IDisposable
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class Sharding
{
    static void Main()
    {
        OracleConnection con = new OracleConnection("user id=hr;password=hr;Data
Source=orcl;");
        //Setting a shard key
        OracleShardingKey shardingKey = new OracleShardingKey(OracleDbType.Int32, 123);
        //Setting a second shard key value for a composite key
        shardingKey.SetShardingKey(OracleDbType.Varchar2, "gold");
        //Creating and setting the super shard key
        OracleShardingKey superShardingKey = new OracleShardingKey();
        superShardingKey.SetShardingKey(OracleDbType.Int32, 1000);

        //Setting super sharding key and sharding key on the connection
```

```

con.SetShardingKey(shardingKey, superShardingKey);
con.Open();

//perform SQL query
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Members](#)
- [OracleShardingKey Constructors](#)
- [OracleShardingKey Instance Methods](#)

OracleShardingKey Members

OracleShardingKey members are listed in the following tables.

OracleShardingKey Constructors

OracleShardingKey constructors are listed in [Table 6-163](#).

Table 6-163 OracleShardingKey Constructors

Constructor	Description
OracleShardingKey Constructors	Instantiates a new instance of OracleShardingKey class (Overloaded)

OracleShardingKey Instance Methods

OracleShardingKey instance methods are listed in [Table 6-164](#).

Table 6-164 OracleShardingKey Instance Methods

Method	Description
SetShardingKey(OracleDbType, object)	Enables applications to set a key within the OracleShardingKey object
Dispose	Enables applications to explicitly dispose the OracleShardingKey object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Class](#)

OracleShardingKey Constructors

OracleShardingKey constructors instantiate new instances of the OracleShardingKey class.

Overload List:

- [OracleShardingKey\(\)](#)
This constructor instantiates a new instance of OracleShardingKey class.
- [OracleShardingKey\(OracleDbType, object\)](#)
This constructor instantiates a new instance of the OracleShardingKey class using the supplied data type and key.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Class](#)
- [OracleShardingKey Members](#)

OracleShardingKey()

This constructor enables applications to construct the OracleShardingKey object.

Declaration

```
// C#  
public OracleShardingKey();
```

Exceptions

None

Remarks

This constructs an OracleShardingKey without any keys set.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Class](#)
- [OracleShardingKey Members](#)

OracleShardingKey(OracleDbType, object)

This constructor enables applications to construct the `OracleShardingKey` object with the supplied key.

Declaration

```
// C#
public OracleShardingKey(OracleDbType type, object key);
```

Exceptions

`InvalidArgumentException` – The supplied argument is invalid

Remarks

This constructs an `OracleShardingKey` with the supplied key set.

Acceptable `OracleDbType` enumeration values are `Byte`, `Decimal`, `Double`, `Int16`, `In32`, `Int64`, `Single`, `Varchar2`, `String`, `Date`, `TimeStamp`, and `Raw`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Class](#)
- [OracleShardingKey Members](#)

OracleShardingKey Instance Methods

`OracleShardingKey` instance methods are listed in [Table 6-165](#).

Table 6-165 OracleShardingKey Instance Methods

Instance Method	Description
SetShardingKey(OracleDbType, object)	Enables applications to set a key within the <code>OracleShardingKey</code> object
Dispose	Enables applications to explicitly dispose the <code>OracleShardingKey</code> object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Class](#)
- [OracleShardingKey Members](#)

SetShardingKey(OracleDbType, object)

This instance method enables applications to set a key within the `OracleShardingKey` object.

Declaration

```
// C#  
public void SetShardingKey(OracleDbType type, object key);
```

Exceptions

`InvalidArgumentException` – The supplied argument is invalid

Remarks

This method sets a key within the `OracleShardingKey` object.

Acceptable `OracleDbType` enumeration values are `Byte`, `Decimal`, `Double`, `Int16`, `In32`, `Int64`, `Single`, `Varchar2`, `String`, `Date`, `TimeStamp`, and `Raw`.

This can be called multiple times to construct a composite key.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Class](#)
- [OracleShardingKey Members](#)

Dispose

This instance method enables applications to explicitly dispose the `OracleShardingKey` object.

Declaration

```
// C#  
public void Dispose();
```

Exceptions

None

RemarksThis method disposes the `OracleShardingKey` object. **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleShardingKey Class](#)
- [OracleShardingKey Members](#)

OracleTransaction Class

An `OracleTransaction` object represents a local transaction.**Class Inheritance**`System.Object``System.MarshalByRefObject``System.Data.Common.DbTransaction``Oracle.DataAccess.Client.OracleTransaction`**Declaration**

```
// C#
public sealed class OracleTransaction : DbTransaction

// C#
public sealed class OracleTransaction : MarshalByRefObject,
    IDbTransaction, IDisposable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The application calls `BeginTransaction` on the `OracleConnection` object to create an `OracleTransaction` object. The `OracleTransaction` object can be created in `Read Committed` mode only. Any other mode results in an exception.

The execution of a [DDL](#) statement in the context of a transaction is not recommended since it results in an implicit commit that is not reflected in the state of the `OracleTransaction` object.

All operations related to [savepoints](#) pertain to the current local transaction. Operations like `commit` and `rollback` performed on the transaction have no effect on data in any existing `DataSet`.

Example

```
// Database Setup, if you have not done so yet.
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);
--CREATE TABLE MyTable (MyColumn NUMBER PRIMARY KEY);

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleTransactionSample
{
    static void Main()
    {
        // Drop & Create MyTable as indicated Database Setup, at beginning

        // This sample starts a transaction and inserts two records with the same
        // value for MyColumn into MyTable.
        // If MyColumn is not a primary key, the transaction will commit.
        // If MyColumn is a primary key, the second insert will violate the
        // unique constraint and the transaction will rollback.

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = con.CreateCommand();

        // Check the number of rows in MyTable before transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Print the number of rows in MyTable
```

```
Console.WriteLine("myTableCount = " + myTableCount);

// Start a transaction
OracleTransaction txn = con.BeginTransaction(
    IsolationLevel.ReadCommitted);

try
{
    // Insert the same row twice into MyTable
    cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
    cmd.ExecuteNonQuery();
    cmd.ExecuteNonQuery(); // This may throw an exception
    txn.Commit();
}
catch (Exception e)
{
    // Print the exception message
    Console.WriteLine("e.Message = " + e.Message);

    // Rollback the transaction
    txn.Rollback();
}

// Check the number of rows in MyTable after transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows
// If MyColumn is not a PRIMARY KEY, the value should increase by two.
// If MyColumn is a PRIMARY KEY, the value should remain same.
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

Not supported in a .NET stored procedure

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Members](#)
- [OracleTransaction Static Methods](#)
- [OracleTransaction Properties](#)

OracleTransaction Members

OracleTransaction members are listed in the following tables.

OracleTransaction Static Methods

The `OracleTransaction` static method is listed in [Table 6-166](#).

Table 6-166 OracleTransaction Static Method

Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

OracleTransaction Properties

`OracleTransaction` properties are listed in [Table 6-167](#).

Table 6-167 OracleTransaction Properties

Property	Description
IsolationLevel	Specifies the isolation level for the transaction
Connection	Specifies the connection that is associated with the transaction

OracleTransaction Public Methods

`OracleTransaction` public methods are listed in [Table 6-168](#).

Table 6-168 OracleTransaction Public Methods

Public Method	Description
Commit	Commits the database transaction
<code>CreateObjRef</code>	Inherited from <code>System.MarshalByRefObject</code>
Dispose	Frees the resources used by the <code>OracleTransaction</code> object
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>InitializeLifetimeService</code>	Inherited from <code>System.MarshalByRefObject</code>
Rollback	Rolls back a database transaction (Overloaded)
Save	Creates a savepoint within the current transaction
<code>ToString</code>	Inherited from <code>System.Object</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)

OracleTransaction Static Methods

The `OracleTransaction` static method is listed in [Table 6-169](#).

Table 6-169 OracleTransaction Static Method

Method	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

OracleTransaction Properties

`OracleTransaction` properties are listed in [Table 6-170](#).

Table 6-170 OracleTransaction Properties

Property	Description
IsolationLevel	Specifies the isolation level for the transaction
Connection	Specifies the connection that is associated with the transaction

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

IsolationLevel

This property specifies the isolation level for the transaction.

Declaration

```
// C#  
public override IsolationLevel IsolationLevel {get;}
```

Property Value

IsolationLevel

Implements

IDbTransaction

Exceptions

InvalidOperationException - The transaction has already completed.

Remarks

Default = IsolationLevel.ReadCommitted

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Connection

This property specifies the connection that is associated with the transaction.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

Connection

Implements

IDbTransaction

Remarks

This property indicates the `OracleConnection` object that is associated with the transaction.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

OracleTransaction Public Methods

OracleTransaction public methods are listed in [Table 6-171](#).

Table 6-171 OracleTransaction Public Methods

Public Method	Description
Commit	Commits the database transaction
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Frees the resources used by the OracleTransaction object
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
Rollback	Rolls back a database transaction (Overloaded)
Save	Creates a savepoint within the current transaction
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Commit

This method commits the database transaction.

Declaration

```
// C#  
public override void Commit();
```

Implements

```
IDbTransaction
```

Exceptions

`InvalidOperationException` - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

Remarks

Upon a successful commit, the transaction enters a completed state.

Example

```
// Database Setup, if you have not done so yet  
/*  
connect scott/tiger@oracle  
DROP TABLE MyTable;  
CREATE TABLE MyTable (MyColumn NUMBER);  
--CREATE TABLE MyTable (MyColumn NUMBER PRIMARY KEY);  
  
*/  
  
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class CommitSample  
{  
    static void Main()  
    {  
        // Drop & Create MyTable as indicated in Database Setup, at beginning  
  
        // This sample starts a transaction and inserts two records with the same  
        // value for MyColumn into MyTable.  
        // If MyColumn is not a primary key, the transaction will commit.  
        // If MyColumn is a primary key, the second insert will violate the  
        // unique constraint and the transaction will rollback.  
  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = con.CreateCommand();  
  
        // Check the number of rows in MyTable before transaction  
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";  
        int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());  
  
        // Print the number of rows in MyTable  
        Console.WriteLine("myTableCount = " + myTableCount);  
    }  
}
```

```
// Start a transaction
OracleTransaction txn = con.BeginTransaction(
    IsolationLevel.ReadCommitted);

try
{
    // Insert the same row twice into MyTable
    cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
    cmd.ExecuteNonQuery();
    cmd.ExecuteNonQuery(); // This may throw an exception
    txn.Commit();
}
catch (Exception e)
{
    // Print the exception message
    Console.WriteLine("e.Message = " + e.Message);

    // Rollback the transaction
    txn.Rollback();
}

// Check the number of rows in MyTable after transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows
// If MyColumn is not a PRIMARY KEY, the value should increase by two.
// If MyColumn is a PRIMARY KEY, the value should remain same.
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Dispose

This method frees the resources used by the `OracleTransaction` object.

Declaration

```
// C#
public void Dispose();
```


Implements

IDisposable

Remarks

This method releases both the managed and unmanaged resources held by the `OracleTransaction` object. If the transaction is not in a completed state, an attempt to rollback the transaction is made.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Rollback

Rollback rolls back a database transaction.

Overload List:

- [Rollback\(\)](#)
This method rolls back a database transaction.
- [Rollback\(string\)](#)
This method rolls back a database transaction to a [savepoint](#) within the current transaction.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Rollback()

This method rolls back a database transaction.

Declaration

```
// C#  
public override void Rollback();
```

Implements

IDbTransaction

Exceptions

InvalidOperationException - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

Remarks

After a Rollback(), the OracleTransaction object can no longer be used because the Rollback ends the transaction.

Example

```
// Database Setup, if you have not done so yet.
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class RollbackSample
{
    static void Main()
    {
        // Drop & Create MyTable as indicated previously in Database Setup

        // This sample starts a transaction and inserts one record into MyTable.
        // It then rollsback the transaction, the number of rows remains the same

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = con.CreateCommand();

        // Check the number of rows in MyTable before transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Print the number of rows in MyTable
        Console.WriteLine("myTableCount = " + myTableCount);

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(
            IsolationLevel.ReadCommitted);

        // Insert a row into MyTable
        cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
        cmd.ExecuteNonQuery();
    }
}
```

```
// Rollback the transaction
txn.Rollback();

// Check the number of rows in MyTable after transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows, should remain the same
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Rollback(string)

This method rolls back a database transaction to a [savepoint](#) within the current transaction.

Declaration

```
// C#
public override void Rollback(string savepointName);
```

Parameters

- *savepointName*
The name of the savepoint to rollback to, in the current transaction.

Exceptions

`InvalidOperationException` - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

Remarks

After a rollback to a savepoint, the current transaction remains active and can be used for further operations.

The *savepointName* specified does not have to match the case of the *savepointName* created using the *Save* method, since savepoints are created in the database in a case-insensitive manner.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Save

This method creates a [savepoint](#) within the current transaction.

Declaration

```
// C#  
public void Save(string savepointName);
```

Parameters

- *savepointName*

The name of the savepoint being created in the current transaction.

Exceptions

`InvalidOperationException` - The transaction has already been completed.

Remarks

After creating a savepoint, the transaction does not enter a completed state and can be used for further operations.

The *savepointName* specified is created in the database in a case-insensitive manner. Calling the `Rollback` method rolls back to *savepointName*. This allows portions of a transaction to be rolled back, instead of the entire transaction.

Example

```
// Database Setup, if you have not done so yet.  
/*  
connect scott/tiger@oracle  
DROP TABLE MyTable;  
CREATE TABLE MyTable (MyColumn NUMBER);  
  
*/  
  
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class SaveSample  
{  
    static void Main()  
    {  

```

```
// Drop & Create MyTable as indicated in Database Setup, at beginning

// This sample starts a transaction and creates a savepoint after
// inserting one record into MyTable.
// After inserting the second record it rollsback to the savepoint
// and commits the transaction. Only the first record will be inserted

string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

OracleCommand cmd = con.CreateCommand();

// Check the number of rows in MyTable before transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Print the number of rows in MyTable
Console.WriteLine("myTableCount = " + myTableCount);

// Start a transaction
OracleTransaction txn = con.BeginTransaction(
    IsolationLevel.ReadCommitted);

// Insert a row into MyTable
cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
cmd.ExecuteNonQuery();

// Create a savepoint
txn.Save("MySavePoint");

// Insert another row into MyTable
cmd.CommandText = "insert into mytable values (2)";
cmd.ExecuteNonQuery();

// Rollback to the savepoint
txn.Rollback("MySavePoint");

// Commit the transaction
txn.Commit();

// Check the number of rows in MyTable after transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows, should have increased by 1
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

OracleConnectionType Enumeration

`OracleConnectionType` enumerated values specify whether a particular connection object is associated with an Oracle database connection, a TimesTen database connection, or no physical connection at all.

[Table 6-172](#) lists all the `OracleConnectionType` enumeration values with a description of each enumerated value.

Table 6-172 OracleConnectionType Enumeration Values

Member Name	Description
Undefined	No connection is associated with the <code>OracleConnection</code> object.
Oracle	The <code>OracleConnection</code> object is associated with an Oracle database.
TimesTen	The <code>OracleConnection</code> object is associated with a TimesTen database.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleConnection Class"](#)
- ["ConnectionType"](#)

OracleCollectionType Enumeration

OracleCollectionType enumerated values specify whether or not the OracleParameter object represents a collection, and if so, specifies the collection type.

Table 6-173 lists all the OracleCollectionType enumeration values with a description of each enumerated value.

Table 6-173 OracleCollectionType Enumeration Values

Member Name	Description
None	Is not a collection type
PLSQLAssociativeArray	Indicates that the collection type is a PL/SQL Associative Array (or PL/SQL Index-By Table)

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleParameter Class"](#)
- ["CollectionType"](#)

OracleDBAPrivilege Enumeration

OracleDBAPrivilege enumerated values are used to explicitly specify the DBA Privilege required while creating the OracleCredential object.

Table 6-172 lists all the OracleDBAPrivilege enumeration values with a description of each enumerated value.

Table 6-174 OracleDBAPrivilege Enumeration Values

Member Name	Description
None	Default value, no DBA privilege set.
SYSDBA	SYSDBA connection
SYSOPER	SYSOPER connection

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleCredential Class](#)
- [DBAPrivilege](#)

OracleDBShutdownMode Enumeration

OracleDBShutdownMode enumerated values specify the database shutdown options.

[Table 6-176](#) lists all the OracleDBShutdownMode enumeration values with a description of each enumerated value.

Table 6-175 OracleDBShutdownMode Enumeration Values

Member Name	Description
Default	Refuses new connections and waits for existing connections to end.
Transactional	Refuses new connections and does not allow any new transactions. Waits for active transactions to commit.
TransactionalLocal	Refuses new connections and does not allow any new transactions. Waits for only local transactions to commit.

Table 6-175 (Cont.) OracleDBShutdownMode Enumeration Values

Member Name	Description
Immediate	Does not wait for current calls to complete or users to disconnect from the database. All uncommitted transactions are terminated and rolled back.
Final	Shuts down the database. Used in the second call for shutdown after the database has been closed and dismounted.
Abort	Does not wait for current calls to complete or users to disconnect from the database. All uncommitted transactions are terminated and are not rolled back.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleConnection Class"](#)
- ["Shutdown"](#)

OracleDBStartupMode Enumeration

OracleDBStartupMode enumerated values specify the database startup options.

[Table 6-176](#) lists all the OracleDBStartupMode enumeration values with a description of each enumerated value.

Table 6-176 OracleDBStartupMode Enumeration Values

Member Name	Description
NoRestriction	Starts the database and allows access to all users.
Restrict	Starts the database and allows database access only to users having the CREATE SESSION and RESTRICTED SESSION privileges. These privileges are normally assigned to database administrators.
Force	Shuts down a running instance in abort mode and starts a new instance.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleConnection Class"](#)
- ["Startup"](#)

OracleDbType Enumeration

OracleDbType enumerated values are used to explicitly specify the OracleDbType of an OracleParameter.

[Table 6-177](#) lists all the OracleDbType enumeration values with a description of each enumerated value.

Table 6-177 OracleDbType Enumeration Values

Member Name	Description
Array	Oracle Collection (VArray or Nested Table) <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
BFile	Oracle BFILE type
BinaryFloat	Oracle BINARY_FLOAT type
BinaryDouble	Oracle BINARY_DOUBLE type
Blob	Oracle BLOB type
Boolean	Oracle BOOLEAN type
Byte	byte type
Char	Oracle CHAR type
Clob	Oracle CLOB type
Date	Oracle DATE type
Decimal	Oracle NUMBER type
Double	8-byte FLOAT type
Int16	2-byte INTEGER type
Int32	4-byte INTEGER type

Table 6-177 (Cont.) OracleDbType Enumeration Values

Member Name	Description
Int64	8-byte INTEGER type
IntervalDS	Oracle INTERVAL DAY TO SECOND type
IntervalYM	Oracle INTERVAL YEAR TO MONTH type
Long	Oracle LONG type
LongRaw	Oracle LONG RAW type
NChar	Oracle NCHAR type
NClob	Oracle NCLOB type
NVarchar2	Oracle NVARCHAR2 type
Object	Oracle Object <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
Raw	Oracle RAW type
Ref	Oracle REF <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
RefCursor	Oracle REF CURSOR type
Single	4-byte FLOAT type, supports 6 precisions
TimeStamp	Oracle TIMESTAMP type
TimeStampLTZ	Oracle TIMESTAMP WITH LOCAL TIME ZONE type
TimeStampTZ	Oracle TIMESTAMP WITH TIME ZONE type
Varchar2	Oracle VARCHAR2 type
XmlType	Oracle XMLType type

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleParameter Class"](#)
- ["OracleParameterCollection Class"](#)
- OracleParameter ["OracleDbType "](#)

OracleDRCPPurity Enumeration

OracleDRCPPurity enumerated values specify the session purity.

[Table 6-178](#) lists all the OracleDRCPPurity enumeration values with a description of each enumerated value.

Table 6-178 OracleDRCPPurity Enumeration Values

Member Name	Description
New	The application requires a session without any previously set session state.
Pooled	An application can reuse a pooled session (i.e. the session can have been used before)

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleConnection Class"](#)
- [DRCPPurity](#)

OracleIdentityType Enumeration

The `OracleIdentityType` enumeration specifies how Oracle identity column values are generated.

[Table 6-179](#) lists all the `OracleIdentityType` enumeration values with a description of each enumerated value.

Table 6-179 OracleIdentityType Members

Member Name	Description
<code>GeneratedAlways</code>	Indicates that unique values are generated for every insertion. No updates or inserts are allowed for this identity column.
<code>GeneratedByDefault</code>	Indicates that the values are generated only if no explicit value is provided for the identity column. Null values are not allowed for this identity column.
<code>GeneratedByDefaultOnNull</code>	Indicates that the values are generated only if no explicit value is provided or a NULL is inserted for the identity column.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleDataAdapter Class "](#)
- `OracleDataAdapter` ["IdentityInsert"](#)
- `OracleDataAdapter` ["IdentityUpdate"](#)

OracleParameterStatus Enumeration

The `OracleParameterStatus` enumeration type indicates whether a NULL value is fetched from a column, or truncation has occurred during the fetch, or a NULL value is to be inserted into a database column.

[Table 6-180](#) lists all the `OracleParameterStatus` enumeration values with a description of each enumerated value.

Table 6-180 OracleParameterStatus Members

Member Name	Description
Success	Indicates that (for input parameters) the input value has been assigned to the column. For output parameter, it indicates that the provider assigned an intact value to the parameter.
NullFetched	Indicates that a NULL value has been fetched from a column or an OUT parameter.
NullInsert	Indicates that a NULL value is to be inserted into a column.
Truncation	Indicates that truncation has occurred when fetching the data from the column.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleParameter Class"](#)
- OracleParameter ["ArrayBindStatus "](#)
- OracleParameter ["Value "](#)

7

Oracle Data Provider for .NET XML-Related Classes

This chapter describes ODP.NET XML-related classes and enumerations.

This chapter contains these topics:

- [OracleXmlCommandType Enumeration](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlStream Class](#)
- [OracleXmlType Class](#)

All offsets are 0-based for `OracleXmlStream` object parameters.

OracleXmlCommandType Enumeration

The `OracleXmlCommandType` enumeration specifies the values that are allowed for the `XmlCommandType` property of the `OracleCommand` class. It is used to specify the type of XML operation.

[Table 7-1](#) lists all the `OracleXmlCommandType` enumeration values with a description of each enumerated value.

Table 7-1 OracleXmlCommandType Members

Member Name	Description
None	No XML operation is desired
Query	The command text is a SQL query and the result of the query is an XML document. The SQL query needs to be a select statement
Insert	The command text is an XML document containing rows to insert.
Update	The command text is an XML document containing rows to update.
Delete	The command text is an XML document containing rows to delete.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher



See Also:

"Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"

OracleXmlQueryProperties Class

An `OracleXmlQueryProperties` object represents the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Query`.

Class Inheritance

`System.Object`

`System.OracleXmlQueryProperties`

Declaration

```
public sealed class OracleXmlQueryProperties : ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

`OracleXmlQueryProperties` can be accessed, and modified using the `XmlQueryProperties` property of the `OracleCommand` class. Each `OracleCommand` object has its own instance of the `OracleXmlQueryProperties` class in the `XmlQueryProperties` property.

Use the default constructor to get a new instance of the `OracleXmlQueryProperties`.
Use the `OracleXmlQueryProperties.Clone()` method to get a copy of an `OracleXmlQueryProperties` instance.

Example

This example retrieves relational data as XML.

```
// C#

using System;
using System.IO;
using System.Data;
using System.Xml;
using System.Text;
using Oracle.DataAccess.Client;

class OracleXmlQueryPropertiesSample
{
    static void Main()
    {
        int rows = 0;
        StreamReader sr = null;

        // Define the XSL document for doing the transform.
        string xslstr = "<?xml version='1.0'?>\n" +
            "<xsl:stylesheet version='1.0'\n" +
            " xmlns:xsl='http://www.w3.org/1999/XSL/Transform'\n" +
            " <xsl:output encoding='utf-8' />\n" +
            " <xsl:template match='/'>\n" +
            "     <EMPLOYEES>\n" +
            "         <xsl:apply-templates select='ROWSET' />\n" +
            "     </EMPLOYEES>\n" +
            " </xsl:template>\n" +
            " <xsl:template match='ROWSET'>\n" +
            "     <xsl:apply-templates select='ROW' />\n" +
            " </xsl:template>\n" +
            " <xsl:template match='ROW'>\n" +
            "     <EMPLOYEE>\n" +
            "         <EMPLOYEE_ID>\n" +
            "             <xsl:apply-templates select='EMPNO' />\n" +
            "         </EMPLOYEE_ID>\n" +
            "         <EMPLOYEE_NAME>\n" +
            "             <xsl:apply-templates select='ENAME' />\n" +
            "         </EMPLOYEE_NAME>\n" +
            "         <HIRE_DATE>\n" +
            "             <xsl:apply-templates select='HIREDATE' />\n" +
            "         </HIRE_DATE>\n" +
            "         <JOB_TITLE>\n" +
            "             <xsl:apply-templates select='JOB' />\n" +
            "         </JOB_TITLE>\n" +
            "     </EMPLOYEE>\n" +
            " </xsl:template>\n" +
            "</xsl:stylesheet>\n";

        // Create the connection.
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Set the date, and timestamp formats for Oracle 9i Release 2, or later.
```

```
// This is just needed for queries.
if (!con.ServerVersion.StartsWith("9.0") &&
    !con.ServerVersion.StartsWith("8.1"))
{
    OracleGlobalization sessionParams = con.GetSessionInfo();
    sessionParams.DateFormat = "YYYY-MM-DD\"T\"HH24:MI:SS";
    sessionParams.TimeStampFormat = "YYYY-MM-DD\"T\"HH24:MI:SS.FF3";
    sessionParams.TimeStampTZFormat = "YYYY-MM-DD\"T\"HH24:MI:SS.FF3";
    con.SetSessionInfo(sessionParams);
}

// Create the command.
OracleCommand cmd = new OracleCommand("", con);

// Set the XML command type to query.
cmd.XmlCommandType = OracleXmlCommandType.Query;

// Set the SQL query.
cmd.CommandText = "select * from emp e where e.empno = :empno";

// Set command properties that affect XML query behaviour.
cmd.BindByName = true;

// Bind values to the parameters in the SQL query.
Int32 empNum = 7369;
cmd.Parameters.Add("empno", OracleDbType.Int32, empNum,
    ParameterDirection.Input);

// Set the XML query properties.
cmd.XmlQueryProperties.MaxRows = 1;
cmd.XmlQueryProperties.RootTag = "ROWSET";
cmd.XmlQueryProperties.RowTag = "ROW";
cmd.XmlQueryProperties.Xslt = xslstr;

// Test query execution without returning a result.
Console.WriteLine("SQL query: select * from emp e where e.empno = 7369");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("Return Value from OracleCommand.ExecuteNonQuery():");
rows = cmd.ExecuteNonQuery();
Console.WriteLine(rows);
Console.WriteLine("\n");

// Get the XML document as an XmlReader.
Console.WriteLine("SQL query: select * from emp e where e.empno = 7369");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("XML Document from OracleCommand.ExecuteXmlReader():");

XmlReader xmlReader = cmd.ExecuteXmlReader();
XmlDocument xmlDocument = new XmlDocument();
xmlDocument.PreserveWhitespace = true;
xmlDocument.Load(xmlReader);
Console.WriteLine(xmlDocument.OuterXml);
Console.WriteLine("\n");

// Change the SQL query, and set the maximum number of rows to 2.
cmd.CommandText = "select * from emp e";
cmd.Parameters.Clear();
cmd.XmlQueryProperties.MaxRows = 2;

// Get the XML document as a Stream.
Console.WriteLine("SQL query: select * from emp e");
```

```

Console.WriteLine("Maximum rows: 2");
Console.WriteLine("XML Document from OracleCommand.ExecuteStream():");
Stream stream = cmd.ExecuteStream();
sr = new StreamReader(stream, Encoding.Unicode);
Console.WriteLine(sr.ReadToEnd());
Console.WriteLine("\n");

// Get all the rows.
cmd.XmlQueryProperties.MaxRows = -1;

// Append the XML document to an existing Stream.
Console.WriteLine("SQL query: select * from emp e");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("XML Document from OracleCommand.ExecuteToStream():");
MemoryStream mstream = new MemoryStream(32);
cmd.ExecuteToStream(mstream);
mstream.Seek(0, SeekOrigin.Begin);
sr = new StreamReader(mstream, Encoding.Unicode);
Console.WriteLine(sr.ReadToEnd());
Console.WriteLine("\n");

// Clean up.
cmd.Dispose();
con.Close();
con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Members](#)
- [OracleXmlQueryProperties Constructor](#)
- [OracleXmlQueryProperties Properties](#)
- [OracleXmlQueryProperties Public Methods](#)

OracleXmlQueryProperties Members

OracleXmlQueryProperties members are listed in the following tables.

OracleXmlQueryProperties Constructors

The OracleXmlQueryProperties constructors are listed in [Table 7-2](#).

Table 7-2 OracleXmlQueryProperties Constructors

Constructor	Description
OracleXmlQueryProperties Constructor	Instantiates a new instance of the OracleXmlQueryProperties class

OracleXmlQueryProperties Properties

The `OracleXmlQueryProperties` properties are listed in [Table 7-3](#).

Table 7-3 OracleXmlQueryProperties Properties

Name	Description
MaxRows	Specifies the maximum number of rows from the result set of the query that can be represented in the result XML document
RootTag	Specifies the root element of the result XML document
RowTag	Specifies the value of the XML element which identifies a row of data from the result set in an XML document
Xslt	Specifies the XSL document used for XML transformation using XSLT
XsltParams	Specifies parameters for the XSL document

OracleXmlQueryProperties Public Methods

The `OracleXmlQueryProperties` public methods are listed in [Table 7-4](#).

Table 7-4 OracleXmlQueryProperties Public Methods

Name	Description
Clone	Creates a copy of an <code>OracleXmlQueryProperties</code> object



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)

OracleXmlQueryProperties Constructor

The `OracleXmlQueryProperties` constructor instantiates a new instance of the `OracleXmlQueryProperties` class.

Declaration

```
// C#  
public OracleXmlQueryProperties();
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

OracleXmlQueryProperties Properties

The OracleXmlQueryProperties properties are listed in [Table 7-5](#).

Table 7-5 OracleXmlQueryProperties Properties

Name	Description
MaxRows	Specifies the maximum number of rows from the result set of the query that can be represented in the result XML document
RootTag	Specifies the root element of the result XML document
RowTag	Specifies the value of the XML element which identifies a row of data from the result set in an XML document
Xslt	Specifies the XSL document used for XML transformation using XSLT
XsltParams	Specifies parameters for the XSL document

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

MaxRows

This property specifies the maximum number of rows from the result set of the query that can be represented in the result XML document.

Declaration

```
// C#
public int MaxRows {get; set;}
```

Property Value

The maximum number of rows.

Exceptions

`ArgumentException` - The new value for `MaxRows` is not valid.

Remarks

Default value is -1.

Possible values are:

- -1 (all rows).
- A number greater than or equal to 0.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

RootTag

This property specifies the root element of the result XML document.

Declaration

```
// C#  
public string RootTag {get; set;}
```

Property Value

The root element of the result XML document.

Remarks

The default root tag is `ROWSET`.

To indicate that no root tag is to be used in the result XML document, set this property to `null` or `""` or `String.Empty`.

If both `RootTag` and `RowTag` are set to `null`, an XML document is returned only if the result set returns one row and one column.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

RowTag

This property specifies the value of the XML element which identifies a row of data from the result set in an XML document.

Declaration

```
// C#  
public string RowTag {get; set;}
```

Property Value

The value of the XML element.

Remarks

The default is ROW.

To indicate that no row tag is to be used in the result XML document, set this property to null or "" or `String.Empty`.

If both `RootTag` and `RowTag` are set to null, an XML document is returned only if the result set returns one row and one column.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

Xslt

This property specifies the XSL document used for XML transformation using XSLT.

Declaration

```
// C#  
public string Xslt {get; set;}
```

Property Value

The XSL document used for XML transformation.

Remarks

Default value is `null`.

The XSL document is used for XML transformation of the XML document generated from the result set of the query.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

XsltParams

This property specifies parameters for the XSL document.

Declaration

```
// C#  
public string XsltParams {get; set;}
```

Property Value

The parameters for the XSL document.

Remarks

Default value is `null`.

The parameters are specified as a string of "name=value" pairs of the form "param1=value1; param2=value2;..." delimited by semicolons.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

OracleXmlQueryProperties Public Methods

The `OracleXmlQueryProperties` public methods are listed in [Table 7-6](#).

Table 7-6 OracleXmlQueryProperties Public Methods

Name	Description
Clone	Creates a copy of an <code>OracleXmlQueryProperties</code> object

Clone

This method creates a copy of an `OracleXmlQueryProperties` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An `OracleXmlQueryProperties` object

Implements

`ICloneable`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

OracleXmlSaveProperties Class

An `OracleXmlSaveProperties` object represents the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.

Class Inheritance

`System.Object`

`System.OracleXmlSaveProperties`

Declaration

```
public sealed class OracleXmlSaveProperties : ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

OracleXmlSaveProperties can be accessed and modified using the XmlSaveProperties property of the OracleCommand class. Each OracleCommand object has its own instance of the OracleXmlSaveProperties class in the XmlSaveProperties property.

Use the default constructor to get a new instance of OracleXmlSaveProperties. Use the OracleXmlSaveProperties.Clone() method to get a copy of an OracleXmlSaveProperties instance.

Example

This sample demonstrates how to do inserts, updates, and deletes to a relational table or view using an XML document.

```
// C#
/* -- If HR account is being locked, you need to log on as a DBA
   -- to unlock the account first. Unlock a locked users account:

ALTER USER hr ACCOUNT UNLOCK;
*/

using System;
using Oracle.DataAccess.Client;

class OracleXmlSavePropertiesSample
{
    static void Main()
    {
        string[] KeyColumnsList = null;
        string[] UpdateColumnsList = null;
        int rows = 0;

        // Create the connection.
        string constr = "User Id=hr;Password=hr;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create the command.
```

```
OracleCommand cmd = new OracleCommand("", con);

// Set the XML command type to insert.
cmd.XmlCommandType = OracleXmlCommandType.Insert;

// Set the XML document.
cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
    "<ROWSET>\n" +
    "  <MYROW num = \"1\">\n" +
    "    <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Smith</LAST_NAME>\n" +
    "    <EMAIL>Smith@Oracle.com</EMAIL>\n" +
    "    <HIRE_DATE>1982-01-23T00:00:00.000</HIRE_DATE>\n" +
    "    <JOB_ID>IT_PROG</JOB_ID>\n" +
    "  </MYROW>\n" +
    "  <MYROW num = \"2\">\n" +
    "    <EMPLOYEE_ID>1235</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Barney</LAST_NAME>\n" +
    "    <EMAIL>Barney@Oracle.com</EMAIL>\n" +
    "    <HIRE_DATE>1982-01-23T00:00:00.000</HIRE_DATE>\n" +
    "    <JOB_ID>IT_PROG</JOB_ID>\n" +
    "  </MYROW>\n" +
    "</ROWSET>\n";

// Set the XML save properties.
KeyColumnsList = new string[1];
KeyColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList = new string[5];
UpdateColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList[1] = "LAST_NAME";
UpdateColumnsList[2] = "EMAIL";
UpdateColumnsList[3] = "HIRE_DATE";
UpdateColumnsList[4] = "JOB_ID";
cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
cmd.XmlSaveProperties.RowTag = "MYROW";
cmd.XmlSaveProperties.Table = "employees";
cmd.XmlSaveProperties.UpdateColumnsList = UpdateColumnsList;
cmd.XmlSaveProperties.Xslt = null;
cmd.XmlSaveProperties.XsltParams = null;

// Do the inserts.
rows = cmd.ExecuteNonQuery();
Console.WriteLine("rows: " + rows);

// Set the XML command type to update.
cmd.XmlCommandType = OracleXmlCommandType.Update;

// Set the XML document.
cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
    "<ROWSET>\n" +
    "  <MYROW num = \"1\">\n" +
    "    <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Adams</LAST_NAME>\n" +
    "  </MYROW>\n" +
    "</ROWSET>\n";

// Set the XML save properties.
KeyColumnsList = new string[1];
KeyColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList = new string[1];
UpdateColumnsList[0] = "LAST_NAME";
```

```
cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
cmd.XmlSaveProperties.UpdateColumnsList = UpdateColumnsList;
rows = cmd.ExecuteNonQuery();
Console.WriteLine("rows: " + rows);

// Set the XML command type to delete.
cmd.XmlCommandType = OracleXmlCommandType.Delete;

// Set the XML document.
cmd.CommandText = "<?xml version='1.0'?>\n" +
    "<ROWSET>\n" +
    "  <MYROW num = \"1\">\n" +
    "    <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    "  </MYROW>\n" +
    "  <MYROW num = \"2\">\n" +
    "    <EMPLOYEE_ID>1235</EMPLOYEE_ID>\n" +
    "  </MYROW>\n" +
    "</ROWSET>\n";

// Set the XML save properties.
KeyColumnsList = new string[1];
KeyColumnsList[0] = "EMPLOYEE_ID";
cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
cmd.XmlSaveProperties.UpdateColumnsList = null;

// Do the deletes.
rows = cmd.ExecuteNonQuery();
Console.WriteLine("rows: " + rows);

// Clean up.
cmd.Dispose();
con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Members](#)
- [OracleXmlSaveProperties Constructor](#)
- [OracleXmlSaveProperties Properties](#)
- [OracleXmlSaveProperties Public Methods](#)

OracleXmlSaveProperties Members

OracleXmlSaveProperties members are listed in the following tables.

OracleXmlSaveProperties Constructor

OracleXmlSaveProperties constructors are listed in [Table 7-7](#)

Table 7-7 OracleXmlSaveProperties Constructor

Constructor	Description
OracleXmlSaveProperties Constructor	Instantiates a new instance of the OracleXmlSaveProperties class

OracleXmlSaveProperties Properties

The OracleXmlSaveProperties properties are listed in [Table 7-8](#).

Table 7-8 OracleXmlSaveProperties Properties

Name	Description
KeyColumnsList	Specifies the list of columns used as a key to locate existing rows for update or delete using an XML document
RowTag	Specifies the value for the XML element that identifies a row of data in an XML document
Table	Specifies the name of the table or view to which changes are saved
UpdateColumnsList	Specifies the list of columns to update or insert
Xslt	Specifies the XSL document used for XML transformation using XSLT
XsltParams	Specifies the parameters for the XSLT document specified in the Xslt property

OracleXmlSaveProperties Public Methods

The OracleXmlSaveProperties public methods are listed in [Table 7-9](#).

Table 7-9 OracleXmlSaveProperties Public Methods

Name	Description
Clone	Creates a copy of an OracleXmlSaveProperties object

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlSaveProperties Constructor

The `OracleXmlSaveProperties` constructor instantiates a new instance of `OracleXmlSaveProperties` class.

Declaration

```
// C#  
public OracleXmlSaveProperties;
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlSaveProperties Properties

The `OracleXmlSaveProperties` properties are listed in [Table 7-10](#).

Table 7-10 OracleXmlSaveProperties Properties

Name	Description
KeyColumnsList	Specifies the list of columns used as a key to locate existing rows for update or delete using an XML document
RowTag	Specifies the value for the XML element that identifies a row of data in an XML document
Table	Specifies the name of the table or view to which changes are saved
UpdateColumnsList	Specifies the list of columns to update or insert
Xslt	Specifies the XSL document used for XML transformation using XSLT
XsltParams	Specifies the parameters for the XSLT document specified in the <code>Xslt</code> property

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

KeyColumnsList

This property specifies the list of columns used as a key to locate existing rows for update or delete using an XML document.

Declaration

```
// C#  
public string[] KeyColumnsList {get; set;}
```

Property Value

The list of columns.

Remarks

Default value is null.

The first null value (if any) terminates the list.

`KeyColumnsList` usage with `XMLCommandType` property values:

- Insert - `KeyColumnsList` is ignored and can be null.
- Update - `KeyColumnsList` must be specified; it identifies the columns to use to find the rows to be updated.
- Delete - If `KeyColumnsList` is null, all the column values in each row element in the XML document are used to locate the rows to delete. Otherwise, `KeyColumnsList` specifies the columns used to identify the rows to delete.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

RowTag

This property specifies the value for the XML element that identifies a row of data in an XML document.

Declaration

```
// C#  
public string RowTag {get; set;}
```

Property Value

An XML element name.

Remarks

The default value is `ROW`.

Each element in the XML document identifies one row in a table or view.

If `RowTag` is set to `" "` or `null`, no row tag is used in the XML document. In this case, the XML document is assumed to contain only one row.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

Table

This property specifies the name of the table or view to which changes are saved.

Declaration

```
// C#  
public string Table {get; set;}
```

Property Value

A table name.

Remarks

Default value is `null`.

The property must be set to a valid table or view name.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

UpdateColumnsList

This property specifies the list of columns to update or insert.

Declaration

```
// C#  
public string[] UpdateColumnsList {get; set;}
```

Property Value

A list of columns.

Remarks

Default value is null.

The first null value (if any) terminates the list.

UpdateColumnList usage with XMLCommandType property values:

- Insert - UpdateColumnList indicates which columns are assigned values when a new row is created. If UpdateColumnList is null, then all columns are assigned values. If a column is on the UpdateColumnList, but no value is specified for the row in the XML file, then NULL is used. If a column is not on the UpdateColumnList, then the default value for that column is used.
- Update - UpdateColumnList specifies columns to modify for each row of data in the XML document. If UpdateColumnList is null, all the values in each XML element in the XML document are used to modify the columns.
- Delete - UpdateColumnsList is ignored and can be null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

Xslt

This property specifies the XSL document used for XML transformation using XSLT.

Declaration

```
// C#  
public string Xslt {get; set;}
```

Property Value

The XSL document used for XML transformation.

Remarks

Default = null.

The XSL document is used for XSLT transformation of a given XML document. The transformed XML document is used to save changes to the table or view.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

XsltParams

This property specifies the parameters for the XSLT document specified in the `xslt` property.

Declaration

```
// C#  
public string XsltParams {get; set;}
```

Property Value

The parameters for the XSLT document.

Remarks

Default is `null`.

This property is a string delimited by semicolons in "name=value" pairs of the form "param1=value1; param2=value2; ...".

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlSaveProperties Public Methods

The `OracleXmlSaveProperties` public methods are listed in [Table 7-11](#).

Table 7-11 OracleXmlSaveProperties Public Methods

Name	Description
Clone	Creates a copy of an <code>OracleXmlSaveProperties</code> object

Clone

This method creates a copy of an `OracleXmlSaveProperties` object.

Declaration

```
// C#
public object Clone();
```

Return Value

An `OracleXmlSaveProperties` object

Implements

`ICloneable`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlStream Class

An `OracleXmlStream` object represents a read-only stream of XML data stored in an `OracleXmlType` object.

Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.Stream
            System.OracleXmlStream
```

Declaration

```
// C#
public sealed class OracleXmlStream : IDisposable, ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Namespace	Oracle.DataAccess .Client	Oracle.ManagedDat aAccess.Client	Oracle.ManagedDat aAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Members](#)
- [OracleXmlStream Constructor](#)
- [OracleXmlStream Static Methods](#)
- [OracleXmlStream Instance Properties](#)
- [OracleXmlStream Instance Methods](#)

OracleXmlStream Members

OracleXmlStream members are listed in the following tables.

OracleXmlStream Constructors

The OracleXmlStream constructors are listed in [Table 7-12](#).

Table 7-12 OracleXmlStream Constructors

Constructor	Description
OracleXmlStream Constructor	Creates an instance of an OracleXmlStream object which provides a Stream representation of the XML data stored in an OracleXmlType

OracleXmlStream Static Methods

The OracleXmlStream static methods are listed in [Table 7-13](#).

Table 7-13 OracleXmlStream Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleXmlStream Instance Properties

The OracleXmlStream instance properties are listed in [Table 7-14](#).

Table 7-14 OracleXmlStream Instance Properties

Properties	Description
CanRead	Indicates whether or not the XML stream can be read
CanSeek	Indicates whether or not forward and backward seek operation can be performed
CanWrite	OracleXmlStream is a sequential read only, forward only stream.
Connection	Indicates the OracleConnection that is used to retrieve the XML data
Length	Indicates the number of bytes in the XML stream
Position	Gets or sets the byte position within the stream
Value	Returns the XML data, starting from the first character in the stream as a string

OracleXmlStream Instance Methods

The OracleXmlStream instance methods are listed in [Table 7-15](#).

Table 7-15 OracleXmlStream Instance Methods

Methods	Description
BeginRead	Inherited from System.IO.Stream
BeginWrite	Inherited from System.IO.Stream
Clone	Creates a copy of an OracleXmlStream object
Close	Closes the current stream and releases any resources associated with it
Dispose	Releases resources allocated by this object
EndRead	Inherited from System.IO.Stream
EndWrite	Inherited from System.IO.Stream
Equals	Inherited from System.Object
Flush	<i>Not Supported</i>
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
Read	Reads a specified amount from the current stream instance and populates the array buffer (Overloaded)
ReadByte	Inherited from System.IO.Stream

Table 7-15 (Cont.) OracleXmlStream Instance Methods

Methods	Description
Seek	Sets the position within the current stream and returns the new position within the current stream
SetLength	<i>Not Supported</i>
ToString	Inherited from <code>System.Object</code>
Write	<i>Not Supported</i>
WriteByte	<i>Not Supported</i>
WriteLine	<i>Not Supported</i>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)

OracleXmlStream Constructor

This constructor creates an instance of an `OracleXmlStream` object which provides a Stream representation of the XML data stored in an `OracleXmlType` object.

Declaration

```
// C#  
public OracleXmlStream(OracleXmlType xmlType);
```

Parameters

- `xmlType`
The `OracleXmlType` object.

Remarks

The `OracleXmlStream` implicitly uses the `OracleConnection` object from the `OracleXmlType` object from which it was constructed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlStream Static Methods

The OracleXmlStream static methods are listed in [Table 7-16](#).

Table 7-16 OracleXmlStream Static Methods

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlStream Instance Properties

The OracleXmlStream instance properties are listed in [Table 7-17](#).

Table 7-17 OracleXmlStream Instance Properties

Properties	Description
CanRead	Indicates whether or not the XML stream can be read
CanSeek	Indicates whether or not forward and backward seek operation can be performed
CanWrite	OracleXmlStream is a sequential read only, forward only stream.
Connection	Indicates the <code>OracleConnection</code> that is used to retrieve the XML data
Length	Indicates the number of bytes in the XML stream
Position	Gets or sets the byte position within the stream
Value	Returns the XML data, starting from the first character in the stream as a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

CanRead

Overrides `Stream`

This property indicates whether or not the XML stream can be read.

Declaration

```
// C#  
public override bool CanRead{get;}
```

Property Value

If the XML stream is can be read, returns `true`; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

CanSeek

Overrides `Stream`

This property indicates whether or not forward and backward seek operation can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, this property returns `true`. Otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

CanWrite

Overrides `Stream`

`OracleXmlStream` is a sequential read only, forward only stream.

Declaration

```
// C#  
public override bool CanWrite {get;}
```

Property Value

Always returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Connection

This instance property indicates the `OracleConnection` that is used to retrieve the XML data.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Length

Overrides `Stream`

This property indicates the number of bytes in the XML stream.

Declaration

```
// C#  
public override Int64 Length{get;}
```

Property Value

An `Int64` value representing the number of bytes in the XML stream. An empty stream has a length of 0 bytes.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Position

Overrides `Stream`

This property gets or sets the byte position within the stream.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An `Int64` that indicates the current position in the stream.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Position` is less than 0.

Remarks

The beginning of the stream is represented by position 0. Seeking to any location beyond the length of the stream is supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Value

This property returns the XML data, starting from the first character of the stream as a string.

Declaration

```
// C#  
public string Value{get; set;}
```

Property Value

A string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The value of `Position` is neither used nor changed by using this property.

The maximum length of the string that can be returned by this property is 2 GB.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlStream Instance Methods

The OracleXmlStream instance methods are listed in [Table 7-18](#).

Table 7-18 OracleXmlStream Instance Methods

Methods	Description
BeginRead	Inherited from System.IO.Stream
BeginWrite	Inherited from System.IO.Stream
Clone	Creates a copy of an OracleXmlStream object
Close	Closes the current stream and releases any resources associated with it
Dispose	Releases resources allocated by this object
EndRead	Inherited from System.IO.Stream
EndWrite	Inherited from System.IO.Stream
Equals	Inherited from System.Object
Flush	<i>Not Supported</i>
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
Read	Reads a specified amount from the current XML stream instance and populates the array buffer (Overloaded)
ReadByte	Inherited from System.IO.Stream
Seek	Sets the position within the current stream and returns the new position within the current stream
SetLength	<i>Not Supported</i>
ToString	Inherited from System.Object
Write	<i>Not Supported</i>
WriteByte	<i>Not Supported</i>
WriteLine	<i>Not Supported</i>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Clone

This method creates a copy of an `OracleXmlStream` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An `OracleXmlStream` object.

Implements

`ICloneable`

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Close

Overrides `Stream`

This method closes the current stream and releases any resources associated with it.

Declaration

```
// C#  
public override void Close();
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Dispose

This public method releases resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

The object cannot be reused after being disposed. Although some properties can still be accessed, their values cannot be accountable. Since resources are freed, method calls can lead to exceptions.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Flush

This method is not supported.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Read

This method reads a specified amount from the current XML stream instance and populates the array buffer.

Overload List:

- [Read\(byte\[\], int, int\)](#)
This method reads a specified amount of unicode bytes from the current instance, advances the position within the stream, and populates the byte array buffer.
- [Read\(char\[\], int, int\)](#)
This method reads a specified amount of characters from the current instance, advances the position within the stream, and populates the character array buffer.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Read(byte[], int, int)

Overrides `Stream`

This method reads a specified amount of unicode bytes from the current instance, advances the position within the stream, and populates the byte array buffer.

Declaration

```
// C#  
public override int Read(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer that is populated.
- *offset*

The zero-based offset (in bytes) at which the buffer is populated.

- *count*

The maximum amount of bytes to be read.

Return Value

The number of unicode bytes read into the given `byte[]` buffer or 0 if the end of the stream has been reached.

Remarks

This method reads a maximum of *count* bytes from the current stream and stores them in buffer beginning at *offset*. The current position within the stream is advanced by the number of bytes read. However, if an exception occurs, the current position within the stream remains unchanged.

The XML data is read starting from the position specified by the `Position` property.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Read(char[], int, int)

Overrides `Stream`

This method reads a specified amount of characters from the current instance, advances the position within the stream, and populates the character array buffer.

Declaration

```
// C#  
public override int Read(char[] buffer, int offset, int count);
```

Parameters

- *buffer*

The character array buffer to be populated.

- *offset*

The zero-based offset (in characters) in the buffer at which the buffer is populated.

- *count*

The maximum amount of characters to be read from the stream.

Return Value

The return value indicates the number of characters read from the stream or 0 if the end of the stream has been reached.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

This method requires that the `Position` on the stream instance be zero or an even number.

The XML data is read starting from the position specified by the `Position` property.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Seek

Overrides `Stream`.

This method sets the position within the current stream and returns the new position within the current stream.

Declaration

```
// C#  
public long Seek(long offset, SeekOrigin origin);
```

Parameters

- *offset*

A byte offset relative to origin.

- If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.
- If *offset* is zero, the new position is the position specified by *origin*.
- If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.

- *origin*
A value of type `SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

The new `Position` within the current stream.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object

Remarks

Use the `CanSeek` property to determine whether or not the current instance supports seeking. Seeking to any location beyond the length of the stream is supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

SetLength

This method is not supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Write

This method is not supported.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

WriteLine

This method is not supported.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlType Class

An `OracleXmlType` object represents an Oracle XMLType instance.

Class Inheritance

`System.Object`

`System.OracleXmlType`

Declaration

```
// C#
public sealed class OracleXmlType : IDisposable, INullable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

OracleXmlType objects can be used for well-formed XML documents with or without XML schemas or XML fragments.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Members](#)
- [OracleXmlType Constructors](#)
- [OracleXmlType Static Methods](#)
- [OracleXmlType Static Fields](#)
- [OracleXmlType Instance Properties](#)
- [OracleXmlType Instance Methods](#)

OracleXmlType Members

OracleXmlType members are listed in the following tables.

OracleXmlType Constructors

The OracleXmlType constructors are listed in [Table 7-19](#).

Table 7-19 OracleXmlType Constructors

Constructor	Description
OracleXmlType Constructors	Creates an instance of the OracleXmlType class (Overloaded)

OracleXmlType Static Methods

The OracleXmlType static methods are listed in [Table 7-20](#).

Table 7-20 OracleXmlType Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleXmlType Static Fields

The OracleXmlType static field is listed in [Table 7-21](#).

Table 7-21 OracleXmlType Static Field

Static Field	Description
Null	Represents a null value that can be assigned to an OracleXmlType instance

OracleXmlType Instance Properties

The OracleXmlType instance properties are listed in [Table 7-22](#).

Table 7-22 OracleXmlType Instance Properties

Properties	Description
Connection	Indicates the OracleConnection that is used to retrieve and store XML data in the OracleXmlType
IsEmpty	Indicates whether or not the OracleXmlType is empty
IsFragment	Indicates whether the XML data is a collection of XML elements or a well-formed XML document
IsNull	Indicates whether or not the OracleXmlType is null
IsSchemaBased	Indicates whether or not the XML data represented by the OracleXmlType is based on an XML schema
RootElement	Represents the name of the top-level element of the schema-based XML data contained in the OracleXmlType
Schema	Represents the XML schema of the XML data contained in the OracleXmlType
SchemaUrl	Represents in the database for the XML schema of the XML data contained in the OracleXmlType.
Value	Returns the XML data starting from the first character in the current instance as a string

OracleXmlType Instance Methods

The OracleXmlType instance methods are listed in [Table 7-23](#).

Table 7-23 OracleXmlType Instance Methods

Methods	Description
Clone	Creates a copy of the OracleXmlType instance
Dispose	Releases the resources allocated by this OracleXmlType object
Equals	Inherited from System.Object
Extract	Extracts a subset from the XML data using the given XPath expression (Overloaded)

Table 7-23 (Cont.) OracleXmlType Instance Methods

Methods	Description
GetHashCode	Inherited from <code>System.Object</code>
GetStream	Returns an instance of <code>OracleXmlStream</code> which provides a read-only stream of the XML data stored in this <code>OracleXmlType</code> instance
GetType	Inherited from <code>System.Object</code>
GetXmlDocument	Returns a <code>XmlDocument</code> object containing the XML data stored in this <code>OracleXmlType</code> instance
GetXmlReader	Returns a <code>XmlTextReader</code> object that can be used to manipulate XML data directly using the .NET Framework classes and methods
IsExists	Checks for the existence of a particular set of nodes identified by the given XPath expression in the XML data (Overloaded)
ToString	Inherited from <code>System.Object</code>
Transform	Transforms the <code>OracleXmlType</code> into another <code>OracleXmlType</code> instance using the given XSL document (Overloaded)
Update	Updates the XML node or fragment identified by the given XPath expression in the current <code>OracleXmlType</code> instance (Overloaded)
Validate	Validates whether or not the XML data in the <code>OracleXmlType</code> object conforms to the given XML schema.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)

OracleXmlType Constructors

`OracleXmlType` constructors create instances of the `OracleXmlType` class.

Overload List:

- [OracleXmlType\(OracleClob\)](#)
This constructor creates an instance of the `OracleXmlType` class using the XML data contained in an `OracleClob` object.
- [OracleXmlType\(OracleConnection, string\)](#)
This constructor creates an instance of the `OracleXmlType` class using the XML data contained in the .NET `String`.
- [OracleXmlType\(OracleConnection, XmlReader\)](#)

This constructor creates an instance of the `OracleXmlType` class using the contents of the .NET `XmlReader` object.

- [OracleXmlType\(OracleConnection, XmlDocument\)](#)

This constructor creates an instance of the `OracleXmlType` object using the contents of the XML [DOM](#) document in the .NET `XmlDocument` object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleClob)

This constructor creates an instance of the `OracleXmlType` class using the XML data contained in an `OracleClob` object.

Declaration

```
// C#  
public OracleXmlType(OracleClob oraClob);
```

Parameters

- `oraClob`
An `OracleClob` object.

Exceptions

`ArgumentNullException` - The `OracleClob` object is null.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The `CLOB` data depends on a valid connection object and the new `OracleXMLType` uses the `OracleConnection` in the `OracleClob` object to store data for the current instance.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleConnection, string)

This constructor creates an instance of the `OracleXmlType` class using the XML data contained in the .NET `String`.

Declaration

```
// C#  
public OracleXmlType(OracleConnection con, string xmlData);
```

Parameters

- `con`
An `OracleConnection` object.
- `xmlData`
A string containing the XML data.

Exceptions

`ArgumentNullException` - The `OracleConnection` object is null.

`ArgumentException` - The `xmlData` argument is an empty string.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The new `OracleXmlType` uses the given `OracleConnection` object to store data for the current instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleConnection, XmlReader)

This constructor creates an instance of the `OracleXmlType` class using the contents of the .NET `XmlReader` object.

Declaration

```
// C#  
public OracleXmlType(OracleConnection con, XmlReader reader);
```

Parameters

- `con`

An `OracleConnection` object.

- `reader`

An `XmlReader` object.

Exceptions

`ArgumentNullException` - The `OracleConnection` object is null.

`ArgumentException` - The `reader` argument contains no data.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The new `OracleXMLType` uses the given `OracleConnection` object to store data for the current instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleConnection, XmlDocument)

This constructor creates an instance of the `OracleXmlType` object using the contents of the XML [DOM](#) document in the .NET `XmlDocument` object.

Declaration

```
// C#  
public OracleXmlType(OracleConnection con, XmlDocument domDoc);
```

Parameters

- `con`
An `OracleConnection` object.
- `domDoc`
An XML document.

Exceptions

`ArgumentNullException` - The `OracleConnection` object is null.

`ArgumentException` - The `domDoc` argument contains no data.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The new `OracleXMLType` uses the given `OracleConnection` object to store data for the current instance.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Static Methods

The `OracleXmlType` static methods are listed in [Table 7-24](#).

Table 7-24 OracleXmlType Static Methods

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Static Fields

The `OracleXmlType` static field is listed in [Table 7-25](#).

Table 7-25 OracleXmlType Static Field

Static Field	Description
<code>Null</code>	Represents a null value that can be assigned to an <code>OracleXmlType</code> instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Null

This static field represents a null value that can be assigned to an `OracleXmlType` instance.

Declaration

```
// C#
public static readonly OracleXmlType Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Instance Properties

The `OracleXmlType` instance properties are listed in [Table 7-26](#).

Table 7-26 OracleXmlType Instance Properties

Properties	Description
Connection	Indicates the <code>OracleConnection</code> that is used to retrieve and store XML data in the <code>OracleXmlType</code>
IsEmpty	Indicates whether or not the <code>OracleXmlType</code> is empty
IsFragment	Indicates whether the XML data is a collection of XML elements or a well-formed XML document
IsNull	Indicates whether or not the <code>OracleXmlType</code> is null
IsSchemaBased	Indicates whether or not the XML data represented by the <code>OracleXmlType</code> is based on an XML schema
Null	Represents a null value that can be assigned to an <code>OracleXmlType</code> instance
RootElement	Represents the name of the top-level element of the schema-based XML data contained in the <code>OracleXmlType</code>

Table 7-26 (Cont.) OracleXmlType Instance Properties

Properties	Description
Schema	Represents the XML schema of the XML data contained in the OracleXmlType
SchemaUrl	Represents URL in the database for the XML schema of the XML data contained in the OracleXmlType
Value	Returns the XML data starting from the first character in the current instance as a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Connection

This property indicates the `OracleConnection` that is used to retrieve and store XML data in the `OracleXmlType`.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An `OracleConnection` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The connection must explicitly be opened by the user before creating or using `OracleXmlType`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsEmpty

This property indicates whether or not the `OracleXmlType` is empty.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

Returns `true` if the `OracleXmlType` represents an empty XML document. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsFragment

This property indicates whether the XML data is a collection of XML elements or a well-formed XML document.

Declaration

```
// C#  
public bool IsFragment {get;}
```

Property Value

Returns `true` if the XML data contained in the `OracleXmlType` object is a collection of XML elements with no root element. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsNull

This property indicates whether or not the `OracleXmlType` is null.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns `true` if the `OracleXmlType` represents a null value. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsSchemaBased

This property indicates whether or not the XML data represented by the `OracleXmlType` is based on an XML schema.

Declaration

```
// C#  
public bool IsSchemaBased {get;}
```

Property Value

Returns `true` if the XML data represented by the `OracleXmlType` is based on an XML schema. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

RootElement

This property represents the name of the top-level or root element of the schema-based XML data contained in the `OracleXmlType`.

Declaration

```
// C#  
public string RootElement{get;}
```

Property Value

A string that represents the name of the top-level or root element of the XML data contained in the `OracleXmlType`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Schema

This property represents the XML schema for the XML data contained in the `OracleXmlType`.

Declaration

```
// C#  
public OracleXmlType Schema {get;}
```

Property Value

An `OracleXmlType` instance that represents the XML schema for the XML data contained in the `OracleXmlType`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an `OracleXmlType` instance representing an empty XML document.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

SchemaUrl

This property represents the XML schema in the database for the XML schema of the XML data contained in the `OracleXmlType`.

Declaration

```
// C#  
public string SchemaUrl {get;}
```

Property Value

A string that represents the URL in the database for the XML schema of the XML data.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Value

This property returns the XML data starting from the first character in the current instance as a `string`.

Declaration

```
// C#  
public string Value{get;}
```

Property Value

The entire XML data as a `string`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Instance Methods

The `OracleXmlType` instance methods are listed in [Table 7-27](#).

Table 7-27 OracleXmlType Instance Methods

Methods	Description
Clone	Creates a copy of the OracleXmlType instance
Dispose	Releases the resources allocated by this OracleXmlType object
Equals	Inherited from System.Object
Extract	Extracts a subset from the XML data using the given XPath expression (Overloaded)
GetHashCode	Inherited from System.Object
GetStream	Returns an instance of OracleXmlStream which provides a read-only stream of the XML data stored in this OracleXmlType instance
GetType	Inherited from System.Object
GetXmlDocument	Returns a XmlDocument object containing the XML data stored in this OracleXmlType instance
GetXmlReader	Returns a XmlTextReader object that can be used to manipulate XML data directly using the .NET Framework classes and methods
IsExists	Checks for the existence of a particular set of nodes identified by the given XPath expression in the XMLdata (Overloaded)
ToString	Inherited from System.Object
Transform	Transforms the OracleXmlType into another OracleXmlType instance using the given XSL document (Overloaded)
Update	Updates the XML node or fragment identified by the given XPath expression in the current OracleXmlType instance (Overloaded)
Validate	Validates whether or not the XML data in the OracleXmlType object conforms to the given XML schema.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Clone

This method creates a copy of this OracleXmlType instance.

Declaration

```
// C#
public object Clone();
```

Implements

ICloneable

Return Value

An OracleXmlType object.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Dispose

This method releases the resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Extract

This method extracts a subset from the XML data using the given XPath expression.

Overload List:

- [Extract\(string, string\)](#)

This method extracts a subset from the XML data represented by the `OracleXmlType` object using the given XPath expression and a string parameter for namespace resolution.

- [Extract\(string, XmlNamespaceManager\)](#)

This method extracts a subset from the XML data represented by the `OracleXmlType` object, using the given XPath expression and a .NET `XmlNamespaceManager` object for namespace resolution.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Extract(string, string)

This method extracts a subset from the XML data represented by the `OracleXmlType` object using the given XPath expression and a string parameter for namespace resolution.

Declaration

```
// C#  
public OracleXmlType Extract(string xpathExpr, string nsMap);
```

Parameters

- *xpathExpr*
The XPath expression.
- *nsMap*
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null. For example:

```
xmlns:ns1="http://www.company1.com" xmlns:ns2="http://www.company2.com"
```

Return Value

An `OracleXmlType` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Extract(string, XmlNameSpaceManager)

This public method extracts a subset from the XML data represented by the OracleXmlType object, using the given XPath expression and a .NET XmlNameSpaceManager object for namespace resolution.

Declaration

```
// C#  
public OracleXmlType Extract(string xpathExpr, XmlNameSpaceManager nsMgr);
```

Parameters

- *xpathExpr*
The XPath expression.
- *nsMgr*
The .NET XmlNameSpaceManager object used for namespace resolution of the XPath expression. *nsMgr* can be null.

Return Value

An OracleXmlType.

Exceptions

ObjectDisposedException - The object is already disposed.

ArgumentNullException - The *xpathExpr* is null or zero-length.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

GetStream

This public method returns an instance of `OracleXmlStream` which provides a read-only stream of the XML data stored in this `OracleXmlType` instance.

Declaration

```
// C#  
public Stream GetStream();
```

Return Value

A `Stream` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

GetXmlDocument

This public method returns a `XmlDocument` object containing the XML data stored in this `OracleXmlType` instance.

Declaration

```
// C#  
public XmlDocument GetXmlDocument();
```

Return Value

An `XmlDocument` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The XML data in the `XmlDocument` object is a copy of the XML data in the `OracleXmlType` instance and modifying it does not automatically modify the XML data in the `OracleXmlType` instance. The `XmlDocument` instance returned has the `PreserveWhitespace` property set to `true`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

GetXmlReader

This public method returns a `XmlTextReader` object that can be used to manipulate XML data directly using the .NET Framework classes and methods.

Declaration

```
// C#  
public XmlTextReader GetXmlReader();
```

Return Value

An `XmlTextReader` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The `XmlTextReader` is a read-only, forward-only representation of the XML data stored in the `OracleXmlType` instance.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsExists

`IsExists` checks for the existence of a particular set of nodes identified by the XPath expression in the XML data.

Overload List:

- [IsExists\(string, string\)](#)
This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML data represented by the current `OracleXmlType` instance using a string parameter for namespace resolution.
- [IsExists\(string, XmlNamespaceManager\)](#)
This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML document represented by the current `OracleXmlType` instance using a .NET `XmlNamespaceManager` object for namespace resolution.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsExists(string, string)

This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML data represented by the current `OracleXmlType` instance using a string parameter for namespace resolution.

Declaration

```
// C#  
public bool IsExists(string xpathExpr, string nsMap);
```

Parameters

- `xpathExpr`
The XPath expression.

- *nsMap*
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null.

Return Value

Returns `true` if the required set of nodes exists; otherwise, returns `false`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsExists(string, XmlNameSpaceManager)

This method checks the existence of a particular set of nodes identified by the XPath expression in the XML document represented by the current `OracleXmlType` instance using a `.NET XmlNameSpaceManager` object for namespace resolution.

Declaration

```
// C#  
public bool IsExists(string xpathExpr, XmlNameSpaceManager nsMgr);
```

Parameters

- *xpathExpr*
The XPath expression.
- *nsMgr*
The `.NET XmlNameSpaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.

Return Value

Returns `true` if the required set of nodes exists; otherwise, returns `false`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The `xpathExpr` is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Transform

This method transforms the `OracleXmlType` into another `OracleXmlType` instance using the given XSL document.

Overload List:

- [Transform\(OracleXmlType, string\)](#)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document (as an `OracleXmlType` object) and a string of XSLT parameters.

- [Transform\(string, string\)](#)

This public method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Transform(OracleXmlType, string)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

Declaration

```
// C#  
public OracleXmlType Transform(OracleXmlType xslDoc, string paramMap);
```

Parameters

- `xslDoc`
The XSL document as an `OracleXmlType` object.
- `paramMap`
A string which provides the parameters for the XSL document.
For this release, `paramMap` is ignored.

Return Value

An `OracleXmlType` object containing the transformed XML document.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The `xslDoc` parameter is null.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Transform(string, string)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

Declaration

```
// C#  
public OracleXmlType Transform(string xslDoc, string paramMap);
```

Parameters

- *xslDoc*
The XSL document to be used for XSLT.
- *paramMap*
A string which provides the parameters for the XSL document.
For this release, *paramMap* is ignored.

Return Value

An `OracleXmlType` object containing the transformed XML document.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xslDoc* parameter is null.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update

This method updates the XML node or fragment identified by the given XPath expression in the current `OracleXmlType` instance.

Overload List:

- [Update\(string, string, string\)](#)
This method updates the XML nodes identified by the given XPath expression with the given string value and a string parameter for namespace resolution.
- [Update\(string, XmlNamespaceManager, string\)](#)
This method updates the XML nodes identified by the given XPath expression with the given string value and a .NET `XmlNamespaceManager` object for namespace resolution.
- [Update\(string, string, OracleXmlType\)](#)
This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a string parameter for namespace resolution.

- [Update\(string, XmlNamespaceManager, OracleXmlType\)](#)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a .NET `XmlNamespaceManager` object for namespace resolution.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, string, string)

This method updates the XML nodes identified by the given XPath expression with the given string value and a string parameter for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, string nsMap, string value);
```

Parameters

- *xpathExpr*
The XPath expression that identifies the nodes to update.
- *nsMap*
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null. For example:

```
xmlns:ns1="http://www.company1.com" xmlns:ns2="http://www.company2.com"
```
- *value*
The new value as a string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, XmlNamespaceManager, string)

This method updates the XML nodes identified by the given XPath expression with the given string value and a .NET `XmlNamespaceManager` object for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, XmlNamespaceManager nsMgr, string  
value);
```

Parameters

- *xpathExpr*
The XPath expression that identifies the nodes to update.
- *nsMgr*
The .NET `XmlNamespaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.
- *value*
The new value as a string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, string, OracleXmlType)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a string parameter for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, string nsMap, OracleXmlType value);
```

Parameters

- *xpathExpr*
The XPath expression that identifies the nodes to update.
- *nsMap*
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null.
- *value*
The new value as an `OracleXmlType` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, XmlNamespaceManager, OracleXmlType)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a .NET `XmlNamespaceManager` object for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, XmlNamespaceManager nsMgr, OracleXmlType  
value);
```

Parameters

- *xpathExpr*
The XPath expression that identifies the nodes to update.
- *nsMgr*
The .NET `XmlNamespaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.
- *value*
The new value as an `OracleXmlType` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Validate

This methods validates whether or not the XML data in the `OracleXmlType` object conforms to the given XML schema.

Declaration

```
// C#  
public bool Validate(String schemaUrl);
```

Parameters

- `schemaUrl`
A string representing the [URL](#) in the database of the XML schema.

Return Value

Returns true if the XML data conforms to the XML schema; otherwise, returns false.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentNullException` - The `schemaUrl` argument is null or an empty string.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

8

Oracle Data Provider for .NET HA Event Classes

This chapter describes the following ODP.NET HA event class and enumerations:

- [OracleHAEventArgs Class](#)
- [OracleHAEventHandler Delegate](#)
- [OracleHAEventSource Enumeration](#)
- [OracleHAEventStatus Enumeration](#)

OracleHAEventArgs Class

The `OracleHAEventArgs` class provides event data for the `OracleConnection.HAEvent` event.

Class Inheritance

```
System.Object
    System.EventArgs
        Oracle.DataAccess.Client.OracleHAEventArgs
```

Declaration

```
// C#
public sealed class OracleHAEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

When any HA event occurs for a service, service member, host, node, or instance that an `OracleConnection` object is set to with `"ha_events=true"`, the `OracleConnection.HAEvent` is triggered and passes an instance of `OracleHAEventArgs` to all the delegates that have registered with the event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Members](#)
- [OracleHAEventArgs Properties](#)
- ["OracleConnection Class"](#)
- ["HAEvent"](#)

OracleHAEventArgs Members

`OracleHAEventArgs` members are listed in the following table.

OracleHAEventArgs Properties

The `OracleHAEventArgs` properties are listed in [Table 8-2](#).

Table 8-1 OracleHAEventArgs Properties

Name	Description
DatabaseDomainName	Specifies the domain name of the database affected by the <code>HAEvent</code>
DatabaseName	Specifies the database affected by the <code>HAEvent</code>
DrainTimeout	Indicates the number of seconds allowed for resource draining to be completed during a planned outage
HostName	Specifies the host that triggered the event
InstanceName	Specifies the instance that triggered the event
Reason	Specifies the reason for which the HA event was sent by the server
ServiceName	Specifies the service that triggered the event
Source	Specifies the source that triggered the event
Status	Specifies the status of the source that triggered the event
Time	Specifies the time when the event was triggered on the server

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- ["HAEvent"](#)

OracleHAEventArgs Properties

The OracleHAEventArgs properties are listed in [Table 8-2](#).

Table 8-2 OracleHAEventArgs Properties

Name	Description
DatabaseDomainName	Specifies the domain name of the database affected by the HAevent
DatabaseName	Specifies the database affected by the HAevent
DrainTimeout	Indicates the number of seconds allowed for resource draining to be completed during a planned outage
HostName	Specifies the host that triggered the event
InstanceName	Specifies the instance that triggered the event
Reason	Specifies the reason for which the HA event was sent by the server
ServiceName	Specifies the service that triggered the event
Source	Specifies the source that triggered the event
Status	Specifies the status of the source that triggered the event
Time	Specifies the time when the event was triggered on the server

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)

DatabaseDomainName

This property specifies the domain name of the database that is affected by the HA event.

Declaration

```
// C#
public string DatabaseDomainName {get;}
```

Property Value

The domain name of the database that is affected by the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

DatabaseName

This property specifies the database that is affected by the HA event.

Declaration

```
// C#  
public string DatabaseName {get;}
```

Property Value

This property specifies the database name that is affected by the HA event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

DrainTimeout

An integer value indicating the maximum time period in seconds that ODP.NET waits for the service to drain connections from the database service from when the Fast Application Notification `SERVICE DOWN` event is received.

Declaration

```
// C#  
public int DrainTimeout {get;}
```

Property Value

The number of seconds allowed for resource draining to be completed during a planned outage

Remarks

When connecting to Oracle Data Guard in Oracle Database 12c Release 2 or later, database administrators can set their own timeout value, `drain_timeout`, to indicate the number of seconds allowed for resource draining to be completed during a planned outage. The `drain_timeout` value populates `OracleHAEventArgs.DrainTimeout.drain_timeout` can be used by the ODP.NET `ServiceRelocationConnectionTimeout` to wait for a service to be relocated before attempting new connections.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)
- [ServiceRelocationConnectionTimeout](#)

HostName

This property specifies the host that triggered the HA event.

Declaration

```
// C#  
public string HostName {get;}
```

Property Value

The host that is affected by the HA Event.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

InstanceName

This property specifies the instance that triggered the HA event.

Declaration

```
// C#  
public string InstanceName {get;}
```

Property Value

The instance that is affected by the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

Reason

This property specifies reason for which the HA event was sent by the server.

Declaration

```
// C#  
public string Reason {get;}
```

Property Value

The reason the HA Event was triggered. Possible values include `Data_Guard_Failover`, `Failure`, `Dependency`, `User`, `Autostart`, and `Restart`.

The value `User` is indicative of a planned outage. All other values are indicative of an unplanned outage.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

ServiceName

This property specifies the service that triggered the HA event.

Declaration

```
// C#  
public string ServiceName {get;}
```

Property Value

The service that is affected by the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

Source

This property specifies the source that triggered the HA event.

Declaration

```
// C#  
public OracleHAEventSource Source {get;}
```

Property Value

The source that triggered the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

Status

This property specifies the status of the source that triggered the HA event.

Declaration

```
// C#  
public OracleHAEventStatus Status {get;}
```

Property Value

The status of the source that triggered the HA Event.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

Time

This property specifies the time when the HA event was triggered on the server.

Declaration

```
// C#  
public DateTime Time {get;}
```

Property Value

The time that the HA Event was triggered.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#)

OracleHAEventHandler Delegate

The `OracleHAEventHandler` delegate represents the signature of the method that handles the `OracleConnection.HAEvent` event.

Declaration

```
// C#
public delegate void OracleHAEvEntHandler(OracleHAEvEntArgs eventArgs);
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Parameters

- *sender*
The source of the event.
- *EventArgs*
The OracleHAEvEntArgs object that contains the event data.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEvEntArgs Class](#)
- ["HAEvent"](#)

OracleHAEvEntSource Enumeration

The OracleHAEvEntSource enumeration indicates the source of the HA event.

[Table 8-3](#) lists all the OracleHAEvEntSource enumeration values with a description of each enumerated value.

Table 8-3 OracleHAEvEntSource Enumeration Member Values

Member Name	Description
Service	The source of the HA Event is a service.
ServiceMember	The source of the HA Event is a service member.
Database	The source of the HA Event is a database.
Host	The source of the HA Event is a host.

Table 8-3 (Cont.) OracleHAEventSource Enumeration Member Values

Member Name	Description
Instance	The source of the HA Event is an instance.
Node	The source of the HA Event is a node.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- ["Source"](#)

OracleHAEventStatus Enumeration

The `OracleHAEventStatus` enumeration indicates the status of the HA event source.

[Table 8-4](#) lists all the `OracleHAEventStatus` enumeration values with a description of each enumerated value.

Table 8-4 OracleHAEventStatus Enumeration Values

Member Name	Description
Up	The source of the HA Event is up.
Down	The source of the HA Event is down.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleHAEventArgs Class](#)
- ["Status"](#)

9

Continuous Query Notification Classes

This chapter describes Oracle Data Provider for .NET Continuous Query Notification Classes, Event Delegates, and Enumerations.



See Also:

["Continuous Query Notification Support "](#)

This chapter contains these topics:

- [OracleDependency Class](#)
- [OracleNotificationRequest Class](#)
- [OracleNotificationEventArgs Class](#)
- [OnChangeEventHandler Delegate](#)
- [OracleRowidInfo Enumeration](#)
- [OracleNotificationType Enumeration](#)
- [OracleNotificationSource Enumeration](#)
- [OracleNotificationInfo Enumeration](#)

OracleDependency Class

An `OracleDependency` class represents a dependency between an application and an Oracle database, enabling the application to get notifications whenever the data of interest or the state of the Oracle database changes.

Class Inheritance

```
System.Object
```

```
Oracle.DataAccess.Client.OracleDependency
```

Declaration

```
// C#  
public sealed class OracleDependency
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess .dll	Oracle.ManagedDat aAccess.dll	Oracle.ManagedDat aAccess.dll

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Namespace	Oracle.DataAccess. Client	Oracle.ManagedDat aAccess.Client	Oracle.ManagedDat aAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Members](#)
- [OracleDependency Constructors](#)
- [OracleDependency Static Fields](#)
- [OracleDependency Static Methods](#)
- [OracleDependency Methods](#)
- [OracleDependency Properties](#)
- [OracleDependency Events](#)

OracleDependency Members

OracleDependency members are listed in the following tables.

OracleDependency Constructors

OracleDependency constructors are listed in [Table 9-1](#).

Table 9-1 OracleDependency Constructors

Constructors	Description
OracleDependency Constructors	Instantiates a new instance of OracleDependency class (Overloaded)

OracleDependency Static Fields

The OracleDependency static fields are listed in [Table 9-2](#).

Table 9-2 OracleDependency Static Fields

Static Field	Description
Address	Indicates the address that the notification listener listens on, for database notifications Supported in ODP.NET Core only
Port	Indicates the port number that the notification listener listens on, for database notifications

OracleDependency Static Methods

OracleDependency static methods are listed in [Table 9-3](#).

Table 9-3 OracleDependency Static Methods

Static Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
GetOracleDependency	Returns an <code>OracleDependency</code> instance based on the specified unique identifier

OracleDependency Properties

OracleDependency properties are listed in [Table 9-4](#).

Table 9-4 OracleDependency Properties

Properties	Description
DataSource	Indicates the data source associated with the <code>OracleDependency</code> instance
HasChanges	Indicates whether or not there is any change in the database associated with this dependency
Id	Represents the unique identifier for the <code>OracleDependency</code> instance
IsEnabled	Specifies whether or not the dependency is enabled between the application and the database
QueryBasedNotification	Specifies whether the change notification registration is object-based or query-based
RegisteredQueryIDs	Provides a list of <code>CHANGE_NOTIFICATION_QUERY_IDS</code>
RegisteredResources	Indicates the database resources that are registered in the notification registration
RowidInfo	Specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database
UserName	Indicates the database user name associated with the <code>OracleDependency</code> instance

OracleDependency Methods

OracleDependency methods are listed in [Table 9-5](#).

Table 9-5 OracleDependency Methods

Methods	Description
AddCommandDependency	Binds the OracleDependency instance to the specified OracleCommand instance
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
RemoveRegistration	Removes the specified dependency between the application and the database
ToString	Inherited from System.Object

OracleDependency Events

The OracleDependency event is listed in [Table 9-6](#).

Table 9-6 OracleDependency Events

Event	Description
OnChange	An event that is sent when a database notification associated with the dependency is received from the database

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)

OracleDependency Constructors

OracleDependency constructors create instances of the OracleDependency class.

Overload List:

- [OracleDependency \(\)](#)
This constructor creates an instance of the OracleDependency class.
- [OracleDependency\(OracleCommand\)](#)
This constructor creates an instance of the OracleDependency class and binds it to the specified OracleCommand instance.
- [OracleDependency\(OracleCommand, bool, int, bool\)](#)
This constructor creates an instance of the OracleDependency class and binds it to the specified OracleCommand instance, specifying whether or not a notification is to

be removed upon notification, the timeout value of the notification registration, and the persistence of the notification.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency ()

This constructor creates an instance of the `OracleDependency` class.

Declaration

```
// C#  
public OracleDependency ( )
```

Remarks

Using this constructor does not bind any `OracleCommand` to the newly constructed `OracleDependency`. Use the `AddCommandDependency` method to do so.

 **Note:**

The dependency between the application and the database is not established when the `OracleDependency` instance is created. The dependency is established when the command that is associated with this dependency is executed.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency(OracleCommand)

This constructor creates an instance of the `OracleDependency` class and binds it to an `OracleCommand` instance.

Declaration

```
// C#  
public OracleDependency (OracleCommand cmd)
```

Parameters

- *cmd*

The command that the `OracleDependency` object binds to.

Exceptions

`ArgumentNullException` - The *cmd* parameter is null.

`InvalidOperationException` - The specified `OracleCommand` instance already contains a notification request.

Remarks

When this `OracleDependency` constructor binds the `OracleCommand` instance to an `OracleDependency` instance, it causes the creation of an `OracleNotificationRequest` instance and then sets that `OracleNotificationRequest` instance to the `OracleCommand.Notification` property.

The Continuous Query Notification is registered with the database, when the command is executed. Any of the command execution methods (for example, `ExecuteNonQuery`, `ExecuteReader`, and so on) will register the notification request. An `OracleDependency` may be bound to more than one `OracleCommand`. When one of these `OracleCommand` object statements is executed, the statement is registered with the associated `OracleCommand`. Although the registration happens on each `OracleCommand` separately, one `OracleDependency` can be responsible for detecting and sending notifications that occur for all `OracleCommand` objects that the `OracleDependency` is associated with. The `OnChangeEventArgs` that is passed to the application for the `OnChange` event provides information on what has changed in the database.

The `OracleNotificationRequest` instance that is created by this constructor has the following default property values:

- `IsNotifiedOnce` is set to the value `True`.
- `Timeout` is set to 50,000 seconds.
- `IsPersistent` is set to the value `False`, that is, the invalidation message is not persistent, but is stored in an in-memory queue before delivery.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency(OracleCommand, bool, int, bool)

This constructor creates an instance of the `OracleDependency` class and binds it to the specified `OracleCommand` instance, while specifying whether or not a registration is to be removed upon notification, the timeout value of the notification registration, and the persistence of the notification.

Declaration

```
// C#  
public OracleDependency (OracleCommand cmd, bool isNotifiedOnce, long timeout,  
    bool isPersistent)
```

Parameters

- *cmd*
The command associated with the Continuous Query Notification request.
- *isNotifiedOnce*
An indicator that specifies whether or not the registration is removed automatically once the notification occurs.
- *timeout*
The amount of time, in seconds, that the registration stays active. When *timeout* is set to 0, the registration never expires. The valid values for *timeout* are between 0 and 4294967295.
- *isPersistent*
Indicates whether or not the invalidation message should be queued persistently in the database before delivery. If the *isPersistent* parameter is set to `True`, the message is queued persistently in the database and cannot be lost upon database failures or shutdowns. If the *isPersistent* property is set to `False`, the message is stored in an in-memory queue before delivery and might be lost.

Database performance is faster if the message is stored in an in-memory queue rather than in the database queue.

Exceptions

`ArgumentNullException` - The *cmd* parameter is null.

`ArgumentOutOfRangeException` - The specified *timeout* is invalid.

`InvalidOperationException` - The specified `OracleCommand` instance already contains a notification request.

Remarks

When this `OracleDependency` constructor binds the `OracleCommand` instance to an `OracleDependency` instance, it causes the creation of an `OracleNotificationRequest` instance and then sets that `OracleNotificationRequest` instance to the `OracleCommand.Notification` property.

The Continuous Query Notification is registered with the database, when the command is executed. Any of the command execution methods (for example, `ExecuteNonQuery`, `ExecuteReader`, and so on) will register the notification request. An

OracleDependency may be bound to more than one OracleCommand. When one of these OracleCommand object statements is executed, the statement is registered with the associated OracleCommand. Although the registration happens on each OracleCommand separately, one OracleDependency can be responsible for detecting and sending notifications that occur for all OracleCommand objects that the OracleDependency is associated with. The OnChangeEventArgs that is passed to the application for the OnChange event provides information on what has changed in the database.

The OracleNotificationRequest instance that is created by this constructor has the following default property values:

- IsNotifiedOnce is set to the specified value.
- Timeout is set to the specified value.
- IsPersistent is set to the specified value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Static Fields

The OracleDependency static fields are listed in [Table 9-7](#).

Table 9-7 OracleDependency Static Fields

Static Field	Description
Address	Indicates the address that the notification listener listens on, for database notifications Supported in ODP.NET Core only
Port	Indicates the port number that the notification listener listens on, for database notifications

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

Address

This static field indicates the address that the notification listener listens on, for database notifications.

Declaration

```
// C#  
public static string Address{get; set}
```

Property Value

A `string` value that represents the address that listens for the database notifications.

If the address is not set, then `OracleConfiguration.DBNotificationAddress` will be used if set. If `OracleDependency.Address` is explicitly set to `string.Empty` or null, then the hostname will be used.

Remarks

This property allows specifying a particular IPv4 or IPv6 address to use, such as the case with a machine that contains multiple network cards. The address can be set to any valid hostname, IPv4, or IPv6 address, which is associated with the machine on which the ODP.NET application is running on, which will be listening for notifications.

The address specified by the `OracleDependency.Address` static field is used by the notification listener that runs within the same application domain as ODP.NET. This address receives Continuous Query Notifications from the database. One notification listener is capable of listening to all Continuous Query Notifications and therefore, only one notification listener is created for each application domain.

The notification listener is created when a command associated with an `OracleDependency` object is executed for the first time during the application domain lifetime. The address specified for the `OracleDependency.Address` static field is used by the listener for its lifetime. The `OracleDependency.Address` static field can be changed after the creation of the notification listener, but doing so does not affect the actual address that the notification listener listens on.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

Port

This static field indicates the port number that the notification listener listens on, for database notifications.

Declaration

```
// C#
public static int Port{get; set}
```

Property Value

An `int` value that represents the number of the port that listens for the database notifications. If the port number is set to `-1`, a random port number is assigned for the listener when the listener is started. Otherwise, the specified port number is used to start the listener.

Exceptions

`ArgumentOutOfRangeException` - The port number is set to a negative value.

`InvalidOperationException` - The port number is being changed after the listener has started.

Remarks

The port number specified by the `OracleDependency.Port` static field is used by the notification listener that runs within the same application domain as ODP.NET. This port number receives Continuous Query Notifications from the database. One notification listener is capable of listening to all Continuous Query Notifications and therefore, only one notification listener is created for each application domain.

The notification listener is created when a command associated with an `OracleDependency` object is executed for the first time during the application domain lifetime. The port number specified for the `OracleDependency.Port` static field is used by the listener for its lifetime. The `OracleDependency.Port` static field can be changed after the creation of the notification listener, but doing so does not affect the actual port number that the notification listener listens on.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Static Methods

`OracleDependency` static methods are listed in [Table 9-8](#).

Table 9-8 OracleDependency Static Methods

Static Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code>

Table 9-8 (Cont.) OracleDependency Static Methods

Static Methods	Description
GetOracleDependency	Returns an <code>OracleDependency</code> instance based on the specified unique identifier

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

GetOracleDependency

This static method returns an `OracleDependency` instance based on the specified unique identifier.

Declaration

```
// C#  
public static OracleDependency GetOracleDependency(string guid)
```

Parameters

- *guid*
The string representation of the unique identifier of an `OracleDependency` instance.

Exceptions

`ArgumentException` - The specified unique identifier cannot locate an `OracleDependency` instance.

Return Value

An `OracleDependency` instance that has the specified *guid* parameter.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Properties

OracleDependency properties are listed in [Table 9-9](#).

Table 9-9 OracleDependency Properties

Properties	Description
DataSource	Indicates the data source associated with the OracleDependency instance
HasChanges	Indicates whether or not there is any change in the database associated with this dependency
Id	Represents the unique identifier for the OracleDependency instance
IsEnabled	Specifies whether or not the dependency is enabled between the application and the database
QueryBasedNotification	Specifies whether the change notification registration is object-based or query-based
RegisteredQueryIDs	Provides a list of CHANGE_NOTIFICATION_QUERY_IDS
RegisteredResources	Indicates the database resources that are registered in the notification registration
RowidInfo	Specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database
UserName	Indicates the database user name associated with the OracleDependency instance

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

DataSource

This property indicates the data source associated with the OracleDependency instance.

Declaration

```
// C#  
public string DataSource{get;}
```

Property Value

A string that indicates the data source associated with the OracleDependency instance.

Remarks

The `DataSource` property is populated with the data source once the `OracleCommand` associated with the `OracleDependency` executes and registers for the notification successfully.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

HasChanges

This property indicates whether or not there is any change in the database associated with this dependency.

Declaration

```
// C#  
public bool HasChanges{get;}
```

Property Value

A `bool` value that returns `True` if the database has detected changes that are associated with this dependency; otherwise, returns `False`.

Remarks

As an alternative to using the `OnChange` event, applications can check the `HasChanges` property to determine if there are any changes in the database associated with this dependency.

Once the `HasChanges` property is accessed, its value is reset to `False` so that the next notification can then be acknowledged.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

Id

This property represents the unique identifier for the `OracleDependency` instance.

Declaration

```
// C#  
public string Id{get;}
```

Property Value

A string that represents the unique identifier that was generated for the `OracleDependency` instance when it was created.

Remarks

This property is set when the `OracleDependency` instance is created.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

IsEnabled

This property specifies whether or not the dependency is enabled between the application and the database.

Declaration

```
// C#  
public bool IsEnabled {get;}
```

Property Value

A `bool` value that specifies whether or not dependency is enabled between the application and the database.

Remarks

The dependency between the application and the database is not established when the `OracleDependency` instance is created. The dependency is established when the command that is associated with this dependency is executed, at which time the notification request is registered with the database. The dependency ends when the notification registration is removed from the database or when it times out.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

QueryBasedNotification

This instance property specifies whether the change notification registration is object-based or query-based.

Declaration

```
// C#  
public bool QueryBasedNotification{get; set;}
```

Property Value

Specifies whether the change notification registration is object-based or not.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property value will be ignored if it is set after the command execution that registers the command for change notification.

By default, this property is true.

ODP.NET developers can register their queries on the row level, not just the object level, beginning with Oracle Data Provider for .NET release 11.1 and Oracle Database 11g release 1 (11.1). The application only receives notification when the selected row or rows change. Query-based notifications provide developers more granularity for using client-side cached data, as they can be more specific about what changes the application needs to be notified of.

`OracleNotificationType` enumeration is set to `Query` for query-based notifications.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

RegisteredQueryIDs

This instance property provides a list of `CHANGE_NOTIFICATION_QUERY_IDS`.

Declaration

```
// C#  
public ArrayList RegisteredQueryIDs {get;}
```

Property Value

This property is an `ArrayList` of `CHANGE_NOTIFICATION_QUERY_IDS`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property provides a list of `CHANGE_NOTIFICATION_QUERY_IDS` that uniquely identify the query that has been registered for change notification. The notification returned from the database will also contain these IDs, allowing applications to determine the query that the notifications are for.

The `QueryId` at index n in `RegisteredQueryIDs` is for the statement at index n the `RegisteredResources` at index n .



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

RegisteredResources

This property indicates the database resources that are registered in the notification registration.

Declaration

```
// C#  
public ArrayList RegisteredResources{get;}
```

Property Value

The registered resources in the notification registration.

Remarks

The `ArrayList` contains all the command statement or statements that are registered for notification through this `OracleDependency` object. It is appropriately updated when the Continuous Query Notification is registered by a command execution.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

RowidInfo

This property specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database.

Declaration

```
// C#  
public OracleRowidInfo RowidInfo {get; set;};
```

Property Value

An `OracleRowidInfo` enumeration type that determines the inclusion of ROWID in the change notification event.

Remarks

There are three `OracleRowidInfo` enumeration types that are valid for this property:

- `Default` includes ROWID information in the change notification event only if `OracleCommand.AddRowid` property is set to true or if ROWID is in the select list of the query that is registered for change notification.
- `Include` includes ROWID information regardless of whether or not ROWID is in the select-list for the query.
- `Exclude` excludes ROWID information regardless of whether or not ROWID is in the select-list.

For change notification registrations that involve stored procedure executions, change notification events related to the `REF CURSOR` contain ROWID information only if `RowidInfo` property is set to `OracleRowidInfo.Include`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)
- ["OracleRowidInfo Enumeration"](#)

UserName

This property indicates the database user name associated with the `OracleDependency` instance.

Declaration

```
// C#  
public string UserName{get;}
```

Property Value

A string that indicates the database user name associated with the `OracleDependency` instance. This database user registers the Continuous Query Notification request with the database.

Remarks

The `UserName` property is populated with the user name once the `OracleCommand` associated with the `OracleDependency` executes and registers for the notification successfully. Only the database user who creates the notification registration, or the database system administrator, can remove the registration.

The user specified by this property must have the `CHANGE NOTIFICATION` privilege to register successfully for the Continuous Query Notification with the database.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Methods

`OracleDependency` methods are listed in [Table 9-10](#).

Table 9-10 OracleDependency Methods

Methods	Description
AddCommandDependency	Binds the OracleDependency instance to the specified OracleCommand instance
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
RemoveRegistration	Removes the specified dependency between the application and the database
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

AddCommandDependency

This instance method binds the OracleDependency instance to the specified OracleCommand instance.

Declaration

```
// C#  
Public void AddCommandDependency (OracleCommand cmd);
```

Parameters

- *cmd*

The command that is to be bound to the OracleDependency object.

Exceptions

ArgumentNullException - The *cmd* parameter is null.

InvalidOperationException - The specified OracleCommand instance already contains a notification request.

Remarks

An OracleDependency instance can bind to multiple OracleCommand instances.

While it binds an existing OracleDependency instance to an OracleCommand instance, the AddCommandDependency method creates an OracleNotificationRequest instance, and sets it to the specified OracleCommand.Notification property.

When this method creates an `OracleNotificationRequest` instance, the following `OracleNotificationRequest` properties are set:

- `IsNotifiedOnce` is set to the value `True`.
- `Timeout` is set to 50,000 seconds.
- `IsPersistent` is set to the value `False`, indicating that the invalidation message is stored in an in-memory queue before delivery.

With this method, multiple commands can be associated with a single `Continuous Query Notification` registration request. Furthermore, the `OracleNotificationRequest` attribute values assigned to the `OracleCommand` can be changed once the association between the `OracleCommand` and the `OracleDependency` is established.

However, when multiple `OracleCommand` objects are associated with a single `OracleDependency` object, the `OracleNotificationRequest` attributes (`Timeout`, `IsPersistent`, and `IsNotifiedOnce`) of the first executed `OracleCommand` object are used for registration, the attributes associated with subsequent `OracleCommand` executions will be ignored.

Furthermore, once a command associated with an `OracleDependency` is executed and registered, all other subsequent command executions and registration associated with the same `OracleDependency` must use a connection with the same "User Id" and "Data Source" connection string attribute value settings.

Otherwise, an exception will be thrown.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)
- ["OracleDependency\(OracleCommand\)"](#) for `OracleNotificationRequest` property value

RemoveRegistration

This instance method removes the specified dependency between the application and the database. Once the registration of the dependency is removed from the database, the `OracleDependency` is no longer able to detect any changes that the database undergoes.

Declaration

```
// C#  
public void RemoveRegistration(OracleConnection con)
```

Parameters

- `con`
The connection associated with the `OracleDependency` instance.

Exceptions

`InvalidOperationException` - The associated connection is not open.

Remarks

The notification registration associated with the `OracleDependency` instance is removed from the database.

The `OracleConnection` parameter must be in an *opened state*. This instance method does not open the connection implicitly for the application.

An exception is thrown if the dependency is not valid.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Events

The `OracleDependency` event is listed in [Table 9-11](#).

Table 9-11 OracleDependency Event

Event	Description
OnChange	An event that is sent when a database notification associated with the dependency is received from the database

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OnChange

The `OnChange` event is sent when a database notification associated with the dependency is received from the database. The information related to the notification is stored in the `OracleChangeNotificationEventArgs` class.

Declaration

```
// C#
public event OnChangeEventHandler OnChange;
```

Remarks

The `OnChange` event occurs if any result set associated with the dependency changes. For objects that are part of a Transaction, notifications will be received for each modified object. This event also occurs for other actions related to database or registration status, such as database shutdowns and startups, or registration timeouts.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleNotificationRequest Class

An `OracleNotificationRequest` class represents a notification request to be subscribed in the database. It contains information about the request and the characteristics of the notification. Using the `OracleNotificationRequest` class, Oracle Data Provider for .NET can create the notification registration in the database.

Class Inheritance

System.Object

Oracle.DataAccess.Client.OracleNotificationRequest

Declaration

```
// C#
public sealed class OracleNotificationRequest
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Static Methods](#)
- [OracleNotificationRequest Properties](#)
- [OracleNotificationRequest Methods](#)

OracleNotificationRequest Members

OracleNotificationRequest members are listed in the following tables.

OracleNotificationRequest Static Method

The OracleNotificationRequest static method is listed in [Table 9-12](#).

Table 9-12 OracleNotificationRequest Static Method

Static Method	Description
Equals	Inherited from System.Object

OracleNotificationRequest Properties

OracleNotificationRequest properties are listed in [Table 9-13](#).

Table 9-13 OracleNotificationRequest Properties

Properties	Description
IsNotifiedOnce	Indicates whether or not the registration is to be removed upon notification
IsPersistent	Indicates whether or not the notification message should be queued persistently in the database before delivery
Timeout	Specifies the time that the registration remains alive
GroupingNotificationEnabled	Specifies whether grouping notification is enabled or not
GroupingType	Specifies the type of grouping notification
GroupingInterval	Specifies the interval between grouping notifications, in seconds

OracleNotificationRequest Methods

OracleNotificationRequest methods are listed in [Table 9-14](#).

Table 9-14 OracleNotificationRequest Methods

Methods	Description
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationRequest Static Methods

The OracleNotificationRequest static method is listed in [Table 9-15](#).

Table 9-15 OracleNotificationRequest Static Method

Static Method	Description
Equals	Inherited from System.Object

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationRequest Properties

The OracleNotificationRequest properties are listed in [Table 9-16](#).

Table 9-16 OracleNotificationRequest Properties

Properties	Description
IsNotifiedOnce	Indicates whether or not the registration is to be removed upon notification
IsPersistent	Indicates whether or not the notification message should be queued persistently in the database before delivery
Timeout	Specifies the time that the registration remains alive
GroupingNotificationEnabled	Specifies whether grouping notification is enabled or not
GroupingType	Specifies the type of grouping notification
GroupingInterval	Specifies the interval between grouping notifications, in seconds

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

IsNotifiedOnce

This property indicates whether or not the registration is to be removed upon notification.

Declaration

```
// C#  
public bool IsNotifiedOnce{get; set;}
```

Property Value

A `bool` value that indicates whether or not the registration is to be removed upon notification.

Remarks

The default value is `false` for AQ. This is different from change notification where the default value is `true`.

Modifying this property after the completion of a successful registration has no effect.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

IsPersistent

This property indicates whether or not the notification message should be queued persistently in the database until delivery.

Declaration

```
// C#  
public bool IsPersistent{get; set;}
```

Property Value

A `bool` value that indicates whether or not the notifications should be stored persistently in the database until delivery.

When the `IsPersistent` property is set to `True`, the message is queued persistently in the database and cannot be lost upon database failures or shutdowns. When the `IsPersistent` property is set to `False`, the message is stored in an in-memory queue before delivery and could be lost.

This property does not apply to `NotificationRegistration` which is always persistent.

This property only applies to the notification message after it has been sent.

Remarks

The default value is `false`.

The database performs faster if the message is stored in an in-memory queue rather than a database queue.

Modifying this property after the completion of a successful registration has no effect.

This property is ignored for grouping notifications.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

Timeout

This property specifies the time, in seconds, that the registration remains alive.

Declaration

```
// C#  
public long Timeout {get; set}
```

Property Value

A `long` value that specifies the time, in seconds, that the registration remains alive. The valid values for the `Timeout` property are between 0 and 4294967295.

Exceptions

`ArgumentOutOfRangeException` - The specified `Timeout` is invalid.

Remarks

The default value is 0 (infinite) for AQ and 50000 for change notification. If the `Timeout` property is set to 0, then the registration does not expire.

If the registration is removed because the `Timeout` value has been reached, then the database sends a notification indicating the expiration.

Modifying this property after the completion of a successful registration has no effect.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

GroupingNotificationEnabled

This property specifies whether to group notifications together by time is enabled or not.

Declaration

```
// C#  
public bool GroupingNotificationEnabled {get; set}
```

Property Value

A `true` value indicates that grouping notification is enabled. A `false` value indicates that grouping notification is disabled.

Remarks

The default value is `false`.

Modifying this property after the completion of a successful registration has no effect.

If enabled, then ODP.NET will group notifications together that occur during the same time period. The time period is defined by `OracleNotificationRequest.GroupingInterval`.

If disabled, then notifications will be generated immediately after the event that triggers them.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

GroupingType

This property specifies the type of grouping notification, which can summarize all notifications during the time period or only the last notification.

Declaration

```
// C#  
public OracleAQNotificationGroupingType GroupingType {get; set}
```

Property Value

An `OracleAQNotificationGroupingType` enum value. The possible enum values are `OracleAQNotificationGroupingType.Summary` and `OracleAQNotificationGroupingType.Last`.

Remarks

The default value is `OracleAQNotificationGroupingType.Summary`.

Modifying this property after the completion of a successful registration has no effect.

`OracleAQNotificationGroupingType.Summary` : All notifications in the group are summarized into a single notification.

Note:

The single notification does not include ROWIDS, even if ROWID information was requested to be returned.

`OracleAQNotificationGroupingType.Last` : Only the last notification in the group is published. The earlier ones discarded.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

GroupingInterval

This property specifies the interval of grouping notification in seconds. The group notifications are delivered at intervals specified by this property.

Declaration

```
// C#
public int GroupingInterval {get; set}
```

Property Value

An integer specifying the grouping interval in seconds.

Remarks

If this value is 900, then notifications generated in the same 15 minute interval are grouped together into a single notification. The default value is 600 seconds.

The range of `GroupingInterval` is from 1 to `Int32.MaxValue`.

Modifying this property after the completion of a successful registration has no effect.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationRequest Methods

`OracleNotificationRequest` methods are listed in [Table 9-17](#).

Table 9-17 OracleNotificationRequest Methods

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
<code>GetHashCode</code>	Inherited from <code>System.Object</code>

Table 9-17 (Cont.) OracleNotificationRequest Methods

Methods	Description
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationEventArgs Class

The `OracleNotificationEventArgs` class provides event data for a notification.

Class Inheritance

System.Object

System.EventArgs

Oracle.DataAccess.Client.OracleNotificationEventArgs

Declaration

```
// C#
public sealed class OracleNotificationEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Members](#)
- [OracleNotificationEventArgs Static Fields](#)
- [OracleNotificationEventArgs Static Methods](#)
- [OracleNotificationEventArgs Properties](#)
- [OracleNotificationEventArgs Methods](#)

OracleNotificationEventArgs Members

OracleNotificationEventArgs members are listed in the following tables.

OracleNotificationEventArgs Static Fields

The OracleNotificationEventArgs static field is listed in [Table 9-18](#).

Table 9-18 OracleNotificationEventArgs Static Field

Static Field	Description
Empty	Inherited from System.EventArgs

OracleNotificationEventArgs Static Methods

The OracleNotificationEventArgs static method is listed in [Table 9-19](#).

Table 9-19 OracleNotificationEventArgs Static Method

Static Method	Description
Equals	Inherited from System.Object

OracleNotificationEventArgs Properties

OracleNotificationEventArgs properties are listed in [Table 9-20](#).

Table 9-20 OracleNotificationEventArgs Properties

Properties	Description
Details	Contains detailed information about the current notification
Info	Indicates the database events for the notification
ResourceNames	Indicates the database resources related to the current notification
Source	Returns the database event source for the notification
Type	Returns the database event type for the notification

OracleNotificationEventArgs Methods

OracleNotificationEventArgs methods are listed in [Table 9-21](#).

Table 9-21 OracleNotificationEventArgs Methods

Methods	Description
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)

OracleNotificationEventArgs Static Fields

The OracleNotificationEventArgs static field is listed in [Table 9-22](#).

Table 9-22 OracleNotificationEventArgs Static Field

Static Field	Description
Empty	Inherited from System.EventArgs

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OracleNotificationEventArgs Static Methods

The OracleNotificationEventArgs static method is listed in [Table 9-23](#).

Table 9-23 OracleNotificationEventArgs Static Method

Static Method	Description
Equals	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OracleNotificationEventArgs Properties

OracleNotificationEventArgs properties are listed in [Table 9-24](#).

Table 9-24 OracleNotificationEventArgs Properties

Properties	Description
Details	Contains detailed information about the current notification
Info	Indicates the database events for the notification
ResourceNames	Indicates the database resources related to the current notification
Source	Returns the database event source for the notification
Type	Returns the database event type for the notification

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

Details

This property contains detailed information about the current notification.

Declaration

```
// C#
Public DataTable Details{get;}
```

Property Value

A `DataTable` instance that contains detailed information about the current notification.

Remarks

The returned `DataTable` object contains column data about the current notification in order as shown in [Table 9-25](#).

Table 9-25 DataTable Object Column Data

Name	Type	Description
ResourceName	System.String	The resource name of the invalidated object in the format <Schema_name>.<object_name>
Info	OracleNotificationInfo	The information about the database event that occurs on a resource
Rowid	System.String	The rowid for the invalidated table row
QueryId	Int32	The CHANGE_NOTIFICATION_QUERY_ID

The `QueryId` column contains the `CHANGE_NOTIFICATION_QUERY_ID` that corresponds to the pseudo-column that may have been retrieved by a `SELECT` statement at the time of the query-based notification. Also, the `OracleDependency` object maintains all the `CHANGE_NOTIFICATION_QUERY_IDS` that are registered with it.

For Continuous Query Notification:

- The `Details` property indicates changes for each invalidated object in the notification in the data table.
- If `ROWID` information is requested, then the `ROWID` information is populated into the `Rowid` column. However, if many rows are modified in a table, then the whole table is invalidated, and `ROWID` information is not provided. Therefore, the `Rowid` column contains all `Null` values.
- If the database event is related to a DDL change of the table or a table drop, then the `Rowid` column is set to `Null`.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

Info

This property indicates the database events for the notification.

Declaration

```
// C#  
public OracleNotificationInfo Info{get;}
```

Property Value

An `OracleNotificationInfo` value that indicates the database event for the notification.

Remarks

The `OracleNotificationInfo` value is an enumeration type. If several events are received from the invalidation message, the `Info` property is set to one of the `OracleNotificationInfo` enumeration values associated with the database events. For example, if a table has been altered and a new row has been inserted into another table, the `Info` property is set to either `OracleNotificationInfo.Altered` or `OracleNotificationInfo.Insert`.

To obtain more detailed information from the invalidation message, use the `Details` and the `ResourceNames` properties.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["Details"](#)
- ["ResourceNames"](#)
- ["OracleNotificationInfo Enumeration"](#)

ResourceNames

This property indicates the database resources related to the current notification.

Declaration

```
// C#  
public string[] ResourceNames{get;}
```

Property Value

A string array that indicates the database resources related to the current notification.

Remarks

For Continuous Query Notification, the `ResourceNames` property contains information about the invalidated object names in the format `<schema_name>.<object_name>`. To obtain more detailed information about the changes for invalidated objects, use the `Details` property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["Details"](#)

Source

This property returns the database event source for the notification.

Declaration

```
// C#  
public OracleNotificationSource Source{get;}
```

Property Value

The `OracleNotificationSource` value for the notification.

Remarks

The `OracleNotificationSource` value is an enumeration type. If several event sources are received from the notification message, the `Source` property is set to one of the `OracleNotificationSource` enumeration values related to the database event source. For example, if a table has been altered (by the `ALTER TABLE` command) and a new row has been inserted into the same table, the `Source` property is set to either `OracleNotificationSource.Object` or `OracleNotificationSource.Data`.

For Continuous Query Notification:

- When the `Source` property is set to `OracleNotificationSource.Data`:
 - The `Info` property is set to one of the following:
 - * `OracleNotificationInfo.Insert`
 - * `OracleNotificationInfo.Delete`
 - * `OracleNotificationInfo.Update`
 - The `ResourceNames` property is set, and the elements are set to the invalidated object names.
 - The `Details` property contains detailed information on the change of each invalidated table.
- When the `Source` property is set to `OracleNotificationSource.Database`:
 - The `Info` property is set to one of the following:
 - * `OracleNotificationInfo.Startup`
 - * `OracleNotificationInfo.Shutdown`
 - * `OracleNotificationInfo.Shutdown_Any`

- * OracleNotificationInfo.Dropped
- When the `Source` property is set to `OracleNotificationSource.Object`:
 - The `Info` property is set to either `OracleNotificationInfo.Altered` or `OracleNotificationInfo.Dropped`.
 - The `ResourceNames` property is set, and the array elements of the `ResourceNames` property are set to the object names that have been altered or dropped.
 - The `Details` property contains detailed information on the changes of the object.
- When the `Source` property is set to `OracleNotificationSource.Subscription`:
 - The `Info` property is set to the following:
 - * OracleNotificationInfo.End

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["OracleNotificationSource Enumeration"](#)

Type

This property returns the database event type for the notification.

Declaration

```
// C#  
public OracleNotificationType Type{get;}
```

Property Value

An `OracleNotificationType` enumeration value that represents the type of the database event notification.

Remarks

The `OracleNotificationType` value is an enumeration type. If several event types are received from the notification message, then the `Type` property is set to one of the `OracleNotificationType` enumeration values related to the database event type.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["OracleNotificationType Enumeration"](#)

OracleNotificationEventArgs Methods

OracleNotificationEventArgs methods are listed in [Table 9-26](#).

Table 9-26 OracleNotificationEventArgs Methods

Methods	Description
Equals	Inherited from System.Object
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OnChangeEventHandler Delegate

The OnChangeEventHandler delegate represents the signature of the method that handles the notification.

Declaration

```
// C#  
public delegate void OnChangeEventHandler(object sender,  
    OracleNotificationEventArgs args);
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Not supported in a .NET stored procedure

Parameters

- *sender*
The source of the event.
- *args*
The `OracleNotificationEventArgs` instance that contains the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OracleRowidInfo Enumeration

`OracleRowidInfo` enumeration values specify whether ROWID information is included as part of the `ChangeNotificationEventArgs` or not.

[Table 9-28](#) lists all the `OracleRowidInfo` enumeration values with a description of each enumerated value.

Table 9-27 OracleRowidInfo Members

Member Name	Description
Default	ROWID information is included only if <code>OracleCommand.AddRowid</code> property is set to true or if ROWID column is explicitly included in the query.
Include	ROWID information is included regardless of whether ROWID is included in the select-list of the query or not.

Table 9-27 (Cont.) OracleRowidInfo Members

Member Name	Description
Exclude	ROWID information is not included regardless of whether ROWID is included in the select-list of the query or not.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["RowidInfo"](#)

OracleNotificationType Enumeration

OracleNotificationType enumerated values specify the different types that cause the notification.

Table 9-28 lists all the OracleNotificationType enumeration values with a description of each enumerated value.

Table 9-28 OracleNotificationType Members

Member Name	Description
Change	A change occurs in the database.
Subscribe	A change occurs in the subscription.
Query	A query-based change occurs in the database.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher



See Also:

"Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"

OracleNotificationSource Enumeration

OracleNotificationSource enumerated values specify the different sources that cause notification.

Table 9-29 lists all the OracleNotificationSource enumeration values with a description of each enumerated value.

Table 9-29 OracleNotificationSource Members

Member Name	Description
Data	The data in a table has changed.
Database	A database event such as a database startup or shutdown occurs.
Object	A database object is altered or dropped.
Subscription	The subscription is changed.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

**See Also:**

"Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"

OracleNotificationInfo Enumeration

OracleNotificationInfo enumerated values specify the database event that causes the notification.

Table 9-30 lists all the OracleNotificationInfo enumeration values with a description of each enumerated value.

Table 9-30 OracleNotificationInfo Members

Member Name	Description
Insert	A row is inserted.
Delete	A row is deleted.
Update	A row is updated.
Startup	A database starts.
Shutdown	A database shuts down.
Shutdown_any	A database instance in a Real Application Cluster (Oracle RAC) environment shuts down.
Alter	An object is altered.
Drop	An object or database is dropped.
End	A registration is removed.
Error	A notification error occurs.

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

 **See Also:**

"Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"

10

Oracle Data Provider for .NET Globalization Classes

This chapter describes the ODP.NET globalization classes.

This chapter contains these topics:

- [OracleGlobalization Class](#)

OracleGlobalization Class

The `OracleGlobalization` class is used to obtain and set the Oracle globalization settings of the session, thread, and local computer (read-only).

Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleGlobalization`

Declaration

```
public sealed class OracleGlobalization : ICloneable, IDisposable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An exception is thrown for invalid property values. All newly set property values are validated, except the `TimeZone` property.

Changing the `OracleGlobalization` object properties does not change the globalization settings of the session or the thread. Either the `SetSessionInfo` method of the `OracleConnection` object or the `SetThreadInfo` method of the

OracleGlobalization object must be called to alter the session's and thread's globalization settings, respectively.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class OracleGlobalizationSample
{
    static void Main()
    {
        // Get thread's globalization info
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        // Set language on thread's globalization info
        glob.Language = "FRENCH";
        OracleGlobalization.SetThreadInfo(glob);
        OracleGlobalization.GetThreadInfo(glob);

        // Prints "glob.Language = FRENCH"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Members](#)
- [OracleGlobalization Static Methods](#)
- [OracleGlobalization Properties](#)
- [OracleGlobalization Public Methods](#)
- [Oracle Database SQL Language Reference](#)
- [Oracle Database Globalization Support Guide](#)

OracleGlobalization Members

OracleGlobalization members are listed in the following tables.

OracleGlobalization Static Methods

The OracleGlobalization static methods are listed in [Table 10-1](#).

Table 10-1 OracleGlobalization Static Methods

Name	Description
GetClientInfo	Returns an <code>OracleGlobalization</code> object that represents the Oracle globalization settings of the local computer (Overloaded) <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetThreadInfo	Returns or refreshes an <code>OracleGlobalization</code> instance that represents Oracle globalization settings of the current thread (Overloaded) <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
SetThreadInfo	Sets Oracle globalization parameters to the current thread <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>

OracleGlobalization Properties

The `OracleGlobalization` properties are listed in [Table 10-2](#).

Table 10-2 OracleGlobalization Properties

Name	Description
Calendar	Specifies the calendar system
ClientCharacterSet	Specifies a client character set <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
Comparison	Specifies a method of comparison for <code>WHERE</code> clauses and comparison in PL/SQL blocks
Currency	Specifies the string to use as a local currency symbol for the L number format element
DateFormat	Specifies the date format for Oracle <code>Date</code> type as a string
DateLanguage	Specifies the language used to spell day and month names and date abbreviations
DualCurrency	Specifies the dual currency symbol, such as <i>Euro</i> , for the U number format element
ISOCurrency	Specifies the string to use as an international currency symbol for the C number format element
Language	Specifies the default language of the database
LengthSemantics	Enables creation of <code>CHAR</code> and <code>VARCHAR2</code> columns using either byte or character (default) length semantics
NCharConversionException	Determines whether or not data loss during an implicit or explicit character type conversion reports an error
NumericCharacters	Specifies the characters used for the decimal character and the group separator character for numeric values in strings
Sort	Specifies the collating sequence for <code>ORDER BY</code> clause
Territory	Specifies the name of the territory
TimeStampFormat	Specifies the string format for <code>TimeStamp</code> types

Table 10-2 (Cont.) OracleGlobalization Properties

Name	Description
TimeStampTZFormat	Specifies the string format for TimeStampTZ types
TimeZone	Specifies the time zone region name

OracleGlobalization Public Methods

OracleGlobalization public methods are listed in [Table 10-3](#).

Table 10-3 OracleGlobalization Public Methods

Public Method	Description
Clone	Creates a copy of an OracleGlobalization object
Dispose	Releases any resources or memory allocated by the object

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

OracleGlobalization Static Methods

The OracleGlobalization static methods are listed in [Table 10-4](#).

Table 10-4 OracleGlobalization Static Methods

Name	Description
GetClientInfo	Returns an OracleGlobalization object that represents the Oracle globalization settings of the local computer (Overloaded) <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
GetThreadInfo	Returns or refreshes an OracleGlobalization instance that represents Oracle globalization settings of the current thread (Overloaded) <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
SetThreadInfo	Sets Oracle globalization parameters to the current thread <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetClientInfo

`GetClientInfo` returns an `OracleGlobalization` object instance that represents the Oracle globalization settings of the local computer.

Overload List:

- [GetClientInfo\(\)](#)
This method returns an `OracleGlobalization` instance that represents the globalization settings of the local computer.
- [GetClientInfo\(OracleGlobalization\)](#)
This method refreshes the provided `OracleGlobalization` object with the globalization settings of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetClientInfo()

This method returns an `OracleGlobalization` instance that represents the globalization settings of the local computer.

Declaration

```
// C#  
public static OracleGlobalization GetClientInfo();
```

Return Value

An `OracleGlobalization` instance.

Example

```
// C#  
using System;
```

```
using Oracle.DataAccess.Client;

class GetClientInfoSample
{
    static void Main()
    {
        // Get client's globalization info
        OracleGlobalization glob = OracleGlobalization.GetClientInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetClientInfo(OracleGlobalization)

This method refreshes the provided `OracleGlobalization` object with the globalization settings of the local computer.

Declaration

```
// C#
public static void GetClientInfo(OracleGlobalization oraGlob);
```

Parameters

- `oraGlob`

The `OracleGlobalization` object being updated.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetClientInfoSample
{
    static void Main()
    {
        // Get client's globalization info
        OracleGlobalization glob = OracleGlobalization.GetClientInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);
    }
}
```

```
// Get client's globalization info using overload
OracleGlobalization.GetClientInfo(glob);

// Prints "glob.Language = AMERICAN"
Console.WriteLine("glob.Language = " + glob.Language);

glob.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetThreadInfo

GetThreadInfo returns or refreshes an OracleGlobalization instance.

Overload List:

- [GetThreadInfo\(\)](#)
This method returns an OracleGlobalization object instance of the current thread.
- [GetThreadInfo\(OracleGlobalization\)](#)
This method refreshes the OracleGlobalization object instance with the globalization settings of the current thread.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetThreadInfo()

This method returns an OracleGlobalization instance of the current thread.

Declaration

```
// C#
public static OracleGlobalization GetThreadInfo();
```

Return Value

An OracleGlobalization instance.

Remarks

Initially, `GetThreadInfo()` returns an OracleGlobalization object that has the same property values as that returned by `GetClientInfo()`, unless the application changes it by invoking `SetThreadInfo()`.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetThreadInfoSample
{
    static void Main()
    {
        // Get thread's globalization info
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        // Get thread's globalization info using overloaded
        OracleGlobalization.GetThreadInfo(glob);

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetThreadInfo(OracleGlobalization)

This method refreshes the OracleGlobalization object with the globalization settings of the current thread.

Declaration

```
// C#
public static void GetThreadInfo(OracleGlobalization oraGlob);
```

Parameters

- *oraGlob*
The OracleGlobalization object being updated.

Remarks

Initially `GetThreadInfo()` returns an OracleGlobalization object that has the same property values as that returned by `GetClientInfo()`, unless the application changes it by invoking `SetThreadInfo()`.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class GetThreadInfoSample  
{  
    static void Main()  
    {  
        // Get thread's globalization info  
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();  
  
        // Prints "glob.Language = AMERICAN"  
        Console.WriteLine("glob.Language = " + glob.Language);  
  
        // Get thread's globalization info using overloaded  
        OracleGlobalization.GetThreadInfo(glob);  
  
        // Prints "glob.Language = AMERICAN"  
        Console.WriteLine("glob.Language = " + glob.Language);  
  
        glob.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

SetThreadInfo

This method sets Oracle globalization parameters to the current thread.

Declaration

```
// C#  
public static void SetThreadInfo(OracleGlobalization oraGlob);
```


Parameters

- `oraGlob`
An `OracleGlobalization` object.

Remarks

Any .NET string conversions to and from ODP.NET Types, as well as ODP.NET Type constructors, use the globalization property values where applicable. For example, when constructing an `OracleDate` structure from a .NET string, that string is expected to be in the format specified by the `OracleGlobalization.DateFormat` property of the thread.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class SetThreadInfoSample  
{  
    static void Main()  
    {  
        // Get thread's globalization info  
        OracleGlobalization glob1 = OracleGlobalization.GetThreadInfo();  
  
        // Prints "glob1.Language = AMERICAN"  
        Console.WriteLine("glob1.Language = " + glob1.Language);  
  
        // Set language on thread's globalization info  
        glob1.Language = "FRENCH";  
        OracleGlobalization.SetThreadInfo(glob1);  
        OracleGlobalization glob2 = OracleGlobalization.GetThreadInfo();  
  
        // Prints "glob2.Language = FRENCH"  
        Console.WriteLine("glob2.Language = " + glob2.Language);  
  
        glob1.Dispose();  
        glob2.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

OracleGlobalization Properties

The `OracleGlobalization` properties are listed in [Table 10-5](#).

Table 10-5 OracleGlobalization Properties

Name	Description
Calendar	Specifies the calendar system
ClientCharacterSet	Specifies a client character set <i>Not Available in ODP.NET, Managed Driver and ODP.NET Core</i>
Comparison	Specifies a method of comparison for WHERE clauses and comparison in PL/SQL blocks
Currency	Specifies the string to use as a local currency symbol for the L number format element
DateFormat	Specifies the date format for Oracle Date type as a string
DateLanguage	Specifies the language used to spell day and month names and date abbreviations
DualCurrency	Specifies the dual currency symbol, such as <i>Euro</i> , for the U number format element
ISOCurrency	Specifies the string to use as an international currency symbol for the C number format element
Language	Specifies the default language of the database
LengthSemantics	Enables creation of CHAR and VARCHAR2 columns using either byte or character (default) length semantics
NCharConversionException	Determines whether or not data loss during an implicit or explicit character type conversion reports an error
NumericCharacters	Specifies the characters used for the decimal character and the group separator character for numeric values in strings
Sort	Specifies the collating sequence for ORDER by clause
Territory	Specifies the name of the territory
TimeStampFormat	Specifies the string format for TimeStamp types
TimeStampTZFormat	Specifies the string format for TimeStampTZ types
TimeZone	Specifies the time zone region name

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Calendar

This property specifies the calendar system.

Declaration

```
// C#  
public string Calendar {get; set;}
```

Property Value

A string representing the Calendar.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_CALENDAR` setting of the local computer. This value is the same regardless of whether or not the `OracleGlobalization` object represents the settings of the client, thread, or session.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

ClientCharacterSet

This property specifies a client character set.

Declaration

```
// C#  
public string ClientCharacterSet {get;}
```

Property Value

A string that provides the name of the character set of the local computer.

Remarks

The default value is the character set of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Comparison

This property represents a method of comparison for `WHERE` clauses and comparison in PL/SQL blocks.

Declaration

```
// C#  
public string Comparison {get; set;}
```

Property Value

A string that provides the name of the method of comparison.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_COMP` setting of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Currency

This property specifies the string to use as a local currency symbol for the L number format element.

Declaration

```
// C#  
public string Currency {get; set;}
```

Property Value

The string to use as a local currency symbol for the L number format element.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_CURRENCY` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Language Reference* for further information on the L number format element

DateFormat

This property specifies the date format for Oracle `Date` type as a string.

Declaration

```
// C#  
public string DateFormat {get; set;}
```

Property Value

The date format for Oracle `Date` type as a string

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_DATE_FORMAT` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

DateLanguage

This property specifies the language used to spell names of days and months, and date abbreviations (for example: a.m., p.m., AD, BC).

Declaration

```
// C#  
public string DateLanguage {get; set;}
```

Property Value

A string specifying the language.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_DATE_LANGUAGE` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

DualCurrency

This property specifies the dual currency symbol, such as *Euro*, for the U number format element.

Declaration

```
// C#  
public string DualCurrency {get; set;}
```

Property Value

A string that provides the dual currency symbol.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_DUAL_CURRENCY` setting of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Language Reference* for further information on the U number format element

ISOCurrency

This property specifies the string to use as an international currency symbol for the C number format element.

Declaration

```
// C#  
public string ISOCurrency {get; set;}
```

Property Value

The string used as an international currency symbol.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is the `NLS_ISO_CURRENCY` setting of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Language Reference* for further information on the C number format element

Language

This property specifies the default language of the database.

Declaration

```
// C#  
public string Language {get; set;}
```

Property Value

The default language of the database.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_LANGUAGE` setting of the local computer.

`Language` is used for messages, day and month names, and sorting algorithms. It also determines `NLS_DATE_LANGUAGE` and `NLS_SORT` parameter values.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

LengthSemantics

This property indicates whether or not `CHAR` and `VARCHAR2` columns use byte or character (default) length semantics.

Declaration

```
// C#  
public string LengthSemantics {get; set;}
```

Property Value

A string that indicates either byte or character length semantics.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_LENGTH_SEMANTICS` setting of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

NCharConversionException

This property determines whether or not data loss during an implicit or explicit character type conversion reports an error.

Declaration

```
// C#  
public bool NCharConversionException {get; set;}
```

Property Value

A string that indicates whether or not a character type conversion causes an error message.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value of `NLS_NCHAR_CONV_EXCP` is `False`, unless it is overridden by a setting in the `INIT.ORA` file.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

NumericCharacters

This property specifies the characters used for the decimal character and the group separator character for numeric values in strings.

Declaration

```
// C#  
public string NumericCharacters {get; set;}
```

Property Value

A string that represents the characters used.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_NUMERIC_CHARACTERS` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Sort

This property specifies the collating sequence for `ORDER by` clause.

Declaration

```
// C#  
public string Sort {get; set;}
```

Property Value

A string that indicates the collating sequence.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_SORT` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Territory

This property specifies the name of the territory.

Declaration

```
// C#  
public string Territory {get; set;}
```

Property Value

A string that provides the name of the territory.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_TERRITORY` setting of the local computer.

Changing this property changes other globalization properties.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database Globalization Support Guide.*

TimeStampFormat

This property specifies the string format for `TimeStamp` types.

Declaration

```
// C#  
public string TimeStampFormat {get; set;}
```

Property Value

The string format for `TimeStamp` types.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_TIMESTAMP_FORMAT` setting of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

TimeStampTZFormat

This property specifies the string format for `TimeStampTZ` types.

Declaration

```
// C#  
public string TimeStampTZFormat {get; set;}
```

Property Value

The string format for `TimeStampTZ` types.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_TIMESTAMP_TZ_FORMAT` setting of the local computer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

TimeZone

This property specifies the time zone region name or hour offset.

Declaration

```
// C#  
public string TimeZone {get; set;}
```

Property Value

The string represents the time zone region name or the time zone offset.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the time zone region name of the local computer

`TimeZone` is only used when the thread constructs one of the `TimeStamp` structures. `TimeZone` has no effect on the session.

`TimeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

Note:

PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleGlobalization`.

This property returns an empty string if the `OracleGlobalization` object is obtained using `GetSessionInfo()` or `GetSessionInfo(OracleGlobalization)`. Initially, by default, the time zone of the session is identical to the time zone of the thread. Therefore, given that the session time zone is not changed by invoking `ALTER SESSION` calls, the session time zone can be fetched from the client's globalization settings.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

OracleGlobalization Public Methods

`OracleGlobalization` public methods are listed in [Table 10-6](#).

Table 10-6 OracleGlobalization Public Methods

Public Method	Description
Clone	Creates a copy of an <code>OracleGlobalization</code> object
Dispose	Releases any resources or memory allocated by the object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Clone

This method creates a copy of an `OracleGlobalization` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An `OracleGlobalization` object.

Implements

`ICloneable`

Remarks

The cloned object has the same property values as that of the object being cloned.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`

Remarks

The `Dispose` method also closes the `OracleGlobalization` object.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

11

Oracle Data Provider for .NET Failover Classes

This chapter describes the ODP.NET failover classes and enumerations.

This chapter contains these topics:

- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventHandler Delegate](#)
- [FailoverEvent Enumeration](#)
- [FailoverReturnCode Enumeration](#)
- [FailoverType Enumeration](#)

OracleFailoverEventArgs Class

The `OracleFailoverEventArgs` class provides event data for the `OracleConnection.Failover` event. When database failover occurs, the `OracleConnection.Failover` event is triggered along with the `OracleFailoverEventArgs` object that stores the event data.

Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleFailoverEventArgs`

Declaration

```
// C#  
public sealed class OracleFailoverEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example (Oracle.DataAccess.Client only)

```
// Transparent Application Failover (TAF) Setup
// Refer Oracle® Database Net Services Administrator's Guide

// C#

using System;
using System.Threading;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class FailoverSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Register the event handler OnFailover
        con.Failover += new OracleFailoverEventHandler(OnFailover);

        Console.WriteLine("Wait for a failover for 5 seconds");
        Thread.Sleep(5000);

        con.Close();
        con.Dispose();
    }

    // TAF callback function
    static FailoverReturnCode OnFailover(object sender,
        OracleFailoverEventArgs eventArgs)
    {
        switch (eventArgs.FailoverEvent)
        {
            case FailoverEvent.Begin:
            {
                Console.WriteLine("FailoverEvent.Begin - Failover is starting");
                Console.WriteLine("FailoverType = " + eventArgs.FailoverType);
                break;
            }
            case FailoverEvent.End:
            {
                Console.WriteLine("FailoverEvent.End - Failover was successful");
                break;
            }
            case FailoverEvent.Reauth:
            {
                Console.WriteLine("FailoverEvent.Reauth - User reauthenticated");
                break;
            }
            case FailoverEvent.Error:
            {
                Console.WriteLine("FailoverEvent.Error - Failover was unsuccessful");

                // Sleep for 3 sec and Retry
                Thread.Sleep(3000);
                return FailoverReturnCode.Retry;
            }
        }
    }
}
```

```

        case FailoverEvent.Abort:
        {
            Console.WriteLine("FailoverEvent.Abort - Failover was unsuccessful");
            break;
        }
        default:
        {
            Console.WriteLine("Invalid FailoverEvent : " + eventArgs.FailoverEvent);
            break;
        }
    }
    return FailoverReturnCode.Success;
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Members](#)
- [OracleFailoverEventArgs Static Methods](#)
- [OracleFailoverEventArgs Properties](#)
- [OracleFailoverEventArgs Public Methods](#)
- ["OracleConnection Class"](#)
- *Oracle Database Net Services Administrator's Guide*

OracleFailoverEventArgs Members

OracleFailoverEventArgs members are listed in the following tables.

OracleFailoverEventArgs Static Methods

The OracleFailoverEventArgs static methods are listed in [Table 11-1](#).

Table 11-1 OracleFailoverEventArgs Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleFailoverEventArgs Properties

The OracleFailoverEventArgs properties are listed in [Table 11-2](#).

Table 11-2 OracleFailoverEventArgs Properties

Name	Description
FailoverType	Specifies the type of failover the client has requested

Table 11-2 (Cont.) OracleFailoverEventArgs Properties

Name	Description
FailoverEvent	Indicates the state of the failover

OracleFailoverEventArgs Public Methods

The OracleFailoverEventArgs public methods are listed in [Table 11-3](#).

Table 11-3 OracleFailoverEventArgs Public Methods

Name	Description
Equals	Inherited from System.Object (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Class](#)
- ["FailoverType Enumeration"](#)

OracleFailoverEventArgs Static Methods

The OracleFailoverEventArgs static methods are listed in [Table 11-1](#).

Table 11-4 OracleFailoverEventArgs Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

OracleFailoverEventArgs Properties

The OracleFailoverEventArgs properties are listed in [Table 11-5](#).

Table 11-5 OracleFailoverEventArgs Properties

Name	Description
FailoverType	Specifies the type of failover the client has requested
FailoverEvent	Indicates the state of the failover

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

FailoverType

This property indicates the state of the failover.

Declaration

```
// C#  
public FailoverType FailoverType {get;}
```

Property Value

A FailoverType enumeration value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["FailoverType Enumeration"](#)

FailoverEvent

This property indicates the state of the failover.

Declaration

```
// C#
public FailoverEvent FailoverEvent {get;}
```

Property Value

A `FailoverEvent` enumerated value.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["FailoverEvent Enumeration"](#)

OracleFailoverEventArgs Public Methods

The `OracleFailoverEventArgs` public methods are listed in [Table 11-6](#).

Table 11-6 OracleFailoverEventArgs Public Methods

Name	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)
<code>GetHashCode</code>	Inherited from <code>System.Object</code>
<code>GetType</code>	Inherited from <code>System.Object</code>
<code>ToString</code>	Inherited from <code>System.Object</code>

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

OracleFailoverEventHandler Delegate

The `OracleFailoverEventHandler` represents the signature of the method that handles the `OracleConnection.Failover` event.

Declaration

```
// C#  
public delegate FailoverReturnCode OracleFailoverEventHandler(object sender,  
    OracleFailoverEventArgs eventArgs);
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Not supported in a .NET stored procedure

Parameter

- *sender*
The source of the event.
- *eventArgs*
The OracleFailoverEventArgs object that contains the event data.

Return Type

An int.

Remarks

To receive failover notifications, a callback function can be registered as follows:

```
ConObj.Failover += new OracleFailoverEventHandler(OnFailover);
```

The definition of the callback function OnFailover can be as follows:

```
public FailoverReturnCode OnFailover(object sender, OracleFailoverEventArgs  
eventArgs)
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["Failover"](#)

FailoverEvent Enumeration

FailoverEvent enumerated values are used to specify the state of the failover.

Table 11-7 lists all the FailoverEvent enumeration values with a description of each enumerated value.

Table 11-7 FailoverEvent Enumeration Values

Member Names	Description
FailoverEvent.Begin	Indicates that failover has detected a lost connection and that failover is starting.
FailoverEvent.End	Indicates successful completion of failover.
FailoverEvent.Abort	Indicates that failover was unsuccessful, and there is no option of retrying.
FailoverEvent.Error	Indicates that failover was unsuccessful, and it gives the application the opportunity to handle the error and retry failover. The application can retry failover by returning <code>FailoverReturnCode.Retry</code> for the event notification.
FailoverEvent.Reauth	Indicates that a user handle has been reauthenticated. This applies to the situation where a client has multiple user sessions on a single server connection. During the initial failover, only the active user session is failed over. Other sessions are failed over when the application tries to use them. This is the value passed to the callback during these subsequent failovers.

No significant database operation should occur immediately after a `FailoverEvent.Begin` event. SQL and major database operations should wait until the `FailoverEvent.End` event. `FailoverEvent.Begin` is primarily used to reject failover or to trace it. `FailoverEvent.Begin` can also be used for non-database application operations, such as informing the end user a failover is in progress and to wait until it completes before proceeding. Transactions can be used in the `FailoverEvent.End` callback phase, such as to file fault tickets or audit. These transactions must be committed before the callback completes.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

 **See Also:**

- [FailoverEvent Enumeration](#)
- ["OracleFailoverEventArgs Class"](#)
- ["FailoverEvent"](#)
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database Net Services Reference*

FailoverReturnCode Enumeration

`FailoverReturnCode` enumerated values are passed back by the application to the ODP.NET provider to request a retry in case of a failover error, or to continue in case of a successful failover.

[Table 11-8](#) lists the `FailoverReturnCode` enumeration values with a description of each enumerated value.

Table 11-8 FailoverReturnCode Enumeration Values

Member Names	Description
<code>FailoverReturnCode.Retry</code>	Requests ODP.NET to retry failover in case <code>FailoverEvent.Error</code> is passed to the application
<code>FailoverReturnCode.Success</code>	Requests ODP.NET to proceed so that the application receive more notifications, if any

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

 **See Also:**

- [FailoverEvent Enumeration](#)
- ["OracleFailoverEventArgs Class"](#)
- ["FailoverEvent"](#)
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database Net Services Reference*

FailoverType Enumeration

FailoverType enumerated values are used to indicate the type of failover event that was raised.

Table 11-9 lists all the FailoverType enumeration values with a description of each enumerated value.

Table 11-9 FailoverType Enumeration Values

Member Names	Description
FailoverType.Session	Indicates that the user has requested only session failover.
FailoverType.Select	Indicates that the user has requested select and session failover.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

See Also:

- [FailoverEvent Enumeration](#)
- ["OracleFailoverEventArgs Class"](#)
- ["FailoverType"](#)
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database Net Services Reference*

12

Oracle Database Advanced Queuing Classes

This chapter describes the following Oracle Data Provider for .NET classes:

- [OracleAQAgent Class](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQMessage Class](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventHandler Delegate](#)
- [OracleAQQueue Class](#)
- [OracleAQDequeueMode Enumeration](#)
- [OracleAQMessageDeliveryMode Enumeration](#)
- [OracleAQMessageState Enumeration](#)
- [OracleAQMessageType Enumeration](#)
- [OracleAQNavigationMode Enumeration](#)
- [OracleAQNotificationGroupingType Enumeration](#)
- [OracleAQNotificationType Enumeration](#)
- [OracleAQVisibilityMode Enumeration](#)

OracleAQAgent Class

The `OracleAQAgent` class represents agents that may be senders or recipients of a message.

Class Inheritance

`System.Object`

`OracleAQAgent`

Declaration

```
// C#  
public sealed class OracleAQAgent
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>

Provider	ODP.NET, Unmanaged Driver
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An agent may be a consumer, another queue, or a consumer of another queue. The queue may be either local or remote. A remote queue is specified through a database link.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Members](#)
- [OracleAQAgent Constructors](#)
- [OracleAQAgent Properties](#)

OracleAQAgent Members

OracleAQAgent members are listed in the following tables.

OracleAQAgent Constructors

OracleAQAgent constructors are listed in [Table 12-1](#).

Table 12-1 OracleAQAgent Constructors

Constructor	Description
OracleAQAgent Constructors	Instantiates a new instance of the OracleAQAgent class (Overloaded).

OracleAQAgent Properties

OracleAQAgent properties are listed in [Table 12-2](#).

Table 12-2 OracleAQAgent Properties

Property	Description
Address	Specifies the address of the agent.
Name	Specifies the name of the agent.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Class](#)

OracleAQAgent Constructors

OracleAQAgent constructors instantiate new instances of the OracleAQAgent class.

Overload List:

- [OracleAQAgent \(string\)](#)
This constructor instantiates the OracleAQAgent class using the specified name.
- [OracleAQAgent \(string, string\)](#)
This constructor instantiates the OracleAQAgent class using the specified name and address.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQAgent (string)

This constructor instantiates the OracleAQAgent class using the specified name.

Declaration

```
// C#  
public OracleAQAgent(string name);
```

Parameters

- *name*
The name of the agent.

Exceptions

ArgumentNullException - The *name* parameter is null.

ArgumentException - The *name* parameter is empty.

Remarks

The agent name signifies the name of a producer or consumer of a message. In the context of functionality exposed by `Listen`, an agent name corresponds to the name of a consumer for which a message is expected on a multiconsumer queue. It may also be set on a message to signify sender identification or intended recipients of the message.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQAgent (string, string)

This constructor instantiates the `OracleAQAgent` class using the specified name and address.

Declaration

```
// C#  
public OracleAQAgent(string name, string address);
```

Parameters

- *name*
The name of the agent.
- *address*
The address is of the form `[schema.]queue[@dblink]`.

Exceptions

`ArgumentNullException` - The *address* parameter is null.

`ArgumentException` - The *address* parameter is empty.

Remarks

The agent name signifies the name of a producer or consumer of a message. In the context of functionality exposed by `Listen`, an agent name corresponds to the name of a consumer for which a message is expected on a multiconsumer queue.

The *name* parameter can be specified as `null` in this constructor. In such a scenario, the agent only has an *address*.

The *address* parameter signifies the name of the queue against which this agent listens for new messages. The *address* represents a queue at a local or remote database. The validity of the *address* is not checked implicitly. The exceptions due to wrong *address* are thrown only during database operations such as `Listen`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQAgent Properties

OracleAQAgent properties are listed in [Table 12-3](#).

Table 12-3 OracleAQAgent Properties

Property	Description
Address	Specifies the address of the agent.
Name	Specifies the name of the agent.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

Address

This instance property specifies the address of the agent.

Declaration

```
// C#  
public string Address {get; }
```

Property Value

A *string* that specifies the agent address.

Remarks

The address represents a queue at a local or remote database. The default value is *null*. The address of the agent is of the form [*schema.*]*queue*[*@dblink*]. The string length can be up to 128 characters.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

Name

This instance property specifies the name of the agent.

Declaration

```
// C#  
public string Name {get; }
```

Property Value

A string.

Remarks

The default is `null`. The string length can be up to 30 characters. A non-`null` value implies that this agent name either corresponds to a consumer name in a multiconsumer queue, or a recipient as specified in message properties.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQDequeueOptions Class

An `OracleAQDequeueOptions` object represents the options available when dequeuing a message from an `OracleAQQueue` object.

Class Inheritance

`System.Object`

`OracleAQDequeueOptions`

Declaration

```
// C#  
public sealed class OracleAQDequeueOptions : ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Members](#)
- [OracleAQDequeueOptions Constructor](#)
- [OracleAQDequeueOptions Properties](#)
- [OracleAQDequeueOptions Public Methods](#)

OracleAQDequeueOptions Members

OracleAQDequeueOptions members are listed in the following tables.

OracleAQDequeueOptions Constructor

The OracleAQDequeueOptions constructor is listed in [Table 12-4](#).

Table 12-4 OracleAQDequeueOptions Constructor

Constructor	Description
OracleAQDequeueOptions Constructor	Instantiates a new instance of the OracleAQDequeueOptions class

OracleAQDequeueOptions Properties

OracleAQDequeueOptions properties are listed in [Table 12-5](#).

Table 12-5 OracleAQDequeueOptions Properties

Property	Description
ConsumerName	Specifies the consumer name for which to dequeue the message

Table 12-5 (Cont.) OracleAQDequeueOptions Properties

Property	Description
Correlation	Specifies the correlation identifier of the message to be dequeued
DeliveryMode	Specifies the expected delivery mode of the message being dequeued
DequeueMode	Specifies the locking behavior associated with the dequeue operation
MessageId	Specifies the message identifier of the message to be dequeued
NavigationMode	Specifies the position of the message that will be retrieved
ProviderSpecificType	Specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type
Visibility	Specifies whether or not the new message is dequeued as part of the current transaction
Wait	Specifies the wait time, in seconds, for a message that matches the search criteria

OracleAQDequeueOptions Public Methods

OracleAQDequeueOptions public methods are listed in [Table 12-6](#).

Table 12-6 OracleAQDequeueOptions Public Methods

Public Method	Description
Clone	Creates a copy of an OracleAQDequeueOptions object.

**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)

OracleAQDequeueOptions Constructor

The OracleAQDequeueOptions constructor creates an instance of the OracleAQDequeueOptions class and sets all its properties to their default values.

Declaration

```
// C#
public OracleAQDequeueOptions();
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

OracleAQDequeueOptions Properties

OracleAQDequeueOptions properties are listed in [Table 12-7](#).

Table 12-7 OracleAQDequeueOptions Properties

Property	Description
ConsumerName	Specifies the consumer name for which to dequeue the message
Correlation	Specifies the correlation identifier of the message to be dequeued
DeliveryMode	Specifies the expected delivery mode of the message being dequeued
DequeueMode	Specifies the locking behavior associated with the dequeue operation
MessageId	Specifies the message identifier of the message to be dequeued
NavigationMode	Specifies the position of the message that will be retrieved
ProviderSpecificType	Specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type
Visibility	Specifies whether or not the new message is dequeued as part of the current transaction
Wait	Specifies the wait time, in seconds, for a message that matches the search criteria

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

ConsumerName

This instance property specifies the consumer name for which to dequeue the message.

Declaration

```
// C#  
public string ConsumerName {get;set;}
```

Property Value

A string.

Remarks

The `ConsumerName` property only accesses those messages that match the consumer name. If a queue is not set up for multiple consumers, then this field should be set to null.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

Correlation

This instance property specifies the correlation identifier of the message to be dequeued.

Declaration

```
// C#  
public string Correlation {get;set;}
```

Property Value

A string.

Remarks

This property specifies the identification of the message to be dequeued. Special pattern matching characters, such as the percent sign (%) and the underscore (_) can be used. If more than one message satisfies the pattern, then the order of dequeuing is undetermined.

The maximum length of `Correlation` is 128.

`MessageId` and `Correlation` are two independent identifiers. While `MessageId` is unique for a message, a group of messages can be assigned the same `Correlation`. Also, pattern matching is possible only with `Correlation`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

DeliveryMode

This instance property specifies the expected delivery mode of the message being dequeued.

Declaration

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;set;}
```

Property Value

An `OracleAQMessageDeliveryMode` enumerated value.

Remarks

This property specifies the type of messages to be dequeued. It can be set to dequeue either persistent or buffered messages, or both from a queue. The following values are valid:

- `OracleAQMessageDeliveryMode.Persistent`
- `OracleAQMessageDeliveryMode.Buffered`
- `OracleAQMessageDeliveryMode.PersistentOrBuffered`

The default value is `OracleAQMessageDeliveryMode.Persistent`.

Buffered messaging is supported in all queue tables created with a database compatibility level of 8.1 or higher.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

DequeueMode

This instance property specifies the locking behavior associated with the dequeue operation.

Declaration

```
// C#  
public OracleAQDequeueMode DequeueMode {get;set;}
```

Property Value

An OracleAQDequeueMode enumerated value.

Exceptions

ArgumentOutOfRangeException - The specified DequeueMode value is invalid.

Remarks

The default value is OracleAQDequeueMode.Remove.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

MessageId

This instance property specifies the message identifier of the message to be dequeued.

Declaration

```
// C#  
public byte[] MessageId {get;set;}
```

Property Value

A byte[].

Remarks

The dequeue operation succeeds only if the message ID of the message being dequeued matches with the message ID specified.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

NavigationMode

This instance property specifies the position of the message that will be retrieved.

Declaration

```
// C#  
public OracleAQNavigationMode NavigationMode {get;set;}
```

Property Value

An OracleAQNavigationMode enumerated value.

Exceptions

ArgumentOutOfRangeException - The specified NavigationMode value is invalid.

Remarks

The default value is OracleAQNavigationMode.NextMessage.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

ProviderSpecificType

This property specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type.

Declaration

```
// C#  
public bool ProviderSpecificType {get;set;}
```

Property Value

A bool.

Remarks

The default value of this property is `false`. For a discussion of how this property affects payload type, refer to ["MessageType"](#) under the `OracleAQQueue` class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)
- ["MessageType"](#)

Visibility

This instance property specifies whether or not the new message is dequeued as part of the current transaction.

Declaration

```
// C#  
public OracleAQVisibilityMode Visibility {get;set;}
```

Property Value

An `OracleAQVisibilityMode` enumerated value.

Exceptions

`ArgumentOutOfRangeException` - The `Visibility` value specified is invalid.

Remarks

The default value is `OracleAQVisibilityMode.OnCommit`. You must use transactions when using the default value for this property. This ensures that applications do not lose messages and the messages are appropriately removed from the queue after the dequeue operation is successful. If transactions are not used when using the default visibility mode of `OracleAQVisibilityMode.OnCommit`, then messages are not removed from the queue.

Using the alternative visibility mode value, `OracleAQVisibilityMode.Immediate` can eliminate the need to create, commit, and rollback a transaction. However, if an error occurs during the dequeue operation, then the message may be lost.

The visibility parameter is ignored when `DequeueMode` is set to `OracleAQDequeueMode.Browse`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

Wait

This instance property specifies the wait time, in seconds, for a message that matches the search criteria.

Declaration

```
// C#  
public int Wait {get;set;}
```

Property Value

Any positive integer value or 0 or -1.

Exceptions

`ArgumentOutOfRangeException` - The specified `Wait` value is invalid.

Remarks

The default value is -1, which implies an infinite wait. The following values are valid:

- Positive integer: Wait time in seconds.
- -1: Wait forever.
- 0: Do not wait.

A value of less than -1 raises an `ArgumentOutOfRangeException`.

This parameter is ignored if messages in the same group are being dequeued.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

OracleAQDequeueOptions Public Methods

The `OracleAQDequeueOptions` public method is listed in [Table 12-8](#).

Table 12-8 OracleAQDequeueOptions Public Methods

Public Method	Description
Clone	Creates a copy of an OracleAQDequeueOptions object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

Clone

This method creates a copy of an OracleAQDequeueOptions object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleAQDequeueOptions object.

Implements

ICloneable.

Remarks

The cloned object has the same property values as the object being cloned.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

OracleAQEnqueueOptions Class

The OracleAQEnqueueOptions class represents the options available when enqueueing a message to an OracleAQQueue.

Class Inheritance

System.Object

OracleAQEnqueueOptions

Declaration

```
// C#
public sealed class OracleAQEnqueueOptions : ICloneable
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Members](#)
- [OracleAQEnqueueOptions Constructor](#)
- [OracleAQEnqueueOptions Properties](#)
- [OracleAQEnqueueOptions Public Methods](#)

OracleAQEnqueueOptions Members

The OracleAQEnqueueOptions members are listed in the following tables.

OracleAQEnqueueOptions Constructor

OracleAQEnqueueOptions constructor is listed in [Table 12-9](#).

Table 12-9 OracleAQEnqueueOptions Constructor

Constructor	Description
OracleAQEnqueueOptions Constructor	Instantiates a new instance of the OracleAQEnqueueOptions class.

OracleAQEnqueueOptions Properties

OracleAQEnqueueOptions properties are listed in [Table 12-10](#).

Table 12-10 OracleAQEnqueueOptions Properties

Property	Description
DeliveryMode	Specifies the delivery mode of the message being enqueued.
Visibility	Specifies whether or not the new message is enqueued as part of the current transaction.

OracleAQEnqueueOptions Public Methods

The OracleAQEnqueueOptions public method is listed in [Table 12-11](#).

Table 12-11 OracleAQEnqueueOptions Public Methods

Public Method	Description
Clone	Creates a copy of an OracleAQEnqueueOptions object.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Class](#)

OracleAQEnqueueOptions Constructor

This constructor creates an instance of the OracleAQEnqueueOptions class with default property values.

Declaration

```
// C#  
public OracleAQEnqueueOptions();
```



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

OracleAQEnqueueOptions Properties

OracleAQEnqueueOptions properties are listed in [Table 12-12](#).

Table 12-12 OracleAQEnqueueOptions Properties

Property	Description
DeliveryMode	Specifies the delivery mode of the message being enqueued.
Visibility	Specifies whether or not the new message is enqueued as part of the current transaction.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

DeliveryMode

This instance property specifies the delivery mode of the message being enqueued.

Declaration

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;set;}
```

Exceptions

`ArgumentOutOfRangeException` - The specified `Visibility` value is invalid.

Remarks

The valid values can be any of the following enumerated values:

- `OracleAQMessageDeliveryMode.Persistent`
- `OracleAQMessageDeliveryMode.Buffered`

The default is `OracleAQMessageDeliveryMode.Persistent`.

`OracleAQMessageDeliveryMode.PersistentOrBuffered` cannot be set on this property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

Visibility

This instance property specifies whether or not the new message is enqueued as part of the current transaction.

Declaration

```
// C#  
public OracleAQVisibilityMode Visibility {get;set;}
```

Property Value

An `OracleAQVisibilityMode` enumerated value.

Exceptions

`ArgumentOutOfRangeException` - The specified `Visibility` value is invalid.

Remarks

The default value is `OracleAQVisibilityMode.OnCommit`. You must use transactions when using the default value. If transactions are not used when using the default visibility mode of `OracleAQVisibilityMode.OnCommit`, then messages are not enqueued to the queue.

Using the alternative visibility mode value, `OracleAQVisibilityMode.Immediate` eliminates the need to use a transaction. The queue is not affected in case the enqueue operation fails. The message does not get enqueued to the queue for such cases.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

OracleAQEnqueueOptions Public Methods

`OracleAQEnqueueOptions` public method is listed in [Table 12-13](#).

Table 12-13 OracleAQEnqueueOptions Public Methods

Public Method	Description
Clone	Creates a copy of an OracleAQEnqueueOptions object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

Clone

This method creates a copy of an OracleAQEnqueueOptions object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleAQEnqueueOptions object.

Implements

ICloneable.

Remarks

The cloned object has the same property values as that of the object being cloned.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

OracleAQMessage Class

An OracleAQMessage object represents a message to be enqueued and dequeued.

Class Inheritance

System.Object

OracleAQMessage

Declaration

```
// C#  
public sealed class OracleAQMessage
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An `OracleAQMessage` object consists of control information (metadata) and Payload (data). The control information is exposed by various properties on the `OracleAQMessage` object and is used by Oracle Database Advanced Queuing to manage messages. The payload is the information stored in the queue.

Note:

An instance of `OracleAQMessage` cannot be re-used across multiple operations of `OracleAQQueue` public method `Enqueue()` or `EnqueueArray()`, if the payload is an `XmlReader`. This is a direct consequence of the forward-only semantics of the `XmlReader`, as an `Enqueue()` or `EnqueueArray()` operation internally invokes a read operation on the `XmlReader` to extract the data to be enqueued.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Members](#)
- [OracleAQMessage Constructors](#)
- [OracleAQMessage Properties](#)

OracleAQMessage Members

OracleAQMessage members are listed in the following tables.

OracleAQMessage Constructor

OracleAQMessage constructors are listed in [Table 12-14](#).

Table 12-14 OracleAQMessage Constructors

Constructor	Description
OracleAQMessage Constructors	Instantiates a new instance of the OracleAQMessage class (Overloaded).

OracleAQMessage Properties

OracleAQMessage properties are listed in [Table 12-15](#).

Table 12-15 OracleAQMessage Properties

Property	Description
Correlation	Specifies an identification for the message.
Delay	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
DeliveryMode	Specifies the delivery mode of the dequeued message.
DequeueAttempts	Returns the number of attempts that have been made to dequeue the message.
EnqueueTime	Specifies the time when the message was enqueued.
ExceptionQueue	Specifies the name of the queue that the message should be moved to if it cannot be processed successfully.
Expiration	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing.
MessageId	Returns the message identifier.
OriginalMessageId	Specifies the identifier of the message in the last queue that generated this message.
Payload	Specifies the payload of the message.
Priority	Specifies the priority of the message.
Recipients	Specifies the list of recipients that overrides the default queue subscribers.
SenderId	Identifies the original sender of the message.
State	Specifies the state of the message at the time of dequeue.
TransactionGroup	Specifies the transaction group for the dequeued message.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)

OracleAQMessage Constructors

OracleAQMessage constructors create new instances of the OracleAQMessage class.

Overload List:

- [OracleAQMessage\(\)](#)
This constructor instantiates the OracleAQMessage class.
- [OracleAQMessage\(Object\)](#)
This constructor instantiates the OracleAQMessage class using the object provided as the payload.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessage()

This constructor instantiates the OracleAQMessage class.

Declaration

```
// C#  
public OracleAQMessage();
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessage(Object)

This constructor instantiates the `OracleAQMessage` class using the `Object` provided as the `payload`.

Declaration

```
// C#  
public OracleAQMessage(Object payload);
```

Parameters

- `payload`
An `Object` specifying `payload`. It can be one of the following types:
 - `byte[]`
 - `IOracleCustomType`
 - `OracleBinary`
 - `OracleXmlType`
 - `String`
 - `XmlReader`

Exceptions

`ArgumentException` - The specified `payload` value is of invalid type.

Remarks

The ODP.NET AQ implementation currently does not support user defined types with LOB attributes. It also does not support other variants of user defined types such as VARRAY and nested tables, as Oracle Database AQ does not support them inherently.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessage Properties

`OracleAQMessage` properties are listed in [Table 12-16](#).

Table 12-16 OracleAQMessage Properties

Property	Description
Correlation	Specifies an identification for the message.

Table 12-16 (Cont.) OracleAQMessage Properties

Property	Description
Delay	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
DeliveryMode	Specifies the delivery mode of the dequeued message.
DequeueAttempts	Returns the number of attempts that have been made to dequeue the message.
EnqueueTime	Specifies the time when the message was enqueued.
ExceptionQueue	Specifies the name of the queue that the message should be moved to if it cannot be processed successfully.
Expiration	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing.
MessageId	Returns the message identifier.
OriginalMessageId	Specifies the identifier of the message in the last queue that generated this message.
Payload	Specifies the payload of the message.
Priority	Specifies the priority of the message.
Recipients	Specifies the list of recipients that overrides the default queue subscribers.
SenderId	Identifies the original sender of the message.
State	Specifies the state of the message at the time of dequeue.
TransactionGroup	Specifies the transaction group for the dequeued message.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Correlation

This instance property specifies an identification for the message.

Declaration

```
// C#
public string Correlation {get;set;}
```

Property Value

A `string` that specifies the identification for the message.

Remarks

The producer of a message can set this property at the time of enqueueing. The consumer can then use this identification to dequeue specific messages by setting the `Correlation` property of an `OracleAQDequeueOptions` object. For more information regarding dequeuing messages based on `Correlation`, refer to "[Correlation](#)" under the `OracleAQDequeueOptions` class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)
- ["Correlation"](#)

Delay

This instance property specifies the duration, in seconds, after which an enqueued message is available for dequeuing.

Declaration

```
// C#  
public int Delay {get;set;}
```

Property Value

An `integer` that indicates the number of seconds after which an enqueued message is available for dequeuing.

Exceptions

`ArgumentException` - The value specified is less than 0.

Remarks

This property delays the immediate consumption of an enqueued message. The following are valid values for this property:

- Positive integer - Indicates the delay in seconds.
- 0 - indicates that the message is immediately available for dequeuing.

The default value is 0. The `Delay` property is not supported with buffered messaging.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

DeliveryMode

This instance property specifies the delivery mode of the dequeued message.

Declaration

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;}
```

Property Value

An `OracleAQMessageDeliveryMode` enumerated value (`OracleAQMessageDeliveryMode.Persistent` OR `OracleAQMessageDeliveryMode.Buffered`).

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

DequeueAttempts

This instance property returns the number of attempts that have been made to dequeue the message.

Declaration

```
// C#  
public int DequeueAttempts {get;}
```

Property Value

An integer that indicates the number of dequeue attempts.

Remarks

This property is available in an `OracleAQMessage` after the message has been dequeued from a queue.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

EnqueueTime

This instance property specifies the time when the message was enqueued.

Declaration

```
// C#  
public DateTime EnqueueTime {get;}
```

Property Value

A `DateTime` object.

Remarks

This property is available after the message is dequeued. It provides the enqueue time of a dequeued message.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

ExceptionQueue

This instance property specifies the name of the queue that the message should be moved to if it cannot be processed successfully.

Declaration

```
// C#  
public string ExceptionQueue {get;set;}
```

Property Value

The name of the queue that a message should be moved to if it cannot be processed successfully. The default value is `null`.

Remarks

This property specifies the queue that a message should be moved to if the message has expired or if the number of unsuccessful dequeue attempts have exceeded the `max_retries` value for the queue.

If this property is not set or the specified exception queue name does not exist, then the default exception queue associated with the queue table is used.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Expiration

This instance property specifies the duration, in seconds, for which an enqueued message is available for dequeuing.

Declaration

```
// C#  
public int Expiration {get;set;}
```

Property Value

An `integer` that specifies the number of seconds an enqueued message is available for dequeuing.

Exceptions

`ArgumentException` - The value specified is less than -1.

Remarks

The value specified is an offset from the value specified in the `Delay` property.

The following are valid values for the property:

- Positive integer - Indicates the expiration in seconds.
- -1 - Indicates that the message never expires.

The default value is -1. When a message expires, the message moves from the `READY` state to the `EXPIRED` state.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

MessageId

This instance property returns the message identifier.

Declaration

```
// C#  
public byte[] MessageId {get;}
```

Property Value

A `byte[]` that specifies the message identifier.

Remarks

This property is available after an enqueue or dequeue operation. Dequeued buffered messages have a `null` value for `MessageId`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OriginalMessageId

This instance property specifies the identifier of the message in the last queue that generated this message.

Declaration

```
// C#  
public byte[] OriginalMessageId {get;}
```

Property Value

A `byte[]` that specifies the original message identifier.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Payload

This instance property specifies the payload of the message.

Declaration

```
// C#  
public Object Payload {get;set;}
```

Property Value

An `Object` that specifies the payload of the message.

Exceptions

`ArgumentException` - The specified object is not one of the allowed types.

Remarks

For a complete discussion of various payload types, refer to "[MessageType](#)" under the `OracleAQQueue` class.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)
- ["MessageType"](#)

Priority

This instance property specifies the priority of the message.

Declaration

```
// C#  
public int Priority {get;set;}
```

Property Value

An integer that specifies the priority of the message.

Remarks

The default value is 0. In order to take effect, this property must be set prior to enqueueing the message.

Smaller values indicate higher priority for the message. Negative values may also be used.

The priority of an enqueued message is useful for priority-based dequeuing.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Recipients

This instance property specifies the list of recipients that overrides the default queue subscribers.

Declaration

```
// C#  
public OracleAQAgent[] Recipients {get; set}
```

Property Value

An OracleAQAgent[].

Remarks

This recipient list is valid only for messages being enqueued to multiconsumer queues. The list of recipients is not returned with the message at the time of dequeuing.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

SenderId

This instance property identifies the original sender of the message.

Declaration

```
// C#  
public OracleAQAgent SenderId {get; set;}
```

Property Value

An `OracleAQAgent` object.

Remarks

Sender identification is supported in all queue tables created with a database compatibility level of 8.1 or higher.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

State

This instance property specifies the state of the message at the time of dequeue.

Declaration

```
// C#  
public OracleAQMessageState State {get;}
```

Property Value

An `OracleAQMessageState` enumerated value.

Remarks

This property is available after the message is dequeued.

The state of buffered messages dequeued by specifying `Correlation` under `dequeue` options is always `OracleAQMessageState.Ready`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

TransactionGroup

This instance property specifies the transaction group for the dequeued message.

Declaration

```
// C#  
public string TransactionGroup {get;}
```

Property Value

A string that specifies the transaction group.

Remarks

This property is set only after the call to `DequeueArray`. This property is supported only when using Oracle Database 10g database or higher.

Messages belonging to one queue can be grouped to form a set that can only be consumed by one user at a time. This requires that the queue be created in a queue table that is enabled for message grouping. All messages belonging to a group must be created in the same transaction. Also, all messages created in one transaction belong to the same group.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessageAvailableEventArgs Class

The `OracleAQMessageAvailableEventArgs` class provides event data for the `OracleAQQueue.MessageAvailable` event.

Class Inheritance

`System.Object`

`System.EventArgs`

```
Oracle.DataAccess.Client.OracleAQMessageAvailableEventArgs
```

Declaration

```
// C#
public sealed class OracleAQMessageAvailableEventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

This class cannot be inherited.

For detailed information on all the inherited properties and methods, please read the documentation provided by Microsoft's .NET Documentation.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Members](#)
- [OracleAQMessageAvailableEventArgs Constructor](#)
- [OracleAQMessageAvailableEventArgs Properties](#)

OracleAQMessageAvailableEventArgs Members

OracleAQMessageAvailableEventArgs members are listed in the following tables.

OracleAQMessageAvailableEventArgs Constructor

OracleAQMessageAvailableEventArgs properties are listed in [Table 12-17](#)

Table 12-17 OracleAQMessageAvailableEventArgs Constructor

Property	Description
OracleAQMessageAvailableEventArgs Constructor	Instantiates a new instance of the OracleAQMessageAvailableEventArgs class.

OracleAQMessageAvailableEventArgs Properties

OracleAQMessageAvailableEventArgs properties are listed in [Table 12-18](#).

Table 12-18 OracleAQMessageAvailableEventArgs Properties

Property	Description
AvailableMessages	Specifies the number of messages that raised this notification.
ConsumerName	Provides the name of the consumer for which the message is available for dequeuing.
Correlation	Provides the name of the consumer for which the message is available for dequeuing.
Delay	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
DeliveryMode	Specifies the delivery mode of the message.
EnqueueTime	Specifies the time when the message was enqueued.
ExceptionQueue	Specifies the name of the queue that the message is moved to if it cannot be processed successfully.
Expiration	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring.
MessageId	Returns an array of message identifiers.
NotificationType	Indicates the type of notification such as regular, grouping, or timeout.
OriginalMessageId	Specifies the ID of the message, in the last queue, that generated this message.
Priority	Specifies the priority of the message.
QueueName	Indicates the name of the queue that contains the message to be dequeued.
SenderId	Identifies the original sender of the message.
State	Specifies the state of the message.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)

OracleAQMessageAvailableEventArgs Constructor

This constructor creates an instance of the `OracleAQMessageAvailableEventArgs` class with default property values.

Declaration

```
// C#
public OracleAQMessageAvailableEventArgs();
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

OracleAQMessageAvailableEventArgs Properties

OracleAQMessageAvailableEventArgs properties are listed in [Table 12-19](#).

Table 12-19 OracleAQMessageAvailableEventArgs Properties

Property	Description
AvailableMessages	Specifies the number of messages that raised this notification.
ConsumerName	Provides the name of the consumer for which the message is available for dequeuing.
Correlation	Provides the name of the consumer for which the message is available for dequeuing.
Delay	Specifies the duration, in seconds, after which an enqueued message is available for dequeuing.
DeliveryMode	Specifies the delivery mode of the message.
EnqueueTime	Specifies the time when the message was enqueued.
ExceptionQueue	Specifies the name of the queue that the message is moved to if it cannot be processed successfully.
Expiration	Specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring.
MessageId	Returns an array of message identifiers.
NotificationType	Indicates the type of notification such as regular, grouping, or timeout.
OriginalMessageId	Specifies the ID of the message, in the last queue, that generated this message.
Priority	Specifies the priority of the message.
QueueName	Indicates the name of the queue that contains the message to be dequeued.
SenderId	Identifies the original sender of the message.
State	Specifies the state of the message.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

AvailableMessages

This instance property specifies the number of messages that raised this notification.

Declaration

```
// C#  
public int AvailableMessages{get;}
```

Property Value

An integer indicating the number of messages that raised this notification.

Remarks

The property value is 1 for a regular notification type. The notification type can be specified using the `OracleAQQueue.Notification` property.

This property is not relevant if the `NotificationType` is `OracleAQNotificationType.Timeout`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

ConsumerName

This property provides the name of the consumer for which the message is available for dequeuing.

Declaration

```
// C#  
public string ConsumerName {get;}
```

Property Value

A string that identifies the name of the consumer.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

Correlation

This instance property specifies the identification for the message.

Declaration

```
// C#  
public string Correlation {get;}
```

Property Value

A *string* that specifies the identification for the message.

Remarks

This property specifies the correlation of the message for which the notification is raised. The consumer can then use this identification to dequeue specific messages by setting the "[Correlation](#)" property of the `OracleAQDequeueOptions` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)
- ["Correlation"](#)

Delay

This instance property specifies the duration, in seconds, after which an enqueued message is available for dequeuing.

Declaration

```
// C#  
public int Delay {get;}
```

Property Value

An *integer* that indicates the duration, in seconds, after which an enqueued message is available for dequeuing.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

DeliveryMode

This instance property specifies the delivery mode of the message.

Declaration

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;}
```

Property Value

An `OracleAQMessageDeliveryMode` enumerated value.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

EnqueueTime

This instance property specifies the time when the message was enqueued.

Declaration

```
// C#  
public DateTime EnqueueTime {get;}
```

Property Value

A `DateTime` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

ExceptionQueue

This instance property specifies the name of the queue that the message is moved to if it cannot be processed successfully.

Declaration

```
// C#  
public string ExceptionQueue {get;}
```

Property Value

The name of the queue that a message to is moved if it cannot be processed successfully.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

Expiration

This instance property specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring.

Declaration

```
// C#  
public int Expiration {get;}
```

Property Value

An integer that specifies the duration, in seconds, for which an enqueued message is available for dequeuing.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

MessageId

This instance property returns an array of message identifiers.

Declaration

```
// C#  
public byte[][] MessageId{get;}
```

Property Value

A `byte[][]` that specifies the message identifiers received as part of the notification.

Remarks

This property specifies the message identifiers of the messages that raise the notification.

The size of the `MessageId` array is 1 for regular notifications. The size of the `MessageId` array is 1 for grouping notifications if the notification grouping type is `OracleAQNotificationGroupingType.Last`. This property is not relevant if the `NotificationType` is `OracleAQNotificationType.Timeout`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

NotificationType

This property indicates the type of notification such as regular, grouping, or timeout.

Declaration

```
// C#  
public OracleAQNotificationType NotificationType {get;}
```

Property Value

An `OracleAQNotificationType` enum value.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

OriginalMessageId

This property specifies the ID of the message, in the last queue, that generated this message.

Declaration

```
// C#  
public byte[] OriginalMessageId {get;}
```

Property Value

A `byte[]` that specifies the original message ID.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

Priority

This instance property specifies the priority of the message.

Declaration

```
// C#  
public int Priority {get;}
```

Property Value

An integer that specifies the priority of the message.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

QueueName

This property indicates the name of the queue that contains the message to be dequeued.

Declaration

```
// C#  
public string QueueName {get;}
```

Property Value

A string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

SenderId

This property identifies the original sender of the message.

Declaration

```
// C#  
public OracleAQAgent SenderId {get;}
```

Property Value

An OracleAQAgent object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

State

This instance property specifies the state of the message.

Declaration

```
// C#  
public OracleAQMessageState State {get;}
```

Property Value

An `OracleAQMessageState` enumerated value.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

OracleAQMessageAvailableEventHandler Delegate

The `OracleAQMessageAvailableEventHandler` delegate represents the signature of the method that handles the `OracleAQQueue.MessageAvailable` event.

Declaration

```
// C#  
public delegate void OracleAQMessageAvailableEventHandler (object  
    sender, OracleAQMessageAvailableEventArgs eventArgs);
```

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleAQMessageAvailableEventArgs` object that contains the event data.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["MessageAvailable Event"](#)

OracleAQQueue Class

An `OracleAQQueue` object represents a queue.

Class Inheritance

`System.Object`

`OracleAQQueue`

Declaration

```
// C#  
public class OracleAQQueue : IDisposable
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

A queue is a repository of messages and may either be a user queue, or an exception queue. A user queue is for normal message processing. A message is moved from a user queue to an exception queue if it cannot be retrieved and processed for some reason.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Members](#)
- [OracleAQQueue Constructors](#)
- [OracleAQQueue Static Methods](#)
- [OracleAQQueue Properties](#)
- [OracleAQQueue Public Methods](#)
- [OracleAQQueue Events](#)

OracleAQQueue Members

OracleAQQueue members are listed in the following tables.

OracleAQQueue Constructors

OracleAQQueue constructors are listed in [Table 12-20](#).

Table 12-20 OracleAQQueue Constructors

Constructor	Description
OracleAQQueue Constructors	Instantiate a new instance of the OracleAQQueue class (Overloaded).

OracleAQQueue Static Methods

The OracleAQQueue static method is listed in [Table 12-21](#).

Table 12-21 OracleAQQueue Static Methods

Static Method	Description
Listen	Listens for messages on one or more queues for one or more consumers, as specified in the array of OracleAQAgent objects (Overloaded).

OracleAQQueue Properties

OracleAQQueue properties are listed in [Table 12-22](#).

Table 12-22 OracleAQQueue Properties

Property	Description
Connection	Specifies the OracleConnection object associated with the queue.

Table 12-22 (Cont.) OracleAQQueue Properties

Property	Description
DequeueOptions	Specifies the dequeuing options to use when dequeuing a message from a queue.
EnqueueOptions	Specifies the enqueueing options used to enqueue a message to a queue.
MessageType	Specifies the type of queue table associated with this queue.
Name	Returns the name of the queue.
Notification	Specifies the various notification options for notifications that are registered using the <code>MessageAvailable</code> event.
NotificationConsumers	Specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue.
UdtTypeName	Specifies the type name on which the queue and the corresponding queue table is based if the <code>MessageType</code> is <code>OracleAQMessageType.UDT</code> .

OracleAQQueue Public Methods

The `OracleAQQueue` public methods are listed in [Table 12-23](#).

Table 12-23 OracleAQQueue Public Methods

Public Method	Description
Dequeue	Dequeues messages from queues (Overloaded).
DequeueArray	Dequeues multiple messages from queues (Overloaded).
Dispose	Releases any resources or memory allocated by the object
Enqueue	Enqueues messages to queues (Overloaded).
EnqueueArray	Enqueues multiple messages to a queue (Overloaded).
Listen	Listens for messages on the queue on behalf of <code>listenConsumers</code> (Overloaded).

OracleAQQueue Events

The `OracleAQQueue` event is listed in [Table 12-24](#).

Table 12-24 OracleAQQueue Events

Event Name	Description
MessageAvailable Event	Notifies when a message is available in the queue for <code>NotificationConsumers</code> .

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)

OracleAQQueue Constructors

`OracleAQQueue` constructors create new instances of the `OracleAQQueue` class.

Overload List:

- [OracleAQQueue\(string\)](#)
This constructor takes a queue name to initialize a queue object.
- [OracleAQQueue\(string, OracleConnection\)](#)
This constructor takes a queue name and connection to initialize a queue object. The connection does not need be open during the queue object construction.
- [OracleAQQueue\(string, OracleConnection, OracleAQMessageType\)](#)
This constructor takes a queue name, connection, and message type enumeration to initialize a queue object.
- [OracleAQQueue\(string, OracleConnection, OracleAQMessageType, string\)](#)
This constructor takes a queue name, connection, message type enumeration, and UDT type name to initialize a queue object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string)

This constructor takes a queue name to initialize a queue object.

Declaration

```
// C#  
public OracleAQQueue(string name);
```

Parameters

- *name*
The name of the queue as specified in the database.

Exceptions

`ArgumentNullException` - The queue name is null.

`ArgumentException` - The queue name is empty.

Remarks

The operation of creating an `OracleAQQueue` object does not involve checking for the existence of the queue in the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string, OracleConnection)

This constructor takes a queue name and connection to initialize a queue object. The connection does not need to be open during the queue object construction.

Declaration

```
// C#  
public OracleAQQueue(string name, OracleConnection con);
```

Parameters

- *name*
Name of the queue as specified in the database.
- *con*
An `OracleConnection` object that connects to the queue.

Exceptions

`ArgumentNullException` - Either the connection is null or queue name is null.

`ArgumentException` - Queue name is empty.

Remarks

The connection can be accessed using the `Connection` property, and it must be opened before calling any operational APIs such as `Enqueue` and `Dequeue`.

Creating an `OracleAQQueue` object does not check for the existence of the queue in the database.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string, OracleConnection, OracleAQMessageType)

This constructor takes a queue name, connection and message type enumeration to initialize a queue object. The connection does not need to be open during the queue object construction.

Declaration

```
// C#  
public OracleAQQueue(string name, OracleConnection con, OracleAQMessageType  
    messageType);
```

Parameters

- *name*
The name of the queue as specified in the database.
- *con*
An *OracleConnection* object that is used to connect to the queue.
- *messageType*
An *OracleAQMessageType* enumeration specifying the type of the message that is enqueued or dequeued from this queue.

Exceptions

ArgumentNullException - Either the connection is null or queue name is null.

ArgumentException - Queue name is empty or the specified message type is not valid.

Remarks

Creating an *OracleAQQueue* object does not check for the existence of the queue in the database.

You need to set the *UdtTypeName* property before using the queue object if the *messageType* is a UDT. Another approach is to create a queue using the other constructor overload by supplying the *udtTypeName*.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string, OracleConnection, OracleAQMessageType, string)

This constructor takes a queue name, connection, message type enumeration, and UDT type name to initialize a queue object. The connection does not need to be open during the queue object construction.

Declaration

```
// C#  
public OracleAQQueue(string name, OracleConnection con, OracleAQMessageType  
    messageType, string udtTypeName);
```

Parameters

- *name*
The name of the queue as specified in the database.
- *con*
An `OracleConnection` object that is used to connect to the queue.
- *messageType*
An `OracleAQMessageType` enumeration specifying the type of the message that is enqueued or dequeued from this queue.
- *udtTypeName*
The name of the database object type used if the `messageType` is UDT. The `udtTypeName` parameter represents the type on which the queue is based.

Exceptions

`ArgumentNullException` - The connection is null or the queue name is null.

`ArgumentException` - The queue name is empty or the specified `messageType` is not valid.

Remarks

Creating an `OracleAQQueue` object does not check for the existence of the queue in the database.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Static Methods

OracleAQQueue static methods are listed in [Table 12-25](#).

Table 12-25 OracleAQQueue Static Methods

Static Method	Description
Listen	Listens for messages on one or more queues for one or more consumers, as specified in the array of OracleAQAgent objects (Overloaded).

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen

Listen methods listen for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.

Overload list

- [Listen\(OracleConnection, OracleAQAgent\[\]\)](#)
This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.
- [Listen\(OracleConnection, OracleAQAgent\[\], int\)](#)
This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects. It also specifies a wait time.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen(OracleConnection, OracleAQAgent[])

This static method listens for messages on one or more queues for one or more consumers as specified in the array of `OracleAQAgent` objects.

Declaration

```
// C#  
public static OracleAQAgent Listen(OracleConnection con, OracleAQAgent[]  
    listenConsumers);
```

Parameters

- *con*
An `OracleConnection` instance.
- *listenConsumers*
The array of consumers being listened for. The name of the `OracleAQAgent` object must be null or empty for single consumer queues.

Return Value

An `OracleAQAgent` object.

Exceptions

`ArgumentNullException` - The *con* or *listenConsumers* parameter is null.

`InvalidOperationException` - The connection is not open.

Remarks

`Listen` is useful in situations where one needs to monitor multiple queues until a message is available for a consumer in one of the queues. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property represents the name of the queue.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the list. It returns an `OracleAQAgent` object which specifies the consumer and queue for which a message is ready to be dequeued.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen(OracleConnection, OracleAQAgent[], int)

This static method listens for messages on one or more queues for one or more consumers as specified in the array of `OracleAQAgent` objects. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property of the `OracleAQAgent` object represents the name of the queue.

In case of timeout, this method returns `null`.

Declaration

```
// C#  
public static OracleAQAgent Listen(OracleConnection con, OracleAQAgent[]  
    listenConsumers, int waitTime);
```

Parameters

- `con`
An `OracleConnection` instance.
- `listenConsumers`
The array of consumers being listened for. The name of the `OracleAQAgent` object must be `null` or empty for single consumer queues.
- `waitTime`
Wait time in seconds.

Return Value

An `OracleAQAgent` object.

Exceptions

`ArgumentNullException` - The `con` or `listenConsumers` parameter is `null`.

`InvalidOperationException` - The connection is not open.

`ArgumentException` - `waitTime` is less than -1.

Remarks

`Listen` is useful in situations where one needs to monitor multiple queues until a message is available for a consumer in one of the queues. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property of the `OracleAQAgent` object represents the name of the queue.

A *waitTime* of -1 implies an infinite wait time.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the list. It returns an `OracleAQAgent` object which specifies the consumer and queue for which a message is ready to be dequeued.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Properties

`OracleAQQueue` properties are listed in [Table 12-26](#).

Table 12-26 OracleAQQueue Properties

Property	Description
Connection	Specifies the <code>OracleConnection</code> object associated with the queue.
DequeueOptions	Specifies the dequeuing options to use when dequeuing a message from a queue.
EnqueueOptions	Specifies the enqueueing options used to enqueue a message to a queue.
MessageType	Specifies the type of queue table associated with this queue.
Name	Returns the name of the queue.
Notification	Specifies the various notification options for notifications that are registered using the <code>MessageAvailable</code> event.
NotificationConsumers	Specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue.
UdtTypeName	Specifies the type name on which the queue and the corresponding queue table is based if the <code>MessageType</code> is <code>OracleAQMessageType.UDT</code> .

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Connection

This property specifies the `OracleConnection` object associated with the queue.

Declaration

```
// C#  
public OracleConnection Connection {get; set;}
```

Property Value

An `OracleConnection` object that indicates the connection associated with the queue.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This connection must be opened before calling methods like `Enqueue` and `Dequeue`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueOptions

This instance property specifies the dequeuing options to use when dequeuing a message from a queue.

Declaration

```
// C#  
public OracleAQDequeueOptions DequeueOptions {get; set;}
```

Property Value

An `OracleAQDequeueOptions` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is an `OracleAQDequeueOptions` object with default property values. Setting this property to `null` resets all dequeue options to their default values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueOptions

This instance property specifies the enqueueing options used to enqueue a message to a queue.

Declaration

```
// C#  
public OracleAQEnqueueOptions EnqueueOptions {get; set}
```

Property Value

An `OracleAQEnqueueOptions` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is an `OracleAQEnqueueOptions` object with default property values. Setting this property to `null` resets all enqueue options to their default values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

MessageType

This instance property specifies the type of queue table associated with this queue.

Declaration

```
// C#
public OracleAQMessageType MessageType {get; set;}
```

Property Value

An `OracleAQMessageType` enumerated value.

Exceptions

`ArgumentOutOfRangeException` - The type value specified is invalid.

`ObjectDisposedException` - The object is already disposed.

Remarks

The `MessageType` property also dictates the type of message payloads that are enqueued or dequeued from the queue. It is possible to enqueue a variety of payloads depending on the `MessageType`.

[Table 12-27](#) lists the allowed payload types for various message types.

Table 12-27 Message Types and Payloads

OracleAQQueue.MessageType	Allowed OracleAQMessage.Payload type to Enqueue
OracleAQMessageType.Raw	OracleBinary, byte[]
OracleAQMessageType.Xml	OracleXmlType, XmlReader, String (well-formed XML, else exception is raised)
OracleAQMessageType.UDT	UDT Custom Object

[Table 12-28](#) lists the payload types for dequeued messages.

Table 12-28 Payload Types for Dequeued Messages

OracleAQQueue.MessageType	DequeueOptions.ProviderSpecificType	OracleAQMessage.Payload of dequeued message
OracleAQMessageType.Xml	true	OracleXmlType
OracleAQMessageType.Xml	false	XmlReader
OracleAQMessageType.Raw	true	OracleBinary
OracleAQMessageType.Raw	false	Byte[]
OracleAQMessageType.UDT	N.A.	UDT Custom Object

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Name

This instance property returns the name of the queue.

Declaration

```
// C#  
public string Name {get;}
```

Property Value

A string that indicates the name of the queue.

Exceptions

`ObjectDisposedException` - The object is already disposed.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Notification

This instance property specifies the various notification options for notifications that are registered using the `MessageAvailable` event.

Declaration

```
// C#  
public OracleNotificationRequest Notification {get;}
```

Property Value

Specifies an `OracleNotificationRequest` object whose properties can be changed to alter the notification behavior.

Remarks

This property can be used to change various notification options. The notification options must be changed before registering with the `MessageAvailable` event. This property can be modified again only after unregistering from the `MessageAvailable` event.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

NotificationConsumers

This instance property specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue.

Declaration

```
// C#  
public string[] NotificationConsumers {get; set;}
```

Property Value

Specifies an array of consumer name strings for which the notifications are delivered.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - `MessageAvailable` registration is active.

Remarks

The consumer names must be in uppercase. This functionality only supports queues with uppercase names.

The list of consumers is used in the `MessageAvailable` event. The list must be set before registering for the event. This property cannot be modified after registering for the `MessageAvailable` event. This property can be modified again only after unregistering from `MessageAvailable` event.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

UdtTypeName

This instance property specifies the type name on which the queue and the corresponding queue table is based if the `MessageType` is `OracleAQMessageType.UDT`.

Declaration

```
// C#  
public string UdtTypeName {get; set;}
```

Property Value

Specifies the Oracle user-defined type name if the `MessageType` is `OracleAQMessageType.UDT`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The `UdtTypeName` property corresponds to the user-defined type name of the payload. This property must always be specified if the payload is a user-defined type. This property need not be set for other payload types.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Public Methods

`OracleAQQueue` public methods are listed in [Table 12-29](#).

Table 12-29 OracleAQQueue Public Methods

Public Method	Description
Dequeue	Dequeues messages from queues (Overloaded).
DequeueArray	Dequeues multiple messages from queues (Overloaded).
Dispose	Releases any resources or memory allocated by the object
Enqueue	Enqueues messages to queues (Overloaded).
EnqueueArray	Enqueues multiple messages to a queue (Overloaded).
Listen	Listens for messages on the queue on behalf of <code>listenConsumers</code> (Overloaded).

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dequeue

Dequeue methods dequeue messages from queues.

Overload List

- [Dequeue\(\)](#)
This instance method dequeues messages from a queue using the `DequeueOptions` for the instance.
- [Dequeue\(OracleAQDequeueOptions\)](#)
This instance method dequeues messages from a queue using the supplied dequeue options.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dequeue()

This instance method is used to dequeue a message from a queue using the `DequeueOptions` for the instance.

Declaration

```
// C#  
public OracleAQMessage Dequeue();
```

Return Value

An `OracleAQMessage` instance representing the dequeued message.

Exceptions

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than `-1`.

Remarks

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

Dequeued buffered messages always have null `MessageId` values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dequeue(OracleAQDequeueOptions)

This instance method dequeues messages from a queue using the supplied dequeue options.

Declaration

```
// C#  
public OracleAQMessage Dequeue(OracleAQDequeueOptions dequeueOptions);
```

Parameters

- `dequeueOptions`

An `OracleAQDequeueOptions` object.

Return Value

An `OracleAQMessage` instance representing the dequeued message.

Exceptions

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than `-1`.

Remarks

If the supplied `dequeueOptions` object is `null`, then the dequeue options default values are used. The queue object's `DequeueOptions` property is ignored for this operation.

Calling this method does not change the `DequeueOptions` property of the queue.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

Dequeued buffered messages always have `null` `MessageId` values.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueArray

`DequeueArray` methods dequeue multiple messages from queues.

Overload List

- [DequeueArray\(int\)](#)

This instance method dequeues multiple messages from a queue using the `DequeueOptions` of the instance.

- [DequeueArray\(int, OracleAQDequeueOptions\)](#)

This instance method dequeues multiple messages from a queue using the supplied dequeue options.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueArray(int)

This instance method dequeues multiple messages from a queue using the `DequeueOptions` of the instance.

Declaration

```
// C#  
public OracleAQMessage[] DequeueArray(int dequeueCount);
```

Parameters

- `dequeueCount`
An integer specifying the numbers of messages to dequeue.

Return Value

An array of `OracleAQMessage` instances representing the dequeued messages.

Exceptions

`ArgumentOutOfRangeException` - `dequeueCount` is less than or equal to 0.

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than -1.

Remarks

This method is supported for Oracle Database 10g and higher releases.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

The size of the returned array may be less than the `dequeueCount`. It depends on the actual number of messages present in the queue.

For database versions earlier than Oracle Database 12c Release 2 (12.2), the `MessageId` property of persistent `OracleAQMessage` objects retrieved using `DequeueArray` is always null.

Dequeued buffered messages always have null `MessageId` values irrespective of the database version.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueArray(int, OracleAQDequeueOptions)

This instance method dequeues multiple messages from a queue using the supplied dequeue options.

Declaration

```
// C#  
public OracleAQMessage[] DequeueArray(int dequeueCount, OracleAQDequeueOptions  
dequeueOptions);
```

Parameters

- *dequeueCount*
An integer specifying the numbers of messages to dequeue.
- *dequeueOptions*
An `OracleAQDequeueOptions` object.

Return Value

An array of `OracleAQMessage` instances representing the dequeued messages.

Exceptions

`ArgumentOutOfRangeException` - *dequeueCount* is less than or equal to 0.

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, `ORA-25228: timeout or end-of-fetch during message dequeue from queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than -1.

Remarks

This method is supported for Oracle Database 10g Release 1 (10.1) and higher releases. Calling this method does not change the `DequeueOptions` property of the queue.

If the supplied `dequeueOptions` object is `null`, then the dequeue options default values are used. The `DequeueOptions` property of the queue object is ignored in this operation.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

The size of the returned array may be less than the `dequeueCount`. It depends on the actual number of messages present in the queue.

For database versions earlier than Oracle Database 12c Release 2 (12.2), the `MessageId` property of persistent `OracleAQMessage` objects retrieved using `DequeueArray` is always `null`.

Dequeued buffered messages always have `null` `MessageId` values irrespective of the database version.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Enqueue

`Enqueue` instance methods enqueue messages to queues.

Overload List

- [Enqueue\(OracleAQMessage\)](#)
This instance method enqueues messages to a queue using the `EnqueueOptions` of the instance.
- [Enqueue\(OracleAQMessage, OracleAQEnqueueOptions\)](#)
This instance method enqueues messages to a queue using the supplied enqueue options.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Enqueue(OracleAQMessage)

This instance method enqueues messages to a queue using the `EnqueueOptions` of the instance.

Declaration

```
// C#  
public void Enqueue(OracleAQMessage message);
```

Parameters

- *message*
An `OracleAQMessage` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The connection is not open.

`ArgumentNullException` - The message parameter is null.

`ArgumentException` - The message payload is `OracleXmlType` and the connection used to create `OracleXmlType` is different from the queue's connection.

Remarks

`MessageId` of the enqueued message is populated after the call to `Enqueue` completes. Enqueued buffered messages always have null `MessageId` values.

The `MessageType` property needs to be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Enqueue(OracleAQMessage, OracleAQEnqueueOptions)

This instance method enqueues messages to a queue using the supplied enqueue options.

Declaration

```
// C#  
public void Enqueue(OracleAQMessage message, OracleAQEnqueueOptions enqueueOptions);
```

Parameters

- *message*
An OracleAQMessage object.
- *enqueueOptions*
An OracleAQEnqueueOptions object.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The connection is not open.

ArgumentNullException - The message parameter is null.

ArgumentException - The message payload is OracleXmlType and the connection used to create OracleXmlType is different from the queue's connection.

Remarks

If the supplied enqueueOptions object is null, then the enqueue options default values are used. The EnqueueOptions property of the queue object is ignored in this operation.

The MessageId of the enqueued message is populated after the call to Enqueue completes. Enqueued buffered messages always have null MessageId values. Calling this method does not change the EnqueueOptions property of the queue.

The MessageType property must be set appropriately before calling this function. If the MessageType is OracleAQMessageType.UDT, then the UdtTypeName property must also be set.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueArray

EnqueueArray instance methods enqueue multiple messages to a queue.

Overload List

- [EnqueueArray\(OracleAQMessage\[\]\)](#)
This instance method enqueues multiple messages to a queue using the `EnqueueOptions` of the instance.
- [EnqueueArray\(OracleAQMessage\[\], OracleAQEnqueueOptions\)](#)
This instance method enqueues multiple messages to a queue using the supplied enqueue options.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueArray(OracleAQMessage[])

This instance method enqueues multiple messages to a queue using the `EnqueueOptions` of the instance.

Declaration

```
// C#  
public int EnqueueArray(OracleAQMessage[] messages);
```

Parameters

- *messages*
An array of `OracleAQMessage` objects.

Return Value

An integer representing the number of messages actually enqueued.

Exceptions

`ArgumentNullException` - The message parameter is null.

`ArgumentException` - At least one of the `OracleAQMessage[]` elements is null, or at least one of the `OracleAQMessage[]` elements has a payload of `OracleXmlType`, which is created using a connection that is different from the queue's connection.

`InvalidOperationException` - The `OracleAQMessage` array is empty or the connection is not open.

`ObjectDisposedException` - The object is already disposed.

Remarks

This method is supported by Oracle Database 10g and higher releases. The `MessageId` properties of the enqueued messages are populated after the call to `Enqueue` completes. Enqueued buffered messages always have null `MessageId` values.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueArray(OracleAQMessage[], OracleAQEnqueueOptions)

This instance method enqueues multiple messages to a queue using the supplied enqueue options.

Declaration

```
// C#
public int EnqueueArray(OracleAQMessage[] messages, OracleAQEnqueueOptions
    enqueueOptions);
```

Parameters

- *messages*
An array of `OracleAQMessage` objects.
- *enqueueOptions*
An `OracleAQEnqueueOptions` object.

Return Value

An integer representing the number of messages actually enqueued.

Exceptions

`ArgumentNullException` - The message parameter is null.

`ArgumentException` - At least one of the `OracleAQMessage[]` elements is null, or at least one of the `OracleAQMessage[]` elements has a payload of `OracleXmlType`, which is created using a connection that is different from the queue's connection.

`InvalidOperationException` - The `OracleAQMessage` array is empty or the connection is not open.

`ObjectDisposedException` - The object is already disposed.

Remarks

This method is supported by Oracle Database 10g and higher releases. `MessageId` properties of the enqueued messages are populated after the call to `Enqueue` completes. Enqueued buffered messages always have null `MessageId` values. Calling this method does not change the `EnqueueOptions` property of the queue.

If the supplied `enqueueOptions` object is null, then the enqueue options default values are used. The `EnqueueOptions` property of the queue object is ignored in this operation.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen

Listen methods listen for messages on the queue on behalf of `listenConsumers`.

Overload List

- [Listen\(string\[\]\)](#)
This method listens for messages on the queue on behalf of `listenConsumers`.
- [Listen \(string\[\], int\)](#)
This method listens for messages on behalf of `listenConsumers` for a specified time.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen(string[])

This method listens for messages on the queue on behalf of `listenConsumers`.

Declaration

```
// C#  
public string Listen(string[] listenConsumers);
```

Parameters

- *listenConsumers*

An array of consumers to listen for on this queue. This parameter should be `null` in case of single consumer queues.

Return Value

A `string`.

Exceptions

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

Remarks

This call blocks the calling thread until there is a message ready for consumption for a consumer in the `listenConsumers` array. It returns a `string` representing the consumer name for which the message is ready.

`Listen` is useful in situations that require waiting until a message is available in the queue for consumers whose names are specified in `listenConsumers`.

Example

The following example demonstrates using the `Listen` method. The first part of the example performs the requisite database setup for the database user, `SCOTT`. The second part of the example demonstrates how a thread can listen and wait until a message is enqueued.

```
-- Part I: Database setup required for this demo  
  
-----  
-- SQL to grant appropriate privilege to database user, SCOTT  
-----  
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
```

```
User altered.
GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PLSQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PLSQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
  DBMS_AQADM.STOP_QUEUE('scott.test_q');

  DBMS_AQADM.DROP_QUEUE(
    queue_name => 'scott.test_q',
    auto_commit => TRUE);

  DBMS_AQADM.DROP_QUEUE_TABLE(
    queue_table => 'scott.test_q_tab',
    force => FALSE,
    auto_commit => TRUE);
END;
/
-- End of Part I, database setup.

//Part II: Demonstrates using the Listen method
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;
using System.Threading;

namespace ODPSample
{
  /// <summary>
  /// Demonstrates how a thread can listen and wait until a message is enqueued.
  /// Once a message is enqueued, the listening thread returns from the
  /// blocked Listen() method invocation and dequeues the message.
  /// </summary>
  class EnqueueDequeue
  {
    static bool s_bListenReturned = false;

    static void Main(string[] args)
    {
      // Create connection
      string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
```

```
OracleConnection con = new OracleConnection(constr);

// Create queue
OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

try
{
    // Open connection
    con.Open();

    // Set message type for the queue
    queue.MessageType = OracleAQMessageType.Raw;

    // Spawning a thread which will listen for a message
    ThreadStart ts = new ThreadStart(TestListen);
    Thread t = new Thread(ts);
    t.Start();

    System.Threading.Thread.Sleep(2000);

    // Begin transaction for enqueue
    OracleTransaction txn = con.BeginTransaction();

    // Prepare message and RAW payload
    OracleAQMessage enqMsg = new OracleAQMessage();
    byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
    enqMsg.Payload = bytePayload;

    // Prepare to Enqueue
    queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;

    Console.WriteLine("[Main Thread]   Enqueuing a message...");
    Console.WriteLine("[Main Thread]   Enqueued Message Payload       : "
        + ByteArrayToString(enqMsg.Payload as byte[]));
    Console.WriteLine();

    // Enqueue message
    queue.Enqueue(enqMsg);

    // Enqueue transaction commit
    txn.Commit();

    // Loop till Listen returns
    while (!s_bListenReturned)
        System.Threading.Thread.Sleep(1000);
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queue.Dispose();
    con.Close();
    con.Dispose();
}

static void TestListen()
{
```

```
// Create connection
string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
OracleConnection conListen = new OracleConnection(constr);

// Create queue
OracleAQQueue queueListen = new OracleAQQueue("scott.test_q", conListen);

try
{
    // Open the connection for Listen thread.
    // Connection blocked on Listen thread can not be used for other DB
    // operations
    conListen.Open();

    // Set message type for the queue
    queueListen.MessageType = OracleAQMessageType.Raw;

    // Listen
    queueListen.Listen(null);

    Console.WriteLine("[Listen Thread] Listen returned... Dequeueing...");

    // Begin txn for Dequeue
    OracleTransaction txn = conListen.BeginTransaction();

    // Prepare to Dequeue
    queueListen.DequeueOptions.Visibility = OracleAQVisibilityMode.OnCommit;
    queueListen.DequeueOptions.Wait = 10;

    // Dequeue message
    OracleAQMessage deqMsg = queueListen.Dequeue();
    Console.WriteLine("[Listen Thread] Dequeued Message Payload      : "
        + ByteArrayToString(deqMsg.Payload as byte[]));

    // Dequeue txn commit
    txn.Commit();

    // Allow the main thread to exit
    s_bListenReturned = true;
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queueListen.Dispose();
    conListen.Close();
    conListen.Dispose();
}
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
    for (int n = 0; n < byteArray.Length; n++)
    {
        sb.Append((int.Parse(byteArray[n].ToString())).ToString("X"));
    }
}
```

```
        return sb.ToString();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen (string[], int)

This method listens for messages on behalf of `listenConsumers` for a specified time.

Declaration

```
// C#  
public string Listen(string[] listenConsumers, int waitTime);
```

Parameters

- `listenConsumers`
Array of consumers for which to listen on this queue.
- `waitTime`
Wait time in seconds.

Return Value

A `string`

Exceptions

`InvalidOperationException` - The connection is not open.

`ArgumentException` - `waitTime` is less than -1.

`ObjectDisposedException` - The object is already disposed.

Remarks

`Listen` is useful in situations that require waiting until a message is available in the queue for consumers whose names are specified in `listenConsumers`.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the `listenConsumers` array. It returns a `string` representing the consumer name for which the message is ready. The method returns `null` if a timeout occurs.

The `listenConsumers` parameter should be `null` for single consumer queues. An empty string is returned in such cases.

A `waitTime` of `-1` implies infinite wait time.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Events

The `OracleAQQueue` event is listed in [Table 12-30](#).

Table 12-30 OracleAQQueue Events

Event Name	Description
MessageAvailable Event	Notifies when a message is available in the queue for <code>NotificationConsumers</code> .



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

MessageAvailable Event

This event is notified when a message is available in the queue for `NotificationConsumers`.

Declaration

```
// C#  
public event OracleAQMessageAvailableEventHandler MessageAvailable;
```

Event Data

The event handler receives an `OracleAQMessageAvailableEventArgs` object.

Exceptions

`InvalidOperationException` - The connection is not open.

Remarks

Asynchronous notification is supported in all queue tables created with a database compatibility level of 8.1 or higher.

In order to receive the notification about message availability, the client must create an `OracleAQMessageAvailableEventHandler` delegate to listen to this event. The delegate should be added to this event only after setting the [NotificationConsumers](#) and [Notification](#) properties.

The notification registration takes place after the first delegate is added to the event. The notification is unregistered when the last delegate is removed from the event. Notifications set on an `OracleAQQueue` object get cancelled automatically when the object gets disposed.

Oracle Data Provider for .NET opens a port to listen for notifications. HA events, load balancing, and continuous query notification features also share the same port. This port can be configured centrally by setting the database notification port in an application or Web configuration file. The following example code specifies a port number of 1200:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DbNotificationPort" value="1200"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

If the configuration file does not exist or the db notification port is not specified, then ODP.NET uses a valid and random port number. The configuration file may also request for a random port number by specifying a db notification port value of -1.

The notification listener, which runs in the same application domain as ODP.NET, uses the specified port number to listen to notifications from the database. A notification listener gets created when the application registers with `OracleAQQueue.MessageAvailable` event. One notification listener can listen to all notification types. Only one notification listener is created for each application domain.

Example

The following example demonstrates application notification. The first part of the example performs the requisite database setup for the database user, `SCOTT`. The second part of the example demonstrates how an application is notified when a message is available in the queue.

```
-- Part I: Database setup required for this demo
-----
-- SQL to grant appropriate privilege to database user, SCOTT
-----
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
SQL> GRANT ALL ON DBMS_AQADM TO scott;
-----
-- PLSQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
```

```
DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PLSQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
    DBMS_AQADM.STOP_QUEUE('scott.test_q');

    DBMS_AQADM.DROP_QUEUE(
        queue_name => 'scott.test_q',
        auto_commit => TRUE);

    DBMS_AQADM.DROP_QUEUE_TABLE(
        queue_table => 'scott.test_q_tab',
        force => FALSE,
        auto_commit => TRUE);
END;
/
-- End of Part I, database setup.

//Part II: Demonstrates application notification
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

namespace ODPSample
{
    /// <summary>
    /// Demonstrates how the application can be notified when a message is
    /// available in a queue.
    /// </summary>
    class Notification
    {
        static bool isNotified = false;

        static void Main(string[] args)
        {
            // Create connection
            string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
            OracleConnection con = new OracleConnection(constr);

            // Create queue
            OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

            try
            {
                // Open connection
                con.Open();
            }
        }
    }
}
```

```
// Set message type for the queue
queue.MessageType = OracleAQMessageType.Raw;

// Add the event handler to handle the notification. The
// MsgReceived method will be invoked when a message is enqueued
queue.MessageAvailable +=
    new OracleAQMessageAvailableEventHandler(Notification.MsgReceived);

Console.WriteLine("Notification registered...");

// Begin txn for enqueue
OracleTransaction txn = con.BeginTransaction();

Console.WriteLine("Now enqueueing message...");

// Prepare message and RAW payload
OracleAQMessage enqMsg = new OracleAQMessage();
byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
enqMsg.Payload = bytePayload;

// Prepare to Enqueue
queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;

// Enqueue message
queue.Enqueue(enqMsg);

Console.WriteLine("Enqueued Message Payload      : "
    + ByteArrayToString(enqMsg.Payload as byte[]));
Console.WriteLine("MessageId of Enqueued Message : "
    + ByteArrayToString(enqMsg.MessageId));
Console.WriteLine();

// Enqueue txn commit
txn.Commit();

// Loop while waiting for notification
while (isNotified == false)
{
    System.Threading.Thread.Sleep(2000);
}
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queue.Dispose();
    con.Close();
    con.Dispose();
}
}

static void MsgReceived(object src, OracleAQMessageAvailableEventArgs arg)
{
    try
    {
        Console.WriteLine("Notification Received...");
        Console.WriteLine("QueueName : {0}", arg.QueueName);
    }
}
```

```

        Console.WriteLine("Notification Type : {0}", arg.NotificationType);

        //following type-cast to "byte[]" is required only for .NET 1.x
        byte[] notifiedMsgId = (byte[]) arg.MessageId[0];
        Console.WriteLine("MessageId of Notified Message : "
            + ByteArrayToString(notifiedMsgId));
        isNotified = true;
    }
    catch (Exception e)
    {
        Console.WriteLine("Error: {0}", e.Message);
    }
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
    for (int n = 0; n < byteArray.Length; n++)
    {
        sb.Append((int.Parse(byteArray[n].ToString())).ToString("X"));
    }
    return sb.ToString();
}
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQDequeueMode Enumeration

[Table 12-31](#) lists all the `OracleAQDequeueMode` enumeration values with a description of each enumerated value.

Table 12-31 OracleAQDequeueMode Members

Member Name	Description
Browse	Reads the message without acquiring any lock on the message. This is equivalent to a <code>SELECT</code> statement.
Locked	Reads and obtains a write lock on the message. The lock lasts for the duration of the transaction. This is equivalent to a <code>SELECT FOR UPDATE</code> statement.
Remove	Reads the message and updates or deletes it. This is the default. The message can be retained in the queue table based on the retention properties

Table 12-31 (Cont.) OracleAQDequeueMode Members

Member Name	Description
RemoveNoData	Confirms receipt of the message but does not deliver the actual message content.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleAQDequeueOptions Class"](#)
- ["DequeueMode"](#)

OracleAQMessageDeliveryMode Enumeration

The `OracleAQMessageDeliveryMode` enumeration type specifies the delivery mode of the message.

[Table 12-32](#) lists all the `OracleAQMessageDeliveryMode` enumeration values with a description of each enumerated value.

Table 12-32 OracleAQMessageDeliveryMode Members

Member Name	Description
Buffered	<p>Indicates a buffered message.</p> <p>Both enqueue and dequeue buffered messaging operations must be in IMMEDIATE visibility mode. This means that these operations cannot be part of another transaction. You cannot specify delay when enqueueing buffered messages.</p> <p>Dequeueing applications can choose to dequeue persistent messages only, buffered messages only, or both types.</p> <p>Buffered messages can be queried using the AQ\$Queue_Table_Name view. These messages appear with states, IN-MEMORY or SPILLED.</p> <p>Transaction grouping queues and array enqueues are not supported for buffered messages in Oracle Database 11g release 1 (11.1) . One can still use the array enqueue procedure to enqueue buffered messages, but the array size must be set to 1. Array dequeue is not supported for buffered messaging, but one can still use the array dequeue procedure by setting array size to 1.</p> <p>Buffered messaging is faster than persistent messaging. Use buffered messaging for applications that do not require the reliability and transaction support of Oracle Database AQ persistent messaging.</p>
Persistent	<p>Indicates a persistent message.</p> <p>Persistent messaging ensures reliability and support transactions. It is slower than buffered messaging.</p>
PersistentOrBuffered	<p>Indicates a persistent or buffered message.</p> <p>This is used with Dequeue () when a consumer wants to dequeue a message irrespective of whether it is Persistent or Buffered.</p>

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleAQDequeueOptions Class"](#)
- ["DeliveryMode"](#)

OracleAQMessageState Enumeration

The `OracleAQMessageState` enumeration type identifies the state of the message at the time of dequeue.

[Table 12-33](#) lists all the `OracleAQMessageState` enumeration values with a description of each enumerated value.

Table 12-33 OracleAQMessageState Members

Member Name	Description
Expired	Indicates that the message has been moved to the exception queue.
Processed	Indicates that the message has been processed and retained.
Ready	Indicates that the message is ready to be processed.
Waiting	Indicates that the message delay has not been reached.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleAQMessage Class"](#)
- ["State"](#)

OracleAQMessageType Enumeration

The `OracleAQMessageType` enumeration type specifies the message payload type.

[Table 12-34](#) lists all the `OracleAQMessageType` enumeration values with a description of each enumerated value.

Table 12-34 OracleAQMessageType Members

Member Name	Description
Raw	Indicates the Raw message type. The data type of the payload must be either <code>OracleBinary</code> or <code>byte[]</code> to enqueue the message.
Udt	Indicates the Oracle UDT message type. The ODP.NET AQ implementation currently does not support user defined types with LOB attributes. It also does not support other variants of user defined types such as VARRAY and nested tables, as Oracle Database AQ does not support them inherently.
Xml	Indicates the XML message type. The data type of the payload must be <code>OracleXmlType</code> , <code>XmlReader</code> , or <code>String</code> in order to enqueue the message. If the data type is <code>String</code> , it must be well-formed XML, else an exception is raised when enqueueing the message.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleAQQueue Class"](#)
- ["OracleAQQueue Constructors"](#)
- ["MessageType"](#)

OracleAQNavigationMode Enumeration

[Table 12-35](#) lists all the `OracleAQNavigationMode` enumeration values with a description of each enumerated value.

Table 12-35 OracleAQNavigationMode Members

Member Name	Description
<code>FirstMessage</code>	Retrieves the first message that is available and matches the search criteria. This resets the position to the beginning of the queue.

Table 12-35 (Cont.) OracleAQNavigationMode Members

Member Name	Description
FirstMessageMultiGroup	<p>Indicates that a call to <code>DequeueArray</code> resets the position to the beginning of the queue, and dequeues messages that are available and match the search criteria. Messages are dequeued till the <code>dequeueCount</code> limit is reached. The dequeued messages can belong to different transaction groups.</p> <p>You can use the <code>OracleAQMessage.TransactionGroup</code> property to distinguish between messages from different transaction groups. All messages from the same transaction group have the same value for the <code>OracleAQMessage.TransactionGroup</code> property.</p>
NextMessage	Retrieves the next message that is available and matches the search criteria. If the previous message belongs to a message group, AQ retrieves the next available message that matches the search criteria and belongs to the message group.
NextMessageMultiGroup	<p>Indicates that a call to <code>DequeueArray</code> dequeues the next set of messages that are available and match the search criteria. Messages are dequeued till the <code>dequeueCount</code> limit is reached. The dequeued messages can belong to different transaction groups.</p> <p>You can use the <code>OracleAQMessage.TransactionGroup</code> property to distinguish between messages from different transaction groups. All messages from the same transaction group have the same value for the <code>OracleAQMessage.TransactionGroup</code> property.</p>
NextTransaction	Skips the remainder of the current transaction group (if any) and retrieves the first message of the next transaction group.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleAQDequeueOptions Class"](#)
- ["NavigationMode"](#)

OracleAQNotificationGroupingType Enumeration

The `OracleAQNotificationGroupingType` enumeration type specifies the notification grouping type.

[Table 12-36](#) lists all the `OracleAQNotificationGroupingType` enumeration values with a description of each enumerated value.

Table 12-36 OracleAQNotificationGroupingType Members

Member Name	Description
Last	Indicates that only details of the last message in the notification group are provided.
Summary	Indicates that the Summary of all messages in the notification group is provided.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleNotificationRequest Class"](#)

OracleAQNotificationType Enumeration

The `OracleAQNotificationType` enumeration type specifies the notification type of the received notification.

[Table 12-37](#) lists all the `OracleAQNotificationType` enumeration values with a description of each enumerated value.

Table 12-37 OracleAQNotificationType Members

Member Name	Description
Group	Indicates that the received notification is a grouping notification.
Regular	Indicates that the received notification is a regular notification.
Timeout	Indicates that the received notification is raised due to a timeout.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)

OracleAQVisibilityMode Enumeration

[Table 12-38](#) lists all the OracleAQVisibilityMode enumeration values with a description of each enumerated value.

Table 12-38 OracleAQVisibilityMode Members

Member Name	Description
Immediate	Indicates that the enqueue or dequeue operation is not part of the current transaction. The operation constitutes a transaction of its own.
OnCommit	Indicates that the enqueue or dequeue operation is part of the current transaction. This is the default case.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)

13

Oracle Data Provider for .NET Types Classes

This chapter describes the large object and `REF CURSOR` objects provided by Oracle Data Provider for .NET.

This chapter contains these topics:

- ODP.NET Types (ODP.NET LOB objects) consisting of these object classes:
 - [OracleBFile Class](#)
 - [OracleBlob Class](#)
 - [OracleClob Class](#)
- [OracleRefCursor Class](#)

All offsets are 0-based for all ODP.NET LOB object parameters.

OracleBFile Class

An `OracleBFile` is an object that has a reference to `BFILE` data. It provides methods for performing operations on `BFILES`.

Note:

`OracleBFile` is supported for applications running against Oracle8.x and later.

Class Inheritance

```
System.Object
  System.MarshalByRefObject
    System.IO.Stream
      Oracle.DataAccess.Types.OracleBFile
```

Declaration

```
// C#
public sealed class OracleBFile : Stream, ICloneable, INullable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

OracleBFile is supported for applications running against Oracle8.x and later.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleBFileSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Read 7 bytes into readBuffer, starting at buffer offset 0
        byte[] readBuffer = new byte[7];
        int bytesRead = bFile.Read(readBuffer, 0, 7);
    }
}
```

```
// Prints "bytesRead = 7"
Console.WriteLine("bytesRead = " + bytesRead);

// Prints "readBuffer = 65666768656667"
Console.Write("readBuffer = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Search for the 2nd occurrence of a byte pattern {66,67}
// starting from byte offset 1 in the OracleBFile
byte[] pattern = new byte[2] {66, 67};
long posFound = bFile.Search(pattern, 1, 2);

// Prints "posFound = 6"
Console.WriteLine("posFound = " + posFound);

// Close the OracleBFile
bFile.CloseFile();

bFile.Close();
bFile.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Members](#)
- [OracleBFile Constructors](#)
- [OracleBFile Static Fields](#)
- [OracleBFile Static Methods](#)
- [OracleBFile Instance Properties](#)
- [OracleBFile Instance Methods](#)

OracleBFile Members

OracleBFile members are listed in the following tables.

OracleBFile Constructors

OracleBFile constructors are listed in [Table 13-1](#).

Table 13-1 OracleBFile Constructors

Constructor	Description
OracleBFile Constructors	Creates an instance of the OracleBFile class (Overloaded)

OracleBFile Static Fields

OracleBFile static fields are listed in [Table 13-2](#).

Table 13-2 OracleBFile Static Fields

Field	Description
MaxSize	The static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 (2 ³² - 1) bytes
Null	Represents a null value that can be assigned to the value of an OracleBFile instance

OracleBFile Static Methods

OracleBFile static methods are listed in [Table 13-3](#).

Table 13-3 OracleBFile Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleBFile Instance Properties

OracleBFile instance properties are listed in [Table 13-4](#).

Table 13-4 OracleBFile Instance Properties

Properties	Description
CanRead	Indicates whether or not the LOB stream can be read
CanSeek	Indicates whether or not forward and backward seek operations can be performed
CanWrite	Indicates whether or not the LOB object supports writing
Connection	Indicates the connection used to read from a BFILE
DirectoryName	Indicates the directory alias of the BFILE
FileExists	Indicates whether or not the specified BFILE exists
FileName	Indicates the name of the BFILE
IsEmpty	Indicates whether the BFILE is empty or not

Table 13-4 (Cont.) OracleBFile Instance Properties

Properties	Description
IsNull	Indicates whether or not the current instance has a null value
IsOpen	Indicates whether the BFILE has been opened by this instance or not
Length	Indicates the size of the BFILE data in bytes
Position	Indicates the current read position in the LOB stream
Value	Returns the data, starting from the first byte in BFILE, as a byte array

OracleBFile Instance Methods

OracleBFile instance methods are listed in [Table 13-5](#).

Table 13-5 OracleBFile Instance Methods

Methods	Description
BeginRead	Inherited from <code>System.IO.Stream</code>
BeginWrite	<i>Not Supported</i>
Clone	Creates a copy of an OracleBFile object
Close	Closes the current stream and releases any resources associated with the stream
CloseFile	Closes the BFILE referenced by the current BFILE instance
Compare	Compares data referenced by the two OracleBFiles
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
CopyTo	Copies data as specified (Overloaded)
Dispose	Releases resources allocated by this object
EndRead	Inherited from <code>System.IO.Stream</code>
EndWrite	<i>Not Supported</i>
Equals	Inherited from <code>System.Object</code> (Overloaded)
Flush	<i>Not Supported</i>
FlushAsync	<i>Not Supported</i>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
IsEqual	Compares the LOB references

Table 13-5 (Cont.) OracleBFile Instance Methods

Methods	Description
OpenFile	Opens the BFILE specified by the FileName and DirectoryName
Read	Reads a specified amount of bytes from the OracleBFile instance and populates the buffer
ReadByte	Inherited from System.IO.Stream
Search	Searches for a binary pattern in the current instance of an OracleBFile
Seek	Sets the position on the current LOB stream
SetLength	<i>Not Supported</i>
ToString	Inherited from System.Object
Write	<i>Not Supported</i>
WriteByte	<i>Not Supported</i>

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Members](#)

OracleBFile Constructors

OracleBFile constructors create new instances of the OracleBFile class.

Overload List:

- [OracleBFile\(OracleConnection\)](#)
This constructor creates an instance of the OracleBFile class with an OracleConnection object.
- [OracleBFile\(OracleConnection, string, string\)](#)
This constructor creates an instance of the OracleBFile class with an OracleConnection object, the location of the BFILE, and the name of the BFILE.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile(OracleConnection)

This constructor creates an instance of the `OracleBFile` class with an `OracleConnection` object.

Declaration

```
// C#  
public OracleBFile(OracleConnection con);
```

Parameters

- `con`
The `OracleConnection` object.

Exceptions

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The connection must be opened explicitly by the application. `OracleBFile` does not open the connection implicitly.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile(OracleConnection, string, string)

This constructor creates an instance of the `OracleBFile` class with an `OracleConnection` object, the location of the `BFILE`, and the name of the `BFILE`.

Declaration

```
// C#
public OracleBFile(OracleConnection con, string directoryName, string
    fileName);
```

Parameters

- *con*
The `OracleConnection` object.
- *directoryName*
The directory alias created by the `CREATE DIRECTORY SQL` statement.
- *fileName*
The name of the external LOB.

Exceptions

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The `OracleConnection` must be opened explicitly by the application. `OracleBFile` does not open the connection implicitly.

To initialize a `BFILE` column using an `OracleBFile` instance as an input parameter of a SQL `INSERT` statement, *directoryName* and *fileName* must be properly set.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Static Fields

`OracleBFile` static fields are listed in [Table 13-6](#).

Table 13-6 OracleBFile Static Fields

Field	Description
MaxSize	The static field holds the maximum number of bytes a <code>BFILE</code> can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes
Null	Represents a null value that can be assigned to the value of an <code>OracleBFile</code> instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

MaxSize

This static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes.

Declaration

```
// C#  
public static readonly Int64 MaxSize = 4294967295;
```

Remarks

This field is useful in code that checks whether or not the operation exceeds the maximum length allowed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Null

This static field represents a null value that can be assigned to the value of an OracleBFile instance.

Declaration

```
// C#  
public static readonly OracleBFile Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Static Methods

OracleBFile static methods are listed in [Table 13-7](#).

Table 13-7 OracleBFile Static Methods

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Instance Properties

OracleBFile instance properties are listed in [Table 13-8](#).

Table 13-8 OracleBFile Instance Properties

Properties	Description
CanRead	Indicates whether or not the LOB stream can be read
CanSeek	Indicates whether or not forward and backward seek operations can be performed
CanWrite	Indicates whether or not the LOB object supports writing
Connection	Indicates the connection used to read from a BFILE
DirectoryName	Indicates the directory alias of the BFILE
FileExists	Indicates whether or not the specified BFILE exists
FileName	Indicates the name of the BFILE
IsEmpty	Indicates whether the BFILE is empty or not
IsNull	Indicates whether or not the current instance has a null value

Table 13-8 (Cont.) OracleBFile Instance Properties

Properties	Description
IsOpen	Indicates whether the BFILE has been opened by this instance or not
Length	Indicates the size of the BFILE data in bytes
Position	Indicates the current read position in the LOB stream
Value	Returns the data, starting from the first byte in BFILE, as a byte array

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CanRead

Overrides `Stream`

This instance property indicates whether or not the LOB stream can be read.

Declaration

```
// C#  
public override bool CanRead{get;}
```

Property Value

If the LOB stream can be read, returns `true`; otherwise, returns `false`.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

Declaration

```
// C#  
public override bool CanWrite{get;}
```

Property Value

`BFILE` is read only.

Remarks

`BFILE` is read-only, therefore, the boolean value is always `false`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Connection

This instance property indicates the connection used to read from a `BFILE`.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An object of `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

DirectoryName

This instance property indicates the directory alias of the `BFILE`.

Declaration

```
// C#  
public string DirectoryName {get;set;}
```

Property Value

A string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The value of the `DirectoryName` changed while the `BFILE` is open.

Remarks

The maximum length of a `DirectoryName` is 30 bytes.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

FileExists

This instance property indicates whether or not the `BFILE` specified by the `DirectoryName` and `FileName` exists.

Declaration

```
// C#  
public bool FileExists {get;}
```

Property Value

bool

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Unless a connection, file name, and directory name are provided, this property is set to `false` by default.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

FileName

This instance property indicates the name of the `BFILE`.

Declaration

```
// C#  
public string FileName {get;set}
```

Property Value

A string that contains the BFILE name.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The value of the `DirectoryName` changed while the BFILE is open.

Remarks

The maximum length of a `FileName` is 255 bytes.

Changing the `FileName` property while the BFILE object is opened causes an exception.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsEmpty

This instance property indicates whether the BFILE is empty or not.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

bool

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsOpen

This instance property indicates whether the `BFILE` has been opened by this instance or not.

Declaration

```
// C#  
public bool IsOpen {get;}
```

Property Value

A `bool`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Length

Overrides `Stream`

This instance property indicates the size of the `BFILE` data in bytes.

Declaration

```
// C#  
public override Int64 Length {get;}
```

Property Value

Int64

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Position

Overrides Stream

This instance property indicates the current read position in the LOB stream.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An Int64 value that indicates the read position.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The value is less than 0.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Value

This instance property returns the data, starting from the first byte in `BFILE`, as a byte array.

Declaration

```
// C#  
public byte[] Value{get;}
```

Property Value

A byte array.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The length of data is bound by the maximum length of the byte array. The current value of the `Position` property is not used or changed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Instance Methods

`OracleBFile` instance methods are listed in [Table 13-9](#).

Table 13-9 OracleBFile Instance Methods

Methods	Description
BeginRead	Inherited from <code>System.IO.Stream</code>
BeginWrite	<i>Not Supported</i>
Clone	Creates a copy of an OracleBFile object
Close	Closes the current stream and releases any resources associated with the stream
CloseFile	Closes the BFILE referenced by the current BFILE instance
Compare	Compares data referenced by the two OracleBFiles
CreateObjRef	Inherited from <code>System.MarshalByRefObject</code>
CopyTo	Copies data as specified (Overloaded)
Dispose	Releases resources allocated by this object
EndRead	Inherited from <code>System.IO.Stream</code>
EndWrite	<i>Not Supported</i>
Equals	Inherited from <code>System.Object</code> (Overloaded)
Flush	<i>Not Supported</i>
FlushAsync	<i>Not Supported</i>
GetHashCode	Inherited from <code>System.Object</code>
GetLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
GetType	Inherited from <code>System.Object</code>
InitializeLifetimeService	Inherited from <code>System.MarshalByRefObject</code>
IsEqual	Compares the LOB references
OpenFile	Opens the BFILE specified by the <code>FileName</code> and <code>DirectoryName</code>
Read	Reads a specified amount of bytes from the OracleBFile instance and populates the buffer
ReadByte	Inherited from <code>System.IO.Stream</code>
Search	Searches for a binary pattern in the current instance of an OracleBFile
Seek	Sets the position on the current LOB stream
SetLength	<i>Not Supported</i>
ToString	Inherited from <code>System.Object</code>
Write	<i>Not Supported</i>
WriteByte	<i>Not Supported</i>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Clone

This instance method creates a copy of an `OracleBFile` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An `OracleBFile` object.

Implements

`ICloneable`

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// Database Setup, if you have not done so yet.  
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.  
  
CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';  
  
*/  
  
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class CloneSample  
{  
    static void Main()  
    {  
        // Create MYDIR directory object as indicated above and create a file
```



```
// MyFile.txt with the text ABCDABC under C:\TEMP directory.
// Note that the byte representation of the ABCDABC is 65666768656667

string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

OracleBFile bFile1 = new OracleBFile(con, "MYDIR", "MyFile.txt");

// Open the OracleBFile
bFile1.OpenFile();

// Prints "bFile1.Position = 0"
Console.WriteLine("bFile1.Position = " + bFile1.Position);

// Set the Position before calling Clone()
bFile1.Position = 1;

// Clone the OracleBFile
OracleBFile bFile2 = (OracleBFile) bFile1.Clone();

// Open the OracleBFile
bFile2.OpenFile();

// Prints "bFile2.Position = 1"
Console.WriteLine("bFile2.Position = " + bFile2.Position);

// Close the OracleBFile
bFile1.CloseFile();

bFile1.Close();
bFile1.Dispose();

// Close the Cloned OracleBFile
bFile2.CloseFile();

bFile2.Close();
bFile2.Dispose();

con.Close();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Close

Overrides Stream

This instance method closes the current stream and releases any resources associated with it.

Declaration

```
// C#  
public override void Close();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CloseFile

This instance method closes the `BFILE` referenced by the current `BFILE` instance.

Declaration

```
// C#  
public void CloseFile();
```

Remarks

No error is returned if the `BFILE` exists, but is not opened.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Compare

This instance method compares data referenced by the two `OracleBFiles`.

Declaration

```
// C#  
public int Compare(Int64 src_offset, OracleBFile obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- *src_offset*
The offset of the current instance.
- *obj*
The provided OracleBFile object.
- *dst_offset*
The offset of the OracleBFile object.
- *amount*
The number of bytes to compare.

Return Value

Returns a number that is:

- Less than zero: if the BFILE data of the current instance is less than that of the provided BFILE data.
- Zero: if both the BFILES store the same data.
- Greater than zero: if the BFILE data of the current instance is greater than that of the provided BFILE data.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The *src_offset*, the *dst_offset*, or the *amount* is less than 0.

Remarks

The provided object and the current instance must be using the same connection, that is, the same OracleConnection object.

The BFILE needs to be opened using `OpenFile` before the operation.

Example

```
// Database Setup, if you have not done so yet.  
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.  
  
CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';  
  
*/  
  
// C#
```

```
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CompareSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile1 = new OracleBFile(con, "MYDIR", "MyFile.txt");
        OracleBFile bFile2 = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFiles
        bFile1.OpenFile();
        bFile2.OpenFile();

        // Compare 2 bytes from the 1st byte of bFile1 and
        // the 5th byte of bFile2 onwards
        int result = bFile1.Compare(1, bFile2, 5, 2);

        // Prints "result = 0" (Indicates the data is identical)
        Console.WriteLine("result = " + result);

        // Close the OracleBFiles
        bFile1.CloseFile();
        bFile2.CloseFile();

        bFile1.Close();
        bFile1.Dispose();

        bFile2.Close();
        bFile2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo

`CopyTo` copies data from the current instance to the provided object.

Overload List:

- [CopyTo\(OracleBlob\)](#)
This instance method copies data from the current instance to the provided `OracleBlob` object.
- [CopyTo\(OracleBlob, Int64\)](#)
This instance method copies data from the current `OracleBFile` instance to the provided `OracleBlob` object with the specified destination offset.
- [CopyTo\(Int64, OracleBlob, Int64, Int64\)](#)
This instance method copies data from the current `OracleBFile` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.
- [CopyTo\(OracleClob\)](#)
This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object.
- [CopyTo\(OracleClob, Int64\)](#)
This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified destination offset.
- [CopyTo\(Int64, OracleClob, Int64, Int64\)](#)
This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified source offset, destination offset, and amount of characters.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleBlob)

This instance method copies data from the current instance to the provided `OracleBlob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj);
```

Parameters

- *obj*
The `OracleBlob` object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleBlob, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleBlob` object with the specified destination offset.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj, Int64 dst_offset);
```

Parameters

- *obj*
The `OracleBlob` object to which the data is copied.
- *dst_offset*
The offset (in bytes) at which the `OracleBlob` object is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The `dst_offset` is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the `dst_offset` is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(Int64, OracleBlob, Int64, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

Declaration

```
// C#  
public Int64 CopyTo(Int64 src_offset, OracleBlob obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- `src_offset`
The offset (in bytes) in the current instance, from which the data is read.
- `obj`

An `OracleBlob` object to which the data is copied.

- `dst_offset`

The offset (in bytes) to which the `OracleBlob` object is copied.

- `amount`

The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The `src_offset`, the `dst_offset`, or the `amount` is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the `dst_offset` is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleClob)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleClob obj);
```


Parameters

- *obj*
The `OracleClob` object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleClob, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified destination offset.

Declaration

```
// C#  
public Int64 CopyTo(OracleClob obj, Int64 dst_offset);
```

Parameters

- *obj*
The `OracleClob` object that the data is copied to.
- *dst_offset*
The offset (in characters) at which the `OracleClob` object is copied to.

Return Value

The amount copied.

Exceptions

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The `dst_offset` is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the `dst_offset` is beyond the end of the `OracleClob` data, spaces are written into the `OracleClob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(Int64, OracleClob, Int64, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified source offset, destination offset, and amount of characters.

Declaration

```
// C#
public Int64 CopyTo(Int64 src_offset, OracleClob obj, Int64 dst_offset,
    Int64 amount);
```

Parameters

- `src_offset`
The offset (in characters) in the current instance, from which the data is read.

- *obj*
An `OracleClob` object that the data is copied to.
- *dst_offset*
The offset (in characters) at which the `OracleClob` object is copied to.
- *amount*
The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *src_offset*, the *dst_offset*, or the *amount* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the *dst_offset* is beyond the end of the current `OracleClob` data, spaces are written into the `OracleClob` until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Dispose

This instance method releases resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls may lead to exceptions. The object cannot be reused after being disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Flush

This method is not supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

FlushAsync

This method is not supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsEqual

This instance method compares the LOB references.

Declaration

```
// C#  
public bool IsEqual(OracleBFile obj);
```

Parameters

- *obj*
The provided OracleBFile object.

Return Value

Returns `true` if the current OracleBFile and the provided OracleBFile object refer to the same external LOB. Returns `false` otherwise.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

Note that this method can return `true` even if the two OracleBFile objects return `false` for `==` or `Equals()` since two different OracleBFile instances can refer to the same external LOB.

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OpenFile

This instance method opens the BFILE specified by the FileName and DirectoryName.

Declaration

```
// C#  
public void OpenFile();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Many operations, such as `Compare()`, `CopyTo()`, `Read()`, and `Search()` require that the `BFILE` be opened using `OpenFile` before the operation.

Calling `OpenFile` on an opened `BFILE` is not operational.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Read

Overrides `Stream`

This instance method reads a specified amount of bytes from the `OracleBFile` instance and populates the `buffer`.

Declaration

```
// C#  
public override int Read(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer to be populated.
- *offset*
The offset of the byte array buffer to be populated.
- *count*
The amount of bytes to read.

Return Value

The return value indicates the number of bytes read from the `BFILE`, that is, the external LOB.

Exceptions

`ObjectDisposedException` - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - Either the *offset* or the *count* parameter is less than 0 or the *offset* is greater than or equal to the *buffer.Length* or the *offset* and the *count* together are greater than *buffer.Length*.

Remarks

The LOB data is read starting from the position specified by the `Position` property.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ReadSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Read 7 bytes into readBuffer, starting at buffer offset 0
        byte[] readBuffer = new byte[7];
        int bytesRead = bFile.Read(readBuffer, 0, 7);

        // Prints "bytesRead = 7"
        Console.WriteLine("bytesRead = " + bytesRead);

        // Prints "readBuffer = 65666768656667"
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        // Close the OracleBFile
        bFile.CloseFile();
    }
}
```

```
bFile.Close();  
bFile.Dispose();  
  
con.Close();  
con.Dispose();  
}  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Search

This instance method searches for a binary pattern in the current instance of an `OracleBFile`.

Declaration

```
// C#  
public int Search(byte[] val, Int64 offset, Int64 nth);
```

Parameters

- *val*
The binary pattern being searched for.
- *offset*
The 0-based offset (in bytes) starting from which the `OracleBFile` is searched.
- *nth*
The specific occurrence (1-based) of the match for which the offset is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - Either the *offset* is less than 0 or *nth* is less than or equal to 0 or *val.Length* is greater than 16383 or *nth* is greater than or equal to `OracleBFile.MaxValue` or *offset* is greater than or equal to `OracleBFile.MaxValue`.

Remarks

The limit of the search pattern is 16383 bytes.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Search for the 2nd occurrence of a byte pattern {66,67}
        // starting from byte offset 1 in the OracleBFile
        byte[] pattern = new byte[2] {66, 67};
        long posFound = bFile.Search(pattern, 1, 2);

        // Prints "posFound = 6"
        Console.WriteLine("posFound = " + posFound);

        // Close the OracleBFile
        bFile.CloseFile();

        bFile.Close();
        bFile.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Seek

Overrides `Stream`

This instance method sets the position on the current LOB stream.

Declaration

```
// C#  
public override Int64 Seek(Int64 offset, SeekOrigin origin);
```

Parameters

- *offset*
A byte offset relative to origin.
- *origin*
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

Returns an `Int64` that indicates the position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

`SeekOrigin.Current` specifies the current position within a stream.

`SeekOrigin.End` specifies the end of a stream.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using System.IO;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SeekSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Set the Position to 2 with respect to SeekOrigin.Begin
        long newPosition = bFile.Seek(2, SeekOrigin.Begin);

        // Prints "newPosition      = 2"
        Console.WriteLine("newPosition      = " + newPosition);

        // Prints "bFile.Position = 2"
        Console.WriteLine("bFile.Position = " + bFile.Position);

        // Read 2 bytes into readBuffer, starting at buffer offset 1
        byte[] readBuffer = new byte[4];
        int bytesRead = bFile.Read(readBuffer, 1, 2);

        // Prints "bytesRead      = 2"
        Console.WriteLine("bytesRead      = " + bytesRead);

        // Prints "readBuffer      = 067680"
        Console.Write("readBuffer      = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        // Close the OracleBFile
        bFile.CloseFile();
    }
}
```

```
bFile.Close();  
bFile.Dispose();  
  
con.Close();  
con.Dispose();  
}  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

SetLength

This method is not supported.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Write

This method is not supported.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBlob Class

An `OracleBlob` object is an object that has a reference to BLOB data. It provides methods for performing operations on BLOBs.

Class Inheritance

System.Object

System.MarshalByRefObject

System.IO.Stream

Oracle.DataAccess.Types.OracleBlob

Declaration

```
// C#
public sealed class OracleBlob : Stream, ICloneable, INullable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleBlobSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 4 bytes from writeBuffer, starting at buffer offset 0
        byte[] writeBuffer = new byte[4] {1, 2, 3, 4};
        blob.Write(writeBuffer, 0, 4);

        // Append first 2 bytes from writeBuffer {1, 2} to the oracleBlob
        blob.Append(writeBuffer, 0, 2);

        // Prints "blob.Length = 6"
```

```
Console.WriteLine("blob.Length = " + blob.Length);

// Reset the Position for the Read
blob.Position = 0;

// Read 6 bytes into readBuffer, starting at buffer offset 0
byte[] readBuffer = new byte[6];
int bytesRead = blob.Read(readBuffer, 0, 6);

// Prints "bytesRead = 6"
Console.WriteLine("bytesRead = " + bytesRead);

// Prints "readBuffer = 123412"
Console.Write("readBuffer = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Search for the 2nd occurrence of a byte pattern '12'
// starting from byte offset 0 in the OracleBlob
byte[] pattern = new byte[2] {1, 2};
long posFound = blob.Search(pattern, 0, 2);

// Prints "posFound = 5"
Console.WriteLine("posFound = " + posFound);

// Erase 4 bytes of data starting at byte offset 1
// Sets bytes to zero
blob.Erase(1, 4);

byte[] erasedBuffer = blob.Value;

//Prints "erasedBuffer = 100002"
Console.Write("erasedBuffer = ");
for(int index = 0; index < erasedBuffer.Length; index++)
{
    Console.Write(erasedBuffer[index]);
}
Console.WriteLine();

blob.Close();
blob.Dispose();

con.Close();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Members](#)
- [OracleBlob Constructors](#)
- [OracleBlob Static Fields](#)
- [OracleBlob Static Methods](#)
- [OracleBlob Instance Properties](#)
- [OracleBlob Instance Methods](#)

OracleBlob Members

OracleBlob members are listed in the following tables.

OracleBlob Constructors

OracleBlob constructors are listed in [Table 13-10](#).

Table 13-10 OracleBlob Constructors

Constructor	Description
OracleBlob Constructors	Creates an instance of the OracleBlob class (Overloaded)

OracleBlob Static Fields

OracleBlob static fields are listed in [Table 13-11](#).

Table 13-11 OracleBlob Static Fields

Field	Description
MaxSize	Holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 (2 ³² - 1) bytes
Null	Represents a null value that can be assigned to the value of an OracleBlob instance

OracleBlob Static Methods

OracleBlob static methods are listed in [Table 13-12](#).

Table 13-12 OracleBlob Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleBlob Instance Properties

OracleBlob instance properties are listed in [Table 13-13](#).

Table 13-13 OracleBlob Instance Properties

Properties	Description
CanRead	Indicates whether or not the LOB stream can be read
CanSeek	Indicates whether or not forward and backward seek operations be performed
CanWrite	Indicates whether or not the LOB object supports writing
Connection	Indicates the <code>OracleConnection</code> that is used to retrieve and write BLOB data
IsEmpty	Indicates whether the BLOB is empty or not
IsInChunkWriteMode	Indicates whether or not the BLOB has been opened to defer index updates
IsNull	Indicates whether or not the current instance has a null value
IsTemporary	Indicates whether or not the current instance is bound to a temporary BLOB
Length	Indicates the size of the BLOB data
OptimumChunkSize	Indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance
Position	Indicates the current read or write position in the LOB stream
Value	Returns the data, starting from the first byte in BLOB, as a byte array

OracleBlob Instance Methods

OracleBlob instance methods are listed in [Table 13-14](#).

Table 13-14 OracleBlob Instance Methods

Methods	Description
Append	Appends the supplied data to the current OracleBlob instance (Overloaded)
BeginChunkWrite	Opens the BLOB
BeginRead	Inherited from <code>System.IO.Stream</code>
BeginWrite	Inherited from <code>System.IO.Stream</code>
Clone	Creates a copy of an OracleBlob object
Close	Closes the current stream and releases any resources associated with it

Table 13-14 (Cont.) OracleBlob Instance Methods

Methods	Description
Compare	Compares data referenced by the current instance and that of the supplied object
CopyTo	Copies from the current OracleBlob instance to an OracleBlob object (Overloaded)
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Releases resources allocated by this object
EndChunkWrite	Closes the BLOB referenced by the current OracleBlob instance
EndRead	Inherited from System.IO.Stream
EndWrite	Inherited from System.IO.Stream
Equals	Inherited from System.Object (Overloaded)
Erase	Erases data (Overloaded)
Flush	<i>Not supported</i>
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializedLifetimeService	Inherited from System.MarshalByRefObject
IsEqual	Compares the LOB data referenced by the two OracleBlobs
Read	Reads a specified amount of bytes from the ODP.NET LOB Type instance and populates the buffer
ReadByte	Inherited from System.IO.Stream
Search	Searches for a binary pattern in the current instance of an OracleBlob
Seek	Sets the position in the current LOB stream
SetLength	Trims or truncates the BLOB value to the specified length
ToString	Inherited from System.Object
Write	Writes the supplied buffer into the OracleBlob
WriteByte	Inherited from System.IO.Stream

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Members](#)

OracleBlob Constructors

OracleBlob constructors are listed in [Table 13-10](#).

Overload List:

- [OracleBlob\(OracleConnection\)](#)
This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object.
- [OracleBlob\(OracleConnection, bool\)](#)
This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object and a boolean value for caching.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob(OracleConnection)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object.

Declaration

```
// C#  
public OracleBlob(OracleConnection con);
```

Parameters

- *con*
The OracleConnection object.

Exceptions

InvalidOperationException - The OracleConnection is not opened.

Remarks

The connection must be opened explicitly by the application. OracleBlob does not open the connection implicitly.

The temporary BLOB utilizes the provided connection to store BLOB data. Caching is not turned on by this constructor.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob(OracleConnection, bool)

This constructor creates an instance of the `OracleBlob` class bound to a temporary BLOB with an `OracleConnection` object and a boolean value for caching.

Declaration

```
// C#  
public OracleBlob(OracleConnection con, bool bCaching);
```

Parameters

- `con`
The `OracleConnection` object.
- `bCaching`
A flag for enabling or disabling server-side caching.

Exceptions

`InvalidOperationException` - The `OracleConnection` is not opened.

Remarks

The connection must be opened explicitly by the application. `OracleBlob` does not open the connection implicitly.

The temporary BLOB uses the provided connection to store BLOB data. The `bCaching` input parameter determines whether or not server-side caching is used.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Static Fields

`OracleBlob` static fields are listed in [Table 13-15](#).

Table 13-15 OracleBlob Static Fields

Field	Description
MaxSize	Holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes
Null	Represents a null value that can be assigned to the value of an <code>OracleBlob</code> instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

MaxSize

The `MaxSize` field holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes.

Declaration

```
// C#  
public static readonly Int64 MaxSize = 4294967295;
```

Remarks

This field can be useful in code that checks whether or not the operation exceeds the maximum length allowed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Null

This static field represents a null value that can be assigned to the value of an `OracleBlob` instance.

Declaration

```
// C#
public static readonly OracleBlob Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Static Methods

OracleBlob static methods are listed in [Table 13-16](#).

Table 13-16 OracleBlob Static Methods

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Instance Properties

OracleBlob instance properties are listed in [Table 13-17](#).

Table 13-17 OracleBlob Instance Properties

Properties	Description
CanRead	Indicates whether or not the LOB stream can be read
CanSeek	Indicates whether or not forward and backward seek operations be performed
CanWrite	Indicates whether or not the LOB object supports writing
Connection	Indicates the <code>OracleConnection</code> that is used to retrieve and write BLOB data

Table 13-17 (Cont.) OracleBlob Instance Properties

Properties	Description
IsEmpty	Indicates whether the BLOB is empty or not
IsInChunkWriteMode	Indicates whether or not the BLOB has been opened to defer index updates
IsNull	Indicates whether or not the current instance has a null value
IsTemporary	Indicates whether or not the current instance is bound to a temporary BLOB
Length	Indicates the size of the BLOB data
OptimumChunkSize	Indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance
Position	Indicates the current read or write position in the LOB stream
Value	Returns the data, starting from the first byte in BLOB, as a byte array

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CanRead

Overrides `Stream`

This instance property indicates whether or not the LOB stream can be read.

Declaration

```
// C#  
public override bool CanRead{get;}
```

Property Value

If the LOB stream can be read, returns `true`; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

Declaration

```
// C#  
public override bool CanWrite{get;}
```

Property Value

If the LOB stream can be written, returns `true`; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Connection

This instance property indicates the `OracleConnection` that is used to retrieve and write BLOB data.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An object of `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsEmpty

This instance property indicates whether the BLOB is empty or not.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

A `bool` that indicates whether or not the BLOB is empty.

Exceptions

`ObjectDisposedException` - The object is already disposed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsInChunkWriteMode

This instance property indicates whether or not the BLOB has been opened to defer index updates.

Declaration

```
// C#  
public bool IsInChunkWriteMode{get;}
```

Property Value

If the BLOB has been opened, returns `true`; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsTemporary

This instance property indicates whether or not the current instance is bound to a temporary BLOB.

Declaration

```
// C#  
public bool IsTemporary {get;}
```

Property Value

bool

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Length

Overrides [Stream](#)

This instance property indicates the size of the BLOB data in bytes.

Declaration

```
// C#  
public override Int64 Length {get;}
```

Property Value

A number indicating the size of the BLOB data in bytes.

Exceptions

[ObjectDisposedException](#) - The object is already disposed.

[InvalidOperationException](#) - The [OracleConnection](#) is not open or has been closed during the lifetime of the object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OptimumChunkSize

This instance property indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance.

Declaration

```
// C#  
public int OptimumChunkSize{get;}
```

Property Value

A number representing the minimum bytes to retrieve or send.

Exceptions

`ObjectDisposedException` - The object is already disposed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Position

Overrides `Stream`

This instance property indicates the current read or write position in the LOB stream.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An `Int64` that indicates the read or write position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Position` is less than 0.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Value

This instance property returns the data, starting from the first byte in the BLOB, as a byte array.

Declaration

```
// C#  
public Byte[] Value{get;}
```

Property Value

A byte array.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Value` is less than 0.

Remarks

The value of `Position` is not used or changed by using this property. 2 GB is the maximum byte array length that can be returned by this property.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Instance Methods

OracleBlob instance methods are listed in [Table 13-18](#).

Table 13-18 OracleBlob Instance Methods

Methods	Description
Append	Appends the supplied data to the current OracleBlob instance (Overloaded)
BeginChunkWrite	Opens the BLOB
BeginRead	Inherited from System.IO.Stream
BeginWrite	Inherited from System.IO.Stream
Clone	Creates a copy of an OracleBlob object
Close	Closes the current stream and releases any resources associated with it
Compare	Compares data referenced by the current instance and that of the supplied object
CopyTo	Copies from the current OracleBlob instance to an OracleBlob object (Overloaded)
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Releases resources allocated by this object
EndChunkWrite	Closes the BLOB referenced by the current OracleBlob instance
EndRead	Inherited from System.IO.Stream
EndWrite	Inherited from System.IO.Stream
Equals	Inherited from System.Object (Overloaded)
Erase	Erases data (Overloaded)
Flush	<i>Not supported</i>
GetHashCode	Inherited from System.Object
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializedLifetimeService	Inherited from System.MarshalByRefObject
IsEqual	Compares the LOB data referenced by the two OracleBlobs

Table 13-18 (Cont.) OracleBlob Instance Methods

Methods	Description
Read	Reads a specified amount of bytes from the ODP.NET LOB Type instance and populates the buffer
ReadByte	Inherited from <code>System.IO.Stream</code>
Search	Searches for a binary pattern in the current instance of an OracleBlob
Seek	Sets the position in the current LOB stream
SetLength	Trims or truncates the BLOB value to the specified length
ToString	Inherited from <code>System.Object</code>
Write	Writes the supplied buffer into the OracleBlob
WriteByte	Inherited from <code>System.IO.Stream</code>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Append

Append appends the supplied data to the end of the current OracleBlob instance.

Overload List:

- [Append\(OracleBlob\)](#)
This instance method appends the BLOB data referenced by the provided OracleBlob object to the current OracleBlob instance.
- [Append\(byte\[\], int, int\)](#)
This instance method appends data from the supplied byte array buffer to the end of the current OracleBlob instance.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Append(OracleBlob)

This instance method appends the BLOB data referenced by the provided `OracleBlob` object to the current `OracleBlob` instance.

Declaration

```
// C#  
public void Append(OracleBlob obj);
```

Parameters

- *obj*
An object of `OracleBlob`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

Remarks

No character set conversions are made.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Append(byte[], int, int)

This instance method appends data from the supplied byte array buffer to the end of the current `OracleBlob` instance.

Declaration

```
// C#  
public void Append(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
An array of bytes.
- *offset*

The zero-based byte offset in the buffer from which data is read.

- *count*

The number of bytes to be appended.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class AppendSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Append 2 bytes {4, 5} to the OracleBlob
        byte[] buffer = new byte[3] {4, 5, 6};
        blob.Append(buffer, 0, 2);

        byte[] appendBuffer = blob.Value;

        // Prints "appendBuffer = 45"
        Console.Write("appendBuffer = ");
        for(int index = 0; index < appendBuffer.Length; index++)
        {
            Console.Write(appendBuffer[index]);
        }
        Console.WriteLine();

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```


 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

BeginChunkWrite

This instance method opens the BLOB.

Declaration

```
// C#  
public void BeginChunkWrite();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

`BeginChunkWrite` does not need to be called before manipulating the BLOB data. This is provided for performance reasons.

After this method is called, write operations do not cause the domain or function-based index on the column to be updated. Index updates occur only once after `EndChunkWrite` is called.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Clone

This instance method creates a copy of an `OracleBlob` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleBlob object.

Implements

ICloneable

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class CloneSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleBlob blob1 = new OracleBlob(con);  
  
        // Prints "blob1.Position = 0"  
        Console.WriteLine("blob1.Position = " + blob1.Position);  
  
        // Set the Position before calling Clone()  
        blob1.Position = 1;  
  
        // Clone the OracleBlob  
        OracleBlob blob2 = (OracleBlob)blob1.Clone();  
  
        // Prints "blob2.Position = 1"  
        Console.WriteLine("blob2.Position = " + blob2.Position);  
  
        blob1.Close();  
        blob1.Dispose();  
  
        blob2.Close();  
        blob2.Dispose();  
  
        con.Close();  
        con.Dispose();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Close

Overrides `Stream`

This instance method closes the current stream and releases any resources associated with it.

Declaration

```
// C#  
public override void Close();
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Compare

This instance method compares data referenced by the current instance and that of the supplied object.

Declaration

```
// C#  
public int Compare(Int64 src_offset, OracleBlob obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- *src_offset*
The comparison starting point (in bytes) for the current instance.
- *obj*
The provided `OracleBlob` object.
- *dst_offset*
The comparison starting point (in bytes) for the provided `OracleBlob`.

- *amount*
The number of bytes to compare.

Return Value

Returns a value that is:

- Less than zero: if the data referenced by the current instance is less than that of the supplied instance
- Zero: if both objects reference the same data
- Greater than zero: if the data referenced by the current instance is greater than that of the supplied instance

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The *src_offset*, the *dst_offset*, or the *amount* parameter is less than 0.

Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo

`CopyTo` copies data from the current instance to the provided `OracleBlob` object.

Overload List:

- [CopyTo\(OracleBlob\)](#)
This instance method copies data from the current instance to the provided `OracleBlob` object.
- [CopyTo\(OracleBlob, Int64\)](#)
This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified destination offset.
- [CopyTo\(Int64, OracleBlob, Int64, Int64\)](#)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo(OracleBlob)

This instance method copies data from the current instance to the provided `OracleBlob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj);
```

Parameters

- *obj*
The `OracleBlob` object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo(OracleBlob, Int64)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified destination offset.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj, Int64 dst_offset);
```

Parameters

- *obj*
The `OracleBlob` object to which the data is copied.
- *dst_offset*
The offset (in bytes) at which the `OracleBlob` object is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *dst_offset* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the *dst_offset* is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo(Int64, OracleBlob, Int64, Int64)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

Declaration

```
// C#  
public Int64 CopyTo(Int64 src_offset, OracleBlob obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- *src_offset*
The offset (in bytes) in the current instance, from which the data is read.
- *obj*
The `OracleBlob` object to which the data is copied.
- *dst_offset*
The offset (in bytes) at which the `OracleBlob` object is copied.
- *amount*
The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The *src_offset*, the *dst_offset*, or the *amount* parameter is less than 0.

Remarks

If the *dst_offset* is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CopyToSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob1 = new OracleBlob(con);
        OracleBlob blob2 = new OracleBlob(con);

        // Write 4 bytes, starting at buffer offset 0
        byte[] buffer = new byte[4] {1, 2, 3, 4};
        blob1.Write(buffer, 0, 4);

        // Copy 2 bytes from byte 0 of blob1 to byte 1 of blob2
        blob1.CopyTo(0, blob2, 1, 2);

        byte[] copyBuffer = blob2.Value;

        //Prints "Value = 012"
        Console.Write("Value = ");
        for(int index = 0; index < copyBuffer.Length; index++)
        {
            Console.Write(copyBuffer[index]);
        }
        Console.WriteLine();

        blob1.Close();
        blob1.Dispose();

        blob2.Close();
        blob2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Dispose

This instance method releases resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

Once `Dispose()` is called, the object of `OracleBlob` is in an uninitialized state.

Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls may lead to exceptions. The object cannot be reused after being disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

EndChunkWrite

This instance method closes the BLOB referenced by the current `OracleBlob` instance.

Declaration

```
// C#  
public void EndChunkWrite();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Index updates occur immediately if there is write operation(s) deferred by the `BeginChunkWrite` method.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Erase

Erase erases a portion or all data.

Overload List:

- [Erase\(\)](#)
This instance method erases all data.
- [Erase\(Int64, Int64\)](#)
This instance method erases a specified portion of data.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Erase()

This instance method erases all data.

Declaration

```
// C#  
public Int64 Erase();
```

Return Value

The number of bytes erased.

Remarks

Erase() replaces all data with zero-byte fillers.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Erase(Int64, Int64)

This instance method erases a specified portion of data.

Declaration

```
// C#  
public Int64 Erase(Int64 offset, Int64 amount);
```

Parameters

- *offset*
The offset from which to erase.
- *amount*
The quantity (in bytes) to erase.

Return Value

The number of bytes erased.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The *OracleConnection* is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The *offset* or *amount* parameter is less than 0.

Remarks

Replaces the specified *amount* of data with zero-byte fillers.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Flush

This method is not supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsEqual

This instance method compares the LOB data referenced by the two `OracleBlobs`.

Declaration

```
// C#  
public bool IsEqual(OracleBlob obj);
```

Parameters

- *obj*
An `OracleBlob` object.

Return Value

If the current `OracleBlob` and the provided `OracleBlob` refer to the same LOB, returns `true`. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Note that this method can return `true` even if the two `OracleBlob` objects return `false` for `==` or `Equals()` because two different `OracleBlob` instances can refer to the same LOB.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Read

Overrides `Stream`

This instance method reads a specified amount of bytes from the ODP.NET LOB instance and populates the `buffer`.

Declaration

```
// C#  
public override int Read(byte[] buffer, int offset, int count);
```

Parameters

- `buffer`
The byte array buffer to be populated.
- `offset`
The starting offset (in bytes) at which the buffer is populated.
- `count`
The amount of bytes to read.

Return Value

The return value indicates the number of bytes read from the LOB.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The `offset` or the `count` parameter is less than 0.
- The `offset` is greater than or equal to the `buffer.Length`.
- The `offset` and the `count` together are greater than the `buffer.Length`.

Remarks

The LOB data is read starting from the position specified by the `Position` property.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ReadSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 3 bytes, starting at buffer offset 1
        byte[] writeBuffer = new byte[4] {1, 2, 3, 4};
        blob.Write(writeBuffer, 1, 3);

        // Reset the Position for Read
        blob.Position = 1;

        // Read 2 bytes into buffer starting at buffer offset 1
        byte[] readBuffer = new byte[4];
        int bytesRead = blob.Read(readBuffer, 1, 2);

        // Prints "bytesRead = 2"
        Console.WriteLine("bytesRead = " + bytesRead);

        // Prints "readBuffer = 0340"
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Search

This instance method searches for a binary pattern in the current instance of an OracleBlob.

Declaration

```
// C#  
public Int64 Search(byte[] val, int64 offset, int64 nth);
```

Parameters

- *val*
The binary pattern being searched for.
- *offset*
The 0-based offset (in bytes) starting from which the OracleBlob is searched.
- *nth*
The specific occurrence (1-based) of the match for which the absolute offset (in bytes) is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *val.Length* is greater than 16383.
- The *nth* is greater than or equal to OracleBlob.MaxSize.
- The *offset* is greater than or equal to OracleBlob.MaxSize.

Remarks

The limit of the search pattern is 16383 bytes.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;
```

```
class SearchSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 7 bytes, starting at buffer offset 0
        byte[] buffer = new byte[7] {1, 2, 3, 4, 1, 2, 3};
        blob.Write(buffer, 0, 7);

        // Search for the 2nd occurrence of a byte pattern '23'
        // starting at offset 1 in the OracleBlob
        byte[] pattern = new byte[2] {2, 3};
        long posFound = blob.Search(pattern, 1, 2);

        // Prints "posFound = 6"
        Console.WriteLine("posFound = " + posFound);

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Seek

Overrides Stream

This instance method sets the position on the current LOB stream.

Declaration

```
// C#
public override Int64 Seek(Int64 offset, SeekOrigin origin);
```

Parameters

- *offset*
A byte offset relative to origin.
- *origin*

A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

Returns `Int64` for the position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

`SeekOrigin.Current` specifies the current position within a stream.

`SeekOrigin.End` specifies the end of a stream.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

SetLength

Overrides `Stream`

This instance method trims or truncates the BLOB value to the specified length (in bytes).

Declaration

```
// C#  
public override void SetLength(Int64 newLen);
```

Parameters

- *newLen*

The desired length of the current stream in bytes.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `newLen` parameter is less than 0.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Write

Overrides `Stream`

This instance method writes the supplied buffer into the `OracleBlob`.

Declaration

```
// C#  
public override void Write(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array `buffer` that provides the data.
- *offset*
The 0-based offset (in bytes) from which the `buffer` is read.
- *count*
The amount of data (in bytes) that is to be written into the `OracleBlob`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the `buffer.Length`.
- The *offset* and the *count* together are greater than `buffer.Length`.

Remarks

Destination *offset* in the OracleBlob can be specified by the `Position` property.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class WriteSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Set the Position for the Write
        blob.Position = 0;

        // Begin ChunkWrite to improve performance
        // Index updates occur only once after EndChunkWrite
        blob.BeginChunkWrite();

        // Write to the OracleBlob in 5 chunks of 2 bytes each
        byte[] b = new byte[2] {1, 2};
        for(int index = 0; index < 5; index++)
        {
            blob.Write(b, 0, b.Length);
        }
        blob.EndChunkWrite();

        byte[] chunkBuffer = blob.Value;

        // Prints "chunkBuffer = 1212121212"
        Console.Write("chunkBuffer = ");
        for(int index = 0; index < chunkBuffer.Length; index++)
        {
            Console.Write(chunkBuffer[index]);
        }
        Console.WriteLine();

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleClob Class

An `OracleClob` is an object that has a reference to `CLOB` data. It provides methods for performing operations on `CLOB`s.

 **Note:**

The `OracleClob` object uses the client side character set when retrieving or writing `CLOB` data using a .NET Framework byte array.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.IO.Stream`

`Oracle.DataAccess.Types.OracleClob`

Declaration

```
// C#
public sealed class OracleClob : Stream, ICloneable, INullable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleClobSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 4 chars from writeBuffer, starting at buffer offset 0
        char[] writeBuffer = new char[4] {'a', 'b', 'c', 'd'};
        clob.Write(writeBuffer, 0, 4);

        // Append first 2 chars from writeBuffer {'a', 'b'} to the oracleClob
        clob.Append(writeBuffer, 0, 2);

        // Prints "clob.Length = 12"
        Console.WriteLine("clob.Length = " + clob.Length);

        // Reset the Position for the Read
        clob.Position = 0;

        // Read 6 chars into readBuffer, starting at buffer offset 0
        char[] readBuffer = new char[6];
        int charsRead = clob.Read(readBuffer, 0, 6);

        // Prints "charsRead = 6"
        Console.WriteLine("charsRead = " + charsRead);

        // Prints "readBuffer = abcdab"
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        // Search for the 2nd occurrence of a char pattern 'ab'
        // starting from char offset 0 in the OracleClob
        char[] pattern = new char[2] {'a', 'b'};
        long posFound = clob.Search(pattern, 0, 2);

        // Prints "posFound = 5"
        Console.WriteLine("posFound = " + posFound);

        // Erase 4 chars of data starting at char offset 1
        // Sets chars to ''
        clob.Erase(1, 4);

        //Prints "clob.Value = a b"
        Console.WriteLine("clob.Value = " + clob.Value);
    }
}
```

```

clob.Close();
clob.Dispose();

con.Close();
con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Members](#)
- [OracleClob Constructors](#)
- [OracleClob Static Fields](#)
- [OracleClob Static Methods](#)
- [OracleClob Instance Properties](#)
- [OracleClob Instance Methods](#)

OracleClob Members

OracleClob members are listed in the following tables.

OracleClob Constructors

OracleClob constructors are listed in [Table 13-19](#).

Table 13-19 OracleClob Constructors

Constructor	Description
OracleClob Constructors	Creates an instance of the OracleClob class bound to a temporary CLOB (Overloaded)

OracleClob Static Fields

OracleClob static fields are listed in [Table 13-20](#).

Table 13-20 OracleClob Static Fields

Field	Description
MaxSize	Holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2 ³² - 1) bytes
Null	Represents a null value that can be assigned to the value of an OracleClob instance

OracleClob Static Methods

OracleClob static methods are listed in [Table 13-21](#).

Table 13-21 OracleClob Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleClob Instance Properties

OracleClob instance properties are listed in [Table 13-22](#).

Table 13-22 OracleClob Instance Properties

Properties	Description
CanRead	Indicates whether or not the LOB stream can be read
CanSeek	Indicates whether or not forward and backward seek operations can be performed
CanWrite	Indicates whether or not the LOB stream can be written
Connection	Indicates the <code>OracleConnection</code> that is used to retrieve and write CLOB data
IsEmpty	Indicates whether the CLOB is empty or not
IsInChunkWriteMode	Indicates whether or not the CLOB has been opened
IsNClob	Indicates whether or not the <code>OracleClob</code> object represents an NCLOB.
IsNull	Indicates whether or not the current instance has a null value
IsTemporary	Indicates whether or not the current instance is bound to a temporary CLOB
Length	Indicates the size of the CLOB data in bytes
OptimumChunkSize	Indicates the minimum number of bytes to retrieve or send from the database during a read or write operation
Position	Indicates the current read or write position in the LOB stream in bytes
Value	Returns the data, starting from the first character in the CLOB or NCLOB, as a string

OracleClob Instance Methods

The `OracleClob` instance methods are listed in [Table 13-23](#).

Table 13-23 OracleClob Instance Methods

Methods	Description
Append	Appends data to the current OracleClob instance (Overloaded)
BeginChunkWrite	Opens the CLOB
BeginRead	Inherited from System.IO.Stream
BeginWrite	Inherited from System.IO.Stream
Clone	Creates a copy of an OracleClob object
Close	Closes the current stream and releases resources associated with it
Compare	Compares data referenced by the current instance to that of the supplied object
CopyTo	Copies the data to an OracleClob (Overloaded)
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Releases resources allocated by this object
EndChunkWrite	Closes the CLOB referenced by the current OracleClob instance
EndRead	Inherited from System.IO.Stream
EndWrite	Inherited from System.IO.Stream
Equals	Inherited from System.Object (Overloaded)
Erase	Erases the specified amount of data (Overloaded)
Flush	<i>Not supported</i>
GetHashCode	Returns a hash code for the current instance
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
IsEqual	Compares the LOB data referenced by two OracleClobs
Read	Reads from the current instance (Overloaded)
ReadByte	Inherited from System.IO.Stream
Search	Searches for a character pattern in the current instance of OracleClob (Overloaded)
Seek	Sets the position in the current LOB stream
SetLength	Trims or truncates the CLOB value
ToString	Inherited from System.Object
Write	Writes the provided buffer into the OracleClob (Overloaded)
WriteByte	Inherited from System.IO.Stream

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)

OracleClob Constructors

`OracleClob` constructors create instances of the `OracleClob` class bound to a temporary `CLOB`.

Overload List:

- [OracleClob\(OracleConnection\)](#)
This constructor creates an instance of the `OracleClob` class bound to a temporary `CLOB` with an `OracleConnection` object.
- [OracleClob\(OracleConnection, bool, bool\)](#)
This constructor creates an instance of the `OracleClob` class that is bound to a temporary `CLOB`, with an `OracleConnection` object, a boolean value for caching, and a boolean value for `NCLOB`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob(OracleConnection)

This constructor creates an instance of the `OracleClob` class bound to a temporary `CLOB` with an `OracleConnection` object.

Declaration

```
// C#  
public OracleClob(OracleConnection con);
```

Parameters

- `con`
The `OracleConnection` object.

Exceptions

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The connection must be opened explicitly by the application. `OracleClob` does not open the connection implicitly. The temporary `CLOB` utilizes the provided connection to store `CLOB` data. Caching is not enabled by default.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob(OracleConnection, bool, bool)

This constructor creates an instance of the `OracleClob` class that is bound to a temporary `CLOB`, with an `OracleConnection` object, a boolean value for caching, and a boolean value for `NCLOB`.

Declaration

```
// C#  
public OracleClob(OracleConnection con, bool bCaching, bool bNCLOB);
```

Parameters

- `con`
The `OracleConnection` object connection.
- `bCaching`
A flag that indicates whether or not server-side caching is enabled.
- `bNCLOB`
A flag that is set to `true` if the instance is a `NCLOB` or `false` if it is a `CLOB`.

Exceptions

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The connection must be opened explicitly by the application. `OracleClob` does not open the connection implicitly. The temporary `CLOB` or `NCLOB` uses the provided connection to store `CLOB` data.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Static Fields

OracleClob static fields are listed in [Table 13-24](#).

Table 13-24 OracleClob Static Fields

Field	Description
MaxSize	Holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2 ³² - 1) bytes
Null	Represents a null value that can be assigned to the value of an OracleClob instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

MaxSize

The `MaxSize` field holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2³² - 1) bytes.

Declaration

```
// C#  
public static readonly Int64 MaxSize = 4294967295;
```

Remarks

This field is useful in code that checks whether or not your operation exceeds the maximum length (in bytes) allowed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Null

This static field represents a null value that can be assigned to the value of an OracleClob instance.

Declaration

```
// C#  
public static readonly OracleClob Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Static Methods

OracleClob static methods are listed in [Table 13-25](#).

Table 13-25 OracleClob Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Instance Properties

OracleClob instance properties are listed in [Table 13-26](#).

Table 13-26 OracleClob Instance Properties

Properties	Description
CanRead	Indicates whether or not the LOB stream can be read
CanSeek	Indicates whether or not forward and backward seek operations can be performed
CanWrite	Indicates whether or not the LOB stream can be written
Connection	Indicates the <code>OracleConnection</code> that is used to retrieve and write CLOB data
IsEmpty	Indicates whether the CLOB is empty or not
IsInChunkWriteMode	Indicates whether or not the CLOB has been opened
IsNClob	Indicates whether or not the <code>OracleClob</code> object represents an NCLOB.
IsNull	Indicates whether or not the current instance has a null value
IsTemporary	Indicates whether or not the current instance is bound to a temporary CLOB
Length	Indicates the size of the CLOB data in bytes
OptimumChunkSize	Indicates the minimum number of bytes to retrieve or send from the database during a read or write operation
Position	Indicates the current read or write position in the LOB stream in bytes
Value	Returns the data, starting from the first character in the CLOB or NCLOB, as a string

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CanRead

Overrides `Stream`

This instance property indicates whether or not the LOB stream can be read.

Declaration

```
// C#  
public override bool CanRead{get;}
```

Property Value

If the LOB stream can be read, returns `true`; otherwise, returns `false`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

Declaration

```
// C#  
public override bool CanWrite{get;}
```

Property Value

If the LOB stream can be written, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Connection

This instance property indicates the `OracleConnection` that is used to retrieve and write `CLOB` data.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

IsEmpty

This instance property indicates whether the `CLOB` is empty or not.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

A bool.

Exceptions

ObjectDisposedException - The object is already disposed.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

IsInChunkWriteMode

This instance property indicates whether or not the CLOB has been opened to defer index updates.

Declaration

```
// C#  
public bool IsInChunkWriteMode{get;}
```

Property Value

If the CLOB has been opened, returns true; otherwise, returns false.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

IsNClob

This instance property indicates whether or not the OracleClob object represents an NClob.

Declaration

```
// C#  
public bool IsNClob {get;}
```

Property Value

A bool.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

IsTemporary

This instance property indicates whether or not the current instance is bound to a temporary CLOB.

Declaration

```
// C#  
public bool IsTemporary {get;}
```

Property Value

A bool.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Length

Overrides `Stream`

This instance property indicates the size of the CLOB data in bytes.

Declaration

```
// C#  
public override Int64 Length {get;}
```

Property Value

An `Int64` that indicates the size of the CLOB in bytes.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OptimumChunkSize

This instance property indicates the minimum number of bytes to retrieve or send from the database during a read or write operation.

Declaration

```
// C#  
public int OptimumChunkSize{get;}
```

Property Value

A number representing the minimum bytes to retrieve or send.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Position

Overrides `Stream`

This instance property indicates the current read or write position in the LOB stream in bytes.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An `Int64` that indicates the read or write position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Position` is less than 0.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Value

This instance property returns the data, starting from the first character in the CLOB or NCLOB, as a string.

Declaration

```
// C#  
public string Value{get;}
```

Property Value

A string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Value` is less than 0.

Remarks

The value of `Position` is neither used nor changed by using this property.

The maximum string length that can be returned by this property is 2 GB.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Instance Methods

The `OracleClob` instance methods are listed in [Table 13-27](#).

Table 13-27 OracleClob Instance Methods

Methods	Description
Append	Appends data to the current OracleClob instance (Overloaded)
BeginChunkWrite	Opens the CLOB
BeginRead	Inherited from System.IO.Stream
BeginWrite	Inherited from System.IO.Stream
Clone	Creates a copy of an OracleClob object
Close	Closes the current stream and releases resources associated with it
Compare	Compares data referenced by the current instance to that of the supplied object
CopyTo	Copies the data to an OracleClob (Overloaded)
CreateObjRef	Inherited from System.MarshalByRefObject
Dispose	Releases resources allocated by this object
EndChunkWrite	Closes the CLOB referenced by the current OracleClob instance
EndRead	Inherited from System.IO.Stream
EndWrite	Inherited from System.IO.Stream
Equals	Inherited from System.Object (Overloaded)
Erase	Erases the specified amount of data (Overloaded)
Flush	<i>Not supported</i>
GetHashCode	Returns a hash code for the current instance
GetLifetimeService	Inherited from System.MarshalByRefObject
GetType	Inherited from System.Object
InitializeLifetimeService	Inherited from System.MarshalByRefObject
IsEqual	Compares the LOB data referenced by two OracleClobs
Read	Reads from the current instance (Overloaded)
ReadByte	Inherited from System.IO.Stream
Search	Searches for a character pattern in the current instance of OracleClob (Overloaded)
Seek	Sets the position in the current LOB stream
SetLength	Trims or truncates the CLOB value
ToString	Inherited from System.Object
Write	Writes the provided buffer into the OracleClob (Overloaded)
WriteByte	Inherited from System.IO.Stream

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Append

This instance method appends data to the current `OracleClob` instance.

Overload List:

- [Append\(OracleClob\)](#)
This instance method appends the `CLOB` data referenced by the provided `OracleClob` object to the current `OracleClob` instance.
- [Append\(byte \[\], int, int\)](#)
This instance method appends data at the end of the `CLOB`, from the supplied byte array buffer, starting from offset (in bytes) of the supplied byte array buffer.
- [Append\(char \[\], int, int\)](#)
This instance method appends data from the supplied character array buffer to the end of the current `OracleClob` instance, starting at the offset (in characters) of the supplied character buffer.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Append(OracleClob)

This instance method appends the `CLOB` data referenced by the provided `OracleClob` object to the current `OracleClob` instance.

Declaration

```
// C#  
public void Append(OracleClob obj);
```

Parameters

- *obj*

An OracleClob object.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The parameter has a different connection than the object, OracleConnection is not opened, or OracleConnection has been reopened.

Remarks

No character set conversions are made.

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Append(byte [], int, int)

This instance method appends data at the end of the CLOB, from the supplied byte array buffer, starting from offset (in bytes) of the supplied byte array buffer.

Declaration

```
// C#  
public int Append(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
An array of bytes, representing a Unicode string.
- *offset*
The zero-based byte offset in the buffer from which data is read.
- *count*
The number of bytes to be appended.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - Either the *offset* or the *count* parameter is not even.

Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Append(char [], int, int)

This instance method appends data from the supplied character array buffer to the end of the current `OracleClob` instance, starting at the *offset* (in characters) of the supplied character buffer.

Declaration

```
// C#  
public void Append(char[] buffer, int offset, int count);
```

Parameters

- *buffer*
An array of characters.
- *offset*
The zero-based offset (in characters) in the buffer from which data is read.
- *count*
The number of characters to be appended.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class AppendSample  
{  
    static void Main()  
}
```



```
{
    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    OracleConnection con = new OracleConnection(constr);
    con.Open();

    OracleClob clob = new OracleClob(con);

    // Append 2 chars {'d', 'e'} to the OracleClob
    char[] buffer = new char[3] {'d', 'e', 'f'};
    clob.Append(buffer, 0, 2);

    // Prints "clob.Value = de"
    Console.WriteLine("clob.Value = " + clob.Value);

    clob.Close();
    clob.Dispose();

    con.Close();
    con.Dispose();
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

BeginChunkWrite

This instance method opens the CLOB.

Declaration

```
// C#
public void BeginChunkWrite();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

`BeginChunkWrite` does not need to be called before manipulating the CLOB data. This is provided for performance reasons.

After this method is called, write operations do not cause the domain or function-based index on the column to be updated. Index updates occur only once after `EndChunkWrite` is called.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Clone

This instance method creates a copy of an `OracleClob` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An `OracleClob` object.

Implements

`ICloneable`

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class CloneSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleClob clob1 = new OracleClob(con);  
  
        // Prints "clob1.Position = 0"  
        Console.WriteLine("clob1.Position = " + clob1.Position);  
    }  
}
```

```
// Set the Position before calling Clone()
clob1.Position = 1;

// Clone the OracleClob
OracleClob clob2 = (OracleClob)clob1.Clone();

// Prints "clob2.Position = 1"
Console.WriteLine("clob2.Position = " + clob2.Position);

clob1.Close();
clob1.Dispose();

clob2.Close();
clob2.Dispose();

con.Close();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Close

Overrides Stream

This instance method closes the current stream and releases resources associated with it.

Declaration

```
// C#
public override void Close();
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Compare

This instance method compares data referenced by the current instance to that of the supplied object.

Declaration

```
// C#  
public int Compare(Int64 src_offset, OracleClob obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- *src_offset*
The comparison starting point (in characters) for the current instance.
- *obj*
The provided `OracleClob` object.
- *dst_offset*
The comparison starting point (in characters) for the provided `OracleClob`.
- *amount*
The number of characters to compare.

Return Value

The method returns a value that is:

- Less than zero: if the data referenced by the current instance is less than that of the supplied instance.
- Zero: if both objects reference the same data.
- Greater than zero: if the data referenced by the current instance is greater than that of the supplied instance.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - Either the *src_offset*, *dst_offset*, or *amount* parameter is less than 0.

Remarks

The character set of the two `OracleClob` objects being compared should be the same for a meaningful comparison.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo

`CopyTo` copies data from the current instance to the provided `OracleClob` object.

Overload List:

- [CopyTo\(OracleClob\)](#)
This instance method copies data from the current instance to the provided `OracleClob` object.
- [CopyTo\(OracleClob, Int64\)](#)
This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified destination offset.
- [CopyTo\(Int64, OracleClob, Int64, Int64\)](#)
This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified source offset, destination offset, and character amounts.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo(OracleClob)

This instance method copies data from the current instance to the provided `OracleClob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleClob obj);
```

Parameters

- *obj*

The `OracleClob` object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo(OracleClob, Int64)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified destination offset.

Declaration

```
// C#  
public Int64 CopyTo(OracleClob obj, Int64 dst_offset);
```

Parameters

- *obj*
The `OracleClob` object to which the data is copied.
- *dst_offset*
The offset (in characters) at which the `OracleClob` object is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The `dst_offset` is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the `dst_offset` is beyond the end of the `OracleClob` data, spaces are written into the `OracleClob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo(Int64, OracleClob, Int64, Int64)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified source offset, destination offset, and character amounts.

Declaration

```
// C#
public Int64 CopyTo(Int64 src_offset, OracleClob obj, Int64 dst_offset,
    Int64 amount);
```

Parameters

- `src_offset`
The offset (in characters) in the current instance, from which the data is read.
- `obj`
The `OracleClob` object to which the data is copied.
- `dst_offset`
The offset (in characters) at which the `OracleClob` object is copied.

- *amount*

The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The *src_offset*, the *dst_offset*, or the *amount* parameter is less than 0.

Remarks

If the *dst_offset* is beyond the end of the `OracleClob` data, spaces are written into the `OracleClob` until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CopyToSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob1 = new OracleClob(con);
        OracleClob clob2 = new OracleClob(con);

        // Write 4 chars, starting at buffer offset 0
        char[] buffer = new char[4] {'a', 'b', 'c', 'd'};
        clob1.Write(buffer, 0, 4);

        // Copy 2 chars from char 0 of clob1 to char 1 of clob2
        clob1.CopyTo(0, clob2, 1, 2);

        //Prints "clob2.Value = ab"
        Console.WriteLine("clob2.Value = " + clob2.Value);

        clob1.Close();
        clob1.Dispose();

        clob2.Close();
    }
}
```



```
        clob2.Dispose();  
  
        con.Close();  
        con.Dispose();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Dispose

This instance method releases resources allocated by this object.

Declaration

```
public void Dispose();
```

Implements

IDisposable

Remarks

The object cannot be reused after being disposed. Although some properties can still be accessed, their values cannot be accountable. Since resources are freed, method calls can lead to exceptions.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

EndChunkWrite

This instance method closes the CLOB referenced by the current OracleClob instance.

Declaration

```
// C#  
public void EndChunkWrite();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Index updates occur immediately if write operation(s) are deferred by the `BeginChunkWrite` method.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Erase

`Erase` erases part or all data.

Overload List:

- [Erase\(\)](#)
This instance method erases all data.
- [Erase\(Int64, Int64\)](#)
This instance method replaces the specified `amount` of data (in characters) starting from the specified `offset` with zero-byte fillers (in characters).



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Erase()

This instance method erases all data.

Declaration

```
// C#  
public Int64 Erase();
```

Return Value

The number of characters erased.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Erase(Int64, Int64)

This instance method replaces the specified `amount` of data (in characters) starting from the specified `offset` with zero-byte fillers (in characters).

Declaration

```
// C#  
public Int64 Erase(Int64 offset, Int64 amount);
```

Parameters

- `offset`
The offset.
- `amount`
The amount of data.

Return Value

The actual number of characters erased.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `offset` or `amount` parameter is less than 0.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Flush

This method is not supported.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the current instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

An `int` representing a hash code.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

IsEqual

This instance method compares the LOB data referenced by two `OracleClob`s.

Declaration

```
// C#  
public bool IsEqual(OracleClob obj);
```

Parameters

- *obj*
An OracleClob object.

Return Value

Returns `true` if the current OracleClob and the provided OracleClob refer to the same LOB. Otherwise, returns `false`.

Remarks

Note that this method can return `true` even if the two OracleClob objects returns `false` for `==` or `Equals()` because two different OracleClob instances can refer to the same LOB.

The provided object and the current instance must be using the same connection, that is, the same OracleConnection object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Read

`Read` reads a specified amount from the current instance and populates the array `buffer`.

Overload List:

- [Read\(byte \[\], int, int\)](#)
This instance method reads a specified amount of bytes from the current instance and populates the byte array `buffer`.
- [Read\(char \[\], int, int\)](#)
This instance method reads a specified amount of characters from the current instance and populates the character array `buffer`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Read(byte [], int, int)

Overrides `Stream`

This instance method reads a specified amount of bytes from the current instance and populates the byte array `buffer`.

Declaration

```
// C#  
public override int Read(byte [] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer that is populated.
- *offset*
The offset (in bytes) at which the buffer is populated.
- *count*
The amount of bytes to be read.

Return Value

The number of bytes read from the CLOB.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

The LOB data is read starting from the position specified by the `Position` property, which must also be an even number.

`OracleClob` is free to return fewer bytes than requested, even if the end of the stream has not been reached.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Read(char [], int, int)

This instance method reads a specified amount of characters from the current instance and populates the character array buffer.

Declaration

```
// C#  
public int Read(char[ ] buffer, int offset, int count);
```

Parameters

- *buffer*
The character array buffer that is populated.
- *offset*
The offset (in characters) at which the buffer is populated.
- *count*
The amount of characters to be read.

Return Value

The return value indicates the number of characters read from the CLOB.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than *buffer.Length*.

Remarks

Handles all CLOB and NCLOB data as Unicode.

The LOB data is read starting from the position specified by the `Position` property.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ReadSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 3 chars, starting at buffer offset 1
        char[] writeBuffer = new char[4] {'a', 'b', 'c', 'd'};
        clob.Write(writeBuffer, 1, 3);

        // Reset the Position (in bytes) for Read
        clob.Position = 2;

        // Read 2 chars into buffer starting at buffer offset 1
        char[] readBuffer = new char[4];
        int charsRead = clob.Read(readBuffer, 1, 2);

        // Prints "charsRead = 2"
        Console.WriteLine("charsRead = " + charsRead);

        // Prints "readBuffer = cd "
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        clob.Close();
        clob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Search

`Search` searches for a character pattern in the current instance of `OracleClob`.

Overload List:

- [Search\(byte\[\], Int64, Int64\)](#)
This instance method searches for a character pattern, represented by the byte array, in the current instance of `OracleClob`.
- [Search\(char\[\], Int64, Int64\)](#)
This instance method searches for a character pattern in the current instance of `OracleClob`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Search(byte[], Int64, Int64)

This instance method searches for a character pattern, represented by the byte array, in the current instance of `OracleClob`.

Declaration

```
// C#  
public int Search(byte[] val, Int64 offset, Int64 nth);
```

Parameters

- *val*
A Unicode byte array.
- *offset*
The 0-based offset (in characters) starting from which the `OracleClob` is searched.
- *nth*
The specific occurrence (1-based) of the match for which the absolute offset (in characters) is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *nth* is greater than or equal to `OracleClob.MaxValue`.
- The *offset* is greater than or equal to `OracleClob.MaxValue`.

Remarks

The `byte[]` is converted to Unicode before the search is made.

The limit of the search pattern is 16383 bytes.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Search(char[], Int64, Int64)

This instance method searches for a character pattern in the current instance of `OracleClob`.

Declaration

```
// C#  
public Int64 Search(char [ ] val, Int64 offset, Int64 nth);
```

Parameters

- *val*
The Unicode string being searched for.
- *offset*
The 0-based offset (in characters) starting from which the `OracleClob` is searched.
- *nth*
The specific occurrence (1-based) of the match for which the absolute offset (in characters) is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in characters) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The `val.Length` doubled is greater than 16383.
- The *nth* is greater than or equal to `OracleClob.MaxSize`.
- The *offset* is greater than or equal to `OracleClob.MaxSize`.

Remarks

The limit of the search pattern is 16383 bytes.

Example

```
// C#
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 7 chars, starting at buffer offset 0
        char[] buffer = new char[7] { 'a', 'b', 'c', 'd', 'a', 'b', 'c' };
        clob.Write(buffer, 0, 7);

        // Search for the 2nd occurrence of a char pattern 'bc'
        // starting at offset 1 in the OracleBlob
        char[] pattern = new char[2] { 'b', 'c' };
        long posFound = clob.Search(pattern, 1, 2);

        // Prints "posFound = 6"
        Console.WriteLine("posFound = " + posFound);

        clob.Close();
        clob.Dispose();
    }
}
```

```
        con.Close();  
        con.Dispose();  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Seek

Overrides [Stream](#)

This instance method sets the position on the current LOB stream.

Declaration

```
// C#  
public override Int64 Seek(Int64 offset, SeekOrigin origin);
```

Parameters

- *offset*
A byte offset relative to origin.
- *origin*
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

Returns an `Int64` that indicates the position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

If *offset* is negative, the new position precedes the position specified by *origin* by the number of characters specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of characters specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

`SeekOrigin.Current` specifies the current position within a stream.

`SeekOrigin.End` specifies the end of a stream.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

SetLength

Overrides `Stream`

This instance method trims or truncates the CLOB value to the specified length (in characters).

Declaration

```
// C#  
public override void SetLength(Int64 newLen);
```

Parameters

- *newLen*
The desired length of the current stream in characters.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The *newLen* parameter is greater than 0.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Write

This instance method writes data from the provided array buffer into the `OracleClob`.

Overload List:

- [Write\(byte\[\], int, int\)](#)
This instance method writes data from the provided byte array buffer into the `OracleClob`.
- [Write\(char\[\], int, int\)](#)
This instance method writes data from the provided character array buffer into the `OracleClob`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Write(byte[], int, int)

Overrides `Stream`

This instance method writes data from the provided byte array buffer into the `OracleClob`.

Declaration

```
// C#  
public override void Write(byte[ ] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer that represents a Unicode string.
- *offset*
The offset (in bytes) from which the `buffer` is read.
- *count*
The amount of data (in bytes) from the buffer to be written into the `OracleClob`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than the *buffer.Length*.
- The *offset*, the *count*, or the *Position* is not even.

Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

The LOB data is read starting from the position specified by the `Position` property. The `Position` property must be an even number.

If necessary, proper data conversion is carried out from the client character set to the database character set.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Write(char[], int, int)

This instance method writes data from the provided character array buffer into the `OracleClob`.

Declaration

```
// C#  
public void Write(char[] buffer, int offset, int count);
```

Parameters

- *buffer*
The character array buffer that is written to the `OracleClob`.
- *offset*
The offset (in characters) from which the *buffer* is read.
- *count*
The amount (in characters) from the buffer that is to be written into the `OracleClob`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than *buffer.Length*.
- The *Position* is not even.

Remarks

Handles all CLOB and NCLOB data as Unicode.

The LOB data is read starting from the position specified by the *Position* property.

If necessary, proper data conversion is carried out from the client character set to the database character set.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class WriteSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Set the Position for the Write;
        clob.Position = 0;

        // Begin ChunkWrite to improve performance
        // Index updates occur only once after EndChunkWrite
        clob.BeginChunkWrite();

        // Write to the OracleClob in 5 chunks of 2 chars each
        char[] c = new char[2] {'a', 'b'};
        for (int index = 0; index < 5; index++)
        {
            clob.Write(c, 0, c.Length);
        }
        clob.EndChunkWrite();

        // Prints "clob.Value = ababababab"
        Console.WriteLine("clob.Value = " + clob.Value);

        clob.Close();
        clob.Dispose();
    }
}
```



```

        con.Close();
        con.Dispose();
    }
}

```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleRefCursor Class

An OracleRefCursor object represents an Oracle REF CURSOR..

Class Inheritance

System.Object

System.MarshalRefByObject

Oracle.DataAccess.Types.OracleRefCursor

Declaration

```

// C#
public sealed class OracleRefCursor : MarshalByRefObject, IDisposable, INullable

```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

To minimize the number of open server cursors, OracleRefReader objects should be explicitly disposed.

Example

```
// Database Setup
/*
connect scott/tiger@oracle
CREATE OR REPLACE FUNCTION MyFunc(refcur_out OUT SYS_REFCURSOR)
  RETURN SYS_REFCURSOR IS refcur_ret SYS_REFCURSOR;
BEGIN
  OPEN refcur_ret FOR SELECT * FROM EMP;
  OPEN refcur_out FOR SELECT * FROM DEPT;
  RETURN refcur_ret;
END MyFunc;
/
*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleRefCursorSample
{
  static void Main()
  {
    // Example demonstrates how to use REF CURSORS returned from
    // PL/SQL Stored Procedures or Functions
    // Create the PL/SQL Function MyFunc as defined previously

    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    OracleConnection con = new OracleConnection(constr);
    con.Open();

    // Create an OracleCommand
    OracleCommand cmd = new OracleCommand("MyFunc", con);
    cmd.CommandType = CommandType.StoredProcedure;

    // Bind the parameters
    // p1 is the RETURN REF CURSOR bound to SELECT * FROM EMP;
    OracleParameter p1 =
      cmd.Parameters.Add("refcur_ret", OracleDbType.RefCursor);
    p1.Direction = ParameterDirection.ReturnValue;

    // p2 is the OUT REF CURSOR bound to SELECT * FROM DEPT
    OracleParameter p2 =
      cmd.Parameters.Add("refcur_out", OracleDbType.RefCursor);
    p2.Direction = ParameterDirection.Output;

    // Execute the command
    cmd.ExecuteNonQuery();

    // Construct an OracleDataReader from the REF CURSOR
    OracleDataReader reader1 = ((OracleRefCursor)p1.Value).GetDataReader();

    // Prints "reader1.GetName(0) = EMPNO"
    Console.WriteLine("reader1.GetName(0) = " + reader1.GetName(0));

    // Construct an OracleDataReader from the REF CURSOR
    OracleDataReader reader2 = ((OracleRefCursor)p2.Value).GetDataReader();
```

```
// Prints "reader2.GetName(0) = DEPTNO"
Console.WriteLine("reader2.GetName(0) = " + reader2.GetName(0));

reader1.Close();
reader1.Dispose();

reader2.Close();
reader2.Dispose();

p1.Dispose();
p2.Dispose();

cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Members](#)
- [OracleRefCursor Static Methods](#)
- [OracleRefCursor Static Fields](#)
- [OracleRefCursor Properties](#)
- [OracleRefCursor Instance Methods](#)

OracleRefCursor Members

OracleRefCursor members are listed in the following tables.

OracleRefCursor Static Methods

OracleRefCursor static methods are listed in [Table 13-28](#).

Table 13-28 OracleRefCursor Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleRefCursor Static Fields

OracleRefCursor static field is listed in [Table 13-29](#).

Table 13-29 OracleRefCursor Static Field

Methods	Description
Null	Represents a null value that can be assigned to an OracleRefCursor instance

OracleRefCursor Properties

OracleRefCursor properties are listed in [Table 13-30](#).

Table 13-30 OracleRefCursor Properties

Properties	Description
Connection	A reference to the OracleConnection used to fetch the REF CURSOR data
FetchSize	Specifies the size that the OracleDataReader internal cache needs to store result set data
IsNull	Indicates whether or not the OracleRefCursor is null
RowSize	Specifies the amount of memory the OracleRefcursor internal cache needs to store one row of data

OracleRefCursor Instance Methods

OracleRefCursor instance methods are listed in [Table 13-31](#).

Table 13-31 OracleRefCursor Instance Methods

Methods	Description
Dispose	Disposes the resources allocated by the OracleRefCursor object
Equals	Inherited from System.Object (Overloaded)
GetDataReader	Returns an OracleDataReader object for the REF CURSOR
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)

OracleRefCursor Static Methods

OracleRefCursor static methods are listed in [Table 13-32](#).

Table 13-32 OracleRefCursor Static Methods

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

OracleRefCursor Static Fields

OracleRefCursor static field is listed in [Table 13-32](#).

Table 13-33 OracleRefCursor Static Field

Methods	Description
Null	Represents a null value that can be assigned to an <code>OracleRefCursor</code> instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

Null

This static field represents a null value that can be assigned to an `OracleRefCursor` instance.

Declaration

```
// C#  
public static readonly OracleRefCursor Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

OracleRefCursor Properties

`OracleRefCursor` properties are listed in [Table 13-34](#).

Table 13-34 OracleRefCursor Properties

Properties	Description
Connection	A reference to the <code>OracleConnection</code> used to fetch the <code>REF CURSOR</code> data
FetchSize	Specifies the size that the <code>OracleDataReader</code> internal cache needs to store result set data
IsNull	Indicates whether or not the <code>OracleRefCursor</code> is null
RowSize	Specifies the amount of memory the <code>OracleRefcursor</code> internal cache needs to store one row of data

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

Connection

This property refers to the `OracleConnection` used to fetch the `REF CURSOR` data.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property is bound to a `REF CURSOR` once it is set. After the `OracleRefCursor` object is created by the constructor, this property is initially `null`. An `OracleRefCursor` object can be bound to a `REF CURSOR` after a command execution.

If the connection is closed or returned to the connection pool, the `OracleRefCursor` is placed in an uninitialized state and no operation can be carried out from it. However, the uninitialized `OracleRefCursor` can be reassigned to another `REF CURSOR`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

FetchSize

This property specifies the size that the `OracleDataReader` internal cache needs to store result set data.

Declaration

```
// C#  
public long FetchSize {get; set;}
```

Property Value

A `long` that specifies the size (in bytes) of the `OracleRefCursor` internal cache.

Exceptions

`ArgumentException` - The `FetchSize` value specified is invalid.

Remarks

Default = 131072.

The `FetchSize` property value is inherited by the `OracleCommand` that created the `OracleRefCursor` object. The `FetchSize` property on the `OracleDataReader` object determines the amount of data the `OracleRefCursor` fetches into its internal cache for each database round-trip.

This property is useful if the `OracleRefCursor` is explicitly used to fill the `DataSet` or `DataTable` through the `OracleDataAdapter`, because it can provide control on how the data of the `REF CURSOR` is fetched.

If an `OracleDataReader` object is created from the `OracleRefCursor`, the resulting `OracleDataReader` object inherits the `FetchSize` value of the `OracleDataReader` object. However, the inherited value can be overridden, if it is set before the first invocation of the `OracleDataReader` `Read` method for the given result set, by setting the `OracleDataReader` `FetchSize` property.

The `RowSize` and `FetchSize` properties handle UDT and `XMLType` data differently than other scalar data types. Because only a reference to the UDT and `XMLType` data is stored in the ODP.NET's internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and `XMLType` data. Thus, applications can inadvertently fetch a large number of UDT or `XMLType` instances from the database in a single database round-trip. This is because the actual size of UDT and `XMLType` data does not count against the `FetchSize`, and it would require numerous UDT and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of UDT and `XMLType` instances that are to be fetched, rather than the amount of the actual UDT and `XMLType` data to be fetched.

NOTE: For LOB and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

IsNull

This property indicates whether or not the `OracleRefCursor` is null.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns `true` if the `OracleRefCursor` represents a null value. Returns `false` otherwise.

Exception

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

RowSize

This property specifies the amount of memory the `OracleRefcursor` internal cache needs to store one row of data.

Declaration

```
// C#  
public long RowSize {get;}
```

Property Value

A `long` that indicates the amount of memory (in bytes) that an `OracleRefcursor` needs to store one row of data for the executed query.

Remarks

The `RowSize` property is set to a nonzero value when the `OracleRefcursor` object is created. This property can be used at design time or dynamically during run time, to set the `FetchSize`, based on number of rows. For example, to enable the `OracleRefcursor` to fetch *N* rows for each database round-trip, the `OracleRefcursor FetchSize` property can be set dynamically to `RowSize * N`. Note that for the `FetchSize` to take effect appropriately, it must be set before the it is used to fill the `DataSet/DataTable` using `OracleDataAdapter`.

If an `OracleDataReader` is obtained from the `OracleRefCursor` through the `GetDataReader` method, the resulting `OracleDataReader` will have its `FetchSize` property set to the `FetchSize` value of the `OracleRefCursor`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

OracleRefCursor Instance Methods

OracleRefCursor instance methods are listed in [Table 13-35](#).

Table 13-35 OracleRefCursor Instance Methods

Methods	Description
Dispose	Disposes the resources allocated by the OracleRefCursor object
Equals	Inherited from System.Object (Overloaded)
GetDataReader	Returns an OracleDataReader object for the REF CURSOR
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
ToString	Inherited from System.Object

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

Dispose

This instance method disposes of the resources allocated by the OracleRefCursor object.

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

Remarks

The object cannot be reused after being disposed.

Once `Dispose()` is called, the object of `OracleRefCursor` is in an uninitialized state. Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls can lead to exceptions.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

GetDataReader

This instance method returns an `OracleDataReader` object for the `REF CURSOR`.

Declaration

```
// C#  
public OracleDataReader GetDataReader();
```

Return Value

`OracleDataReader`

Remarks

Using the `OracleDataReader`, rows can be fetched from the `REF CURSOR`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

14

Oracle Data Provider for .NET Types Structures

This chapter describes the ODP.NET Types structures.

This chapter contains these topics:

- [OracleBinary Structure](#)
- [OracleBoolean Structure](#)
- [OracleDate Structure](#)
- [OracleDecimal Structure](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalYM Structure](#)
- [OracleString Structure](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampTZ Structure](#)
- [INullable Interface](#)

OracleBinary Structure

The `OracleBinary` structure represents a variable-length stream of binary data to be stored in or retrieved from a database.

Class Inheritance

```
System.Object
```

```
System.ValueType
```

```
Oracle.DataAccess.Types.OracleBinary
```

Declaration

```
// C#  
public struct OracleBinary : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Namespace	Oracle.DataAccess .Client	Oracle.ManagedDat aAccess.Client	Oracle.ManagedDat aAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class OracleBinarySample  
{  
    static void Main(string[] args)  
    {  
        // Initialize the OracleBinary structures  
        OracleBinary binary1= new OracleBinary(new byte[] {1,2,3,4,5});  
        OracleBinary binary2 = new OracleBinary(new byte[] {1,2,3});  
        OracleBinary binary3 = new OracleBinary(new byte[] {4,5});  
        OracleBinary binary4 = binary2 + binary3;  
  
        // Compare binary1 and binary4; they're equal  
        if (binary1 == binary4)  
            Console.WriteLine("The two OracleBinary structs are equal");  
        else  
            Console.WriteLine("The two OracleBinary structs are different");  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Members](#)
- [OracleBinary Constructor](#)
- [OracleBinary Static Fields](#)
- [OracleBinary Static Methods](#)
- [OracleBinary Static Operators](#)
- [OracleBinary Static Type Conversion Operators](#)
- [OracleBinary Properties](#)
- [OracleBinary Instance Methods](#)

OracleBinary Members

OracleBinary members are listed in the following tables:

OracleBinary Constructors

OracleBinary constructors are listed in [Table 14-1](#)

Table 14-1 OracleBinary Constructors

Constructor	Description
OracleBinary Constructor	Instantiates a new instance of OracleBinary structure

OracleBinary Static Fields

The OracleBinary static fields are listed in [Table 14-2](#).

Table 14-2 OracleBinary Static Fields

Field	Description
Null	Represents a null value that can be assigned to an instance of the OracleBinary structure

OracleBinary Static Methods

The OracleBinary static methods are listed in [Table 14-3](#).

Table 14-3 OracleBinary Static Methods

Methods	Description
Concat	Returns the concatenation of two OracleBinary structures
Equals	Determines if two OracleBinary values are equal (Overloaded)
GetXsdType	Returns the XML Schema definition language (XSD) of the specified XmlSchemaSet
GreaterThan	Determines if the first of two OracleBinary values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleBinary values is greater than or equal to the second
LessThan	Determines if the first of two OracleBinary values is less than the second
LessThanOrEqual	Determines if the first of two OracleBinary values is less than or equal to the second
NotEquals	Determines if two OracleBinary values are not equal

OracleBinary Static Operators

The OracleBinary static operators are listed in [Table 14-4](#).

Table 14-4 OracleBinary Static Operators

Operator	Description
operator +	Concatenates two OracleBinary values
operator ==	Determines if two OracleBinary values are equal
operator >	Determines if the first of two OracleBinary values is greater than the second
operator >=	Determines if the first of two OracleBinary values is greater than or equal to the second
operator !=	Determines if two OracleBinary values are not equal
operator <	Determines if the first of two OracleBinary value is less than the second
operator <=	Determines if the first of two OracleBinary value is less than or equal to the second

OracleBinary Static Type Conversion Operators

The OracleBinary static type conversion operators are listed in [Table 14-5](#).

Table 14-5 OracleBinary Static Type Conversion Operators

Operator	Description
explicit operator byte[]	Converts an instance value to a byte array
implicit operator OracleBinary	Converts an instance value to an OracleBinary structure

OracleBinary Properties

The OracleBinary properties are listed in [Table 14-6](#).

Table 14-6 OracleBinary Properties

Properties	Description
IsNull	Indicates whether or not the current instance has a null value
Item	Obtains the particular byte in an OracleBinary structure using an index
Length	Returns the length of the binary data
Value	Returns the binary data that is stored in an OracleBinary structure

OracleBinary Instance Methods

The OracleBinary instance methods are listed in [Table 14-7](#).

Table 14-7 OracleBinary Instance Methods

Methods	Description
CompareTo	Compares the current instance to an object and returns an integer that represents their relative values
Equals	Determines if two objects contain the same binary data (Overloaded)
GetHashCode	Returns a hash code for the current instance
GetType	Inherited from <code>System.Object</code>
ToString	Converts the current OracleBinary structure to a string

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)

OracleBinary Constructor

The OracleBinary constructor instantiates a new instance of the OracleBinary structure and sets its value to the provided array of bytes.

Declaration

```
// C#  
public OracleBinary(byte[] bytes);
```

Parameters

- *bytes*
A byte array.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Fields

The `OracleBinary` static fields are listed in [Table 14-8](#).

Table 14-8 OracleBinary Static Fields

Field	Description
Null	Represents a null value that can be assigned to an instance of the <code>OracleBinary</code> structure.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleBinary` structure.

Declaration

```
// C#  
public static readonly OracleBinary Null;
```

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Methods

The OracleBinary static methods are listed in [Table 14-9](#).

Table 14-9 OracleBinary Static Methods

Methods	Description
Concat	Returns the concatenation of two OracleBinary structures
Equals	Determines if two OracleBinary values are equal (Overloaded)
GetXsdType	Returns the XML Schema definition language (XSD) of the specified XmlSchemaSet
GreaterThan	Determines if the first of two OracleBinary values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleBinary values is greater than or equal to the second
LessThan	Determines if the first of two OracleBinary values is less than the second
LessThanOrEqual	Determines if the first of two OracleBinary values is less than or equal to the second
NotEquals	Determines if two OracleBinary values are not equal

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Concat

This method returns the concatenation of two OracleBinary structures.

Declaration

```
// C#  
public static OracleBinary Concat(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

An OracleBinary.

Remarks

If either argument has a null value, the returned OracleBinary structure has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Equals

This method determines if two OracleBinary values are equal.

Declaration

```
// C#  
public static bool Equals(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns true if two OracleBinary values are equal; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

GetXsdType

This method returns the XML Schema definition language (XSD) of the specified `XmlSchemaSet`.

Declaration

```
// C#  
public static XmlQualifiedName GetXsdType(XmlSchemaSet schemaSet);
```

Parameters

- *schemaSet*
An `XmlSchemaSet`.

Return Value

Returns a string that indicates the XSD of the specified `XmlSchemaSet`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

GreaterThan

This method determines whether or not the first of two `OracleBinary` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns `true` if the first of two OracleBinary values is greater than the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class GreaterThanSample  
{  
    static void Main(string[] args)  
    {  
        OracleBinary binary1 = OracleBinary.Null;  
        OracleBinary binary2 = new OracleBinary(new byte[] {1});  
  
        // Compare two OracleBinary structs; binary1 < binary2  
        if (OracleBinary.GreaterThan(binary1, binary2))  
            Console.WriteLine("binary1 > binary2");  
        else  
            Console.WriteLine("binary1 < binary2");  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

GreaterThanOrEqual

This method determines whether or not the first of two `OracleBinary` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleBinary value1, OracleBinary value2);
```

Parameters

- `value1`
The first `OracleBinary`.
- `value2`
The second `OracleBinary`.

Return Value

Returns `true` if the first of two `OracleBinary` values is greater than or equal to the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

LessThan

This method determines whether or not the first of two `OracleBinary` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleBinary value1, OracleBinary value2);
```

Parameters

- `value1`
The first `OracleBinary`.
- `value2`
The second `OracleBinary`.

Return Value

Returns `true` if the first of two `OracleBinary` values is less than the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

LessThanOrEqual

This method determines whether or not the first of two `OracleBinary` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleBinary value1, OracleBinary value2);
```

Parameters

- `value1`

The first OracleBinary.

- *value2*

The second OracleBinary.

Return Value

Returns `true` if the first of two OracleBinary values is less than or equal to the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

NotEquals

This method determines whether or not two OracleBinary values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns `true` if two OracleBinary values are not equal; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.

- Two OracleBinarys that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Operators

The OracleBinary static operators are listed in [Table 14-10](#).

Table 14-10 OracleBinary Static Operators

Operator	Description
<code>operator +</code>	Concatenates two OracleBinary values
<code>operator ==</code>	Determines if two OracleBinary values are equal
<code>operator ></code>	Determines if the first of two OracleBinary values is greater than the second
<code>operator >=</code>	Determines if the first of two OracleBinary values is greater than or equal to the second
<code>operator !=</code>	Determines if two OracleBinary values are not equal
<code>operator <</code>	Determines if the first of two OracleBinary value is less than the second
<code>operator <=</code>	Determines if the first of two OracleBinary value is less than or equal to the second



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator +

This method concatenates two OracleBinary values.

Declaration

```
// C#
public static OracleBinary operator + (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

OracleBinary

Remarks

If either argument has a null value, the returned OracleBinary structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator ==

This method determines if two OracleBinary values are equal.

Declaration

```
// C#  
public static bool operator == (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns true if they are the same; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.

- Two OracleBinarys that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator >

This method determines if the first of two OracleBinary values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns `true` if the first of two OracleBinary values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class OperatorSample  
{  
    static void Main(string[] args)  
    {  
        OracleBinary binary1 = OracleBinary.Null;  
        OracleBinary binary2 = new OracleBinary(new byte[] {1});  
    }  
}
```

```
// Compare two OracleBinary structs; binary1 < binary2
if (binary1 > binary2)
    Console.WriteLine("binary1 > binary2");
else
    Console.WriteLine("binary1 < binary2");
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator >=

This method determines if the first of two `OracleBinary` values is greater than or equal to the second.

Declaration

```
// C#
public static bool operator >= (OracleBinary value1, OracleBinary value2);
```

Parameters

- `value1`
The first `OracleBinary`.
- `value2`
The second `OracleBinary`.

Return Value

Returns `true` if the first of two `OracleBinary` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator !=

This method determines if two `OracleBinary` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleBinary value1, OracleBinary value2);
```

Parameters

- `value1`
The first `OracleBinary`.
- `value2`
The second `OracleBinary`.

Return Value

Returns `true` if the two `OracleBinary` values are not equal; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator <

This method determines if the first of two `OracleBinary` values is less than the second.

Declaration

```
// C#  
public static bool operator < ( OracleBinary value1, OracleBinary value2);
```

Parameters

- `value1`

The first OracleBinary.

- *value2*

The second OracleBinary.

Return Value

Returns `true` if the first of two OracleBinary values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator <=

This method determines if the first of two OracleBinary values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleBinary value1, OracleBinary value1);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns `true` if the first of two OracleBinary values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Type Conversion Operators

The OracleBinary static type conversion operators are listed in [Table 14-11](#).

Table 14-11 OracleBinary Static Type Conversion Operators

Operator	Description
explicit operator byte[]	Converts an instance value to a byte array
implicit operator OracleBinary	Converts an instance value to an OracleBinary structure

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

explicit operator byte[]

This method converts an OracleBinary value to a byte array.

Declaration

```
// C#  
public static explicit operator byte[] (OracleBinary val);
```

Parameters

- *val*
An OracleBinary.

Return Value

A byte array.

Exceptions

`OracleNullValueException` - The `OracleBinary` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

implicit operator OracleBinary

This method converts a byte array to an `OracleBinary` structure.

Declaration

```
// C#  
public static implicit operator OracleBinary(byte[] bytes);
```

Parameters

- *bytes*
A byte array.

Return Value

`OracleBinary`

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Properties

The `OracleBinary` properties are listed in [Table 14-12](#).

Table 14-12 OracleBinary Properties

Properties	Description
IsNull	Indicates whether or not the current instance has a null value
Item	Obtains the particular byte in an OracleBinary structure using an index
Length	Returns the length of the binary data
Value	Returns the binary data that is stored in an OracleBinary structure

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise returns `false`.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Item

This property obtains the particular byte in an OracleBinary structure using an index.

Declaration

```
// C#  
public byte this[int index] {get;}
```

Property Value

A byte in the specified index.

Exceptions

`OracleNullValueException` - The current instance has a null value.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class ItemSample  
{  
    static void Main(string[] args)  
    {  
        OracleBinary binary = new OracleBinary(new byte[] {1,2,3,4});  
  
        // Prints the value 4  
        Console.WriteLine(binary[binary.Length - 1]);  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Length

This property returns the length of the binary data.

Declaration

```
// C#  
public int length {get;}
```

Property Value

Length of the binary data.

Exceptions

`OracleNullValueException` - The current instance has a null value.

Example

```
// C#
```

```
using System;
using Oracle.DataAccess.Types;

class LengthSample
{
    static void Main(string[] args)
    {
        OracleBinary binary = new OracleBinary(new byte[] {1,2,3,4});

        // Prints the value 4
        Console.WriteLine(binary.Length);
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Value

This property returns the binary data that is stored in the `OracleBinary` structure.

Declaration

```
// C#
public byte[] Value {get;}
```

Property Value

Binary data.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Instance Methods

The `OracleBinary` instance methods are listed in [Table 14-13](#).

Table 14-13 OracleBinary Instance Methods

Methods	Description
CompareTo	Compares the current instance to an object and returns an integer that represents their relative values
Equals	Determines if two objects contain the same binary data (Overloaded)
GetHashCode	Returns a hash code for the current instance
GetType	Inherited from <code>System.Object</code>
ToString	Converts the current <code>OracleBinary</code> structure to a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

CompareTo

This method compares the current instance to an object and returns an integer that represents their relative values

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared.

Return Value

The method returns a number that is:

- Less than zero: if the current `OracleBinary` instance value is less than *obj*.
- Zero: if the current `OracleBinary` instance and *obj* values have the same binary data.
- Greater than zero: if the current `OracleBinary` instance value is greater than *obj*.

Implements

`IComparable`

Exceptions

`ArgumentException` - The parameter is not of type `OracleBinary`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleBinary`s. For example, comparing an `OracleBinary` instance with an `OracleTimeStamp` instance is not allowed. When an `OracleBinary` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class CompareToSample  
{  
    static void Main(string[] args)  
    {  
        OracleBinary binary1 = new OracleBinary(new byte[] {1,2,3});  
        OracleBinary binary2 = new OracleBinary(new byte[] {1,2,3,4});  
  
        // Compare  
        if (binary1.CompareTo(binary2) == 0)  
            Console.WriteLine("binary1 is the same as binary2");  
        else  
            Console.WriteLine("binary1 is different from binary2");  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Equals

This method determines whether or not an object is an instance of `OracleBinary`, and has the same binary data as the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*
The object being compared.

Return Value

Returns `true` if *obj* is an instance of `OracleBinary`, and has the same binary data as the current instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleBinary` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

An `int` that represents the hash.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

ToString

Overrides `Object`

This method converts an `OracleBinary` instance to a string instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

string

Remarks

If the current `OracleBinary` instance has a null value, the returned string "null".

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBoolean Structure

The `OracleBoolean` structure represents a logical value that is either `TRUE` or `FALSE`.

ODP.NET, Unmanaged Driver can access Oracle Database PL/SQL Booleans in Oracle Database Release 12.1 and later. ODP.NET, Managed Driver can access Oracle Database PL/SQL Booleans in Oracle Database Release 12.2 and later.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleBoolean`

Declaration

```
// C#
public struct OracleBoolean : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

A `OracleBoolean` structure represents three possible values: `TRUE`, `FALSE`, and `NULL`. A non-zero value is interpreted as `TRUE`.

Example

```
// C#
using System;
using System.Data;
using Oracle.DataAccess.Types; // for use with ODP.NET, Unmanaged Driver
// using Oracle.ManagedDataAccess.Types; // for use with ODP.NET, Managed Driver

class OracleBooleanSample
{
    static void Main(string[] args)
    {
        OracleBoolean oracleBoolean1 = new OracleBoolean(true);
        OracleBoolean oracleBoolean2 = new OracleBoolean(0);

        Console.WriteLine("oracleBoolean1 : " + oracleBoolean1);
        Console.WriteLine("oracleBoolean2 : " + oracleBoolean2);
    }
}
```


 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Members](#)
- [OracleBoolean Constructors](#)
- [OracleBoolean Static Fields](#)
- [OracleBoolean Static Methods](#)
- [OracleBoolean Static Operators](#)
- [OracleBoolean Static Type Conversions](#)
- [OracleBoolean Properties](#)
- [OracleBoolean Instance Methods](#)

OracleBoolean Members

OracleBoolean members are listed in the following tables:

OracleBoolean Constructors

OracleBoolean constructors are listed in [Table 14-14](#)

Table 14-14 OracleBoolean Constructors

Constructor	Description
OracleBoolean Constructors	Instantiates a new instance of OracleBoolean structure (Overloaded)

OracleBoolean Static Fields

The OracleBoolean static fields are listed in [Table 14-15](#).

Table 14-15 OracleBoolean Static Fields

Field	Description
False	Represents a false value that can be assigned to an OracleBoolean instance
Null	Represents a null value that can be assigned to an OracleBoolean instance
One	Indicates a constant representing the positive one value
True	Represents a true value that can be assigned to an OracleBoolean instance
Zero	Indicates a constant representing the zero value

OracleBoolean Static Methods

OracleBoolean static methods are listed in [Table 14-16](#)

Table 14-16 OracleBoolean Static Methods

Methods	Description
And	Returns the result of bitwise AND operation of two OracleBoolean instances
Equals	Determines whether or not the two OracleBoolean values are equal
GreaterThan	Determines whether or not the first of two OracleBoolean values is greater than the second
GreaterThanOrEquals	Determines whether or not the first of two OracleBoolean values is greater than or equal to the second
LessThan	Determines whether or not the first of two OracleBoolean values is less than the second
LessThanOrEquals	Determines whether or not the first of two OracleBoolean values is less than or equal to the second
NotEquals	Determines whether or not two OracleBoolean values are not equal
OnesComplement	Returns the result of a one's complement operation on the specified OracleBoolean value
Or	Returns the result of bitwise OR operation of two OracleBoolean instances
Parse	Returns an OracleBoolean structure and sets its value using a string
Xor	Returns the result of a bitwise exclusive OR operation of two OracleBoolean instances

OracleBoolean Static Operators

The OracleBoolean static operators are listed in [Table 14-17](#).

Table 14-17 OracleBoolean Static Operators

Field	Description
operator >	Determines whether or not the first of two OracleBoolean values is greater than the second
operator >=	Determines whether or not the first of two OracleBoolean values is greater than or equal to the second
operator <	Determines whether or not the first of two OracleBoolean values is less than the second
operator <=	Determines whether or not the first of two OracleBoolean values is less than or equal to the second
operator ==	Indicates whether or not the two OracleBoolean instances are equal

Table 14-17 (Cont.) OracleBoolean Static Operators

Field	Description
operator !=	Determines whether or not two OracleBoolean values are not equal
operator !	Determines the result of a NOT operation on a OracleBoolean
operator ~	Returns the result of a one's complement operation on the specified OracleBoolean value
operator false	Determines whether or not the specified OracleBoolean value is false
operator true	Determines whether or not the specified OracleBoolean value is true
operator &	Returns the result of bitwise AND operation of two OracleBoolean instances
operator 	Returns the result of bitwise OR operation of two OracleBoolean instances
operator ^	Returns the result of bitwise exclusive OR operation of two OracleBoolean instances

The OracleBoolean Static Type conversions

The OracleBoolean static type conversions are listed in [Table 14-18](#)

Table 14-18 OracleBoolean Static Type Conversions

Field	Description
implicit operator OracleBoolean	Returns the OracleBoolean representation of a boolean value
explicit operator bool	Returns the boolean representation of the OracleBoolean value
explicit operator OracleBoolean	Converts a structure to an OracleBoolean structure (Overloaded)

OracleBoolean Properties

The OracleBoolean properties are listed in [Table 14-25](#).

Table 14-19 OracleBoolean Properties

Properties	Description
ByteValue	Returns a byte that represents the OracleBoolean structure
IsFalse	Indicates whether or not the value of the current instance is false
IsNull	Indicates whether or not the current instance has a null value
IsTrue	Indicates whether or not the value of the current instance is true
Value	Returns a boolean value that represents the current instance

OracleBoolean Instance Methods

The `OracleBoolean` instance methods are listed in [Table 14-20](#).

Table 14-20 OracleBoolean Instance Methods

Method	Description
CompareTo	Compares the current instance to the supplied object and returns an integer that represents their relative values
Equals	Determines whether or not an object is an instance of <code>OracleBoolean</code> , and whether or not the value of the object is equal to the current instance
GetHashCode	Returns a hash code for the current instance
ToString	Returns the <code>string</code> representation of the current instance

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)

OracleBoolean Constructors

The `OracleBoolean` constructors instantiates a new instance of the `OracleBoolean` structure.

Overload List:

- [OracleBoolean\(bool\)](#)
This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Boolean` value.
- [OracleBoolean\(int\)](#)
This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Int32` value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean(bool)

This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Boolean` value.

Declaration

```
// C#  
public OracleBoolean(bool value) ;
```

Parameters

- `value`
The provided `Boolean` value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean(int)

This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Int32` value.

Declaration

```
// C#  
public OracleBoolean(int value)
```

Parameters

- `value`
The provided `Int32` value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Fields

The OracleBoolean static fields are listed in [Table 14-21](#).

Table 14-21 OracleBoolean Static Fields

Field	Description
False	Represents a false value that can be assigned to an OracleBoolean instance
Null	Represents a null value that can be assigned to an OracleBoolean instance
One	Indicates a constant representing the positive one value
True	Represents a true value that can be assigned to an OracleBoolean instance
Zero	Indicates a constant representing the zero value

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

False

This static field represents a false value that can be assigned to an OracleBoolean instance.

Declaration

```
// C#  
public static readonly OracleBoolean False;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Null

This static field represents a null value that can be assigned to an `OracleBoolean` instance.

Declaration

```
// C#  
public static readonly OracleBoolean Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

One

This static field indicates a constant representing the positive one value.

Declaration

```
// C#  
public static readonly OracleBoolean One;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

True

This static field represents a true value that can be assigned to an `OracleBoolean` instance.

Declaration

```
// C#  
public static readonly OracleBoolean True;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Zero

This static field indicates a constant representing the zero value.

Declaration

```
// C#
public static readonly OracleBoolean Zero;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Methods

OracleBoolean static methods are listed in [Table 14-22](#)

Table 14-22 OracleBoolean Static Methods

Methods	Description
And	Returns the result of bitwise AND operation of two OracleBoolean instances
Equals	Determines whether or not the two OracleBoolean values are equal
GreaterThan	Determines whether or not the first of two OracleBoolean values is greater than the second
GreaterThanOrEquals	Determines whether or not the first of two OracleBoolean values is greater than or equal to the second
LessThan	Determines whether or not the first of two OracleBoolean values is less than the second
LessThanOrEquals	Determines whether or not the first of two OracleBoolean values is less than or equal to the second

Table 14-22 (Cont.) OracleBoolean Static Methods

Methods	Description
NotEquals	Determines whether or not two OracleBoolean values are not equal
OnesComplement	Returns the result of a one's complement operation on the specified OracleBoolean value
Or	Returns the result of bitwise OR operation of two OracleBoolean instances
Parse	Returns an OracleBoolean structure and sets its value using a string
Xor	Returns the result of a bitwise exclusive OR operation of two OracleBoolean instances

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

And

This method returns the result of bitwise AND operation of two OracleBoolean instances.

Declaration

```
// C#  
public static OracleBoolean And(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise AND operation of two OracleBoolean instances.

Remarks

If either of the specified `OracleBoolean` instances is null, an `OracleBoolean` with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Equals

This method returns an `OracleBoolean` that indicates whether or not the two `OracleBoolean` instances are equal.

Declaration

```
// C#  
public static OracleBoolean Equal(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An `OracleBoolean` instance
- *value2*
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that is true if the specified two `OracleBoolean` instances are equal; otherwise, returns an `OracleBoolean` that is false.

Remarks

If either of the specified `OracleBoolean` instances is null, an `OracleBoolean` with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

GreaterThan

This method determines if the first of two `OracleBoolean` values is greater than the second.

Declaration

```
// C#  
public static OracleBoolean GreaterThan(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- `value1`
The first `OracleBoolean`
- `value2`
The second `OracleBoolean`

Return Value

An `OracleBoolean` that is `true` if the first of two `OracleBoolean` values is greater than the second; otherwise, returns `false`.

Remarks

If either of the specified `OracleBoolean` instances is `null`, an `OracleBoolean` with a `null` value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

GreaterThanOrEquals

This method determines if the first of two `OracleBoolean` values is greater than or equal to the second.

Declaration

```
// C#  
public static OracleBoolean GreaterThanOrEquals(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- `value1`
The first `OracleBoolean`

- *value2*
The second OracleBoolean

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is greater than or equal to the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

LessThan

This method determines if the first of two OracleBoolean values is less than the second.

Declaration

```
// C#  
public static OracleBoolean LessThan(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
The first OracleBoolean
- *value2*
The second OracleBoolean

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is less than the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

LessThanOrEquals

This method determines if the first of two `OracleBoolean` values is less or equal than the second.

Declaration

```
// C#  
public static OracleBoolean LessThanOrEquals(OracleBoolean value1, OracleBoolean  
value2);
```

Parameters

- `value1`
The first `OracleBoolean`
- `value2`
The second `OracleBoolean`

Return Value

An `OracleBoolean` that is `true` if the first of two `OracleBoolean` values is less than or equal to the second; otherwise, returns `false`.

Remarks

If either of the specified `OracleBoolean` instances is `null`, an `OracleBoolean` with a null value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

NotEquals

This method determines if two `OracleBoolean` values are not equal.

Declaration

```
// C#  
public static OracleBoolean NotEquals(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
The first OracleBoolean
- *value2*
The second OracleBoolean

Return Value

An OracleBoolean that is true if two OracleBoolean values are not equal; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OnesComplement

This method returns the result of a one's complement operation on the specified OracleBoolean value.

Declaration

```
// C#  
public static OracleBoolean OnesComplement(OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of a one's complement operation on the specified OracleBoolean value.

Remarks

If the specified `OracleBoolean` instance is null, an `OracleBoolean` with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Or

This method returns the result of bitwise OR operation of two `OracleBoolean` instances.

Declaration

```
// C#  
public static OracleBoolean Or(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- `value1`
An `OracleBoolean` instance
- `value2`
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that contains the value of the result of bitwise OR operation of two `OracleBoolean` instances.

Remarks

If either of the specified `OracleBoolean` instances is null, an `OracleBoolean` with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Parse

This method converts a string to an OracleBoolean.

Declaration

```
// C#  
public static OracleBoolean Parse(string str);
```

Parameters

- *str*
The string being converted.

Return Value

A new OracleBoolean structure.

Exceptions

ArgumentNullException – The *str* parameter is null.

IndexOutOfRangeException – The *str* parameter is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Xor

This method returns the result of a bitwise exclusive OR operation of two OracleBoolean instances.

Declaration

```
// C#  
public static OracleBoolean Xor(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An `OracleBoolean` that contains the value of the result of bitwise exclusive OR operation of two `OracleBoolean` instances.

Remarks

If either of the specified `OracleBoolean` instances is null, an `OracleBoolean` with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Operators

The `OracleBoolean` static operators are listed in [Table 14-23](#).

Table 14-23 OracleBoolean Static Operators

Field	Description
<code>operator ></code>	Determines whether or not the first of two <code>OracleBoolean</code> values is greater than the second
<code>operator >=</code>	Determines whether or not the first of two <code>OracleBoolean</code> values is greater than or equal to the second
<code>operator <</code>	Determines whether or not the first of two <code>OracleBoolean</code> values is less than the second
<code>operator <=</code>	Determines whether or not the first of two <code>OracleBoolean</code> values is less than or equal to the second
<code>operator ==</code>	Indicates whether or not the two <code>OracleBoolean</code> instances are equal
<code>operator !=</code>	Determines whether or not two <code>OracleBoolean</code> values are not equal
<code>operator !</code>	Determines the result of a NOT operation on a <code>OracleBoolean</code>
<code>operator ~</code>	Returns the result of a one's complement operation on the specified <code>OracleBoolean</code> value
<code>operator false</code>	Determines whether or not the specified <code>OracleBoolean</code> value is false
<code>operator true</code>	Determines whether or not the specified <code>OracleBoolean</code> value is true
<code>operator &</code>	Returns the result of bitwise AND operation of two <code>OracleBoolean</code> instances

Table 14-23 (Cont.) OracleBoolean Static Operators

Field	Description
operator 	Returns the result of bitwise OR operation of two OracleBoolean instances
operator ^	Returns the result of bitwise exclusive OR operation of two OracleBoolean instances

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator >

This method determines whether or not the first of two OracleBoolean values is greater than the second.

Declaration

```
// C#  
public static operator > (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is greater than the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator >=

This method determines whether or not the first of two `OracleBoolean` values is greater than or equal to the second.

Declaration

```
// C#  
public static operator >= (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- `value1`
An `OracleBoolean` instance
- `value2`
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that is `true` if the first of two `OracleBoolean` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

If either of the specified `OracleBoolean` instances is `null`, an `OracleBoolean` with a `null` value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator <

This method determines whether or not the first of two `OracleBoolean` values is less than the second.

Declaration

```
// C#  
public static operator < (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is less than the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator <=

This method determines whether or not the first of two OracleBoolean values is less than or equal to the second.

Declaration

```
// C#  
public static operator <= (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An `OracleBoolean` that is `true` if the first of two `OracleBoolean` values is less than or equal to the second; otherwise, returns `false`.

Remarks

If either of the specified `OracleBoolean` instances is `null`, an `OracleBoolean` with a `null` value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator ==

This method returns an `OracleBoolean` that indicates whether or not the two `OracleBoolean` instances are equal.

Declaration

```
// C#  
public static operator == (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- `value1`
An `OracleBoolean` instance
- `value2`
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that is `true` if the specified two `OracleBoolean` instances are equal; otherwise, returns `false`.

Remarks

If either of the specified `OracleBoolean` instances is `null`, an `OracleBoolean` with a `null` value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator !=

This method determines whether or not two `OracleBoolean` values are not equal.

Declaration

```
// C#  
public static operator != (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An `OracleBoolean` instance
- *value2*
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that is true if two `OracleBoolean` values are not equal; otherwise, returns false.

Remarks

If either of the specified `OracleBoolean` instances is null, an `OracleBoolean` with a null value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator !

This method determines the result of a NOT operation on a `OracleBoolean`.

Declaration

```
// C#  
public static operator !(OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the specified OracleBoolean value is true; otherwise, returns false.

Remarks

If the specified OracleBoolean instance is null, an OracleBoolean with a null value will be returned.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator ~

This method returns the result of a one's complement operation on the specified OracleBoolean value.

Declaration

```
// C#  
public static operator ~(OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of a one's complement operation on the specified OracleBoolean value.

Remarks

If the specified OracleBoolean instance is null, an OracleBoolean with a null value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator false

This method determines whether or not the specified `OracleBoolean` value is false.

Declaration

```
// C#  
public static operator false (OracleBoolean value1);
```

Parameters

- `value1`
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that is true if specified `OracleBoolean` value is false; otherwise, returns false.

Remarks

This property will return `false` if the current instance is `null`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator true

This method determines whether or not the specified `OracleBoolean` value is true.

Declaration

```
// C#  
public static operator true (OracleBoolean value1);
```


Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if specified OracleBoolean value is true; otherwise, returns false.

Remarks

This property will return *false* if the current instance is *null*.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator &

This method returns the result of bitwise AND operation of two OracleBoolean instances.

Declaration

```
// C#  
public static operator & (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise AND operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is *null*, an OracleBoolean with a *null* value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator |

This method returns the result of bitwise OR operation of two `OracleBoolean` instances.

Declaration

```
// C#  
public static operator | (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- `value1`
An `OracleBoolean` instance
- `value2`
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that contains the value of the result of bitwise OR operation of two `OracleBoolean` instances.

Remarks

If either of the specified `OracleBoolean` instances is null, an `OracleBoolean` with a null value will be returned.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator ^

This method returns the result of bitwise exclusive OR operation of two `OracleBoolean` instances.

Declaration

```
// C#  
public static operator ^ (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise exclusive OR operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Type Conversions

The OracleBoolean static type conversions are listed in [Table 14-24](#)

Table 14-24 OracleBoolean Static Type Conversions

Field	Description
implicit operator OracleBoolean	Returns the OracleBoolean representation of a boolean value
explicit operator bool	Returns the boolean representation of the OracleBoolean value
explicit operator OracleBoolean	Converts a structure to an OracleBoolean structure (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

implicit operator OracleBoolean

This method returns the `OracleBoolean` representation of a boolean value.

Declaration

```
// C#  
public static implicit operator OracleBoolean(bool value1);
```

Parameters

- `value1`
An `OracleBoolean` instance

Return Value

An `OracleBoolean`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator bool

This method returns the boolean representation of the `OracleBoolean` value.

Declaration

```
// C#  
public static explicit operator bool(OracleBoolean value1);
```

Parameters

- `value1`
An `OracleBoolean` structure

Return Value

A boolean

Exception

OracleNullValueException – OracleBoolean has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean

explicit operator OracleBoolean converts the provided structure to an OracleBoolean structure.

Overload List

- [explicit operator OracleBoolean\(byte\)](#)
This method converts the supplied byte to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Decimal\)](#)
This method converts the supplied Decimal to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Double\)](#)
This method converts the supplied Double to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Int16\)](#)
This method converts the supplied Int16 to an OracleBoolean structure.
- [explicit operator OracleBoolean\(int\)](#)
This method converts the supplied int to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Int64\)](#)
This method converts the supplied Int64 to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Single\)](#)
This method converts the supplied Single to an OracleBoolean structure.
- [explicit operator OracleBoolean\(String\)](#)
This method converts the supplied String to an OracleBoolean structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(byte)

This method converts the supplied byte to an `OracleBoolean` structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(byte value1);
```

Parameters

- *value1*
A byte

Return Value

An `OracleBoolean` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Decimal)

This method converts the supplied `Decimal` to an `OracleBoolean` structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Decimal value1);
```

Parameters

- *value1*
A `Decimal`

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Double)

This method converts the supplied Double to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Double value1);
```

Parameters

- *value1*
A Double

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Int16)

This method converts the supplied Int16 to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Int16 value1);
```

Parameters

- *value1*
An Int16

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(int)

This method converts the supplied int to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(int value1);
```

Parameters

- *value1*
An int

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Int64)

This method converts the supplied Int64 to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Int64 value1);
```

Parameters

- *value1*
An Int64

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Single)

This method converts the supplied Single to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Single value1);
```

Parameters

- *value1*
A Single

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(String)

This method converts the supplied String to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(String value1);
```

Parameters

- *value1*
A String

Return Value

An OracleBoolean structure.

See Also:


- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Properties

The OracleBoolean properties are listed in [Table 14-25](#).

Table 14-25 OracleBoolean Properties

Properties	Description
ByteValue	Returns a byte that represents the OracleBoolean structure
IsFalse	Indicates whether or not the value of the current instance is false
IsNull	Indicates whether or not the current instance has a null value
IsTrue	Indicates whether or not the value of the current instance is true
Value	Returns a boolean value that represents the current instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

ByteValue

This property returns a byte that represents the `OracleBoolean` structure.

Declaration

```
// C#  
public byte ByteValue {get;}
```

Property Value

A byte that represents the value of `OracleBoolean` structure.

Exceptions

`OracleNullValueException` – The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

IsFalse

This property indicates whether or not the value of the current instance is false.

Declaration

```
// C#  
public bool IsFalse {get;}
```

Property Value

A `bool` value that returns `true` if the current instance is false; otherwise, returns `false`.

Remarks

This property will return `false` if the current instance is null.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

A bool value that returns `true` if the current instance has a null value; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

IsTrue

This property indicates whether or not the value of the current instance is true.

Declaration

```
// C#  
public bool IsTrue {get;}
```

Property Value

A bool value that returns `true` if the current instance is true; otherwise, returns `false`.

Remarks

This property will return `false` if the current instance is null.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Value

This property returns a boolean value that represents the current instance.

Declaration

```
// C#
public bool Value {get;}
```

Property Value

A bool value that returns true if the current instance is true; otherwise, returns false.

Exceptions

`OracleNullValueException` – The current instance has a null value.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Instance Methods

The `OracleBoolean` instance methods are listed in [Table 14-26](#).

Table 14-26 OracleBoolean Instance Methods

Method	Description
CompareTo	Compares the current instance to the supplied object and returns an integer that represents their relative values
Equals	Determines whether or not an object is an instance of <code>OracleBoolean</code> , and whether or not the value of the object is equal to the current instance
GetHashCode	Returns a hash code for the current instance
ToString	Returns the <code>string</code> representation of the current instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

CompareTo

This method compares the current instance to the supplied object and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameter

- *obj*
The supplied instance.

Return Value

The method returns a number:

- Less than zero: if the value of the current instance is less than *obj*.
- Zero: if the value of the current instance is equal to *obj*.
- Greater than zero: if the value of the current instance is greater than *obj*.

Implements

Comparable

Exceptions

ArgumentException - The parameter is not of type OracleBoolean.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between OracleBoolean. For example, comparing an OracleBoolean instance with an OracleBinary instance is not allowed. When an OracleBoolean is compared with a different type, an ArgumentException is thrown.
- Any OracleBoolean that has a value compares greater than an OracleBoolean that has a null value.
- Two OracleBoolean that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Equals

Overrides `Object`

This method determines whether or not an object is an instance of `OracleBoolean`, and whether or not the value of the object is equal to the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameter

- `obj`
An `OracleBoolean` instance.

Return Value

Returns `true` if `obj` is an instance of `OracleBoolean`, and the value of `obj` is equal to the current instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBoolean` that has a value compares greater than an `OracleBoolean` that has a null value.
- Two `OracleBooleans` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the current instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

Returns a hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

ToString

Overrides `Object`

This method returns the string representation of the current instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns the `OracleBoolean` value in a string representation.

Remarks

If the current instance has a null value, the returned string is `null`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleDate Structure

The `OracleDate` structure represents the Oracle `DATE` data type to be stored in or retrieved from a database. Each `OracleDate` stores the following information: year, month, day, hour, minute, and second.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleDate`

Declaration

```
// C#
public struct OracleDate : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleDateSample
{
    static void Main(string[] args)
    {
        // Initialize the dates to the lower and upper boundaries
        OracleDate date1 = OracleDate.MinValue;
        OracleDate date2 = OracleDate.MaxValue;
        OracleDate date3 = new OracleDate(DateTime.MinValue);
        OracleDate date4 = new OracleDate(DateTime.MaxValue);

        // Set the thread's DateFormat for output
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
```

```

info.DateFormat = "DD-MON-YYYY BC";
OracleGlobalization.SetThreadInfo(info);

// Print the lower and upper boundaries
Console.WriteLine("OracleDate ranges from\n{0}\nto\n{1}\n",
    date1, date2);
Console.WriteLine(".NET DateTime ranges from\n{0}\nto\n{1}\n",
    date3, date4);
}
}

```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Members](#)
- [OracleDate Constructors](#)
- [OracleDate Static Fields](#)
- [OracleDate Static Methods](#)
- [OracleDate Static Operators](#)
- [OracleDate Static Type Conversions](#)
- [OracleDate Properties](#)
- [OracleDate Methods](#)

OracleDate Members

OracleDate members are listed in the following tables:

OracleDate Constructors

OracleDate constructors are listed in [Table 14-27](#)

Table 14-27 OracleDate Constructors

Constructor	Description
OracleDate Constructors	Instantiates a new instance of OracleDate structure (Overloaded)

OracleDate Static Fields

The OracleDate static fields are listed in [Table 14-28](#).

Table 14-28 OracleDate Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59
MinValue	Represents the minimum valid date for an OracleDate structure, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to the value of an OracleDate structure instance

OracleDate Static Methods

The OracleDate static methods are listed in [Table 14-29](#).

Table 14-29 OracleDate Static Methods

Methods	Description
Equals	Determines if two OracleDate values are equal (Overloaded)
GreaterThan	Determines if the first of two OracleDate values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleDate values is greater than or equal to the second
LessThan	Determines if the first of two OracleDate values is less than the second
LessThanOrEqual	Determines if the first of two OracleDate values is less than or equal to the second
NotEquals	Determines if two OracleDate values are not equal
GetSysDate	Returns an OracleDate structure that represents the current date and time
Parse	Returns an OracleDate structure and sets its value using a string

OracleDate Static Operators

The OracleDate static operators are listed in [Table 14-30](#).

Table 14-30 OracleDate Static Operators

Operator	Description
operator ==	Determines if two OracleDate values are the same
operator >	Determines if the first of two OracleDate values is greater than the second
operator >=	Determines if the first of two OracleDate values is greater than or equal to the second
operator !=	Determines if the two OracleDate values are not equal

Table 14-30 (Cont.) OracleDate Static Operators

Operator	Description
<code>operator <</code>	Determines if the first of two OracleDate values is less than the second
<code>operator <=</code>	Determines if the first of two OracleDate values is less than or equal to the second

OracleDate Static Type Conversions

The OracleDate static type conversions are listed in [Table 14-31](#).

Table 14-31 OracleDate Static Type Conversions

Operator	Description
<code>explicit operator DateTime</code>	Converts a structure to a DateTime structure
<code>explicit operator OracleDate</code>	Converts a structure to an OracleDate structure (Overloaded)

OracleDate Properties

The OracleDate properties are listed in [Table 14-32](#).

Table 14-32 OracleDate Properties

Properties	Description
<code>BinData</code>	Gets an array of bytes that represents an Oracle DATE in Oracle internal format
<code>Day</code>	Gets the day component of an OracleDate method
<code>IsNull</code>	Indicates whether or not the current instance has a null value
<code>Hour</code>	Gets the hour component of an OracleDate
<code>Minute</code>	Gets the minute component of an OracleDate
<code>Month</code>	Gets the month component of an OracleDate
<code>Second</code>	Gets the second component of an OracleDate
<code>Value</code>	Gets the date and time that is stored in the OracleDate structure
<code>Year</code>	Gets the year component of an OracleDate

OracleDate Methods

The OracleDate methods are listed in [Table 14-33](#).

Table 14-33 OracleDate Methods

Methods	Description
CompareTo	Compares the current <code>OracleDate</code> instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current <code>OracleDate</code> instance (Overloaded)
GetHashCode	Returns a hash code for the <code>OracleDate</code> instance
GetDaysBetween	Calculates the number of days between the current <code>OracleDate</code> instance and an <code>OracleDate</code> structure
GetType	Inherited from <code>System.Object</code>
ToOracleTimeStamp	Converts the current <code>OracleDate</code> structure to an <code>OracleTimeStamp</code> structure
ToString	Converts the current <code>OracleDate</code> structure to a string

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)

OracleDate Constructors

The `OracleDate` constructors instantiates a new instance of the `OracleDate` structure.

Overload List:

- [OracleDate\(DateTime\)](#)
This constructor creates a new instance of the `OracleDate` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleDate\(string\)](#)
This constructor creates a new instance of the `OracleDate` structure and sets its value using the supplied string.
- [OracleDate\(int, int, int\)](#)
This constructor creates a new instance of the `OracleDate` structure and set its value for date using the supplied year, month, and day.
- [OracleDate\(int, int, int, int, int, int\)](#)
This constructor creates a new instance of the `OracleDate` structure and set its value for time using the supplied year, month, day, hour, minute, and second.
- [OracleDate\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleDate` structure and sets its value to the provided byte array, which is in the internal Oracle `DATE` format.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(DateTime)

This constructor creates a new instance of the `OracleDate` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleDate (DateTime dt);
```

Parameters

- `dt`
The provided `DateTime` value.

Remarks

The `OracleDate` structure only supports up to a second precision. The time value in the provided `DateTime` structure that has a precision smaller than second is ignored.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(string)

This constructor creates a new instance of the `OracleDate` structure and sets its value using the supplied string.

Declaration

```
// C#  
public OracleDate (string dateStr);
```

Parameters

- *dateStr*
A string that represents an Oracle DATE.

Exceptions

ArgumentException - The *dateStr* is an invalid string representation of an Oracle DATE or the *dateStr* is not in the date format specified by the thread's `OracleGlobalization.DateFormat` property, which represents the Oracle `NLS_DATE_FORMAT` parameter.

ArgumentNullException - The *dateStr* is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleDateSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat for the OracleDate constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleDate from a string using the DateFormat specified.
        OracleDate date = new OracleDate("1999-DEC-01");

        // Set a different DateFormat for the thread
        info.DateFormat = "MM/DD/YYYY";
        OracleGlobalization.SetThreadInfo(info);

        // Print "12/01/1999"
        Console.WriteLine(date.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#)
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleDate(int, int, int)

This constructor creates a new instance of the `OracleDate` structure and set its value for date using the supplied year, month, and day.

Declaration

```
// C#  
public OracleDate (int year, int month, int day);
```

Parameters

- *year*
The supplied year. Range of *year* is (-4712 to 9999).
- *month*
The supplied month. Range of *month* is (1 to 12).
- *day*
The supplied day. Range of *day* is (1 to 31).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleDate` (that is, the day is out of range for the month).

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleDate` structure and set its value for time using the supplied year, month, day, hour, minute, and second.

Declaration

```
// C#  
public OracleDate (int year, int month, int day, int hour, int minute, int second);
```

Parameters

- *year*
The supplied year. Range of *year* is (-4712 to 9999).
- *month*
The supplied month. Range of *month* is (1 to 12).
- *day*
The supplied day. Range of *day* is (1 to 31).
- *hour*
The supplied hour. Range of *hour* is (0 to 23).
- *minute*
The supplied minute. Range of *minute* is (0 to 59).
- *second*
The supplied second. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleDate` (that is, the day is out of range for the month).



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(byte [])

This constructor creates a new instance of the `OracleDate` structure and sets its value to the provided byte array, which is in the internal Oracle `DATE` format.

Declaration

```
// C#
public OracleDate(byte [] bytes);
```

Parameters

- *bytes*
A byte array that represents Oracle DATE in the internal Oracle DATE format.

Exceptions

ArgumentException - *bytes* is null or *bytes* is not in internal Oracle DATE format or *bytes* is not a valid Oracle DATE.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Static Fields

The OracleDate static fields are listed in [Table 14-34](#).

Table 14-34 OracleDate Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59
MinValue	Represents the minimum valid date for an OracleDate structure, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to the value of an OracleDate structure instance

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

MaxValue

This static field represents the maximum valid date for an `OracleDate` structure, which is December 31, 9999 23:59:59.

Declaration

```
// C#  
public static readonly OracleDate MaxValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

MinValue

This static field represents the minimum valid date for an `OracleDate` structure, which is January 1, -4712.

Declaration

```
// C#  
public static readonly OracleDate MinValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Null

This static field represents a null value that can be assigned to the value of an `OracleDate` instance.

Declaration

```
// C#  
public static readonly OracleDate Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Static Methods

The `OracleDate` static methods are listed in [Table 14-35](#).

Table 14-35 OracleDate Static Methods

Methods	Description
Equals	Determines if two <code>OracleDate</code> values are equal (Overloaded)
GreaterThan	Determines if the first of two <code>OracleDate</code> values is greater than the second
GreaterThanOrEqual	Determines if the first of two <code>OracleDate</code> values is greater than or equal to the second
LessThan	Determines if the first of two <code>OracleDate</code> values is less than the second
LessThanOrEqual	Determines if the first of two <code>OracleDate</code> values is less than or equal to the second
NotEquals	Determines if two <code>OracleDate</code> values are not equal
GetSysDate	Returns an <code>OracleDate</code> structure that represents the current date and time
Parse	Returns an <code>OracleDate</code> structure and sets its value using a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Equals

Overloads `Object`

This method determines if two `OracleDate` values are equal.

Declaration

```
// C#  
public static bool Equals(OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if two OracleDate values are equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

GreaterThan

This method determines if the first of two OracleDate values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns `true` if the first of two `OracleDate` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

GreaterThanOrEqual

This method determines if the first of two `OracleDate` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleDate value1, OracleDate value2);
```

Parameters

- `value1`
The first `OracleDate`.
- `value2`
The second `OracleDate`.

Return Value

Returns `true` if the first of two `OracleDate` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

LessThan

This method determines if the first of two `OracleDate` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleDate value1, OracleDate value2);
```

Parameters

- `value1`
The first `OracleDate`.
- `value2`
The second `OracleDate`.

Return Value

Returns `true` if the first of two `OracleDate` values is less than the second. Otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

LessThanOrEqual

This method determines if the first of two `OracleDate` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleDate value1, OracleDate value2);
```

Parameters

- `value1`
The first `OracleDate`.
- `value2`
The second `OracleDate`.

Return Value

Returns `true` if the first of two `OracleDate` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

NotEquals

This method determines if two `OracleDate` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleDate value1, OracleDate value2);
```

Parameters

- `value1`

The first OracleDate.

- *value2*

The second OracleDate.

Return Value

Returns true if two OracleDate values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

GetSysDate

This method gets an OracleDate structure that represents the current date and time.

Declaration

```
// C#  
public static OracleDate GetSysDate ();
```

Return Value

An OracleDate structure that represents the current date and time.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Parse

This method gets an `OracleDate` structure and sets its value for date and time using the supplied string.

Declaration

```
// C#  
public static OracleDate Parse (string dateStr);
```

Parameters

- *dateStr*
A string that represents an Oracle DATE.

Return Value

An `OracleDate` structure.

Exceptions

`ArgumentException` - The *dateStr* is an invalid string representation of an Oracle DATE or the *dateStr* is not in the date format specified by the thread's `OracleGlobalization.DateFormat` property, which represents the Oracle NLS_DATE_FORMAT parameter.

`ArgumentNullException` - The *dateStr* is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class ParseSample  
{  
    static void Main(string[] args)  
    {  
        // Set the thread's DateFormat for the OracleDate constructor  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.DateFormat = "YYYY-MON-DD";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // Construct OracleDate from a string using the DateFormat specified  
        OracleDate date = OracleDate.Parse("1999-DEC-01");  
  
        // Set a different DateFormat on the thread for ToString()  
        info.DateFormat = "MM-DD-YY";  
        OracleGlobalization.SetThreadInfo(info);  
    }  
}
```

```
// Print "12-01-1999"
Console.WriteLine(date.ToString());
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)
- *Oracle Database SQL Language Reference* for further information on datetime format elements

OracleDate Static Operators

The OracleDate static operators are listed in [Table 14-36](#).

Table 14-36 OracleDate Static Operators

Operator	Description
<code>operator ==</code>	Determines if two OracleDate values are the same
<code>operator ></code>	Determines if the first of two OracleDate values is greater than the second
<code>operator >=</code>	Determines if the first of two OracleDate values is greater than or equal to the second
<code>operator !=</code>	Determines if the two OracleDate values are not equal
<code>operator <</code>	Determines if the first of two OracleDate values is less than the second
<code>operator <=</code>	Determines if the first of two OracleDate values is less than or equal to the second

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator ==

This method determines if two `OracleDate` values are the same.

Declaration

```
// C#  
public static bool operator == (OracleDate value1, OracleDate value2);
```

Parameters

- `value1`
The first `OracleDate`.
- `value2`
The second `OracleDate`.

Return Value

Returns `true` if they are the same; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator >

This method determines if the first of two `OracleDate` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleDate value1, OracleDate value2);
```

Parameters

- `value1`
The first `OracleDate`.

- *value2*
The second OracleDate.

Return Value

Returns `true` if the first of two OracleDate values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator >=

This method determines if the first of two OracleDate values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns `true` if the first of two OracleDate values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.

- Two `OracleDate`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator `!=`

This method determines if the two `OracleDate` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleDate value1, OracleDate value2);
```

Parameters

- `value1`
The first `OracleDate`.
- `value2`
The second `OracleDate`.

Return Value

Returns `true` if the two `OracleDate` values are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDate`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator <

This method determines if the first of two `OracleDate` values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleDate value1, OracleDate value2);
```

Parameters

- `value1`
The first `OracleDate`.
- `value2`
The second `OracleDate`.

Return Value

Returns `true` if the first of two `OracleDate` values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator <=

This method determines if the first of two `OracleDate` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleDate value1, OracleDate value2);
```

Parameters

- `value1`

The first `OracleDate`.

- `value2`

The second `OracleDate`.

Return Value

Returns `true` if the first of two `OracleDate` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Static Type Conversions

The `OracleDate` static type conversions are listed in [Table 14-37](#).

Table 14-37 OracleDate Static Type Conversions

Operator	Description
explicit operator DateTime	Converts a structure to a <code>DateTime</code> structure
explicit operator OracleDate	Converts a structure to an <code>OracleDate</code> structure (Overloaded)

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator DateTime

This method converts an `OracleDate` structure to a `DateTime` structure.

Declaration

```
// C#  
public static explicit operator DateTime(OracleDate val);
```

Parameters

- `val`
An `OracleDate` structure.

Return Value

A `DateTime` structure.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate

`explicit operator OracleDate` converts the provided structure to an `OracleDate` structure.

Overload List:

- [explicit operator OracleDate\(DateTime\)](#)
This method converts a `DateTime` structure to an `OracleDate` structure.
- [explicit operator OracleDate\(OracleTimeStamp\)](#)
This method converts an `OracleTimeStamp` structure to an `OracleDate` structure.
- [explicit operator OracleDate\(string\)](#)
This method converts the supplied string to an `OracleDate` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate(DateTime)

This method converts a `DateTime` structure to an `OracleDate` structure.

Declaration

```
// C#  
public static explicit operator OracleDate(DateTime dt);
```

Parameters

- *dt*
A `DateTime` structure.

Return Value

An `OracleDate` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate(OracleTimeStamp)

This method converts an `OracleTimeStamp` structure to an `OracleDate` structure.

Declaration

```
// C#  
public explicit operator OracleDate(OracleTimeStamp ts);
```

Parameters

- *ts*
`OracleTimeStamp`

Return Value

The returned `OracleDate` structure contains the date and time in the `OracleTimeStamp` structure.

Remarks

The precision of the `OracleTimeStamp` value can be lost during the conversion.

If the `OracleTimeStamp` structure has a null value, the returned `OracleDate` structure also has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate(string)

This method converts the supplied string to an `OracleDate` structure.

Declaration

```
// C#  
public explicit operator OracleDate (string dateStr);
```

Parameters

- *dateStr*
A string representation of an Oracle `DATE`.

Return Value

The returned `OracleDate` structure contains the date and time in the string *dateStr*.

Exceptions

`ArgumentNullException` - The *dateStr* is null.

`ArgumentException` - This exception is thrown if any of the following conditions exist:

- The *dateStr* is an invalid string representation of an Oracle `DATE`.
- The *dateStr* is not in the date format specified by the thread's `OracleGlobalization.DateFormat` property, which represents the Oracle `NLS_DATE_FORMAT` parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization`

object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleDateSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat to a specific format
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // Construct OracleDate from a string using the DateFormat specified
        OracleDate date = (OracleDate)"1999-DEC-01";

        // Set a different DateFormat on the thread for ToString()
        info.DateFormat = "MON DD YY";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "DEC 01 99"
        Console.WriteLine(date.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

OracleDate Properties

The `OracleDate` properties are listed in [Table 14-38](#).

Table 14-38 OracleDate Properties

Properties	Description
BinData	Gets an array of bytes that represents an Oracle DATE in Oracle internal format
Day	Gets the day component of an <code>OracleDate</code> method

Table 14-38 (Cont.) OracleDate Properties

Properties	Description
IsNull	Indicates whether or not the current instance has a null value
Hour	Gets the hour component of an OracleDate
Minute	Gets the minute component of an OracleDate
Month	Gets the month component of an OracleDate
Second	Gets the second component of an OracleDate
Value	Gets the date and time that is stored in the OracleDate structure
Year	Gets the year component of an OracleDate

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

BinData

This property gets a array of bytes that represents an Oracle DATE in Oracle internal format.

Declaration

```
// C#  
public byte[] BinData{get;}
```

Property Value

An array of bytes.

Exceptions

OracleNullValueException - OracleDate has a null value.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Day

This property gets the day component of an `OracleDate`.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of `Day` is (1 to 31).

Exceptions

`OracleNullValueException` - `OracleDate` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Hour

This property gets the `hour` component of an `OracleDate`.

Declaration

```
// C#  
public int Hour {get;}
```

Property Value

A number that represents `Hour`. Range of `Hour` is (0 to 23).

Exceptions

`OracleNullValueException` - `OracleDate` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Minute

This property gets the minute component of an `OracleDate`.

Declaration

```
// C#  
public int Minute {get;}
```

Property Value

A number that represents `Minute`. Range of `Minute` is (0 to 59).

Exceptions

`OracleNullValueException` - `OracleDate` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Month

This property gets the month component of an `OracleDate`.

Declaration

```
// C#  
public int Month {get;}
```

Property Value

A number that represents Month. Range of Month is (1 to 12).

Exceptions

OracleNullValueException - OracleDate has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Second

This property gets the second component of an OracleDate.

Declaration

```
// C#  
public int Second {get;}
```

Property Value

A number that represents Second. Range of Second is (0 to 59).

Exceptions

OracleNullValueException - OracleDate has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Value

This property specifies the date and time that is stored in the OracleDate structure.

Declaration

```
// C#  
public DateTime Value {get;}
```

Property Value

A `DateTime`.

Exceptions

`OracleNullValueException` - `OracleDate` has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Year

This property gets the `year` component of an `OracleDate`.

Declaration

```
// C#  
public int Year {get;}
```

Property Value

A number that represents `Year`. Range of `Year` is (-4712 to 9999).

Exceptions

`OracleNullValueException` - `OracleDate` has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Methods

The `OracleDate` methods are listed in [Table 14-39](#).

Table 14-39 OracleDate Methods

Methods	Description
CompareTo	Compares the current <code>OracleDate</code> instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current <code>OracleDate</code> instance (Overloaded)
GetHashCode	Returns a hash code for the <code>OracleDate</code> instance
GetDaysBetween	Calculates the number of days between the current <code>OracleDate</code> instance and an <code>OracleDate</code> structure
GetType	Inherited from <code>System.Object</code>
ToOracleTimeStamp	Converts the current <code>OracleDate</code> structure to an <code>OracleTimeStamp</code> structure
ToString	Converts the current <code>OracleDate</code> structure to a string

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

CompareTo

This method compares the current `OracleDate` instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
An object.

Return Value

The method returns:

- Less than zero: if the current `OracleDate` instance value is less than that of *obj*.
- Zero: if the current `OracleDate` instance and *obj* values are equal.
- Greater than zero: if the current `OracleDate` instance value is greater than *obj*.

Implements

IComparable

Exceptions

ArgumentException - The *obj* parameter is not an instance of OracleDate.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between OracleDates. For example, comparing an OracleDate instance with an OracleBinary instance is not allowed. When an OracleDate is compared with a different type, an ArgumentException is thrown.
- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

Equals

This method determines whether or not an object has the same date and time as the current OracleDate instance.

Declaration

```
// C#  
public override bool Equals( object obj);
```

Parameters

- *obj*
An object.

Return Value

Returns `true` if *obj* has the same type as the current instance and represents the same date and time; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleDate` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

GetDaysBetween

This method calculates the number of days between the current `OracleDate` instance and the supplied `OracleDate` structure.

Declaration

```
// C#  
public int GetDaysBetween (OracleDate val);
```

Parameters

- `val`
An `OracleDate` structure.

Return Value

The number of days between the current `OracleDate` instance and the `OracleDate` structure.

Exceptions

`OracleNullValueException` - The current instance or the supplied `OracleDate` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

ToOracleTimeStamp

This method converts the current `OracleDate` structure to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```

Return Value

An `OracleTimeStamp` structure.

Remarks

The returned `OracleTimeStamp` structure has date and time in the current instance.

If the `OracleDate` instance has a null value, the returned `OracleTimeStamp` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

ToString

Overrides ValueType

This method converts the current OracleDate structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string.

Remarks

The returned value is a string representation of the OracleDate in the format specified by the thread's OracleGlobalization.DateFormat property. The names and abbreviations used for months and days are in the language specified by the thread's OracleGlobalization.DateLanguage and OracleGlobalization.Calendar properties. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class ToStringSample  
{  
    static void Main(string[] args)  
    {  
        // Set the thread's DateFormat to a specific format  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.DateFormat = "YYYY-MON-DD";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // Construct OracleDate from a string using the DateFormat specified  
        OracleDate date = (OracleDate)"1999-DEC-01";  
  
        // Set a different DateFormat on the thread for ToString()  
        info.DateFormat = "YYYY/MM/DD";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // Prints "1999/12/01"  
        Console.WriteLine(date.ToString());  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

OracleDecimal Structure

The `OracleDecimal` structure represents an Oracle `NUMBER` in the database or any Oracle numeric value.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleDecimal`

Declaration

```
// C#
public struct OracleDecimal : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

`OracleDecimal` can store up to 38 precision, while the `.NET Decimal` data type can only hold up to 28 precision. When accessing the `OracleDecimal.Value` property from an `OracleDecimal` that has a value greater than 28 precision, an exception is thrown. To retrieve the actual value of `OracleDecimal`, use the `OracleDecimal.ToString()`

method. Another approach is to obtain the `OracleDecimal` value as a byte array in an internal Oracle `NUMBER` format through the `BinData` property.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class OracleDecimalSample  
{  
    static void Main(string[] args)  
    {  
        // Illustrates the range of OracleDecimal vs. .NET decimal  
        OracleDecimal decimal1 = OracleDecimal.MinValue;  
        OracleDecimal decimal2 = OracleDecimal.MaxValue;  
        OracleDecimal decimal3 = new OracleDecimal(decimal.MinValue);  
        OracleDecimal decimal4 = new OracleDecimal(decimal.MaxValue);  
  
        // Print the ranges  
        Console.WriteLine("OracleDecimal can range from\n{0}\nto\n{1}\n",  
            decimal1, decimal2);  
        Console.WriteLine(".NET decimal can range from\n{0}\nto\n{1}\n",  
            decimal3, decimal4);  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Constructors](#)
- [OracleDecimal Static Fields](#)
- [OracleDecimal Static \(Comparison\) Methods](#)
- [OracleDecimal Static \(Manipulation\) Methods](#)
- [OracleDecimal Static \(Logarithmic\) Methods](#)
- [OracleDecimal Static \(Trigonometric\) Methods](#)
- [OracleDecimal Static \(Comparison\) Operators](#)
- [OracleDecimal Static Operators \(Conversion from .NET Type to OracleDecimal\)](#)
- [OracleDecimal Static Operators \(Conversion from OracleDecimal to .NET\)](#)
- [OracleDecimal Properties](#)
- [OracleDecimal Instance Methods](#)

OracleDecimal Members

OracleDecimal members are listed in the following tables:

OracleDecimal Constructors

OracleDecimal constructors are listed in [Table 14-40](#)

Table 14-40 OracleDecimal Constructors

Constructor	Description
OracleDecimal Constructors	Instantiates a new instance of OracleDecimal structure (Overloaded)

OracleDecimal Static Fields

The OracleDecimal static fields are listed in [Table 14-41](#).

Table 14-41 OracleDecimal Static Fields

Field	Description
MaxPrecision	A constant representing the maximum precision, which is 38
MaxScale	A constant representing the maximum scale, which is 127
MaxValue	A constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$
MinScale	A constant representing the minimum scale, which is -84
MinValue	A constant representing the minimum value for this structure, which is -1.0×10^{130}
NegativeOne	A constant representing the negative one value
Null	Represents a null value that can be assigned to an OracleDecimal instance
One	A constant representing the positive one value
Pi	A constant representing the numeric Pi value
Zero	A constant representing the zero value

OracleDecimal Static (Comparison) Methods

The OracleDecimal static (comparison) methods are listed in [Table 14-42](#).

Table 14-42 OracleDecimal Static (Comparison) Methods

Methods	Description
Equals	Determines if two OracleDecimal values are equal (Overloaded)
GreaterThan	Determines if the first of two OracleDecimal values is greater than the second

Table 14-42 (Cont.) OracleDecimal Static (Comparison) Methods

Methods	Description
GreaterThanOrEqualTo	Determines if the first of two OracleDecimal values is greater than or equal to the second
LessThan	Determines if the first of two OracleDecimal values is less than the second
LessThanOrEqualTo	Determines if the first of two OracleDecimal values is less than or equal to the second.
NotEquals	Determines if two OracleDecimal values are not equal

OracleDecimal Static (Manipulation) Methods

The OracleDecimal static (manipulation) methods are listed in [Table 14-43](#).

Table 14-43 OracleDecimal Static (Manipulation) Methods

Methods	Description
Abs	Returns the absolute value of an OracleDecimal
Add	Adds two OracleDecimal structures
AdjustScale	Returns a new OracleDecimal with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than original
Ceiling	Returns a new OracleDecimal structure with its value set to the ceiling of an OracleDecimal structure
ConvertToPrecScale	Returns a new OracleDecimal structure with a new precision and scale
Divide	Divides one OracleDecimal value by another
Floor	Returns a new OracleDecimal structure with its value set to the floor of an OracleDecimal structure
Max	Returns the maximum value of the two supplied OracleDecimal structures
Min	Returns the minimum value of the two supplied OracleDecimal structures
Mod	Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures
Multiply	Returns a new OracleDecimal structure with its value set to the result of multiplying two OracleDecimal structures
Negate	Returns a new OracleDecimal structure with its value set to the negation of the supplied OracleDecimal structure
Parse	Converts a string to an OracleDecimal
Round	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure and rounded off to the specified place

Table 14-43 (Cont.) OracleDecimal Static (Manipulation) Methods

Methods	Description
SetPrecision	Returns a new OracleDecimal structure with a new specified precision.
Shift	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure, and its decimal place shifted to the specified number of places to the right
Sign	Determines the sign of an OracleDecimal structure
Sqrt	Returns a new OracleDecimal structure with its value set to the square root of the supplied OracleDecimal structure
Subtract	Returns a new OracleDecimal structure with its value set to result of subtracting one OracleDecimal structure from another
Truncate	Truncates the OracleDecimal at a specified position

OracleDecimal Static (Logarithmic) Methods

The OracleDecimal static (logarithmic) methods are listed in [Table 14-44](#).

Table 14-44 OracleDecimal Static (Logarithmic) Methods

Methods	Description
Exp	Returns a new OracleDecimal structure with its value set to e raised to the supplied power
Log	Returns the supplied OracleDecimal structure with its value set to the logarithm of the supplied OracleDecimal structure (Overloaded)
Pow	Returns a new OracleDecimal structure with its value set to the supplied OracleDecimal structure raised to the supplied power (Overloaded)

OracleDecimal Static (Trigonometric) Methods

The OracleDecimal static (trigonometric) methods are listed in [Table 14-45](#).

Table 14-45 OracleDecimal Static (Trigonometric) Methods

Methods	Description
Acos	Returns an angle in radians whose cosine is the supplied OracleDecimal structure
Asin	Returns an angle in radians whose sine is the supplied OracleDecimal structure
Atan	Returns an angle in radians whose tangent is the supplied OracleDecimal structure
Atan2	Returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures

Table 14-45 (Cont.) OracleDecimal Static (Trigonometric) Methods

Methods	Description
Cos	Returns the cosine of the supplied angle in radians
Sin	Returns the sine of the supplied angle in radians
Tan	Returns the tangent of the supplied angle in radians
Cosh	Returns the hyperbolic cosine of the supplied angle in radians
Sinh	Returns the hyperbolic sine of the supplied angle in radians
Tanh	Returns the hyperbolic tangent of the supplied angle in radians

OracleDecimal Static (Comparison) Operators

The `OracleDecimal` static (comparison) operators are listed in [Table 14-46](#).

Table 14-46 OracleDecimal Static (Comparison) Operators

Operator	Description
operator +	Adds two <code>OracleDecimal</code> values
operator /	Divides one <code>OracleDecimal</code> value by another
operator ==	Determines if the two <code>OracleDecimal</code> values are equal
operator >	Determines if the first of two <code>OracleDecimal</code> values is greater than the second
operator >=	Determines if the first of two <code>OracleDecimal</code> values is greater than or equal to the second
operator !=	Determines if the two <code>OracleDecimal</code> values are not equal
operator <	Determines if the first of two <code>OracleDecimal</code> values is less than the second
operator <=	Determines if the first of two <code>OracleDecimal</code> values is less than or equal to the second
operator *	Multiplies two <code>OracleDecimal</code> structures
operator -	Subtracts one <code>OracleDecimal</code> structure from another
operator -	Negates an <code>OracleDecimal</code> structure
operator %	Returns a new <code>OracleDecimal</code> structure with its value set to the modulus of two <code>OracleDecimal</code> structures.

OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

The `OracleDecimal` static operators (Conversion from .NET Type to `OracleDecimal`) are listed in [Table 14-47](#).

Table 14-47 OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

Operator	Description
implicit operator OracleDecimal	Converts an instance value to an OracleDecimal structure (Overloaded)
explicit operator OracleDecimal	Converts an instance value to an OracleDecimal structure (Overloaded)

OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

The OracleDecimal static operators (Conversion from OracleDecimal to .NET) are listed in [Table 14-48](#).

Table 14-48 OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

Operator	Description
explicit operator byte	Returns the byte representation of the OracleDecimal value
explicit operator decimal	Returns the decimal representation of the OracleDecimal value
explicit operator double	Returns the double representation of the OracleDecimal value
explicit operator short	Returns the short representation of the OracleDecimal value
explicit operator int	Returns the int representation of the OracleDecimal value
explicit operator long	Returns the long representation of the OracleDecimal value
explicit operator float	Returns the float representation of the OracleDecimal value

OracleDecimal Properties

The OracleDecimal properties are listed in [Table 14-49](#).

Table 14-49 OracleDecimal Properties

Properties	Description
BinData	Returns a byte array that represents the Oracle NUMBER in Oracle internal format
Format	Specifies the format for ToString()
IsInt	Indicates whether or not the current instance is an integer
IsNull	Indicates whether or not the current instance has a null value
IsPositive	Indicates whether or not the current instance is greater than 0
IsZero	Indicates whether or not the current instance has a zero value
Value	Returns a decimal value

OracleDecimal Instance Methods

The `OracleDecimal` instance methods are listed in [Table 14-50](#).

Table 14-50 OracleDecimal Instance Methods

Method	Description
CompareTo	Compares the current instance to the supplied object and returns an integer that represents their relative values
Equals	Determines whether or not an object is an instance of <code>OracleDecimal</code> , and whether or not the value of the object is equal to the current instance (Overloaded)
GetHashCode	Returns a hash code for the current instance
GetType	Inherited from <code>System.Object</code>
ToByte	Returns the <code>byte</code> representation of the current instance
ToDouble	Returns the <code>double</code> representation of the current instance
ToInt16	Returns the <code>Int16</code> representation of the current instance
ToInt32	Returns the <code>Int32</code> representation of the current instance
ToInt64	Returns the <code>Int64</code> representation of the current instance
ToSingle	Returns the <code>Single</code> representation of the current instance
ToString	Overloads <code>Object.ToString()</code> Returns the <code>string</code> representation of the current instance

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Structure](#)

OracleDecimal Constructors

The `OracleDecimal` constructors instantiate a new instance of the `OracleDecimal` structure.

Overload List:

- [OracleDecimal\(byte \[\]\)](#)
This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied byte array, which is in an Oracle `NUMBER` format.
- [OracleDecimal\(decimal\)](#)
This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Decimal` value.
- [OracleDecimal\(double\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `double` value.

- [OracleDecimal\(int\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int32` value.

- [OracleDecimal\(float\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Single` value.

- [OracleDecimal\(long\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int64` value.

- [OracleDecimal\(string\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `string` value.

- [OracleDecimal\(string, string\)](#)

This constructor creates a new instance of the `OracleDecimal` structure with the supplied `string` value and number format.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(byte [])

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied byte array, which is in an Oracle `NUMBER` format.

Declaration

```
// C#  
public OracleDecimal(byte [] bytes);
```

Parameters

- *bytes*

A byte array that represents an Oracle `NUMBER` in an internal Oracle format.

Exceptions

`ArgumentException` - The *bytes* parameter is not in a internal Oracle `NUMBER` format or *bytes* has an invalid value.

`ArgumentNullException` - The *bytes* parameter is null.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(decimal)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Decimal` value.

Declaration

```
// C#  
public OracleDecimal(decimal decX);
```

Parameters

- *decX*
The provided `Decimal` value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(double)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `double` value.

Declaration

```
// C#  
public OracleDecimal(double doubleX)
```

Parameters

- *doubleX*
The provided `double` value.

Exceptions

`OverflowException` - The value of the supplied `double` is greater than the maximum value or less than the minimum value of `OracleDecimal`.

Remarks

`OracleDecimal` contains the following values depending on the provided double value:

- `double.PositiveInfinity`: positive infinity value
- `double.NegativeInfinity`: negative infinity value.
- `double.NaN`: null value

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(int)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int32` value.

Declaration

```
// C#  
public OracleDecimal(int intX);
```

Parameters

- `intX`
The provided `Int32` value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(float)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Single` value.

Declaration

```
// C#  
public OracleDecimal(float floatX);
```

Parameters

- `floatX`
The provided float value.

Remarks

`OracleDecimal` contains the following values depending on the provided float value:

`float.PositiveInfinity`: positive infinity value

`float.NegativeInfinity`: negative infinity value

`float.NaN`: null value

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(long)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int64` value.

Declaration

```
// C#  
public OracleDecimal(long longX);
```

Parameters

- `longX`
The provided `Int64` value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(string)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `string` value.

Declaration

```
// C#  
public OracleDecimal(string numStr);
```

Parameters

- `numStr`
The provided `string` value.

Exceptions

`ArgumentException` - The `numStr` parameter is an invalid string representation of an `OracleDecimal`.

`ArgumentNullException` - The `numStr` parameter is null.

`OverflowException` - The value of `numStr` is greater than the maximum value or less than the minimum value of `OracleDecimal`.

`input string format is incorrect` - The locale's numeric separator is a comma(,).

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

OracleDecimal(string, string)

This constructor creates a new instance of the `OracleDecimal` structure with the supplied `string` value and number format.

Declaration

```
// C#  
public OracleDecimal(string numStr, string format);
```

Parameters

- *numStr*
The provided string value.
- *format*
The provided number format.

Exceptions

ArgumentException - The *numStr* parameter is an invalid string representation of an `OracleDecimal` or the *numStr* is not in the numeric format specified by *format*.

ArgumentNullException - The *numStr* parameter is null.

OverflowException - The value of *numStr* parameter is greater than the maximum value or less than the minimum value of `OracleDecimal`.

Remarks

If the numeric format includes decimal and group separators, then the provided string must use those characters defined by the `OracleGlobalization.NumericCharacters` of the thread.

If the numeric format includes the currency symbol, ISO currency symbol, or the dual currency symbol, then the provided string must use those symbols defined by the `OracleGlobalization.Currency`, `OracleGlobalization.ISOCurrency`, and `OracleGlobalization.DualCurrency` properties respectively.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class OracleDecimalSample  
{  
    static void Main(string[] args)  
    {  
        // Set the nls parameters related to currency  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.Currency = "$";  
        info.NumericCharacters = ".,";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // Construct an OracleDecimal using a valid numeric format  
        OracleDecimal dec = new OracleDecimal("$2,222.22", "L9G999D99");  
  
        // Print "$2,222.22"  
        Console.WriteLine(dec.ToString());  
    }  
}
```

```
}
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

OracleDecimal Static Fields

The OracleDecimal static fields are listed in [Table 14-51](#).

Table 14-51 OracleDecimal Static Fields

Field	Description
MaxPrecision	A constant representing the maximum precision, which is 38
MaxScale	A constant representing the maximum scale, which is 127
MaxValue	A constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$
MinScale	A constant representing the minimum scale, which is -84
MinValue	A constant representing the minimum value for this structure, which is -1.0×10^{130}
NegativeOne	A constant representing the negative one value
Null	Represents a null value that can be assigned to an OracleDecimal instance
One	A constant representing the positive one value
Pi	A constant representing the numeric Pi value
Zero	A constant representing the zero value

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MaxPrecision

This static field represents the maximum precision, which is 38.

Declaration

```
// C#  
public static readonly byte MaxPrecision;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MaxScale

This static field a constant representing the maximum scale, which is 127.

Declaration

```
// C#  
public static readonly byte MaxScale;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MaxValue

This static field indicates a constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$ (38 nines followed by 88 zeroes).

Declaration

```
// C#  
public static readonly OracleDecimal MaxValue;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MinScale

This static field indicates a constant representing the maximum scale, which is -84.

Declaration

```
// C#  
public static readonly int MinScale;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MinValue

This static field indicates a constant representing the minimum value for this structure, which is -1.0×10^{130} .

Declaration

```
// C#  
public static readonly OracleDecimal MinValue;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

NegativeOne

This static field indicates a constant representing the negative one value.

Declaration

```
// C#  
public static readonly OracleDecimal NegativeOne;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Null

This static field represents a null value that can be assigned to an `OracleDecimal` instance.

Declaration

```
// C#  
public static readonly OracleDecimal Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

One

This static field indicates a constant representing the positive one value.

Declaration

```
// C#  
public static readonly OracleDecimal One;
```


 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pi

This static field indicates a constant representing the numeric Pi value.

Declaration

```
// C#  
public static readonly OracleDecimal Pi;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Zero

This static field indicates a constant representing the zero value.

Declaration

```
// C#  
public static readonly OracleDecimal Zero;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Comparison) Methods

The `OracleDecimal` static (comparison) methods are listed in [Table 14-52](#).

Table 14-52 OracleDecimal Static (Comparison) Methods

Methods	Description
Equals	Determines if two OracleDecimal values are equal (Overloaded)
GreaterThan	Determines if the first of two OracleDecimal values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleDecimal values is greater than or equal to the second
LessThan	Determines if the first of two OracleDecimal values is less than the second
LessThanOrEqual	Determines if the first of two OracleDecimal values is less than or equal to the second.
NotEquals	Determines if two OracleDecimal values are not equal

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Equals

This method determines if two OracleDecimal values are equal.

Declaration

```
// C#  
public static bool Equals(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*
The first OracleDecimal.
- *value2*
The second OracleDecimal.

Return Value

Returns true if two OracleDecimal values are equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

GreaterThan

This method determines if the first of two `OracleDecimal` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- `value1`
The first `OracleDecimal`.
- `value2`
The second `OracleDecimal`.

Return Value

Returns `true` if the first of two `OracleDecimal` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

GreaterThanOrEqual

This method determines if the first of two `OracleDecimal` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*
The first `OracleDecimal`.
- *value2*
The second `OracleDecimal`.

Return Value

Returns `true` if the first of two `OracleDecimal` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

LessThan

This method determines if the first of two `OracleDecimal` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- `value1`
The first `OracleDecimal`.
- `value2`
The second `OracleDecimal`.

Return Value

Returns `true` if the first of two `OracleDecimal` values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

LessThanOrEqual

This method determines if the first of two `OracleDecimal` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- `value1`

The first OracleDecimal.

- *value2*

The second OracleDecimal.

Return Value

Returns `true` if the first of two OracleDecimal values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

NotEquals

This method determines if two OracleDecimal values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*
The first OracleDecimal.
- *value2*
The second OracleDecimal.

Return Value

Returns `true` if two OracleDecimal values are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.

- Two OracleDecimals that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Manipulation) Methods

The OracleDecimal static (manipulation) methods are listed in [Table 14-53](#).

Table 14-53 OracleDecimal Static (Manipulation) Methods

Methods	Description
Abs	Returns the absolute value of an OracleDecimal
Add	Adds two OracleDecimal structures
AdjustScale	Returns a new OracleDecimal with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than original
Ceiling	Returns a new OracleDecimal structure with its value set to the ceiling of an OracleDecimal structure
ConvertToPrecScale	Returns a new OracleDecimal structure with a new precision and scale
Divide	Divides one OracleDecimal value by another
Floor	Returns a new OracleDecimal structure with its value set to the floor of an OracleDecimal structure
Max	Returns the maximum value of the two supplied OracleDecimal structures
Min	Returns the minimum value of the two supplied OracleDecimal structures
Mod	Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures
Multiply	Returns a new OracleDecimal structure with its value set to the result of multiplying two OracleDecimal structures
Negate	Returns a new OracleDecimal structure with its value set to the negation of the supplied OracleDecimal structure
Parse	Converts a string to an OracleDecimal
Round	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure and rounded off to the specified place

Table 14-53 (Cont.) OracleDecimal Static (Manipulation) Methods

Methods	Description
SetPrecision	Returns a new OracleDecimal structure with a new specified precision.
Shift	Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure, and its decimal place shifted to the specified number of places to the right
Sign	Determines the sign of an OracleDecimal structure
Sqrt	Returns a new OracleDecimal structure with its value set to the square root of the supplied OracleDecimal structure
Subtract	Returns a new OracleDecimal structure with its value set to result of subtracting one OracleDecimal structure from another
Truncate	Truncates the OracleDecimal at a specified position

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Abs

This method returns the absolute value of an OracleDecimal.

Declaration

```
// C#  
public static OracleDecimal Abs(OracleDecimal val);
```

Parameters

- `val`
An OracleDecimal.

Return Value

The absolute value of an OracleDecimal.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Add

This method adds two `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal Add(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- `val1`
The first `OracleDecimal`.
- `val2`
The second `OracleDecimal`.

Return Value

Returns an `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

AdjustScale

This method returns a new `OracleDecimal` with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than the original.

Declaration

```
// C#  
public static OracleDecimal AdjustScale(OracleDecimal val, int digits,  
    bool fRound);
```

Parameters

- *val*
An OracleDecimal.
- *digits*
The number of digits.
- *fRound*
Indicates whether or not to round or truncate the number. Setting it to `true` rounds the number and setting it to `false` truncates the number.

Return Value

An OracleDecimal.

Remarks

If the supplied OracleDecimal has a null value, the returned OracleDecimal has a null value.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class AdjustScaleSample  
{  
    static void Main(string[] args)  
    {  
        OracleDecimal dec1 = new OracleDecimal(5.555);  
  
        // Adjust Scale to 2 with rounding off  
        OracleDecimal dec2 = OracleDecimal.AdjustScale(dec1, 2, true);  
  
        // Prints 5.56  
        Console.WriteLine(dec2.ToString());  
  
        // Adjust Scale to 2 with truncation  
        OracleDecimal dec3 = OracleDecimal.AdjustScale(dec1, 2, false);  
  
        // Prints 5.55  
        Console.WriteLine(dec3.ToString());  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Ceiling

This method returns a new `OracleDecimal` structure with its value set to the ceiling of the supplied `OracleDecimal`.

Declaration

```
// C#  
public static OracleDecimal Ceiling(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal`.

Return Value

A new `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ConvertToPrecScale

This method returns a new `OracleDecimal` structure with a new precision and scale.

Declaration

```
// C#  
public static OracleDecimal ConvertToPrecScale(OracleDecimal val  
    int precision, int scale);
```

Parameters

- *val*
An OracleDecimal structure.
- *precision*
The precision. Range of precision is 1 to 38.
- *scale*
The number of digits to the right of the decimal point. Range of scale is -84 to 127.

Return Value

A new OracleDecimal structure.

Remarks

If the supplied OracleDecimal has a null value, the returned OracleDecimal has a null value.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class ConvertToPrecScaleSample  
{  
    static void Main(string[] args)  
    {  
        OracleDecimal dec1 = new OracleDecimal(555.6666);  
  
        // Set the precision of od to 5 and scale to 2  
        OracleDecimal dec2 = OracleDecimal.ConvertToPrecScale(dec1,5,2);  
  
        // Prints 555.67  
        Console.WriteLine(dec2.ToString());  
  
        // Set the precision of od to 3 and scale to 0  
        OracleDecimal dec3 = OracleDecimal.ConvertToPrecScale(dec1,3,0);  
  
        // Prints 556  
        Console.WriteLine(dec3.ToString());  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Divide

This method divides one `OracleDecimal` value by another.

Declaration

```
// C#  
public static OracleDecimal Divide(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- `val1`
An `OracleDecimal`.
- `val2`
An `OracleDecimal`.

Return Value

A new `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Floor

This method returns a new `OracleDecimal` structure with its value set to the floor of the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal Floor(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

A new `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Max

This method returns the maximum value of the two supplied `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal Max(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- `val1`
An `OracleDecimal` structure.
- `val2`
An `OracleDecimal` structure.

Return Value

An `OracleDecimal` structure that has the greater value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Min

This method returns the minimum value of the two supplied `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal Min(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An OracleDecimal structure.
- *val2*
An OracleDecimal structure.

Return Value

An OracleDecimal structure that has the smaller value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Mod

This method returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Mod(OracleDecimal val1, OracleDecimal divider);
```

Parameters

- *val1*
An OracleDecimal structure.
- *divider*
An OracleDecimal structure.

Return Value

An OracleDecimal.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Multiply

This method returns a new `OracleDecimal` structure with its value set to the result of multiplying two `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal Multiply(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An `OracleDecimal` structure.
- *val2*
An `OracleDecimal` structure.

Return Value

A new `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Negate

This method returns a new `OracleDecimal` structure with its value set to the negation of the supplied `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal Negate(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A new OracleDecimal structure.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Parse

This method converts a string to an OracleDecimal.

Declaration

```
// C#  
public static OracleDecimal Parse (string str);
```

Parameters

- *str*
The string being converted.

Return Value

A new OracleDecimal structure.

Exceptions

ArgumentException - The *numStr* parameter is an invalid string representation of an OracleDecimal.

ArgumentNullException - The *numStr* parameter is null.

OverflowException - The value of *numStr* is greater than the maximum value or less than the minimum value of OracleDecimal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

Round

This method returns a new `OracleDecimal` structure with its value set to that of the supplied `OracleDecimal` structure and rounded off to the specified place.

Declaration

```
// C#  
public static OracleDecimal Round(OracleDecimal val, int decplace);
```

Parameters

- *val*
An `OracleDecimal` structure.
- *decplace*
The specified decimal place. If the value is positive, the function rounds the `OracleDecimal` structure to the right of the decimal point. If the value is negative, the function rounds to the left of the decimal point.

Return Value

An `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

SetPrecision

This method returns a new `OracleDecimal` structure with a new specified precision.

Declaration

```
// C#  
public static OracleDecimal SetPrecision(OracleDecimal val, int precision);
```

Parameters

- *val*
An `OracleDecimal` structure.
- *precision*
The specified precision. Range of precision is 1 to 38.

Return Value

An `OracleDecimal` structure.

Remarks

The returned `OracleDecimal` is rounded off if the specified precision is smaller than the precision of *val*.

If *val* has a null value, the returned `OracleDecimal` has a null value.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class SetPrecisionSample  
{  
    static void Main(string[] args)  
    {  
        OracleDecimal dec1 = new OracleDecimal(555.6666);  
  
        // Set the precision of dec1 to 3  
        OracleDecimal dec2 = OracleDecimal.SetPrecision(dec1, 3);  
  
        // Prints 556  
        Console.WriteLine(dec2.ToString());  
  
        // Set the precision of dec1 to 4  
        OracleDecimal dec3 = OracleDecimal.SetPrecision(dec1, 4);  
  
        // Prints 555.7  
        Console.WriteLine(dec3.ToString());  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" / "Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Shift

This method returns a new `OracleDecimal` structure with its value set to that of the supplied `OracleDecimal` structure, and its decimal place shifted to the specified number of places to the right.

Declaration

```
// C#  
public static OracleDecimal Shift(OracleDecimal val, int decplaces);
```

Parameters

- *val*
An `OracleDecimal` structure.
- *decplaces*
The specified number of places to be shifted.

Return Value

An `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

If *decplaces* is negative, the shift is to the left.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" / "Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sign

This method determines the sign of an `OracleDecimal` structure.

Declaration

```
// C#  
public static int Sign(OracleDecimal val);
```

Parameters

- `val`
An OracleDecimal structure.

Return Value

- -1: if the supplied OracleDecimal < 0
- 0: if the supplied OracleDecimal == 0
- 1: if the supplied OracleDecimal > 0

Exceptions

OracleNullValueException - The argument has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sqrt

This method returns a new OracleDecimal structure with its value set to the square root of the supplied OracleDecimal structure.

Declaration

```
// C#  
public static OracleDecimal Sqrt(OracleDecimal val);
```

Parameters

- `val`
An OracleDecimal structure.

Return Value

An OracleDecimal structure.

Exceptions

ArgumentOutOfRangeException - The provided OracleDecimal structure is less than zero.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Subtract

This method returns a new `OracleDecimal` structure with its value set to result of subtracting one `OracleDecimal` structure from another.

Declaration

```
// C#  
public static OracleDecimal Subtract(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An `OracleDecimal` structure.
- *val2*
An `OracleDecimal` structure.

Return Value

An `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Truncate

This method truncates the `OracleDecimal` at a specified position.

Declaration

```
// C#  
public static OracleDecimal Truncate(OracleDecimal val, int pos);
```

Parameters

- *val*
An `OracleDecimal` structure.
- *pos*
The specified position. If the value is positive, the function truncates the `OracleDecimal` structure to the right of the decimal point. If the value is negative, it truncates the `OracleDecimal` structure to the left of the decimal point.

Return Value

An `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Logarithmic) Methods

The `OracleDecimal` static (logarithmic) methods are listed in [Table 14-54](#).

Table 14-54 OracleDecimal Static (Logarithmic) Methods

Methods	Description
Exp	Returns a new <code>OracleDecimal</code> structure with its value set to e raised to the supplied power
Log	Returns the supplied <code>OracleDecimal</code> structure with its value set to the logarithm of the supplied <code>OracleDecimal</code> structure (Overloaded)
Pow	Returns a new <code>OracleDecimal</code> structure with its value set to the supplied <code>OracleDecimal</code> structure raised to the supplied power (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Exp

This method returns a new `OracleDecimal` structure with its value set to e raised to the supplied `OracleDecimal`.

Declaration

```
// C#  
public static OracleDecimal Exp(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

An `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log

`Log` returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure.

Overload List:

- [Log\(OracleDecimal\)](#)
This method returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of the supplied `OracleDecimal` structure.

- [Log\(OracleDecimal, int\)](#)
This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.
- [Log\(OracleDecimal, OracleDecimal\)](#)
This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log(OracleDecimal)

This method returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure whose logarithm is to be calculated.

Return Value

Returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of `val`.

Exceptions

`ArgumentOutOfRangeException` - The supplied `OracleDecimal` value is less than zero.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

If the supplied `OracleDecimal` structure has zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log(OracleDecimal, int)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val, int logBase);
```

Parameters

- *val*
An `OracleDecimal` structure whose logarithm is to be calculated.
- *logBase*
An `int` that specifies the base of the logarithm.

Return Value

A new `OracleDecimal` structure with its value set to the logarithm of *val* in the supplied base.

Exceptions

`ArgumentOutOfRangeException` - Either argument is less than zero.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

If both arguments have zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log(OracleDecimal, OracleDecimal)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val, OracleDecimal logBase);
```

Parameters

- *val*
An `OracleDecimal` structure whose logarithm is to be calculated.
- *logBase*
An `OracleDecimal` structure that specifies the base of the logarithm.

Return Value

Returns the logarithm of *val* in the supplied base.

Exceptions

`ArgumentOutOfRangeException` - Either the *val* or *logBase* parameter is less than zero.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

If both arguments have zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pow

`Pow` returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied power.

Overload List:

- [Pow\(OracleDecimal, int\)](#)
This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` value raised to the supplied `Int32` power.

- [Pow\(OracleDecimal, OracleDecimal\)](#)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied `OracleDecimal` power.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pow(OracleDecimal, int)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` value raised to the supplied `Int32` power.

Declaration

```
// C#  
public static OracleDecimal Pow(OracleDecimal val, int power);
```

Parameters

- `val`
An `OracleDecimal` structure.
- `power`
An `int` value that specifies the power.

Return Value

An `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pow(OracleDecimal, OracleDecimal)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied `OracleDecimal` power.

Declaration

```
// C#  
public static OracleDecimal Pow(OracleDecimal val, OracleDecimal power);
```

Parameters

- *val*
An `OracleDecimal` structure.
- *power*
An `OracleDecimal` structure that specifies the power.

Return Value

An `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Trigonometric) Methods

The `OracleDecimal` static (trigonometric) methods are listed in [Table 14-55](#).

Table 14-55 OracleDecimal Static (Trigonometric) Methods

Methods	Description
Acos	Returns an angle in radians whose cosine is the supplied <code>OracleDecimal</code> structure
Asin	Returns an angle in radians whose sine is the supplied <code>OracleDecimal</code> structure
Atan	Returns an angle in radians whose tangent is the supplied <code>OracleDecimal</code> structure

Table 14-55 (Cont.) OracleDecimal Static (Trigonometric) Methods

Methods	Description
Atan2	Returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures
Cos	Returns the cosine of the supplied angle in radians
Sin	Returns the sine of the supplied angle in radians
Tan	Returns the tangent of the supplied angle in radians
Cosh	Returns the hyperbolic cosine of the supplied angle in radians
Sinh	Returns the hyperbolic sine of the supplied angle in radians
Tanh	Returns the hyperbolic tangent of the supplied angle in radians

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ACOS

This method returns an angle in radians whose cosine is the supplied OracleDecimal structure.

Declaration

```
// C#  
public static OracleDecimal Acos(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure. Range is (-1 to 1).

Return Value

An OracleDecimal structure that represents an angle in radians.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Asin

This method returns an angle in radians whose sine is the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal Asin(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure. Range is (-1 to 1).

Return Value

An `OracleDecimal` structure that represents an angle in radians.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Atan

This method returns an angle in radians whose tangent is the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal Atan(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal.

Return Value

An OracleDecimal structure that represents an angle in radians.

Remarks

If the argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Atan2

This method returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Atan2(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An OracleDecimal structure that represents the y-coordinate.
- *val2*
An OracleDecimal structure that represents the x-coordinate.

Return Value

An OracleDecimal structure that represents an angle in radians.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Cos

This method returns the cosine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Cos(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure that represents an angle in radians.

Return Value

An OracleDecimal instance.

Exceptions

ArgumentOutOfRangeException - The *val* parameter is positive or negative infinity.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sin

This method returns the sine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Sin(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

An `OracleDecimal` structure that represents an angle in radians.

Exceptions

`ArgumentOutOfRangeException` - The `val` parameter is positive or negative infinity.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Tan

This method returns the tangent of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Tan(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure that represents an angle in radians.

Return Value

An `OracleDecimal` instance.

Exceptions

`ArgumentOutOfRangeException` - The `val` parameter is positive or negative infinity.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Cosh

This method returns the hyperbolic cosine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Cosh(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure that represents an angle in radians.

Return Value

An OracleDecimal instance.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sinh

This method returns the hyperbolic sine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Sinh(OracleDecimal val);
```

Parameters

- *val*

An OracleDecimal structure that represents an angle in radians.

Return Value

An OracleDecimal instance.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Tanh

This method returns the hyperbolic tangent of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Tanh(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure that represents an angle in radians.

Return Value

An OracleDecimal instance.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Comparison) Operators

The OracleDecimal static (comparison) operators are listed in [Table 14-56](#).

Table 14-56 OracleDecimal Static (Comparison) Operators

Operator	Description
operator +	Adds two OracleDecimal values
operator /	Divides one OracleDecimal value by another
operator ==	Determines if the two OracleDecimal values are equal
operator >	Determines if the first of two OracleDecimal values is greater than the second
operator >=	Determines if the first of two OracleDecimal values is greater than or equal to the second
operator !=	Determines if the two OracleDecimal values are not equal
operator <	Determines if the first of two OracleDecimal values is less than the second
operator <=	Determines if the first of two OracleDecimal values is less than or equal to the second
operator *	Multiplies two OracleDecimal structures
operator -	Subtracts one OracleDecimal structure from another
operator -	Negates an OracleDecimal structure
operator%	Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator +

This method adds two OracleDecimal values.

Declaration

```
// C#
public static OracleDecimal operator + (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*

The first OracleDecimal.

- `val2`

The second OracleDecimal.

Return Value

An OracleDecimal structure.

Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator /

This method divides one OracleDecimal value by another.

Declaration

```
/ C#  
public static OracleDecimal operator / (OracleDecimal val1, OracleDecimal val2)
```

Parameters

- `val1`
The first OracleDecimal.
- `val2`
The second OracleDecimal.

Return Value

An OracleDecimal structure.

Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator ==

This method determines if two `OracleDecimal` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first `OracleDecimal`.
- *val2*
The second `OracleDecimal`.

Return Value

Returns `true` if their values are equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator >

This method determines if the first of two `OracleDecimal` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

Returns true if the two OracleDecimal values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator >=

This method determines if the first of two OracleDecimal values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

Returns `true` if the first of two `OracleDecimal` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator !=

This method determines if the first of two `OracleDecimal` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- `val1`
The first `OracleDecimal`.
- `val2`
The second `OracleDecimal`.

Return Value

Returns `true` if the two `OracleDecimal` values are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator <

This method determines if the first of two `OracleDecimal` values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first `OracleDecimal`.
- *val2*
The second `OracleDecimal`.

Return Value

Returns `true` if the first of two `OracleDecimal` values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator <=

This method determines if the first of two `OracleDecimal` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- `val1`
The first `OracleDecimal`.
- `val2`
The second `OracleDecimal`.

Return Value

Returns `true` if the first of two `OracleDecimal` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator *

This method multiplies two `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal operator * (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- `val1`

The first OracleDecimal.

- `val2`

The second OracleDecimal.

Return Value

A new OracleDecimal structure.

Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator -

This method subtracts one OracleDecimal structure from another.

Declaration

```
// C#  
public static OracleDecimal operator - (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- `val1`
The first OracleDecimal.
- `val2`
The second OracleDecimal.

Return Value

A new OracleDecimal structure.

Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator -

This method negates the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal operator - (OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal`.

Return Value

A new `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator%

This method returns a new `OracleDecimal` structure with its value set to the modulus of two `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal operator % (OracleDecimal val,  
    OracleDecimal divider);
```

Parameters

- *val*
An OracleDecimal.
- *divider*
An OracleDecimal.

Return Value

A new OracleDecimal structure.

Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

The OracleDecimal static operators (Conversion from .NET Type to OracleDecimal) are listed in [Table 14-57](#).

Table 14-57 OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

Operator	Description
implicit operator OracleDecimal	Converts an instance value to an OracleDecimal structure (Overloaded)
explicit operator OracleDecimal	Converts an instance value to an OracleDecimal structure (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal

`implicit operator OracleDecimal` returns the `OracleDecimal` representation of a value.

Overload List:

- [implicit operator OracleDecimal\(decimal\)](#)
This method returns the `OracleDecimal` representation of a decimal value.
- [implicit operator OracleDecimal\(int\)](#)
This method returns the `OracleDecimal` representation of an `int` value.
- [implicit operator OracleDecimal\(long\)](#)
This method returns the `OracleDecimal` representation of a long value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal(decimal)

This method returns the `OracleDecimal` representation of a decimal value.

Declaration

```
// C#  
public static implicit operator OracleDecimal(decimal val);
```

Parameters

- `val`
A decimal value.

Return Value

An `OracleDecimal`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal(int)

This method returns the `OracleDecimal` representation of an `int` value.

Declaration

```
// C#  
public static implicit operator OracleDecimal(int val);
```

Parameters

- `val`
An `int` value.

Return Value

An `OracleDecimal`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal(long)

This method returns the `OracleDecimal` representation of a `long` value.

Declaration

```
// C#  
public static implicit operator OracleDecimal(long val);
```

Parameters

- `val`
A `long` value.

Return Value

An OracleDecimal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator OracleDecimal

OracleDecimal returns the OracleDecimal representation of a value.

Overload List:

- [explicit operator OracleDecimal\(double\)](#)
This method returns the OracleDecimal representation of a double.
- [explicit operator OracleDecimal\(string\)](#)
This method returns the OracleDecimal representation of a string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator OracleDecimal(double)

This method returns the OracleDecimal representation of a double.

Declaration

```
// C#  
public static explicit operator OracleDecimal(double val);
```

Parameters

- *val*
A double.

Return Value

An OracleDecimal.

Exceptions

OverflowException - The value of the supplied double is greater than the maximum value of OracleDecimal or less than the minimum value of OracleDecimal.

Remarks

OracleDecimal contains the following values depending on the provided double value:

- double.PositiveInfinity: positive infinity value
- double.NegativeInfinity: negative infinity value.
- double.NaN: null value

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator OracleDecimal(string)

This method returns the OracleDecimal representation of a string.

Declaration

```
// C#  
public static explicit operator OracleDecimal(string numStr);
```

Parameters

- *numStr*
A string that represents a numeric value.

Return Value

An OracleDecimal.

Exceptions

ArgumentException - The *numStr* parameter is an invalid string representation of an OracleDecimal.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

The `OracleDecimal` static operators (Conversion from `OracleDecimal` to .NET) are listed in [Table 14-58](#).

Table 14-58 OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

Operator	Description
explicit operator byte	Returns the byte representation of the <code>OracleDecimal</code> value
explicit operator decimal	Returns the decimal representation of the <code>OracleDecimal</code> value
explicit operator double	Returns the double representation of the <code>OracleDecimal</code> value
explicit operator short	Returns the short representation of the <code>OracleDecimal</code> value
explicit operator int	Returns the int representation of the <code>OracleDecimal</code> value
explicit operator long	Returns the long representation of the <code>OracleDecimal</code> value
explicit operator float	Returns the float representation of the <code>OracleDecimal</code> value

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator byte

This method returns the `byte` representation of the `OracleDecimal` value.

Declaration

```
// C#  
public static explicit operator byte(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

A `byte`.

Exceptions

`OracleNullValueException` - `OracleDecimal` has a null value.

`OverflowException`- The `byte` cannot represent the supplied `OracleDecimal` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator decimal

This method returns the `decimal` representation of the `OracleDecimal` value.

Declaration

```
// C#  
public static explicit operator decimal(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

A `decimal`.

Exceptions

`OracleNullValueException` - The `OracleDecimal` has a null value.

OverflowException - The decimal cannot represent the supplied OracleDecimal structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator double

This method returns the double representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator double(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A double.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The double cannot represent the supplied OracleDecimal structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator short

This method returns the short representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator short(OracleDecimal val);
```

Parameters

- `val`
An OracleDecimal structure.

Return Value

A short.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The short cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator int

This method returns the int representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator int(OracleDecimal val);
```

Parameters

- `val`
An OracleDecimal structure.

Return Value

An int.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The int cannot represent the supplied OracleDecimal structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator long

This method returns the `long` representation of the `OracleDecimal` value.

Declaration

```
// C#  
public static explicit operator long(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

A `long`.

Exceptions

`OracleNullValueException` - The `OracleDecimal` has a null value.

`OverflowException` - The `long` cannot represent the supplied `OracleDecimal` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator float

This method returns the `float` representation of the `OracleDecimal` value.

Declaration

```
// C#  
public static explicit operator float(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

A float.

Exceptions

`OracleNullValueException` - The `OracleDecimal` has a null value.

`OverflowException` - The float cannot represent the supplied `OracleDecimal` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Properties

The `OracleDecimal` properties are listed in [Table 14-59](#).

Table 14-59 OracleDecimal Properties

Properties	Description
BinData	Returns a byte array that represents the Oracle NUMBER in Oracle internal format
Format	Specifies the format for <code>ToString()</code>
IsInt	Indicates whether or not the current instance is an integer
IsNull	Indicates whether or not the current instance has a null value
IsPositive	Indicates whether or not the current instance is greater than 0
IsZero	Indicates whether or not the current instance has a zero value
Value	Returns a decimal value

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

BinData

This property returns a byte array that represents the Oracle `NUMBER` in an internal Oracle format.

Declaration

```
// C#  
public byte[] BinData {get;}
```

Property Value

A byte array that represents the Oracle `NUMBER` in an internal Oracle format.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Format

This property specifies the format for `ToString()`.

Declaration

```
// C#  
public string Format {get; set;}
```

Property Value

The string which specifies the format.

Remarks

`Format` is used when `ToString()` is called on an instance of an `OracleDecimal`. It is useful if the `ToString()` method needs a specific currency symbol, group, or decimal separator as part of a string.

By default, this property is `null` which indicates that no special formatting is used.

The decimal and group separator characters are specified by the thread's `OracleGlobalization.NumericCharacters`.

The currency symbols are specified by the following thread properties:

- `OracleGlobalization.Currency`
- `OracleGlobalization.ISOCurrency`
- `OracleGlobalization.DualCurrency`

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

IsInt

This property indicates whether or not the current instance is an integer value.

Declaration


```
// C#  
public bool IsInt {get;}
```

Property Value

A `bool` value that returns `true` if the current instance is an integer value; otherwise, returns `false`.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

A `bool` value that returns `true` if the current instance has a null value; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

IsPositive

This property indicates whether or not the value of the current instance is greater than 0.

Declaration

```
// C#  
public bool IsPositive {get;}
```

Property Value

A `bool` value that returns `true` if the current instance is greater than 0; otherwise, returns `false`.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

IsZero

This property indicates whether or not the current instance has a zero value.

Declaration

```
// C#  
public bool IsZero{get;}
```

Property Value

A `bool` value that returns `true` if the current instance has a zero value; otherwise, returns `false`.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Value

This method returns a decimal value.

Declaration

```
// C#  
public decimal Value {get;}
```

Property Value

A decimal value.

Exceptions

`OracleNullValueException` - The current instance has a null value.

OverflowException - The decimal cannot represent the supplied OracleDecimal structure.

Remarks

Precision can be lost when the decimal value is obtained from an OracleDecimal. See Remarks under "OracleDecimal Structure" for further information.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Instance Methods

The OracleDecimal instance methods are listed in [Table 14-60](#).

Table 14-60 OracleDecimal Instance Methods

Method	Description
CompareTo	Compares the current instance to the supplied object and returns an integer that represents their relative values
Equals	Determines whether or not an object is an instance of OracleDecimal, and whether or not the value of the object is equal to the current instance (Overloaded)
GetHashCode	Returns a hash code for the current instance
GetType	Inherited from System.Object
ToByte	Returns the byte representation of the current instance
ToDouble	Returns the double representation of the current instance
ToInt16	Returns the Int16 representation of the current instance
ToInt32	Returns the Int32 representation of the current instance
ToInt64	Returns the Int64 representation of the current instance
ToSingle	Returns the Single representation of the current instance
ToString	Overloads Object.ToString() Returns the string representation of the current instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

CompareTo

This method compares the current instance to the supplied object and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
The supplied instance.

Return Value

The method returns a number:

- Less than zero: if the value of the current instance is less than *obj*.
- Zero: if the value of the current instance is equal to *obj*.
- Greater than zero: if the value of the current instance is greater than *obj*.

Implements

Comparable

Exceptions

ArgumentException - The parameter is not of type OracleDecimal.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between OracleDecimals. For example, comparing an OracleDecimal instance with an OracleBinary instance is not allowed. When an OracleDecimal is compared with a different type, an ArgumentException is thrown.
- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Equals

Overrides `Object`

This method determines whether or not an object is an instance of `OracleDecimal`, and whether or not the value of the object is equal to the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*
An `OracleDecimal` instance.

Return Value

Returns `true` if *obj* is an instance of `OracleDecimal`, and the value of *obj* is equal to the current instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the current instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

Returns a hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToByte

This method returns the `byte` representation of the current instance.

Declaration

```
// C#  
public byte ToByte();
```

Return Value

A `byte`.

Exceptions

`OverflowException` - The `byte` cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToDouble

This method returns the `double` representation of the current instance.

Declaration

```
// C#  
public double ToDouble();
```

Return Value

A double.

Exceptions

`OverflowException` - The double cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToInt16

This method returns the `Int16` representation of the current instance.

Declaration

```
// C#  
public short ToInt16();
```

Return Value

A short.

Exceptions

`OverflowException` - The short cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToInt32

This method returns the `Int32` representation of the current instance.

Declaration

```
// C#  
public int ToInt32();
```

Return Value

An `int`.

Exceptions

`OverflowException` - The `int` cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToInt64

This method returns the `Int64` representation of the current instance.

Declaration

```
// C#  
public long ToInt64();
```

Return Value

A `long`.

Exceptions

`OverflowException` - The `long` cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToSingle

This method returns the `Single` representation of the current instance.

Declaration

```
// C#  
public float ToSingle();
```

Return Value

A float.

Exceptions

`OverflowException` - The float cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToString

Overrides `Object`

This method returns the `string` representation of the current instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns the number in a string returns and a period (.) as a numeric separator.

Remarks

If the current instance has a null value, the returned string is "null".

The returned value is a string representation of an `OracleDecimal` in the numeric format specified by the `Format` property.

The decimal and group separator characters are specified by the thread's `OracleGlobalization.NumericCharacters`.

The currency symbols are specified by the following thread properties:

- `OracleGlobalization.Currency`
- `OracleGlobalization.ISOCurrency`
- `OracleGlobalization.DualCurrency`

If the numeric format is not specified, an Oracle default value is used.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

OracleIntervalDS Structure

The `OracleIntervalDS` structure represents the Oracle `INTERVAL DAY TO SECOND` data type to be stored in or retrieved from a database. Each `OracleIntervalDS` stores a period of time in term of days, hours, minutes, seconds, and fractional seconds.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleIntervalDS`

Declaration

```
// C#  
public struct OracleIntervalDS : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleIntervalDSSample
{
    static void Main()
    {
        OracleIntervalDS iDSMax = OracleIntervalDS.MaxValue;
        double totalDays = iDSMax.TotalDays;

        totalDays -= 1;
        OracleIntervalDS iDSMax_1 = new OracleIntervalDS(totalDays);

        // Calculate the difference
        OracleIntervalDS iDSDiff = iDSMax - iDSMax_1;

        // Prints "iDSDiff.ToString() = +000000000 23:59:59.999999999"
        Console.WriteLine("iDSDiff.ToString() = " + iDSDiff.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Members](#)
- [OracleIntervalDS Constructors](#)
- [OracleIntervalDS Static Fields](#)
- [OracleIntervalDS Static Methods](#)
- [OracleIntervalDS Static Operators](#)
- [OracleIntervalDS Type Conversions](#)
- [OracleIntervalDS Properties](#)
- [OracleIntervalDS Methods](#)

OracleIntervalDS Members

OracleIntervalDS members are listed in the following tables:

OracleIntervalDS Constructors

OracleIntervalDS constructors are listed in [Table 14-61](#)

Table 14-61 OracleIntervalDS Constructors

Constructor	Description
OracleIntervalDS Constructors	Instantiates a new instance of OracleIntervalDS structure (Overloaded)

OracleIntervalDS Static Fields

The OracleIntervalDS static fields are listed in [Table 14-62](#).

Table 14-62 OracleIntervalDS Static Fields

Field	Description
MaxValue	Represents the maximum valid time interval for an OracleIntervalDS structure
MinValue	Represents the minimum valid time interval for an OracleIntervalDS structure
Null	Represents a null value that can be assigned to an OracleIntervalDS instance
Zero	Represents a zero value for an OracleIntervalDS structure

OracleIntervalDS Static Methods

The OracleIntervalDS static methods are listed in [Table 14-63](#).

Table 14-63 OracleIntervalDS Static Methods

Methods	Description
Equals	Determines whether or not two OracleIntervalDS values are equal (Overloaded)
GreaterThan	Determines whether or not one OracleIntervalDS value is greater than another
GreaterThanOrEqual	Determines whether or not one OracleIntervalDS value is greater than or equal to another
LessThan	Determines whether or not one OracleIntervalDS value is less than another
LessThanOrEqual	Determines whether or not one OracleIntervalDS value is less than or equal to another
NotEquals	Determines whether or not two OracleIntervalDS values are not equal
Parse	Returns an OracleIntervalDS structure and sets its value for time interval using a string
SetPrecision	Returns a new instance of an OracleIntervalDS with the specified day precision and fractional second precision

OracleIntervalDS Static Operators

The OracleIntervalDS static operators are listed in [Table 14-64](#).

Table 14-64 OracleIntervalDS Static Operators

Operator	Description
operator +	Adds two OracleIntervalDS values
operator ==	Determines whether or not two OracleIntervalDS values are equal
operator >	Determines whether or not one OracleIntervalDS value is greater than another
operator >=	Determines whether or not one OracleIntervalDS value is greater than or equal to another
operator !=	Determines whether or not two OracleIntervalDS values are not equal
operator <	Determines whether or not one OracleIntervalDS value is less than another

Table 14-64 (Cont.) OracleIntervalDS Static Operators

Operator	Description
<code>operator <=</code>	Determines whether or not one OracleIntervalDS value is less than or equal to another
<code>operator -</code>	Subtracts one OracleIntervalDS value from another
<code>operator -</code>	Negates an OracleIntervalDS structure
<code>operator *</code>	Multiplies an OracleIntervalDS value by a number
<code>operator /</code>	Divides an OracleIntervalDS value by a number

OracleIntervalDS Type Conversions

The OracleIntervalDS type conversions are listed in [Table 14-65](#).

Table 14-65 OracleIntervalDS Type Conversions

Operator	Description
<code>explicit operator TimeSpan</code>	Converts an OracleIntervalDS structure to a TimeSpan structure
<code>explicit operator OracleIntervalDS</code>	Converts a string to an OracleIntervalDS structure
<code>implicit operator OracleIntervalDS</code>	Converts a TimeSpan structure to an OracleIntervalDS structure

OracleIntervalDS Properties

The OracleIntervalDS properties are listed in [Table 14-66](#).

Table 14-66 OracleIntervalDS Properties

Properties	Description
<code>BinData</code>	Returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format
<code>Days</code>	Gets the days component of an OracleIntervalDS
<code>Hours</code>	Gets the hours component of an OracleIntervalDS
<code>IsNull</code>	Indicates whether or not the current instance has a null value
<code>Milliseconds</code>	Gets the milliseconds component of an OracleIntervalDS
<code>Minutes</code>	Gets the minutes component of an OracleIntervalDS

Table 14-66 (Cont.) OracleIntervalDS Properties

Properties	Description
Nanoseconds	Gets the nanoseconds component of an OracleIntervalDS
Seconds	Gets the seconds component of an OracleIntervalDS
TotalDays	Returns the total number, in days, that represent the time period in the OracleIntervalDS structure
Value	Specifies the time interval that is stored in the OracleIntervalDS structure

OracleIntervalDS Methods

The OracleIntervalDS methods are listed in [Table 14-67](#).

Table 14-67 OracleIntervalDS Methods

Methods	Description
CompareTo	Compares the current OracleIntervalDS instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
GetHashCode	Returns a hash code for the OracleIntervalDS instance
GetType	Inherited from System.Object
ToString	Converts the current OracleIntervalDS structure to a string

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)

OracleIntervalDS Constructors

OracleIntervalDS constructors create a new instance of the OracleIntervalDS structure.

Overload List:

- [OracleIntervalDS\(TimeSpan\)](#)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using a `TimeSpan` structure.

- [OracleIntervalDS\(string\)](#)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using a string that indicates a period of time.

- [OracleIntervalDS\(double\)](#)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the total number of days.

- [OracleIntervalDS\(int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds and milliseconds.

- [OracleIntervalDS\(int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds, and nanoseconds.

- [OracleIntervalDS\(byte\[\]\)](#)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(TimeSpan)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using a `TimeSpan` structure.

Declaration

```
// C#  
public OracleIntervalDS(TimeSpan ts);
```

Parameters

- *ts*
A `TimeSpan` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(string)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using a string that indicates a period of time.

Declaration

```
// C#  
public OracleIntervalDS(string intervalStr);
```

Parameters

- *intervalStr*
A string representing the Oracle `INTERVAL DAY TO SECOND`.

Exceptions

`ArgumentException` - The *intervalStr* parameter is not in the valid format or has an invalid value.

`ArgumentNullException` - The *intervalStr* parameter is null.

Remarks

The value specified in the supplied *intervalStr* must be in Day HH:MI:SSxFF format.

Example

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes, 4 seconds, and 990 milliseconds or 1 day, 2 hours, 3 minutes, 4 seconds, and 990000000 nanoseconds.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(double)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the total number of days.

Declaration

```
// C#  
public OracleIntervalDS(double totalDays);
```

Parameters

- *totalDays*

The supplied total number of days for a time interval. Range of days is $-1000,000,000 < totalDays < 1000,000,000$.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(int, int, int, int, double)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds, and milliseconds.

Declaration

```
// C#  
public OracleIntervalDS (int days, int hours, int minutes, int seconds,  
    double milliSeconds);
```

Parameters

- *days*
The days provided. Range of day is (-999,999,999 to 999,999,999).
- *hours*
The hours provided. Range of hour is (-23 to 23).
- *minutes*

The minutes provided. Range of minute is (-59 to 59).

- *seconds*

The seconds provided. Range of second is (-59 to 59).

- *milliSeconds*

The milliseconds provided. Range of millisecond is (- 999.999999 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

Remarks

The sign of all the arguments must be the same.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(int, int, int, int, int)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds, and nanoseconds.

Declaration

```
// C#  
public OracleIntervalDS (int days, int hours, int minutes, int seconds,  
    int nanoseconds);
```

Parameters

- *days*

The days provided. Range of day is (-999,999,999 to 999,999,999).

- *hours*

The hours provided. Range of hour is (-23 to 23).

- *minutes*

The minutes provided. Range of minute is (-59 to 59).

- *seconds*

The seconds provided. Range of second is (-59 to 59).

- *nanoseconds*
The nanoseconds provided. Range of nanosecond is (-999,999,999 to 999,999,999)

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

Remarks

The sign of all the arguments must be the same.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(byte[])

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

Declaration

```
// C#  
public OracleIntervalDS (byte[ ] bytes);
```

Parameters

- *bytes*
A byte array that is in an internal Oracle `INTERVAL DAY TO SECOND` format.

Exceptions

`ArgumentException` - *bytes* is not in internal Oracle `INTERVAL DAY TO SECOND` format, or *bytes* is not a valid Oracle `INTERVAL DAY TO SECOND`.

`ArgumentNullException` - *bytes* is null.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Static Fields

The OracleIntervalDS static fields are listed in [Table 14-68](#).

Table 14-68 OracleIntervalDS Static Fields

Field	Description
MaxValue	Represents the maximum valid time interval for an OracleIntervalDS structure
MinValue	Represents the minimum valid time interval for an OracleIntervalDS structure
Null	Represents a null value that can be assigned to an OracleIntervalDS instance
Zero	Represents a zero value for an OracleIntervalDS structure

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

MaxValue

This static field represents the maximum value for an OracleIntervalDS structure.

Declaration

```
// C#
public static readonly OracleIntervalDS MaxValue;
```

Remarks

Maximum values:

- Day: 999999999
- hour: 23

- minute is 59
- second: 59
- nanosecond: 999999999

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

MinValue

This static field represents the minimum value for an `OracleIntervalDS` structure.

Declaration

```
// C#  
public static readonly OracleIntervalDS MinValue;
```

Remarks

Minimum values:

- Day: -999999999
- hour: -23
- minute: -59
- second: -59
- nanosecond: -999999999

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Null

This static field represents a null value that can be assigned to an `OracleIntervalDS` instance.

Declaration

```
// C#
public static readonly OracleIntervalDS Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Zero

This static field represents a zero value for an `OracleIntervalDS` structure.

Declaration

```
// C#
public static readonly OracleIntervalDS Zero;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Static Methods

The `OracleIntervalDS` static methods are listed in [Table 14-69](#).

Table 14-69 OracleIntervalDS Static Methods

Methods	Description
Equals	Determines whether or not two <code>OracleIntervalDS</code> values are equal (Overloaded)
GreaterThan	Determines whether or not one <code>OracleIntervalDS</code> value is greater than another
GreaterThanOrEqual	Determines whether or not one <code>OracleIntervalDS</code> value is greater than or equal to another
LessThan	Determines whether or not one <code>OracleIntervalDS</code> value is less than another

Table 14-69 (Cont.) OracleIntervalDS Static Methods

Methods	Description
LessThanOrEqual	Determines whether or not one OracleIntervalDS value is less than or equal to another
NotEquals	Determines whether or not two OracleIntervalDS values are not equal
Parse	Returns an OracleIntervalDS structure and sets its value for time interval using a string
SetPrecision	Returns a new instance of an OracleIntervalDS with the specified day precision and fractional second precision

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Equals

This static method determines whether or not two OracleIntervalDS values are equal.

Declaration

```
// C#
public static bool Equals(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

If the two OracleIntervalDS structures represent the same time interval, returns `true`; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

GreaterThan

This static method determines whether or not the first of two `OracleIntervalDS` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleIntervalDS val1, OracleIntervalDS  
    val2);
```

Parameters

- `val1`
The first `OracleIntervalDS`.
- `val2`
The second `OracleIntervalDS`.

Return Value

Returns `true` if the first of two `OracleIntervalDS` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

GreaterThanOrEqual

This static method determines whether or not the first of two `OracleIntervalDS` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- `val1`
The first `OracleIntervalDS`.
- `val2`
The second `OracleIntervalDS`.

Return Value

Returns `true` if the first of two `OracleIntervalDS` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

LessThan

This static method determines whether or not the first of two `OracleIntervalDS` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns `true` if the first of two OracleIntervalDS values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

LessThanOrEqual

This static method determines whether or not the first of two OracleIntervalDS values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns `true` if the first of two OracleIntervalDS values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

NotEquals

This static method determines whether or not two `OracleIntervalDS` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first `OracleIntervalDS`.
- *val2*
The second `OracleIntervalDS`.

Return Value

Returns true if two `OracleIntervalDS` values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Parse

This static method returns an `OracleIntervalDS` instance and sets its value for time interval using a string.

Declaration

```
// C#  
public static OracleIntervalDS Parse(string intervalStr);
```

Parameters

- *intervalStr*
A string representing the Oracle `INTERVAL DAY TO SECOND`.

Return Value

Returns an `OracleIntervalDS` instance representing the time interval from the supplied string.

Exceptions

`ArgumentException` - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

`ArgumentNullException` - The *intervalStr* parameter is null.

Remarks

The value specified in *intervalStr* must be in Day HH:MI:SSxFF format.

Example

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes, 4 seconds, and 990 milliseconds or 1 day, 2 hours, 3 minutes, 4 seconds, and 990000000 nanoseconds.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

SetPrecision

This static method returns a new instance of an `OracleIntervalDS` with the specified day precision and fractional second precision.

Declaration

```
// C#  
public static OracleIntervalDS SetPrecision(OracleIntervalDS value1,  
    int dayPrecision, int fracSecPrecision);
```

Parameters

- *value1*
An `OracleIntervalDS` structure.
- *dayPrecision*
The day precision provided. Range of day precision is (0 to 9).
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An `OracleIntervalDS` instance.

Exceptions

`ArgumentOutOfRangeException` - An argument value is out of the specified range.

Remarks

Depending on the value specified in the supplied *dayPrecision*, 0 or more leading zeros are displayed in the string returned by `ToString()`.

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleIntervalDS` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

Example

The `OracleIntervalDS` with a value of "1 2:3:4.99" results in the string "001 2:3:4.99000" when `SetPrecision()` is called, with the day precision set to 3 and fractional second precision set to 5.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Static Operators

The OracleIntervalDS static operators are listed in [Table 14-70](#).

Table 14-70 OracleIntervalDS Static Operators

Operator	Description
operator +	Adds two OracleIntervalDS values
operator ==	Determines whether or not two OracleIntervalDS values are equal
operator >	Determines whether or not one OracleIntervalDS value is greater than another
operator >=	Determines whether or not one OracleIntervalDS value is greater than or equal to another
operator !=	Determines whether or not two OracleIntervalDS values are not equal
operator <	Determines whether or not one OracleIntervalDS value is less than another
operator <=	Determines whether or not one OracleIntervalDS value is less than or equal to another
operator -	Subtracts one OracleIntervalDS value from another
operator -	Negates an OracleIntervalDS structure
operator *	Multiplies an OracleIntervalDS value by a number
operator /	Divides an OracleIntervalDS value by a number

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator +

This static operator adds two OracleIntervalDS values.

Declaration

```
// C#
public static OracleIntervalDS operator + (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

Parameters

- *val1*

The first OracleIntervalDS.

- *val2*

The second OracleIntervalDS.

Return Value

An OracleIntervalDS.

Remarks

If either argument has a null value, the returned OracleIntervalDS structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator ==

This static operator determines if two OracleIntervalDS values are equal.

Declaration

```
// C#  
public static bool operator == (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.


Return Value

Returns `true` if the two OracleIntervalDS values are the same; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSS that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator >

This static operator determines if the first of two `OracleIntervalDS` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- `val1`
The first `OracleIntervalDS`.
- `val2`
The second `OracleIntervalDS`.

Return Value

Returns `true` if one `OracleIntervalDS` value is greater than another; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator >=

This static operator determines if the first of two `OracleIntervalDS` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- `val1`
The first `OracleIntervalDS`.
- `val2`
The second `OracleIntervalDS`.

Return Value

Returns `true` if the first of two `OracleIntervalDS` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator !=

This static operator determines if the two `OracleIntervalDS` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if the two OracleIntervalDS values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator <

This static operator determines if the first of two OracleIntervalDS values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns `true` if the first of two `OracleIntervalDS` values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator <=

This static operator determines if the first of two `OracleIntervalDS` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- `val1`
The first `OracleIntervalDS`.
- `val2`
The second `OracleIntervalDS`.

Return Value

Returns `true` if the first of two `OracleIntervalDS` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator -

This static operator subtracts one `OracleIntervalDS` structure from another.

Declaration

```
// C#  
public static OracleIntervalDS operator - (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- `val1`
The first `OracleIntervalDS`.
- `val2`
The second `OracleIntervalDS`.

Return Value

An `OracleIntervalDS` structure.

Remarks

If either argument has a null value, the returned `OracleIntervalDS` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator -

This static operator negates the supplied `OracleIntervalDS` structure.

Declaration

```
// C#  
public static OracleIntervalDS operator - (OracleIntervalDS val);
```

Parameters

- *val*
An OracleIntervalDS.

Return Value

An OracleIntervalDS structure.

Remarks

If the supplied OracleIntervalDS structure has a null value, the returned OracleIntervalDS structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator *

This static operator multiplies an OracleIntervalDS value by a number.

Declaration

```
// C#  
public static OracleIntervalDS operator * (OracleIntervalDS val1,  
int multiplier);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *multiplier*
A multiplier.

Return Value

A new OracleIntervalDS instance.

Remarks

If the OracleIntervalDS structure has a null value, the returned OracleIntervalDS structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator /

This static operator divides an `OracleIntervalDS` value by a number.

Declaration

```
// C#  
public static OracleIntervalDS operator / (OracleIntervalDS val1,  
    int divisor);
```

Parameters

- *val1*
The first `OracleIntervalDS`.
- *divisor*
A divisor.

Return Value

An `OracleIntervalDS` structure.

Remarks

If the `OracleIntervalDS` structure has a null value, the returned `OracleIntervalDS` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Type Conversions

The `OracleIntervalDS` type conversions are listed in [Table 14-71](#).

Table 14-71 OracleIntervalDS Type Conversions

Operator	Description
explicit operator TimeSpan	Converts an OracleIntervalDS structure to a TimeSpan structure
explicit operator OracleIntervalDS	Converts a string to an OracleIntervalDS structure
implicit operator OracleIntervalDS	Converts a TimeSpan structure to an OracleIntervalDS structure

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

explicit operator TimeSpan

This type conversion operator converts an OracleIntervalDS structure to a TimeSpan structure.

Declaration

```
// C#  
public static explicit operator TimeSpan(OracleIntervalDS val);
```

Parameters

- *val*
An OracleIntervalDS instance.

Return Value

A TimeSpan structure.

Exceptions

OracleNullValueException - The OracleIntervalDS structure has a null value.

Remarks



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

explicit operator OracleIntervalDS

This type conversion operator converts a string to an `OracleIntervalDS` structure.

Declaration

```
// C#  
public static explicit operator OracleIntervalDS (string intervalStr);
```

Parameters

- *intervalStr*

A string representation of an Oracle `INTERVAL DAY TO SECOND`.

Return Value

An `OracleIntervalDS` structure.

Exceptions

`ArgumentException` - The supplied *intervalStr* parameter is not in the correct format or has an invalid value.

`ArgumentNullException` - The *intervalStr* parameter is null.

Remarks

The returned `OracleIntervalDS` structure contains the same time interval represented by the supplied *intervalStr*. The value specified in the supplied *intervalStr* must be in Day HH:MI:SSxFF format.

Example

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes 4 seconds and 990 milliseconds or 1 day, 2 hours, 3 minutes 4 seconds and 990000000 nanoseconds.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

implicit operator OracleIntervalDS

This type conversion operator converts a `TimeSpan` structure to an `OracleIntervalDS` structure.

Declaration

```
// C#  
public static implicit operator OracleIntervalDS(TimeSpan val);
```

Parameters

- `val`
A `TimeSpan` instance.

Return Value

An `OracleIntervalDS` structure.

Remarks

The returned `OracleIntervalDS` structure contains the same days, hours, seconds, and milliseconds as the supplied `TimeSpan val`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Properties

The `OracleIntervalDS` properties are listed in [Table 14-72](#).

Table 14-72 OracleIntervalDS Properties

Properties	Description
BinData	Returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format
Days	Gets the days component of an OracleIntervalDS
Hours	Gets the hours component of an OracleIntervalDS
IsNull	Indicates whether or not the current instance has a null value
Milliseconds	Gets the milliseconds component of an OracleIntervalDS
Minutes	Gets the minutes component of an OracleIntervalDS
Nanoseconds	Gets the nanoseconds component of an OracleIntervalDS
Seconds	Gets the seconds component of an OracleIntervalDS
TotalDays	Returns the total number, in days, that represent the time period in the OracleIntervalDS structure
Value	Specifies the time interval that is stored in the OracleIntervalDS structure

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

BinData

This property returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle INTERVAL DAY TO SECOND in Oracle internal format.

Exceptions

OracleNullValueException - The current instance has a null value.

Remarks



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Days

This property gets the days component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Days {get;}
```

Property Value

An `int` representing the days component.

Exceptions

`OracleNullValueException` - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Hours

This property gets the hours component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Hours {get;}
```

Property Value

An `int` representing the hours component.

Exceptions

OracleNullValueException - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Milliseconds

This property gets the milliseconds component of an `OracleIntervalDS`.

Declaration

```
// C#  
public double Milliseconds {get;}
```

Property Value

A double that represents milliseconds component.

Exceptions

OracleNullValueException - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Minutes

This property gets the minutes component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Minutes {get;}
```

Property Value

A `int` that represents minutes component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Nanoseconds

This property gets the nanoseconds component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Nanoseconds {get;}
```

Property Value

An `int` that represents nanoseconds component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Seconds

This property gets the seconds component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Seconds {get;}
```

Property Value

An `int` that represents seconds component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

TotalDays

This property returns the total number, in days, that represent the time period in the `OracleIntervalDS` structure.

Declaration

```
// C#  
public double TotalDays {get;}
```

Property Value

A `double` that represents the total number of days.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Value

This property specifies the time interval that is stored in the `OracleIntervalDS` structure.

Declaration

```
// C#
public TimeSpan Value {get;}
```

Property Value

A time interval.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Methods

The `OracleIntervalDS` methods are listed in [Table 14-73](#).

Table 14-73 OracleIntervalDS Methods

Methods	Description
CompareTo	Compares the current <code>OracleIntervalDS</code> instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
GetHashCode	Returns a hash code for the <code>OracleIntervalDS</code> instance
GetType	Inherited from <code>System.Object</code>

Table 14-73 (Cont.) OracleIntervalDS Methods

Methods	Description
ToString	Converts the current OracleIntervalDS structure to a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

CompareTo

This method compares the current OracleIntervalDS instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared to.

Return Value

The method returns:

- Less than zero: if the current OracleIntervalDS represents a shorter time interval than *obj*.
- Zero: if the current OracleIntervalDS and *obj* represent the same time interval.
- Greater than zero: if the current OracleIntervalDS represents a longer time interval than *obj*.

Implements

IComparable

Exceptions

ArgumentException - The *obj* parameter is not of type OracleIntervalDS.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleIntervalDS`s. For example, comparing an `OracleIntervalDS` instance with an `OracleBinary` instance is not allowed. When an `OracleIntervalDS` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Equals

This method determines whether or not the specified `object` has the same time interval as the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*
The specified object.

Return Value

Returns `true` if *obj* is of type `OracleIntervalDS` and has the same time interval as the current instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleIntervalDS` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

ToString

Overrides `Object`

This method converts the current `OracleIntervalDS` structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns a `string`.

Remarks

If the current instance has a null value, the returned string contains "null".

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalYM Structure

The `OracleIntervalYM` structure represents the Oracle `INTERVAL YEAR TO MONTH` data type to be stored in or retrieved from a database. Each `OracleIntervalYM` stores a period of time in years and months.

Class Inheritance

```
System.Object
```

```
System.ValueType
```

```
Oracle.DataAccess.Types.OracleIntervalYM
```

Declaration

```
// C#
public struct OracleIntervalYM : IComparable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#
using System;
using Oracle.DataAccess.Types;

class OracleIntervalYMSample
{
```

```

static void Main()
{
    OracleIntervalYM iYMMax = OracleIntervalYM.MaxValue;
    double totalYears = iYMMax.TotalYears;

    totalYears -= 1;
    OracleIntervalYM iYMMax_1 = new OracleIntervalYM(totalYears);

    // Calculate the difference
    OracleIntervalYM iYMDiff = iYMMax - iYMMax_1;

    // Prints "iYMDiff.ToString() = +000000001-00"
    Console.WriteLine("iYMDiff.ToString() = " + iYMDiff.ToString());
}
}

```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Members](#)
- [OracleIntervalYM Constructors](#)
- [OracleIntervalYM Static Fields](#)
- [OracleIntervalYM Static Methods](#)
- [OracleIntervalYM Static Operators](#)
- [OracleIntervalYM Type Conversions](#)
- [OracleIntervalYM Properties](#)
- [OracleIntervalYM Methods](#)

OracleIntervalYM Members

OracleIntervalYM members are listed in the following tables:

OracleIntervalYM Constructors

OracleIntervalYM constructors are listed in [Table 14-74](#)

Table 14-74 OracleIntervalYM Constructors

Constructor	Description
OracleIntervalYM Constructors	Instantiates a new instance of OracleIntervalYM structure (Overloaded)

OracleIntervalYM Static Fields

The OracleIntervalYM static fields are listed in [Table 14-75](#).

Table 14-75 OracleIntervalYM Static Fields

Field	Description
MaxValue	Represents the maximum value for an OracleIntervalYM structure
MinValue	Represents the minimum value for an OracleIntervalYM structure
Null	Represents a null value that can be assigned to an OracleIntervalYM instance
Zero	Represents a zero value for an OracleIntervalYM structure

OracleIntervalYM Static Methods

The OracleIntervalYM static methods are listed in [Table 14-76](#).

Table 14-76 OracleIntervalYM Static Methods

Methods	Description
Equals	Determines whether or not two OracleIntervalYM values are equal (Overloaded)
GreaterThan	Determines whether or not one OracleIntervalYM value is greater than another
GreaterThanOrEqual	Determines whether or not one OracleIntervalYM value is greater than or equal to another
LessThan	Determines whether or not one OracleIntervalYM value is less than another
LessThanOrEqual	Determines whether or not one OracleIntervalYM value is less than or equal to another
NotEquals	Determines whether two OracleIntervalYM values are not equal
Parse	Returns an OracleIntervalYM structure and sets its value for time interval using a string
SetPrecision	Returns a new instance of an OracleIntervalYM with the specified year precision.

OracleIntervalYM Static Operators

The OracleIntervalYM static operators are listed in [Table 14-77](#).

Table 14-77 OracleIntervalYM Static Operators

Operator	Description
operator +	Adds two OracleIntervalYM values

Table 14-77 (Cont.) OracleIntervalYM Static Operators

Operator	Description
<code>operator ==</code>	Determines whether or not two OracleIntervalYM values are equal
<code>operator ></code>	Determines whether or not one OracleIntervalYM value is greater than another
<code>operator >=</code>	Determines whether or not one OracleIntervalYM value is greater than or equal to another
<code>operator !=</code>	Determines whether two OracleIntervalYM values are not equal
<code>operator <</code>	Determines whether or not one OracleIntervalYM value is less than another
<code>operator <=</code>	Determines whether or not one OracleIntervalYM value is less than or equal to another
<code>operator -</code>	Subtracts one OracleIntervalYM value from another
<code>operator -</code>	Negates an OracleIntervalYM structure
<code>operator *</code>	Multiplies an OracleIntervalYM value by a number
<code>operator /</code>	Divides an OracleIntervalYM value by a number

OracleIntervalYM Type Conversions

The OracleIntervalYM conversions are listed in [Table 14-78](#).

Table 14-78 OracleIntervalYM Type Conversions

Operator	Description
<code>explicit operator long</code>	Converts an OracleIntervalYM structure to a number
<code>explicit operator OracleIntervalYM</code>	Converts a string to an OracleIntervalYM structure
<code>implicit operator OracleIntervalYM</code>	Converts the number of months to an OracleIntervalYM structure

OracleIntervalYM Properties

The OracleIntervalYM properties are listed in [Table 14-79](#).

Table 14-79 OracleIntervalYM Properties

Properties	Description
BinData	Returns an array of bytes that represents the Oracle INTERVAL YEAR TO MONTH in an Oracle internal format
IsNull	Indicates whether or not the current instance has a null value
Months	Gets the months component of an OracleIntervalYM
TotalYears	Returns the total number, in years, that represents the period of time in the current OracleIntervalYM structure
Value	Specifies the total number of months that is stored in the OracleIntervalYM structure
Years	Gets the years component of an OracleIntervalYM

OracleIntervalYM Methods

The OracleIntervalYM methods are listed in [Table 14-80](#).

Table 14-80 OracleIntervalYM Methods

Methods	Description
CompareTo	Compares the current OracleIntervalYM instance to the supplied object, and returns an integer that represents their relative values
Equals	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
GetHashCode	Returns a hash code for the OracleIntervalYM instance
GetType	Inherited from System.Object
ToString	Converts the current OracleIntervalYM structure to a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)

OracleIntervalYM Constructors

The `OracleIntervalYM` constructors creates a new instance of the `OracleIntervalYM` structure.

Overload List:

- [OracleIntervalYM\(long\)](#)

This method creates a new instance of the `OracleIntervalYM` structure using the supplied total number of months for a period of time.
- [OracleIntervalYM\(string\)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the supplied string.
- [OracleIntervalYM\(double\)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the total number of years.
- [OracleIntervalYM\(int, int\)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using years and months.
- [OracleIntervalYM\(byte\[\] \)](#)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(long)

This method creates a new instance of the `OracleIntervalYM` structure using the supplied total number of months for a period of time.

Declaration

```
// C#  
public OracleIntervalYM (long totalMonths);
```

Parameters

- *totalMonths*

The number of total months for a time interval. Range is $-12,000,000,000 < totalMonths < 12,000,000,000$.

Exceptions

`ArgumentOutOfRangeException` - The `totalMonths` parameter is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(string)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the supplied string.

Declaration

```
// C#  
public OracleIntervalYM (string intervalStr);
```

Parameters

- `intervalStr`
A string representing the Oracle `INTERVAL YEAR TO MONTH`.

Remarks

The value specified in the supplied `intervalStr` must be in Year-Month format.

Exceptions

`ArgumentException` - The `intervalStr` parameter is not in the valid format or `intervalStr` has an invalid value.

`ArgumentNullException` - The `intervalStr` parameter is null.

Example

"1-2" means 1 year and 2 months.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(double)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the total number of years.

Declaration

```
// C#  
public OracleIntervalYM (double totalYears);
```

Parameters

- *totalYears*
Number of total years. Range is $-1,000,000,000 < totalYears > 1,000,000,000$.

Exceptions

`ArgumentOutOfRangeException` - The *totalYears* parameter is out of the specified range.

`ArgumentException` - The *totalYears* parameter cannot be used to construct a valid `OracleIntervalYM`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(int, int)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using years and months.

Declaration

```
// C#  
public OracleIntervalYM (int years, int months);
```

Parameters

- *years*
Number of years. Range of year is (-999,999,999 to 999,999,999).
- *months*
Number of months. Range of month is (-11 to 11).

Remarks

The sign of all the arguments must be the same.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalYM`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(byte[])

This method creates a new instance of the `OracleIntervalYM` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

Declaration

```
// C#  
public OracleIntervalYM (byte[] bytes);
```

Parameters

- *bytes*
A byte array that is in an internal Oracle `INTERVAL YEAR TO MONTH` format.

Exceptions

`ArgumentException` - The supplied byte array is not in an internal Oracle `INTERVAL YEAR TO MONTH` format or the supplied byte array has an invalid value.

`ArgumentNullException` - *bytes* is null.

Remarks

The supplied byte array must be in an internal Oracle `INTERVAL YEAR TO MONTH` format.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Static Fields

The `OracleIntervalYM` static fields are listed in [Table 14-81](#).

Table 14-81 OracleIntervalYM Static Fields

Field	Description
MaxValue	Represents the maximum value for an <code>OracleIntervalYM</code> structure
MinValue	Represents the minimum value for an <code>OracleIntervalYM</code> structure
Null	Represents a null value that can be assigned to an <code>OracleIntervalYM</code> instance
Zero	Represents a zero value for an <code>OracleIntervalYM</code> structure

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

MaxValue

This static field represents the maximum value for an `OracleIntervalYM` structure.

Declaration

```
// C#
public static readonly OracleIntervalYM MaxValue;
```

Remarks

Year is 999999999 and Month is 11.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

MinValue

This static field represents the minimum value for an `OracleIntervalYM` structure.

Declaration

```
// C#  
public static readonly OracleIntervalYM MinValue;
```

Remarks

Year is -999999999 and Month is -11.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Null

This static field represents a null value that can be assigned to an `OracleIntervalYM` instance.

Declaration

```
// C#  
public static readonly OracleIntervalYM Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Zero

This static field represents a zero value for an `OracleIntervalYM` structure.

Declaration

```
// C#
public static readonly OracleIntervalDS Zero;
```



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Static Methods

The `OracleIntervalYM` static methods are listed in [Table 14-82](#).

Table 14-82 OracleIntervalYM Static Methods

Methods	Description
Equals	Determines whether or not two <code>OracleIntervalYM</code> values are equal (Overloaded)
GreaterThan	Determines whether or not one <code>OracleIntervalYM</code> value is greater than another
GreaterThanOrEqual	Determines whether or not one <code>OracleIntervalYM</code> value is greater than or equal to another
LessThan	Determines whether or not one <code>OracleIntervalYM</code> value is less than another
LessThanOrEqual	Determines whether or not one <code>OracleIntervalYM</code> value is less than or equal to another
NotEquals	Determines whether two <code>OracleIntervalYM</code> values are not equal
Parse	Returns an <code>OracleIntervalYM</code> structure and sets its value for time interval using a string
SetPrecision	Returns a new instance of an <code>OracleIntervalYM</code> with the specified year precision.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Equals

This static method determines whether or not two `OracleIntervalYM` values are equal.

Declaration

```
// C#  
public static bool Equals(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
An `OracleIntervalYM` structure.
- *val2*
An `OracleIntervalYM` structure.

Return Value

Returns `true` if two `OracleIntervalYM` values represent the same time interval, otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

GreaterThan

This static method determines whether or not the first of two `OracleIntervalYM` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- `val1`
The first `OracleIntervalYM`.
- `val2`
The second `OracleIntervalYM`.

Return Value

Returns `true` if the first of two `OracleIntervalYM` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

GreaterThanOrEqual

This static method determines whether or not the first of two `OracleIntervalYM` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleIntervalYM val1,  
OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns `true` if the first of two OracleIntervalYM values is greater than or equal to the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

LessThan

This static method determines whether or not the first of two OracleIntervalYM values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns `true` if the first of two OracleIntervalYM values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

LessThanOrEqual

This static method determines whether or not the first of two `OracleIntervalYM` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- `val1`
The first `OracleIntervalYM`.
- `val2`
The second `OracleIntervalYM`.

Return Value

Returns `true` if the first of two `OracleIntervalYM` values is less than or equal to the second. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

NotEquals

This static method determines whether two `OracleIntervalYM` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first `OracleIntervalYM`.
- *val2*
The second `OracleIntervalYM`.

Return Value

Returns `true` if two `OracleIntervalYM` values are not equal. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Parse

This static method returns an `OracleIntervalYM` structure and sets its value for time interval using a string.

Declaration

```
// C#  
public static OracleIntervalYM Parse (string intervalStr);
```

Parameters

- *intervalStr*
A string representing the Oracle INTERVAL YEAR TO MONTH.

Return Value

Returns an OracleIntervalYM structure.

Exceptions

ArgumentException - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

ArgumentNullException - The *intervalStr* parameter is null.

Remarks

The value specified in the supplied *intervalStr* must be in the Year-Month format.

Example

"1-2" means 1 year and 2 months.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

SetPrecision

This static method returns a new instance of an OracleIntervalYM with the specified year precision.

Declaration

```
// C#  
public static OracleIntervalYM SetPrecision(OracleIntervalYM value1,  
int yearPrecision);
```

Parameters

- *value1*
An OracleIntervalYM structure.

- *yearPrecision*

The year precision provided. Range of year precision is (0 to 9).

Return Value

An `OracleIntervalDS` instance.

Exceptions

`ArgumentOutOfRangeException` - *yearPrecision* is out of the specified range.

Remarks

Depending on the value specified in the supplied *yearPrecision*, 0 or more leading zeros are displayed in the string returned by `ToString()`.

Example

An `OracleIntervalYM` with a value of "1-2" results in the string "001-2" when `SetPrecision()` is called with the year precision set to 3.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Static Operators

The `OracleIntervalYM` static operators are listed in [Table 14-83](#).

Table 14-83 OracleIntervalYM Static Operators

Operator	Description
<code>operator +</code>	Adds two <code>OracleIntervalYM</code> values
<code>operator ==</code>	Determines whether or not two <code>OracleIntervalYM</code> values are equal
<code>operator ></code>	Determines whether or not one <code>OracleIntervalYM</code> value is greater than another
<code>operator >=</code>	Determines whether or not one <code>OracleIntervalYM</code> value is greater than or equal to another
<code>operator !=</code>	Determines whether two <code>OracleIntervalYM</code> values are not equal
<code>operator <</code>	Determines whether or not one <code>OracleIntervalYM</code> value is less than another

Table 14-83 (Cont.) OracleIntervalYM Static Operators

Operator	Description
operator <=	Determines whether or not one OracleIntervalYM value is less than or equal to another
operator -	Subtracts one OracleIntervalYM value from another
operator -	Negates an OracleIntervalYM structure
operator *	Multiplies an OracleIntervalYM value by a number
operator /	Divides an OracleIntervalYM value by a number

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator +

This static operator adds two OracleIntervalYM values.

Declaration

```
// C#
public static OracleIntervalYM operator + (OracleIntervalYM val1,
    OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

OracleIntervalYM

Remarks

If either argument has a null value, the returned OracleIntervalYM structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator ==

This static operator determines if two `OracleIntervalYM` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first `OracleIntervalYM`.
- *val2*
The second `OracleIntervalYM`.

Return Value

Returns `true` if they are equal; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator >

This static operator determines if the first of two `OracleIntervalYM` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if one OracleIntervalYM value is greater than another; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator >=

This static operator determines if the first of two OracleIntervalYM values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns `true` if one `OracleIntervalYM` value is greater than or equal to another; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator !=

This static operator determines whether two `OracleIntervalYM` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleIntervalYM val1, OracleIntervalYM val2)
```

Parameters

- `val1`
The first `OracleIntervalYM`.
- `val2`
The second `OracleIntervalYM`.

Return Value

Returns `true` if two `OracleIntervalYM` values are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator <

This static operator determines if the first of two `OracleIntervalYM` values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- `val1`
The first `OracleIntervalYM`.
- `val2`
The second `OracleIntervalYM`.

Return Value

Returns `true` if the first of two `OracleIntervalYM` values is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator <=

This static operator determines if the first of two `OracleIntervalYM` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- `val1`
The first `OracleIntervalYM`.
- `val2`
The second `OracleIntervalYM`.

Return Value

Returns `true` if the first of two `OracleIntervalYM` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator -

This static operator subtracts one `OracleIntervalYM` structure from another.

Declaration

```
// C#  
public static OracleIntervalYM operator - (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- `val1`

The first OracleIntervalYM.

- `val2`

The second OracleIntervalYM.

Return Value

An OracleIntervalYM structure.

Remarks

If either argument has a null value, the returned OracleIntervalYM structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator -

This static operator negates an OracleIntervalYM structure.

Declaration

```
// C#  
public static OracleIntervalYM operator - (OracleIntervalYM val);
```

Parameters

- `val`
An OracleIntervalYM.

Return Value

An OracleIntervalYM structure.

Remarks

If the supplied OracleIntervalYM structure has a null value, the returned OracleIntervalYM structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator *

This static operator multiplies an `OracleIntervalYM` value by a number.

Declaration

```
// C#  
public static OracleIntervalYM operator * (OracleIntervalYM val1, int multiplier);
```

Parameters

- *val1*
The first `OracleIntervalYM`.
- *multiplier*
A multiplier.

Return Value

An `OracleIntervalYM` structure.

Remarks

If the supplied `OracleIntervalYM` structure has a null value, the returned `OracleIntervalYM` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator /

This static operator divides an `OracleIntervalYM` value by a number.

Declaration

```
// C#  
public static OracleIntervalYM operator / (OracleIntervalYM val1, int divisor);
```


Parameters

- *val1*
The first OracleIntervalYM.
- *divisor*
A divisor.

Return Value

An OracleIntervalYM structure.

Remarks

If the supplied OracleIntervalYM structure has a null value, the returned OracleIntervalYM structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Type Conversions

The OracleIntervalYM conversions are listed in [Table 14-84](#).

Table 14-84 OracleIntervalYM Type Conversions

Operator	Description
explicit operator long	Converts an OracleIntervalYM structure to a number
explicit operator OracleIntervalYM	Converts a string to an OracleIntervalYM structure
implicit operator OracleIntervalYM	Converts the number of months to an OracleIntervalYM structure

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

explicit operator long

This type conversion operator converts an `OracleIntervalYM` to a number that represents the number of months in the time interval.

Declaration

```
// C#  
public static explicit operator long (OracleIntervalYM val);
```

Parameters

- `val`
An `OracleIntervalYM` structure.

Return Value

A long number in months.

Exceptions

`OracleNullValueException` - The `OracleIntervalYM` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

explicit operator OracleIntervalYM

This type conversion operator converts the string `intervalStr` to an `OracleIntervalYM` structure.

Declaration

```
// C#  
public static explicit operator OracleIntervalYM (string intervalStr);
```

Parameters

- `intervalStr`
A string representation of an Oracle `INTERVAL YEAR TO MONTH`.

Return Value

An `OracleIntervalYM` structure.

Exceptions

`ArgumentException` - The supplied `intervalStr` parameter is not in the correct format or has an invalid value.

`ArgumentNullException` - The `intervalStr` parameter is null.

Remarks

The returned `OracleIntervalDS` structure contains the same time interval represented by the supplied `intervalStr`. The value specified in the supplied `intervalStr` must be in Year-Month format.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

implicit operator OracleIntervalYM

This type conversion operator converts the total number of months as time interval to an `OracleIntervalYM` structure.

Declaration

```
// C#  
public static implicit operator OracleIntervalYM (long months);
```

Parameters

- `months`

The number of months to be converted. Range is $(-999,999,999 * 12) - 11 \leq months \leq (999,999,999 * 12) + 11$.

Return Value

An `OracleIntervalYM` structure.

Exceptions

`ArgumentOutOfRangeException` - The `months` parameter is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Properties

The OracleIntervalYM properties are listed in [Table 14-85](#).

Table 14-85 OracleIntervalYM Properties

Properties	Description
BinData	Returns an array of bytes that represents the Oracle INTERVAL YEAR TO MONTH in an Oracle internal format
IsNull	Indicates whether or not the current instance has a null value
Months	Gets the months component of an OracleIntervalYM
TotalYears	Returns the total number, in years, that represents the period of time in the current OracleIntervalYM structure
Value	Specifies the total number of months that is stored in the OracleIntervalYM structure
Years	Gets the years component of an OracleIntervalYM

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

BinData

This property returns an array of bytes that represents the Oracle INTERVAL YEAR TO MONTH in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle `INTERVAL YEAR TO MONTH` in Oracle internal format.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

IsNull

This property indicates whether or not the value has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns `true` if value has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Months

This property gets the months component of an `OracleIntervalYM`.

Declaration

```
// C#  
public int Months {get;}
```

Property Value

An `int` representing the months component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

TotalYears

This property returns the total number, in years, that represents the period of time in the current `OracleIntervalYM` structure.

Declaration

```
// C#  
public double TotalYears {get;}
```

Property Value

A double representing the total number of years.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Value

This property gets the total number of months that is stored in the `OracleIntervalYM` structure.

Declaration

```
// C#  
public long Value {get;}
```

Property Value

The total number of months representing the time interval.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Years

This property gets the years component of an `OracleIntervalYM`.

Declaration

```
// C#  
public int Years {get;}
```

Property Value

An `int` representing the years component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Methods

The `OracleIntervalYM` methods are listed in [Table 14-86](#).

Table 14-86 OracleIntervalYM Methods

Methods	Description
CompareTo	Compares the current OracleIntervalYM instance to the supplied object, and returns an integer that represents their relative values
Equals	Determines whether or not the specified object has the same time interval as the current instance (Overloaded)
GetHashCode	Returns a hash code for the OracleIntervalYM instance
GetType	Inherited from System.Object
ToString	Converts the current OracleIntervalYM structure to a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

CompareTo

This method compares the current OracleIntervalYM instance to the supplied object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
The supplied object.

Return Value

The method returns a number:

Less than zero: if the current OracleIntervalYM represents a shorter time interval than *obj*.

Zero: if the current OracleIntervalYM and *obj* represent the same time interval.

Greater than zero: if the current OracleIntervalYM represents a longer time interval than *obj*.

Implements

IComparable

Exceptions

`ArgumentException` - The `obj` parameter is not of type `OracleIntervalYM`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleIntervalYMs`. For example, comparing an `OracleIntervalYM` instance with an `OracleBinary` instance is not allowed. When an `OracleIntervalYM` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Equals

Overrides `Object`

This method determines whether or not the specified object has the same time interval as the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- `obj`
The supplied object.

Return Value

Returns `true` if the specified object instance is of type `OracleIntervalYM` and has the same time interval; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.

- Two OracleIntervalYMs that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

GetHashCode

Overrides Object

This method returns a hash code for the OracleIntervalYM instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

An int representing a hash code.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

ToString

Overrides Object

This method converts the current OracleIntervalYM structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string that represents the current OracleIntervalYM structure.

Remarks

If the current instance has a null value, the returned string contain "null".

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleString Structure

The `OracleString` structure represents a variable-length stream of characters to be stored in or retrieved from a database.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleString`

Declaration

```
// C#
public struct OracleString : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleStringSample
{
    static void Main()
```

```
{
// Initialize OracleString structs
OracleString string1 = new OracleString("AAA");

// Display the string "AAA"
Console.WriteLine("{0} has length of {1}", string1, string1.Length);

// Contatenate characters to string1 until the length is 5
while (string1.Length < 5)
    string1 = OracleString.Concat(string1,"a");

// Display the string of "AAAaa"
Console.WriteLine("{0} has length of {1}", string1, string1.Length);
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Members](#)
- [OracleString Constructors](#)
- [OracleString Static Fields](#)
- [OracleString Static Methods](#)
- [OracleString Static Operators](#)
- [OracleString Type Conversions](#)
- [OracleString Properties](#)
- [OracleString Methods](#)

OracleString Members

OracleString members are listed in the following tables:

OracleString Constructors

OracleString constructors are listed in [Table 14-87](#)

Table 14-87 OracleString Constructors

Constructor	Description
OracleString Constructors	Instantiates a new instance of OracleString structure (Overloaded)

OracleString Static Fields

The OracleString static fields are listed in [Table 14-88](#).

Table 14-88 OracleString Static Fields

Field	Description
Null	Represents a null value that can be assigned to an instance of the <code>OracleString</code> structure

OracleString Static Methods

The `OracleString` static methods are listed in [Table 14-89](#).

Table 14-89 OracleString Static Methods

Methods	Description
Concat	Concatenates two <code>OracleString</code> instances and returns a new <code>OracleString</code> instance that represents the result
Equals	Determines if two <code>OracleString</code> values are equal (Overloaded)
GreaterThan	Determines whether or not the first of two <code>OracleString</code> values is greater than the second
GreaterThanOrEqual	Determines whether or not the first of two <code>OracleString</code> values is greater than or equal to the second
LessThan	Determines whether or not the first of two <code>OracleString</code> values is less than the second
LessThanOrEqual	Determines whether or not the first of two <code>OracleString</code> values is less than or equal to the second
NotEquals	Determines whether two <code>OracleString</code> values are not equal

OracleString Static Operators

The `OracleString` static operators are listed in [Table 14-90](#).

Table 14-90 OracleString Static Operators

Operator	Description
operator +	Concatenates two <code>OracleString</code> values
operator ==	Determines if two <code>OracleString</code> values are equal
operator >	Determines if the first of two <code>OracleString</code> values is greater than the second
operator >=	Determines if the first of two <code>OracleString</code> values is greater than or equal to the second
operator !=	Determines if the two <code>OracleString</code> values are not equal

Table 14-90 (Cont.) OracleString Static Operators

Operator	Description
operator <	Determines if the first of two OracleString values is less than the second
operator <=	Determines if two OracleString values are not equal

OracleString Type Conversions

The OracleString type conversions are listed in [Table 14-91](#).

Table 14-91 OracleString Type Conversions

Operator	Description
explicit operator string	Converts the supplied OracleString to a string instance
implicit operator OracleString	Converts the supplied string to an OracleString instance

OracleString Properties

The OracleString properties are listed in [Table 14-92](#).

Table 14-92 OracleString Properties

Properties	Description
IsCaseIgnored	Indicates whether or not case should be ignored when performing string comparison
IsNull	Indicates whether or not the current instance has a null value
Item	Obtains the particular character in an OracleString using an index.
Length	Returns the length of the OracleString
Value	Returns the string data that is stored in the OracleString structure.

OracleString Methods

The OracleString methods are listed in [Table 14-93](#).

Table 14-93 OracleString Methods

Methods	Description
Clone	Returns a copy of the current OracleString instance

Table 14-93 (Cont.) OracleString Methods

Methods	Description
CompareTo	Compares the current <code>OracleString</code> instance to the supplied object, and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same string value as the current <code>OracleString</code> structure (Overloaded)
GetHashCode	Returns a hash code for the <code>OracleString</code> instance
GetNonUnicodeBytes	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in the client character set format
GetType	Inherited from <code>System.Object</code>
GetUnicodeBytes	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in Unicode format
ToString	Converts the current <code>OracleString</code> instance to a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)

OracleString Constructors

The `OracleString` constructors create new instances of the `OracleString` structure.

Overload List:

- [OracleString\(string\)](#)
This constructor creates a new instance of the `OracleString` structure and sets its value using a string.
- [OracleString\(string, bool\)](#)
This constructor creates a new instance of the `OracleString` structure and sets its value using a string and specifies if case is ignored in comparison.
- [OracleString\(byte \[\], bool\)](#)
This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies if the supplied byte array is Unicode encoded.
- [OracleString\(byte \[\], bool, bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies the following: if the supplied byte array is Unicode encoded and if case is ignored in comparison.

- [OracleString\(byte \[\], int, int, bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, and if the supplied byte array is Unicode encoded.

- [OracleString\(byte \[\], int, int, bool, bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, if the supplied byte array is Unicode encoded, and if case is ignored in comparison.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(string)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string.

Declaration

```
// C#  
public OracleString(string data);
```

Parameters

- *data*
A string value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(string, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string and specifies if case is ignored in comparison.

Declaration

```
// C#  
public OracleString(string data, bool isCaseIgnored);
```

Parameters

- *data*
A string value.
- *isCaseIgnored*
Specifies if case is ignored in comparison. Specifies `true` if case is to be ignored; otherwise, specifies `false`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies if the supplied byte array is Unicode encoded.

Declaration

```
// C#  
public OracleString(byte[] data, bool fUnicode);
```

Parameters

- *data*
Byte array data for the new `OracleString`.
- *fUnicode*
Specifies if the supplied *data* is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.

Exceptions

`ArgumentNullException` - The *data* parameter is null.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], bool, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies the following: if the supplied byte array is Unicode encoded and if case is ignored in comparison.

Declaration

```
// C#  
public OracleString(byte[] data, bool fUnicode, bool isCaseIgnored);
```

Parameters

- *data*
Byte array data for the new `OracleString`.
- *fUnicode*
Specifies if the supplied `data` is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.
- *isCaseIgnored*
Specifies if case is ignored in comparison. Specifies `true` if case is to be ignored; otherwise, specifies `false`.

Exceptions

`ArgumentNullException` - The *data* parameter is null.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], int, int, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte

array, the number of bytes to copy from the byte array, and if the supplied byte array is Unicode encoded.

Declaration

```
// C#  
public OracleString(byte[] data, int index, int count, bool fUnicode);
```

Parameters

- *data*
Byte array data for the new `OracleString`.
- *index*
The starting index to copy from *data*.
- *count*
The number of bytes to copy.
- *fUnicode*
Specifies if the supplied *data* is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.

Exceptions

`ArgumentNullException` - The *data* parameter is null.

`ArgumentOutOfRangeException` - The *count* parameter is less than zero.

`IndexOutOfRangeException` - The *index* parameter is greater than or equal to the length of *data* or less than zero.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], int, int, bool, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, if the supplied byte array is Unicode encoded, and if case is ignored in comparison.

Declaration

```
// C#  
public OracleString(byte[] data, int index, int count, bool fUnicode,  
    bool isCaseIgnored);
```

Parameters

- *data*
Byte array data for the new `OracleString`.
- *index*
The starting index to copy from *data*.
- *count*
The number of bytes to copy.
- *fUnicode*
Specifies if the supplied *data* is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.
- *isCaseIgnored*
Specifies if case is ignored in comparison. Specifies `true` if case is to be ignored; otherwise, specifies `false`.

Exceptions

`ArgumentNullException` - The *data* parameter is null.

`ArgumentOutOfRangeException` - The *count* parameter is less than zero.

`IndexOutOfRangeException` - The *index* parameter is greater than or equal to the length of *data* or less than zero.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Static Fields

The `OracleString` static fields are listed in [Table 14-94](#).

Table 14-94 OracleString Static Fields

Field	Description
Null	Represents a null value that can be assigned to an instance of the <code>OracleString</code> structure

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleString` structure.

Declaration

```
// C#
public static readonly OracleString Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Static Methods

The `OracleString` static methods are listed in [Table 14-95](#).

Table 14-95 OracleString Static Methods

Methods	Description
Concat	Concatenates two <code>OracleString</code> instances and returns a new <code>OracleString</code> instance that represents the result
Equals	Determines if two <code>OracleString</code> values are equal (Overloaded)
GreaterThan	Determines whether or not the first of two <code>OracleString</code> values is greater than the second
GreaterThanOrEqual	Determines whether or not the first of two <code>OracleString</code> values is greater than or equal to the second
LessThan	Determines whether or not the first of two <code>OracleString</code> values is less than the second
LessThanOrEqual	Determines whether or not the first of two <code>OracleString</code> values is less than or equal to the second
NotEquals	Determines whether two <code>OracleString</code> values are not equal

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Concat

This static method concatenates two `OracleString` instances and returns a new `OracleString` instance that represents the result.

Declaration

```
// C#  
public static OracleString Concat(OracleString str1, OracleString str2);
```

Parameters

- `str1`
The first `OracleString`.
- `str2`
The second `OracleString`.

Return Value

An `OracleString`.

Remarks

If either argument has a null value, the returned `OracleString` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Equals

Overloads `Object`

This static method determines whether or not the two `OracleStrings` being compared are equal.

Declaration

```
// C#  
public static bool Equals(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first OracleString.
- *str2*
The second OracleString.

Return Value

Returns `true` if the two OracleStrings being compared are equal; returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleString that has a value is greater than an OracleString that has a null value.
- Two OracleStrings that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

GreaterThan

This static method determines whether or not the first of two OracleString values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first OracleString.
- *str2*
The second OracleString.

Return Value

Returns `true` if the first of two `OracleStrings` is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

GreaterThanOrEqual

This static method determines whether or not the first of two `OracleString` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleString str1,  
    OracleString str2);
```

Parameters

- *str1*
The first `OracleString`.
- *str2*
The second `OracleString`.

Return Value

Returns `true` if the first of two `OracleStrings` is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

LessThan

This static method determines whether or not the first of two `OracleString` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first `OracleString`.
- *str2*
The second `OracleString`.

Return Value

Returns `true` if the first is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

LessThanOrEqualTo

This static method determines whether or not the first of two `OracleString` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqualTo(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first `OracleString`.
- *str2*
The second `OracleString`.

Return Value

Returns `true` if the first is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

NotEquals

This static method determines whether two `OracleString` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first `OracleString`.

- `str2`
The second `OracleString`.

Return Value

Returns `true` if the two `OracleString` instances are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Static Operators

The `OracleString` static operators are listed in [Table 14-96](#).

Table 14-96 OracleString Static Operators

Operator	Description
<code>operator +</code>	Concatenates two <code>OracleString</code> values
<code>operator ==</code>	Determines if two <code>OracleString</code> values are equal
<code>operator ></code>	Determines if the first of two <code>OracleString</code> values is greater than the second
<code>operator >=</code>	Determines if the first of two <code>OracleString</code> values is greater than or equal to the second
<code>operator !=</code>	Determines if the two <code>OracleString</code> values are not equal
<code>operator <</code>	Determines if the first of two <code>OracleString</code> values is less than the second
<code>operator <=</code>	Determines if two <code>OracleString</code> values are not equal

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator +

This static operator concatenates two `OracleString` values.

Declaration

```
// C#  
public static OracleString operator + (OracleString value1, OracleString value2);
```

Parameters

- `value1`
The first `OracleString`.
- `value2`
The second `OracleString`.

Return Value

An `OracleString`.

Remarks

If either argument has a null value, the returned `OracleString` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator ==

This static operator determines if two `OracleString` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*
The second `OracleString`.

Return Value

Returns `true` if two `OracleString` values are equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator >

This static operator determines if the first of two `OracleString` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*
The second `OracleString`.

Return Value

Returns `true` if the first of two `OracleString` values is greater than the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator >=

This static operator determines if the first of two `OracleString` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleString value1, OracleString value2);
```

Parameters

- `value1`
The first `OracleString`.
- `value2`
The second `OracleString`.

Return Value

Returns `true` if the first of two `OracleString` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator !=

This static operator determines if two `OracleString` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleString value1, OracleString value2);
```

Parameters

- `value1`
The first `OracleString`.
- `value2`
The second `OracleString`.

Return Value

Returns `true` if two `OracleString` values are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator <

This static operator determines if the first of two `OracleStrings` is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first OracleString.
- *value2*
The second OracleString.

Return Value

Returns true if the first of two OracleStrings is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleString that has a value is greater than an OracleString has a null value.
- Two OracleStrings that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator <=

This static operator determines if the first of two OracleString values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleString value1, OracleString value1);
```

Parameters

- *value1*
The first OracleString.
- *value2*
The second OracleString.

Return Value

Returns `true` if the first of two `OracleString` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Type Conversions

The `OracleString` type conversions are listed in [Table 14-97](#).

Table 14-97 OracleString Type Conversions

Operator	Description
explicit operator string	Converts the supplied <code>OracleString</code> to a <code>string</code> instance
implicit operator OracleString	Converts the supplied <code>string</code> to an <code>OracleString</code> instance

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

explicit operator string

This type conversion operator converts the supplied `OracleString` to a `string`.

Declaration

```
//C#  
public static explicit operator string (OracleString value1);
```

Parameters

- *value1*
The supplied OracleString.

Return Value

string

Exceptions

OracleNullValueException - The OracleString structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

implicit operator OracleString

This type conversion operator converts the supplied string to an OracleString.

Declaration

```
// C#  
public static implicit operator OracleString (string value1);
```

Parameters

- *value1*
The supplied string.

Return Value

An OracleString.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Properties

The `OracleString` properties are listed in [Table 14-98](#).

Table 14-98 OracleString Properties

Properties	Description
IsCaseIgnored	Indicates whether or not case should be ignored when performing string comparison
IsNull	Indicates whether or not the current instance has a null value
Item	Obtains the particular character in an <code>OracleString</code> using an index.
Length	Returns the length of the <code>OracleString</code>
Value	Returns the string data that is stored in the <code>OracleString</code> structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

IsCaseIgnored

This property indicates whether or not case should be ignored when performing string comparison.

Declaration

```
//C#  
public bool IsCaseIgnored {get;set;}
```

Property Value

Returns `true` if string comparison must ignore case; otherwise `false`.

Remarks

Default value is true.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class IsCaseIgnoredSample
{
    static void Main()
    {
        OracleString string1 = new OracleString("aAaAa");
        OracleString string2 = new OracleString("AaAaA");

        // Ignore case for comparisons
        string1.IsCaseIgnored = true;
        string2.IsCaseIgnored = true;

        // Same; Prints 0
        Console.WriteLine(string1.CompareTo(string2));

        // Make comparisons case sensitive
        // Note that IsCaseIgnored must be set to false for both
        // OracleStrings; otherwise an exception is thrown
        string1.IsCaseIgnored = false;
        string2.IsCaseIgnored = false;

        // Different; Prints nonzero value
        Console.WriteLine(string1.CompareTo(string2));
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

IsNull

This property indicates whether or not the current instance contains a null value.

Declaration

```
// C#
public bool IsNull {get;}
```

Property Value

Returns `true` if the current instance contains has a null value; otherwise, returns `false`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Item

This property obtains the particular character in an `OracleString` using an index.

Declaration

```
// C#  
public char Item {get;}
```

Property Value

A `char` value.

Exceptions

`OracleNullValueException` - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Length

This property returns the length of the `OracleString`.

Declaration

```
// C#  
public int Length {get;}
```

Property Value

A `int` value.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Value

This property returns the string data that is stored in the `OracleString`.

Declaration

```
// C#
public string Value {get;}
```

Property Value

The stored string value

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Methods

The `OracleString` methods are listed in [Table 14-99](#).

Table 14-99 OracleString Methods

Methods	Description
Clone	Returns a copy of the current <code>OracleString</code> instance
CompareTo	Compares the current <code>OracleString</code> instance to the supplied object, and returns an integer that represents their relative values

Table 14-99 (Cont.) OracleString Methods

Methods	Description
Equals	Determines whether or not an object has the same string value as the current <code>OracleString</code> structure (Overloaded)
GetHashCode	Returns a hash code for the <code>OracleString</code> instance
GetNonUnicodeBytes	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in the client character set format
<code>GetType</code>	Inherited from <code>System.Object</code>
GetUnicodeBytes	Returns an array of bytes, containing the contents of the <code>OracleString</code> , in Unicode format
ToString	Converts the current <code>OracleString</code> instance to a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Clone

This method creates a copy of an `OracleString` instance.

Declaration

```
// C#  
public OracleString Clone();
```

Return Value

An `OracleString` structure.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class CloneSample  
{  
    static void Main()  
    {  
        OracleString str1 = new OracleString("aAaAa");  
    }  
}
```

```
OracleString str2 = str1.Clone();

// The OracleStrings are same; Prints 0
Console.WriteLine(str1.CompareTo(str2));
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

CompareTo

This method compares the current `OracleString` instance to the supplied object, and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared to the current instance.

Return Value

The method returns a number that is:

- Less than zero: if the current `OracleString` value is less than *obj*.
- Zero: if the current `OracleString` value is equal to *obj*.
- Greater than zero: if the current `OracleString` value is greater than *obj*.

Implements

`IComparable`

Exceptions

`ArgumentException` - The *obj* parameter is not of type `OracleString`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleStrings`. For example, comparing an `OracleString` instance with an `OracleBinary` instance is not allowed. When an `OracleString` is compared with a different type, an `ArgumentException` is thrown.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

Equals

This method determines whether or not supplied object is an instance of `OracleString` and has the same values as the current `OracleString` instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*
An object being compared.

Return Value

Returns `true` if the supplied object is an instance of `OracleString` and has the same values as the current `OracleString` instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleString` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

GetNonUnicodeBytes

This method returns an array of bytes, containing the contents of the `OracleString`, in the client character set format.

Declaration

```
// C#  
public byte[] GetNonUnicodeBytes();
```

Return Value

A byte array that contains the contents of the `OracleString` in the client character set format.

Remarks

If the current instance has a null value, an `OracleNullValueException` is thrown.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

GetUnicodeBytes

This method returns an array of bytes, containing the contents of the `OracleString` in Unicode format.

Declaration

```
// C#  
public byte[] GetUnicodeBytes();
```

Return Value

A byte array that contains the contents of the `OracleString` in Unicode format.

Remarks

If the current instance has a null value, an `OracleNullValueException` is thrown.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

ToString

Overrides `Object`

This method converts the current `OracleString` instance to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string.

Remarks

If the current `OracleString` instance has a null value, the string contains "null".

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleTimeStamp Structure

The `OracleTimeStamp` structure represents the Oracle `TIMESTAMP` data type to be stored in or retrieved from a database. Each `OracleTimeStamp` stores the following information: year, month, day, hour, minute, second, and nanosecond.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleTimeStamp`

Declaration

```
// C#public struct OracleTimeStamp : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	<code>Oracle.DataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>	<code>Oracle.ManagedDataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>	<code>Oracle.ManagedDataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#
using System;
using Oracle.DataAccess.Types;

class OracleTimeStampSample
{
    static void Main()
```

```

{
OracleTimeStamp tsCurrent1 = OracleTimeStamp.GetSysDate();
OracleTimeStamp tsCurrent2 = DateTime.Now;

// Calculate the difference between tsCurrent1 and tsCurrent2
OracleIntervalDS idsDiff = tsCurrent2.GetDaysBetween(tsCurrent1);

// Calculate the difference using AddNanoseconds()
int nanoDiff = 0;
while (tsCurrent2 > tsCurrent1)
{
nanoDiff += 10;
tsCurrent1 = tsCurrent1.AddNanoseconds(10);
}
Console.WriteLine("idsDiff.Nanoseconds = " + idsDiff.Nanoseconds);
Console.WriteLine("nanoDiff = " + nanoDiff);
}
}

```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Members](#)
- [OracleTimeStamp Constructors](#)
- [OracleTimeStamp Static Fields](#)
- [OracleTimeStamp Static Methods](#)
- [OracleTimeStamp Static Operators](#)
- [OracleTimeStamp Static Type Conversions](#)
- [OracleTimeStamp Properties](#)
- [OracleTimeStamp Methods](#)

OracleTimeStamp Members

OracleTimeStamp members are listed in the following tables:

OracleTimeStamp Constructors

OracleTimeStamp constructors are listed in [Table 14-100](#)

Table 14-100 OracleTimeStamp Constructors

Constructor	Description
OracleTimeStamp Constructors	Instantiates a new instance of OracleTimeStamp structure (Overloaded)

OracleTimeStamp Static Fields

The OracleTimeStamp static fields are listed in [Table 14-101](#).

Table 14-101 OracleTimeStamp Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an OracleTimeStamp structure, which is December 31, 9999 23:59:59.999999999
MinValue	Represents the minimum valid date for an OracleTimeStamp structure, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to an instance of the OracleTimeStamp structure

OracleTimeStamp Static Methods

The OracleTimeStamp static methods are listed in [Table 14-102](#).

Table 14-102 OracleTimeStamp Static Methods

Methods	Description
Equals	Determines if two OracleTimeStamp values are equal (Overloaded)
GreaterThan	Determines if the first of two OracleTimeStamp values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleTimeStamp values is greater than or equal to the second
LessThan	Determines if the first of two OracleTimeStamp values is less than the second
LessThanOrEqual	Determines if the first of two OracleTimeStamp values is less than or equal to the second
NotEquals	Determines if two OracleTimeStamp values are not equal
GetSysDate	Gets an OracleTimeStamp structure that represents the current date and time
Parse	Gets an OracleTimeStamp structure and sets its value using the supplied string
SetPrecision	Returns a new instance of an OracleTimeStamp with the specified fractional second precision

OracleTimeStamp Static Operators

The OracleTimeStamp static operators are listed in [Table 14-103](#).

Table 14-103 OracleTimeStamp Static Operators

Operator	Description
operator +	Adds the supplied instance value to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded)
operator ==	Determines if two OracleTimeStamp values are equal
operator >	Determines if the first of two OracleTimeStamp values is greater than the second
operator >=	Determines if the first of two OracleTimeStamp values is greater than or equal to the second
operator !=	Determines if the two OracleTimeStamp values are not equal
operator <	Determines if the first of two OracleTimeStamp values is less than the second
operator <=	Determines if the first of two OracleTimeStamp values is less than or equal to the second
operator -	Subtracts the supplied instance value from the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded)

OracleTimeStamp Static Type Conversions

The OracleTimeStamp static type conversions are listed in [Table 14-104](#).

Table 14-104 OracleTimeStamp Static Type Conversions

Operator	Description
explicit operator OracleTimeStamp	Converts an instance value to an OracleTimeStamp structure (Overloaded)
implicit operator OracleTimeStamp	Converts an instance value to an OracleTimeStamp structure (Overloaded)
explicit operator DateTime	Converts an OracleTimeStamp value to a DateTime structure

OracleTimeStamp Properties

The OracleTimeStamp properties are listed in [Table 14-105](#).

Table 14-105 OracleTimeStamp Properties

Properties	Description
BinData	Returns an array of bytes that represents an Oracle TIMESTAMP in Oracle internal format
Day	Specifies the day component of an OracleTimeStamp

Table 14-105 (Cont.) OracleTimeStamp Properties

Properties	Description
IsNull	Indicates whether or not the OracleTimeStamp instance has a null value
Hour	Specifies the hour component of an OracleTimeStamp
Millisecond	Specifies the millisecond component of an OracleTimeStamp
Minute	Specifies the minute component of an OracleTimeStamp
Month	Specifies the month component of an OracleTimeStamp
Nanosecond	Specifies the nanosecond component of an OracleTimeStamp
Second	Specifies the second component of an OracleTimeStamp
Value	Specifies the date and time that is stored in the OracleTimeStamp structure
Year	Specifies the year component of an OracleTimeStamp

OracleTimeStamp Methods

The OracleTimeStamp methods are listed in [Table 14-106](#).

Table 14-106 OracleTimeStamp Methods

Methods	Description
AddDays	Adds the supplied number of days to the current instance
AddHours	Adds the supplied number of hours to the current instance
AddMilliseconds	Adds the supplied number of milliseconds to the current instance
AddMinutes	Adds the supplied number of minutes to the current instance
AddMonths	Adds the supplied number of months to the current instance
AddNanoseconds	Adds the supplied number of nanoseconds to the current instance
AddSeconds	Adds the supplied number of seconds to the current instance
AddYears	Adds the supplied number of years to the current instance

Table 14-106 (Cont.) OracleTimeStamp Methods

Methods	Description
CompareTo	Compares the current OracleTimeStamp instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current OracleTimeStamp instance (Overloaded)
GetHashCode	Returns a hash code for the OracleTimeStamp instance
GetDaysBetween	Subtracts an OracleTimeStamp value from the current instance and returns an OracleIntervalDS that represents the time difference between the supplied OracleTimeStamp and the current instance
GetYearsBetween	Subtracts value1 from the current instance and returns an OracleIntervalYM that represents the difference between value1 and the current instance using OracleIntervalYM
GetType	Inherited from System.Object
ToOracleDate	Converts the current OracleTimeStamp structure to an OracleDate structure
ToOracleTimeStampLTZ	Converts the current OracleTimeStamp structure to an OracleTimeStampLTZ structure
ToOracleTimeStampTZ	Converts the current OracleTimeStamp structure to an OracleTimeStampTZ structure
ToString	Converts the current OracleTimeStamp structure to a string

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)

OracleTimeStamp Constructors

The OracleTimeStamp constructors create new instances of the OracleTimeStamp structure.

Overload List:

- [OracleTimeStamp\(DateTime\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using the supplied `DateTime` value.

- [OracleTimeStamp\(string\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value using the supplied string.

- [OracleTimeStamp\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date using year, month, and day.

- [OracleTimeStamp\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, and second.

- [OracleTimeStamp\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

- [OracleTimeStamp\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

- [OracleTimeStamp\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP` format.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(DateTime)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleTimeStamp (DateTime dt);
```

Parameters

- *dt*
The supplied `DateTime` value.

Exceptions

`ArgumentException` - The `dt` parameter cannot be used to construct a valid `OracleTimeStamp`.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(string)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value using the supplied string.

Declaration

```
// C#  
public OracleTimeStamp (string tsStr);
```

Parameters

- `tsStr`
A string that represents an Oracle `TIMESTAMP`.

Exceptions

`ArgumentException` - The `tsStr` value is an invalid string representation of an Oracle `TIMESTAMP` or the supplied `tsStr` is not in the timestamp format specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The `tsStr` value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class OracleTimeStampSample
```

```
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStamp(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleTimeStamp(int, int, int)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date using year, month, and day.

Declaration

```
// C#
public OracleTimeStamp(int year, int month, int day);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*

The day provided. Range of *day* is (1 to 31).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, and second.

Declaration

```
// C#  
public OracleTimeStamp (int year, int month, int day, int hour,  
    int minute, int second);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(int, int, int, int, int, int, double)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

Declaration

```
// C#
public OracleTimeStamp(int year, int month, int day, int hour,
    int minute, int second, double millisecond);
```

Parameters

- *year*
The year provided. Range of year is (-4712 to 9999).
- *month*
The month provided. Range of month is (1 to 12).
- *day*
The day provided. Range of day is (1 to 31).
- *hour*
The hour provided. Range of hour is (0 to 23).
- *minute*
The minute provided. Range of minute is (0 to 59).
- *second*
The second provided. Range of second is (0 to 59).
- *milliSeconds*
The milliseconds provided. Range of millisecond is (0 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(int, int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using `year`, `month`, `day`, `hour`, `minute`, `second`, and `nanosecond`.

Declaration

```
// C#  
public OracleTimeStamp (int year, int month, int day, int hour,  
    int minute, int second, int nanosecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(byte [])

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP` format.

Declaration

```
// C#  
public OracleTimeStamp (byte[] bytes);
```

Parameters

- *bytes*
A byte array that represents an Oracle `TIMESTAMP` in Oracle internal format.

Exceptions

`ArgumentException` - *bytes* is not in an internal Oracle `TIMESTAMP` format or *bytes* is not a valid Oracle `TIMESTAMP`.

`ArgumentNullException` - *bytes* is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Fields

The OracleTimeStamp static fields are listed in [Table 14-107](#).

Table 14-107 OracleTimeStamp Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an OracleTimeStamp structure, which is December 31, 9999 23:59:59.999999999
MinValue	Represents the minimum valid date for an OracleTimeStamp structure, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to an instance of the OracleTimeStamp structure

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

MaxValue

This static field represents the maximum valid date and time for an OracleTimeStamp structure, which is December 31, 9999 23:59:59.999999999.

Declaration

```
// C#  
public static readonly OraTimestamp MaxValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

MinValue

This static field represents the minimum valid date and time for an OracleTimeStamp structure, which is January 1, -4712 0:0:0.

Declaration

```
// C#  
public static readonly OracleTimeStamp MinValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStamp` structure.

Declaration

```
// C#  
public static readonly OracleTimeStamp Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Methods

The `OracleTimeStamp` static methods are listed in [NOT_SUPPORTED](#).

NOT_SUPPORTED

Methods	Description
Equals	Determines if two <code>OracleTimeStamp</code> values are equal (Overloaded)
GreaterThan	Determines if the first of two <code>OracleTimeStamp</code> values is greater than the second
GreaterThanOrEqual	Determines if the first of two <code>OracleTimeStamp</code> values is greater than or equal to the second
LessThan	Determines if the first of two <code>OracleTimeStamp</code> values is less than the second

NOT_SUPPORTED

Methods	Description
LessThanOrEqualTo	Determines if the first of two OracleTimeStamp values is less than or equal to the second
NotEquals	Determines if two OracleTimeStamp values are not equal
GetSysDate	Gets an OracleTimeStamp structure that represents the current date and time
Parse	Gets an OracleTimeStamp structure and sets its value using the supplied string
SetPrecision	Returns a new instance of an OracleTimeStamp with the specified fractional second precision

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Equals

This static method determines if two OracleTimeStamp values are equal.

Declaration

```
// C#  
public static bool Equals(OracleTimeStamp value1, OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns `true` if two OracleTimeStamp values are equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.

- Two OracleTimeStamp values that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GreaterThan

This static method determines if the first of two OracleTimeStamp values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if the first of two OracleTimeStamp values is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamp values that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GreaterThanOrEqualTo

This static method determines if the first of two `OracleTimeStamp` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqualTo(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- `value1`
The first `OracleTimeStamp`.
- `value2`
The second `OracleTimeStamp`.

Return Value

Returns `true` if the first of two `OracleTimeStamp` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

LessThan

This static method determines if the first of two `OracleTimeStamp` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if the first of two OracleTimeStamp values is less than the second. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

LessThanOrEqual

This static method determines if the first of two OracleTimeStamp values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns `true` if the first of two `OracleTimeStamp` values is less than or equal to the second. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

NotEquals

This static method determines if two `OracleTimeStamp` values are not equal.

Declaration

```
// C#
public static bool NotEquals(OracleTimeStamp value1,
    OracleTimeStamp value2);
```

Parameters

- `value1`
The first `OracleTimeStamp`.
- `value2`
The second `OracleTimeStamp`.

Return Value

Returns `true` if two `OracleTimeStamp` values are not equal. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetSysDate

This static method gets an `OracleTimeStamp` structure that represents the current date and time.

Declaration

```
// C#  
public static OracleTimeStamp GetSysDate();
```

Return Value

An `OracleTimeStamp` structure that represents the current date and time.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Parse

This static method gets an `OracleTimeStamp` structure and sets its value using the supplied string.

Declaration

```
// C#  
public static OracleTimeStamp Parse(string datetime);
```

Parameters

- *datetime*
A string that represents an Oracle `TIMESTAMP`.

Return Value

An `OracleTimeStamp` structure.

Exceptions

ArgumentException - The *tsStr* is an invalid string representation of an Oracle TIMESTAMP or the supplied *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle NLS_TIMESTAMP_FORMAT parameter.

ArgumentNullException - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the Parse() method
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts =
            OracleTimeStamp.Parse("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

SetPrecision

This static method returns a new instance of an `OracleTimeStamp` with the specified fractional second precision.

Declaration

```
// C#  
public static OracleTimeStamp SetPrecision(OracleTimeStamp value1,  
    int fracSecPrecision);
```

Parameters

- *value1*
The provided `OracleTimeStamp` object.
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An `OracleTimeStamp` structure with the specified fractional second precision.

Exceptions

`ArgumentOutOfRangeException` - *fracSecPrecision* is out of the specified range.

Remarks

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleTimeStamp` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

Example

The `OracleTimeStamp` with a value of "December 31, 9999 23:59:59.99" results in the string "December 31, 9999 23:59:59.99000" when `SetPrecision()` is called with the fractional second precision set to 5.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Operators

The OracleTimeStamp static operators are listed in [Table 14-109](#).

Table 14-109 OracleTimeStamp Static Operators

Operator	Description
operator +	Adds the supplied instance value to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded)
operator ==	Determines if two OracleTimeStamp values are equal
operator >	Determines if the first of two OracleTimeStamp values is greater than the second
operator >=	Determines if the first of two OracleTimeStamp values is greater than or equal to the second
operator !=	Determines if the two OracleTimeStamp values are not equal
operator <	Determines if the first of two OracleTimeStamp values is less than the second
operator <=	Determines if the first of two OracleTimeStamp values is less than or equal to the second
operator -	Subtracts the supplied instance value from the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded)

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator +

`operator+` adds the supplied object to the OracleTimeStamp and returns a new OracleTimeStamp structure.

Overload List:

- [operator + \(OracleTimeStamp, OracleIntervalDS\)](#)
This static operator adds the supplied `OracleIntervalDS` to the `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.
- [operator + \(OracleTimeStamp, OracleIntervalYM\)](#)
This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.
- [operator + \(OracleTimeStamp, TimeSpan\)](#)
This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator + (OracleTimeStamp, OracleIntervalDS)

This static operator adds the supplied `OracleIntervalDS` to the `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator + (OracleTimeStamp value1, OracleIntervalDS value2);
```

Parameters

- `value1`
An `OracleTimeStamp`.
- `value2`
An `OracleIntervalDS`.

Return Value

An `OracleTimeStamp`.

Remarks

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator + (OracleTimeStamp, OracleIntervalYM)

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator + (OracleTimeStamp value1, OracleIntervalYM value2);
```

Parameters

- `value1`
An `OracleTimeStamp`.
- `value2`
An `OracleIntervalYM`.

Return Value

An `OracleTimeStamp`.

Remarks

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator + (OracleTimeStamp, TimeSpan)

This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator + (OracleTimeStamp value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStamp.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStamp.

Remarks

If the OracleTimeStamp instance has a null value, the returned OracleTimeStamp has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator ==

This static operator determines if two OracleTimeStamp values are equal.

Declaration

```
// C#  
public static bool operator == (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if they are the same; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamp`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator >

This static operator determines if the first of two `OracleTimeStamp` values is greater than the second.

Declaration

```
// C#
public static bool operator > (OracleTimeStamp value1,
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first `OracleTimeStamp`.
- *value2*
The second `OracleTimeStamp`.

Return Value

Returns `true` if the first `OracleTimeStamp` value is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamp`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator >=

This static operator determines if the first of two `OracleTimeStamp` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- `value1`
The first `OracleTimeStamp`.
- `value2`
The second `OracleTimeStamp`.

Return Value

Returns `true` if the first `OracleTimeStamp` is greater than or equal to the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamp`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator !=

This static operator determines if two `OracleTimeStamp` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- `value1`
The first `OracleTimeStamp`.
- `value2`
The second `OracleTimeStamp`.

Return Value

Returns `true` if two `OracleTimeStamp` values are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator <

This static operator determines if the first of two `OracleTimeStamp` values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- `value1`

The first OracleTimeStamp.

- *value2*

The second OracleTimeStamp.

Return Value

Returns `true` if the first OracleTimeStamp is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator <=

This static operator determines if the first of two OracleTimeStamp values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns `true` if the first OracleTimeStamp is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator -

operator- subtracts the supplied value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.

Overload List:

- [operator - \(OracleTimeStamp, OracleIntervalDS\)](#)
This static operator subtracts the supplied OracleIntervalDS value, from the supplied OracleTimeStamp value, and return a new OracleTimeStamp structure.
- [operator - \(OracleTimeStamp, OracleIntervalYM\)](#)
This static operator subtracts the supplied OracleIntervalYM value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.
- [operator - \(OracleTimeStamp, TimeSpan\)](#)
This static operator subtracts the supplied TimeSpan value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator - (OracleTimeStamp, OracleIntervalDS)

This static operator subtracts the supplied OracleIntervalDS value, from the supplied OracleTimeStamp value, and return a new OracleTimeStamp structure.

Declaration

```
// C#  
public static operator - (OracleTimeStamp value1, OracleIntervalDS value2);
```

Parameters

- *value1*
An OracleTimeStamp.
- *value2*
An OracleIntervalDS instance.

Return Value

An OracleTimeStamp structure.

Remarks

If either parameter has a null value, the returned OracleTimeStamp has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator - (OracleTimeStamp, OracleIntervalYM)

This static operator subtracts the supplied OracleIntervalYM value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.

Declaration

```
// C#  
public static operator - (OracleTimeStamp value1, OracleIntervalYM value2);
```

Parameters

- *value1*
An OracleTimeStamp.
- *value2*
An OracleIntervalYM instance.

Return Value

An OracleTimeStamp structure.

Remarks

If either parameter has a null value, the returned OracleTimeStamp has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator - (OracleTimeStamp, TimeSpan)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStamp` value, and returns a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStamp value1, TimeSpan value2);
```

Parameters

- `value1`
An `OracleTimeStamp`.
- `value2`
A `TimeSpan` instance.

Return Value

An `OracleTimeStamp` structure.

Remarks

If the `OracleTimeStamp` instance has a null value, the returned `OracleTimeStamp` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Type Conversions

The `OracleTimeStamp` static type conversions are listed in [Table 14-110](#).

Table 14-110 OracleTimeStamp Static Type Conversions

Operator	Description
explicit operator OracleTimeStamp	Converts an instance value to an OracleTimeStamp structure (Overloaded)
implicit operator OracleTimeStamp	Converts an instance value to an OracleTimeStamp structure (Overloaded)
explicit operator DateTime	Converts an OracleTimeStamp value to a DateTime structure

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp

`explicit operator OracleTimeStamp` converts the supplied value to an OracleTimeStamp structure

Overload List:

- [explicit operator OracleTimeStamp\(OracleTimeStampLTZ\)](#)
This static type conversion operator converts an OracleTimeStampLTZ value to an OracleTimeStamp structure.
- [explicit operator OracleTimeStamp\(OracleTimeStampTZ\)](#)
This static type conversion operator converts an OracleTimeStampTZ value to an OracleTimeStamp structure.
- [explicit operator OracleTimeStamp\(string\)](#)
This static type conversion operator converts the supplied string to an OracleTimeStamp structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp(OracleTimeStampLTZ)

This static type conversion operator converts an `OracleTimeStampLTZ` value to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStamp(OracleTimeStampLTZ value1);
```

Parameters

- `value1`
An `OracleTimeStampLTZ` instance.

Return Value

The returned `OracleTimeStamp` contains the date and time of the `OracleTimeStampLTZ` structure.

Remarks

If the `OracleTimeStampLTZ` structure has a null value, the returned `OracleTimeStamp` structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp(OracleTimeStampTZ)

This static type conversion operator converts an `OracleTimeStampTZ` value to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStamp(OracleTimeStampTZ value1);
```

Parameters

- `value1`
An `OracleTimeStampTZ` instance.

Return Value

The returned `OracleTimeStamp` contains the date and time information from `value1`, but the time zone information from `value1` is truncated.

Remarks

If the `OracleTimeStampTZ` structure has a null value, the returned `OracleTimeStamp` structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp(string)

This static type conversion operator converts the supplied string to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStamp(string tsStr);
```

Parameters

- *tsStr*

A string representation of an Oracle `TIMESTAMP`.

Return Value

An `OracleTimeStamp`.

Exceptions

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP` or the *tsStr* is not in the timestamp format specified by the thread's `OracleGlobalization.TimeStampFormat` property, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;
```



```
class OracleTimeStampSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the explicit
        // operator OracleTimeStamp(string)
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)
- *Oracle Database SQL Language Reference* for further information on datetime format elements

implicit operator OracleTimeStamp

This static type conversion operator converts a value to an `OracleTimeStamp` structure.

Overload List:

- [implicit operator OracleTimeStamp\(OracleDate\)](#)
This static type conversion operator converts an `OracleDate` value to an `OracleTimeStamp` structure.
- [implicit operator OracleTimeStamp\(DateTime\)](#)
This static type conversion operator converts a `DateTime` value to an `OracleTimeStamp` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

implicit operator OracleTimeStamp(OracleDate)

This static type conversion operator converts an `OracleDate` value to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStamp (OracleDate value1);
```

Parameters

- `value1`
An `OracleDate` instance.

Return Value

An `OracleTimeStamp` structure that contains the date and time of the `OracleDate` structure, `value1`.

Remarks

If the `OracleDate` structure has a null value, the returned `OracleTimeStamp` structure also has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

implicit operator OracleTimeStamp(DateTime)

This static type conversion operator converts a `DateTime` value to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStamp(DateTime value);
```

Parameters

- *value*
A `DateTime` instance.

Return Value

An `OracleTimeStamp` structure.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator DateTime

This static type conversion operator converts an `OracleTimeStamp` value to a `DateTime` structure.

Declaration

```
// C#  
public static explicit operator DateTime(OracleTimeStamp value1);
```

Parameters

- *value1*
An `OracleTimeStamp` instance.

Return Value

A `DateTime` containing the date and time in the current instance.

Exceptions

`OracleNullValueException` - The `OracleTimeStamp` structure has a null value.

Remarks

The precision of the `OracleTimeStamp` can be lost during the conversion.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Properties

The OracleTimeStamp properties are listed in [Table 14-111](#).

Table 14-111 OracleTimeStamp Properties

Properties	Description
BinData	Returns an array of bytes that represents an Oracle TIMESTAMP in Oracle internal format
Day	Specifies the day component of an OracleTimeStamp
IsNull	Indicates whether or not the OracleTimeStamp instance has a null value
Hour	Specifies the hour component of an OracleTimeStamp
Millisecond	Specifies the millisecond component of an OracleTimeStamp
Minute	Specifies the minute component of an OracleTimeStamp
Month	Specifies the month component of an OracleTimeStamp
Nanosecond	Specifies the nanosecond component of an OracleTimeStamp
Second	Specifies the second component of an OracleTimeStamp
Value	Specifies the date and time that is stored in the OracleTimeStamp structure
Year	Specifies the year component of an OracleTimeStamp

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

BinData

This property returns an array of bytes that represents an Oracle TIMESTAMP in Oracle internal format.

Declaration

```
// C#  
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle `TIMESTAMP` in an internal format.

Exceptions

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Day

This property specifies the day component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of `Day` is (1 to 31).

Exceptions

`OracleNullValueException` - The current instance has a null value.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Hour

This property specifies the hour component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Hour{get;}
```

Property Value

A number that represents the hour. Range of `hour` is (0 to 23).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Millisecond

This property gets the millisecond component of an `OracleTimeStamp`.

Declaration

```
// C#  
public double Millisecond{get;}
```

Property Value

A number that represents a millisecond. Range of `Millisecond` is (0 to 999.999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Minute

This property gets the minute component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Minute{get;}
```

Property Value

A number that represent a minute. Range of `Minute` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Month

This property gets the month component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Month{get;}
```

Property Value

A number that represents a month. Range of `Month` is (1 to 12).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Nanosecond

This property gets the nanosecond component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Nanosecond{get;}
```

Property Value

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Second

This property gets the second component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Second{get;}
```


Property Value

A number that represents a second. Range of `Second` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Value

This property specifies the date and time that is stored in the `OracleTimeStamp` structure.

Declaration

```
// C#  
public DateTime Value{get;}
```

Property Value

A `DateTime`.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Year

This property gets the year component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Year{get;}
```

Property Value

A number that represents a year. The range of `year` is (-4712 to 9999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Methods

The `OracleTimeStamp` methods are listed in [Table 14-112](#).

Table 14-112 OracleTimeStamp Methods

Methods	Description
AddDays	Adds the supplied number of days to the current instance
AddHours	Adds the supplied number of hours to the current instance
AddMilliseconds	Adds the supplied number of milliseconds to the current instance
AddMinutes	Adds the supplied number of minutes to the current instance
AddMonths	Adds the supplied number of months to the current instance
AddNanoseconds	Adds the supplied number of nanoseconds to the current instance
AddSeconds	Adds the supplied number of seconds to the current instance
AddYears	Adds the supplied number of years to the current instance
CompareTo	Compares the current <code>OracleTimeStamp</code> instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current <code>OracleTimeStamp</code> instance (Overloaded)
GetHashCode	Returns a hash code for the <code>OracleTimeStamp</code> instance
GetDaysBetween	Subtracts an <code>OracleTimeStamp</code> value from the current instance and returns an <code>OracleIntervalDS</code> that represents the time difference between the supplied <code>OracleTimeStamp</code> and the current instance

Table 14-112 (Cont.) OracleTimeStamp Methods

Methods	Description
GetYearsBetween	Subtracts value1 from the current instance and returns an OracleIntervalYM that represents the difference between value1 and the current instance using OracleIntervalYM
GetType	Inherited from System.Object
ToOracleDate	Converts the current OracleTimeStamp structure to an OracleDate structure
ToOracleTimeStampLTZ	Converts the current OracleTimeStamp structure to an OracleTimeStampLTZ structure
ToOracleTimeStampTZ	Converts the current OracleTimeStamp structure to an OracleTimeStampTZ structure
ToString	Converts the current OracleTimeStamp structure to a string

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddDays

This method adds the supplied number of days to the current instance.

Declaration

```
// C#
public OracleTimeStamp AddDays(double days);
```

Parameters

- *days*
The supplied number of days. Range is (-1,000,000,000 < *days* < 1,000,000,000)

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.
OracleNullValueException - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddHours

This method adds the supplied number of hours to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddHours(double hours);
```

Parameters

- *hours*
The supplied number of hours. Range is $(-24,000,000,000 < hours < 24,000,000,000)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.
OracleNullValueException - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddMilliseconds(double milliseconds);
```

Parameters

- *milliseconds*

The supplied number of milliseconds. Range is $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddMinutes

This method adds the supplied number of minutes to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddMinutes(double minutes);
```

Parameters

- *minutes*

The supplied number of minutes. Range is $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddMonths

This method adds the supplied number of months to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddMonths(long months);
```

Parameters

- *months*
The supplied number of months. Range is $(-12,000,000,000 < months < 12,000,000,000)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddNanoseconds(long nanoseconds);
```

Parameters

- *nanoseconds*
The supplied number of nanoseconds.

Return Value

An OracleTimeStamp.

Exceptions

OracleNullValueException - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddSeconds

This method adds the supplied number of seconds to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddSeconds(double seconds);
```

Parameters

- *seconds*
The supplied number of seconds. Range is $(-8.64 * 1013 < seconds < 8.64 * 1013)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddYears

This method adds the supplied number of years to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddYears(int years);
```

Parameters

- *years*
The supplied number of years. Range is (-999,999,999 <= *years* <= 999,999,999)

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

CompareTo

This method compares the current OracleTimeStamp instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```


Parameters

- *obj*
The object being compared to the current `OracleTimeStamp` instance.

Return Value

The method returns a number that is:

Less than zero: if the current `OracleTimeStamp` instance value is less than that of *obj*.

Zero: if the current `OracleTimeStamp` instance and *obj* values are equal.

Greater than zero: if the current `OracleTimeStamp` instance value is greater than that of *obj*.

Implements

`Comparable`

Exceptions

`ArgumentException` - The *obj* parameter is not of type `OracleTimeStamp`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStamps`. For example, comparing an `OracleTimeStamp` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStamp` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Equals

Overrides `Object`

This method determines whether or not an object has the same date and time as the current `OracleTimeStamp` instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*

The object being compared to the current `OracleTimeStamp` instance.

Return Value

Returns `true` if the *obj* is of type `OracleTimeStamp` and represents the same date and time; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleTimeStamp` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetDaysBetween

This method subtracts an `OracleTimeStamp` value from the current instance and returns an `OracleIntervalDS` that represents the time difference between the supplied `OracleTimeStamp` structure and the current instance.

Declaration

```
// C#  
public OracleIntervalDS GetDaysBetween(OracleTimeStamp value1);
```

Parameters

- `value1`
The `OracleTimeStamp` value being subtracted.

Return Value

An `OracleIntervalDS` that represents the interval between two `OracleTimeStamp` values.

Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalDS` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetYearsBetween

This method subtracts an `OracleTimeStamp` value from the current instance and returns an `OracleIntervalYM` that represents the time difference between the `OracleTimeStamp` value and the current instance.

Declaration

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStamp value1);
```

Parameters

- *value1*
The OracleTimeStamp value being subtracted.

Return Value

An OracleIntervalYM that represents the interval between two OracleTimeStamp values.

Remarks

If either the current instance or the parameter has a null value, the returned OracleIntervalYM has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

ToOracleDate

This method converts the current OracleTimeStamp structure to an OracleDate structure.

Declaration

```
// C#  
public OracleDate ToOracleDate();
```

Return Value

The returned OracleDate contains the date and time in the current instance.

Remarks

The precision of the OracleTimeStamp value can be lost during the conversion.

If the value of the OracleTimeStamp has a null value, the value of the returned OracleDate structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

ToOracleTimeStampLTZ

This method converts the current `OracleTimeStamp` structure to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public OracleTimeStampLTZ ToOracleTimeStampLTZ();
```

Return Value

The returned `OracleTimeStampLTZ` contains date and time in the current instance.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStampLTZ` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

ToOracleTimeStampTZ

This method converts the current `OracleTimeStamp` structure to an `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public OracleTimeStampTZ ToOracleTimeStampTZ();
```

Return Value

The returned `OracleTimeStampTZ` contains the date and time from the `OracleTimeStamp` and the time zone from the `OracleGlobalization.TimeZone` of the thread.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

ToString

Overrides `Object`

This method converts the current `OracleTimeStamp` structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string that represents the same date and time as the current `OracleTimeStamp` structure.

Remarks

The returned value is a string representation of an `OracleTimeStamp` in the format specified by the `OracleGlobalization.TimeStampFormat` property of the thread.

The names and abbreviations used for months and days are in the language specified by the `OracleGlobalization's DateLanguage` and `Calendar` properties of the thread. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class ToStringSample  
{  
    static void Main()  
    {
```

```
// Set the nls_timestamp_format for the OracleTimeStamp(string)
// constructor
OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.TimestampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// construct OracleTimeStamp from a string using the format specified.
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

// Set the nls_timestamp_format for the ToString() method
info.TimestampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM"
Console.WriteLine(ts.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

OracleTimeStampLTZ Structure

The `OracleTimeStampLTZ` structure represents the Oracle `TIMESTAMP WITH LOCAL TIME ZONE` data type to be stored in or retrieved from a database. Each `OracleTimeStampLTZ` stores the following information: year, month, day, hour, minute, second, and nanosecond.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleTimeStampLTZ`

Declaration

```
// C#
public struct OracleTimeStampLTZ : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampLTZSample
{
    static void Main()
    {
        // Illustrates usage of OracleTimeStampLTZ
        // Display Local Time Zone Name
        Console.WriteLine("Local Time Zone Name = " +
            OracleTimeStampLTZ.GetLocalTimeZoneName());
        OracleTimeStampLTZ tsLocal1 = OracleTimeStampLTZ.GetSysDate();
        OracleTimeStampLTZ tsLocal2 = DateTime.Now;

        // Calculate the difference between tsLocal1 and tsLocal2
        OracleIntervalDS idsDiff = tsLocal2.GetDaysBetween(tsLocal1);

        // Calculate the difference using AddNanoseconds()
        int nanoDiff = 0;
        while (tsLocal2 > tsLocal1)
        {
            nanoDiff += 10;
            tsLocal1 = tsLocal1.AddNanoseconds(10);
        }
        Console.WriteLine("idsDiff.Nanoseconds = " + idsDiff.Nanoseconds);
        Console.WriteLine("nanoDiff = " + nanoDiff);
    }
}
```


 **See Also:**

- "Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"
- OracleTimeStampLTZ Members
- OracleTimeStampLTZ Constructors
- OracleTimeStampLTZ Static Fields
- OracleTimeStampLTZ Static Methods
- OracleTimeStampLTZ Static Operators
- OracleTimeStampLTZ Static Type Conversions
- OracleTimeStampLTZ Properties
- OracleTimeStampLTZ Methods

OracleTimeStampLTZ Members

OracleTimeStampLTZ members are listed in the following tables:

OracleTimeStampLTZ Constructors

OracleTimeStampLTZ constructors are listed in [Table 14-113](#)

Table 14-113 OracleTimeStampLTZConstructors

Constructor	Description
OracleTimeStampLTZ Constructors	Instantiates a new instance of OracleTimeStampLTZ structure (Overloaded)

OracleTimeStampLTZ Static Fields

The OracleTimeStampLTZ static fields are listed in [Table 14-114](#).

Table 14-114 OracleTimeStampLTZ Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999
MinValue	Represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to an instance of the OracleTimeStampLTZ structure

OracleTimeStampLTZ Static Methods

The OracleTimeStampLTZ static methods are listed in [Table 14-115](#).

Table 14-115 OracleTimeStampLTZ Static Methods

Methods	Description
Equals	Determines if two OracleTimeStampLTZ values are equal (Overloaded)
GetLocalTimeZoneName	Gets the client's local time zone name
GetLocalTimeZoneOffset	Gets the client's local time zone offset relative to UTC
GetSysDate	Gets an OracleTimeStampLTZ structure that represents the current date and time
GreaterThan	Determines if the first of two OracleTimeStampLTZ values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
LessThan	Determines if the first of two OracleTimeStampLTZ values is less than the second
LessThanOrEqual	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
NotEquals	Determines if two OracleTimeStampLTZ values are not equal
Parse	Gets an OracleTimeStampLTZ structure and sets its value for date and time using the supplied string
SetPrecision	Returns a new instance of an OracleTimeStampLTZ with the specified fractional second precision

OracleTimeStampLTZ Static Operators

The OracleTimeStampLTZ static operators are listed in [Table 14-116](#).

Table 14-116 OracleTimeStampLTZ Static Operators

Operator	Description
operator +	Adds the supplied instance value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)
operator ==	Determines if two OracleTimeStampLTZ values are equal

Table 14-116 (Cont.) OracleTimeStampLTZ Static Operators

Operator	Description
operator >	Determines if the first of two OracleTimeStampLTZ values is greater than the second
operator >=	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
operator !=	Determines if two OracleTimeStampLTZ values are not equal
operator <	Determines if the first of two OracleTimeStampLTZ values is less than the second
operator <=	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
operator -	Subtracts the supplied instance value from the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)

OracleTimeStampLTZ Static Type Conversions

The OracleTimeStampLTZ static type conversions are listed in [Table 14-117](#).

Table 14-117 OracleTimeStampLTZ Static Type Conversions

Operator	Description
explicit operator OracleTimeStampLTZ	Converts an instance value to an OracleTimeStampLTZ structure (Overloaded)
implicit operator OracleTimeStampLTZ	Converts an instance value to an OracleTimeStampLTZ structure (Overloaded)
explicit operator DateTime	Converts an OracleTimeStampLTZ value to a DateTime structure

OracleTimeStampLTZ Properties

The OracleTimeStampLTZ properties are listed in [Table 14-118](#).

Table 14-118 OracleTimeStampLTZ Properties

Properties	Description
BinData	Returns an array of bytes that represents an Oracle TIMESTAMP WITH LOCAL TIME ZONE in Oracle internal format
Day	Specifies the day component of an OracleTimeStampLTZ

Table 14-118 (Cont.) OracleTimeStampLTZ Properties

Properties	Description
IsNull	Indicates whether or not the OracleTimeStampLTZ instance has a null value
Hour	Specifies the hour component of an OracleTimeStampLTZ
Millisecond	Specifies the millisecond component of an OracleTimeStampLTZ
Minute	Specifies the minute component of an OracleTimeStampLTZ
Month	Specifies the month component of an OracleTimeStampLTZ
Nanosecond	Specifies the nanosecond component of an OracleTimeStampLTZ
Second	Specifies the second component of an OracleTimeStampLTZ
Value	Specifies the date and time that is stored in the OracleTimeStampLTZ structure
Year	Specifies the year component of an OracleTimeStampLTZ

OracleTimeStampLTZ Methods

The OracleTimeStampLTZ methods are listed in [Table 14-119](#).

Table 14-119 OracleTimeStampLTZ Methods

Methods	Description
AddDays	Adds the supplied number of days to the current instance
AddHours	Adds the supplied number of hours to the current instance
AddMilliseconds	Adds the supplied number of milliseconds to the current instance
AddMinutes	Adds the supplied number of minutes to the current instance
AddMonths	Adds the supplied number of months to the current instance
AddNanoseconds	Adds the supplied number of nanoseconds to the current instance
AddSeconds	Adds the supplied number of seconds to the current instance
AddYears	Adds the supplied number of years to the current instance

Table 14-119 (Cont.) OracleTimeStampLTZ Methods

Methods	Description
CompareTo	Compares the current OracleTimeStampLTZ instance to an object and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current OracleTimeStampLTZ instance (Overloaded)
GetHashCode	Returns a hash code for the OracleTimeStampLTZ instance
GetDaysBetween	Subtracts an OracleTimeStampLTZ from the current instance and returns an OracleIntervalDS that represents the difference
GetYearsBetween	Subtracts an OracleTimeStampLTZ from the current instance and returns an OracleIntervalYM that represents the difference
GetType	Inherited from System.Object
ToOracleDate	Converts the current OracleTimeStampLTZ structure to an OracleDate structure
ToOracleTimeStamp	Converts the current OracleTimeStampLTZ structure to an OracleTimeStamp structure
ToOracleTimeStampTZ	Converts the current OracleTimeStampLTZ structure to an OracleTimeStampTZ structure
ToString	Converts the current OracleTimeStampLTZ structure to a string
ToUniversalTime	Converts the current local time to Coordinated Universal Time (UTC)

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)

OracleTimeStampLTZ Constructors

The OracleTimeStampLTZ constructors create new instances of the OracleTimeStampLTZ structure.

Overload List:

- [OracleTimeStampLTZ\(DateTime\)](#)
This constructor creates a new instance of the OracleTimeStampLTZ structure and sets its value for date and time using the supplied DateTime value.

- [OracleTimeStampLTZ\(string\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied string.
- [OracleTimeStampLTZ\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date using year, month, and day.
- [OracleTimeStampLTZ\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStampLTZ\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.
- [OracleTimeStampLTZ\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.
- [OracleTimeStampLTZ\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP WITH LOCAL TIME ZONE` format.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(DateTime)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleTimeStampLTZ (DateTime dt);
```

Parameters

- *dt*

The supplied `DateTime` value.

Exceptions

ArgumentException - The *dt* parameter cannot be used to construct a valid `OracleTimeStampLTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(string)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied string.

Declaration

```
// C#  
public OracleTimeStampLTZ(string tsStr);
```

Parameters

- *tsStr*
A string that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

Exceptions

ArgumentException - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` or the supplied *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimestampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

ArgumentNullException - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class OracleTimeStampLTZSample
```

```
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimestampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format
        // specified.
        OracleTimeStampLTZ ts =
            new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimestampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleTimeStampLTZ(int, int, int)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date using year, month, and day.

Declaration

```
// C#
public OracleTimeStampLTZ(int year, int month, int day);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).

- *day*
The day provided. Range of *day* is (1 to 31).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.

Declaration

```
// C#  
public OracleTimeStampLTZ (int year, int month, int day, int hour,  
    int minute, int second);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(int, int, int, int, int, int, double)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

Declaration

```
// C#  
public OracleTimeStampLTZ(int year, int month, int day, int hour, int minute, int  
second, double millisecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *milliSeconds*
The milliseconds provided. Range of *millisecond* is (0 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(int, int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

Declaration

```
// C#  
public OracleTimeStampLTZ (int year, int month, int day, int hour,  
    int minute, int second, int nanosecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(byte [])

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP WITH LOCAL TIME ZONE` format.

Declaration

```
// C#  
public OracleTimeStampLTZ (byte[] bytes);
```

Parameters

- *bytes*

A byte array that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` in Oracle internal format.

Exceptions

`ArgumentException` - *bytes* is not in an internal Oracle `TIMESTAMP WITH LOCAL TIME ZONE` format or *bytes* is not a valid Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

`ArgumentNullException` - *bytes* is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Fields

The OracleTimeStampLTZ static fields are listed in [Table 14-120](#).

Table 14-120 OracleTimeStampLTZ Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999
MinValue	Represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to an instance of the OracleTimeStampLTZ structure

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

MaxValue

This static field represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999.

Declaration

```
// C#  
public static readonly OracleTimeStampLTZ MaxValue;
```

Remarks

This value is the maximum date and time in the client time zone.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

MinValue

This static field represents the minimum valid date for an `OracleTimeStampLTZ` structure, which is January 1, -4712 0:0:0.

Declaration

```
// C#  
public static readonly OracleTimeStampLTZ MinValue;
```

Remarks

This value is the minimum date and time in the client time zone.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static readonly OracleTimeStampLTZ Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Methods

The `OracleTimeStampLTZ` static methods are listed in [Table 14-121](#).

Table 14-121 OracleTimeStampLTZ Static Methods

Methods	Description
Equals	Determines if two OracleTimeStampLTZ values are equal (Overloaded)
GetLocalTimeZoneName	Gets the client's local time zone name
GetLocalTimeZoneOffset	Gets the client's local time zone offset relative to UTC
GetSysDate	Gets an OracleTimeStampLTZ structure that represents the current date and time
GreaterThan	Determines if the first of two OracleTimeStampLTZ values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
LessThan	Determines if the first of two OracleTimeStampLTZ values is less than the second
LessThanOrEqual	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
NotEquals	Determines if two OracleTimeStampLTZ values are not equal
Parse	Gets an OracleTimeStampLTZ structure and sets its value for date and time using the supplied string
SetPrecision	Returns a new instance of an OracleTimeStampLTZ with the specified fractional second precision

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Equals

This static method determines if two OracleTimeStampLTZ values are equal.

Declaration

```
// C#
public static bool Equals(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.

- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if two OracleTimeStampLTZ values are equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetLocalTimeZoneName

This static method gets the client's local time zone name.

Declaration

```
// C#  
public static string GetLocalTimeZoneName();
```

Return Value

A string containing the local time zone.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetLocalTimeZoneOffset

This static method gets the client's local time zone offset relative to Coordinated Universal Time (UTC).

Declaration

```
// C#  
public static TimeSpan GetLocalTimeZoneOffset( );
```

Return Value

A `TimeSpan` structure containing the local time zone hours and time zone minutes.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetSysDate

This static method gets an `OracleTimeStampLTZ` structure that represents the current date and time.

Declaration

```
// C#  
public static OracleTimeStampLTZ GetSysDate();
```

Return Value

An `OracleTimeStampLTZ` structure that represents the current date and time.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GreaterThan

This static method determines if the first of two `OracleTimeStampLTZ` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if the first of two OracleTimeStampLTZ values is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GreaterThanOrEqual

This static method determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns `true` if the first of two `OracleTimeStampLTZ` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

LessThan

This static method determines if the first of two `OracleTimeStampLTZ` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampLTZ`.
- `value2`
The second `OracleTimeStampLTZ`.

Return Value

Returns `true` if the first of two `OracleTimeStampLTZ` values is less than the second. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

LessThanOrEqual

This static method determines if the first of two `OracleTimeStampLTZ` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampLTZ`.
- `value2`
The second `OracleTimeStampLTZ`.

Return Value

Returns `true` if the first of two `OracleTimeStampLTZ` values is less than or equal to the second. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

NotEquals

This static method determines if two `OracleTimeStampLTZ` values are not equal.

Declaration

```
// C#
public static bool NotEquals(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampLTZ`.
- `value2`
The second `OracleTimeStampLTZ`.

Return Value

Returns `true` if two `OracleTimeStampLTZ` values are not equal. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Parse

This static method creates an `OracleTimeStampLTZ` structure and sets its value using the supplied string.

Declaration

```
// C#
public static OracleTimeStampLTZ Parse(string tsStr);
```

Parameters

- `tsStr`

A string that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

Return Value

An `OracleTimeStampLTZ` structure.

Exceptions

`ArgumentException` - The `tsStr` parameter is an invalid string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` or the `tsStr` is not in the timestamp format specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The `tsStr` value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the Parse() method
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format specified.
        OracleTimeStampLTZ ts =
            OracleTimeStampLTZ.Parse("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

SetPrecision

This static method returns a new instance of an `OracleTimeStampLTZ` with the specified fractional second precision.

Declaration

```
// C#  
public static OracleTimeStampLTZ SetPrecision(OracleTimeStampLTZ value1,  
    int fracSecPrecision);
```

Parameters

- *value1*
The provided `OracleTimeStampLTZ` object.
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An `OracleTimeStampLTZ` structure with the specified fractional second precision

Exceptions

`ArgumentOutOfRangeException` - *fracSecPrecision* is out of the specified range.

Remarks

The value specified in the supplied *fracSecPrecision* parameter is used to perform a rounding off operation on the supplied `OracleTimeStampLTZ` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

Example

The `OracleTimeStampLTZ` with a value of "December 31, 9999 23:59:59.99" results in the string "December 31, 9999 23:59:59.99000" when `SetPrecision()` is called with the fractional second precision set to 5.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Operators

The OracleTimeStampLTZ static operators are listed in [Table 14-122](#).

Table 14-122 OracleTimeStampLTZ Static Operators

Operator	Description
operator +	Adds the supplied instance value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)
operator ==	Determines if two OracleTimeStampLTZ values are equal
operator >	Determines if the first of two OracleTimeStampLTZ values is greater than the second
operator >=	Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second
operator !=	Determines if two OracleTimeStampLTZ values are not equal
operator <	Determines if the first of two OracleTimeStampLTZ values is less than the second
operator <=	Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second
operator -	Subtracts the supplied instance value from the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded)

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator +

`operator +` adds the supplied value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.

Overload List:

- [operator + \(OracleTimeStampLTZ, OracleIntervalDS\)](#)
This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.
- [operator + \(OracleTimeStampLTZ, OracleIntervalYM\)](#)
This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.
- [operator + \(OracleTimeStampLTZ, TimeSpan\)](#)
This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator + (OracleTimeStampLTZ, OracleIntervalDS)

This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampLTZ value1,  
    OracleIntervalDS value2);
```

Parameters

- `value1`
An `OracleTimeStampLTZ`.
- `value2`
An `OracleIntervalDS`.

Return Value

An `OracleTimeStampLTZ`.

Remarks

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator + (OracleTimeStampLTZ, OracleIntervalYM)

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampLTZ value1,  
    OracleIntervalYM value2);
```

Parameters

- `value1`
An `OracleTimeStampLTZ`.
- `value2`
An `OracleIntervalYM`.

Return Value

An `OracleTimeStampLTZ`.

Remarks

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator + (OracleTimeStampLTZ, TimeSpan)

This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampLTZ value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStampLTZ.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStampLTZ.

Remarks

If the OracleTimeStampLTZ instance has a null value, the returned OracleTimeStampLTZ has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator ==

This static operator determines if two OracleTimeStampLTZ values are equal.

Declaration

```
// C#  
public static bool operator ==(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if they are the same; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator >

This static operator determines if the first of two `OracleTimeStampLTZ` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampLTZ`.
- *value2*
The second `OracleTimeStampLTZ`.

Return Value

Returns `true` if the first `OracleTimeStampLTZ` value is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator >=

This static operator determines if the first of two `OracleTimeStampLTZ` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- `value1`
An `OracleTimeStampLTZ`.
- `value2`
The second `OracleTimeStampLTZ`.

Return Value

Returns `true` if the first `OracleTimeStampLTZ` is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator !=

This static operator determines if two `OracleTimeStampLTZ` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampLTZ`.
- `value2`
The second `OracleTimeStampLTZ`.

Return Value

Returns `true` if two `OracleTimeStampLTZ` values are not equal; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator <

This static operator determines if the first of two `OracleTimeStampLTZ` values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if the first OracleTimeStampLTZ is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator <=

This static operator determines if the first of two OracleTimeStampLTZ values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns `true` if the first `OracleTimeStampLTZ` is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator -

`operator-` subtracts the supplied value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

Overload List:

- [operator - \(OracleTimeStampLTZ, OracleIntervalDS\)](#)
This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampLTZ` value, and return a new `OracleTimeStampLTZ` structure.
- [operator - \(OracleTimeStampLTZ, OracleIntervalYM\)](#)
This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.
- [operator - \(OracleTimeStampLTZ, TimeSpan\)](#)
This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator - (OracleTimeStampLTZ, OracleIntervalDS)

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampLTZ` value, and return a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStampLTZ value1,  
    OracleIntervalDS value2);
```

Parameters

- `value1`
An `OracleTimeStampLTZ`.
- `value2`
An `OracleIntervalDS` instance.

Return Value

An `OracleTimeStampLTZ` structure.

Remarks

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator - (OracleTimeStampLTZ, OracleIntervalYM)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStampLTZ value1,  
    OracleIntervalYM value2);
```

Parameters

- *value1*
An OracleTimeStampLTZ.
- *value2*
An OracleIntervalYM.

Return Value

An OracleTimeStampLTZ structure.

Remarks

If either parameter has a null value, the returned OracleTimeStampLTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator - (OracleTimeStampLTZ, TimeSpan)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator -(OracleTimeStampLTZ value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStampLTZ.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStampLTZ structure.

Remarks

If the `OracleTimeStampLTZ` instance has a null value, the returned `OracleTimeStampLTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Type Conversions

The `OracleTimeStampLTZ` static type conversions are listed in [Table 14-123](#).

Table 14-123 OracleTimeStampLTZ Static Type Conversions

Operator	Description
explicit operator OracleTimeStampLTZ	Converts an instance value to an <code>OracleTimeStampLTZ</code> structure (Overloaded)
implicit operator OracleTimeStampLTZ	Converts an instance value to an <code>OracleTimeStampLTZ</code> structure (Overloaded)
explicit operator DateTime	Converts an <code>OracleTimeStampLTZ</code> value to a <code>DateTime</code> structure

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ

`explicit operator OracleTimeStampLTZ` converts the supplied value to an `OracleTimeStampLTZ` structure.

Overload List:

- [explicit operator OracleTimeStampLTZ\(OracleTimeStamp\)](#)
This static type conversion operator converts an `OracleTimeStamp` value to an `OracleTimeStampLTZ` structure.

- [explicit operator OracleTimeStampLTZ\(OracleTimeStampTZ\)](#)
This static type conversion operator converts an `OracleTimeStampTZ` value to an `OracleTimeStampLTZ` structure.
- [explicit operator OracleTimeStampLTZ\(string\)](#)
This static type conversion operator converts the supplied string to an `OracleTimeStampLTZ` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ(OracleTimeStamp)

This static type conversion operator converts an `OracleTimeStamp` value to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampLTZ (OracleTimeStamp value1);
```

Parameters

- `value1`
An `OracleTimeStamp`.

Return Value

The `OracleTimeStampLTZ` structure contains the date and time of the `OracleTimeStampTZ` structure.

Remarks

If the `OracleTimeStamp` structure has a null value, the returned `OracleTimeStampLTZ` structure also has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ(OracleTimeStampTZ)

This static type conversion operator converts an `OracleTimeStampTZ` value to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampLTZ  
    (OracleTimeStampTZ value1);
```

Parameters

- `value1`
An `OracleTimeStampTZ` instance.

Return Value

The `OracleTimeStampLTZ` structure contains the date and time in the `OracleTimeStampTZ` structure (which is normalized to the client local time zone).

Remarks

If the `OracleTimeStampTZ` structure has a null value, the returned `OracleTimeStampLTZ` structure also has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ(string)

This static type conversion operator converts the supplied string to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampLTZ (string tsStr);
```

Parameters

- `tsStr`
A string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

Return Value

A `OracleTimeStampLTZ`.

Exceptions

`ArgumentException` - The `tsStr` parameter is an invalid string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` or the `tsStr` is not in the timestamp format specified by the thread's `OracleGlobalization.TimeStampFormat` property, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampLTZSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format specified.
        OracleTimeStampLTZ ts =
            new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)
- *Oracle Database SQL Language Reference* for further information on datetime format elements

implicit operator OracleTimeStampLTZ

implicit operator OracleTimeStampLTZ converts the supplied structure to an OracleTimeStampLTZ structure.

Overload List:

- [implicit operator OracleTimeStampLTZ\(OracleDate\)](#)
This static type conversion operator converts an OracleDate value to an OracleTimeStampLTZ structure.
- [implicit operator OracleTimeStampLTZ\(DateTime\)](#)
This static type conversion operator converts a DateTime structure to an OracleTimeStampLTZ structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

implicit operator OracleTimeStampLTZ(OracleDate)

This static type conversion operator converts an OracleDate value to an OracleTimeStampLTZ structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStampLTZ(OracleDate value1);
```

Parameters

- *value1*
An `OracleDate`.

Return Value

The returned `OracleTimeStampLTZ` structure contains the date and time in the `OracleDate` structure.

Remarks

If the `OracleDate` structure has a null value, the returned `OracleTimeStampLTZ` structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

implicit operator OracleTimeStampLTZ(DateTime)

This static type conversion operator converts a `DateTime` structure to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStampLTZ(DateTime value1);
```

Parameters

- *value1*
A `DateTime` structure.

Return Value

An `OracleTimeStampLTZ` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator DateTime

This static type conversion operator converts an `OracleTimeStampLTZ` value to a `DateTime` structure.

Declaration

```
// C#
public static explicit operator DateTime(OracleTimeStampLTZ value1);
```

Parameters

- `value1`
An `OracleTimeStampLTZ` instance.

Return Value

A `DateTime` that contains the date and time in the current instance.

Exceptions

`OracleNullValueException` - The `OracleTimeStampLTZ` structure has a null value.

Remarks

The precision of the `OracleTimeStampLTZ` value can be lost during the conversion.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Properties

The `OracleTimeStampLTZ` properties are listed in [Table 14-124](#).

Table 14-124 OracleTimeStampLTZ Properties

Properties	Description
BinData	Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH LOCAL TIME ZONE</code> in Oracle internal format
Day	Specifies the day component of an <code>OracleTimeStampLTZ</code>
IsNull	Indicates whether or not the <code>OracleTimeStampLTZ</code> instance has a null value
Hour	Specifies the hour component of an <code>OracleTimeStampLTZ</code>

Table 14-124 (Cont.) OracleTimeStampLTZ Properties

Properties	Description
Millisecond	Specifies the millisecond component of an OracleTimeStampLTZ
Minute	Specifies the minute component of an OracleTimeStampLTZ
Month	Specifies the month component of an OracleTimeStampLTZ
Nanosecond	Specifies the nanosecond component of an OracleTimeStampLTZ
Second	Specifies the second component of an OracleTimeStampLTZ
Value	Specifies the date and time that is stored in the OracleTimeStampLTZ structure
Year	Specifies the year component of an OracleTimeStampLTZ

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` internal format.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Day

This property specifies the day component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of `Day` is (1 to 31).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance contains a null value; otherwise, returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Hour

This property specifies the hour component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Hour{get;}
```

Property Value

A number that represents the hour. Range of `Hour` is (0 to 23).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Millisecond

This property gets the millisecond component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public double Millisecond{get;}
```

Property Value

A number that represents a millisecond. Range of `Millisecond` is (0 to 999.999999)

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Minute

This property gets the minute component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Minute{get;}
```

Property Value

A number that represent a minute. Range of `Minute` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Month

This property gets the month component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Month{get;}
```

Property Value

A number that represents a month. Range of `Month` is (1 to 12).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Nanosecond

This property gets the nanosecond component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Nanosecond{get;}
```

Property Value

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Second

This property gets the second component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Second{get;}
```

Property Value

A number that represents a second. Range of `Second` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Value

This property specifies the date and time that is stored in the `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public DateTime Value{get;}
```

Property Value

A `DateTime`.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Year

This property gets the year component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Year{get;}
```

Property Value

A number that represents a year. The range of `Year` is (-4712 to 9999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 See Also:

- "Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"
- OracleTimeStampLTZ Structure
- OracleTimeStampLTZ Members

OracleTimeStampLTZ Methods

The OracleTimeStampLTZ methods are listed in [Table 14-125](#).

Table 14-125 OracleTimeStampLTZ Methods

Methods	Description
AddDays	Adds the supplied number of days to the current instance
AddHours	Adds the supplied number of hours to the current instance
AddMilliseconds	Adds the supplied number of milliseconds to the current instance
AddMinutes	Adds the supplied number of minutes to the current instance
AddMonths	Adds the supplied number of months to the current instance
AddNanoseconds	Adds the supplied number of nanoseconds to the current instance
AddSeconds	Adds the supplied number of seconds to the current instance
AddYears	Adds the supplied number of years to the current instance
CompareTo	Compares the current OracleTimeStampLTZ instance to an object and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current OracleTimeStampLTZ instance (Overloaded)
GetHashCode	Returns a hash code for the OracleTimeStampLTZ instance
GetDaysBetween	Subtracts an OracleTimeStampLTZ from the current instance and returns an OracleIntervalDS that represents the difference
GetYearsBetween	Subtracts an OracleTimeStampLTZ from the current instance and returns an OracleIntervalYM that represents the difference
GetType	Inherited from System.Object
ToOracleDate	Converts the current OracleTimeStampLTZ structure to an OracleDate structure
ToOracleTimeStamp	Converts the current OracleTimeStampLTZ structure to an OracleTimeStamp structure

Table 14-125 (Cont.) OracleTimeStampLTZ Methods

Methods	Description
ToOracleTimeStampTZ	Converts the current OracleTimeStampLTZ structure to an OracleTimeStampTZ structure
ToString	Converts the current OracleTimeStampLTZ structure to a string
ToUniversalTime	Converts the current local time to Coordinated Universal Time (UTC)

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddDays

This method adds the supplied number of days to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddDays(double days);
```

Parameters

- *days*
The supplied number of days. Range is $(-1,000,000,000 < days < 1,000,000,000)$

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddHours

This method adds the supplied number of hours to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddHours(double hours);
```

Parameters

- *hours*
The supplied number of hours. Range is $(-24,000,000,000 < hours < 24,000,000,000)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddMilliseconds(double milliseconds);
```

Parameters

- *milliseconds*

The supplied number of milliseconds. Range is $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddMinutes

This method adds the supplied number of minutes to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddMinutes(double minutes);
```

Parameters

- *minutes*

The supplied number of minutes. Range is $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddMonths

This method adds the supplied number of months to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddMonths(long months);
```

Parameters

- *months*
The supplied number of months. Range is $(-12,000,000,000 < months < 12,000,000,000)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddNanoseconds(long nanoseconds);
```

Parameters

- *nanoseconds*
The supplied number of nanoseconds.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddSeconds

This method adds the supplied number of seconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddSeconds(double seconds);
```

Parameters

- *seconds*
The supplied number of seconds. Range is $(-8.64 * 1013 < seconds < 8.64 * 1013)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddYears

This method adds the supplied number of years to the current instance

Declaration

```
// C#  
public OracleTimeStampLTZ AddYears(int years);
```

Parameters

- *years*

The supplied number of years. Range is $(-999,999,999 \leq \text{years} \leq 999,999,999)$

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

CompareTo

This method compares the current OracleTimeStampLTZ instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared to the current `OracleTimeStampLTZ` instance.

Return Value

The method returns a number that is:

- Less than zero: if the current `OracleTimeStampLTZ` instance value is less than that of *obj*.
- Zero: if the current `OracleTimeStampLTZ` instance and *obj* values are equal.
- Greater than zero: if the current `OracleTimeStampLTZ` instance value is greater than that of *obj*.

Implements

`Comparable`

Exceptions

`ArgumentException` - The *obj* parameter is not of type `OracleTimeStampLTZ`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStampLTZ`s. For example, comparing an `OracleTimeStampLTZ` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStampLTZ` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Equals

Overrides `Object`

This method determines whether or not an object has the same date and time as the current `OracleTimeStampLTZ` instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*

The object being compared to the current `OracleTimeStampLTZ` instance.

Return Value

Returns `true` if the *obj* is of type `OracleTimeStampLTZ` and represents the same date and time; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleTimeStampLTZ` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetDaysBetween

This method subtracts an `OracleTimeStampLTZ` value from the current instance and returns an `OracleIntervalDS` that represents the difference.

Declaration

```
// C#  
public OracleIntervalDS GetDaysBetween(OracleTimeStampLTZ value1);
```

Parameters

- `value1`
The `OracleTimeStampLTZ` value being subtracted.

Return Value

An `OracleIntervalDS` that represents the interval between two `OracleTimeStampLTZ` values.

Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalDS` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetYearsBetween

This method subtracts an `OracleTimeStampLTZ` value from the current instance and returns an `OracleIntervalYM` that represents the time interval.

Declaration

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStampLTZ value1);
```

Parameters

- `value1`
The `OracleTimeStampLTZ` value being subtracted.

Return Value

An `OracleIntervalYM` that represents the interval between two `OracleTimeStampLTZ` values.

Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalYM` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

ToOracleDate

This method converts the current `OracleTimeStampLTZ` structure to an `OracleDate` structure.

Declaration

```
// C#  
public OracleDate ToOracleDate();
```

Return Value

The returned `OracleDate` structure contains the date and time in the current instance.

Remarks

The precision of the `OracleTimeStampLTZ` value can be lost during the conversion.

If the current instance has a null value, the value of the returned `OracleDate` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

ToOracleTimeStamp

This method converts the current `OracleTimeStampLTZ` structure to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```

Return Value

The returned `OracleTimeStamp` contains the date and time in the current instance.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStamp` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

ToOracleTimeStampTZ

This method converts the current `OracleTimeStampLTZ` structure to an `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public OracleTimeStampTZ ToOracleTimeStampTZ();
```

Return Value

The returned `OracleTimeStampTZ` contains the date and time of the current instance, with the time zone set to the `OracleGlobalization.TimeZone` from the thread.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

ToString

Overrides `Object`

This method converts the current `OracleTimeStampLTZ` structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string that represents the same date and time as the current `OracleTimeStampLTZ` structure.

Remarks

The returned value is a string representation of the `OracleTimeStampLTZ` in the format specified by the `OracleGlobalization.TimeStampFormat` property of the thread.

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class ToStringSample  
{  
    static void Main()  
    {
```

```
// Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
// constructor
OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.TimestampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// construct OracleTimeStampLTZ from a string using the format
// specified.
OracleTimeStampLTZ ts =
    new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

// Set the nls_timestamp_format for the ToString() method
info.TimestampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM"
Console.WriteLine(ts.ToString());
}
}
```



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

ToUniversalTime

This method converts the current local time to Coordinated Universal Time (UTC).

Declaration

```
// C#
public OracleTimeStampTZ ToUniversalTime();
```

Return Value

An `OracleTimeStampTZ` structure.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampTZ Structure

The `OracleTimeStampTZ` structure represents the Oracle `TIMESTAMP WITH TIME ZONE` data type to be stored in or retrieved from a database. Each `OracleTimeStampTZ` stores the following information: year, month, day, hour, minute, second, nanosecond, and time zone.

Class Inheritance

```
System.Object
```

```
System.ValueType
```

```
Oracle.DataAccess.Types.OracleTimeStampTZ
```

Declaration

```
// C#
public struct OracleTimeStampTZ : IComparable, INullable, IXmlSerializable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;
```

```
class OracleTimeStampTZSample
{
    static void Main()
    {
        // Set the nls parameters for the current thread
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeZone = "US/Eastern";
        info.TimestampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        info.TimestampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Create an OracleTimeStampTZ in US/Pacific time zone
        OracleTimeStampTZ tstz1 = new OracleTimeStampTZ("11-NOV-1999 "+
            "11:02:33.444 AM US/Pacific");

        // Note that ToOracleTimeStampTZ uses the thread's time zone region,
        // "US/Eastern"
        OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");
        OracleTimeStampTZ tstz2 = ts.ToOracleTimeStampTZ();

        // Calculate the difference between tstz1 and tstz2
        OracleIntervalDS idsDiff = tstz1.GetDaysBetween(tstz2);

        // Display information
        Console.WriteLine("tstz1.TimeZone = " + tstz1.TimeZone);

        // Prints "US/Pacific"
        Console.WriteLine("tstz2.TimeZone = " + tstz2.TimeZone);

        // Prints "US/Eastern"
        Console.WriteLine("idsDiff.Hours = " + idsDiff.Hours); // Prints 3
        Console.WriteLine("idsDiff.Minutes = " + idsDiff.Minutes); // Prints 0
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Members](#)
- [OracleTimeStampTZ Constructors](#)
- [OracleTimeStampTZ Static Fields](#)
- [OracleTimeStampTZ Static Methods](#)
- [OracleTimeStampTZ Static Operators](#)
- [OracleTimeStampTZ Static Type Conversions](#)
- [OracleTimeStampTZ Properties](#)
- [OracleTimeStampTZ Methods](#)

OracleTimeStampTZ Members

OracleTimeStampTZ members are listed in the following tables:

OracleTimeStampTZ Constructors

OracleTimeStampTZ constructors are listed in [Table 14-126](#)

Table 14-126 OracleTimeStampTZ Constructors

Constructor	Description
OracleTimeStampTZ Constructors	Instantiates a new instance of OracleTimeStampTZ structure (Overloaded)

OracleTimeStampTZ Static Fields

The OracleTimeStampTZ static fields are listed in [Table 14-127](#).

Table 14-127 OracleTimeStampTZ Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an OracleTimeStampTZ structure in UTC, which is December 31, 999923:59:59.999999999
MinValue	Represents the minimum valid date for an OracleTimeStampTZ structure in UTC, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to an instance of the OracleTimeStampTZ structure

OracleTimeStampTZ Static Methods

The OracleTimeStampTZ static methods are listed in [Table 14-128](#).

Table 14-128 OracleTimeStampTZ Static Methods

Methods	Description
Equals	Determines if two OracleTimeStampTZ values are equal (Overloaded)
GetSysDate	Gets an OracleTimeStampTZ structure that represents the current date and time
GreaterThan	Determines if the first of two OracleTimeStampTZ values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second
LessThan	Determines if the first of two OracleTimeStampTZ values is less than the second

Table 14-128 (Cont.) OracleTimeStampTZ Static Methods

Methods	Description
LessThanOrEqualTo	Determines if the first of two OracleTimeStampTZ values is less than or equal to the second
NotEquals	Determines if two OracleTimeStampTZ values are not equal
Parse	Gets an OracleTimeStampTZ structure and sets its value for date and time using the supplied string
SetPrecision	Returns a new instance of an OracleTimeStampTZ with the specified fractional second precision

OracleTimeStampTZ Static Operators

The OracleTimeStampTZ static operators are listed in [Table 14-129](#).

Table 14-129 OracleTimeStampTZ Static Operators

Operator	Description
operator +	Adds the supplied instance value to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded)
operator ==	Determines if two OracleTimeStampTZ values are equal
operator >	Determines if the first of two OracleTimeStampTZ values is greater than the second
operator >=	Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second
operator !=	Determines if two OracleTimeStampTZ values are not equal
operator <	Determines if the first of two OracleTimeStampTZ values is less than the second
operator <=	Determines if the first of two OracleTimeStampTZ values is less than or equal to the second
operator -	Subtracts the supplied instance value from the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded)

OracleTimeStampTZ Static Type Conversions

The OracleTimeStampTZ static type conversions are listed in [Table 14-130](#).

Table 14-130 OracleTimeStampTZ Static Type Conversions

Operator	Description
explicit operator OracleTimeStampTZ	Converts an instance value to an OracleTimeStampTZ structure (Overloaded)
implicit operator OracleTimeStampTZ	Converts an instance value to an OracleTimeStampTZ structure (Overloaded)
explicit operator DateTime	Converts an OracleTimeStampTZ value to a DateTime structure

OracleTimeStampTZ Properties

The OracleTimeStampTZ properties are listed in [Table 14-131](#).

Table 14-131 OracleTimeStampTZ Properties

Properties	Description
BinData	Returns an array of bytes that represents an Oracle TIMESTAMP WITH TIME ZONE in Oracle internal format
Day	Specifies the day component of an OracleTimeStampTZ in the current time zone
IsNull	Indicates whether or not the current instance has a null value
Hour	Specifies the hour component of an OracleTimeStampTZ in the current time zone
Millisecond	Specifies the millisecond component of an OracleTimeStampTZ in the current time zone
Minute	Specifies the minute component of an OracleTimeStampTZ in the current time zone
Month	Specifies the month component of an OracleTimeStampTZ in the current time zone
Nanosecond	Specifies the nanosecond component of an OracleTimeStampTZ in the current time zone
Second	Specifies the second component of an OracleTimeStampTZ in the current time zone
TimeZone	Returns the time zone of the OracleTimeStampTZ instance
Value	Returns the date and time that is stored in the OracleTimeStampTZ structure in the current time zone
Year	Specifies the year component of an OracleTimeStampTZ

OracleTimeStampTZ Methods

The OracleTimeStampTZ methods are listed in [Table 14-132](#).

Table 14-132 OracleTimeStampTZ Methods

Methods	Description
AddDays	Adds the supplied number of days to the current instance
AddHours	Adds the supplied number of hours to the current instance
AddMilliseconds	Adds the supplied number of milliseconds to the current instance
AddMinutes	Adds the supplied number of minutes to the current instance
AddMonths	Adds the supplied number of months to the current instance
AddNanoseconds	Adds the supplied number of nanoseconds to the current instance
AddSeconds	Adds the supplied number of seconds to the current instance
AddYears	Adds the supplied number of years to the current instance
CompareTo	Compares the current OracleTimeStampTZ instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current OracleTimeStampTZ instance
GetDaysBetween	Subtracts an OracleTimeStampTZ from the current instance and returns an OracleIntervalDS that represents the time interval
GetHashCode	Returns a hash code for the OracleTimeStampTZ instance
GetTimeZoneOffset	Gets the time zone information in hours and minutes of the current OracleTimeStampTZ
GetYearsBetween	Subtracts an OracleTimeStampTZ from the current instance and returns an OracleIntervalYM that represents the time interval
GetType	Inherited from System.Object
ToLocalTime	Converts the current OracleTimeStampTZ instance to local time
ToOracleDate	Converts the current OracleTimeStampTZ structure to an OracleDate structure
ToOracleTimeStampLTZ	Converts the current OracleTimeStampTZ structure to an OracleTimeStampLTZ structure
ToOracleTimeStamp	Converts the current OracleTimeStampTZ structure to an OracleTimeStamp structure

Table 14-132 (Cont.) OracleTimeStampTZ Methods

Methods	Description
ToString	Converts the current OracleTimeStampTZ structure to a string
ToUniversalTime	Converts the current datetime to Coordinated Universal Time (UTC)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)

OracleTimeStampTZ Constructors

The `OracleTimeStampTZ` constructors create new instances of the `OracleTimeStampTZ` structure.

Overload List:

- [OracleTimeStampTZ\(DateTime\)](#)
This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleTimeStampTZ\(DateTime, string\)](#)
This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value and the supplied time zone data.
- [OracleTimeStampTZ\(string\)](#)
This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.
- [OracleTimeStampTZ\(int, int, int\)](#)
This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, and day.
- [OracleTimeStampTZ\(int, int, int, string\)](#)
This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, and time zone data.
- [OracleTimeStampTZ\(int, int, int, int, int, int\)](#)
This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStampTZ\(int, int, int, int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and time zone data.

- [OracleTimeStampTZ\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

- [OracleTimeStampTZ\(int, int, int, int, int, int, double, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, millisecond, and time zone data.

- [OracleTimeStampTZ\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

- [OracleTimeStampTZ\(int, int, int, int, int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, nanosecond, and time zone data.

- [OracleTimeStampTZ\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value to the provided byte array, that represents the internal Oracle `TIMESTAMP WITH TIME ZONE` format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(DateTime)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleTimeStampTZ (DateTime dt);
```

Parameters

- *dt*
The supplied `DateTime` value.

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

Exceptions

`ArgumentException` - The `dt` parameter cannot be used to construct a valid `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(DateTime, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure with the supplied `DateTime` value and the time zone data.

Declaration

```
// C#  
public OracleTimeStampTZ (DateTime value1, string timeZone);
```

Parameters

- `value1`
The supplied `DateTime` value.
- `timeZone`
The time zone data provided.

Exceptions

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ`.

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

 **Note:**

PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.

Declaration

```
// C#  
public OracleTimeStampTZ (string tsStr);
```

Parameters

- *tsStr*
A string that represents an Oracle `TIMESTAMP WITH TIME ZONE`.

Exceptions

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH TIME ZONE` or the *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread.

`ArgumentNullException` - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class OracleTimeStampTZSample
```

```
{
    static void Main()
    {
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampTZ from a string using the format specified.
        OracleTimeStampTZ tstz = new OracleTimeStampTZ("11-NOV-1999" +
            "11:02:33.444 AM US/Pacific");

        // Set the nls_timestamp_tz_format for the ToString() method
        info.TimeStampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM US/Pacific"
        Console.WriteLine(tstz.ToString());
    }
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleTimeStampTZ(int, int, int)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, and day.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*

The day provided. Range of *day* is (1 to 31).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, and time zone data.

Declaration

```
// C#  
public OracleTimeStampTZ(int year, int month, int day,  
    string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *timeZone*
The time zone data provided.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as `US/Pacific`. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note:

PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.

Declaration

```
// C#  
public OracleTimeStampTZ(int year, int month, int day, int hour,  
    int minute, int second);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).

- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and time zone data.

Declaration

```
// C#  
public OracleTimeStampTZ (int year, int month, int day, int hour,  
    int minute, int second, string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*

The minute provided. Range of *minute* is (0 to 59).

- *second*

The second provided. Range of *second* is (0 to 59).

- *timeZone*

The time zone data provided.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range of the month or the time zone is invalid).

Remarks

timeZone can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note:

PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, double)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, double millisecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *millisecond*
The millisecond provided. Range of *millisecond* is (0 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int, double, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, millisecond, and time zone data.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, double millisecond, string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *millisecond*
The millisecond provided. Range of *millisecond* is (0 to 999.999999).
- *timeZone*
The time zone data provided.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note:

PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

Declaration

```
// C#  
public OracleTimeStampTZ(int year, int month, int day, int hour,  
    int minute, int second, int nanosecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, nanosecond, and time zone data.

Declaration

```
// C#  
public OracleTimeStampTZ(int year, int month, int day, int hour,  
    int minute, int second, int nanosecond, string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).
- *timeZone*
The time zone data provided.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note:

PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(byte [])

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value to the provided byte array, that represents the internal Oracle `TIMESTAMP WITH TIME ZONE` format.

Declaration

```
// C#  
public OracleTimeStampLTZ (byte[] bytes);
```

Parameters

- `bytes`
The provided byte array that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

Exceptions

`ArgumentException` - *bytes* is not in internal Oracle `TIMESTAMP WITH TIME ZONE` format or *bytes* is not a valid Oracle `TIMESTAMP WITH TIME ZONE`.

`ArgumentNullException` - *bytes* is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Fields

The `OracleTimeStampTZ` static fields are listed in [Table 14-133](#).

Table 14-133 OracleTimeStampTZ Static Fields

Field	Description
MaxValue	Represents the maximum valid date for an <code>OracleTimeStampTZ</code> structure in UTC, which is December 31, 999923:59:59.999999999
MinValue	Represents the minimum valid date for an <code>OracleTimeStampTZ</code> structure in UTC, which is January 1, -4712 0:0:0
Null	Represents a null value that can be assigned to an instance of the <code>OracleTimeStampTZ</code> structure

See Also:


- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

MaxValue

This static field represents the maximum valid datetime time for an `OracleTimeStampTZ` structure in UTC, which is December 31, 999923:59:59.999999999.

Declaration

```
// C#
public static readonly OracleTimeStampTZ MaxValue;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

MinValue

This static field represents the minimum valid datetime for an `OracleTimeStampTZ` structure in UTC, which is January 1, -4712 0:0:0.

Declaration

```
// C#  
public static readonly OracleTimeStampTZ MinValue;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static readonly OracleTimeStampTZ Null;
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Methods

The OracleTimeStampTZ static methods are listed in [Table 14-134](#).

Table 14-134 OracleTimeStampTZ Static Methods

Methods	Description
Equals	Determines if two OracleTimeStampTZ values are equal (Overloaded)
GetSysDate	Gets an OracleTimeStampTZ structure that represents the current date and time
GreaterThan	Determines if the first of two OracleTimeStampTZ values is greater than the second
GreaterThanOrEqual	Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second
LessThan	Determines if the first of two OracleTimeStampTZ values is less than the second
LessThanOrEqual	Determines if the first of two OracleTimeStampTZ values is less than or equal to the second
NotEquals	Determines if two OracleTimeStampTZ values are not equal
Parse	Gets an OracleTimeStampTZ structure and sets its value for date and time using the supplied string
SetPrecision	Returns a new instance of an OracleTimeStampTZ with the specified fractional second precision

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Equals

This static method determines if two OracleTimeStampTZ values are equal.

Declaration

```
// C#  
public static bool Equals(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*

The first OracleTimeStampTZ.

- *value2*

The second OracleTimeStampTZ.

Return Value

Returns true if two OracleTimeStampTZ values are equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetSysDate

This static method gets an OracleTimeStampTZ structure that represents the current date and time.

Declaration

```
// C#  
public static OracleTimeStampTZ GetSysDate();
```

Return Value

An OracleTimeStampTZ structure that represents the current date and time.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GreaterThan

This static method determines if the first of two `OracleTimeStampTZ` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampTZ`.
- `value2`
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if the first of two `OracleTimeStampTZ` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GreaterThanOrEqual

This static method determines if the first of two `OracleTimeStampTZ` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if the first of two OracleTimeStampTZ values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

LessThan

This static method determines if the first of two OracleTimeStampTZ values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns `true` if the first of two `OracleTimeStampTZ` values is less than the second. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

LessThanOrEqual

This static method determines if the first of two `OracleTimeStampTZ` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampTZ`.
- `value2`
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if the first of two `OracleTimeStampTZ` values is less than or equal to the second. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

NotEquals

This static method determines if two `OracleTimeStampTZ` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampTZ`.
- `value2`
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if two `OracleTimeStampTZ` values are not equal. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Parse

This static method returns an `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.

Declaration

```
// C#  
public static OracleTimeStampTZ Parse(string tsStr);
```

Parameters

- *tsStr*

A string that represents an Oracle `TIMESTAMP WITH TIME ZONE`.

Return Value

An `OracleTimeStampTZ` structure.

Exceptions

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH TIME ZONE` or the *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_TZ_FORMAT` parameter.

`ArgumentNullException` - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class ParseSample  
{  
    static void Main()  
    {  
        // Set the nls_timestamp_tz_format for the Parse() method  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // construct OracleTimeStampTZ from a string using the format specified.  
        OracleTimeStampTZ tstz = OracleTimeStampTZ.Parse("11-NOV-1999 " +  
            "11:02:33.444 AM US/Pacific");  
  
        // Set the nls_timestamp_tz_format for the ToString() method  
        info.TimeStampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";
```

```
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM US/Pacific"
Console.WriteLine(tstz.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

SetPrecision

This static method returns a new instance of an `OracleTimeStampTZ` with the specified fractional second precision.

Declaration

```
// C#
public static OracleTimeStampTZ SetPrecision(OracleTimeStampTZ value1,
    int fracSecPrecision);
```

Parameters

- *value1*
The provided `OracleTimeStampTZ` object.
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An `OracleTimeStampTZ` structure with the specified fractional second precision

Exceptions

`ArgumentOutOfRangeException` - *fracSecPrecision* is out of the specified range.

Remarks

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleTimeStampTZ` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

Example

The `OracleTimeStampTZ` with a value of "December 31, 9999 23:59:59.99 US/Pacific" results in the string "December 31, 9999 23:59:59.99000 US/Pacific" when `SetPrecision()` is called with the fractional second precision set to 5.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Operators

The `OracleTimeStampTZ` static operators are listed in [Table 14-135](#).

Table 14-135 OracleTimeStampTZ Static Operators

Operator	Description
<code>operator +</code>	Adds the supplied instance value to the supplied <code>OracleTimeStampTZ</code> and returns a new <code>OracleTimeStampTZ</code> structure (Overloaded)
<code>operator ==</code>	Determines if two <code>OracleTimeStampTZ</code> values are equal
<code>operator ></code>	Determines if the first of two <code>OracleTimeStampTZ</code> values is greater than the second
<code>operator >=</code>	Determines if the first of two <code>OracleTimeStampTZ</code> values is greater than or equal to the second
<code>operator !=</code>	Determines if two <code>OracleTimeStampTZ</code> values are not equal
<code>operator <</code>	Determines if the first of two <code>OracleTimeStampTZ</code> values is less than the second
<code>operator <=</code>	Determines if the first of two <code>OracleTimeStampTZ</code> values is less than or equal to the second
<code>operator -</code>	Subtracts the supplied instance value from the supplied <code>OracleTimeStampTZ</code> and returns a new <code>OracleTimeStampTZ</code> structure (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +

`operator+` adds the supplied structure to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

Overload List:

- [operator +\(OracleTimeStampTZ, OracleIntervalDS\)](#)
This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.
- [operator +\(OracleTimeStampTZ, OracleIntervalYM\)](#)
This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.
- [operator +\(OracleTimeStampTZ, TimeSpan\)](#)
This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +(OracleTimeStampTZ, OracleIntervalDS)

This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampTZ value1,  
    OracleIntervalDS value2);
```

Parameters

- `value1`

An OracleTimeStampTZ.

- *value2*

An OracleIntervalDS.

Return Value

An OracleTimeStampTZ.

Remarks

If either parameter has a null value, the returned OracleTimeStampTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +(OracleTimeStampTZ, OracleIntervalYM)

This static operator adds the supplied OracleIntervalYM to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampTZ value1,  
    OracleIntervalYM value2);
```

Parameters

- *value1*
An OracleTimeStampTZ.
- *value2*
An OracleIntervalYM.

Return Value

An OracleTimeStampTZ.

Remarks

If either parameter has a null value, the returned OracleTimeStampTZ has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +(OracleTimeStampTZ, TimeSpan)

This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampTZ value1, TimeSpan value2);
```

Parameters

- `value1`
An `OracleTimeStampTZ`.
- `value2`
A `TimeSpan`.

Return Value

An `OracleTimeStampTZ`.

Remarks

If the `OracleTimeStampTZ` instance has a null value, the returned `OracleTimeStampTZ` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator ==

This static operator determines if two `OracleTimeStampTZ` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if they are equal; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator >

This static operator determines if the first of two OracleTimeStampTZ values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns `true` if the first `OracleTimeStampTZ` value is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator >=

This static operator determines if the first of two `OracleTimeStampTZ` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampTZ`.
- `value2`
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if the first `OracleTimeStampTZ` is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator !=

This static operator determines if two `OracleTimeStampTZ` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampTZ`.
- *value2*
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if two `OracleTimeStampTZ` values are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator <

This static operator determines if the first of two `OracleTimeStampTZ` values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampTZ`.
- `value2`
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if the first `OracleTimeStampTZ` is less than the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator <=

This static operator determines if the first of two `OracleTimeStampTZ` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- `value1`
The first `OracleTimeStampTZ`.
- `value2`
The second `OracleTimeStampTZ`.

Return Value

Returns true if the first `OracleTimeStampTZ` is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator -

`operator-` subtracts the supplied value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

Overload List:

- [operator - \(OracleTimeStampTZ, OracleIntervalDS\)](#)
This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampTZ` value, and return a new `OracleTimeStampTZ` structure.
- [operator - \(OracleTimeStampTZ, OracleIntervalYM\)](#)
This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.
- [operator - \(OracleTimeStampTZ value1, TimeSpan value2\)](#)
This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator - (OracleTimeStampTZ, OracleIntervalDS)

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampTZ` value, and return a new `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStampTZ value1,  
    OracleIntervalDS value2);
```

Parameters

- `value1`
An `OracleTimeStampTZ`.
- `value2`
An `OracleIntervalDS`.

Return Value

An `OracleTimeStampTZ` structure.

Remarks

If either parameter has a null value, the returned `OracleTimeStampTZ` has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator - (OracleTimeStampTZ, OracleIntervalYM)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStampTZ value1,  
    OracleIntervalYM value2);
```

Parameters

- *value1*
An OracleTimeStampTZ.
- *value2*
An OracleIntervalYM.

Return Value

An OracleTimeStampTZ structure.

Remarks

If either parameter has a null value, the returned OracleTimeStampTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator - (OracleTimeStampTZ value1, TimeSpan value2)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStampTZ value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStampTZ.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStampTZ structure.

Remarks

If the `OracleTimeStampTZ` instance has a null value, the returned `OracleTimeStampTZ` structure has a null value.

 **See Also:**

- "Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Type Conversions

The `OracleTimeStampTZ` static type conversions are listed in [Table 14-136](#).

Table 14-136 OracleTimeStampTZ Static Type Conversions

Operator	Description
explicit operator OracleTimeStampTZ	Converts an instance value to an <code>OracleTimeStampTZ</code> structure (Overloaded)
implicit operator OracleTimeStampTZ	Converts an instance value to an <code>OracleTimeStampTZ</code> structure (Overloaded)
explicit operator DateTime	Converts an <code>OracleTimeStampTZ</code> value to a <code>DateTime</code> structure in the current time zone

 **See Also:**

- "Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

explicit operator OracleTimeStampTZ

`explicit operator OracleTimeStampTZ` converts an instance value to an `OracleTimeStampTZ` structure.

Overload List:

- [explicit operator OracleTimeStampTZ\(OracleTimeStamp\)](#)
This static type conversion operator converts an `OracleTimeStamp` value to an `OracleTimeStampTZ` structure.

- [explicit operator OracleTimeStampTZ\(OracleTimeStampLTZ\)](#)

This static type conversion operator converts an `OracleTimeStampLTZ` value to an `OracleTimeStampTZ` structure.

- [explicit operator OracleTimeStampTZ\(string\)](#)

This static type conversion operator converts the supplied string value to an `OracleTimeStampTZ` structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

explicit operator OracleTimeStampTZ(OracleTimeStamp)

This static type conversion operator converts an `OracleTimeStamp` value to an `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampTZ(OracleTimeStamp value1);
```

Parameters

- `value1`
An `OracleTimeStamp`.

Return Value

The returned `OracleTimeStampTZ` contains the date and time from the `OracleTimeStamp` and the time zone from the `OracleGlobalization.TimeZone` of the thread.

Remarks

The `OracleGlobalization.TimeZone` of the thread is used to convert from an `OracleTimeStamp` structure to an `OracleTimeStampTZ` structure.

If the `OracleTimeStamp` structure has a null value, the returned `OracleTimeStampTZ` structure also has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

explicit operator OracleTimeStampTZ(OracleTimeStampLTZ)

This static type conversion operator converts an `OracleTimeStampLTZ` value to an `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampTZ(OracleTimeStampLTZ value1);
```

Parameters

- `value1`
An `OracleTimeStampLTZ`.

Return Value

The returned `OracleTimeStampTZ` contains the date and time from the `OracleTimeStampLTZ` and the time zone from the `OracleGlobalization.TimeZone` of the thread.

Remarks

If the `OracleTimeStampLTZ` structure has a null value, the returned `OracleTimeStampTZ` structure also has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

explicit operator OracleTimeStampTZ(string)

This static type conversion operator converts the supplied string value to an OracleTimeStampTZ structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampTZ(string tsStr);
```

Parameters

- *tsStr*

A string representation of an Oracle `TIMESTAMP WITH TIME ZONE`.

Return Value

An OracleTimeStampTZ value.

Exceptions

ArgumentException - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH TIME ZONE`, or the *tsStr* is not in the timestamp format specified by the thread's `OracleGlobalization.TimeStampTZFormat` property, which represents the Oracle `NLS_TIMESTAMP_TZ_FORMAT` parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class OracleTimeStampTZSample  
{  
    static void Main()  
    {  
        // Set the nls_timestamp_tz_format for the explicit operator  
        // OracleTimeStampTZ(string)  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // construct OracleTimeStampTZ from a string using the format specified.  
        OracleTimeStampTZ tstz = new OracleTimeStampTZ("11-NOV-1999" +  
            "11:02:33.444 AM US/Pacific");  
  
        // Set the nls_timestamp_tz_format for the ToString() method  
        info.TimeStampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";  
        OracleGlobalization.SetThreadInfo(info);  
    }  
}
```

```
        Console.WriteLine(tstz.ToString());  
    }  
}
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

implicit operator OracleTimeStampTZ

implicit operator OracleTimeStampTZ converts a DateTime structure to an OracleTimeStampTZ structure.

Overload List:

- [implicit operator OracleTimeStampTZ\(OracleDate\)](#)
This static type conversion operator converts an OracleDate value to an OracleTimeStampTZ structure.
- [implicit operator OracleTimeStampTZ\(DateTime\)](#)
This static type conversion operator converts a DateTime structure to an OracleTimeStampTZ structure.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

implicit operator OracleTimeStampTZ(OracleDate)

This static type conversion operator converts an OracleDate value to an OracleTimeStampTZ structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStampTZ(OracleDate value1);
```

Parameters

- *value1*
An OracleDate.

Return Value

The returned OracleTimeStampTZ contains the date and time from the OracleDate and the time zone from the OracleGlobalization.TimeZone of the thread.

Remarks

The OracleGlobalization.TimeZone of the thread is used to convert from an OracleDate to an OracleTimeStampTZ structure. If the OracleDate structure has a null value, the returned OracleTimeStampTZ structure also has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

implicit operator OracleTimeStampTZ(DateTime)

This static type conversion operator converts a DateTime structure to an OracleTimeStampTZ structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStampTZ (DateTime value1);
```

Parameters

- *value1*
A DateTime structure.

Return Value

The returned OracleTimeStampTZ contains the date and time from the DateTime and the time zone from the OracleGlobalization.TimeZone of the thread.

Remarks

The `OracleGlobalization.TimeZone` of the thread is used to convert from a `DateTime` to an Oracle `TimeStampTZ` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

explicit operator DateTime

This static type conversion operator converts an `OracleTimeStampTZ` value to a `DateTime` structure and truncates the time zone information.

Declaration

```
// C#  
public static explicit operator DateTime(OracleTimeStampTZ value1);
```

Parameters

- `value1`
An `OracleTimeStampTZ`.

Return Value

A `DateTime` containing the date and time in the current instance, but with the time zone information in the current instance truncated.

Exceptions

`OracleNullValueException` - The `OracleTimeStampTZ` structure has a null value.

Remarks

The precision of the `OracleTimeStampTZ` value can be lost during the conversion, and the time zone information in the current instance is truncated

 See Also:

- "Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"
- OracleTimeStampTZ Structure
- OracleTimeStampTZ Members

OracleTimeStampTZ Properties

The OracleTimeStampTZ properties are listed in [Table 14-137](#).

Table 14-137 OracleTimeStampTZ Properties

Properties	Description
BinData	Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH TIME ZONE</code> in Oracle internal format
Day	Specifies the day component of an OracleTimeStampTZ in the current time zone
IsNull	Indicates whether or not the current instance has a null value
Hour	Specifies the hour component of an OracleTimeStampTZ in the current time zone
Millisecond	Specifies the millisecond component of an OracleTimeStampTZ in the current time zone
Minute	Specifies the minute component of an OracleTimeStampTZ in the current time zone
Month	Specifies the month component of an OracleTimeStampTZ in the current time zone
Nanosecond	Specifies the nanosecond component of an OracleTimeStampTZ in the current time zone
Second	Specifies the second component of an OracleTimeStampTZ in the current time zone
TimeZone	Returns the time zone of the OracleTimeStampTZ instance
Value	Returns the date and time that is stored in the OracleTimeStampTZ structure in the current time zone
Year	Specifies the year component of an OracleTimeStampTZ

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

Declaration

```
// C#  
public byte[] BinData {get;}
```

Property Value

The provided byte array that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Day

This property specifies the day component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of `Day` is (1 to 31).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value. Otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Hour

This property specifies the hour component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Hour{get;}
```

Property Value

A number that represents the hour. Range of `Hour` is (0 to 23).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Millisecond

This property gets the millisecond component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public double Millisecond{get;}
```

Property Value

A number that represents a millisecond. Range of `Millisecond` is (0 to 999.999999)

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Minute

This property gets the minute component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Minute{get;}
```

Property Value

A number that represent a minute. Range of `Minute` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Month

This property gets the month component of an `OracleTimeStampTZ` in the current time zone

Declaration

```
// C#  
public int Month{get;}
```

Property Value

A number that represents a month. Range of `Month` is (1 to 12).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Nanosecond

This property gets the nanosecond component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Nanosecond{get;}
```

Property Value

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Second

This property gets the second component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Second{get;}
```

Property Value

A number that represents a second. Range of `Second` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

TimeZone

This property returns the time zone of the `OracleTimeStampTZ` instance.

Declaration

```
// C#  
public string TimeZone{get;}
```

Property Value

A string that represents the time zone.

Remarks

If no time zone is specified in the constructor, this property is set to the thread's `OracleGlobalization.TimeZone` by default

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

Value

This property returns the date and time that is stored in the `OracleTimeStampTZ` structure in the current time zone.

Declaration

```
// C#  
public DateTime Value{get;}
```

Property Value

A `DateTime` in the current time zone.

Exceptions

`OracleNullValueException` - The current instance has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Year

This property sets the year component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Year{get;}
```

Property Value

A number that represents a year. The range of `Year` is (-4712 to 9999).

Exceptions

`OracleNullValueException` - The current instance has a null value.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Methods

The `OracleTimeStampTZ` methods are listed in [Table 14-138](#).

Table 14-138 OracleTimeStampTZ Methods

Methods	Description
AddDays	Adds the supplied number of days to the current instance
AddHours	Adds the supplied number of hours to the current instance
AddMilliseconds	Adds the supplied number of milliseconds to the current instance
AddMinutes	Adds the supplied number of minutes to the current instance
AddMonths	Adds the supplied number of months to the current instance
AddNanoseconds	Adds the supplied number of nanoseconds to the current instance
AddSeconds	Adds the supplied number of seconds to the current instance
AddYears	Adds the supplied number of years to the current instance
CompareTo	Compares the current <code>OracleTimeStampTZ</code> instance to an object, and returns an integer that represents their relative values
Equals	Determines whether or not an object has the same date and time as the current <code>OracleTimeStampTZ</code> instance (Overloaded)
GetDaysBetween	Subtracts an <code>OracleTimeStampTZ</code> from the current instance and returns an <code>OracleIntervalDS</code> that represents the time interval
GetHashCode	Returns a hash code for the <code>OracleTimeStampTZ</code> instance
GetTimeZoneOffset	Gets the time zone information in hours and minutes of the current <code>OracleTimeStampTZ</code>
GetYearsBetween	Subtracts an <code>OracleTimeStampTZ</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the time interval
GetType	Inherited from <code>System.Object</code>

Table 14-138 (Cont.) OracleTimeStampTZ Methods

Methods	Description
ToLocalTime	Converts the current OracleTimeStampTZ instance to local time
ToOracleDate	Converts the current OracleTimeStampTZ structure to an OracleDate structure
ToOracleTimeStampLTZ	Converts the current OracleTimeStampTZ structure to an OracleTimeStampLTZ structure
ToOracleTimeStamp	Converts the current OracleTimeStampTZ structure to an OracleTimeStamp structure
ToString	Converts the current OracleTimeStampTZ structure to a string
ToUniversalTime	Converts the current datetime to Coordinated Universal Time (UTC)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddDays

This method adds the supplied number of days to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddDays(double days);
```

Parameters

- *days*
The supplied number of days. Range is $(-1,000,000,000 < days < 1,000,000,000)$

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddHours

This method adds the supplied number of hours to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddHours(double hours);
```

Parameters

- *hours*
The supplied number of hours. Range is $(-24,000,000,000 < hours < 24,000,000,000)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddMilliseconds(double milliseconds);
```

Parameters

- *milliseconds*

The supplied number of milliseconds. Range is $(-8.64 * 10^{16} < \text{milliseconds} < 8.64 * 10^{16})$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddMinutes

This method adds the supplied number of minutes to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddMinutes(double minutes);
```

Parameters

- *minutes*

The supplied number of minutes. Range is $(-1,440,000,000,000 < \text{minutes} < 1,440,000,000,000)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddMonths

This method adds the supplied number of months to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddMonths(long months);
```

Parameters

- *months*
The supplied number of months. Range is $(-12,000,000,000 < months < 12,000,000,000)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddNanoseconds(long nanoseconds);
```

Parameters

- *nanoseconds*
The supplied number of nanoseconds.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddSeconds

This method adds the supplied number of seconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddSeconds(double seconds);
```

Parameters

- *seconds*
The supplied number of seconds. Range is $(-8.64 * 1013 < seconds < 8.64 * 1013)$.


Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddYears

This method adds the supplied number of years to the current instance

Declaration

```
// C#  
public OracleTimeStampTZ AddYears(int years);
```

Parameters

- *years*
The supplied number of years. Range is (-999,999,999 <= *years* <= 999,999,999).

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

CompareTo

This method compares the current OracleTimeStampTZ instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared to the current `OracleTimeStampTZ` instance.

Return Value

The method returns a number that is:

Less than zero: if the current `OracleTimeStampTZ` instance value is less than that of *obj*.

Zero: if the current `OracleTimeStampTZ` instance and *obj* values are equal.

Greater than zero: if the current `OracleTimeStampTZ` instance value is greater than that of *obj*.

Implements

`Comparable`

Exceptions

`ArgumentException` - The *obj* is not of type `OracleTimeStampTZ`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStampTZ`s. For example, comparing an `OracleTimeStampTZ` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStampTZ` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Equals

Overrides `Object`

This method determines whether or not an object has the same date and time as the current `OracleTimeStampTZ` instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*

The object being compared to the current `OracleTimeStampTZ` instance.

Return Value

Returns `true` if the *obj* is of type `OracleTimeStampTZ` and represents the same date and time; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetDaysBetween

This method subtracts an `OracleTimeStampTZ` value from the current instance and returns an `OracleIntervalDS` that represents the time interval.

Declaration

```
// C#  
public OracleIntervalDS GetDaysBetween(OracleTimeStampTZ value1);
```

Parameters

- *value1*

The `OracleTimeStampTZ` value being subtracted.

Return Value

An `OracleIntervalDS` that represents the interval between two `OracleTimeStampTZ` values.

Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalDS` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleTimeStampTZ` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetTimeZoneOffset

This method gets the time zone portion in hours and minutes of the current `OracleTimeStampTZ`.

Declaration

```
// C#  
public TimeSpan GetTimeZoneOffset();
```

Return Value

A `TimeSpan`.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetYearsBetween

This method subtracts an `OracleTimeStampTZ` value from the current instance and returns an `OracleIntervalYM` that represents the time interval.

Declaration

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStampTZ val);
```

Parameters

- `val`
The `OracleTimeStampTZ` value being subtracted.

Return Value

An `OracleIntervalYM` that represents the interval between two `OracleTimeStampTZ` values.

Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalYM` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToLocalTime

This method converts the current `OracleTimeStampTZ` instance to local time.

Declaration

```
// C#  
public OracleTimeStampLTZ ToLocalTime();
```

Return Value

An `OracleTimeStampLTZ` that contains the date and time, which is normalized to the client local time zone, in the current instance.

Remarks

If the current instance has a null value, the returned `OracleTimeStampLTZ` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToOracleDate

This method converts the current `OracleTimeStampTZ` structure to an `OracleDate` structure.

Declaration

```
// C#  
public OracleDate ToOracleDate();
```

Return Value

The returned `OracleDate` contains the date and time in the current instance, but the time zone information in the current instance is truncated.

Remarks

The precision of the `OracleTimeStampTZ` value can be lost during the conversion, and the time zone information in the current instance is truncated.

If the current instance has a null value, the value of the returned `OracleDate` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToOracleTimeStampLTZ

This method converts the current `OracleTimeStampTZ` structure to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public OracleTimeStampLTZ ToOracleTimeStampLTZ();
```

Return Value

The returned `OracleTimeStampLTZ` structure contains the date and time, which is normalized to the client local time zone, in the current instance.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStampLTZ` structure has a null value.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToOracleTimeStamp

This method converts the current `OracleTimeStampTZ` structure to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```

Return Value

The returned `OracleTimeStamp` contains the date and time in the current instance, but the time zone information is truncated.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStamp` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToString

Overrides `Object`

This method converts the current `OracleTimeStampTZ` structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string that represents the same date and time as the current `OracleTimeStampTZ` structure.

Remarks

The returned value is a string representation of an `OracleTimeStampTZ` in the format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread. The names and abbreviations used for months and days are in the language specified by the `OracleGlobalization.DateLanguage` and the `OracleGlobalization.Calendar` properties of the thread. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class ToStringSample  
{  
    static void Main()  
    {  
        // Set the nls parameters for the current thread  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.TimeZone = "US/Eastern";  
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";  
    }  
}
```

```
info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
OracleGlobalization.SetThreadInfo(info);

// Create an OracleTimeStampTZ in US/Pacific time zone
OracleTimeStampTZ tstz1=new OracleTimeStampTZ("11-NOV-1999 "+
    "11:02:33.444 AM US/Pacific");

// Note that ToOracleTimeStampTZ uses the thread's time zone region,
// "US/Eastern"
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");
OracleTimeStampTZ tstz2 = ts.ToOracleTimeStampTZ();

// Calculate the difference between tstz1 and tstz2
OracleIntervalDS idsDiff = tstz1.GetDaysBetween(tstz2);

// Prints "US/Pacific"
Console.WriteLine("tstz1.TimeZone = " + tstz1.TimeZone);

// Prints "US/Eastern"
Console.WriteLine("tstz2.TimeZone = " + tstz2.TimeZone);

// Prints 3
Console.WriteLine("idsDiff.Hours = " + idsDiff.Hours);

// Prints 0
Console.WriteLine("idsDiff.Minutes = " + idsDiff.Minutes);
}
}
```



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#)
- ["Globalization Support "](#)

ToUniversalTime

This method converts the current datetime to Coordinated Universal Time (UTC).

Declaration

```
// C#
public OracleTimeStampTZ ToUniversalTime();
```

Return Value

An OracleTimeStampTZ structure.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

INullable Interface

The `INullable` interface is used to determine whether or not an ODP.NET type has a NULL value.

Declaration

```
// C#
public interface INullable
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [INullable Interface Members](#)
- [INullable Interface Properties](#)

INullable Interface Members

INullable members are listed in the following tables.

INullable Interface Properties

INullable interface properties are listed in [Table 14-139](#).

Table 14-139 INullable Interface Properties

Public Property	Description
IsNull	Indicates whether or not the ODP.NET type has a NULL value



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [INullable Interface](#)

INullable Interface Properties

INullable interface properties are listed in [Table 14-139](#).

Table 14-140 INullable Interface Properties

Public Property	Description
IsNull	Indicates whether or not the ODP.NET type has a NULL value

IsNull

This property indicates whether or not the ODP.NET type has a NULL value.

Declaration

```
// C#  
bool IsNull {get;}
```

Property Value

Returns true if the ODP.NET type has a NULL value; otherwise, returns false.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [INullable Interface](#)
- [INullable Interface Members](#)

15

Oracle Data Provider for .NET Types Exceptions

This section covers the ODP.NET Types exceptions.

This chapter contains these topics:

- [OracleTypeException Class](#)
- [OracleNullValueException Class](#)
- [OracleTruncateException Class](#)

OracleTypeException Class

The `OracleTypeException` is the base exception class for handling exceptions that occur in the ODP.NET Types classes.

Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`Oracle.DataAccess.Types.OracleTypeException`

Declaration

```
// C#  
public class OracleTypeException : SystemException
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Members](#)
- [OracleTypeException Constructors](#)
- [OracleTypeException Static Methods](#)
- [OracleTypeException Properties](#)
- [OracleTypeException Methods](#)

OracleTypeException Members

OracleTypeException members are listed in the following tables.

OracleTypeException Constructors

The OracleTypeException constructors are listed in [Table 15-1](#).

Table 15-1 OracleTypeException Constructor

Constructor	Description
OracleTypeException Constructors	Creates a new instance of the OracleTypeException class (Overloaded)

OracleTypeException Static Methods

The OracleTypeException static methods are listed in [Table 15-2](#).

Table 15-2 OracleTypeException Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleTypeException Properties

The OracleTypeException properties are listed in [Table 15-3](#).

Table 15-3 OracleTypeException Properties

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception

Table 15-3 (Cont.) OracleTypeException Properties

Properties	Description
Message	Specifies the error messages that occur in the exception
Number	Specifies the error number that occurs in the exception
Source	Specifies the name of the data provider that generates the error
StackTrace	Inherited from <code>System.SystemException.Exception</code>
TargetSite	Inherited from <code>System.SystemException.Exception</code>

OracleTypeException Methods

The OracleTypeException methods are listed in [Table 15-4](#).

Table 15-4 OracleTypeException Methods

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)
GetBaseException	Inherited from <code>System.SystemException.Exception</code>
GetHashCode	Inherited from <code>System.Object</code>
GetObjectData	Inherited from <code>System.SystemException.Exception</code>
GetType	Inherited from <code>System.Object</code>
ToString	Returns the fully qualified name of this exception

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)

OracleTypeException Constructors

The OracleTypeException constructors create new instances of the OracleTypeException class.

Overload List:

- [OracleTypeException\(string\)](#)

This constructor creates a new instance of the `OracleTypeException` class with the specified error message, `errorMessage`.

- [OracleTypeException\(SerializationInfo, StreamingContext\)](#)

This constructor creates a new instance of the `OracleTypeException` class with the specified serialization information, `si`, and the specified streaming context, `sc`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException(string)

This constructor creates a new instance of the `OracleTypeException` class with the specified error message, `errorMessage`.

Declaration

```
// C#  
public OracleTypeException (string errorMessage);
```

Parameters

- `errorMessage`
The specified error message.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException(SerializationInfo, StreamingContext)

This constructor creates a new instance of the `OracleTypeException` class with the specified serialization information, `si`, and the specified streaming context, `sc`.

Declaration

```
// C#  
protected OracleTypeException (SerializationInfo si, StreamingContext sc);
```

Parameters

- *si*
The specified serialization information.
- *sc*
The specified streaming context.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException Static Methods

The `OracleTypeException` static methods are listed in [Table 15-5](#).

Table 15-5 OracleTypeException Static Methods

Methods	Description
<code>Equals</code>	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException Properties

The `OracleTypeException` properties are listed in [Table 15-6](#).

Table 15-6 OracleTypeException Properties

Properties	Description
<code>HelpLink</code>	Inherited from <code>System.SystemException.Exception</code>
<code>InnerException</code>	Inherited from <code>System.SystemException.Exception</code>
Message	Specifies the error messages that occur in the exception

Table 15-6 (Cont.) OracleTypeException Properties

Properties	Description
Number	Specifies the error number that occurs in the exception
Source	Specifies the name of the data provider that generates the error
StackTrace	Inherited from <code>System.SystemException.Exception</code>
TargetSite	Inherited from <code>System.SystemException.Exception</code>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

Message

Overrides `Exception`

This property specifies the error messages that occur in the exception.

Declaration

```
// C#  
public override string Message {get;}
```

Property Value

An error message.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

Number

Overrides `Exception`

This property specifies the error number that occurs in the exception

Declaration

```
// C#  
public override int Number {get;}
```

Property Value

An error number

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

Source

Overrides [Exception](#)

This property specifies the name of the data provider that generates the error.

Declaration

```
// C#  
public override string Source {get;}
```

Property Value

Oracle Data Provider for .NET.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException Methods

The [OracleTypeException](#) methods are listed in [Table 15-7](#).

Table 15-7 OracleTypeException Methods

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

Table 15-7 (Cont.) OracleTypeException Methods

Methods	Description
GetBaseException	Inherited from System.SystemException.Exception
GetHashCode	Inherited from System.Object
GetObjectData	Inherited from System.SystemException.Exception
GetType	Inherited from System.Object
ToString	Returns the fully qualified name of this exception

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

ToString

Overrides Exception

This method returns the fully qualified name of this exception, the error message in the Message property, the InnerException.ToString() message, and the stack trace.

Declaration

```
// C#
public override string ToString();
```

Return Value

The fully qualified name of this exception.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleNullValueException Class

The OracleNullValueException represents an exception that is thrown when trying to access an ODP.NET Types structure that has a null value.

Class Inheritance

```

System.Object
  System.Exception
    System.SystemException
      System.OracleTypeException
        Oracle.DataAccess.Types.OracleNullValueException

```

Declaration

```

// C#
public sealed class OracleNullValueException : OracleTypeException

```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleNullValueException Members](#)
- [OracleNullValueException Constructors](#)
- [OracleNullValueException Static Methods](#)
- [OracleNullValueException Properties](#)
- [OracleNullValueException Methods](#)

OracleNullValueException Members

OracleNullValueException members are listed in the following tables.

OracleNullValueException Constructors

The OracleNullValueException constructors are listed in [Table 15-8](#).

Table 15-8 OracleNullValueException Constructors

Constructor	Description
OracleNullValueException Constructors	Creates a new instance of the OracleNullValueException class (Overloaded)

OracleNullValueException Static Methods

The OracleNullValueException static methods are listed in [Table 15-9](#).

Table 15-9 OracleNullValueException Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleNullValueException Properties

The OracleNullValueException properties are listed in [Table 15-10](#).

Table 15-10 OracleNullValueException Properties

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
Message	Inherited from OracleTypeException
Source	Inherited from OracleTypeException
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

OracleNullValueException Methods

The OracleNullValueException methods are listed in [Table 15-11](#).

Table 15-11 OracleNullValueException Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.SystemException.Exception

Table 15-11 (Cont.) OracleNullValueException Methods

Methods	Description
GetHashCode	Inherited from <code>System.Object</code>
GetObjectData	Inherited from <code>System.SystemException.Exception</code>
GetType	Inherited from <code>System.Object</code>
ToString	Inherited from <code>OracleTypeException</code>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleNullValueException Class](#)

OracleNullValueException Constructors

The `OracleNullValueException` constructors create new instances of the `OracleNullValueException` class.

Overload List:

- [OracleNullValueException\(\)](#)
This constructor creates a new instance of the `OracleNullValueException` class with its default properties.
- [OracleNullValueException\(string\)](#)
This constructor creates a new instance of the `OracleNullValueException` class with the specified error message, `errorMessage`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException()

This constructor creates a new instance of the `OracleNullValueException` class with its default properties.

Declaration

```
// C#  
public OracleNullValueException();
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException(string)

This constructor creates a new instance of the `OracleNullValueException` class with the specified error message, `errorMessage`.

Declaration

```
// C#  
public OracleNullValueException (string errorMessage);
```

Parameters

- `errorMessage`
The specified error message.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException Static Methods

The `OracleNullValueException` static methods are listed in [Table 15-12](#).

Table 15-12 OracleNullValueException Static Methods

Methods	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException Properties

The OracleNullValueException properties are listed in [Table 15-13](#).

Table 15-13 OracleNullValueException Properties

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
Message	Inherited from OracleTypeException
Source	Inherited from OracleTypeException
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException Methods

The OracleNullValueException methods are listed in [Table 15-14](#).

Table 15-14 OracleNullValueException Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.SystemException.Exception
GetHashCode	Inherited from System.Object
GetObjectData	Inherited from System.SystemException.Exception

Table 15-14 (Cont.) OracleNullValueException Methods

Methods	Description
GetType	Inherited from System.Object
ToString	Inherited from OracleTypeException

OracleTruncateException Class

The `OracleTruncateException` class represents an exception that is thrown when truncation in a ODP.NET Types class occurs.

Class Inheritance

System.Object

System.Exception

System.SystemException

System.OracleTypeException

Oracle.DataAccess.Types.OracleTruncateException

Declaration

```
// C#
public sealed class OracleTruncateException : OracleTypeException
```

Requirements

Provider	ODP.NET, Unmanaged Driver	ODP.NET, Managed Driver	ODP.NET Core
Assembly	Oracle.DataAccess.dll	Oracle.ManagedDataAccess.dll	Oracle.ManagedDataAccess.dll
Namespace	Oracle.DataAccess.Client	Oracle.ManagedDataAccess.Client	Oracle.ManagedDataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7	4.5, 4.6, 4.7	4.6.1 or higher
.NET Core	-	-	2.1 or higher

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Members](#)
- [OracleTruncateException Constructors](#)
- [OracleTruncateException Static Methods](#)
- [OracleTruncateException Properties](#)
- [OracleTruncateException Methods](#)

OracleTruncateException Members

OracleTruncateException members are listed in the following tables.

OracleTruncateException Constructors

The OracleTruncateException constructors are listed in [Table 15-15](#).

Table 15-15 OracleTruncateException Constructors

Constructor	Description
OracleTruncateException Constructors	Creates a new instance of the OracleTruncateException class (Overloaded)

OracleTruncateException Static Methods

The OracleTruncateException static methods are listed in [Table 15-16](#).

Table 15-16 OracleTruncateException Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

OracleTruncateException Properties

The OracleTruncateException properties are listed in [Table 15-17](#).

Table 15-17 OracleTruncateException Properties

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
Message	Inherited from OracleTypeException

Table 15-17 (Cont.) OracleTruncateException Properties

Properties	Description
Source	Inherited from OracleTypeException
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

OracleTruncateException Methods

The OracleTruncateException methods are listed in [Table 15-18](#).

Table 15-18 OracleTruncateException Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.SystemException.Exception
GetHashCode	Inherited from System.Object
GetObjectData	Inherited from System.SystemException.Exception
GetType	Inherited from System.Object
ToString	Inherited from OracleTypeException

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Class](#)

OracleTruncateException Constructors

The OracleTruncateException constructors create new instances of the OracleTruncateException class

Overload List:

- [OracleTruncateException\(\)](#)
This constructor creates a new instance of the OracleTruncateException class with its default properties.
- [OracleTruncateException\(string\)](#)

This constructor creates a new instance of the `OracleTruncateException` class with the specified error message, `errorMessage`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException()

This constructor creates a new instance of the `OracleTruncateException` class with its default properties.

Declaration

```
// C#  
public OracleTruncateException();
```

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException(string)

This constructor creates a new instance of the `OracleTruncateException` class with the specified error message, `errorMessage`.

Declaration

```
// C#  
public OracleTruncateException (string errorMessage);
```

Parameters

- `errorMessage`
The specified error message.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException Static Methods

The OracleTruncateException static methods are listed in [Table 15-19](#).

Table 15-19 OracleTruncateException Static Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException Properties

The OracleTruncateException properties are listed in [Table 15-20](#).

Table 15-20 OracleTruncateException Properties

Properties	Description
HelpLink	Inherited from System.SystemException.Exception
InnerException	Inherited from System.SystemException.Exception
Message	Inherited from OracleTypeException
Source	Inherited from OracleTypeException
StackTrace	Inherited from System.SystemException.Exception
TargetSite	Inherited from System.SystemException.Exception

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException Methods

The OracleTruncateException methods are listed in [Table 15-21](#).

Table 15-21 OracleTruncateException Methods

Methods	Description
Equals	Inherited from System.Object (Overloaded)
GetBaseException	Inherited from System.SystemException.Exception
GetHashCode	Inherited from System.Object
GetObjectData	Inherited from System.SystemException.Exception
GetType	Inherited from System.Object
ToString	Inherited from OracleTypeException

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

16

Oracle Data Provider for .NET UDT-Related Classes

This chapter describes the object-related classes and interfaces in the Oracle Data Provider for .NET that provide support for Oracle user-defined data types (UDT).

In ODAC Oracle Universal Installer, samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples\UDT` directory.



See Also:

"Oracle User-Defined Types (UDTs) and .NET Custom Types"

- [OracleCustomTypeMappingAttribute Class](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleArrayMappingAttribute Class](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomTypeFactory Interface](#)
- [IOracleArrayTypeFactory Interface](#)
- [OracleUdt Class](#)
- [OracleRef Class](#)
- [OracleUdtFetchOption Enumeration](#)
- [OracleUdtStatus Enumeration](#)

OracleCustomTypeMappingAttribute Class

The `OracleCustomTypeMappingAttribute` class is used to mark a custom type factory class or struct with information that is used by ODP.NET when a custom type is used to represent an Oracle UDT.

Class Inheritance

`System.Object`

`System.Attribute`

`System.OracleCustomTypeMappingAttribute`

Declaration

```
// C#  
[AttributeUsageAttribute(AttributeTargets.Class|AttributeTargets.Struct,
```

```
AllowMultiple=false, Inherited=true)]  
public sealed class OracleCustomTypeMappingAttribute : Attribute
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Types
.NET Framework	3.5, 4.5, 4.6, 4.7

Remarks

The `OracleCustomTypeMapping` attribute must be specified on the custom type factory class to indicate the Oracle UDT that the corresponding custom type represents. The Oracle UDT may be specified in the form `schema_name.type_name`.

For each Oracle UDT that the application uses, there must be a unique custom type factory, as follows:

- Oracle Object Types
The custom type factory must return a custom type that cannot be used to represent any other Oracle Object Type.
- Oracle Collection Types
The custom type factory may return a custom type that can be used by other Oracle Collection Types. This is common when an array type is used to represent an Oracle Collection, that is, when an `int[]` is used to represent a collection of NUMBERS.

If the `OracleCustomTypeMappingAttribute` is not specified, then custom type mappings must be specified through an XML configuration file, for example, `app.config` for Windows applications or the `web.config` for web applications, and the `machine.config`

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Members](#)
- [OracleCustomTypeMappingAttribute Constructors](#)
- [OracleCustomTypeMappingAttribute Static Methods](#)
- [OracleCustomTypeMappingAttribute Methods](#)

OracleCustomTypeMappingAttribute Members

OracleCustomTypeMappingAttribute members are listed in the following tables.

OracleCustomTypeMappingAttribute Constructors

OracleCustomTypeMappingAttribute constructors are listed in [Table 16-1](#).

Table 16-1 OracleCustomTypeMappingAttribute Constructors

Constructor	Description
OracleCustomTypeMappingAttribute Constructors	Instantiates a new instance of OracleCustomTypeMappingAttribute class

OracleCustomTypeMappingAttribute Static Methods

OracleCustomTypeMappingAttribute static methods are listed in [Table 16-2](#).

Table 16-2 OracleCustomTypeMappingAttribute Static Methods

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

OracleCustomTypeMappingAttribute Properties

OracleCustomTypeMappingAttribute properties are listed in [Table 16-3](#).

Table 16-3 OracleCustomTypeMappingAttribute Properties

Property	Description
UdtTypeName	Specifies the Oracle user-defined type name that the custom class maps to
TypeId	Inherited from System.Attribute

OracleCustomTypeMappingAttribute Methods

OracleCustomTypeMappingAttribute methods are listed in [Table 16-4](#).

Table 16-4 OracleCustomTypeMappingAttribute Methods

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute

Table 16-4 (Cont.) OracleCustomTypeMappingAttribute Methods

Method	Description
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Class](#)

OracleCustomTypeMappingAttribute Constructors

OracleCustomTypeMappingAttribute constructors create new instances of the OracleCustomTypeMappingAttribute class.

Overload List:

- [OracleCustomTypeMappingAttribute\(string\)](#)
This constructor creates and initializes an OracleCustomTypeMappingAttribute using the specified Oracle user-defined type name.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Methods](#)

OracleCustomTypeMappingAttribute(string)

This constructor creates and initializes an OracleCustomTypeMappingAttribute using the specified Oracle user-defined type name.

Declaration

```
// C#  
public OracleCustomTypeMappingAttribute(string udtTypeName)
```

Parameters

- *udtTypeName*
The Oracle user-defined type name that the custom class maps to.

Remarks

The *udtTypeName* parameter is case-sensitive. The *udtTypeName* is specified in the form of *schema_name.type_name*.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleCustomTypeMappingAttribute Static Methods

OracleCustomTypeMappingAttribute static methods are listed in [Table 16-5](#).

Table 16-5 OracleCustomTypeMappingAttribute Static Methods

Method	Description
Equals	Inherited from System.Attribute
GetCustomAttribute	Inherited from System.Attribute
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleCustomTypeMappingAttribute Properties

OracleCustomTypeMappingAttribute properties are listed in [Table 16-6](#).

Table 16-6 OracleCustomTypeMappingAttribute Properties

Property	Description
UdtTypeName	Specifies the Oracle user-defined type name that the custom class maps to
TypeId	Inherited from <code>System.Attribute</code>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

UdtTypeName

This property specifies the Oracle user-defined type name that the custom class maps to.

Declaration

```
// C#  
public string UdtTypeName {get; set;}
```

Property Value

A string that represents an Oracle user-defined type name.

Remarks

`UdtTypeName` is case-sensitive. It is specified in the form of *schema_name.type_name*.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleCustomTypeMappingAttribute Methods

`OracleCustomTypeMappingAttribute` methods are listed in [Table 16-7](#).

Table 16-7 OracleCustomTypeMappingAttribute Methods

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleObjectMappingAttribute Class

The `OracleObjectMappingAttribute` class marks custom class fields or properties with information that ODP.NET uses when a custom type represents an Oracle Object type.

Class Inheritance

```
System.Object
```

```
System.Attribute
```

```
System.OracleObjectMappingAttribute
```

Declaration

```
// C#
[AttributeUsageAttribute(AttributeTargets.Field|AttributeTargets.Property,
AllowMultiple=false, Inherited=true)]
```

```
public sealed class OracleObjectMappingAttribute : Attribute
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Types
.NET Framework	3.5, 4.5, 4.6, 4.7

Remarks

The `OracleObjectMappingAttribute` is specified on members of a custom type that represent an Oracle object type. This attribute must specify the name or zero-based index of the attribute in the Oracle object that the custom class field or property maps to. This also allows the custom type to declare field or property names which differ from the Oracle Object type.

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Members](#)
- [OracleObjectMappingAttribute Constructors](#)
- [OracleObjectMappingAttribute Static Methods](#)
- [OracleObjectMappingAttribute Properties](#)
- [OracleObjectMappingAttribute Methods](#)

OracleObjectMappingAttribute Members

`OracleObjectMappingAttribute` members are listed in the following tables.

OracleObjectMappingAttribute Constructors

`OracleObjectMappingAttribute` constructors are listed in [Table 16-8](#).

Table 16-8 OracleObjectMappingAttribute Constructors

Constructor	Description
OracleObjectMappingAttribute Constructors	Instantiates a new instance of <code>OracleObjectMappingAttribute</code> class (Overloaded)

OracleObjectMappingAttribute Static Methods

`OracleObjectMappingAttribute` static methods are listed in [Table 16-9](#).

Table 16-9 OracleObjectMappingAttribute Static Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Attribute</code>
<code>GetCustomAttribute</code>	Inherited from <code>System.Attribute</code>

Table 16-9 (Cont.) OracleObjectMappingAttribute Static Methods

Method	Description
GetCustomAttributes	Inherited from System.Attribute
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

OracleObjectMappingAttribute Properties

OracleObjectMappingAttribute properties are listed in [Table 16-10](#).

Table 16-10 OracleObjectMappingAttribute Properties

Property	Description
AttributeIndex	Specifies the index of the Oracle Object attribute that must be retrieved
AttributeName	Specifies the name of Oracle Object attribute that must be retrieved
TypeId	Inherited from System.Attribute

OracleObjectMappingAttribute Methods

OracleObjectMappingAttribute methods are listed in [Table 16-11](#).

Table 16-11 OracleObjectMappingAttribute Methods

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)

OracleObjectMappingAttribute Constructors

OracleObjectMappingAttribute constructors create new instances of the OracleObjectMappingAttribute class.

Overload List:

- [OracleObjectMappingAttribute\(string\)](#)
This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute name.
- [OracleObjectMappingAttribute\(int\)](#)
This constructor creates and initializes an OracleObjectMappingAttribute with the specified Oracle Object attribute index.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute(string)

This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute name.

Declaration

```
// C#  
public OracleObjectMappingAttribute(string attrName);
```

Parameters

- *attrName*
The name of the Oracle Object attribute to map to.

Remarks

The *attrName* parameter is case-sensitive.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute(int)

This constructor creates and initializes an `OracleObjectMappingAttribute` object with the specified Oracle Object attribute index.

Declaration

```
// C#
public OracleObjectMappingAttribute(int attrIndex);
```

Parameters

- *attrIndex*
The zero-based index of the Oracle Object attribute to map to.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute Static Methods

`OracleObjectMappingAttribute` static methods are listed in [Table 16-12](#).

Table 16-12 OracleObjectMappingAttribute Static Method

Method	Description
<code>Equals</code>	Inherited from <code>System.Attribute</code>
<code>GetCustomAttribute</code>	Inherited from <code>System.Attribute</code>
<code>GetCustomAttributes</code>	Inherited from <code>System.Attribute</code>
<code>IsDefined</code>	Inherited from <code>System.Attribute</code>
<code>ReferenceEquals</code>	Inherited from <code>System.Attribute</code>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute Properties

OracleObjectMappingAttribute properties are listed in [Table 16-13](#).

Table 16-13 OracleObjectMappingAttribute Properties

Property	Description
AttributeIndex	Specifies the index of the Oracle Object attribute that must be retrieved
AttributeName	Specifies the name of the Oracle Object attribute that must be retrieved
TypeId	Inherited from System.Attribute

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

AttributeIndex

This property specifies the index of the Oracle Object attribute that must be retrieved.

Declaration

```
// C#
public int AttributeIndex {get;}
```

Property Value

The zero-based index of an Oracle Object type attribute.

Remarks

The `AttributeIndex` property specifies the index of the Oracle Object type attribute that the custom class field or property maps to. This allows the custom class to declare fields or property names that differ from the Oracle object.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

AttributeName

This property specifies the name of the Oracle Object attribute that must be retrieved.

Declaration

```
// C#
public string AttributeName {get;}
```

Property Value

The name of an attribute of an Oracle Object type.

Remarks

The `AttributeName` property specifies name of the attribute in the Oracle Object type that the custom class field or property maps to. This allows the custom class to declare field or property names that differ from the Oracle object.

The specified attribute name is case-sensitive.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute Methods

`OracleObjectMappingAttribute` methods are listed in [Table 16-14](#).

Table 16-14 OracleObjectMappingAttribute Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Attribute</code>
<code>GetHashCode</code>	Inherited from <code>System.Attribute</code>
<code>GetType</code>	Inherited from <code>System.Attribute</code>

Table 16-14 (Cont.) OracleObjectMappingAttribute Methods

Method	Description
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleArrayMappingAttribute Class

The `OracleArrayMappingAttribute` class is required to mark a custom class field or property with information that ODP.NET uses when a custom type represents an Oracle Collection type.

Class Inheritance

System.Object

System.Attribute

System.OracleArrayMappingAttribute

Declaration

[AttributeUsageAttribute(AttributeTargets.Field|AttributeTargets.Property, AllowMultiple=false, Inherited=true)]

```
// C#
public sealed class OracleArrayMappingAttribute : Attribute
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Types
.NET Framework	3.5, 4.5, 4.6, 4.7

Remarks

An `OracleArrayMappingAttribute` object must be specified when a custom type represents an Oracle Collection. This attribute is applied only to the custom class member that stores the collection elements.

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleArrayMappingAttribute Members](#)
- [OracleArrayMappingAttribute Constructors](#)
- [OracleArrayMappingAttribute Static Methods](#)
- [OracleArrayMappingAttribute Properties](#)
- [OracleArrayMappingAttribute Methods](#)

OracleArrayMappingAttribute Members

`OracleArrayMappingAttribute` members are listed in the following tables.

OracleArrayMappingAttribute Constructors

`OracleArrayMappingAttribute` constructors are listed in [Table 16-15](#).

Table 16-15 OracleArrayMappingAttribute Constructors

Constructor	Description
OracleArrayMappingAttribute Constructors	Instantiates a new instance of <code>OracleArrayMappingAttribute</code> class (Overloaded)

OracleArrayMappingAttribute Static Methods

`OracleArrayMappingAttribute` static methods are listed in [Table 16-16](#).

Table 16-16 OracleArrayMappingAttribute Static Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Attribute</code>
<code>GetCustomAttribute</code>	Inherited from <code>System.Attribute</code>
<code>GetCustomAttributes</code>	Inherited from <code>System.Attribute</code>

Table 16-16 (Cont.) OracleArrayMappingAttribute Static Methods

Method	Description
IsDefined	Inherited from System.Attribute
ReferenceEquals	Inherited from System.Attribute

OracleArrayMappingAttribute Properties

OracleArrayMappingAttribute properties are listed in [Table 16-17](#).

Table 16-17 OracleArrayMappingAttribute Properties

Property	Description
TypeId	Inherited from System.Attribute

OracleArrayMappingAttribute Methods

OracleArrayMappingAttribute methods are listed in [Table 16-18](#).

Table 16-18 OracleArrayMappingAttribute Methods

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleArrayMappingAttribute Class](#)

OracleArrayMappingAttribute Constructors

OracleArrayMappingAttribute constructors create new instances of the OracleArrayMappingAttribute class.

Overload List:

- [OracleArrayMappingAttribute\(\)](#)

This constructor creates and initializes an OracleArrayMappingAttribute object.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute()

This constructor creates and initializes an `OracleArrayMappingAttribute` object.

Declaration

```
// C#
public OracleArrayMappingAttribute();
```

Remarks

An `OracleArrayMappingAttribute` object must be applied when a custom class represents an Oracle Collection type, to specify the custom class field or property that stores the collection elements.

The `OracleArrayMappingAttribute` can be applied to only one field or property in the custom class.

 See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute Static Methods

`OracleArrayMappingAttribute` static methods are listed in [Table 16-19](#).

Table 16-19 OracleArrayMappingAttribute Static Methods

Method	Description
<code>Equals</code>	Inherited from <code>System.Attribute</code>
<code>GetCustomAttribute</code>	Inherited from <code>System.Attribute</code>
<code>GetCustomAttributes</code>	Inherited from <code>System.Attribute</code>
<code>IsDefined</code>	Inherited from <code>System.Attribute</code>
<code>ReferenceEquals</code>	Inherited from <code>System.Attribute</code>

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute Properties

OracleArrayMappingAttribute properties are listed in [Table 16-20](#).

Table 16-20 OracleArrayMappingAttribute Properties

Property	Description
TypeId	Inherited from System.Attribute

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute Methods

OracleArrayMappingAttribute methods are listed in [Table 16-21](#).

Table 16-21 OracleArrayMappingAttribute Methods

Method	Description
Equals	Inherited from System.Attribute
GetHashCode	Inherited from System.Attribute
GetType	Inherited from System.Attribute
IsDefaultAttribute	Inherited from System.Attribute
Match	Inherited from System.Attribute
ToString	Inherited from System.Attribute

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

IOracleCustomType Interface

IOracleCustomType is an interface for converting between a Custom Type and an Oracle Object or Collection Type.

Declaration

```
// C#
public interface IOracleCustomType
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Types
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomType Members](#)
- [IOracleCustomType Interface Methods](#)

IOracleCustomType Members

IOracleCustomType members are listed in the following tables.

IOracleCustomType Interface Methods

IOracleCustomType interface methods are listed in [Table 16-22](#).

Table 16-22 IOracleCustomType Interface Methods

Interface Method	Description
FromCustomObject	Returns the values that set the Oracle Object attributes
ToCustomObject	Provides the Oracle Object with the attribute values to set on the custom type

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomType Interface](#)

IOracleCustomType Interface Methods

IOracleCustomType Interface methods are listed in [Table 16-23](#).

Table 16-23 IOracleCustomType Interface Methods

Interface Method	Description
FromCustomObject	Returns the values that set the Oracle Object attributes
ToCustomObject	Provides the Oracle Object with the attribute values to set on the custom type

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

FromCustomObject

This interface method creates an Oracle Object or Collection by setting the attribute or element values respectively on the specified Oracle UDT.

Declaration

```
// C#
void FromCustomObject(OracleConnection con, IntPtr pUdt);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
An opaque pointer to the Oracle Object or Collection to be created.

Remarks

The `FromCustomObject` method is used to build an Oracle Object or Collection from a custom object by setting attribute or element values respectively through the `OracleUdt.SetValue` method.

The `OracleUdt.SetValue` method is invoked as follows:

- Oracle Object Type
For a custom type that represents an Oracle Object Type, the `OracleUdt.SetValue` method must be invoked for each non-NULL attribute value that needs to be set.
- Oracle Collection Type
For a custom type that represents an Oracle Collection Type, a single call to `OracleUdt.SetValue` method specifies the collection element values.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

ToCustomObject

This interface initializes a custom object using the specified Oracle UDT.

Declaration

```
// C#  
void ToCustomObject (OracleConnection con, IntPtr pUdt);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
An opaque pointer to the Oracle UDT.

Remarks

The `ToCustomObject` method is used to initialize a custom object from the specified Oracle Object or Collection by retrieving attribute or element values respectively through the `OracleUdt.GetValue` method.

The `OracleUdt.GetValue` method is invoked as follows:

- Oracle Object Type
For a custom type that represents an Oracle Object Type, the `OracleUdt.GetValue` method must be invoked for each attribute value to be retrieved.
- For a custom type that represents an Oracle Collection Type, a single call to `OracleUdt.GetValue` method retrieves the collection element values.

**See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

IOracleCustomTypeFactory Interface

The `IOracleCustomTypeFactory` interface is used by ODP.NET to create custom objects that represent Oracle Objects or Collections.

Declaration

```
// C#
public interface IOracleCustomTypeFactory
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Types
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomTypeFactory Members](#)
- [IOracleCustomTypeFactory Interface Methods](#)

IOracleCustomTypeFactory Members

IOracleCustomTypeFactory members are listed in the following tables.

IOracleCustomTypeFactory Interface Methods

IOracleCustomTypeFactory interface methods are listed in [Table 16-24](#).

Table 16-24 IOracleCustomTypeFactory Interface Methods

Public Method	Description
CreateObject	Returns a new custom object to represent an Oracle Object or Collection

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomTypeFactory Interface](#)

IOracleCustomTypeFactory Interface Methods

IOracleCustomTypeFactory Interface methods are listed in [Table 16-25](#).

Table 16-25 IOracleCustomTypeFactory Interface Methods

Public Method	Description
CreateObject	Returns a new custom object to represent an Oracle Object or Collection

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomTypeFactory Interface](#)
- [IOracleCustomTypeFactory Members](#)

CreateObject

This interface method returns a new custom object to represent an Oracle Object or Collection.

Declaration

```
// C#  
IOracleCustomType CreateObject();
```

Return Value

An `IOracleCustomType` object.

Remarks

The `CreateObject` method is used to create a new instance of a custom object to represent an Oracle Object or Collection.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleCustomTypeFactory Interface](#)
- [IOracleCustomTypeFactory Members](#)

IOracleArrayTypeFactory Interface

The `IOracleArrayTypeFactory` interface is used by ODP.NET to create arrays that represent Oracle Collections.

Declaration

```
// C#  
public interface IOracleArrayTypeFactory
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Types
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleArrayTypeFactory Members](#)
- [IOracleArrayTypeFactory Interface Methods](#)

IOracleArrayTypeFactory Members

IOracleArrayTypeFactory members are listed in the following tables.

IOracleArrayTypeFactory Interface Methods

IOracleArrayTypeFactory interface methods are listed in [Table 16-26](#).

Table 16-26 IOracleArrayTypeFactory Interface Methods

Public Method	Description
CreateArray	Returns a new array of the specified length to store Oracle Collection elements
CreateStatusArray	Returns a newly allocated OracleUdtStatus array of the specified length that will be used to store the null status of the collection elements

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleArrayTypeFactory Interface](#)

IOracleArrayTypeFactory Interface Methods

IOracleArrayTypeFactory Interface methods are listed in [Table 16-27](#).

Table 16-27 IOracleArrayTypeFactory Interface Methods

Public Method	Description
CreateArray	Returns a new array of the specified length to store Oracle Collection elements
CreateStatusArray	Returns a newly allocated <code>OracleUdtStatus</code> array of the specified length that will be used to store the null status of the collection elements



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)

CreateArray

This interface method returns a new array of the specified length to store Oracle Collection elements.

Declaration

```
// C#  
Array CreateArray(int numElems);
```

Parameters

- `numElems`
The number of collection elements to be returned.

Return Value

A `System.Array` object.

Remarks

An Oracle Collection Type may be represented in either of the following ways:

- As an array of the appropriate type. The type must be able to represent a collection element.
- As a Custom Type that contains an array of the appropriate type.

In both cases, the `CreateArray` method creates an array of the specified length to store the collection elements.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)

CreateStatusArray

This method returns a newly allocated `OracleUdtStatus` array of the specified length that will be used to store the null status of the collection elements.

Declaration

```
// C#  
Array CreateStatusArray(int numElems);
```

Parameters

- *numElems*
The number of collection elements to be returned.

Return Value

A multi-dimensional `OracleUdtStatus` array as a `System.Array`.

Remarks

An Oracle Collection Type can be represented in the following ways:

- As an array of the appropriate type. The type must be able to represent a collection element.
- As a Custom Type that contains an array of the appropriate type.

In both cases, the `CreateStatusArray` method creates an `OracleUdtStatus` array of the specified length that stores the null status of the collection elements.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

OracleUdt Class

The `OracleUdt` class defines static methods that are used when converting between Custom Types and Oracle UDTs and vice-versa.

Class Inheritance

`System.Object`

`System.OracleUdt`

Declaration

```
public sealed class OracleUdt
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Types</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Members](#)
- [OracleUDT Static Methods](#)

OracleUdt Members

`OracleUdt` static methods are listed in [Table 16-28](#).

Table 16-28 OracleUdt Static Methods

Static Method	Description
<code>Equals</code>	Inherited from <code>System.Object</code>
GetValue	Gets the attributes or elements from the specified Oracle UDT (Overloaded)
IsDBNull	Indicates whether or not the specified attribute being retrieved is NULL (Overloaded)

Table 16-28 (Cont.) OracleUdt Static Methods

Static Method	Description
SetValue	Sets the attributes or elements on the specified Oracle UDT (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)

OracleUDT Static Methods

OracleUDT methods are listed in [Table 16-29](#).

Table 16-29 OracleUdt Static Methods

Static Method	Description
Equals	Inherited from <code>System.Object</code>
GetValue	Gets the attributes or elements from the specified Oracle UDT (Overloaded)
IsDBNull	Indicates whether or not the specified attribute being retrieved is NULL (Overloaded)
SetValue	Sets the attributes or elements on the specified Oracle UDT (Overloaded)

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)

GetValue

`GetValue` methods get the attributes or elements from the specified Oracle UDT.

Overload List:

- [GetValue\(OracleConnection, IntPtr, string\)](#)

This method gets the attributes or elements from the specified Oracle UDT, using the specified attribute name.

- [GetValue\(OracleConnection, IntPtr, int\)](#)

This method gets the attribute or elements from the specified Oracle UDT, using the specified index.

- [GetValue\(OracleConnection, IntPtr, string, out object\)](#)

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

- [GetValue\(OracleConnection, IntPtr, int, out object\)](#)

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

GetValue(OracleConnection, IntPtr, string)

This method gets the attributes or elements from the specified Oracle UDT, using the specified attribute name.

Declaration

```
public static object GetValue(OracleConnection con, IntPtr pUdt, string attrName);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
A pointer to an Oracle UDT.
- *attrName*
The case-sensitive name of the attribute to be retrieved. Null is specified for retrieving collection elements from a Custom Type that represents an Oracle Collection.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

`ArgumentException` - The specified name is not a valid attribute name.

Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the `con` and `pUdt` parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type

For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.

- Oracle Collection Type

For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of `NULL` attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

GetValue(OracleConnection, IntPtr, int)

This method gets the attribute or elements from the specified Oracle UDT, using the specified index.

Declaration

```
// C#  
public static object GetValue(OracleConnection con, IntPtr pUdt, int attrIndex,);
```

Parameters

- `con`
An `OracleConnection` instance.
- `pUdt`
A pointer to an Oracle UDT.
- `attrIndex`

The zero-based index of the attribute to be retrieved. For retrieving collection elements from a Custom Type that represents an Oracle Collection, zero must be specified.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

`ArgumentOutOfRangeException` - The specified index is not a valid attribute index.

Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the `con` and `pUdt` parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of `NULL` attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

GetValue(OracleConnection, IntPtr, string, out object)

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

Declaration

```
// C#  
public static object GetValue(OracleConnection con, IntPtr pUdt, string attrName,  
    out object statusArray);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrName*
The case-sensitive name of the attribute to be retrieved. Null must specified for retrieving collection elements from a Custom Type that represents an Oracle Collection.
- *statusArray* - The OracleUdtStatus array which returns the null status for the retrieved collection elements.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

ArgumentException - The specified name is not a valid attribute name.

Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of NULL attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

If the collection being returned is not NULL, the output *statusArray* parameter is populated with the null status for each of the collection elements.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

GetValue(OracleConnection, IntPtr, int, out object)

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

Declaration

```
// C#  
public static object GetValue(OracleConnection con, IntPtr pUdt, int attrIndex,  
    out object statusArray);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrIndex*
The zero-based index of the attribute to be retrieved. For retrieving collection elements from a Custom Type that represents an Oracle Collection, 0 is specified.
- *statusArray*
The OracleUdtStatus array which returns the null status for the retrieved collection elements.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

ArgumentOutOfRangeException - The specified index is not a valid attribute index.

Remarks

The *IOracleCustomType.ToCustomObject* method invokes *OracleUdt.GetValue* method passing it the *con* and *pUdt* parameters. The *OracleUdt.GetValue* method returns these types of object:

- Oracle Object Type

For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.

- Oracle Collection Type

For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of `NULL` attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

If the collection being returned is not `NULL`, the output `statusArray` parameter is populated with the null status for each of the collection elements.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

IsDBNull

`IsDBNull` methods indicate whether or not the specified attribute being retrieved is `NULL`.

Overload List:

- [IsDBNull\(OracleConnection, IntPtr, string\)](#)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, `pointer`, and attribute name, is `NULL`.

- [IsDBNull\(OracleConnection, IntPtr, int\)](#)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, `pointer`, and attribute index, is `NULL`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

IsDBNull(OracleConnection, IntPtr, string)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, `pointer`, and attribute name, is `NULL`.

Declaration

```
// C#  
public static bool IsDBNull(OracleConnection con, IntPtr pUdt, string attrName);
```

Parameters

- `con`
An `OracleConnection` instance.
- `pUdt`
A pointer to an Oracle UDT.
- `attrName`
The case-sensitive name of the attribute.

Return Value

True if the specified attribute is `NULL`; otherwise, false.

Exceptions

`ArgumentException` - The specified name is not a valid attribute name.

Remarks

This method is invoked from the `IOracleCustomType.ToCustomObject` method. The `con` and `pUdt` parameter is passed from the `IOracleCustomType.ToCustomObject` method to the `OracleUdt.IsDBNull` method. The `attrName` parameter is case-sensitive.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)

IsDBNull(OracleConnection, IntPtr, int)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, pointer, and attribute index, is `NULL`.

Declaration

```
// C#  
public static bool IsDBNull(OracleConnection con, IntPtr pUdt, int attrIndex);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrIndex*
The zero-based index of the attribute.

Return Value

True if the specified attribute is `NULL`; otherwise, false.

Exceptions

`ArgumentOutOfRangeException` - The specified index is not a valid attribute index

Remarks

This method is invoked from the `IOracleCustomType.ToCustomObject` method. The *con* and *pUdt* parameter is passed from the `IOracleCustomType.ToCustomObject` method to the `OracleUdt.IsDBNull` method.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)

SetValue

SetValue methods set the attributes or elements on the specified Oracle UDT.

Overload List:

- [SetValue\(OracleConnection, IntPtr, string, object\)](#)
This method sets the attribute or elements on the specified Oracle UDT, using the specified attribute name and value.
- [SetValue\(OracleConnection, IntPtr, int, object\)](#)
This method sets the attribute or elements on the specified Oracle UDT, using the specified index and value.
- [SetValue\(OracleConnection, IntPtr, string, object, object\)](#)
This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.
- [SetValue\(OracleConnection, IntPtr, int, object, object\)](#)
This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)

SetValue(OracleConnection, IntPtr, string, object)

This method sets the attribute or elements on the specified Oracle UDT, using the specified attribute name and value.

Declaration

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, string attrName,  
    object value);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrName*
The name of the attribute to be set. Specify null for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.

Exceptions

ArgumentException - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

SetValue(OracleConnection, IntPtr, int, object)

This method sets the attribute or elements on the specified Oracle UDT, using the specified index and value.

Declaration

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, int attrIndex, object value);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrIndex*
The index of the attribute to be set. Specify 0 for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.

Exceptions

`ArgumentException` - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

SetValue(OracleConnection, IntPtr, string, object, object)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

Declaration

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, string attrName,  
    object value, object statusArray);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrName*
The name of the attribute to be set. Specify null for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.
- *statusArray*
The null status for the collection elements.

Exceptions

ArgumentException - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.

- Oracle Collection Type

For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

SetValue(OracleConnection, IntPtr, int, object, object)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

Declaration

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, int attrIndex,  
    object value, object statusArray);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrIndex*
The index of the attribute to be set. Specify 0 for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.
- *statusArray*
The null status for the collection elements.

Exceptions

`ArgumentException` - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type

For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.

- Oracle Collection Type

For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

OracleRef Class

An `OracleRef` instance represents an Oracle REF, which references a persistent, standalone, referenceable object that resides in the database. The `OracleRef` object provides methods to insert, update, and delete the Oracle REF.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`Oracle.DataAccess.Types.OracleRef`

Declaration

```
// C#
public sealed class OracleRef : MarshalByRefObject, ICloneable, IDisposable,
    INullable
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Types</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

If two or more `OracleRef` objects that refer to the same Oracle object in the database are retrieved through the same `OracleConnection`, then their operations on the referenced object must be synchronized.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Members](#)
- [OracleRef Constructors](#)
- [OracleRef Static Methods](#)
- [OracleRef Instance Properties](#)
- [Oracle Ref Instance Methods](#)

OracleRef Members

`OracleRef` members are listed in the following tables.

OracleRef Constructors

`OracleRef` constructors are listed in [Table 16-30](#).

Table 16-30 OracleRef Constructors

Constructor	Description
OracleRef Constructors	Instantiates a new instance of <code>OracleRef</code> class (Overloaded)

OracleRef Static Fields

`OracleRef` static methods are listed in [Table 16-31](#)

Table 16-31 OracleRef Static Fields

Static Field	Description
Null	Represents a null value that can be assigned to an <code>OracleRef</code> instance

OracleRef Static Methods

`OracleRef` static methods are listed in [Table 16-32](#).

Table 16-32 OracleRef Static Methods

Method	Description
Equals	Inherited from System.Object (Overloaded)

OracleRef Instance Properties

OracleRef instance properties are listed in [Table 16-33](#).

Table 16-33 OracleRef Instance Properties

Property	Description
Connection	References the connection used by the OracleRef
HasChanges	References the connection used by the OracleRef
IsLocked	Indicates whether or not the REF is locked
IsNull	Indicates whether or not the Oracle REF is NULL
ObjectTableName	Returns the fully qualified object table name that is associated with the REF
Value	Returns a .NET representation of this Oracle REF

OracleRef Instance Methods

OracleRef instance methods are listed in [Table 16-34](#).

Table 16-34 OracleRef Instance Methods

Method	Description
Clone	Clones the REF
Delete	Deletes the referenced object from the database
Dispose	Releases resources allocated for the OracleRef instance
Equals	Inherited from System.Object
Flush	Flushes changes made on the REF object to the database
GetCustomObject	Returns the object that the specified REF references as a custom type (Overloaded)
GetCustomObjectForUpdate	Returns the object that the specified REF references as a custom type (Overloaded)
GetHashCode	Inherited from System.Object
GetType	Inherited from System.Object
IsEqual	Compares two OracleREF objects
Lock	Locks the REF in the database
ToString	Inherited from System.Object
Update	Updates the object referenced by the specified REF in the database using the specified custom object

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)

OracleRef Constructors

OracleRef constructors instantiate new instances of OracleRef class.

Overload List:

- [OracleRef\(OracleConnection, string\)](#)

This constructor creates an instance of the OracleRef class with a connection and a HEX string that represents an REF instance in the database.
- [OracleRef\(OracleConnection, string, string\)](#)

This constructor creates an instance of the OracleRef class using the specified OracleConnection object, user-defined type name, and an object table name

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef(OracleConnection, string)

This constructor creates an instance of the OracleRef class with a connection and a HEX string that represents an REF instance in the database.

Declaration

```
// C#  
public OracleRef(OracleConnection con, string hexStr);
```

Parameters

- *con*

An OracleConnection instance.
- *hexStr*

A HEX string that represents an REF instance in the database.

Exceptions

`ArgumentException` - The HEX string does not represent a valid REF in the database.

`ArgumentNullException` - The connection or HEX string is null.

`InvalidOperationException` - The `OracleConnection` object is not open.

Remarks

When an `OracleRef` instance is created, it is referenced to a specific table in the database.

The connection must be opened explicitly by the application. `OracleRef` does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef(OracleConnection, string, string)

This constructor creates an instance of the `OracleRef` class using the specified `OracleConnection` object, user-defined type name, and an object table name.

Declaration

```
// C#  
public OracleRef(OracleConnection con, string udtTypeName, string objTabName);
```

Parameters

- `con`
An `OracleConnection` instance.
- `udtTypeName`
A user-defined type name.
- `objTabName`
An object table name.

Exceptions

`ArgumentException` - The object type name or the object table name is not valid.

`ArgumentNullException` - The object type name or the table name is null.

`InvalidOperationException` - The `OracleConnection` object is not open.

Remarks

When an `OracleRef` instance is created, this `OracleRef` instance is associated with the specific table in the database. In other words, it represents a persistent REF.

This constructor creates a reference to the object table. However, it does not cause any entries to be made in database tables until the object is flushed to the database, that is, until the `OracleRef.Flush` or the `OracleConnection.FlushCache` method is called on the `OracleRef` Connection. Therefore, any operation that attempts to operate on the database copy of the object before flushing the object, such as, lock the object or fetch the latest copy of the object from the database, results in an `OracleException`.

The connection must be opened explicitly by the application. `OracleRef` does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["FlushCache"](#)

OracleRef Static Fields

`OracleRef` static fields are listed in [Table 16-35](#).

Table 16-35 OracleRef Static Fields

Static Field	Description
Null	Represents a null value that can be assigned to an <code>OracleRef</code> instance

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Null

This static field represents a null value that can be assigned to an `OracleRef` instance.

Declaration

```
// C#
public static readonly OracleRef Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef Static Methods

OracleRef static methods are listed in [Table 16-36](#).

Table 16-36 OracleRef Static Methods

Method	Description
Equals	Inherited from <code>System.Object</code> (Overloaded)

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef Instance Properties

OracleRef instance properties are listed in [Table 16-37](#).

Table 16-37 OracleRef Instance Properties

Property	Description
Connection	References the connection used by the OracleRef
HasChanges	References the connection used by the OracleRef
IsLocked	Indicates whether or not the REF is locked
IsNull	Indicates whether or not the Oracle REF is NULL
ObjectTableName	Returns the fully qualified object table name that is associated with the REF

Table 16-37 (Cont.) OracleRef Instance Properties

Property	Description
Value	Returns a .NET representation of this Oracle REF

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Connection

This instance property references the connection used by the `OracleRef`.

Declaration

```
// C#  
public OracleConnection Connection{get;}
```

Property Value

An `OracleConnection` object associated with the REF.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

Once the `Dispose` method is invoked, this property is set to `null`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

HasChanges

This instance property indicates whether or not the object referenced by the Oracle REF in the object cache has any changes that can be flushed to the database.

Declaration

```
// C#  
public bool HasChanges {get;}
```

Property Value

Returns `true` if the object referenced by the Oracle `REF` in the object cache has any changes that can be flushed to the database; otherwise, returns `false`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property returns `true` if a copy of the referenced object in the object cache is updated or deleted.

If there is no copy of the referenced object in the object cache, the latest copy of the referenced object in the database is cached in the object cache and `false` is returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

IsLocked

This instance property indicates whether or not the `REF` is locked.

Declaration

```
// C#  
public bool IsLocked {get;}
```

Property Value

Returns `true` if the `REF` is locked; otherwise returns `false`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

IsNull

This instance property indicates whether or not the Oracle REF is NULL.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns true if the REF is NULL; otherwise, returns false.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the Oracle REF is NULL, this property returns true. Otherwise, it returns false.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

ObjectTableName

This instance property returns the fully-qualified object table name that is associated with the REF.

Declaration

```
// C#  
public string ObjectTableName{get;}
```

Property Value

A fully-qualified object table name that is associated with the REF.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The object table name is in the form *schema_Name.Table_Name*.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Value

This instance property returns a .NET representation of this Oracle REF.

Declaration

```
// C#  
public string Value{get;}
```

Property Value

A .NET representation of the Oracle REF.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property returns a HEX string that represents the REF.

The returned string can be used to create a new `OracleRef` instance by using the `OracleRef(OracleConnection, string)` constructor.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleRef\(OracleConnection, string\)"](#)

Oracle Ref Instance Methods

OracleRef instance methods are listed in [Table 16-38](#).

Table 16-38 OracleRef Instance Methods

Method	Description
Clone	Clones the REF
Delete	Deletes the referenced object from the database
Dispose	Releases resources allocated for the OracleRef instance
Equals	Inherited from <code>System.Object</code>
Flush	Flushes changes made on the REF object to the database
GetCustomObject	Returns the object that the specified REF references as a custom type (Overloaded)
GetCustomObjectForUpdate	Returns the object that the specified REF references as a custom type (Overloaded)
GetHashCode	Inherited from <code>System.Object</code>
GetType	Inherited from <code>System.Object</code>
IsEqual	Compares two OracleREF objects
Lock	Locks the REF in the database
ToString	Inherited from <code>System.Object</code>
Update	Updates the object referenced by the specified REF in the database using the specified custom object

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Clone

This instance method clones the REF.

Declaration

```
// C#  
public OracleRef Clone();
```

Return Value

A clone of the current instance.

Implements

ICloneable

Exceptions

InvalidOperationException - The associated connection is not open.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Delete

This method deletes the referenced object from the database.

Declaration

```
// C#  
public void Delete(bool bFlush);
```

Parameters

- *bFlush*
A `bool` that specifies whether or not the `REF` is flushed immediately.

Remarks

This method marks the specified `REF` for deletion.

Depending on whether the value of *bFlush* is set to `true` or `false`, the following occurs:

- `True`
The object referenced by the specified `REF` is deleted immediately from the database.

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.
- `False`
The object referenced by the `REF` is not deleted immediately from the database, but only when a subsequent `Flush` method is invoked for the specified `REF` or the `FlushCache` method is invoked on the `OracleRef` or the `FlushCache` method is invoked on the `OracleRef` connection.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)
- [OracleConnection "FlushCache"](#)

Dispose

This instance method releases resources allocated for the `OracleRef` instance.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`

Remarks

The object cannot be reused after it is disposed. Although some properties can still be accessed, their values may not be up-to-date.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Flush

This instance method flushes changes made on the `REF` object to the database, such as updates or deletes.

Declaration

```
// C#  
public void Flush();
```

Exceptions

`InvalidOperationException` - The associated connection is not open.

Remarks

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObject

`GetCustomObject` methods return the object that the specified REF references as a custom type.

Overload List

- [GetCustomObject\(OracleUdtFetchOption\)](#)
This method returns the object that the specified REF references as a custom type using the specified fetch option.
- [GetCustomObject\(OracleUdtFetchOption, int\)](#)
This method returns the object that the specified REF references as a custom type using the specified fetch option and depth level.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObject(OracleUdtFetchOption)

This method returns the object that the specified REF references, as a custom type, using the specified fetch option.

Declaration

```
// C#  
public object GetCustomObject(OracleUdtFetchOption fetchOption);
```

Parameters

- *fetchOption*
An `OracleUdtFetchOption` value.

Return Value

A custom object that represents the object that the specified `REF` references.

Exceptions

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for the type of the referenced object.

Remarks

This method returns a custom type determined by the UDT mappings on the specified connection.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned according to the specified option:

- `OracleUdtFetchOption.Cache` option
If this option is specified, and there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
- `OracleUdtFetchOption.Server` option
If this option is specified, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.
- `OracleUdtFetchOption.TransactionCache` option
If this option is specified, and a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.

Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the `OracleRef.HasChanges` property returns `true`, then the `Recent` option returns the cached copy of the referenced object. Outside of a transaction, the `Recent` option behaves like the `Any` option.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

GetCustomObject(OracleUdtFetchOption, int)

This method returns the object that the specified `REF` references, as a custom type, using the specified fetch option and depth level.

Declaration

```
// C#  
public object GetCustomObject(OracleUdtFetchOption fetchOption, int depthLevel);
```

Parameters

- *fetchOption*
An `OracleUdtFetchOption` value.
- *depthLevel*
The number of levels to be fetched for nested `REF` attributes.

Return Value

A custom object that represents the object that the specified `REF` references.

Exceptions

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for the type of the referenced object.

Remarks

This method returns a custom type determined by the UDT mappings on the specified connection.

If the object that the `REF` references contains nested `REF` attributes, the *depthLevel* can be specified to optimize the subsequent object retrieval. The value of *depthLevel* determines the number of levels that are optimized.

For example, if the *depthLevel* is specified as two, the optimization is applied to all top-level nested `REF` attributes in the object being fetched and also to all nested `REF` attributes within the objects referenced by the top-level nested `REF` attributes.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned according to the specified option:

- `OracleUdtFetchOption.Cache` option
If this option is specified, and there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
- `OracleUdtFetchOption.Server` option
If this option is specified, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.
- `OracleUdtFetchOption.TransactionCache` option
If this option is specified, and a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.

Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the `OracleRef.HasChanges` property returns `true`, then the `Recent` option returns the cached copy of the referenced object. Outside of a transaction, the `Recent` option behaves like the `Any` option.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleUdtFetchOption Enumeration"](#)

GetCustomObjectForUpdate

`GetCustomObjectForUpdate` methods return the object that the specified REF references as a custom type.

- [GetCustomObjectForUpdate\(bool\)](#)
This method locks the specified REF in the database and returns the object that the specified REF references as a custom type using the specified wait option.
- [GetCustomObjectForUpdate\(bool, int\)](#)
This method locks the specified REF in the database and returns the object that the specified REF references as a custom type using the specified wait option and depth level.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObjectForUpdate(bool)

This method locks the specified REF in the database and returns the object that the specified REF references, as a custom type, using the specified wait option.

Declaration

```
// C#  
public object GetCustomObjectForUpdate(bool bWait);
```

Parameters

- *bWait*

Specifies if the REF is to be locked with the no-wait option. If wait is set to true, this method invocation does not return until the REF is locked.

Return Value

A custom object that represents the object that the specified REF references.

Exceptions

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for type of the referenced object.

`OracleException` - *bWait* is set to false, and the lock cannot be acquired.

Remarks

This method returns the latest copy of the referenced object, as a custom type, determined by the custom types registered on the `OracleRef` connection.

To be able to release the lock on the REF appropriately after flushing the REF using the `Flush` method on the `OracleRef` or `FlushCache` method on the `OracleConnection`, the application must commit or rollback the transaction. Therefore, it is required that, before invoking this method, a transaction is explicitly started by executing the `BeginTransaction` method on the `OracleConnection` object.

This method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the associated row object exclusively. Then a call to the `Flush` method on the `OracleRef` or `FlushCache` method on the `OracleConnection` flushes the changes to the database.

If true is passed, this method blocks until the lock can be acquired. If false is passed, this method immediately returns. If the lock cannot be acquired, an `OracleException` is thrown.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObjectForUpdate(bool, int)

This method locks the specified REF in the database and returns the object that the specified REF references, as a custom type, using the specified wait option and depth level

Declaration

```
public object GetCustomObjectForUpdate(bool bWait, int depthlevel);
```

Parameters

- *bWait*
A boolean value that specifies if the REF is to be locked with the no-wait option. If wait is set to true, this method invocation does not return until the REF is locked.
- *depthLevel*
The number of levels to be fetched for nested REF attributes.

Return Value

A custom object that represents the object that the specified REF references.

Exceptions

InvalidOperationException - The specified connection is not open, or a valid custom type has not been registered for type of the referenced object.

OracleException - *bWait* is set to false, and the lock cannot be acquired.

Remarks

This method returns the latest copy of the referenced object, as a custom type, determined by the custom types registered on the *OracleRef* connection.

To be able to release the lock on the REF appropriately after flushing the REF using the *Flush* method on the *OracleRef* or *FlushCache* method on the *OracleConnection*, the application must commit or rollback the transaction. Therefore, it is required that, before invoking this method, a transaction is explicitly started by executing the *BeginTransaction* method on the *OracleConnection* object.

This method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the associated row object exclusively. Then a call to the `Flush` method on the `OracleRef` or `FlushCache` method on the `OracleConnection` flushes the changes to the database.

If `true` is passed, this method blocks until the lock can be acquired. If `false` is passed, this method immediately returns. If the lock cannot be acquired, an `OracleException` is thrown.

If the object that the REF references contains nested REF attributes, the `depthLevel` can be specified to optimize the subsequent object retrieval. The value of `depthLevel` determines the number of levels that are optimized.

For example, if the `depthLevel` is specified as 2, the optimization is applied to all top-level nested REF attributes in the object being fetched and also to all nested REF attributes within the objects referenced by the top-level nested REF attributes.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

IsEqual

This instance method compares two `OracleRef` objects.

Declaration

```
// C#  
public bool IsEqual(OracleRef oraRef);
```

Parameters

- `oraRef`
The provided `OracleRef` object.

Return Value

`bool`

Remarks

This instance method returns `true` if the `OracleRef` instance and the `OracleRef` parameter both reference the same object. Otherwise, it returns `false`.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Lock

This instance method locks the REF in the database.

Declaration

```
// C#  
public bool Lock(bool bWait);
```

Parameters

- *bWait*
Specifies if the lock is set to the no-wait option. If *bWait* is set to `true`, the method invocation does not return until the REF is locked.

Return Value

A boolean value that indicates whether or not the lock has been acquired.

Exceptions

`InvalidOperationException` - The associated connection is not open.

`ObjectDisposedException` - The object is already disposed.

Remarks

In order for the application to release the lock on the REF appropriately after the `Flush` invocation on the `OracleRef` or `FlushCache` methods, the application must commit or rollback the transaction. Therefore, it is required that, before invoking a lock on an `OracleRef` object, a transaction is explicitly started by executing the `BeginTransaction` method on the `OracleConnection` object.

This instance method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the attribute values of the associated row object exclusively. Then a call to the `Flush` instance method on the `OracleRef` or `FlushCache` method on the `OracleConnection` flushes the changes to the database.

If `true` is passed, this method blocks, that is, does not return, until the lock is acquired. Consequently, the return value is always `true`.

If `false` is passed, this method immediately returns. The return value indicates `true` if the lock is acquired, and `false` if it is not.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Update

This method updates the object referenced by the specified `REF` in the database using the specified custom object.

Declaration

```
// C#  
public void Update(object customObject, bool bFlush);
```

Parameters

- *customObject*
The custom object used to update the referenced object.
- *bFlush*
A boolean that specifies if the changes must be flushed immediately. If *bFlush* is set to true, this method invocation flushes the changes immediately.

Exceptions

`InvalidOperationException` - The specified connection is not open or the custom object does not map to the type of referenced object.

Remarks

This method marks the specified `REF` for update. Depending on whether the value of *bFlush* is set to true or false, the following occurs:

- True
The object referenced by the specified `REF` is updated immediately in the database.
Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.
- False
The object referenced by the `REF` is not updated immediately in the database, but only when a subsequent `Flush` method is invoked for the specified `REF` or the `FlushCache` method is invoked for the specified connection.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.



See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleUdtFetchOption Enumeration

`OracleUdtFetchOption` enumeration values specify how to retrieve a copy of the referenceable object.

[Table 16-39](#) lists all the `OracleUdtFetchOption` enumeration values with a description of each enumerated value.

Table 16-39 OracleUdtFetchOption Enumeration Values

Member Name	Description
Cache	If there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
Server	The latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.
TransactionCache	If a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one. Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the <code>OracleRef.HasChanges</code> property returns <code>true</code> , then the <code>Recent</code> option returns the cached copy of the referenced object. Outside of a transaction, the <code>Recent</code> option behaves like the <code>Any</code> option.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleUdtStatus Enumeration

OracleUdtStatus enumeration values specify the status of an object attribute or collection element. An object attribute or a collection element can be a valid value or a null value.

[Table 16-40](#) lists all the OracleUdtStatus enumeration values with a description of each enumerated value:

Table 16-40 OracleUdtStatus Enumeration Values

Member Name	Description
Null	Indicates that an object attribute or collection element is NULL.
NotNull	Indicates that a non-NULL value exists for the object attribute or collection element.

 **See Also:**

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

17

Oracle Data Provider for .NET Bulk Copy Classes

This chapter describes Oracle Data Provider for .NET support for Bulk Copy operations.

Note:

Oracle Data Provider for .NET bulk copy operations do not support loading of UDT type columns.

This chapter includes the following topics:

- [OracleBulkCopy Class](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyOptions Enumeration](#)
- [OracleRowsCopiedEventHandler Delegate](#)
- [OracleRowsCopiedEventArgs Class](#)

OracleBulkCopy Class

An `OracleBulkCopy` object efficiently bulk loads or copies data into an Oracle table from another data source.

Class Inheritance

`System.Object`

`System.OracleBulkCopy`

Declaration

```
// C#  
public sealed class OracleBulkCopy : IDisposable
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client

Provider	ODP.NET, Unmanaged Driver
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The `OracleBulkCopy` class can be used to write data to Oracle database tables only. However, the data source is not limited to Oracle databases; any data source can be used, as long as the data can be loaded to a `DataTable` instance or read with an `IDataReader` instance.

Bulk copy of string data to destination number column is currently not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Members](#)
- [OracleBulkCopy Constructors](#)
- [OracleBulkCopy Properties](#)
- [OracleBulkCopy Public Methods](#)
- [OracleBulkCopy Events](#)

OracleBulkCopy Members

`OracleBulkCopy` members are listed in the following tables.

OracleBulkCopy Constructors

`OracleBulkCopy` constructors are listed in [Table 17-1](#).

Table 17-1 OracleBulkCopy Constructors

Constructor	Description
OracleBulkCopy Constructors	<code>OracleBulkCopy</code> constructors create new instances of the <code>OracleBulkCopy</code> class

OracleBulkCopy Properties

`OracleBulkCopy` properties are listed in [Table 17-2](#).

Table 17-2 OracleBulkCopy Properties

Property	Description
BatchSize	Specifies the number of rows to be sent as a batch to the database
BulkCopyOptions	Specifies the <code>OracleBulkCopyOptions</code> enumeration value that determines the behavior of the bulk copy operation
BulkCopyTimeout	Specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted
ColumnMappings	Specifies the column mappings between the data source and destination table
Connection	Specifies the <code>OracleConnection</code> object that the Oracle database uses to perform the bulk copy operation
DestinationPartitionName	Specifies the database partition that the data is loaded into
DestinationTableName	Specifies the database table that the data is loaded in
NotifyAfter	Defines the number of rows to be processed before a notification event is generated

OracleBulkCopy Public Methods

`OracleBulkCopy` public methods are listed in [Table 17-3](#).

Table 17-3 OracleBulkCopy Public Methods

Method	Description
Close	Closes the <code>OracleBulkCopy</code> instance
Dispose	Releases any resources or memory allocated by the object
WriteToServer	Copies rows to a destination table

OracleBulkCopy Events

`OracleBulkCopy` events are listed in [Table 17-4](#).

Table 17-4 OracleBulkCopy Events

Event	Description
OracleRowsCopied	Triggered every time the number of rows specified by the <code>OracleBulkCopy.NotifyAfter</code> property has been processed

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)

OracleBulkCopy Constructors

OracleBulkCopy constructors create new instances of the OracleBulkCopy class.

Overload List:

- [OracleBulkCopy\(OracleConnection\)](#)
This constructor instantiates a new instance of OracleBulkCopy class using the specified connection and default value for OracleBulkCopyOptions.
- [OracleBulkCopy\(string\)](#)
This constructor instantiates a new instance of OracleBulkCopy based on the supplied *connectionString* and default value for OracleBulkCopyOptions.
- [OracleBulkCopy\(OracleConnection, OracleBulkCopyOptions\)](#)
This constructor instantiates a new instance of OracleBulkCopy using the specified connection object and OracleBulkCopyOptions value.
- [OracleBulkCopy\(string, OracleBulkCopyOptions\)](#)
This constructor instantiates a new instance of OracleConnection based on the supplied *connectionString* and OracleBulkCopyOptions value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleBulkCopy(OracleConnection)

This constructor instantiates a new instance of OracleBulkCopy class using the specified connection and default OracleBulkCopyOptions enumeration values.

Declaration

```
// C#  
public OracleBulkCopy(OracleConnection connection);
```

Parameters

- *connection*
The open instance of OracleConnection that performs the bulk copy operation.

Exceptions

ArgumentNullException - The connection parameter is null.

InvalidOperationException - The connection is not in the open state.

Remarks

The connection object passed to this constructor must be open. It remains open after the `OracleBulkCopy` instance is closed.

This constructor uses the default enumeration value `OracleBulkCopyOptions.Default`.

The `Connection` property is set to the supplied connection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#)

OracleBulkCopy(string)

This constructor instantiates a new instance of the `OracleBulkCopy` class by first creating an `OracleConnection` object based on the supplied `connectionString`, then initializing the new `OracleBulkCopy` object with the `OracleConnection` object and `OracleBulkCopyOptions` default value.

Declaration

```
// C#  
public OracleBulkCopy(string connectionString);
```

Parameters

- `connectionString`

The connection information used to connect to the Oracle database and perform the bulk copy operation.

Exception

`ArgumentNullException` - The `connectionString` parameter is null.

`ArgumentException` - The `connectionString` parameter is empty.

Remarks

The `WriteToServer` method opens the connection, if it is not already opened. The connection is automatically closed when the `OracleBulkCopy` instance is closed.

This constructor uses the default enumeration value `OracleBulkCopyOptions.Default`.

The `Connection` property is set to the `OracleConnection` object initialized using the supplied `connectionString`.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#)

OracleBulkCopy(OracleConnection, OracleBulkCopyOptions)

This constructor instantiates a new instance of `OracleBulkCopy` using the specified connection object and `OracleBulkCopyOptions` value.

Declaration

```
// C#  
public OracleBulkCopy(OracleConnection connection, OracleBulkCopyOptions  
    copyOptions);
```

Parameters

- *connection*
The open instance of an `OracleConnection` object that performs the bulk copy operation.
- *copyOptions*
The combination of `OracleBulkCopyOptions` enumeration values that determine the behavior of the `OracleBulkCopy` object.

Exceptions

`ArgumentNullException` - The *connection* parameter is null.

`InvalidOperationException` - The connection is not in the open state.

Remarks

The connection passed to this constructor must be open. It remains open after the `OracleBulkCopy` instance is closed.

The `Connection` property is set to the supplied connection.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#)

OracleBulkCopy(string, OracleBulkCopyOptions)

This constructor instantiates a new instance of the `OracleBulkCopy` class by first creating an `OracleConnection` object based on the supplied `connectionString`, then initializing the new `OracleBulkCopy` object with the `OracleConnection` object and the supplied `OracleBulkCopyOptions` enumeration values.

Declaration

```
// C#  
public OracleBulkCopy(string connectionString, OracleBulkCopyOptions copyOptions);
```

Parameters

- `connectionString`
The connection information used to connect to the Oracle database to perform the bulk copy operation.
- `copyOptions`
The combination of `OracleBulkCopyOptions` enumeration values that determine the behavior of the bulk copy operation.

Exceptions

`ArgumentNullException` - The `connectionString` is null.

`ArgumentException` - The `connectionString` parameter is empty.

Remarks

The constructor uses the new instance of the `OracleConnection` class to initialize a new instance of the `OracleBulkCopy` class. The `OracleBulkCopy` instance behaves according to options supplied in the `copyOptions` parameter.

The connection is automatically closed when the `OracleBulkCopy` instance is closed.

The `Connection` property is set to an `OracleConnection` object initialized using the supplied `connectionString`.

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#)

OracleBulkCopy Properties

OracleBulkCopy properties are listed in [Table 17-5](#).

Table 17-5 OracleBulkCopy Properties

Property	Description
BatchSize	Specifies the number of rows to be sent as a batch to the database
BulkCopyOptions	Specifies the <code>OracleBulkCopyOptions</code> enumeration value that determines the behavior of the bulk copy operation
BulkCopyTimeout	Specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted
ColumnMappings	Specifies the column mappings between the data source and destination table
Connection	Specifies the <code>OracleConnection</code> object that the Oracle database uses to perform the bulk copy operation
DestinationPartitionName	Specifies the database partition that the data is loaded into
DestinationTableName	Specifies the database table that the data is loaded in
NotifyAfter	Defines the number of rows to be processed before a notification event is generated

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

BatchSize

This property specifies the number of rows to be sent as a batch to the database.

Declaration

```
// C#  
public int BatchSize {get; set;}
```

Property Value

An integer value for the number of rows to be sent to the database as a batch.

Exceptions

`ArgumentOutOfRangeException` - The batch size is less than zero.

Remarks

The default value is zero, indicating that the rows are not sent to the database in batches. The entire set of rows are sent in one single batch.

A large batch size reduces database round trips, but it can also consume large amounts of client side memory. Excessive memory consumption slows down overall machine performance and leads to errors if the process runs out of accessible memory. It is recommended that client side memory is not consumed in excess. This can be done by reducing the batch size.

A batch is complete when `BatchSize` number of rows have been processed or there are no more rows to send to the database.

- If `BatchSize > 0` and the `UseInternalTransaction` bulk copy option is specified, each batch of the bulk copy operation occurs within a transaction. If the connection used to perform the bulk copy operation is already part of a transaction, an `InvalidOperationException` exception is raised.
- If `BatchSize > 0` and the `UseInternalTransaction` option is not specified, rows are sent to the database in batches of size `BatchSize`, but no transaction-related action is taken.

The `BatchSize` property can be set at any time. If a bulk copy is already in progress, the current batch size is determined by the previous batch size. Subsequent batches use the new batch size.

If the `BatchSize` property is initially zero and changes while a `WriteToServer` operation is in progress, that operation loads the data as a single batch. Any subsequent `WriteToServer` operations on the same `OracleBulkCopy` instance use the new `BatchSize`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#)

BulkCopyOptions

This property specifies the `OracleBulkCopyOptions` enumeration value that determines the behavior of the bulk copy option.

Declaration

```
// C#  
public OracleBulkCopyOptions BulkCopyOptions {get; set;}
```

Property Value

The `OracleBulkCopyOptions` enumeration object that defines the behavior of the bulk copy operation.

Exceptions

`ArgumentNullException` - The bulk copy options set is null.

Remarks

The default value of this property is `OracleBulkCopyOptions.Default` value. This property can be used to change the bulk copy options between the batches of a bulk copy operation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#)

BulkCopyTimeout

This property specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted.

Declaration

```
// C#  
public int BulkCopyTimeout {get; set;}
```

Property Value

An integer value for the number of seconds after which the bulk copy operation times out.

Exceptions

`ArgumentOutOfRangeException` - The timeout value is set to less than zero.

Remarks

The default value is 30 seconds.

If `BatchSize>0`, rows that were sent to the database in the previous batches remain committed. The rows that are processed in the current batch are not sent to the database. If `BatchSize=0`, no rows are sent to the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

ColumnMappings

This property specifies the column mappings between the data source and destination table.

Declaration

```
// C#  
public OracleBulkCopyColumnMappingCollection ColumnMappings {get;}
```

Property Value

The `OracleBulkCopyColumnMappingCollection` object that defines the column mapping between the source and destination table.

Remarks

The `ColumnMappings` collection is unnecessary if the data source and the destination table have the same number of columns, and the ordinal position of each source column matches the ordinal position of the corresponding destination column. However, if the column counts differ, or the ordinal positions are not consistent, the `ColumnMappings` collection must be used to ensure that data is copied into the correct columns.

During the execution of a bulk copy operation, this collection can be accessed, but it cannot be changed.

By default, this property specifies an empty collection of column mappings.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

Connection

This property specifies the `OracleConnection` object that the Oracle database uses to perform the bulk copy operation.

Declaration

```
// C#  
public OracleConnection Connection {get; }
```

Property Value

The `OracleConnection` object used for the bulk copy operations.

Remarks

This property gets the connection constructed by the `OracleBulkCopy`, if the `OracleBulkCopy` object is initialized using a connection string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

DestinationPartitionName

This property specifies the database partition that the data is loaded into.

Declaration

```
// C#  
public string DestinationPartitionName {get; set;}
```

Property Value

A string value that identifies the destination partition name.

Remarks

If `DestinationPartitionName` is modified while a `WriteToServer` operation is running, the change does not affect the current operation. The new `DestinationPartitionName` value is used the next time a `WriteToServer` method is called.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

DestinationTableName

This property specifies the database table that the data is loaded into.

Declaration

```
// C#  
public string DestinationTableName {get; set;}
```

Property Value

A string value that identifies the destination table name.

Exceptions

`ArgumentNullException` - The destination table name set is null.

`ArgumentException` - The destination table name is empty.

Remarks

If `DestinationTableName` is modified while a `WriteToServer` operation is running, the change does not affect the current operation. The new `DestinationTableName` value is used the next time a `WriteToServer` method is called.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

NotifyAfter

This property defines the number of rows to be processed before a notification event is generated.

Declaration

```
// C#  
public int NotifyAfter {get; set;}
```

Property Value

An integer value that specifies the number of rows to be processed before the notification event is raised.

Exceptions

`ArgumentOutOfRangeException` - The property value is set to a number less than zero.

Remarks

The default value for this property is zero, to specify that no notifications events are to be generated.

This property can be retrieved in user interface components to display the progress of a bulk copy operation. The `NotifyAfter` property can be set at anytime, even during a bulk copy operation. The changes take effect for the next notification and any subsequent operations on the same instance.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleBulkCopy Public Methods

`OracleBulkCopy` methods are listed in [Table 17-6](#).

Table 17-6 OracleBulkCopy Public Methods

Method	Description
Close	Closes the <code>OracleBulkCopy</code> instance
Dispose	Releases any resources or memory allocated by the object
WriteToServer	Copies rows to a destination table

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

Close

This method closes the `OracleBulkCopy` instance.

Declaration

```
// C#  
public void Close();
```

Exceptions

`InvalidOperationException` - The `Close` method was called from a `OracleRowsCopied` event.

Remarks

After the `Close` method is called on a `OracleBulkCopy` object, no other operation can succeed. Calls to the `WriteToServer` method throw an `InvalidOperationException`. The `Close` method closes the connection if the connection was opened by the `OracleBulkCopy` object, that is, if the `OracleBulkCopy` object was created by a constructor that takes a connection string.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`

Remarks

After the `Dispose` method is called on the `OracleBulkCopy` object, no other operation can succeed. The connection is closed if the connection was opened by the `OracleBulkCopy` object, that is, if a constructor that takes a connection string created the `OracleBulkCopy` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer

`WriteToServer` copies rows to a destination table.

Overload List:

- [WriteToServer\(DataRow\[\]\)](#)
This method copies all rows from the supplied `DataRow` array to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(DataTable\)](#)
This method copies all rows in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(IDataReader\)](#)
This method copies all rows in the supplied `IDataReader` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(DataTable, DataRowState\)](#)
This method copies rows that match the supplied row state in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(OracleRefCursor\)](#)
This method copies all rows from the specified `OracleRefCursor` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(DataRow[])

This method copies all rows from the supplied `DataRow` array to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

Declaration

```
// C#  
public void WriteToServer(DataRow[] rows);
```

Parameters

- `rows`
An array of `DataRow` objects to be copied to the destination table.

Exceptions

`ArgumentNullException` - The `rows` parameter is null.

`InvalidOperationException` - The connection is not in an open state.

Remarks

The `ColumnMappings` collection maps from the `DataRow` columns to the destination database table.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(DataTable)

This method copies all rows in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

Declaration

```
// C#  
public void WriteToServer(DataTable table);
```

Parameters

- *table*

The source `DataTable` containing rows to be copied to the destination table.

Exceptions

`ArgumentNullException` - The *table* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

Remarks

All rows in the `DataTable` are copied to the destination table except those that have been deleted.

The `ColumnMappings` collection maps from the `DataTable` columns to the destination database table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(IDataReader)

This method copies all rows in the supplied `IDataReader` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

Declaration

```
// C#  
public void WriteToServer(IDataReader reader);
```

Parameters

- *reader*

A `IDataReader` instance containing rows to be copied to the destination table.

Exceptions

`ArgumentNullException` - The *reader* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

Remarks

The bulk copy operation starts with the next available row of the data reader. Typically, the *reader* returned by a call to the `ExecuteReader` method is passed to the `WriteToServer` method so that the next row becomes the first row. To copy multiple result sets, the application must call `NextResult` on the *reader* and then call the `WriteToServer` method again.

This `WriteToServer` method changes the state of the reader as it calls `reader.Read` internally to get the source rows. Thus, at the end of the `WriteToServer` operation, the *reader* is at the end of the result set.

The `ColumnMappings` collection maps from the data reader columns to the destination database table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(DataTable, DataRowState)

This method copies rows that match the supplied row state in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

Declaration

```
// C#  
public void WriteToServer(DataTable table, DataRowState rowState);
```

Parameters

- *table*
A `DataTable` containing rows to be copied to the destination table.
- *rowState*
The `DataRowState` enumeration value. Only rows matching the row state are copied to the destination.

Exceptions

`ArgumentNullException` - The *table* or *rowState* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

Remarks

Only rows in the `DataTable` that are in the state indicated in the *rowState* argument and have not been deleted are copied to the destination table.

The `ColumnMappings` collection maps from the `DataTable` columns to the destination database table.

`DataRowState.Deleted` is not supported and the behavior would be that all the rows except the deleted ones are copied.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(OracleRefCursor)

This method copies all rows from the specified `OracleRefCursor` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

Declaration

```
// C#  
public void WriteToServer(OracleRefCursor refCursor);
```

Parameters

- *refCursor*
An `OracleRefCursor` object containing rows to be copied to the destination table.

Exceptions

`ArgumentNullException` - The *refCursor* parameter is null

`InvalidOperationException` - The connection is not in an open state.

Remarks

The `ColumnMappings` collection maps from the `OracleRefCursor` columns to the destination database table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleBulkCopy Events

OracleBulkCopy events are listed in [Table 17-7](#).

Table 17-7 OracleBulkCopy Events

Event	Description
OracleRowsCopied	Triggered every time the number of rows specified by the <code>OracleBulkCopy.NotifyAfter</code> property has been processed

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleRowsCopied

This event is triggered every time the number of rows specified by the `OracleBulkCopy.NotifyAfter` property has been processed.

Declaration

```
// C#  
public event OracleRowsCopiedEventHandler OracleRowsCopied;
```

Exceptions

`InvalidOperationException` - The `Close` method is called inside this event.

Remarks

This event is raised when the number of rows specified by the `NotifyAfter` property has been processed. It does not imply that the rows have been sent to the database or committed.

To cancel the operation from this event, use the `Abort` property of `OracleRowsCopiedEventArgs` class.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["NotifyAfter"](#)

OracleBulkCopyColumnMapping Class

The `OracleBulkCopyColumnMapping` class defines the mapping between a column in the data source and a column in the destination database table.

Class Inheritance

`System.Object`

`System.OracleBulkCopyColumnMapping`

Declaration

```
// C#
public sealed class OracleBulkCopyColumnMapping
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

Column mappings define the mapping between data source and the target table.

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

 **Note:**

Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

Example

```
// C#
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Members](#)
- [OracleBulkCopyColumnMapping Constructors](#)
- [OracleBulkCopyColumnMapping Methods](#)
- [OracleBulkCopyColumnMapping Properties](#)

OracleBulkCopyColumnMapping Members

OracleBulkCopyColumnMapping members are listed in the following tables.

OracleBulkCopyColumnMapping Constructors

The OracleBulkCopyColumnMapping constructors are listed in [Table 17-8](#).

Table 17-8 OracleBulkCopyColumnMapping Constructors

Constructor	Description
OracleBulkCopyColumnMapping Constructors	Instantiates new instances of the OracleBulkCopyColumnMapping class

OracleBulkCopyColumnMapping Methods

The OracleBulkCopyColumnMapping method is listed in [Table 17-9](#).

Table 17-9 OracleBulkCopyColumnMapping Method

Constructor	Description
CompareTo	Compares the current instance to the supplied object and returns an integer that represents their relative values

OracleBulkCopyColumnMapping Properties

The `OracleBulkCopyColumnMapping` properties are listed in [Table 17-10](#).

Table 17-10 OracleBulkCopyColumnMapping Properties

Property	Description
DestinationColumn	Specifies the column name of the destination table that is being mapped
DestinationOrdinal	Specifies the column ordinal value of the destination table that is being mapped
SourceColumn	Specifies the column name of the data source that is being mapped
SourceOrdinal	Specifies the column ordinal value of the data source that is being mapped



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)

OracleBulkCopyColumnMapping Constructors

`OracleBulkCopyColumnMapping` constructors instantiate new instances of the `OracleBulkCopyColumnMapping` class.

Overload List:

- [OracleBulkCopyColumnMapping\(\)](#)
This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class
- [OracleBulkCopyColumnMapping\(int, int\)](#)
This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column ordinal and destination column ordinal.
- [OracleBulkCopyColumnMapping\(int, string\)](#)
This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column ordinal and destination column name.
- [OracleBulkCopyColumnMapping\(string, int\)](#)
This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column name and destination column ordinal.
- [OracleBulkCopyColumnMapping\(string, string\)](#)
This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column name and destination column name.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping()

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping();
```

Remarks

Applications that use this constructor must define the source for the mapping using the `SourceColumn` or `SourceOrdinal` property, and must define the destination for the mapping using the `DestinationColumn` or `DestinationOrdinal` property.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(int, int)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source and destination column ordinal positions.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping(int sourceColumnOrdinal,  
    int destinationOrdinal);
```

Parameters

- *sourceColumnOrdinal*
The ordinal position of the source column within the data source.
- *destinationOrdinal*
The ordinal position of the destination column within the destination table.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(int, string)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column ordinal and destination column name.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping(int sourceColumnOrdinal,  
    string destinationColumn);
```

Parameters

- *sourceColumnOrdinal*
The ordinal position of the source column within the data source.
- *destinationColumn*
The name of the destination column within the destination table.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(string, int)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column name and destination column ordinal.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping(string sourceColumn, int destinationOrdinal);
```

Parameters

- *sourceColumn*
The name of the source column within the data source.

- *destinationOrdinal*
The ordinal position of the destination column within the destination table.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(string, string)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source and destination column names.

Declaration

```
// C#
public OracleBulkCopyColumnMapping(string sourceColumn, string destinationColumn);
```

Parameters

- *sourceColumn*
The name of the source column within the data source.
- *destinationColumn*
The name of the destination column within the destination table.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping Methods

The `OracleBulkCopyColumnMapping` method is listed in [Table 17-11](#).

Table 17-11 OracleBulkCopyColumnMapping Method

Property	Description
CompareTo	Compares the current instance to the supplied object and returns an integer that represents their relative values

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

CompareTo

This method compares the current instance to the supplied object and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

obj - The supplied instance.

Return Value

Less than zero: if the value of the current instance is less than obj.

Zero: if the value of the current instance is equal to obj.

Greater than zero: if the value of the current instance is greater than obj.

Implements

IComparable

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping Properties

The `OracleBulkCopyColumnMapping` properties are listed in [Table 17-12](#).

Table 17-12 OracleBulkCopyColumnMapping Properties

Property	Description
DestinationColumn	Specifies the column name of the destination table that is being mapped
DestinationOrdinal	Specifies the column ordinal value of the destination table that is being mapped
SourceColumn	Specifies the column name of the data source that is being mapped
SourceOrdinal	Specifies the column ordinal value of the data source that is being mapped

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

DestinationColumn

This property specifies the column name of the destination table that is being mapped.

Declaration

```
// C#  
public string DestinationColumn {get; set;}
```

Property Value

A string value that represents the destination column name of the mapping.

Remarks

The `DestinationColumn` and `DestinationOrdinal` properties are mutually exclusive. The last value set takes precedence.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

DestinationOrdinal

This property specifies the column ordinal value of the destination table that is being mapped.

Declaration

```
// C#  
public int DestinationOrdinal {get; set;}
```

Property Value

An integer value that represents the destination column ordinal of the mapping.

Exceptions

`IndexOutOfRangeException` - The destination ordinal is invalid.

Remarks

The `DestinationOrdinal` and `DestinationColumn` properties are mutually exclusive. The last value set takes precedence.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

SourceColumn

This property specifies the column name of the data source that is being mapped.

Declaration

```
// C#  
public string SourceColumn {get; set;}
```

Property Value

A string value that represents the source column name of the mapping.

Remarks

The `SourceColumn` and `SourceOrdinal` properties are mutually exclusive. The last value set takes precedence.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

SourceOrdinal

This property specifies the column ordinal value of the data source that is being mapped.

Declaration

```
// C#  
public int SourceOrdinal {get; set;}
```

Property Value

An integer value that represents the source column ordinal of the mapping.

Exceptions

`IndexOutOfRangeException` - The source ordinal is invalid.

Remarks

The `SourceOrdinal` and `SourceColumn` properties are mutually exclusive. The last value set takes precedence.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMappingCollection Class

The `OracleBulkCopyColumnMappingCollection` class represents a collection of `OracleBulkCopyColumnMapping` objects that are used to map columns in the data source to columns in a destination table.

Class Inheritance

`System.Object`

`System.CollectionBase`

```
System.OracleBulkCopyColumnMappingCollection
```

Declaration

```
// C#  
public sealed class OracleBulkCopyColumnMappingCollection : CollectionBase
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

Column mappings define the mapping between data source and the target table.

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.



Note:

Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

Example

```
// C#
```

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)
- [OracleBulkCopyColumnMappingCollection Properties](#)
- [OracleBulkCopyColumnMappingCollection Public Methods](#)

OracleBulkCopyColumnMappingCollection Members

OracleBulkCopyColumnMappingCollection members are listed in the following tables.

OracleBulkCopyColumnMappingCollection Properties

The OracleBulkCopyColumnMappingCollection properties are listed in [Table 17-13](#).

Table 17-13 OracleBulkCopyColumnMappingCollection Properties

Property	Description
Item[index]	Gets or sets the OracleBulkCopyColumnMappingCollection object at the specified index

OracleBulkCopyColumnMappingCollection Public Methods

The OracleBulkCopyColumnMappingCollection public methods are listed in [Table 17-14](#).

Table 17-14 OracleBulkCopyColumnMappingCollection Public Methods

Public Method	Description
Add	Adds objects to the collection
Clear	Clears the contents of the collection
Contains	Returns a value indicating whether or not a specified OracleBulkCopyColumnMapping object exists in the collection
CopyTo	Copies the elements of the OracleBulkCopyColumnMappingCollection to an array of OracleBulkCopyColumnMapping items, starting at a specified index
IndexOf	Returns the index of the specified OracleBulkCopyColumnMapping object
Insert	Inserts a new OracleBulkCopyColumnMapping object in the collection, at the index specified.

Table 17-14 (Cont.) OracleBulkCopyColumnMappingCollection Public Methods

Public Method	Description
Remove	Removes the specified <code>OracleBulkCopyColumnMapping</code> element from the <code>OracleBulkCopyColumnMappingCollection</code> .
RemoveAt	Removes the mapping from the collection at the specified index.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)

OracleBulkCopyColumnMappingCollection Properties

The `OracleBulkCopyColumnMappingCollection` properties are listed in [Table 17-15](#).

Table 17-15 OracleBulkCopyColumnMappingCollection Properties

Property	Description
Item[index]	Gets or sets the <code>OracleBulkCopyColumnMappingCollection</code> object at the specified index

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Item[index]

This property gets or sets the `OracleBulkCopyColumnMapping` object at the specified index.

Declaration

```
// C#
public OracleBulkCopyColumnMapping this[int index] {get;set;}
```

Parameters

- *index*
The zero-based index of the `OracleBulkCopyColumnMapping` being set or retrieved.

Property Value

An `OracleBulkCopyColumnMapping` object at the specified index.

Exceptions

`IndexOutOfRangeException` - The specified index does not exist.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

OracleBulkCopyColumnMappingCollection Public Methods

The `OracleBulkCopyColumnMappingCollection` public methods are listed in [Table 17-16](#).

Table 17-16 OracleBulkCopyColumnMappingCollection Public Methods

Public Method	Description
Add	Adds objects to the collection
Clear	Clears the contents of the collection
Contains	Returns a value indicating whether or not a specified <code>OracleBulkCopyColumnMapping</code> object exists in the collection
CopyTo	Copies the elements of the <code>OracleBulkCopyColumnMappingCollection</code> to an array of <code>OracleBulkCopyColumnMapping</code> items, starting at a specified index
IndexOf	Returns the index of the specified <code>OracleBulkCopyColumnMapping</code> object
Insert	Inserts a new <code>OracleBulkCopyColumnMapping</code> object in the collection, at the index specified.
Remove	Removes the specified <code>OracleBulkCopyColumnMapping</code> element from the <code>OracleBulkCopyColumnMappingCollection</code> .
RemoveAt	Removes the mapping from the collection at the specified index.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add

Add methods add objects to the collection.

Overload List:

- [Add\(OracleBulkCopyColumnMapping\)](#)
This method adds the supplied `OracleBulkCopyColumnMapping` object to the collection.
- [Add\(int, int\)](#)
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column ordinal positions.
- [Add\(int, string\)](#)
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column ordinal and destination column name.
- [Add\(string, int\)](#)
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column name and destination column ordinal.
- [Add\(string, string\)](#)
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column names.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(OracleBulkCopyColumnMapping)

This method adds the supplied `OracleBulkCopyColumnMapping` object to the collection.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping Add(OracleBulkCopyColumnMapping  
    bulkCopyColumnMapping);
```

Parameters

- *bulkCopyColumnMapping*
The `OracleBulkCopyColumnMapping` object that describes the mapping to be added to the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(int, int)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column ordinal positions.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping Add(int sourceColumnIndex,  
    int destinationColumnIndex);
```

Parameters

- *sourceColumnIndex*
The ordinal position of the source column within the data source.
- *destinationColumnIndex*
The ordinal position of the destination column within the destination table.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note:

Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(int, string)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column ordinal and destination column name.

Declaration

```
// C#
public OracleBulkCopyColumnMapping Add(int sourceColumnIndex,
    string destinationColumn);
```

Parameters

- *sourceColumnIndex*
The ordinal position of the source column within the data source.
- *destinationColumn*
The name of the destination column within the destination table.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note:

Oracle Data Provider for .NET makes one or more round trips to the database to determine the column names if the mapping is specified by ordinal resulting in a performance overhead. Therefore, it is recommended to specify the mapping by column names.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(string, int)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column name and destination column ordinal.

Declaration

```
// C#
public OracleBulkCopyColumnMapping Add(string sourceColumn,
    int destinationColumnIndex);
```

Parameters

- *sourceColumn*
The name of the source column within the data source.
- *destinationColumnIndex*
The ordinal position of the destination column within the destination table.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note:

Oracle Data Provider for .NET makes one or more round trips to the database to determine the column names if the mapping is specified by ordinal resulting in a performance overhead. Therefore, it is recommended to specify the mapping by column names.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(string, string)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column names.

Declaration

```
// C#
public OracleBulkCopyColumnMapping Add(string sourceColumn,
    string destinationColumn);
```

Parameters

- `sourceColumn`
The name of the source column within the data source.
- `destinationColumn`

The name of the destination column within the destination table.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note:

Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Clear

This method clears the contents of the collection.

Declaration

```
// C#  
public void Clear();
```

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

The `Clear` method is most commonly used when an application uses a single `OracleBulkCopy` instance to process more than one bulk copy operation. If column

mappings are created for one bulk copy operation, the `OracleBulkCopyColumnMappingCollection` must be cleared after the `WriteToServer` method invocation and before the next bulk copy is processed.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Contains

This method returns a value indicating whether or not a specified `OracleBulkCopyColumnMapping` object exists in the collection.

Declaration

```
// C#  
public bool Contains(OracleBulkCopyColumnMapping value);
```

Parameters

- `value`
A valid `OracleBulkCopyColumnMapping` object.

Return Value

Returns `true` if the specified mapping exists in the collection; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

CopyTo

This method copies the elements of the `OracleBulkCopyColumnMappingCollection` to an array of `OracleBulkCopyColumnMapping` items, starting at a specified index.

Declaration

```
// C#  
public void CopyTo(OracleBulkCopyColumnMapping[] array, int index);
```

Parameters

- *array*
The one-dimensional `OracleBulkCopyColumnMapping` array that is the destination for the elements copied from the `OracleBulkCopyColumnMappingCollection` object. The array must have zero-based indexing.
- *index*
The zero-based array index at which copying begins.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

IndexOf

This method returns the index of the specified `OracleBulkCopyColumnMapping` object.

Declaration

```
// C#  
public int IndexOf(OracleBulkCopyColumnMapping value);
```

Parameters

- *value*
The `OracleBulkCopyColumnMapping` object that is being returned.

Return Value

The zero-based index of the column mapping or -1 if the column mapping is not found in the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Insert

This method inserts a new `OracleBulkCopyColumnMapping` object in the collection, at the index specified.

Declaration

```
// C#  
public void Insert(int index, OracleBulkCopyColumnMapping value);
```

Parameters

- *index*
The integer value of the location within the `OracleBulkCopyColumnMappingCollection` at which the new `OracleBulkCopyColumnMapping` is inserted.
- *value*
The `OracleBulkCopyColumnMapping` object to be inserted in the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.



See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Remove

This method removes the specified `OracleBulkCopyColumnMapping` element from the `OracleBulkCopyColumnMappingCollection`.

Declaration

```
// C#  
public void Remove(OracleBulkCopyColumnMapping value);
```

Parameters

- *value*
The `OracleBulkCopyColumnMapping` object to be removed from the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

The `Remove` method is most commonly used when a single `OracleBulkCopy` instance processes more than one bulk copy operation. If column mappings are created for one bulk copy operation, mappings that no longer apply must be removed after the `WriteToServer` method invocation and before mappings are defined for the next bulk copy. The `Clear` method can clear the entire collection, and the `Remove` and the `RemoveAt` methods can remove mappings individually.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

RemoveAt

This method removes the mapping from the collection at the specified index.

Declaration

```
// C#  
public void RemoveAt(int index);
```

Parameters

- *index*

The zero-based index of the `OracleBulkCopyColumnMapping` object to be removed from the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

The `RemoveAt` method is most commonly used when a single `OracleBulkCopy` instance is used to process more than one bulk copy operation. If column mappings are created for one bulk copy operation, mappings that no longer apply must be removed after the `WriteToServer` method invocation and before the mappings for the next bulk copy are defined. The `Clear` method can clear the entire collection, and the `Remove` and the `RemoveAt` methods can remove mappings individually.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

OracleBulkCopyOptions Enumeration

The `OracleBulkCopyOptions` enumeration specifies the values that can be combined with an instance of the `OracleBulkCopy` class and used as options to determine its behavior and the behavior of the `WriteToServer` methods for that instance.

[Table 17-17](#) lists all the `OracleBulkCopyOptions` enumeration values with a description of each enumerated value.

Table 17-17 OracleBulkCopyOptions Enumeration Members

Member Name	Description
Default	Indicates that the default value for all options are to be used
UseInternalTransaction	Indicates that each batch of the bulk copy operation occurs within a transaction. If the connection used to perform the bulk copy operation is already part of a transaction, an <code>InvalidOperationException</code> exception is raised. If this member is not specified, <code>BatchSize</code> number of rows are sent to the database, without any transaction-related activity.

 **Note:**

All bulk copy operations are agnostic of any local or distributed transaction created by the application.

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

 See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- OracleBulkCopy ["BulkCopyOptions"](#)

OracleRowsCopiedEventHandler Delegate

The `OracleRowsCopiedEventHandler` delegate represents the method that handles the `OracleRowsCopied` event of an `OracleBulkCopy` object.

Declaration

```
// C#
public delegate void OracleRowsCopiedEventHandler (object sender,
    OracleRowsCopiedEventArgs eventArgs);
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	Oracle.DataAccess.dll
Namespace	Oracle.DataAccess.Client
.NET Framework	3.5, 4.5, 4.6, 4.7

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleRowsCopiedEventArgs` object that contains the event data.

Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified every time the number of rows specified by the `OracleBulkCopy.NotifyAfter` property has been processed.

If the event handler calls the `OracleBulkCopy.Close` method, an exception is generated, and the `OracleBulkCopy` object state does not change.

The event handler can also set the `OracleRowsCopiedEventArgs.Abort` property to `true` to indicate that the bulk copy operation must be aborted. If the bulk copy operation is part of an external transaction, an exception is generated and the transaction is not rolled back. The application is responsible for either committing or rolling back the external transaction.

If there is no external transaction, the internal transaction for the current batch of rows is automatically rolled back. However the previous batches of imported rows are unaffected, as their transactions have already been committed.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- ["OracleRowsCopied"](#)
- ["NotifyAfter"](#)

OracleRowsCopiedEventArgs Class

The `OracleRowsCopiedEventArgs` class represents the set of arguments passed as part of event data for the `OracleRowsCopied` event.

Class Inheritance

`System.Object`

`System.EventArgs`

`System.OracleRowsCopiedEventArgs`

Declaration

```
// C#  
public class OracleRowsCopiedEventArgs : EventArgs
```

Requirements

Provider	ODP.NET, Unmanaged Driver
Assembly	<code>Oracle.DataAccess.dll</code>
Namespace	<code>Oracle.DataAccess.Client</code>
.NET Framework	3.5, 4.5, 4.6, 4.7

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

Each time the number of rows represented by the `OracleBulkCopy.NotifyAfter` property is processed, the `OracleBulkCopy.OracleRowsCopied` event is raised, providing an `OracleRowsCopiedEventArgs` object that stores the event data.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowsCopiedEventArgs Members](#)
- [OracleRowsCopiedEventArgs Constructors](#)
- [OracleRowsCopiedEventArgs Properties](#)

OracleRowsCopiedEventArgs Members

OracleRowsCopiedEventArgs members are listed in the following tables.

OracleRowsCopiedEventArgs Constructors

OracleRowsCopiedEventArgs constructors are listed in [Table 17-18](#).

Table 17-18 OracleRowsCopiedEventArgs Constructors

Constructor	Description
OracleRowsCopiedEventArgs Constructors	OracleRowsCopiedEventArgs creates new instances of the OracleRowsCopiedEventArgs class

OracleRowsCopiedEventArgs Properties

OracleRowsCopiedEventArgs properties are listed in [Table 17-19](#).

Table 17-19 OracleRowsCopiedEventArgs Properties

Property	Description
Abort	Retrieves or sets a value that indicates whether or not the bulk copy operation is aborted
RowsCopied	Retrieves a value that represents the number of rows copied during the current bulk copy operation

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowsCopiedEventArgs Class](#)

OracleRowsCopiedEventArgs Constructors

OracleRowsCopiedEventArgs creates new instances of the OracleRowsCopiedEventArgs class.

Overload List:

- [OracleRowsCopiedEventArgs\(long\)](#)

This constructor creates a new instance of the `OracleRowsCopiedEventArgs` object.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

OracleRowsCopiedEventArgs(long)

This constructor creates a new instance of the `OracleRowsCopiedEventArgs` object.

Declaration

```
// C#  
public OracleRowsCopiedEventArgs(long rowsCopied);
```

Parameters

- *rowsCopied*

An `Int64` value that indicates the number of rows copied during the current bulk copy operation.

Remarks

The value in the *rowsCopied* parameter is reset by each call to a `WriteToServer` method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

OracleRowsCopiedEventArgs Properties

`OracleRowsCopiedEventArgs` properties are listed in [Table 17-20](#).

Table 17-20 OracleRowsCopiedEventArgs Properties

Property	Description
Abort	Retrieves or sets a value that indicates whether or not the bulk copy operation is aborted
RowsCopied	Retrieves a value that represents the number of rows copied during the current bulk copy operation

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

Abort

This property retrieves or sets a value that indicates whether or not the bulk copy operation is aborted.

Declaration

```
// C#  
public bool Abort{get; set;}
```

Property Value

Returns `true` if the bulk copy operation is to be aborted; otherwise, returns `false`.

Remarks

Set the `Abort` property to `true` to cancel the bulk copy operation.

If the `Close` method is called from `OracleRowsCopied`, an exception is generated, and the `OracleBulkCopy` object state does not change.

If the application does not create a transaction, the internal transaction corresponding to the current batch is automatically rolled back. However, changes related to previous batches within the bulk copy operation are retained, because the transactions in those batches are committed. This case is applicable only when `UseInternalTransaction` bulk copy option is chosen.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

RowsCopied

This property retrieves a value that represents the number of rows copied during the current bulk copy operation.

Declaration

```
// C#  
public long RowsCopied {get;}
```

Property Value

An `Int64` value that returns the number of rows copied.

Remarks

The value in the `RowsCopied` property is reset by each call to a `WriteToServer` method.

 **See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

A

Oracle Schema Collections

ODP.NET provides standard metadata collections as well as various Oracle database-specific metadata collections that can be retrieved through the `OracleConnection.GetSchema` API.

See Also:

- ["Schema Discovery"](#)
- ["GetSchema"](#)

This appendix contains the following topics:

- [Common Schema Collections](#)
- [ODP.NET-Specific Schema Collection](#)

Common Schema Collections

The common schema collections are available for all .NET Framework managed providers. ODP.NET supports the same common schema collections.

- [MetaDataCollections](#)
- [DataSourceInformation](#)
- [DataTypes](#)
- [Restrictions](#)
- [ReservedWords](#)

See Also:

"Common Schema Collections" in the [MSDN Library](#)

MetaDataCollections

[Table A-1](#) is a list of metadata collections that is available from the data source, such as tables, columns, indexes, and stored procedures.

Table A-1 MetaDataCollections

Column Name	Data Type	Description
CollectionName	string	The name of the collection passed to the GetSchema method for retrieval.
NumberOfRestrictions	int	Number of restrictions specified for the named collection.
NumberOfIdentifierParts	int	Number of parts in the composite identifier/ database object name.

DataSourceInformation

[Table A-2](#) lists DataSourceInformation information which may include these columns and possibly others.

Table A-2 DataSource Information

Columns	Data Type	Description
CompositeIdentifierSeparatorPattern	string	Separator for multipart names: @ \ .
DataSourceProductName	string	Database name: Oracle
DataSourceProductVersion	string	Database version. Note that this is the version of the database instance currently being accessed by DbConnection.
DataSourceProductVersionNormalized	string	A normalized DataSource version for easier comparison between different versions. For example: DataSource Version: 10.2.0.1.0 Normalized DataSource Version: 10.02.00.01.00
GroupByBehavior	GroupByBehavior	An enumeration that indicates the relationship between the columns in a GROUP BY clause and the non-aggregated columns in a select list.
IdentifierPattern	string	Format for a valid identifier.
IdentifierCase	IdentifierCase	An enumeration that specifies whether or not to treat non-quoted identifiers as case sensitive.
OrderByColumnsInSelect	bool	A boolean that indicates whether or not the select list must contain the columns in an ORDER BY clause.
ParameterMarkerFormat	string	A string indicating whether or not parameter markers begin with a special character.
ParameterMarkerPattern	string	The format of a parameter marker.
ParameterNameMaxLength	int	Maximum length of a parameter.
ParameterNamePattern	string	The format for a valid parameter name.
QuotedIdentifierPattern	string	The format of a quoted identifier.

Table A-2 (Cont.) DataSource Information

Columns	Data Type	Description
QuotedIdentifierCase	IdentifierCase	An enumeration that specifies whether or not to treat quote identifiers as case sensitive.
StringLiteralPattern	string	The format for a string literal.
SupportedJoinOperators	SupportedJoinOperators	An enumeration indicating the types of SQL join statements supported by the data source.

DataTypes

[Table A-3](#) lists DataTypes Collection information which may include these columns and possibly others.

Note:

As an example, the description column includes complete information for the `TIMESTAMP WITH LOCAL TIME ZONE` data type.

Table A-3 Data Types

ColumnName	Data Type	Description
TypeName	string	The provider-specific data type name. Example: <code>TIMESTAMP WITH LOCAL TIME ZONE</code>
ProviderDbType	int	The provider-specific type value. Example: 124
ColumnSize	long	The length of a non-numeric column or parameter. Example: 27
CreateFormat	string	A format string that indicates how to add this column to a DDL statement. Example: <code>TIMESTAMP({0} WITH LOCAL TIME ZONE)</code>
CreateParameters	string	The parameters specified to create a column of this data type. Example: 8
DataType	string	The .NET type for the data type. Example: <code>System.DateTime</code>

Table A-3 (Cont.) Data Types

ColumnName	Data Type	Description
IsAutoIncrementable	bool	A boolean value that indicates whether or not this data type can be auto-incremented. Example: false
IsBestMatch	bool	A boolean value that indicates whether or not this data type is the best match to values in the DataType column. Example: false
IsCaseSensitive	bool	A boolean value that indicates whether or not this data type is case-sensitive. Example: false
IsFixedLength	bool	A boolean value that indicates whether or not this data type has a fixed length. Example: true
IsFixedPrecisionScale	bool	A boolean value that indicates whether or not this data type has a fixed precision and scale. Example: false
IsLong	bool	A boolean value that indicates whether or not this data type contains very long data. Example: false
IsNullable	bool	A boolean value that indicates whether or not this data type is nullable. Example: true
IsSearchable	bool	A boolean value that indicates whether or not the data type can be used in a WHERE clause with any operator, except the LIKE predicate. Example: true
IsSearchableWithLike	bool	A boolean value that indicates whether or not this data type can be used with the LIKE predicate. Example: false
IsUnsigned	bool	A boolean value that indicates whether or not the data type is unsigned.
MaximumScale	short	The maximum number of digits allowed to the right of the decimal point.

Table A-3 (Cont.) Data Types

ColumnName	Data Type	Description
MinimumScale	short	The minimum number of digits allowed to the right of the decimal point.
IsConcurrencyType	bool	A boolean value that indicates whether or not the database updates the data type every time the row is changed and the value of the column differs from all previous values. Example: false
MinimumVersion	String	The earliest version of the database that can be used. Example:09.00.00.00.00
IsLiteralSupported	bool	A boolean value that indicates whether or not the data type can be expressed as a literal. Example: true
LiteralPrefix	string	The prefix of a specified literal. Example: TO_TIMESTAMP_TZ('
LiteralSuffix	string	The suffix of a specified literal. Example: ' , 'YYYY-MM-DD HH24:MI:SS.FF')

Restrictions

[Table A-4](#) lists Restrictions, including the following columns.

Table A-4 Restrictions

ColumnName	Data Type	Description
CollectionName	string	The collection that the restrictions apply to.
RestrictionName	string	The restriction name.
RestrictionNumber	int	A number that indicates the location of the restriction.

ReservedWords

The `ReservedWords` collection exposes information about the words that are reserved by the database currently connected to ODP.NET.

[Table A-5](#) lists the `ReservedWords` Collection.

Table A-5 ReservedWords

ColumnName	Data Type	Description
ReservedWord	string	Provider-specific reserved words

ODP.NET-Specific Schema Collection

Oracle Data Provider for .NET supports both the common schema collections described previously and the following Oracle-specific schema collections:

- [Tables](#)
- [Columns](#)
- [Views](#)
- [XMLSchema](#)
- [Users](#)
- [Synonyms](#)
- [Sequences](#)
- [Functions](#)
- [Procedures](#)
- [ProcedureParameters](#)
- [Arguments](#)
- [Packages](#)
- [PackageBodies](#)
- [JavaClasses](#)
- [Indexes](#)
- [IndexColumns](#)
- [PrimaryKeys](#)
- [ForeignKeys](#)
- [ForeignKeyColumns](#)
- [UniqueKeys](#)

Tables

[Table A-6](#) lists the column name, data type, and description of the Tables Schema Collection.

Table A-6 Tables

Column Name	Data Type	Description
OWNER	String	Owner of the Table.

Table A-6 (Cont.) Tables

Column Name	Data Type	Description
TABLE_NAME	String	Name of the Table.
TYPE	String	Type of Table, for example, System or User.

Columns

[Table A-7](#) lists the column name, data type, and description of the Columns Schema Collection .

Table A-7 Columns

ColumnName	Data Type	Description
OWNER	String	Owner of the table or view.
TABLE_NAME	String	Name of the table or view.
COLUMN_NAME	String	Name of the column.
ID	Decimal	Sequence number of the column as created.
DATATYPE	String	Data type of the column.
LENGTH	Decimal	Length of the column in bytes.
PRECISION	Decimal	Decimal precision for NUMBER data type; binary precision for FLOAT data type, null for all other data types.
Scale	Decimal	Digits to right of decimal point in a number.
NULLABLE	String	Specifies whether or not a column allows NULLs.
CHAR_USED	String	Indicates whether the column uses BYTE length semantics (B) or CHAR length semantics (C).
LengthInChars	Decimal	Length of the column in characters. This value only applies to CHAR, VARCHAR2, NCHAR, and NVARCHAR2.

Views

[Table A-8](#) lists the column name, data type, and description of the Views Schema Collection.

Table A-8 Views

Column Name	Data Type	Description
OWNER	String	Owner of the view.
VIEW_NAME	String	Name of the view.
TEXT_LENGTH	Decimal	Length of the view text.
TEXT	String	View text.

Table A-8 (Cont.) Views

Column Name	Data Type	Description
TYPE_TEXT_LENGTH	Decimal	Length of the type clause of the typed view.
TYPE_TEXT	String	Type clause of the typed view.
OID_TEXT_LENGTH	Decimal	Length of the WITH OID clause of the typed view.
OID_TEXT	String	WITH OID clause of the typed view.
VIEW_TYPE_OWNER	String	Owner of the view type if the view is a typed view.
VIEW_TYPE	String	Type of the view if the view is a typed view.
SUPERVIEW_NAME	String	Name of the superview. (Oracle9i or later)

XMLSchema

[Table A-9](#) lists the column name, data type and description of the XMLSchema Schema Collection.



Note:

This collection is only available with Oracle Database 10g and later.

Table A-9 XMLSchema

Column Name	Data Type	Description
OWNER	String	Owner of the XML schema.
SCHEMA_URL	String	Schema URL of the XML schema.
LOCAL	String	Indicates whether the XML schema is local (YES) or global (NO).
SCHEMA	String	XML schema document.
INT_OBJNAME	String	Internal database object name for the schema.
QUAL_SCHEMA_URL	String	Fully qualified schema URL.
HIER_TYPE	String	Hierarchy type for the schema.

Users

[Table A-10](#) lists the column name, data type and description of the Users Schema Collection.

Table A-10 Users

Column Name	Data Type	Description
NAME	String	Name of the user.
ID	Decimal	ID number of the user.
CREATEDATE	DateTime	User creation date.

Synonyms

[Table A-11](#) lists the column name, data type and description of the Synonyms Schema Collection.

Table A-11 Synonyms

Column Name	Data Type	Description
OWNER	String	Owner of the synonym.
SYNONYM_NAME	String	Name of the synonym.
TABLE_OWNER	String	Owner of the object referenced by the synonym. Although the column is called TABLE_OWNER, the object owned is not necessarily a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
TABLE_NAME	String	Name of the object referenced by the synonym. Although the column is called TABLE_NAME, the object does not necessarily have to be a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
DB_LINK	String	Name of the database link referenced, if any.

Sequences

[Table A-12](#) lists the column name, data type, and description of the Sequences Schema Collection.

Table A-12 Sequences

Column Name	Data Type	Description
SEQUENCE_OWNER	String	Name of the owner of the sequence.
SEQUENCE_NAME	String	Sequence name.
MIN_VALUE	Decimal	Minimum value of the sequence.
MAX_VALUE	Decimal	Maximum value of the sequence.
INCREMENT_BY	Decimal	Value by which sequence is incremented.
CYCLE_FLAG	String	Indicates if sequence wraps around on reaching limit.

Table A-12 (Cont.) Sequences

Column Name	Data Type	Description
ORDER_FLAG	String	Indicates if sequence numbers are generated in order.
CACHE_SIZE	Decimal	Number of sequence numbers to cache.
LAST_NUMBER	Decimal	Last sequence number written to disk. If a sequence uses caching, the number written to disk is the last number placed in the sequence cache. This number is likely to be greater than the last sequence number that was used.

Functions

[Table A-13](#) lists the column name, data type, and description of the Functions Schema Collection.

Table A-13 Functions

Column Name	Data Type	Description
OWNER	String	Owner of the function.
OBJECT_NAME	String	Name of the function.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).
OBJECT_ID	Decimal	Dictionary object number of the function.
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the function.
CREATED	DateTime	Timestamp for the creation of the function.
LAST_DDL_TIME	DateTime	Timestamp for the last modification of the function resulting from a DDL statement (including grants and revokes).
TIMESTAMP	String	Timestamp for the specification of the function (character data).
STATUS	String	Status of the function (VALID, INVALID, or N/A).
TEMPORARY	String	Whether or not the function is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this function is system generated (Y) or not (N).
SECONDARY	String	Whether or not this is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y N).

Procedures

[Table A-14](#) lists the column name, data type, and description of the Procedures Schema Collection.

Table A-14 Procedures

Column Name	Data Type	Description
OWNER	String	Owner of the procedure.
OBJECT_NAME	String	Name of the procedure.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).
OBJECT_ID	Decimal	Dictionary object number of the procedure.
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the procedure.
CREATED	DateTime	Timestamp for the creation of the procedure.
LAST_DDL_TIME	Decimal	Timestamp for the last modification of the procedure resulting from a DDL statement (including grants and revokes).
TIMESTAMP	String	Timestamp for the specification of the procedure (character data).
STATUS	String	Status of the procedure (VALID, INVALID, or N/A).
TEMPORARY	String	Whether or not the procedure is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this procedure is system generated (Y) or not (N).
SECONDARY	String	Whether or not this is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y N).

ProcedureParameters

[Table A-15](#) lists the column name, data type and description of the ProcedureParameters Schema Collection.

Table A-15 ProcedureParameters

Column Name	Data Type	Description
OWNER	String	Owner of the object.
OBJECT_NAME	String	Name of the procedure or function.
PACKAGE_NAME	String	Name of the package.
OBJECT_ID	Decimal	Object number of the object.
OVERLOAD	String	Indicates the <i>n</i> th overloading ordered by its appearance in the source; otherwise, it is NULL.
SUBPROGRAM_ID	Decimal	Subprogram id for the procedure or function
ARGUMENT_NAME	String	If the argument is a scalar type, then the argument name is the name of the argument. A null argument name is used to denote a function return value.

Table A-15 (Cont.) ProcedureParameters

Column Name	Data Type	Description
POSITION	Decimal	If DATA_LEVEL is zero, then this column holds the position of this item in the argument list, or zero for a function return value.
SEQUENCE	Decimal	Defines the sequential order of the argument. Argument sequence starts from 1.
DATA_LEVEL	Decimal	Nesting depth of the argument for composite types.
DATA_TYPE	String	Data type of the argument.
DEFAULT_VALUE	String	Default value for the argument.
DEFAULT_LENGTH	Decimal	Length of the default value for the argument.
IN_OUT	String	Direction of the argument: [IN] [OUT] [IN/OUT].
DATA_LENGTH	Decimal	Length of the column (in bytes).
DATA_PRECISION	Decimal	Length in decimal digits (NUMBER) or binary digits (FLOAT).
DATA_SCALE	Decimal	Digits to the right of the decimal point in a number.
RADIX	Decimal	Argument radix for a number.
CHARACTER_SET_NAME	String	Character set name for the argument.
TYPE_OWNER	String	Owner of the type of the argument.
TYPE_NAME	String	Name of the type of the argument. If the type is a package local type (that is, it is declared in a package specification), then this column displays the name of the package.
TYPE_SUBNAME	String	Displays the name of the type declared in the package identified in the TYPE_NAME column. Relevant only for package local types.
TYPE_LINK	String	Displays the database link that refers to the remote package. Relevant only for package local types when the package identified in the TYPE_NAME column is a remote package.
PLS_TYPE	String	For numeric arguments, the name of the PL/SQL type of the argument. Otherwise, Null.
CHAR_LENGTH	Decimal	Character limit for string data types.
CHAR_USED	String	Indicates whether the byte limit (B) or character limit (C) is official for the string.

Arguments

Table A-16 lists the column name, data type, and description of the Arguments Schema Collection.

Table A-16 Arguments

Column Name	Data Type	Description
OWNER	String	Owner of the object.
PACKAGE_NAME	String	Name of the package.
OBJECT_NAME	String	Name of the procedure or function.
ARGUMENT_NAME	String	If the argument is a scalar type, then the argument name is the name of the argument. A null argument name is used to denote a function return value.
POSITION	Decimal	If DATA_LEVEL is zero, then this column holds the position of this item in the argument list, or zero for a function return value.
SEQUENCE	Decimal	Defines the sequential order of the argument. Argument sequence starts from 1.
DEFAULT_VALUE	String	Default value for the argument.
DEFAULT_LENGTH	Decimal	Length of the default value for the argument.
IN_OUT	String	Direction of the argument: [IN] [OUT] [IN/OUT].
DATA_LENGTH	Decimal	Length of the column (in bytes).
DATA_PRECISION	Decimal	Length in decimal digits (NUMBER) or binary digits (FLOAT).
DATA_SCALE	Decimal	Digits to the right of the decimal point in a number.
DATA_TYPE	String	Data type of the argument.
CHAR_USED	String	Indicates whether the column uses BYTE length semantics (B) or CHAR length semantics (C).

Packages

[Table A-17](#) lists the column name, data type, and description of the Packages Schema Collection.

Table A-17 Packages

Column Name	Data Type	Description
OWNER	String	Owner of the package.
OBJECT_NAME	String	Name of the package.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).
OBJECT_ID	Decimal	Dictionary object number of the package.
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the package.
CREATED	DateTime	Timestamp for the creation of the package.
LAST_DDL_TIME	DateTime	Timestamp for the last modification of the package resulting from a DDL statement (including grants and revokes).

Table A-17 (Cont.) Packages

Column Name	Data Type	Description
TIMESTAMP	String	Timestamp for the specification of the package (character data).
STATUS	String	Status of the package (VALID, INVALID, or N/A).
TEMPORARY	String	Whether or not the package is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this package was system generated (Y) or not (N).
SECONDARY	String	Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y N).

PackageBodies

[Table A-18](#) lists the column name, data type, and description of the PackageBodies Schema Collection.

Table A-18 PackageBodies

Column Name	Data Type	Description
OWNER	String	Owner of the package body.
OBJECT_NAME	String	Name of the package body.
SUBOBJECT_NAME	String	Name of the subobject (for example, partition).
OBJECT_ID	Decimal	Dictionary object number of the package body.
DATA_OBJECT_ID	Decimal	Dictionary object number of the segment that contains the package body.
CREATED	DateTime	Timestamp for the creation of the package body.
LAST_DDL_TIME	DateTime	Timestamp for the last modification of the package body resulting from a DDL statement (including grants and revokes).
TIMESTAMP	String	Timestamp for the specification of the package body (character data).
STATUS	String	Status of the package body (VALID, INVALID, or N/A).
TEMPORARY	String	Whether the package body is temporary (the current session can see only data that it placed in this object itself).
GENERATED	String	Indicates whether the name of this package body is system generated (Y) or not (N).
SECONDARY	String	Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y N).

JavaClasses

[Table A-19](#) lists the column name, data type, and description of the JavaClasses Schema Collection.

Table A-19 JavaClasses

Column Name	Data Type	Description
OWNER	String	Owner of the Java class.
NAME	String	Name of the Java class.
MAJOR	Decimal	Major version number of the Java class, as defined in the JVM specification.
MINOR	Decimal	Minor version number of the Java class, as defined in the JVM specification.
KIND	String	Indicates whether the stored object is a Java class (CLASS) or a Java interface (INTERFACE).
ACCESSIBILITY	String	Accessibility of the Java class.
IS_INNER	String	Indicates whether this Java class is an inner class (YES) or not (NO).
IS_ABSTRACT	String	Indicates whether this Java class is an abstract class (YES) or not (NO).
IS_FINAL	String	Indicates whether this Java class is a final class (YES) or not (NO).
IS_DEBUG	String	Indicates whether this Java class contains debug information (YES) or not (NO).
SOURCE	String	Source designation of the Java class.
SUPER	String	Super class of this Java class.
OUTER	String	Outer class of this Java class if this Java class is an inner class.

Indexes

[Table A-20](#) lists the column name, data type, and description of the Indexes Schema Collection.

Table A-20 Indexes

Column Name	Data Type	Description
OWNER	String	Owner of the index.
INDEX_NAME	String	Name of the index.

Table A-20 (Cont.) Indexes

Column Name	Data Type	Description
INDEX_TYPE	String	Type of the index: <ul style="list-style-type: none"> NORMAL BITMAP FUNCTION-BASED NORMAL FUNCTION-BASED BITMAP DOMAIN
TABLE_OWNER	String	Owner of the indexed object.
TABLE_NAME	String	Name of the indexed object.
TABLE_TYPE	String	Type of the indexed object (for example, TABLE or CLUSTER).
UNIQUENESS	String	Indicates whether the index is UNIQUE or NONUNIQUE.
COMPRESSION	String	Indicates whether index compression is enabled (ENABLED) or not (DISABLED).
PREFIX_LENGTH	Decimal	Number of columns in the prefix of the compression key.
TABLESPACE_NAME	String	Name of the tablespace containing the index.
INI_TRANS	Decimal	Initial number of transactions.
MAX_TRANS	Decimal	Maximum number of transactions.
INITIAL_EXTENT	Decimal	Size of the initial extent.
NEXT_EXTENT	Decimal	Size of secondary extents.
MIN_EXTENTS	Decimal	Minimum number of extents allowed in the segment.
MAX_EXTENTS	Decimal	Maximum number of extents allowed in the segment.
PCT_INCREASE	Decimal	Percentage increase in extent size.
PCT_THRESHOLD	Decimal	Threshold percentage of block space allowed per index entry.
INCLUDE_COLUMN	Decimal	Column ID of the last column to be included in index-organized table primary key (non-overflow) index. This column maps to the COLUMN_ID column of the *_TAB_COLUMNS data dictionary views.
FREELISTS	Decimal	Number of process freelists allocated to this segment.
FREELIST_GROUPS	Decimal	Number of freelist groups allocated to this segment.
PCT_FREE	Decimal	Minimum percentage of free space in a block.
LOGGING	String	Logging information.
BLEVEL	Decimal	B*-Tree level: depth of the index from its root block to its leaf blocks. A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS	Decimal	Number of leaf blocks in the index.

Table A-20 (Cont.) Indexes

Column Name	Data Type	Description
DISTINCT_KEYS	Decimal	Number of distinct indexed values. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is the same as the number of rows in the table (USER_TABLES.NUM_ROWS).
AVG_LEAF_BLOCKS_PER_KEY	Decimal	Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_PER_KEY	Decimal	Average number of data blocks in the table that are pointed to by a distinct value in the index, rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.
CLUSTERING_FACTOR	Decimal	Indicates the amount of order of the rows in the table based on the values of the index.
STATUS	String	Indicates whether a nonpartitioned index is VALID or UNUSABLE.
NUM_ROWS	Decimal	Number of rows in the index.
SAMPLE_SIZE	Decimal	Size of the sample used to analyze the index.
LAST_ANALYZED	Date	Date on which this index was most recently analyzed.
DEGREE	String	Number of threads per instance for scanning the index.
INSTANCES	String	Number of instances across which the indexes to be scanned.
PARTITIONED	String	Indicates whether the index is partitioned (YES) or not (NO).
TEMPORARY	String	Indicates whether or not the index is on a temporary table.
GENERATED	String	Indicates whether the name of the index is system generated (Y) or not (N).
SECONDARY	String	Indicates whether the index is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N).
BUFFER_POOL	String	Name of the default buffer pool to be used for the index blocks.
USER_STATS	String	Indicates whether statistics were entered directly by the user (YES) or not (NO).
DURATION	String	Indicates the duration of a temporary table.
PCT_DIRECT_ACCESS	Decimal	For a secondary index on an index-organized table, the percentage of rows with VALID guess.
ITYP_OWNER	String	For a domain index, the owner of the index type.
ITYP_NAME	String	For a domain index, the name of the index type.
PARAMETERS	String	For a domain index, the parameter string.

Table A-20 (Cont.) Indexes

Column Name	Data Type	Description
GLOBAL_STATS	String	For partitioned indexes, indicates whether statistics are collected by analyzing the index as a whole (YES) or estimated from statistics on underlying index partitions and subpartitions (NO).
DOMIDX_STATUS	String	Status of the domain index: <ul style="list-style-type: none"> • NULL - Index is not a domain index. • VALID - Index is a valid domain index. • IDXTYP_INVLD - Indextype of the domain index is invalid.
DOMIDX_OPSTATUS	String	Status of the operation on the domain index: <ul style="list-style-type: none"> • NULL - Index is not a domain index. • VALID - Operation performed without errors. • FAILED - Operation failed with an error.
FUNCIDX_STATUS	String	Status of a function-based index: <ul style="list-style-type: none"> • NULL - Index is not a function-based index. • ENABLED - Function-based index is enabled. • DISABLED - Function-based index is disabled.
JOIN_INDEX	String	Indicates whether the index is a join index (YES) or not (NO).
IOT_REDUNDANT_PKEY_ELIM	String	Indicates whether redundant primary key columns are eliminated from secondary indexes on index-organized tables (YES) or not (NO).
DROPPED	String	Indicates whether the index has been dropped and is in the recycle bin (YES) or not (NO); null for partitioned tables.

IndexColumns

[Table A-21](#) lists the column name, data type, and description of the IndexColumns Schema Collection.

Table A-21 IndexColumns

Column Name	Data Type	Description
INDEX_OWNER	String	Owner of the index.
INDEX_NAME	String	Name of the index.
TABLE_OWNER	String	Owner of the table or cluster.
TABLE_NAME	String	Name of the table or cluster.
COLUMN_NAME	String	Column name or attribute of object type column.
COLUMN_POSITION	Decimal	Position of column or attribute within the index.
COLUMN_LENGTH	Decimal	Indexed length of the column.

Table A-21 (Cont.) IndexColumns

Column Name	Data Type	Description
DESCEND	String	Whether the column is sorted in descending order (Y/N).
CHAR_LENGTH	Decimal	Maximum codepoint length of the column. (Oracle9i or later)

PrimaryKeys

Table A-22 lists the column name, data type, and description of the PrimaryKeys Schema Collection.

Table A-22 PrimaryKeys

Column Name	Data Type	Description
OWNER	String	Owner of the constraint definition.
CONSTRAINT_NAME	String	Name of the constraint definition.
TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
SEARCH_CONDITION	String	Text of search condition for a check constraint.
R_OWNER	String	Owner of table referred to in a referential constraint.
R_CONSTRAINT_NAME	String	Name of the unique constraint definition for referenced table.
DELETE_RULE	String	Delete rule for a referential constraint (CASCADE or NO ACTION).
STATUS	String	Enforcement status of constraint (ENABLED or DISABLED).
DEFERRABLE	String	Whether or not the constraint is deferrable.
VALIDATED	String	Whether all data obeys the constraint (VALIDATED or NOT VALIDATED).
GENERATED	String	Whether the name of the constraint is user or system generated.
BAD	String	Indicates that this constraint specifies a century in an ambiguous manner. (Yes No) To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year.
RELY	String	Whether an enabled constraint is enforced or unenforced.
LAST_CHANGE	DateTime	When the constraint was last enabled or disabled.
INDEX_OWNER	String	Name of the user owning the index. (Oracle9i or later)

Table A-22 (Cont.) PrimaryKeys

Column Name	Data Type	Description
INDEX_NAME	String	Name of the index (only shown for unique and primary-key constraints). (Oracle9i or later)

ForeignKeys

Table A-23 lists the column name, data type, and description of the ForeignKeys Schema Collection.

Table A-23 ForeignKeys

Column Name	Data Type	Description
PRIMARY_KEY_CONSTRAINT_NAME	String	Name of the constraint definition.
PRIMARY_KEY_OWNER	String	Owner of the constraint definition.
PRIMARY_KEY_TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
FOREIGN_KEY_OWNER	String	Owner of the constraint definition.
FOREIGN_KEY_CONSTRAINT_NAME	String	Name of the constraint definition.
FOREIGN_KEY_TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
SEARCH_CONDITION	String	Text of search condition for a check constraint
R_OWNER	String	Owner of table referred to, in a referential constraint.
R_CONSTRAINT_NAME	String	Name of the unique constraint definition for referenced table.
DELETE_RULE	String	Delete rule for a referential constraint (CASCADE or NO ACTION).
STATUS	String	Enforcement status of constraint (ENABLED or DISABLED).
VALIDATED	String	Whether or not all data obeys the constraint (VALIDATED or NOT VALIDATED).
GENERATED	String	Whether the name of the constraint is user or system generated.
RELY	String	Whether an enabled constraint is enforced or unenforced.
LAST_CHANGE	DateTime	When the constraint was last enabled or disabled.
INDEX_OWNER	String	Name of the user owning the index. (Oracle9i or later)
INDEX_NAME	String	Name of the index. (Oracle9i or later)

ForeignKeyColumns

[Table A-24](#) lists the column name, data type, and description of the ForeignKeyColumns Schema Collection.

Table A-24 ForeignKeyColumns

Column Name	Data Type	Description
OWNER	String	Owner of the constraint definition.
CONSTRAINT_NAME	String	Name of the constraint definition.
TABLE_NAME	String	Name of the table with constraint definition.
COLUMN_NAME	String	Name of the column or attribute of the object type column specified in the constraint definition.
POSITION	String	Original position of column or attribute in the definition of the object.

UniqueKeys

[Table A-25](#) lists the column name, data type, and description of the UniqueKeys Schema Collection.

Table A-25 UniqueKeys

Column Name	Data Type	Description
OWNER	String	Owner of the constraint definition.
CONSTRAINT_NAME	String	Name of the constraint definition.
TABLE_NAME	String	Name associated with the table (or view) with constraint definition.
SEARCH_CONDITION	String	Text of search condition for a check constraint.
R_OWNER	String	Owner of table referred to in a referential constraint.
R_CONSTRAINT_NAME	String	Name of the unique constraint definition for referenced table.
DELETE_RULE	String	Delete rule for a referential constraint (CASCADE or NO ACTION).
STATUS	String	Enforcement status of constraint (ENABLED or DISABLED).
DEFERRABLE	String	Whether or not the constraint is deferrable.
VALIDATED	String	Whether all data obeys the constraint (VALIDATED or NOT VALIDATED).
GENERATED	String	Whether the name of the constraint is user or system generated.

Table A-25 (Cont.) UniqueKeys

Column Name	Data Type	Description
BAD	String	Indicates that this constraint specifies a century in an ambiguous manner. (Yes No) To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year.
RELY	String	Whether an enabled constraint is enforced or not.
LAST_CHANGE	String	When the constraint was last enabled or disabled.
INDEX_OWNER	String	Name of the user owning the index. (Oracle9i or later)
INDEX_NAME	String	Name of the index (only shown for unique and primary-key constraints). (Oracle9i or later)

B

Mapping LINQ Canonical Functions and Oracle Functions

This appendix lists the Entity Framework canonical functions and the corresponding ODP.NET provider functions to which they map.

Aggregate Canonical Functions

Table B-1 Mapping of Aggregate Canonical Functions and Oracle Functions

Canonical Function	Oracle Function
Avg (<i>expression</i>)	AVG(<i>expression</i>)
BigCount (<i>expression</i>)	COUNT(<i>expression</i>)
Count (<i>expression</i>)	COUNT(<i>expression</i>)
Max (<i>expression</i>)	MAX(<i>expression</i>)
Min (<i>expression</i>)	MIN(<i>expression</i>)
StDev (<i>expression</i>)	STDDEV(<i>expression</i>)
StDevP(<i>expression</i>)	STDEV(<i>expression</i>)
Sum (<i>expression</i>)	SUM (<i>expression</i>)
Var(<i>expression</i>)	VAR(<i>expression</i>)
VarP(<i>expression</i>)	VARP(<i>expression</i>)

Math Canonical Functions

Table B-2 Mapping of Math Canonical Functions and Oracle Functions

Canonical Function	Oracle Function
Abs (<i>value</i>)	ABS (<i>value</i>)
Ceiling (<i>value</i>)	CEIL(<i>value</i>)
Floor (<i>value</i>)	FLOOR(<i>value</i>)
Power(<i>value</i> , <i>exponent</i>)	POWER(<i>value</i> , <i>exponent</i>)
Round (<i>value</i>)	ROUND(<i>value</i>)
Round (<i>value</i> , <i>digits</i>)	ROUND(<i>value</i> , <i>digits</i>)
Truncate(<i>value</i> , <i>digits</i>)	TRUNC(<i>value</i> , <i>digits</i>)

String Canonical Functions

Table B-3 Mapping of String Canonical Functions and Oracle Functions

Canonical Function	Oracle Function
Concat (<i>string1</i> , <i>string2</i>)	CONCAT(<i>string1</i> , <i>string2</i>) or ((<i>string1</i>) (<i>string2</i>))
Contains(<i>string</i> , <i>target</i>)	INSTR(<i>string</i> , <i>target</i>)
EndsWith(<i>string</i> , <i>target</i>)	INSTR(REVERSE(<i>string</i>), REVERSE(<i>target</i>))
Comparison operators (<, <=, >, >=, <>, !=)	Comparison operators (<, <=, >, >=, <>, !=)
IndexOf(<i>target</i> , <i>string</i>)	INSTR(<i>string2</i> , <i>target</i>)
Left (<i>string1</i> , <i>length</i>)	SUBSTR(<i>string1</i> , <i>length</i>)
Length (<i>string</i>)	LENGTH(<i>string</i>)
LTrim(<i>string</i>)	LTRIM(<i>string</i>)
Replace (<i>string1</i> , <i>string2</i> , <i>string3</i>)	REPLACE(<i>string1</i> , <i>string2</i> , <i>string3</i>)
Reverse (<i>string</i>)	REVERSE(<i>string</i>)
Right (<i>string</i> , <i>length</i>)	(CASE WHEN LENGTH(<i>string</i>) >= (<i>length</i>) THEN SUBSTR (<i>string</i> ,-(<i>length</i>), <i>length</i>) ELSE <i>string</i> END)
RTrim(<i>string</i>)	RTRIM(<i>string</i>)
Substring (<i>string</i> , <i>start</i> , <i>length</i>)	SUBSTR((<i>string</i> , <i>start</i> , <i>length</i>)
StartsWith(<i>string</i> , <i>target</i>)	INSTR(<i>string</i> , <i>target</i>)
ToLower (<i>string</i>)	LOWER(<i>string</i>)
ToUpper(<i>string</i>)	UPPER
Trim (<i>string</i>)	LTRIM(RTRIM(<i>string</i>))

Date And Time Canonical Functions

Table B-4 Mapping of Date And Time Canonical Functions and Oracle Functions

Canonical Function	Oracle Function
AddNanoseconds(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
AddMicroseconds(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
AddMilliseconds(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL

Table B-4 (Cont.) Mapping of Date And Time Canonical Functions and Oracle Functions

Canonical Function	Oracle Function
AddSeconds(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
AddMinutes(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
AddHours(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
AddDays(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
AddMonths(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
AddYears(<i>expression</i> , <i>number</i>)	(<i>expression</i>) + INTERVAL
CreateDateTime(<i>year</i> , <i>month</i> , <i>day</i> , <i>hour</i> , <i>minute</i> , <i>second</i>)	TO_TIMESTAMP
CreateDateTimeOffset(<i>year</i> , <i>month</i> , <i>day</i> , <i>hour</i> , <i>minute</i> , <i>second</i> , <i>tzoffset</i>)	TO_TIMESTAMP_TZ
CreateTime(<i>hour</i> , <i>minute</i> , <i>second</i>)	Time literals are not supported in Oracle
CurrentDateTime()	LOCALTIMESTAMP
CurrentDateTimeOffset()	SYSTIMESTAMP
CurrentUtcDateTime()	SYS_EXTRACT_UTC (LOCALTIMESTAMP)
Day(<i>expression</i>)	EXTRACT(DAY FROM <i>expression</i>)
DayOfYear(<i>expression</i>)	TO_NUMBER(TO_CHAR(CAST(<i>expression</i> AS TIMESTAMP), 'DDD'))
DiffNanoseconds(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
DiffMilliseconds(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
DiffMicroseconds(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
DiffSeconds(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
DiffMinutes(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
DiffHours(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
DiffDays(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
DiffMonths(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations

Table B-4 (Cont.) Mapping of Date And Time Canonical Functions and Oracle Functions

Canonical Function	Oracle Function
DiffYears(<i>startExpression</i> , <i>endExpression</i>)	EXTRACT and arithmetic operations
Comparison operators (<i><</i> , <i><=</i> , <i>></i> , <i>>=</i> , <i><></i> , <i>!=</i>)	<i><</i> , <i><=</i> , <i>></i> , <i>>=</i> , <i><></i> , <i>!=</i> operators
GetTotalOffsetMinutes (<i>datetimeoffset</i>)	(EXTRACT(TIMEZONE_HOUR FROM (<i>expression</i>)) * 60 + EXTRACT (TIMEZONE_MINUTE FROM(<i>expression</i>)) (Require multiple operations.)
Hour (<i>expression</i>)	EXTRACT(HOUR FROM <i>expression</i>)
Millisecond(<i>expression</i>)	NVL(TO_NUMBER(SUBSTR(TO_CHAR(CAST(<i>expression</i> AS TIMESTAMP), 'DD- MON-RR HH24:MI:SSXFF'), 20, 3)), 0)
Minute(<i>expression</i>)	EXTRACT(MINUTE FROM <i>expression</i>)
Month (<i>expression</i>)	EXTRACT(MONTH FROM <i>expression</i>)
Second(<i>expression</i>)	EXTRACT (SECOND FROM <i>expression</i>)
TruncateDate(<i>expression</i>)	TRUNC(<i>expression</i>)
Year(<i>expression</i>)	EXTRACT(YEAR FROM <i>expression</i>)

Bitwise Canonical Functions**Table B-5 Mapping of Bitwise Canonical Functions and Oracle Functions**

Canonical Function	Oracle Function
BitWiseAnd (<i>value1</i> , <i>value2</i>)	BITAND(<i>value1</i> , <i>value2</i>)
BitWiseNot (<i>value</i>)	(0 - <i>value</i>) - 1
BitWiseOr (<i>value1</i> , <i>value2</i>)	<i>value1</i> - BITAND(<i>value1</i> , <i>value2</i>) + <i>value2</i>
BitWiseXor (<i>value1</i> , <i>value2</i>)	<i>value1</i> - 2 * BITAND(<i>value1</i> , <i>value2</i>) + <i>value2</i>

Other Canonical Functions**Table B-6 Mapping of Other Canonical Functions and Oracle Functions**

Canonical Function	Oracle Function
NewGuid()	SYS_GUID

Glossary

assembly

Assembly is Microsoft's term for the module that is created when a DLL or .EXE is compiled by a .NET compiler.

BFILES

External binary files that exist outside the database tablespaces residing in the operating system. BFILES are referenced from the database semantics, and are also known as external LOBs.

Binary Large Object (BLOB)

A large object data type whose content consists of binary data. Additionally, this data is considered raw as its structure is not recognized by the database.

Character Large Object (CLOB)

The LOB data type whose value is composed of character data corresponding to the database character set. A CLOB may be indexed and searched by the Oracle Text search engine.

data provider

As the term is used with Oracle Data Provider for .NET, a data provider is the connected component in the ADO.NET model and transfers data between a data source and the DataSet.

DataSet

A DataSet is an in-memory copy of database data. The DataSet exists in memory without an active connection to the database.

dirty writes

Dirty writes means writing uncommitted or dirty data.

DDL

DDL refers to data definition language, which includes statements defining or changing data structure.

DOM

Document Object Model (DOM) is an application program interface (API) for HTML and XML documents. It defines the logical structure of documents and the way that a document is accessed and manipulated.

Extensible Stylesheet Language Transformation (XSLT)

The XSL W3C standard specification that defines a transformation language to convert one XML document into another.

flush

Flush or flushing refers to recording changes (that is, sending modified data) to the database.

Global Assembly Cache (GAC)

A cache for .NET assemblies.

goodness

The degree of load in the Oracle database. The lighter load is better and vice versa.

implicit database connection

The connection that is implicitly available from the context of the .NET stored procedure execution.

instantiate

A term used in object-based languages such as C# to refer to the creation of an object of a specific class.

invalidation message

The content of a change notification which indicates that the cache is now invalid

Large Object (LOB)

The class of SQL data type that is further divided into internal LOBs and external LOBs. Internal LOBs include BLOBS, CLOBs, and NCLOBs while external LOBs include BFILES.

Microsoft .NET Framework Class Library

The Microsoft .NET Framework Class Library provides the classes for the .NET framework model.

namespace

- .NET:
A namespace is naming device for grouping related types. More than one namespace can be contained in an assembly.
- XML Documents:
A namespace describes a set of related element names or attributes within an XML document.

National Character Large Object (NCLOB)

The LOB data type whose value is composed of character data corresponding to the database national character set.

Oracle Net Services

The Oracle client/server communication software that offers transparent operation to Oracle tools or databases over any type of network protocol and operating system.

OracleDataReader

An `OracleDataReader` is a read-only, forward-only result set.

Oracle XML DB

Oracle XML DB is the name for a distinct group of technologies related to high-performance XML storage and retrieval that are available within the Oracle database. Oracle XML DB is not a separate server.

Oracle XML DB is based on the W3C XML data model.

PL/SQL

The Oracle procedural language extension to SQL.

primary key

The column or set of columns included in the definition of a table's PRIMARY KEY constraint.

reference semantics

Reference semantics indicates that assignment is to a reference (an address such as a pointer) rather than to a value. See [value semantics](#).

REF

A data type that encapsulates references to row objects of a specified object type.

result set

The output of a SQL query, consisting of one or more rows of data.

Safe Type Mapping

Safe Type Mapping allows the `OracleDataAdapter` to populate a `DataSet` with .NET type representations of Oracle data without any data or precision loss.

savepoint

A point in the workspace to which operations can be rolled back.

stored procedure

A stored procedure is a PL/SQL block that Oracle stores in the database and can be executed from an application.

Transparent Application Failover (TAF)

Transparent Application Failover is a runtime failover for high-availability environments. It enables client applications to automatically reconnect to the database if the connection fails. This reconnect happens automatically from within the Oracle Call Interface (OCI) library.

Unicode

Unicode is a universal encoded character set that enables information from any language to be stored using a single character set.

URL

URL (Universal Resource Locator).

value semantics

Value semantics indicates that assignment copies the value, not the reference or address (such as a pointer). See [reference semantics](#).

XPath

XML Path Language (XPath), based on a W3C recommendation, is a language for addressing parts of an XML document. It is designed to be used by both XSLT and XPointer. It can be used as a searching or query language as well as in hypertext linking.

Index

Symbols

- [.NET custom types, 3-129](#)
- [.NET Framework datatype, 3-87](#)
- [.NET languages, 1-1, 1-2](#)
- [.NET products and documentation, 1-1](#)
- [.NET stored procedures and functions, 5-1](#)
- [.NET Stream class, 3-113](#)
- [.NET type accessors, 3-89](#)
- [.NET Types](#)
 - [inference, 3-72](#)

A

- [abstract data types, 3-129](#)
- [ADO, 1-4](#)
- [ADO.NET, 1-4, 3-143](#)
- [ADO.NET 1.x, 2-1](#)
- [ADO.NET 2.0, 2-5](#)
 - [base or DbCommon classes, 3-1](#)
- [ADO.NET 2.x, 2-1](#)
- [ADTs, 3-129](#)
- [app.config file, 3-8](#)
- [AppDomain, 3-33](#)
- [application config, 2-12](#)
- [array bind](#)
 - [OracleParameter, 3-80](#)
- [array bind operations, 3-79](#)
 - [ArrayBindCount, 6-24](#)
 - [ArrayBindIndex, 6-362](#)
 - [ArrayBindSize, 6-391, 6-393, 6-419](#)
 - [ArrayBindStatus, 6-421](#)
 - [error handling, 3-80](#)
- [array binding, 3-79](#)
- [ArrayBindCount property, 6-24](#)
- [ArrayBindIndex property, 6-362](#)
- [ArrayBindSize property, 3-76, 3-80, 6-419](#)
- [ArrayBindStatus property, 3-76, 3-80, 6-421](#)
- [ASP.NET, 1-3](#)
- [assembly, 1-5](#)
 - [ODP.NET, 1-5](#)

B

- [batch processing, 3-82](#)

- [BatchUpdate](#)
 - [Microsoft Hotfix, 3-82](#)
- [behavior of ExecuteScalar method for REF CURSOR, 3-102](#)
- [BFILE, 3-112](#)
- [binding, 3-69](#)
 - [PL/SQL Associative Array, 3-75](#)
- [BLOB, 3-112](#)
- [bulk copy constraints, 3-145](#)
- [bulk copy feature, 3-145](#)
 - [restrictions, 3-145](#)

C

- [C#, Visual Basic .NET, C++ .NET, 1-1](#)
- [callback support, 3-47](#)
- [case-sensitivity](#)
 - [column name mapping, 3-126](#)
- [change notification](#)
 - [ODP.NET support, 3-156](#)
- [change notification, Continuous Query Notification, 9-1](#)
- [characters with special meaning](#)
 - [in column data, 3-125](#)
 - [in table or view, 3-126](#)
- [characters with special meaning in XML, 3-120](#)
- [client applications, 1-1](#)
- [client globalization settings, 3-168, 3-170](#)
- [client identifier, 3-47](#)
- [CLOB, 3-112](#)
- [close calls, 2-59](#)
- [CLR, 1-2](#)
- [collection types, 3-129](#)
- [CollectionType property, 3-75](#)
- [column data](#)
 - [special characters in, 3-125](#)
- [CommandBehavior.SequentialAccess, 3-93](#)
- [commit transactions](#)
 - [changes to XML data, 3-129](#)
- [CommittableTransaction, 3-65](#)
- [Committed property, 6-391](#)
- [configuration settings](#)
 - [UDTs, 3-145](#)
- [connect descriptor, 3-8](#)
- [connection dependency, 3-117](#)

- connection pool
 - performance counters, [3-29](#)
- connection pooling, [3-27](#)
 - example, [3-27](#)
 - management, [3-29](#)
- ConnectionString attributes, [3-27](#)
 - Connection Lifetime, [3-6](#), [3-27](#), [3-28](#)
 - Connection Timeout, [3-6](#), [3-27](#), [3-28](#)
 - Data Source, [3-6](#)
 - DBA Privilege, [3-6](#)
 - Decr Pool Size, [3-6](#), [3-27](#), [3-28](#)
 - Enlist, [3-6](#)
 - HA Events, [3-6](#), [3-27](#)
 - Incr Pool Size, [3-6](#), [3-27](#), [3-28](#)
 - Load Balancing, [3-6](#), [3-27](#)
 - Max Pool Size, [3-6](#), [3-27](#), [3-28](#)
 - Metadata Pooling, [3-6](#)
 - Min Pool Size, [3-6](#), [3-27](#), [3-28](#)
 - Password, [3-6](#)
 - Persist Security Info, [3-6](#)
 - Pooling, [3-6](#), [3-27](#), [3-28](#)
 - Proxy Password, [3-6](#), [3-45](#)
 - Proxy User Id, [3-6](#), [3-45](#)
 - Statement Cache Purge, [3-6](#)
 - Statement Cache Size, [3-6](#)
 - User Id, [3-6](#)
 - Validate Connection, [3-6](#), [3-27](#), [3-28](#)
- ConnectionString property, [3-27](#), [3-28](#), [6-139](#)
- Constraints property, [3-165](#)
 - configuring, [3-166](#)
- context connection, [5-3](#)
- continuous query notification, [2-58](#), [3-155](#)
 - ODP.NET support, [3-156](#)
- Continuous Query Notification, [3-153](#)
 - best practices, [3-160](#)
 - performance considerations, [3-160](#)
- controlling query reexecution, [3-164](#)
- custom classes, [3-130](#)
- custom type factories, [3-130](#)
- custom type factory, [3-133](#)
- custom type implementations
 - optional, [3-132](#)
- custom type mapping, [3-133](#)
- custom type mappings
 - specifying, [3-133](#)
 - specifying with custom type factories, [3-133](#)
 - specifying with XML, [3-133](#)
 - using, [3-135](#)
- custom types
 - converting to Oracle UDTs, [3-135](#)
 - requirements, [3-130](#)
- custom UDT classes, [3-130](#)

D

- Data Guard, [3-50](#)
- data loss, [3-160](#)
- data manipulation
 - using XML, [3-124](#)
- data source attribute, [3-8](#)
- data source enumerators, [3-11](#)
- database
 - changes to, [3-124](#)
- database notification
 - port to listen, [2-58](#)
- DataSet, [3-114](#)
 - populating, [3-101](#)
 - populating from a REF CURSOR, [3-101](#)
 - populating with generic and custom objects, [3-143](#)
 - updating, [3-101](#)
 - updating to database, [3-165](#)
- DataTable, [3-166](#)
- Datatable properties, [3-165](#)
- DBlinks, [5-3](#)
- DbProviderFactories class, [2-5](#), [2-8](#), [3-1](#)
- DbType
 - inference, [3-72](#)
- debug tracing, [3-172](#)
- default mapping
 - improving, [3-128](#)
- dependent unmanaged DLL mismatch, [2-8](#)
- direct path load, [3-145](#)
- dispose calls, [2-59](#)
- distributed transactions, [3-65](#)
- documentation
 - .NET, [1-1](#)
- Dynamic Enlistment, [3-46](#)
- dynamic help, [1-1](#), [2-5](#), [2-8](#)

E

- Easy Connect naming method, [3-9](#)
- EDM type facets, [4-6](#)
- EDM types, [4-3](#)
 - and Oracle data types, [4-3](#)
- end-to-end tracing, [3-47](#)
- EnlistDistributedTransaction method, [3-46](#)
- Entity Framework, [4-1](#)
- enumeration type
 - OracleDbType, [3-70](#)
- error handling, [3-80](#)
- example
 - connection pooling, [3-27](#)
- examples
 - documentation
 - readme file, [2-6](#), [2-10](#)
- ExecuteNonQuery method, [3-101](#)

ExecuteScalar method, [3-102](#)
 explicit user connections, [5-1](#)
 EZCONNECT, [3-9](#)

F

failover, [3-47](#)
 registering an event handler, [3-47](#)
 FailoverEvent Enumeration
 description, [11-8](#)
 FailoverReturnCode Enumeration
 description, [11-9](#)
 FailoverType Enumeration
 description, [11-10](#)
 Fast Application Notification (FAN), [3-51](#)
 Fast Connection Failover (FCF), [3-53](#)
 FCF, [3-54](#)
 features, [3-1](#)
 FetchSize property
 fine-tuning, [3-98](#)
 setting at design time, [3-99](#)
 setting at run time, [3-99](#)
 using, [3-98](#)
 file locations, [2-6, 2-10](#)

G

garbage collection, [2-59](#)
 GDS, [3-50](#)
 geographic data, [3-129](#)
 Global Assembly Cache (GAC), [2-5, 2-8](#)
 Global Data Services, [3-52](#)
 Global Data Services (GDS), [3-50](#)
 globalization settings, [3-167, 3-168](#)
 client, [3-168](#)
 session, [3-168](#)
 thread-based, [3-169](#)
 globalization support, [3-167](#)
 globalization-sensitive operations, [3-170](#)
 GoldenGate, [3-50](#)
 GUI access to ODP.NET, [1-2](#)

H

HA events, [2-58](#)
 HA Events, [3-6](#)
 handling date and time format
 manipulating data in XML, [3-124](#)
 retrieving queries in XML, [3-120](#)
 high availability, [3-50](#)

I

implicit database connection, [5-1, 5-3, 6-146](#)

implicit REF CURSOR, [3-103](#)
 bind and metadata, [3-104](#)
 bindinfo, [3-104](#)
 configuration, [3-108](#)
 examples, [3-108](#)
 usage, [3-111](#)
 improving default mapping, [3-128](#)
 inference of DbType and OracleDbType from Value, [3-74](#)
 inference of DbType from OracleDbType, [3-72](#)
 inference of OracleDbType from DbType, [3-73](#)
 inference of types, [3-72](#)
 InitialLOBFetchSize property, [3-94](#)
 InitialLONGFetchSize property, [3-93](#)
 input binding
 XMLType column, [3-118](#)
 insert triggers, [3-147](#)
 installation, [2-5, 2-8](#)
 Oracle Data Provider for .NET, [2-5](#)
 Oracle Data Provider for .NET, Manager Provider, [2-8](#)
 XCopy class, [2-5, 2-8](#)
 integrated help, [2-5, 2-8](#)
 interference in OracleParameter class, [3-72](#)
 introduction, overview, [1-4](#)
 INullable Interface
 interface description, [14-497](#)
 interface members, [14-498](#)
 interface properties, [14-498](#)
 invalidation message, [3-155](#)
 ensuring persistency of, [3-156](#)
 IOracleArrayTypeFactory Interface
 interface description, [16-24](#)
 interface members, [16-25](#)
 interface methods, [16-26](#)
 IOracleCustomType Interface
 interface description, [16-19](#)
 interface members, [16-19](#)
 interface methods, [16-20](#)
 IOracleCustomTypeFactory Interface
 interface description, [16-22](#)
 interface members, [16-23](#)
 interface methods, [16-23](#)

L

large binary datatypes, [3-112](#)
 large character datatypes, [3-112](#)
 limitations and restrictions, [5-2](#)
 LINQ to Entities, [4-1](#)
 load balancing, [2-58](#)
 Load Balancing, [3-6](#)
 LOBs
 temporary, [3-115](#)
 updating, [3-114](#)

LOBs updating, [3-114](#)
 local transactions, [3-65](#)
 location data, [3-129](#)
 logical transaction ID (LTXID), [3-57](#)
 LONG and LONG RAW datatypes, [3-113](#)
 LTXID, [3-57](#)

M

machine.config, [2-12](#)
 machine.config file, [2-5](#), [2-8](#)
 metadata, [3-167](#)
 method invocation
 UDT, [3-144](#)
 Microsoft .NET Framework, [2-1](#)
 Microsoft .NET Framework Class Library, [1-4](#)
 Microsoft Common Language Runtime (CLR),
 [1-2](#)
 Microsoft Hotfix
 BatchUpdate, [3-82](#)
 multiple notification requests, [3-156](#)
 multiple tables
 changes to, [3-128](#)

N

namespace
 Oracle.DataAccess.Types, [1-19](#)
 native XML support, [3-115](#)
 NCLOB, [3-112](#)
 nested table types, [3-129](#)
 notification framework, [3-155](#)
 notification information
 retrieving, [3-156](#)
 notification process
 flow, [3-157](#)
 notification registration, [3-156](#)
 requirements of, [3-157](#)
 NULL values
 retrieving from column, [3-124](#)
 number of rows fetched in round-trip
 controlling, [3-98](#)

O

object data type support, [3-129](#)
 object types, [3-129](#)
 object-relational data, [3-124](#)
 saving changes from XML data, [3-128](#)
 obtaining a REF CURSOR, [3-100](#), [3-101](#)
 obtaining an OracleRefCursor, [3-100](#)
 obtaining data from an OracleDataReader, [3-88](#)
 obtaining LOB data
 InitialLOBFetchSize property, [3-94](#)
 obtaining LONG and LONG RAW Data, [3-93](#)

OCI
 statement caching, [3-83](#)
 ODP.NET
 installing, [2-5](#)
 ODP.NET Configuration, [2-12](#)
 ODP.NET LOB classes, [3-112](#)
 ODP.NET Type accessors, [3-91](#)
 ODP.NET Type classes, [3-87](#)
 ODP.NET Type exceptions, [15-1](#)
 ODP.NET Type structures, [3-87](#), [14-1](#)
 ODP.NET Types, [3-87](#)
 overview, [3-87](#)
 ODP.NET within a .NET stored procedure
 limitations and restrictions, [5-2](#)
 transaction support, [5-3](#)
 unsupported SQL commands, [5-6](#)
 ODP.NET XML Support, [3-115](#)
 OnChangedEventArgs Class
 instance properties, [9-33](#)
 members, [9-31](#)
 static fields, [9-32](#)
 static methods, [9-32](#)
 OnChangeEventHandler Delegate
 description, [9-38](#)
 operating system authentication, [3-40](#)
 Oracle Call Interface
 statement caching, [3-83](#)
 Oracle Data Provider for .NET
 installing, [2-5](#)
 system requirements, [2-1](#)
 Oracle Data Provider for .NET assembly, [1-5](#)
 Oracle Data Provider for .NET, Managed Driver
 installing, [2-8](#)
 Oracle data types, [4-3](#)
 and EDM types, [4-3](#)
 mapping and customizing, [4-14](#)
 Oracle Database Extensions for .NET, [1-2](#), [5-1](#)
 Oracle Developer Tools for Visual Studio, [1-2](#)
 Oracle Label Security, [3-47](#)
 Oracle native types, [3-87](#)
 supported by ODP.NET, [3-89](#)
 Oracle Providers for ASP.NET, [1-3](#)
 Oracle RAC, [3-50](#)
 Oracle Real Application Clusters (Oracle RAC),
 [3-50](#)
 Oracle UDT attribute mappings, [3-136](#)
 Oracle Universal Installer (OUI), [2-5](#), [2-8](#)
 Oracle user-defined types, [3-129](#)
 Oracle User-Defined Types (UDTs), [3-129](#)
 Oracle Virtual Private Database (VPD), [3-47](#)
 Oracle XML DB, [3-116](#)
 Oracle.DataAccess.Client namespace, [1-5](#)
 Oracle.DataAccess.dll, [1-5](#)
 Oracle.DataAccess.Types namespace, [1-5](#), [1-19](#)

- OracleAQAgent
 - constructors, [12-3](#)
- OracleAQAgent Class
 - constructors, [12-3](#)
 - description, [12-1](#)
 - members, [12-2](#), [12-36](#)
 - properties, [12-5](#), [12-9](#)
- OracleAQDequeueMode Enumeration
 - description, [12-84](#)
- OracleAQDequeueOptions Class
 - constructor, [12-8](#)
 - description, [12-6](#)
 - members, [12-7](#)
 - properties, [12-9](#)
 - public methods, [12-15](#)
- OracleAQEnqueueOptions Class
 - constructor, [12-18](#)
 - description, [12-16](#)
 - members, [12-17](#)
 - properties, [12-19](#)
 - public methods, [12-20](#)
- OracleAQMessage Class
 - constructors, [12-24](#)
 - description, [12-21](#)
 - members, [12-23](#)
 - properties, [12-25](#)
- OracleAQMessageAvailableEventArgs Class
 - description, [12-35](#)
 - members, [12-36](#)
 - properties, [12-38](#)
- OracleAQMessageAvailableEventHandler
 - Delegate
 - description, [12-46](#)
- OracleAQMessageDeliveryMode Enumeration
 - description, [12-85](#)
- OracleAQMessageState Enumeration
 - description, [12-87](#)
- OracleAQMessageType Enumeration
 - description, [12-87](#)
- OracleAQNavigationMode Enumeration
 - description, [12-88](#)
- OracleAQNotificationGroupingType Enumeration
 - description, [12-90](#)
- OracleAQNotificationType Enumeration
 - description, [12-90](#)
- OracleAQQueue Class
 - constructors, [12-50](#)
 - description, [12-47](#)
 - events, [12-80](#)
 - members, [12-48](#)
 - properties, [12-57](#)
 - public methods, [12-63](#)
 - static methods, [12-50](#)
- OracleAQVisibilityMode Enumeration
 - description, [12-91](#)
- OracleArrayMappingAttribute Class
 - constructors, [16-16](#)
 - description, [16-14](#)
 - members, [16-15](#)
 - methods, [16-18](#)
 - properties, [16-18](#)
 - static methods, [16-17](#)
- OracleBFile Class
 - class description, [13-1](#)
 - constructors, [13-6](#)
 - instance methods, [13-18](#)
 - instance properties, [13-10](#)
 - members, [13-3](#)
 - static fields, [13-8](#)
 - static methods, [13-10](#)
- OracleBinary Structure
 - constructor, [14-5](#)
 - description, [14-1](#)
 - instance methods, [14-24](#)
 - members, [14-3](#)
 - properties, [14-21](#)
 - static fields, [14-6](#)
 - static methods, [14-7](#)
 - static operators, [14-14](#)
 - static type conversion operators, [14-20](#)
- OracleBlob Class
 - class description, [13-40](#)
 - constructors, [13-46](#)
 - instance methods, [13-57](#)
 - instance properties, [13-49](#)
 - members, [13-43](#)
 - static fields, [13-47](#)
 - static methods, [13-49](#)
- OracleBulkCopy Class
 - class description, [17-1](#)
 - constructors, [17-4](#)
 - events, [17-21](#)
 - members, [17-2](#)
 - properties, [17-8](#)
 - public methods, [17-14](#)
- OracleBulkCopyColumnMapping Class
 - class description, [17-22](#)
 - constructors, [17-24](#)
 - members, [17-23](#)
 - properties, [17-27](#), [17-28](#)
- OracleBulkCopyColumnMappingCollection Class
 - class description, [17-31](#)
 - members, [17-33](#)
 - properties, [17-34](#)
 - public methods, [17-35](#)
- OracleBulkCopyOptions Enumeration
 - description, [17-46](#)
- OracleClientFactory, [2-5](#), [2-8](#)
- OracleClientFactory class
 - instantiating, [3-1](#)

- OracleClientFactory Class
 - class description, [6-2](#)
 - class members, [6-3](#)
 - public methods, [6-7](#)
 - public properties, [6-6](#)
- OracleClob Class
 - class description, [13-80](#)
 - constructors, [13-85](#)
 - instance methods, [13-96](#)
 - instance properties, [13-89](#)
 - members, [13-82](#)
 - static fields, [13-87](#)
 - static methods, [13-88](#)
- OracleCollectionType Enumeration, [6-516](#)
- OracleCommand
 - constructors, [6-17](#)
 - InitialLOBFetchSize property, [3-94](#)
 - InitialLONGFetchSize property, [3-93](#)
 - Transaction property, [3-64](#)
- OracleCommand Class
 - ArrayBindCount, [6-24](#)
 - class description, [6-12](#)
 - ExecuteScalar method, [3-102](#)
 - FetchSize property, [3-98](#)
 - members, [6-14](#)
 - properties, [6-20](#)
 - public methods, [6-41](#), [12-15](#)
 - RowSize property, [3-99](#)
 - static methods, [6-19](#)
- OracleCommand object, [3-64](#)
- OracleCommand properties
 - ArrayBindCount, [3-79](#)
- OracleCommand Transaction object, [3-64](#)
- OracleCommandBuilder Class, [3-167](#)
 - class description, [6-57](#)
 - constructors, [6-62](#)
 - events, [6-82](#)
 - members, [6-59](#)
 - properties, [6-67](#)
 - public methods, [6-72](#)
 - static methods, [6-63](#)
 - updating dataset, [3-165](#)
- OracleConfiguration
 - members, [6-85](#)
- OracleConfiguration Class
 - class description, [6-82](#)
 - properties, [6-88](#), [6-93](#), [6-102](#), [6-103](#), [6-108](#), [6-114](#), [6-119](#)
- OracleConnection
 - ClearAllPools property, [3-29](#)
 - ClearPool property, [3-29](#)
 - ClientId property, [3-47](#)
 - events, [6-185](#)
- OracleConnection class
 - GetSchema methods, [3-25](#)
- OracleConnection Class
 - class description, [6-121](#)
 - constructors, [6-127](#)
 - members, [6-123](#)
 - obtaining a reference, [3-117](#)
 - properties, [6-135](#)
 - static methods, [6-132](#)
- OracleConnectionOpenEventArgs
 - members, [6-192](#)
 - properties, [6-192](#)
- OracleConnectionOpenEventArgs Class, [6-191](#)
- OracleConnectionOpenEventHandler Delegate, [6-193](#)
- OracleConnectionStringBuilder class
 - using, [3-8](#)
- OracleConnectionStringBuilder Class
 - class description, [6-194](#)
 - class members, [6-197](#)
 - constructors, [6-200](#)
 - public methods, [6-220](#)
 - public properties, [6-202](#)
- OracleConnectionType Enumeration
 - description, [6-515](#)
- OracleCredential, [3-42](#)
 - constructors, [6-227](#)
 - members, [6-226](#)
- OracleCredential Class, [6-224](#)
 - properties, [6-229](#)
- OracleCustomTypeMappingAttribute Class
 - constructors, [16-4](#)
 - description, [16-1](#)
 - members, [16-3](#)
 - methods, [16-6](#)
 - properties, [16-5](#)
 - static methods, [16-5](#)
- OracleDataAdapter, [3-160](#)
 - constructors, [6-237](#)
 - members, [6-235](#)
 - SafeMapping Property, [3-162](#)
 - SelectCommand property, [3-101](#)
- OracleDataAdapter class
 - FillSchema method, [3-166](#)
 - Requery property, [3-164](#)
 - SelectCommand property, [3-166](#)
- OracleDataAdapter Class, [6-233](#)
 - events, [6-255](#)
 - FillSchema method, [3-167](#)
 - properties, [6-241](#)
 - public methods, [6-250](#)
 - SelectCommand property, [3-167](#)
 - static methods, [6-241](#)
- OracleDataAdapter Safe Type Mapping, [3-160](#)
- OracleDatabase Class
 - class description, [6-259](#)
 - constructor, [6-262](#), [6-263](#)

- OracleDatabase Class (*continued*)
 - members, [6-261](#)
 - properties, [6-264](#)
 - public methods, [6-265](#)
 - Shutdown method, [6-266](#)
 - Startup method, [6-270](#)
- OracleDatabase Constructors, [6-262](#)
- OracleDataReader, [3-88](#), [3-93](#)
 - members, [6-275](#)
 - retrieving UDTs from, [3-138](#)
 - typed accessors, [3-89](#)
- OracleDataReader Class
 - class description, [6-272](#)
 - FetchSize property, [3-98](#)
 - populating, [3-100](#)
 - properties, [6-279](#)
 - public methods, [6-292](#)
 - static methods, [6-279](#)
- OracleDataReader Class SchemaTable, [6-337](#)
- OracleDataSource Enumerator class
 - using, [3-11](#)
- OracleDataSourceCollection
 - members, [6-350](#)
- OracleDataSourceCollection Class
 - class description, [6-348](#)
 - methods, [6-350](#)
 - properties, [6-352](#)
- OracleDataSourceEnumerator Class
 - class description, [6-354](#)
 - class members, [6-355](#)
 - public methods, [6-357](#)
- OracleDate Structure
 - constructors, [14-74](#)
 - description, [14-70](#)
 - members, [14-71](#)
 - methods, [14-102](#)
 - properties, [14-97](#)
 - static fields, [14-79](#)
 - static methods, [14-81](#)
 - static operators, [14-88](#)
 - static type conversions, [14-93](#)
- OracleDBAPrivilege Enumeration
 - description, [6-516](#)
- OracleDBShutdownMode Enumeration
 - description, [6-517](#)
- OracleDBStartupMode Enumeration
 - description, [6-518](#)
- OracleDbType
 - inference, [3-72](#)
- OracleDbType enumeration, [3-72](#)
- OracleDbType Enumeration
 - description, [6-519](#)
- OracleDbType enumeration type, [3-70](#), [6-519](#)
- OracleDecimal Structure
 - constructors, [14-115](#)
- OracleDecimal Structure (*continued*)
 - description, [14-108](#)
 - instance methods, [14-186](#)
 - members, [14-110](#)
 - properties, [14-181](#)
 - static comparison methods, [14-126](#)
 - static comparison operators, [14-162](#)
 - static logarithmic methods, [14-148](#)
 - static manipulation methods, [14-132](#)
 - static operators, .NET Type to
 - OracleDecimal, [14-171](#)
 - static operators, OracleDecimal to .NET, [14-176](#)
 - static trigonometric methods, [14-154](#)
- OracleDependency Class
 - change notification, [3-155](#)
 - class description, [9-1](#)
 - constructors, [9-4](#)
 - Continuous Query Notification, [3-153](#)
 - events, [9-21](#)
 - instance methods, [9-18](#)
 - instance properties, [9-12](#)
 - members, [9-2](#)
 - static fields, [9-8](#)
 - static methods, [9-10](#)
- OracleDRCPPurity Enumeration
 - description, [6-521](#)
- OracleError Class
 - ArrayBindIndex, [6-362](#)
 - class description, [6-358](#)
 - members, [6-360](#)
 - methods, [6-365](#)
 - properties, [6-361](#)
 - static methods, [6-361](#)
- OracleErrorCollection
 - members, [6-367](#)
 - properties, [6-369](#)
 - public methods, [6-369](#)
 - static methods, [6-368](#)
- OracleErrorCollection Class, [6-366](#)
- OracleException
 - members, [6-372](#)
 - methods, [6-379](#)
 - properties, [6-374](#)
 - static methods, [6-373](#)
- OracleException Class, [6-370](#)
- OracleFailoverEventArgs
 - members, [11-3](#)
 - properties, [11-5](#)
 - public methods, [11-6](#)
- OracleFailoverEventHandler Delegate
 - description, [11-6](#)
- OracleGlobalization Class
 - class description, [10-1](#)
 - members, [10-2](#)

- OracleGlobalization Class (*continued*)
 - properties, [10-10](#)
 - public methods, [10-22](#)
- OracleHAEventArgs Class
 - description, [8-1](#)
 - members, [8-2](#)
 - properties, [8-3](#)
- OracleHAEventHandler Delegate
 - description, [8-8](#)
- OracleHAEventSource Enumeration
 - description, [8-9](#)
- OracleHAEventStatus Enumeration
 - description, [8-10](#)
- OracleIdentityType Enumeration
 - description, [6-522](#)
- OracleInfoMessageEventArgs
 - members, [6-383](#)
 - properties, [6-385](#)
 - public methods, [6-386](#)
 - static methods, [6-384](#)
- OracleInfoMessageEventHandler Delegate,
 - [6-387](#)
- OracleIntervalDS Structure
 - constructors, [14-198](#)
 - description, [14-193](#)
 - members, [14-195](#)
 - methods, [14-231](#)
 - properties, [14-225](#)
 - static methods, [14-206](#)
 - static operators, [14-214](#)
 - type conversions, [14-222](#)
- OracleIntervalYM Structure
 - constructors, [14-240](#)
 - description, [14-235](#)
 - members, [14-236](#)
 - methods, [14-246](#), [14-268](#)
 - properties, [14-265](#)
 - static fields, [14-244](#)
 - static operators, [14-253](#)
 - type conversions, [14-262](#)
- OracleNotificationEventArgs Class
 - change notification, [3-155](#)
 - class description, [9-30](#)
 - instance methods, [9-38](#)
- OracleNotificationInfo Enumeration
 - description, [9-42](#)
- OracleNotificationRequest Class
 - change notification, [3-155](#)
 - class description, [9-22](#)
 - Continuous Query Notification, [3-153](#)
 - instance methods, [9-29](#)
 - instance properties, [9-24](#)
 - members, [9-23](#)
 - static methods, [9-24](#)
- OracleNotificationSource Enumeration
 - description, [9-41](#)
- OracleNotificationType Enumeration
 - description, [9-40](#)
- OracleNullValueException Class
 - class description, [15-8](#)
 - constructors, [15-11](#)
 - members, [15-9](#)
 - methods, [15-12](#), [15-13](#)
 - properties, [15-13](#)
- OracleObjectMappingAttribute Class
 - constructors, [16-10](#)
 - description, [16-7](#)
 - members, [16-8](#)
 - methods, [16-13](#)
 - properties, [16-12](#)
 - static methods, [16-11](#)
- OracleOnsServerCollection
 - members, [6-398](#)
- OracleOnsServerCollection Class
 - class description, [6-396](#)
 - methods, [6-398](#)
 - properties, [6-400](#)
- OracleParameter
 - array bind properties, [3-80](#)
 - ArrayBindSize property, [3-80](#), [6-391](#), [6-393](#), [6-419](#)
 - ArrayBindStatus property, [3-80](#), [6-421](#)
 - constructors, [6-406](#)
 - inferences of types, [3-72](#)
 - members, [6-404](#)
 - properties, [6-418](#)
 - public methods, [6-436](#)
 - static methods, [6-418](#)
- OracleParameter array bind feature, [3-79](#)
- OracleParameter Class, [6-402](#)
- OracleParameter object, [3-69](#)
 - OracleDbType enumerated values, [3-70](#)
- OracleParameter property
 - ArrayBindSize, [3-76](#)
 - ArrayBindStatus, [3-76](#)
 - CollectionType, [3-75](#)
 - Size, [3-76](#)
 - Value, [3-76](#)
- OracleParameterCollection
 - members, [6-441](#)
 - public methods, [6-449](#)
 - static methods, [6-443](#)
- OracleParameterCollection Class, [6-440](#)
- OracleParameterStatus Enumeration
 - description, [6-522](#)
- OracleParameterStatus enumeration type, [3-82](#), [6-522](#)
- Oraclepermission Class
 - description, [6-470](#)

- OraclePermission Class
 - constructor, [6-473](#)
 - members, [6-471](#)
 - public methods, [6-475](#)
 - public properties, [6-474](#)
 - static methods, [6-474](#)
- OraclePermissionAttribute Class
 - constructor, [6-481](#)
 - description, [6-478](#)
 - members, [6-479](#)
 - public methods, [6-482](#)
 - public properties, [6-482](#)
 - static methods, [6-481](#)
- OracleRef Class
 - class description, [16-43](#)
 - class members, [16-44](#)
 - constructors, [16-46](#)
 - instance methods, [16-54](#)
 - instance properties, [16-49](#)
 - static fields, [16-48](#)
 - static methods, [16-49](#)
- OracleRefCursor, [3-100](#)
- OracleRefCursor Class
 - class description, [13-125](#)
 - instance methods, [13-134](#)
 - members, [13-127](#)
 - populating from a REF CURSOR, [3-101](#)
 - properties, [13-130](#)
 - static methods, [13-129](#)
- OracleRowsCopiedEventArgs Class
 - class description, [17-48](#)
 - constructors, [17-49](#)
 - members, [17-49](#)
 - properties, [17-50](#)
- OracleRowsCopiedEventHandler Delegate
 - description, [17-47](#)
- OracleRowUpdatedEventArgs
 - constructor, [6-486](#)
 - members, [6-484](#)
 - properties, [6-487](#)
 - public methods, [6-488](#)
 - static methods, [6-487](#)
- OracleRowUpdatedEventArgs Class, [6-483](#)
- OracleRowUpdatedEventHandler Delegate,
 - [6-489](#)
- OracleRowUpdatingEventArgs
 - constructor, [6-492](#)
 - members, [6-491](#)
 - properties, [6-493](#)
 - public methods, [6-494](#)
 - static methods, [6-493](#)
- OracleRowUpdatingEventArgs Class, [6-489](#)
- OracleRowUpdatingEventHandler Delegate,
 - [6-495](#)
- OracleShardingKey
 - constructors, [6-498](#)
 - members, [6-497](#)
- OracleShardingKey Class, [6-496](#)
 - instance methods, [6-499](#)
- OracleString Structure
 - constructors, [14-276](#)
 - description, [14-272](#)
 - members, [14-273](#)
 - methods, [14-299](#)
 - properties, [14-296](#)
 - static fields, [14-281](#)
 - static methods, [14-282](#)
 - static operators, [14-288](#)
 - type conversions, [14-294](#)
- OracleTimeStamp Structure
 - constructors, [14-310](#)
 - description, [14-305](#)
 - members, [14-306](#)
 - methods, [14-351](#)
 - properties, [14-345](#)
 - static methods, [14-319](#)
 - static operators, [14-328](#)
 - static type conversions, [14-338](#)
- OracleTimeStampLTZ Structure
 - constructors, [14-370](#)
 - description, [14-364](#)
 - members, [14-366](#)
 - methods, [14-413](#)
 - properties, [14-406](#)
 - static fields, [14-378](#)
 - static methods, [14-379](#)
 - static operators, [14-389](#)
 - static type conversions, [14-400](#)
- OracleTimeStampTZ Structure
 - constructors, [14-433](#)
 - description, [14-427](#)
 - members, [14-429](#)
 - methods, [14-482](#)
 - properties, [14-475](#)
 - static fields, [14-447](#)
 - static methods, [14-449](#)
 - static operators, [14-457](#)
 - static type conversions, [14-468](#)
- OracleTransaction
 - members, [6-503](#)
 - properties, [6-505](#)
 - public methods, [6-507](#)
 - static methods, [6-505](#)
- OracleTransaction Class
 - class description, [6-501](#)
- OracleTruncateException Class
 - class description, [15-14](#)
 - constructors, [15-16](#)
 - members, [15-15](#)

OracleTruncateException Class (*continued*)
 methods, [15-19](#)
 properties, [15-18](#)
 static methods, [15-18](#)

OracleTypeException Class
 class description, [15-1](#)
 constructors, [15-3](#)
 members, [15-2](#)
 properties, [15-5](#)
 static methods, [15-5](#)

OracleUdt Class
 description, [16-28](#)
 members, [16-28](#)
 static methods, [16-29](#)

OracleUdtFetchOption Enumeration
 description, [16-66](#)

OracleUdtStatus Enumeration
 description, [16-67](#)

OracleXmlCommandType Enumeration, [7-1](#)

OracleXmlQueryProperties Class
 class description, [7-2](#)
 constructors, [7-6](#)
 members, [7-5](#)
 properties, [7-7](#)
 public methods, [7-11](#)

OracleXmlSaveProperties Class, [7-11](#)
 constructors, [7-16](#)
 members, [7-14](#)
 properties, [7-16](#)
 public methods, [7-20](#)

OracleXmlStream Class
 class description, [7-21](#)
 constructors, [7-24](#)
 instance methods, [7-30](#)
 instance properties, [7-25](#)
 members, [7-22](#)
 static methods, [7-25](#)

OracleXmlType Class, [3-117](#)
 class description, [7-37](#)
 constructors, [7-40](#)
 instance methods, [7-51](#)
 instance properties, [7-45](#)
 members, [7-38](#)
 static methods, [7-44](#)

outages, [3-54](#)

P

parameter binding, [3-69](#)
 parameter binding with OracleParameter, [3-140](#)
 password expiration, [3-44](#)
 passwords in code examples, [lxxxiii](#)
 performance, [3-50](#), [3-83](#)
 array binding, [3-79](#)
 connection pooling, [3-27](#)

performance (*continued*)
 fine-tuning FetchSize, [3-98](#)
 number of rows fetched, [3-98](#)
 Obtaining LOB Data, [3-94](#)

performance counters
 connection pool, [3-29](#)
 publishing, [3-29](#), [3-33](#)

PL/SQL Associative Array binding, [3-75](#)
 PL/SQL Index-By Tables, [3-75](#)
 PL/SQL language, [3-100](#)
 PL/SQL REF CURSOR, [3-100](#)
 PL/SQL REF CURSOR and OracleRefCursor, [3-100](#)

planned outage, [3-54](#)
 PLSQLAssociativeArray, [6-516](#)

pool size attributes
 Oracle RAC, [3-56](#)

populating an OracleDataReader from a REF CURSOR, [3-100](#)
 populating an OracleRefCursor from a REF CURSOR, [3-101](#)
 populating the DataSet from a REF CURSOR, [3-101](#)
 populating the DataSet with generic and custom objects, [3-143](#)

port
 listen for database notifications, [2-58](#)

port number
 defining listener, [3-156](#)

porting
 client application to .NET stored procedure, [5-6](#)

preventing data loss, [3-160](#), [3-162](#)
 preventing logical corruption, [3-57](#)
 PrimaryKey property, [3-165](#)
 configuring, [3-166](#)

privileged connections, [3-42](#)
 promotable transactions, [3-65](#)

properties
 ClientId property, [3-47](#)
 provider factory classes, [3-1](#)
 proxy authentication, [3-45](#)

Q

query result set
 retrieving as XML, [3-120](#)

R

REF CURSOR, [3-103](#)
 behavior of ExecuteScalar method, [3-102](#)
 implicit, [3-103](#)
 obtaining, [3-100](#), [3-101](#)
 passing to stored procedure, [3-102](#)

REF CURSOR (*continued*)
 populating DataSet from, [3-101](#)
 populating from OracleDataReader, [3-100](#)
 registry entries, [2-12](#)
 release Oracle8i (8.1.7), [3-124](#)
 release Oracle9i(9.0.x), [3-124](#)
 Requery property, [3-164](#)
 round-trip, [3-79](#)
 RowSize property, [3-99](#)
 runtime connection load balancing, [3-52](#)

S

Safe Type Mapping, [3-160](#)
 SafeMapping Property, [3-162](#)
 samples, [2-6](#), [2-10](#)
 UDT, [16-1](#)
 Samples, [1-28](#)
 saving change using an XML document, [3-127](#)
 saving changes
 using XML data, [3-125](#)
 schema metadata
 customizing metadata, [3-25](#)
 SchemaTable, [6-337](#)
 search order
 unmanaged DLLs, [2-7](#)
 SecureFiles, [3-112](#)
 SelectCommand property, [3-101](#)
 session globalization parameters, [3-171](#)
 session globalization settings, [3-168](#)
 Shutdown method, [6-266](#)
 simple application, [1-26](#)
 Size property, [3-76](#)
 SQL commands
 unsupported, [5-6](#)
 Startup method, [6-270](#)
 Statement Caching
 connection string attributes, [3-83](#)
 methods and properties, [3-84](#)
 Statement Cache Purge, [3-83](#)
 Statement Cache Size, [3-83](#)
 StatementCacheWithUdts, [3-145](#)
 stored procedures and functions, [3-102](#), [5-1](#)
 Stream class, [3-113](#)
 support comparison
 client application versus .NET stored
 procedure, [5-6](#)
 SYSDBA privileges, [3-42](#)
 SYSOPER privileges, [3-42](#)
 system requirements
 Oracle Data Provider for .NET, [2-1](#)
 System.Transactions support, [3-65](#)

T

table or view
 special characters in, [3-126](#)
 TAF, [3-47](#)
 TAF callback support, [3-47](#)
 Temporary LOBs, [3-115](#)
 thread globalization settings, [3-170](#)
 thread-based globalization settings, [3-169](#)
 Thread.Abort method, [2-59](#)
 tips for ODP.NET, [2-59](#)
 TNS alias, [3-8](#)
 tracing attributes, [3-47](#)
 Transaction Guard, [3-57](#)
 Transaction object, [3-64](#)
 Transaction property, [3-64](#)
 transaction support, [5-3](#)
 transactions
 commit, [3-129](#)
 TransactionScope, [3-65](#)
 Transparent Application Failover (TAF), [3-47](#)
 triggers, [3-147](#)
 insert triggers, [3-147](#)
 troubleshooting, [3-172](#)
 typed OracleDataReader accessors, [3-89](#)

U

UDT
 method invocation, [3-144](#)
 UDT metadata retrieval from OracleDataReader,
 [3-139](#)
 UdtCacheSize, [3-145](#)
 UDTs, [3-129](#)
 collection types, [3-129](#)
 configuration settings, [3-145](#)
 object types, [3-129](#)
 parameter binding with OracleParameter,
 [3-140](#)
 retrieving from OracleDataReader, [3-138](#)
 samples, [16-1](#)
 UDTs (Oracle User-Defined Types), [3-129](#)
 UdtTypeName property, [3-140](#)
 unique columns, [3-93](#), [3-94](#)
 unique constraint, [3-93](#), [3-94](#)
 unique index, [3-93](#), [3-94](#)
 UniqueConstraint, [3-166](#)
 uniqueness
 in updating DataSet to database, [3-165](#)
 uniqueness in DataRows, [3-166](#)
 unmanaged DLLs
 mismatch, [2-8](#)
 search order, [2-7](#)
 unmanged DLLs
 config support, [2-7](#)

unsupported SQL commands, [5-6](#)
updating
 LOBs, [3-114](#)
updating a DataSet obtained from a REF
 CURSOR, [3-101](#)
updating LOBs using a DataSet, [3-114](#)
updating LOBs using ODP.NET LOB objects,
 [3-114](#)
updating LOBs using OracleCommand and
 OracleParameter, [3-114](#)
updating without PrimaryKey and Constraints,
 [3-167](#)
user-defined types, [3-129](#)
UserCallCompleted public read-only property,
 [6-393](#)
using FetchSize property, [3-98](#)

V

Value property, [3-76](#)
VARRAY types, [3-129](#)
Virtual Private Database(VPD), [3-47](#)
Visual Studio
 documentation, [2-5](#), [2-8](#)

W

web.config, [2-12](#)
Windows registry, [2-26](#)

X

XML
 characters with special meaning, [3-120](#)
 data manipulation using, [3-124](#)
XML data
 saving changes using, [3-125](#)
 updating in OracleXmlType, [3-119](#)
XML Database, [3-115](#)
XML DB, [3-115](#), [3-117](#)
XML element name
 case-sensitivity in, [3-126](#)
XML Element Name to Column Name Mapping,
 [3-126](#)
XML related classes, [7-1](#)
XML related enumerations, [7-1](#)
XML Support, [3-115](#)
XML to specify custom type mappings, [3-134](#)
XMLQuery, [3-116](#)
XMLTable, [3-116](#)
XMLType column
 as a .NET String, [3-118](#)
 fetching into the DataSet, [3-118](#)
 updating with OracleCommand, [3-118](#)
XMLType columns
 setting to NULL, [3-119](#)
XQuery
 support, [3-117](#)
XQUERY, [3-116](#)
XQuery language, [3-116](#)