



PRODUCT-INFORMATION

MINOX DC 2133

DIGITAL COMPANION WITH 3 X OPTICAL ZOOM

The digital camera MINOX DC 2133 makes every picture an unforgettable memory. As with the previous MINOX digital cameras, this model is versatile and extremely user friendly. Even without previous knowledge the amateur photographer can join the world of digital photography easily and fast.

The MINOX DC 2133 has a CCD-image sensor, with 2.1 mega pixels, as well as the high quality MINOCTAR multi-coated lens.

This auto-focus camera has a 3x optical zoom lens and offers the photographer a wide scope of creativity. The results are high quality snaps with a natural color and highly dynamic reproduction. Even in difficult light condition the automatic light balance provides

the ideal speed to ensure the user always gets excellent pictures. A simple menu plus clear and precise symbols enable the user to change quickly between shooting the picture, reproduction and image storage. The 1.6" monitor provides an instant judgement of the picture both during and after the shot. The camera has an 8 MB internal memory, and up to 128 MB via optional memory cards, making for high flexibility.

The images from the MINOX DC 2133 can be easily downloaded to a computer via the USB cord, and processed with the software supplied. Compact dimensions make this lightweight (only 170 g) the ideal companion for every occasion.

The modern housing, coated with a high quality and handy soft-touch laqueur, emphasizes this camera excellent design.

The MINOX DC 2133 is supplied complete with a CD-ROM, 2 batteries, an ever-ready case, wrist strap, USB-cable and a user manual.

TECHNICAL DATA

Memory	internal: 8 MB; external: SD-card up to 128 MB
Image sensor	2.1 mega pixels CCD; 24 BIT (RGB) color
Image resolution	Fine: 1600 x 1200 / Normal: 800 x 600
Lens	Auto Focus MINOCTAR Lens
Aperture	f/2.8, f/4.8
Focus range	Normal: 0.4 – infinity / Macro: 0.1 for wide
Focal length	5.2mm ~ 15.6 mm (equivalent to 33 ~ 98 mm for film camera)
Shutter speed	1/10 -1/1000 s
Zoom	3x optical and 2 x digital zoom
White balance	Auto, daylight, incandescence, fluorescence
Exposure	Auto; manual: 0.3 EV step, -1.8 ~ +1.8 EV
Monitor	1.6" Color-TFT-LCD
Flash	Auto, Fill-In and OFF, Red-eye reduction, night mode
Self timer	10 sec. delay
File Format	JPEG (EXIF 2.2), DPOF, DCF 1.1, Motion JPEG
Language support	English, german, french, spanish, italian, chinese, japanese
Driver	WINDOWS'98/2000/ME/XP; Mac OS 8.6 or later
Software	MGI Photo Suite IV, Photo vista
Connectors	AC power port, USB-port; Video-output (NTSC/PAL switchable)
Power	2 x (AA), Alkaline (1.5 V); CRV3 Lithium; AC-DC adaptor (optional)
Dimensions	105 x 63 x 42 mm (L x H x W)
Weight	approx. 170 g
Scope of delivery	2 AA-batteries; case; wrist cord; USB-cable; CD-ROM; manual
Order number	60612

MINOX GmbH

Walter-Zapp-Str. 4

D-35578 Wetzlar, Germany

Tel.: +49 (0) 6441 / 917-0

Fax: +49 (0) 6441 / 917-612

E-mail: info@minox.com

www.minox.com