



PRODUCT-INFORMATION

MINOX DC 4011 A MINOX WITH PIXEL POWER

The MINOX DC 4011 with 4.0 mega pixels - a compact digital reportage camera for the ambitious amateur photographer - features outstanding optical quality and great flexibility. Classic elements in design and operating panel make the MINOX DC 4011 a composition of proven success and new technology.

The digital MINOX highlight consists of a CCD image sensor with 4.0 mega pixels. The high quality MINOCTAR lens with multi-coating and 3x optical zoom lens has an auto-focus and offers the photographer a wide scope of creativity. Individually adjusted to the 4 mega pixel sensor the MINOCTAR lens offers together with the electronics and the software high quality snaps with a natural colour reproduction and

high dynamic. Even in difficult light the automatic alignment provides the ideal speed to ensure that the user always gets natural colours and the correct setting for every motive.

The 1.6" monitor provides an instant judgement of the picture both during and after the shot. A high flexibility is granted with an up to 128 MB SD card. A quick sequence and minimal shutter release delay allow for spontaneous photographing in any situation.

For the easy transmission between camera and computer the MINOX DC 4011 has an USB interface. Using the software, which comes with the camera, the pictures can be directly processed on the PC and passed on.

The great accuracy in details and sharpness provide brilliant enlargements even in big sizes. Compact dimensions (106 x 40 x 63 mm) and easy handling make the MINOX DC 4011 the ideal companion for every occasion. The modern design with a special soft touch lacquer is a perfect match for today's modern high-performance lifestyle products.

TECHNICAL DATA

Memory	no internal memory; external SD card up to 128 MB
Image sensor	4.0 mega pixels CCD; 24 BIT (RGB) color
Image resolution	2,272 x 1,704 pixels / 1,600 x 1,200 pixels / 1,280 x 960 Pixel / 640 x 480 pixels
Lens	MINOCTAR auto focus lens
Aperture	f/2.9, f/4.8
Focus range	0.7 m to infinity
Focal length	f/7.25 ~ 20.3 mm; (equivalent to 34 ~ 97 mm for film camera)
Shutter speed	2 s - 1/1000 s
Zoom	3 x optical zoom and 2 x digital zoom
White balance	Auto, daylight, incandescence, fluorescence
Exposure	Auto; manual: 0.25 EV step, - 1.5 ~ +1.5 EV
Monitor	1.6" Color-TFT-LCD
Flash	Auto, Fill-In and OFF, red-eye reduction
Self timer	10 s delay
File Format	JPEG (EXIF 2.2), DPOF, M-JPEG
Language support	english, german, french, spanish, italian, japanese
Driver	WINDOWS'98/98SE/2000/ME/XP; Mac OS 8.6 or later
Software	MGI Photo Suite III SE and Photo Vista
Connectors	AC power port, USB-port; Video output (NTSC/PAL selectable)
Power	2 x AA (NiMh, Lithium, CR-V 3)
Dimensions	106 x 40 x 63 mm
Weight	approx. 212 g
Scope of delivery	8 MB SD card; 2 AA-batteries; ever-ready-case; wrist cord; USB-cable; video-cable; CD-ROM; manual
Order number	60613

MINOX GmbH
Walter-Zapp-Str. 4
D-35578 Wetzlar, Germany
Tel.: +49 (0) 6441 / 917-0
Fax: +49 (0) 6441 / 917-612
E-mail: info@minox.com
www.minox.com